

Normal data modes with Z-chan same as H1.x															8-slice configuration										
A8 (D8)	A7 (D7)	A6 (D6)	A5 (D5)	A4 (D4)	A3 (D3)	A2 (D2)	A1 (D1)	B1 (D1)	B2 (D2)	B3 (D3)	B4 (D4)	B5 (D5)	B6 (D6)	B7 (D7)	B8 (D8)	Slice mode	FET mode	Detector Mode name	Protocol Mode name	FET 1 LED	FET 2 LED	FET 3 LED	FET 4 LED	FET 5 LED	FET 6 LED
2	1					4	3	3	4					1	2	Z-chan	17	8Cal6	Cal6	OFF	ON	ON	ON	OFF	ON
2	2	2	2	1	1	1	1	1	1	1	1	2	2	2	2	4x5.00	8	4x5.00	4x5.00	ON	ON	ON	OFF	ON	ON
3	2	1					4	4					1	2	3	Z-chan	16	8Cal5	Cal5	ON	ON	ON	ON	OFF	ON
		2	2	2	1	1	1	1	1	1	2	2	2			4x3.75	7	4x3.75	4x3.75	OFF	OFF	OFF	ON	ON	ON
	4	3	2	1							1	2	3	4		Z-chan	14	8Cal3	Cal3	ON	OFF	OFF	OFF	ON	ON
				2	2	1	1	1	1	2	2					4x2.50	6	4x2.50	4x2.50	ON	OFF	OFF	ON	ON	ON
				2	2	1	1	1	1	2	2					Z-chan	6	4x2.50	4x2.50	ON	OFF	OFF	ON	ON	ON
						2	1	1	2							4x1.25	5	4x1.25	4x1.25	OFF	ON	OFF	ON	ON	ON
	4	3	2	1							1	2	3	4		Z-chan	14	8Cal3	Cal3	ON	OFF	OFF	OFF	ON	ON
				4	3	2	1	1	2	3	4					8x1.25	0	8x1.25	8x1.25	ON	ON	ON	ON	ON	ON
2	1					4	3	3	4					1	2	Z-chan	17	8Cal6	Cal6	OFF	ON	ON	ON	OFF	ON
4	4	3	3	2	2	1	1	1	1	2	2	3	3	4	4	8x2.50	1	8x2.50	8x2.50	OFF	ON	ON	ON	ON	ON
						2	1	1	2							Z-chan	5	4x1.25	4x1.25	OFF	ON	OFF	ON	ON	ON
						2	1	1	2							1x1.25	5	4x1.25	4x1.25	OFF	ON	OFF	ON	ON	ON
						2	1	1	2							Z-chan	5	4x1.25	4x1.25	OFF	ON	OFF	ON	ON	ON
						2	1	1	2							Thin twin	5	4x1.25	4x1.25	OFF	ON	OFF	ON	ON	ON