

Normal data modes with Z-chan same as H1.x															4-slice configuration											
A8 (D8)	A7 (D7)	A6 (D6)	A5 (D5)	A4 (D4)	A3 (D3)	A2 (D2)	A1 (D1)		B1 (D1)	B2 (D2)	B3 (D3)	B4 (D4)	B5 (D5)	B6 (D6)	B7 (D7)	B8 (D8)	Slice mode	FET mode	Detector Mode name	Protocol Mode name	FET 1 LED	FET 2 LED	FET 3 LED	FET 4 LED	FET 5 LED	FET 6 LED
2	1														1	2	Z-chan	45	4Cal6	Cal6	OFF	ON	OFF	OFF	ON	OFF
2	2	2	2	1	1	1	1		1	1	1	1	2	2	2	2	4x5.00	36	4x5.00	4x5.00	ON	ON	OFF	ON	ON	OFF
	2	1												1	2		Z-chan	44	4Cal5	Cal5	ON	ON	OFF	OFF	ON	OFF
		2	2	2	1	1	1		1	1	1	2	2	2			4x3.75	35	4x3.75	4x3.75	OFF	OFF	ON	ON	ON	OFF
			2	1								1	2				Z-chan	42	4Cal3	Cal3	ON	OFF	ON	OFF	ON	OFF
				2	2	1	1		1	1	2	2					4x2.50	34	4x2.50	4x2.50	ON	OFF	ON	ON	ON	OFF
				2	2	1	1		1	1	2	2					Z-chan	34	4x2.50	4x2.50	ON	OFF	ON	ON	ON	OFF
						2	1		1	2							4x1.25	33	4x1.25	4x1.25	OFF	ON	ON	ON	ON	OFF
						2	1		1	2							Z-chan	33	4x1.25	4x1.25	OFF	ON	ON	ON	ON	OFF
						2	1		1	2							1x1.25	33	4x1.25	4x1.25	OFF	ON	ON	ON	ON	OFF
						2	1		1	2							Z-chan	33	4x1.25	4x1.25	OFF	ON	ON	ON	ON	OFF
						2	1		1	2							Thin twin	33	4x1.25	4x1.25	OFF	ON	ON	ON	ON	OFF