


NO TES:

- © REPRESENTS A CRITICAL DIMENSION.
- 2. MIN CONTACT RETENTION 2 LB
- 2. MAX ALLO WA BLE BO W: .006 [.015] IN/IN .001 .03
 4. "END WALLS" A FTER C UTTING SHO ULD BE .015± .005[.38 .13]
 5. MAX C UT FLA SH: .015 [.38] WITH NO FLA SH A LLO WED IN HO LES.
- 6. MAX TERMINAL BURR: .003 [.08] 7. WHEN FILLING THE ASSEMBLY, ALL CONTACTS MUST BE
- FACING THE SAME DIRECTION. 8. TO BE MEASURED AT THE BEND



PLATING SPECIFICATION -T: MATTE TIN, CONTACT AND TAIL -G: 10μ" GOLD IN CONTACTAREA, 3µ" G O LD O N TA IL

MÀTTE TIN ON TAIL

MATTE TIN ON TAIL

MATTE TIN ON TAIL

-S: 3Öμ" SELECTIVE G O LD IN C O NTA C T A REA ,

-F: 3μ" SELECTIVE GOLD IN CONTACTAREA,

-L: 10u" SELECTIVE GOLD IN CONTACT AREA.


No OF POSITIONS--01 THRU -50


CES-1XX-XX-X-S-XX

CONTACT LEAD STYLE


-01: USE C -45-01-X -02: USE C -45-02-X O PTIO NS -RA: RIG HT ANG LE (STYLE -02 O NLY)

ROW SPECIFIC A TION -S: SING LE ROW (USE C ES-XX-S)






SEC TIO N "B"-"B"



SEC TIO N "A "-"A "



NOTE: PINS TO BE

FACING THE SA MF DIRECTION

NOTE: MIXED PIN O RIENTATIO N

A C C EPTA BLE

PACKAGING VIEW LEAD STYLE -02-RA

PACKAGING VIEW

PACKAGING TABLE (5 POS MIN)					
LEAD.STYLE		TUBE		PLUG	
TP-09		-01 & -02	PT-1-24-01-53		
TP-09		-02-RA	PT-	1-24-03-78	

TABLE 1				
STYLE	"A"			
-01	.128 [3.25]			
-02	.223 [5.66]			

UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES. TO LERANCES ARE:

.010[0.25] REF

2° MAX SWAY

(EITHER DIRECTION)

DEC IMALS ANGLES .XX: ±.01 [.3] .XXX: ±.005 [.13] .XXXX: ±.0020 [.051]

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISC LO SED TO OTHERS OR USED FOR ANY PURPO SE O THER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN

SHEET SC A LE: 3:1

PRO PRIETA RY NO TE

-RA

DO NOT SCALE DRAWING

INSULATOR: PBT, UL 94 VO COLOR: BLACK

TERMINAL: PHOS BRONZE

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHO NE: 812-944-6733 FA X: 812-948-5047 e-Mail info@SAMTEC.com

DESC RIPTION

CLOSED ENTRY SOCKET STRIP

C ES-1XX-XX-X-S-XX

KO LB 12-6-89 SHEET 1 OF 1

:\DWG\MISC\MKTG\CES-1XX-XX-X-S-XX-MKT.SLDDRW