



Lanes™ is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification

Product name	Lanes	
Description	100% polyester lightweight semi-rigid panel	
		Metric
Lanes dimensions	Lanes are 300 mm wide sections x 2400 mm length. Custom lengths available.	
Tolerance	(+5 mm) (+10 mm)	
Thickness	12 mm	
Tolerance	(+/- 6%)	

Physical description/  
properties

Boiling point:	N/A
Melting point:	250°C
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A

Acoustic performance

Lanes is specifically designed to reduce and control reverberated noise and echo in building interiors.  Minimum Noise Reduction Coefficient 0.80	Frequency (Hz)	125	250	500	1000	2000	4000	NRC
	Lanes Plane	0.10	0.40	0.85	1.00	0.95	0.95	0.80
	Lanes Peak	0.15	0.45	0.85	0.95	0.90	0.95	0.80
	Lanes Sawtooth	0.15	0.45	0.90	1.00	0.95	0.95	0.85



## Service

For further information about Lanes or any other Autex Acoustics® product, please contact your account manager or visit our website.

## Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

## Product specifications

### Composition

100% polyester fibre from polyethylene terephthalate (PET). Lanes contains a minimum of 80% previously recycled polyester fibre.

### Suitable applications

Feature acoustic wall, not recommended for high impact areas.

### Fire ratings

Cube has been evaluated using the following test methods.

### ISO 9705: 1993

Classification: Group 1-S

Smoke production rate:

<5.0m<sup>2</sup>/s

As required by NZBC C/VM2

### AS ISO 9705 - 2003

Classification: Group 1

(SMOGRArc): <100m<sup>2</sup>/s<sup>2</sup>

Assessed using methodology AS ISO 9705 - 2003 in accordance with AS 5637:2015, as required by NCC Specification 7: Fire Hazard properties: S7C4 FI 4974 FAR 4055

### ASTM E-84-15a

Class A, FS:0 - SD:45

(Cube 1/2")

RJ4479-2

### BS EN 13501-1:2018

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011.

Fire compliance information is available on request. Please contact your Autex Acoustics account manager.

### Thermal performance

Cube 12 mm R0.41 (@15°C)

### VOC emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product. VOC concentration: 0.009 mg/m<sup>3</sup> (7 days)

### Water vapour sorption

ASTM C1104 / C1104M-13a

Test conditions: 49°C, 95%RH

Water vapour absorbed and

adsorped after 4 days:

0.4% by weight

### Microbial resistance

ASTM G21-15

Growth rating: 0 (No growth)

Lanes does not promote the growth of moulds and mildew.

### Colour fastness to light

Lanes is suitable for indoor

use only. Light fastness

is dependent on use and

exposure. Lanes has been

evaluated to the following

standard: ISO 105-B02:2014

Rating: 6 (Highest = 7)

### Colour fastness to rubbing

ISO 105-X12:2016

Dry rating: 4-5 (Highest = 5)

Wet rating: 4-5 (Highest = 5)

### Pattern repeat

Non-woven. No pattern repeat

but product has directional

grain. Product may vary from

samples and batch to batch

due to fibre blending and

lay-up, which is an inherent

feature of this product.

### Fabric care

Blot spills from fabric quickly.

Wipe with a damp cloth.

Avoid rubbing and excessive

amounts of water as this

will affect the finish.

Use carpet or upholstery

shampoo as directed.

Blot with a clean dry cloth after

each application of solution.

Custom printed Lanes requires

the services of a specialist

cleaning company. Refer to

the Autex Acoustics Care and

Maintenance Guide for more

information.

● **New Zealand**  
702-718 Rosebank Road,  
Private Bag 19988  
Avondale 1746, Auckland  
T 0800 428 839  
T +64 9 828 9179  
[autexacoustics.co.nz](http://autexacoustics.co.nz)

● **Australia**  
285 Swan Street,  
Richmond, VIC 3121  
T 1800 678 160  
T +61 3 9450 6700  
[autexacoustics.com.au](http://autexacoustics.com.au)

● **United Kingdom**  
Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
HX5 9DA  
T +44 0 142 241 8899  
[autexacoustics.co.uk](http://autexacoustics.co.uk)

● **United States**  
1630 Dan Kipper Drive,  
Riverside, CA 92507  
T +1 424 203 1813  
[autexacoustics.com](http://autexacoustics.com)

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), and Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited or other members of the Autex Group. © Copyright 2025 Autex Industries Ltd. All rights reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex Acoustics account manager.