

AUTEX DUCT WRAP (ADW)

GreenStuf® Autex Duct Wrap (ADW™) insulation is a lightweight, flexible acoustic and thermal insulation manufactured from thermally bonded polyester with an e-foil finish on one side.

GreenStuf ADW is used for external wrapping of air conditioning sheet metal ductwork. It provides noise absorption and thermal insulation for the ducting. GreenStuf ADW also acts as a moisture barrier preventing condensation on cold air systems that could otherwise lead to corrosion and staining of ceilings if not insulated.

GreenStuf ADW is designed to be easy to install with a 150mm overlap of foil provided on one side of the roll for simple and quick joining with standard foil tapes.

APPLICATIONS

GreenStuf ADW is designed to be fitted without gaps around ducting, edges to be overlapped and sealed with tape. Where used to control condensation, the ducting wrap must be fully sealed to prevent moisture ingress. Deviations from the above must be consulted with the specifying engineer.

To ensure Building Code compliance, architects and building designers are advised to consult an engineer or the relevant NZ standards before specifying thermal and acoustic insulation products. For information and assistance please contact your GreenStuf account manager.

TECHNICAL

NZBC compliance: GreenStuf ADW, when installed in accordance with the manufacturer's instructions, will satisfy the 50-year durability clause NZBC B2.3.1 (a). GreenStuf meets the relevant clauses of NZBC C3.4(a) Prevention of Fire, E3 Internal Moisture, F2 Hazardous Building Materials, and contributes to meeting H1 Energy Efficiency requirements.

Fire regulations: GreenStuf insulation may not be suitable for all applications, as stipulated in the NZBC.

Please consult a fire engineer when specifying Greenstuf insulation or contact your local GreenStuf account manager for further information.

Thermal performance: GreenStuf ADW thermal performance has been tested internally to ASTM C518 using the procedures of ASTM C653 including the modifications specified in AS/NZS 4859.1.

The R-value of flexible ducting insulation is calculated according to the formula prescribed by H1/VM3 and varies with the duct diameter. The declared R-value represents the minimum thermal resistance that can be achieved when installed in duct sizes varying from 100mm to 600mm diameter.

GreenStuf's e-foil facing enhances thermal performance by reflecting heat away from the surface, thereby enhancing the thermal resistance of the adjacent air film layer.

Non-toxic, non-allergenic, non-irritant: There are no known hazards with the use or handling of GreenStuf polyester.

Durability: GreenStuf has a 50 Year durability warranty.

Respiratory Safe: Polyester fibres used in GreenStuf are above 20 micrometres in size and will not reach the lower respiratory tract when inhaled.

Fire ratings:

ISO 9705: 1993

Classification: Group 1-S

Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

FI 5550

Maximum service temperature: GreenStuf ADW can be used in environments with temperatures not exceeding 90°C.

Vermin: GreenStuf is naturally resistant to insect and vermin attack and does not contain chemical deterrents. Birds and vermin will live and nest in all bulk-fibre insulation materials if allowed access. In high-risk areas, GreenStuf recommends ensuring that the building perimeter is vermin proofed.

Non-corrosive: GreenStuf polyester is considered non-corrosive based on AS/NZS 4859.1 Standard for insulation.

VOC emissions: GreenStuf has been tested for chemical emissions in accordance with ASTM D5116 and is considered as a low VOC product.

VOC concentration: 0.01 mg/m³ (7 days).

GECA/GreenGuard Limit: 0.25 mg/m³ (7 days).

Water vapour sorption: ASTM C1104 / C1104M-13a. Test conditions: 49°C, 95%RH. Water vapour absorbed and adsorped after 4 days: 1.1% by weight.

Microbial resistance: ASTM G21-15. Growth Rating: 0 (No growth). GreenStuf insulation does not promote the growth of moulds and mildew.



Declare.



PRODUCT	THICKNESS	R-VALUE	THERMAL CONDUCTIVITY	DIMENSIONS	ROLLS	TOTAL AREA
ADW Duct Wrap 25mm – White – E-foil	25mm	0.6	0.0417W/m.K	1200mm x 10m	1	12m ²
ADW Duct Wrap 25mm – White – E-foil – Peel and Stick backing	25mm	0.6	0.0417W/m.K	1200mm x 10m	1	12m ²
ADW Duct Wrap 50mm – White – E-foil	50mm	1.0	0.0500W/m.K	1200mm x 10m 1400mm x 10m	1	12m ² 14m ²
ADW Duct Wrap 50mm – White – E-foil – Peel and Stick backing	50mm	1.0	0.0500W/m.K	1200mm x 10m	1	12m ²
ADW Duct Wrap 65mm – White – E-foil	65mm	1.2	0.0504W/m.K	1200mm x 6m 1400mm x 6m	1	7.2m ² 8.4m ²

MSDS: Material Safety Data Sheets (MSDS) are available on request from your GreenStuf account manager or can be downloaded from our website greenstuf.co.nz

Nominal thickness: The products nominal thickness is the off-line manufactured thickness. Packaging, storage, and handling may affect the “out of the pack” thickness. This is not considered a manufacturing fault. If thickness is critical to a particular installation, please discuss your requirements with your GreenStuf account manager.

ISO certifications: GreenStuf is committed to Quality, Environmental, and Health & Safety best practice through our ISO 9001, ISO 14001, and ISO 45001 certified Quality, Environmental, and Health & Safety Management Systems.

Takeback programme: GreenStuf is recyclable. We will gladly recycle used polyester insulation site waste, including offcuts and packaging, to help keep it out of landfills. Please ensure used polyester insulation and offcuts are in a general state of cleanliness in line with standard site conditions. Excessive contamination, such as metal and cement, will not be accepted. Please contact your account manager to request a Material Diversion Certificate prior to dropping insulation off. For more information on recycling GreenStuf, contact us on 0800 428 839.

Packaging recycling: GreenStuf packaging is recyclable LDPE 4. Please refer to your local recycling centres for drop-off and collection services.

Environmental: GreenStuf Autex Duct Wrap (ADW) is manufactured using 100% polyester fibre and contains a minimum of 51% previously recycled fibre content (from PET plastic). Greenstuf views waste as a resource with potential, not something to be disposed of. With this in mind, all product trimmings and offcuts are reused, and waste material goes back through production to make more GreenStuf.

GreenStuf products are Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star, Homestar, and WELL certification.

GreenStuf is also Declare certified to be Red List chemical-free and can be used in Living Building Challenge projects.

For more information, please contact your GreenStuf account manager, or visit our website greenstuf.co.nz.



GreenStuf® FACTORY AND COLLECTIONS

40 Westpoint Drive,
Hobsonville, Auckland 0618,
New Zealand

FREEPHONE 0800 428 839
PHONE +64 9 828 9179
FAX +64 9 828 5810
WEB greenstuf.co.nz

AN ISO 9001, ISO 14001 AND ISO 45001 CERTIFIED COMPANY

The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2025 Autex Industries Ltd. All Rights Reserved.

It is the user's responsibility to determine if the product and information presented in this document are suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your GreenStuf® account manager.