



Lattice is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 certified Quality Management System. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification

Product name	Lattice
Description	100% polyester lightweight semi-rigid panel.
	Metric
Assembled size	Available in 3 assembled sizes Please refer to Lattice Data Sheet for individual dimensions
Thickness	12mm
Tolerance	(+/- 6%)
Density	192kg/m ³

Physical description/
properties

Boiling point:	N/A
Melting point:	250°C
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A



Acoustic performance

Lattice Eclipse is specifically designed to reduce and control reverberated (echo) noise in building interiors.

Frequency (Hz)	125	250	500	1000	2000	4000	Metric Sabin Per Unit
Lattice Eclipse (12mm Direct Fix)	0.5	1.8	1.6	2.2	2.7	3.3	2.10
Lattice Eclipse (12mm Suspended 200mm)	0.3	1.0	1.8	2.3	3.1	3.6	2.05

Acoustic performance

Lattice Torus is specifically designed to reduce and control reverberated (echo) noise in building interiors.

Frequency (Hz)	125	250	500	1000	2000	4000	Metric Sabin Per Unit
Lattice Torus (12mm Direct Fix)	0.5	1.5	1.6	1.8	2.1	2.4	1.75
Lattice Torus (12mm Suspended 200mm)	0.3	0.8	1.3	1.8	2.4	2.9	1.60

Acoustic performance

Lattice Trapezium is specifically designed to reduce and control reverberated (echo) noise in building interiors.

Frequency (Hz)	125	250	500	1000	2000	4000	Metric Sabin Per Unit
Lattice Trapezium (12mm Direct Fix)	2.1	4.1	3.1	4.0	4.4	4.6	3.90
Lattice Trapezium (12mm Suspended 200mm)	1.4	2.6	3.1	4.0	5.1	5.4	3.70

Service

For further information about Lattice, or any other Autex Acoustics® product, please contact your account manager or visit our website.

Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.



Product specifications

Composition

100% polyester fibre from polyethylene terephthalate (PET). Lattice is made from Autex Cube™ which contains a minimum of 80% previously recycled polyester fibre.

Suitable applications

Suspended and direct fixed.

Fire Ratings

Lattice is a value-added product made from Autex Cube acoustic panels as the base material. Cube (12mm) has been evaluated using the following test methods:

ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate:
<5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1
(SMOGR_{Arc}): <100m²/s²
Assessed using methodology AS ISO 9705 - 2003 in accordance with AS 5637:2015, as required by NCC Specification 7: Fire Hazard properties: S7C4
FI 4974
FAR 4055

BS EN 13501-1:2018

Ceiling applications
Classification: B-s1, d0
(Cube™ 12mm)

Tested according to BS EN ISO 11925-2:2020 and BS EN 13823:2020 + A1:2022 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014. 7191361939-MEC25/03-JV

ASTM E-84-15a

Class A, FS:0 - SD:45
(Cube™ 12mm)
RJ4479-2

VOC emissions

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered as a low VOC product.
VOC concentration:
0.009 mg/m³ (7 days)

Water vapour sorption

ASTM C1104 / C1104M-13a
Test conditions: 49°C, 95%RH
Water vapour absorbed and adsorped after 4 days:
0.4% by weight

Microbial resistance

ASTM G21-15
Growth Rating: 0 (No growth)
Lattice does not promote the growth of moulds and mildew.

Colour fastness to light

Lattice is suitable for indoor use only. Light fastness is dependent on use and exposure. Lattice has been evaluated to the following standard:
ISO 105-B02:2014
Rating: 6 (Highest = 7)

Colour fastness to rubbing

ISO 105-X12:2016
Dry Rating: 4-5 (Highest = 5)
Wet Rating: 4-5 (Highest = 5)

Pattern repeat

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

Custom printed Cube requires the services of a specialist cleaning company. Refer to the Lattice Cleaning and Maintenance Guide for more information.

Finish

Non-woven. No pattern repeat but Workstation has a directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

● **New Zealand**
702-718 Rosebank Road,
Private Bag 19988,
Avondale 1746, Auckland
T 0800 428 839
T +64 9 828 9179
autexacoustics.co.nz

● **Australia**
121-131 Global Avenue,
Essendon Fields,
VIC 3041
T 1800 678 160
T +61 3 9450 6700
autexacoustics.com.au

● **United Kingdom**
Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire,
HX5 9DA
T +44 0 142 241 8899
autexacoustics.co.uk

● **United States**
742 S Hill Street,
Suite 501, Los Angeles,
CA 90014
T +1 424 203 1813
autexacoustics.com

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), and Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited or other members of the Autex Group. © Copyright 2025 Autex Industries Ltd. All rights reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex Acoustics' account manager.