2024-07-12

OpenHPC: Beyond the Install Guide

OpenHPC: Beyond the Install Guide
for PEARC24

Sharon Colson Jim Moroney Mike Renfro
Tennessee Tech University

2024-07-22

Acknowledgments and shameless plugs

OpenHPC especially Tim Middelkoop (Internet2) and Chris Simmons (Massachusetts Green High Performance Computing Center). They have a BOF at 1:30 Wednesday. You should go to it.

x

x

Acknowledgments and shameless plugs

OpenHPC especially Tim Middelkoop (Internet2) and Chris Simmons (Massachusetts Green High Performance Computing Center). They have a BOF at 1:30 Wednesday. You should go to it.

Jetstream2 especially Jeremy Fischer, Mike Lowe, and Julian Pistorius. Jetstream2 has a tutorial at the same time as this one. Please stay here.

Acknowledgments and shameless plugs

OpenHPC especially Tim Middelkoop (Internet2) and Chris Simmons (Massachusetts Green High Performance Computing Center). They have a BOF at 1:30 Wednesday. You should go to it.

Jetstream2 especially Jeremy Fischer, Mike Lowe, and Julian Pistorius. Jetstream2 has a tutorial at the same time as this one. Please stay here.

NSF CC* for the equipment that led to some of the lessons we're sharing today (award #2127188).

x

Acknowledgments and shameless plugs

OpenHPC especially Tim Middelkoop (Internet2) and Chris Simmons (Massachusetts Green High Performance Computing Center). They have a BOF at 1:30 Wednesday. You should go to it.

Jetstream2 especially Jeremy Fischer, Mike Lowe, and Julian Pistorius. Jetstream2 has a tutorial at the same time as this one. Please stay here.

NSF CC* for the equipment that led to some of the lessons we're sharing today (award #2127188).

ACCESS current maintainers of the project formerly known as the XSEDE Compatible Basic Cluster.

x

x

Where we're starting from

Figure 1: Two example HPC networks for the tutorial

You:

- have installed OpenHPC before
- have been issued a (basically) out-of-the-box OpenHPC cluster for this tutorial

Cluster details:

- Rocky Linux 9 (x86_64)
- OpenHPC 3.1, Warewulf 3, Slurm 23.11.6
- 2 non-GPU nodes
- 2 GPU nodes (currently without GPU drivers, so: expensive non-GPU nodes)
- 1 management node (SMS)
- 1 unprovisioned login node

Where we're starting from

We used the OpenHPC automatic installation script from Appendix A with a few variations:

1. Installed `s-nail` to have a valid `MailProg` for `slurm.conf`.
2. Created `user1` and `user2` accounts with password-less `sudo` privileges.
3. Changed `CHROOT` from `/opt/ohpc/admin/images/rocky9.3` to `/opt/ohpc/admin/images/rocky9.4`.
4. Enabled `slurmd` and `munge` in `CHROOT`.
5. Added `nano` and `yum` to `CHROOT`.
6. Removed a redundant `ReturnToService` line from `/etc/slurm/slurm.conf`.
7. Stored all compute/GPU nodes' SSH host keys in `/etc/ssh/ssh_known_hosts`.
8. Globally set an environment variable `CHROOT` to `/opt/ohpc/admin/images/rocky9.4`.

x

Where we're going

1. A login node that's practically identical to a compute node (except for where it needs to be different)
2. A slightly more secured SMS and login node
3. GPU drivers on the GPU nodes
4. Using node-local storage for the OS and/or scratch
5. De-coupling the SMS and the compute nodes (e.g., independent kernel versions)
6. Easier management of node differences (GPU or not, diskless/single-disk/multi-disk, Infiniband or not, etc.)
7. Slurm configuration to match some common policy goals (fair share, resource limits, etc.)

x

Assumptions

1. We have a VM named `login`, with no operating system installed.
2. The `eth0` network interface for `login` is attached to the internal network, and `eth1` is attached to the external network.
3. The `eth0` MAC address for `login` is known—check the **Login server** section of your handout for that. It's of the format `aa:bb:cc:dd:ee:ff`.
4. We're logged into the SMS as `user1` or `user2` that has `sudo` privileges.

x

Create a new login node

Working from section 3.9.3 of the install guide:

```
[user1@sms ~]$ sudo wwsh -y node new login --netdev eth0 \
    --ipaddr=172.16.0.2 --hwaddr=__:__:__:__:__:__
[user1@sms ~]$ sudo wwsh -y provision set login \
    --vnfs=rocky9.4 --bootstrap=$(uname -r) \
    --files=dynamic_hosts,passwd,group,shadow,munge.key,network
```

Make sure to replace the __ with the characters from your login node's MAC address!

x

What'd we just do?

Ever since `login` was powered on, it's been stuck in a loop trying to PXE boot. What's the usual PXE boot process for a client in an OpenHPC environment?

1. The client network card tries to get an IP address from a DHCP server (the SMS) by broadcasting its MAC address.

x


What'd we just do?
Ever since login was powered on, it's been stuck in a loop trying to PXE boot. What's the usual PXE boot process for a client in an OpenHPC environment?
1. The client network card tries to get an IP address from a DHCP server (the SMS) by broadcasting its MAC address.
2. The SMS responds with the client's IP and network info, a next-server IP (the SMS again), and a filename option (a bootloader from the iPXE project).

x


What'd we just do?
Ever since login was powered on, it's been stuck in a loop trying to PXE boot. What's the usual PXE boot process for a client in an OpenHPC environment?
1. The client network card tries to get an IP address from a DHCP server (the SMS) by broadcasting its MAC address.
2. The SMS responds with the client's IP and network info, a next-server IP (the SMS again), and a filename option (a bootloader from the iPXE project).
3. The network card gets the bootloader over TFTP and executes it.

x


What'd we just do?
Ever since login was powered on, it's been stuck in a loop trying to PXE boot. What's the usual PXE boot process for a client in an OpenHPC environment?
1. The client network card tries to get an IP address from a DHCP server (the SMS) by broadcasting its MAC address.
2. The SMS responds with the client's IP and network info, a next-server IP (the SMS again), and a filename option (a bootloader from the iPXE project).
3. The network card gets the bootloader over TFTP and executes it.
4. iPXE makes a second DHCP request and this time, it gets a URL (by default, http://SMS_IP/WW/ipxe/cfg/${client_mac}) for an iPXE config file.

x

x

What'd we just do?

Ever since `login` was powered on, it's been stuck in a loop trying to PXE boot. What's the usual PXE boot process for a client in an OpenHPC environment?

1. The client network card tries to get an IP address from a DHCP server (the SMS) by broadcasting its MAC address.
2. The SMS responds with the client's IP and network info, a `next-server` IP (the SMS again), and a `filename` option (a bootloader from the iPXE project).
3. The network card gets the bootloader over TFTP and executes it.
4. iPXE makes a second DHCP request and this time, it gets a URL (by default, `http://SMS_IP/WW/ipxe/cfg/${client_mac}`) for an iPXE config file.
5. The config file contains the URL of a Linux kernel and initial ramdisk, plus multiple kernel parameters available after initial bootup for getting the node's full operating system contents.

What'd we just do?

1. The node name, `--bmaddr`, and `--ipaddr` parameters go into the SMS DHCP server settings.

x

x

What'd we just do?

1. The node name, `--bwaddr`, and `--ipaddr` parameters go into the SMS DHCP server settings.
2. The `--bootstrap` parameter defines the kernel and ramdisk for the iPXE configuration.


What'd we just do?
1. The node name, --hwaddr, and --ipaddr parameters go into the SMS DHCP server settings.
2. The --bootstrap parameter defines the kernel and ramdisk for the iPXE configuration.
3. The node name, --netdev, --ipaddr, --hwaddr parameters all go into kernel parameters accessible from the provisioning software.

x

What'd we just do?

1. The node name, `--hwaddr`, and `--ipaddr` parameters go into the SMS DHCP server settings.
2. The `--bootstrap` parameter defines the kernel and ramdisk for the iPXE configuration.
3. The node name, `--netdev`, `--ipaddr`, `--hwaddr` parameters all go into kernel parameters accessible from the provisioning software.
4. During the initial bootup, the `--hwaddr` parameter is passed to a CGI script on the SMS to identify the correct VNFS for the provisioning software to download (set by the `--vnfs` parameter).

x

x

What'd we just do?

1. The node name, `--hwaddr`, and `--ipaddr` parameters go into the SMS DHCP server settings.
2. The `--bootstrap` parameter defines the kernel and ramdisk for the iPXE configuration.
3. The node name, `--netdev`, `--ipaddr`, `--hwaddr` parameters all go into kernel parameters accessible from the provisioning software.
4. During the initial bootup, the `--hwaddr` parameter is passed to a CGI script on the SMS to identify the correct VNFS for the provisioning software to download (set by the `--vnfs` parameter).
5. After downloading the VNFS, the provisioning software will also download files from the SMS set by the `--files` parameter.

Did it work? So far, so good.

```
[user1@smn ~]$ sudo ssh login
[root@login ~]# df -h
Filesystem
...
172.16.0.1:/home
172.16.0.1:/opt/ohpc/pub
```

x


Did it work? Not entirely.
[root@login ~]# sinfo
sinfo: error: resolve_ctls_from_dns_srv: res_nsearch error: Unknown host
sinfo: error: fetch_config: DNS SRV lookup failed
sinfo: error: _establish_config_source: failed to fetch config
sinfo: fatal: Could not establish a configuration source
systemctl status slurmd is more helpful, with
fatal: Unable to determine this slurmd's NodeName. So how do we fix this one?

x

Option 1: take the error message literally

So there's no entry for login in the SMS `slurm.conf`. To fix that:

1. Run `slurmd -C` on the login node to capture its correct CPU specifications. Copy that line to your laptop's clipboard.

x


Option 1: take the error message literally
So there's no entry for login in the SMS slurm.conf. To fix that:
1. Run slurmd -C on the login node to capture its correct CPU specifications. Copy that line to your laptop's clipboard.
2. On the SMS, run nano /etc/slurm/slurm.conf and make a new line of all the slurmd -C output from the previous step (pasted from your laptop clipboard).

x


Option 1: take the error message literally
So there's no entry for login in the SMS slurm.conf. To fix that:
1. Run slurmd -C on the login node to capture its correct CPU specifications. Copy that line to your laptop's clipboard.
2. On the SMS, run nano /etc/slurm/slurm.conf and make a new line of all the slurmd -C output from the previous step (pasted from your laptop clipboard).
3. Save and exit nano by pressing Ctrl-X and then Enter.

x


Option 1: take the error message literally
So there's no entry for login in the SMS slurm.conf. To fix that:
1. Run slurmd -C on the login node to capture its correct CPU specifications. Copy that line to your laptop's clipboard.
2. On the SMS, run nano /etc/slurm/slurm.conf and make a new line of all the slurmd -C output from the previous step (pasted from your laptop clipboard).
3. Save and exit nano by pressing Ctrl-X and then Enter.
4. Reload the new Slurm configuration everywhere (well, everywhere functional) with sudo scontrol reconfigure on the SMS.

x

x


Option 1: take the error message literally
So there's no entry for login in the SMS slurm.conf. To fix that:
1. Run slurmd -C on the login node to capture its correct CPU specifications. Copy that line to your laptop's clipboard.
2. On the SMS, run nano /etc/slurm/slurm.conf and make a new line of all the slurmd -C output from the previous step (pasted from your laptop clipboard).
3. Save and exit nano by pressing Ctrl-X and then Enter.
4. Reload the new Slurm configuration everywhere (well, everywhere functional) with sudo scontrol reconfigure on the SMS.
5. ssh back to the login node and restart slurmd, since it wasn't able to respond to the scontrol reconfigure from the previous step
(sudo ssh login systemctl restart slurmd on the SMS).

Option 1: take the error message literally

Now an `sinfo` should work on the login node:

```
[root@login ~]# sinfo
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
normal*      up 1-00:00:00      1   idle c[1-2]
```

x

Option 2: why are we running `slurmd` anyway?

The `slurmd` service is really only needed on systems that will be running computational jobs, and the login node is not in that category.

Running `slurmd` like the other nodes means the login node can get all its information from the SMS, but we can do the same thing with a very short customized `slurm.conf` with two lines from the SMS' `slurm.conf`:

```
ClusterName=cluster
SlurmctldHost=sms
```

x


Interactive test
1. On the login node as root, temporarily stop the slurmd service with systemctl stop slurmd
2. On the login node as root, edit /etc/slurm/slurm.conf with nano /etc/slurm/slurm.conf
3. Add the two lines to the right, save and exit nano by pressing Ctrl-X and then Enter.
/etc/slurm/slurm.conf on login node
ClusterName=cluster
SlurmctldHost=sms
Verify that sinfo still works without slurmd and with the custom /etc/slurm/slurm.conf.
[root@login ~]# sinfo
PARTITION AVAIL TIMELIMIT NODES STATE NODELIST
normal* up 1-00:00:00 1 idle c[1-2]

x

Make permanent changes from the SMS

Let's reproduce the changes we made interactively on the login node in the Warewulf settings on the SMS.

For the customized `slurm.conf` file, we can keep a copy of it on the SMS and add it to the Warewulf file store.

We've done that previously for files like the shared `munge.key` for all cluster nodes (see section 3.8.5 of the OpenHPC install guide).

We also need to make sure that file is part of the login node's provisioning settings.

x


Make permanent changes from the SMS
On the SMS:
[user1@sms ~]$ sudo scp login:/etc/slurm/slurm.conf \
/etc/slurm/slurm.conf.login
slurm.conf 100% 40 57.7KB/s 00:00
[user1@sms ~]$ sudo wwsh -y file import \
/etc/slurm/slurm.conf.login --name=slurm.conf.login \
--path=/etc/slurm/slurm.conf
Now the file is available, but we need to ensure the login node gets it. That's handled
with wwsh provision.

x

x

A quick look at wwsh provision

What are the provisioning settings for compute node c1?

```
[user1@sms ~]$ wwsh provision print c1
################################################################################
### c1 #########################################################################
c1: MASTER              = UNDEF
c1: BOOTSTRAP           = 6.1.96-1.el9.elrepo.x86_64
c1: VNFS                = rocky9.4
c1: VALIDATE            = FALSE
c1: FILES               = dynamic_hosts,group,munge.key,network,
  passwd,shadow
...
c1: KARGS               = "net.ifnames=0 biosdevname=0 quiet"
c1: ROOTLOCAL           = FALSE
```


A quick look at wwsh provision
What are the provisioning settings for node login?
[user1@sms ~]$ wwsh provision print login
login
login: MASTER = UNDEF
login: BOOTSTRAP = 6.1.96-1.el9.elrepo.x86_64
login: VNFS = rocky9.4
login: VALIDATE = FALSE
login: FILES = dynamic_hosts,group,munge.key,network,
passwd,shadow
...
login: KARGS = "net.ifnames=0 biosdevname=0 quiet"
login: BOOTLOCAL = FALSE

x

x

A quick look at `wwsh provision`

The provisioning settings for `c1` and `login` are identical, but there's a lot to read in there to be certain about it.

We could run the two outputs through `diff`, but every line contains the node name, so **no lines are literally identical**.

Let's simplify and filter the `wwsh provision` output to make it easier to compare.

x


Filter the wwsh provision output
I only care about the lines containing = signs, so
wwsh provision print c1 | grep =
is a start.

Filter the `wwsh provision` output

- I only care about the lines containing = signs, so

```
wwsh provision print c1 | grep =
```

is a start.

- Now all the lines are prefixed with `c1:`, and I want to keep everything after that, so

```
wwsh provision print c1 | grep = | cut -d: -f2-
```

will take care of that.

x

x

Filtered result

```
wwsh provision print c1 | grep = | cut -d: -f2-
```

```
MASTER              = UNDEF
BOOTSTRAP           = 6.1.96-1.el9.elrepo.x86_64
VNFS                = rocky9.4
VALIDATE            = FALSE
FILES               = dynamic_hosts,group,munge.key,network,
  passwd,shadow
...
KARGS               = "net.ifnames=0 biosdevname=0 quiet"
BOOTLOCAL           = FALSE
```

Much more useful.


Make a function for this
We may be typing that command pipeline a lot, so let's make a shell function to cut down on typing:
[user1@sms ~]$ function proprint() { \
> wwsh provision print $@ | grep = | cut -d: -f2- ; }
[user1@sms ~]$ proprint c1
MASTER = UNDEF
BOOTSTRAP = 6.1.96-1.el9.elrepo.x86_64
...

x

diff the outputs

We could redirect a `proprint c1` and a `proprint login` to files and `diff` the resulting files, or we can use the shell's `<()` operator to treat command output as a file:

```
[user1@sms ~]$ diff -u <(proprint c1) <(proprint login)
[user1@sms ~]$
```

Either of those shows there are zero provisioning differences between a compute node and the login node.

x


Add the custom slurm.conf to the login node
Add a file to login's FILES property with:
[user1@smc ~]$ sudo wwsh -y provision set login \
--fileadd=slurm.conf.login
(refer to section 3.9.3 of the install guide for previous examples of --fileadd).

x

Check for provisioning differences

```
[user1@xnx ~]$ diff -u <(proprint c1) <(proprint login)
--- /dev/fd/63  2024-07-06 11:11:07.682859677 -0400
+++ /dev/fd/62  2024-07-06 11:11:07.683959681 -0400
@@ -2,7 +2,7 @@
  BOOTSTRAP          = 6.1.96-1.el9.elrepo.x86_64
  VNFS               = rocky9.4
  VALIDATE           = FALSE
- FILES              = dynamic_hosts,group,munge.key,network,
  passwd,shadow
+ FILES              = dynamic_hosts,group,munge.key,network,
  passwd,shadow,slurm.conf.login
  PRESHELL           = FALSE
  POSTSHELL          = FALSE
  POSTNETDOWN        = FALSE
```

x

x



Ensure slurmd doesn't run on the login node

To disable the slurmd service on just the login node, we can take advantage of conditions in the systemd service file. Back on the login node as root:

```
[user1@smc ~]$ sudo ssh login
[root@login ~]# systemctl edit slurmd
```

Insert three lines between the lines of ### Anything between here... and ### Lines below this comment...:

```
[Unit]
ConditionHost=|c*
ConditionHost=|g*
```

This will only run the service on nodes whose hostnames start with c or g.

x


Ensure slurmd doesn't run on the login node
Once that file is saved, try to start the slurmd service with systemctl start slurmd and check its status with systemctl status slurmd
slurmd.service - Slurm node daemon
Condition: start condition failed at Sat 2024-07-06 18:12:17 EDT; 4min 22s ago
Jul 06 17:14:16 login systemd[1]: Stopped Slurm node daemon.
Jul 06 18:12:17 login systemd[1]: Slurm node daemon was skipped because of an unmet condition check (ConditionPath=!/e

x


Make the changes permanent
The systemctl edit command resulted in a file /etc/systemd/system/slurmd.service.d/override.conf. Let's:
make a place for it in the chroot on the SMS, and
copy the file over from the login node.
[user1@sms ~]$ sudo mkdir -p \
${CHROOT}/etc/systemd/system/slurmd.service.d/
[user1@sms ~]$ sudo scp \
login:/etc/systemd/system/slurmd.service.d/override.conf \
${CHROOT}/etc/systemd/system/slurmd.service.d/
override.conf 100% 23 36.7KB/s 00:00
(Note: we globally pre-set the CHROOT environment for any account that logs into the SMS so that you didn't have to.)


Make the changes permanent
Finally, we'll:
rebuild the VNFS, and
reboot both the login node and a compute node to test the changes.
[user1@sms ~]$ sudo wwvnfs --chroot=${CHROOT}
Using 'rocky9.4' as the VNFS name
...
Total elapsed time
= 84.45 s
[user1@sms ~]$ sudo ssh login reboot
[user1@sms ~]$ sudo ssh c1 reboot

x


Verify the changes on the login node
Verify that the login node doesn't start slurmd, but can still run sinfo without any error messages.
[user1@sms ~]$ sudo ssh login systemctl status slurmd
o slurmd.service - Slurm node daemon
...
Jul 06 18:26:23 login systemd[1]: Slurm node daemon was
skipped because of an unmet condition check
(ConditionHost=c*).
[user1@sms ~]$ sudo ssh login sinfo
PARTITION AVAIL TIMELIMIT NODES STATE NODELIST
normal* up 1-00:00:00 1 idle c[1-2]

x


Verify the changes on a compute node

Verify that the compute node still starts slurmd (it can also run sinfo).

```
[user1@sms ~]$ sudo ssh c1 systemctl status slurmd
● slurmd.service - Slurm node daemon
...
Jul 06 19:03:22 c1 systemd[1]: Started Slurm node daemon.
Jul 06 19:03:22 c1 slurmd[1082]: slurmd: CPUs=2 Boards=1
  Sockets=2 Cores=1 Threads=1 Memory=5012 TmpDisk=2956
  Uptime=28 CPUSpecList=(null) FeaturesAvail=(null)
  FeaturesActive=(null)
[user1@sms ~]$ sudo ssh c1 sinfo
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
normal*      up 1-00:00:00      1   idle c2
normal*      up 1-00:00:00      1   down c1
```

(Yes, c1 is marked down—we'll fix that shortly.)

x

Problem: the login node doesn't let users log in

What if we ssh to the login node as someone other than root?

```
[user1@sms ~]$ ssh login
Access denied: user user1 (uid=1001) has no active jobs on this
    node.
Connection closed by 172.16.0.2 port 22
```

which makes this the exact opposite of a login node for normal users. Let's fix that.

x

Make the login node function as a login node

- The `Access denied` is caused by the `pam_slurm.so` entry at the end of `/etc/pam.d/sshd`, which is invaluable on a normal compute node, but not on a login node.
- On the SMS, you can also do a `diff -u /etc/pam.d/sshd ${CHROOT}/etc/pam.d/sshd`
- You'll see that the `pam_slurm.so` line is the only difference between the two files.

x

Test a PAM change to the login node

- Temporarily comment out the last line of the login node's `/etc/pam.d/ssh` and see if you can ssh into the login node as a normal user (i.e., `ssh user16login`).
- Your user should be able to log in now.
- In case the PAM configuration won't let root log in, **don't panic**! Instructors can reboot your login node from its console to put it back to its original state.

x


Make the change permanent
We want to ensure that the login node gets the same /etc/pam.d/sshd that the SMS uses.
We'll follow the same method we used to give the login node a custom slurm.conf:
[user1@sms ~]$ sudo wwsh -y file import /etc/pam.d/sshd \
--name=sshd.login
[user1@sms ~]$ wwsh file list
...
sshd.login : rw-r--r-- 1 root root 727 /etc/pam.d/sshd

x

x

Make the change permanent

```
[user1@sms ~]$ sudo wwsh -y provision set login \
  --fileadd=sshd.login
[user1@sms ~]$ diff -u <(proprint c1) <(proprint login)
...
  VALIDATE            = FALSE
- FILES               = dynamic_hosts,group,munge.key,network,
  passwd,shadow
+ FILES               = dynamic_hosts,group,munge.key,network,
  passwd,shadow,slurm.conf.login,sshd.login
...
```

(refer to section 3.9.3 of the install guide for previous examples of `--fileadd`).

Test the change

Reboot the login node and let's see if we can log in as a regular user.

```
[user1@sms ~]$ sudo ssh login reboot
[user1@sms ~]$ ssh login
[user1@login ~]$
```

x


A bit more security for the login node
Not too long after your SMS and/or login nodes are booted, you'll see messages in the SMS /var/log/secure like:
Jul 11 11:24:06 sms sshd[162636]: Invalid user evilmike from 68.66.205.120 port 1028
...
Jul 11 11:24:08 sms sshd[162636]: Failed password for invalid user evilmike from 68.66.205.120 port 1028 ssh2
...
because people who want to break into computers for various reasons have Internet connections.

x

A bit more security for the login node

There's a lot of things that can be done to secure things, including:

1. Placing the SMS and login node external interfaces on protected network segment.
2. Allowing only administrative users to SSH into the SMS.
3. Replacing password-based authentication with key-based authentication.

Though #3 will eliminate brute-force password guessing attacks, it's usually not practical for a login node. So let's mitigate that differently with `fail2ban`.

x


How fail2ban works (by default)
1. Monitor /var/log/secure and other logs for indicators of brute-force attacks (invalid users, failed passwords, etc.).
2. If indicators from a specific IP address happen often enough over a period of time, use firewalld to block all access from that address for a period of time.
3. Once that period has expired, remove the IP address from the block list.
This reduces the effectiveness of brute-force password guessing by orders of magnitude (~10 guesses per hour versus ~100 or ~1000 guesses per hour).
Including firewalld could mean that some necessary services get blocked by default when firewalld starts. Let's see what those could be.

x

x

See what processes are listening on the login node

We'll use the `netstat` command to look for sockets that are udp or tcp, listening, and what process the socket is attached to. We omit anything only listening for `localhost` connections.

```
[user1@smc ~]$ sudo ssh login netstat -utlp | grep -v localhost
Active Internet connections (only servers)
Proto ...  Local Address  ...  State       PID/Program name
tcp        0.0.0.0:ssh          LISTEN      1034/sshd: /usr/sbi
tcp        0.0.0.0:sunrpc       LISTEN      1/init
tcp6       [::]:ssh             LISTEN      1034/sshd: /usr/sbi
tcp6       [::]:sunrpc          LISTEN      1/init
udp        0.0.0.0:sunrpc       0.0.0.0:*   1/init
udp        0.0.0.0:37036        0.0.0.0:*   1143/rsyslogd
udp6       [::]:sunrpc          [::]:*      1/init
```

x


See what processes are listening on the login node
sshd secure shell daemon, the main thing we want to protect against brute force attempts
init the first process started during booing the operating system. Effectively, this shows up when you participate in NFS file storage, as a server or a client (and login is a client).
rsyslogd message logging for all kinds of applications and services
Of these, sshd is the only one that we need to ensure firewalld doesn't block by default. In practice, the ssh port (22) is always in the default list of allowed ports.


Test installing fail2ban on the login node
Install the fail2ban packages into the CHROOT with
[user1@smu ~]$ sudo yum install --installroot=${CHROOT} \
fail2ban
[user1@smu ~]$ sudo chroot ${CHROOT} systemctl enable \
fail2ban firewalld
(the yum command will also install firewalld as a dependency of fail2ban).
Add the following to the chroot's sshd.local file with
sudo nano ${CHROOT}/etc/fail2ban/jail.d/sshd.local:
[sshd]
enabled = true

x


Should I run fail2ban everywhere?
fail2ban is probably best to keep to the login node, and not the compute nodes:
Nobody can SSH into your compute nodes from outside.
Thus, the only things a compute node could ban would be your SMS or your login node.
A malicious or unwitting user could easily ban your login node from a compute node by SSH'ing to it repeatedly, which would effectively be a denial of service.

x

Test installing fail2ban on the login node

```
[user1@rms ~]$ sudo mkdir -p \
  ${CHROOT}/etc/systemd/system/fail2ban.service.d/ \
  ${CHROOT}/etc/systemd/system/firewalld.service.d/
```

x

x


Test installing fail2ban on the login node
[user18xmm ~]$ sudo nano \
${CHROOT}/etc/systemd/system/fail2ban.service.d/override.conf
Add the lines
[Unit]
ConditionHost=|login*
save and exit with Ctrl-X.


Test installing fail2ban on the login node
Finally, duplicate the override file for firewalld:
[user18xxx ~]$ sudo cp \
${CHROOT}/etc/systemd/system/fail2ban.service.d/override.conf \
${CHROOT}/etc/systemd/system/firewalld.service.d/override.conf

x


Test installing fail2ban on the login node
Before we go further, check if there's anything in /var/log/secure on the login node:
[user1@sms ~]$ sudo ssh login1 ls -l /var/log/secure
-rw------- 1 root root 0 Jul 7 03:14 /var/log/secure
Nope. Let's fix that, too.
Looking in /etc/rsyslog.conf, we see a bunch of things commented out, including the line #authpriv.* /var/log/secure.
Rather than drop in an entirely new rsyslog.conf file that we'd have to maintain, rsyslog will automatically include any *.conf files in /etc/rsyslog.d.
Let's make one of those for the chroot.

x

Make an rsyslog.d file, rebuild the VNFS, reboot the login node

```
[user1@sms ~]$ echo "authpriv.* /var/log/secure" | \
  sudo tee ${CHROOT}/etc/rsyslog.d/authpriv-local.conf
authpriv.* /var/log/secure
[user1@sms ~]$ cat \
  ${CHROOT}/etc/rsyslog.d/authpriv-local.conf
authpriv.* /var/log/secure
[user1@sms ~]$ sudo wwvnfs --chroot=${CHROOT}
[user1@sms ~]$ sudo ssh login reboot
```

x

Post-reboot, how's fail2ban and firewalld on the login node?

```
[user18ema ~]$ sudo ssh login systemctl status firewalld
[root@login ~]# systemctl status firewalld
x firewalld.service - firewalld - dynamic firewall daemon
     Loaded: loaded (/usr/lib/systemd/system/firewalld.service;
             enabled; preset>
     Active: failed (Result: exit-code) since Thu 2024-07-11
             16:49:47 EDT, 46m>
...
Jul 11 16:49:47 login systemd[1]: firewalld.service: Main
  process exited, code=exited, status=3/NOTIMPLEMENTED
Jul 11 16:49:47 login systemd[1]: firewalld.service: Failed
  with result 'exit-code'.
```

Not great.

x

x

Diagnosing 3/NOTIMPLEMENTED

- **So many** Google results amount to "reboot to get your new kernel", but we've just booted a new kernel.

Diagnosing 3/NOTIMPLEMENTED

- **So many** Google results amount to "reboot to get your new kernel", but we've just booted a new kernel.
- Red Hat has an article telling you to verify that you haven't disabled module loading by checking `sysctl -a | grep modules_disabled`, but that's not disabled either.

x


Diagnosing 3/NOTIMPLEMENTED
So many Google results amount to "reboot to get your new kernel", but we've just booted a new kernel.
Red Hat has an article telling you to verify that you haven't disabled module loading by checking sysctl -a | grep modules_disabled, but that's not disabled either.
The Red Hat article does tell you that packet filtering capabilities have to be enabled in the kernel, and that gets us closer.

x

Diagnosing 3/NOTIMPLEMENTED

- **So many** Google results amount to "reboot to get your new kernel", but we've just booted a new kernel.
- Red Hat has an article telling you to verify that you haven't disabled module loading by checking `sysctl -a | grep modules_disabled`, but that's not disabled either.
- The Red Hat article does tell you that packet filtering capabilities have to be enabled in the kernel, and that gets us closer.
- It is possible to install and start firewalld on the SMS (you don't have to verify this right now), and that's using the same kernel as the login node.

x

Diagnosing 3/NOTIMPLEMENTED

- **So many** Google results amount to "reboot to get your new kernel", but we've just booted a new kernel.
- Red Hat has an article telling you to verify that you haven't disabled module loading by checking `sysctl -a | grep modules_disabled`, but that's not disabled either.
- The Red Hat article does tell you that packet filtering capabilities have to be enabled in the *kernel*, and that gets us closer.
- It is possible to install and start firewalld on the SMS (you don't have to verify this right now), and that's using the same kernel as the login node.
- Or **is it?**

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?
- Via `wwbootstrap $(uname -r)` on the SMS (section 3.9.1)

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?
- Via `wwbootstrap $(uname -r)` on the SMS (section 3.9.1)
- That section **also** had a command that most of us don't pay close attension to: `echo "drivers += updates/kernel/" >> /etc/warewulf/bootstrap.conf`

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?
- Via `vwbootstrap $(uname -r)` on the SMS (section 3.9.1)
- That section **also** had a command that most of us don't pay close attension to: `echo "drivers += updates/kernel/" >> /etc/warewulf/bootstrap.conf`
- So though the login node is running the same kernel **version** as the SMS, it may **not** have all the drivers included.

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?
- Via `wwbootstrap $(uname -r)` on the SMS (section 3.9.1)
- That section **also** had a command that most of us don't pay close attension to: `echo "drivers += updates/kernel/" >> /etc/warewulf/bootstrap.conf`
- So though the login node is running the same kernel **version** as the SMS, it may **not** have all the drivers included.
- Where are the drivers we care about? `lsmod` on the SMS shows a lot of `nf`-named modules for the Netfilter kernel framework.

x

Diagnosing 3/NOTIMPLEMENTED

- How did we get the kernel that the login node is using?
- Via `wwbootstrap $(uname -r)` on the SMS (section 3.9.1)
- That section **also** had a command that most of us don't pay close attension to: `echo "drivers += updates/kernel/" >> /etc/warewulf/bootstrap.conf`
- So though the login node is running the same kernel **version** as the SMS, it may **not** have all the drivers included.
- Where are the drivers we care about? `lsmod` on the SMS shows a lot of `nf`-named modules for the Netfilter kernel framework.
- `find /lib/modules/$(uname -r) -name 'nft*'` shows these modules are largely located in the `kernel/net` folder (specifically `kernel/net/ipv4/netfilter`, `kernel/net/ipv6/netfilter`, and `kernel/net/netfilter`).

x


Diagnosing 3/NOTIMPLEMENTED
Is kernel/net in our /etc/warewulf/bootstrap.conf at all?
[user1@sms ~]$ grep kernel/net /etc/warewulf/bootstrap.conf
[user1@sms ~]$
Nope, let's add it.
[user1@sms ~]$ grep kernel/net /etc/warewulf/bootstrap.conf
[user1@sms ~]$ echo "drivers += kernel/net/" | \
sudo tee -a /etc/warewulf/bootstrap.conf
drivers += kernel/net/
[user1@sms ~]$ grep kernel/net /etc/warewulf/bootstrap.conf
drivers += kernel/net/

x


Diagnosing 3/NOTIMPLEMENTED
Let's re-run the wwbootstrap command and reboot the login node:
[user1@sms ~]$ sudo wwbootstrap $(uname -r)
...
Bootstrap image '6.1.97-1.el9.elrepo.x86_64' is ready
Done.
[user1@sms ~]$ sudo ssh login reboot

x

x

Did 3/NOTIMPLEMENTED go away?

```
[user1@sms ~]$ sudo ssh login systemctl status firewalld
● firewalld.service - firewalld - dynamic firewall daemon
     Loaded: loaded (/usr/lib/systemd/system/firewalld.service;
             enabled; preset: enabled)
     Active: active (running) since Thu 2024-07-11 21:58:18
             EDT; 43s ago
...
Jul 11 21:58:18 login systemd[1]: Starting firewalld - dynamic
  firewall daemon...
Jul 11 21:58:18 login systemd[1]: Started firewalld - dynamic
  firewall daemon.
```

It did.


Does fail2ban actually work now?
[user18cmg ~]$ sudo zgrep login grep 68.66.205.120 \
/var/log/fail2ban.log
2024-07-11 22:02:27,030 fail2ban.actions ... [sshd] Ban \
68.66.205.120
It does.

x

x

What does it look like from evilmike's side?

```
mike@server:~$ ssh evilmike@149.165.155.235
evilmike@149.165.155.235's password:
Permission denied, please try again.
evilmike@149.165.155.235's password:
Permission denied, please try again.
evilmike@149.165.155.235's password:
evilmike@149.165.155.235: Permission denied (publickey,
  gssapi-keyex,gssapi-with-mic,password).
mike@server:~$ ssh evilmike@149.165.155.235
ssh: connect to host 149.165.155.235 port 22: Connection
  refused.
```

evilmike is thwarted, at least for now.


Why was c1 marked as down?
You can return c1 to an idle state by running
sudo scontrol update node=c1 state=resume on the SMS:
[user1@sms ~]$ sudo scontrol update node=c1 state=resume
[user1@sms ~]$ sinfo
PARTITION AVAIL TIMELIMIT NODES STATE NODELIST
normal* up 1-00:00:00 1 idle c[1-2]
We should configure things so that we don't have to manually resume nodes every time we reboot them.

x

More seamless reboots of compute nodes

- Slurm doesn't like it when a node gets rebooted without its knowledge.
- There's an `scontrol reboot` option that's handy to have nodes reboot when system updates occur, but it requires a valid setting for `RebootProgram` in `/etc/slurm/slurm.conf`.
- By default, Slurm and OpenHPC don't ship with a default `RebootProgram`, so let's make one.

x

Adding a valid RebootProgram

```
[user1@smc ~]$ grep -i reboot /etc/slurm/slurm.conf
#RebootProgram=
[user1@smc ~]$ echo 'RebootProgram="/sbin/shutdown -r now"' \
  | sudo tee -a /etc/slurm/slurm.conf
[user1@smc ~]$ grep -i reboot /etc/slurm/slurm.conf
#RebootProgram=
RebootProgram="/sbin/shutdown -r now"
```

x


Informing all nodes of the changes and testing it out
[user1@smn ~]$ sudo scontrol reconfigure
[user1@smn ~]$ sudo scontrol reboot ASAP nextstate=RESUME c1
scontrol reboot will wait for all jobs on a group of nodes to finish before rebooting the nodes.
scontrol reboot ASAP will immediately put the nodes in a DRAIN state, routing all pending jobs to other nodes until the rebooted nodes are returned to service.
scontrol reboot ASAP nextstate=RESUME will set the nodes to accept jobs after the reboot. nextstate=DOWN will lave the nodes in a DOWN state if you need to do more work on them before returning them to service.

x


[user1@smu ~]$ sudo ssh c1 uptime
15:52:27 up 1 min, 0 users, load average: 0.09, 0.06, 0.02
[user1@smu ~]$ sinfo
PARTITION AVAIL TIMELIMIT NODES STATE NODELIST
normal* up 1-00:00:00 1 idle c[1-2]

x

x

Decoupling kernels from the SMS

- If you keep your HPC around for a long period, you might want/need to support different operating systems or releases.
- Maybe you need to run a few nodes on Rocky 8 while keeping the SMS on Rocky 9 (`wwmkchroot` supports that).
- Maybe you need to use a different kernel version for exotic hardware or new features, but don't want to risk the stability of your SMS.
- A simple `wwbootstrap $(uname -r)` won't do that.

x


Decoupling kernels from the SMS
Check wwbootstrap --help:
[user1@sms ~]$ wwbootstrap --help
USAGE: /usr/bin/wwbootstrap [options] kernel_version
...
OPTIONS:
-c, --chroot Look into this chroot directory to find the kernel
...
So if we install a kernel into the ${CHROOT} like any other package, we can bootstrap from it instead of the SMS kernel.

Install a different kernel into the CHROOT, bootstrap it

```
[user1@sms ~]$ sudo yum -y install --installroot=$CHROOT kernel
...
Installing:
 kernel   x86_64 5.14.0-427.24.1.el9_4 ...
...
Complete!
[rocky@sms ~]$ sudo wwbootstrap --chroot=${CHROOT} \
  5.14.0-427.24.1.el9_4.x86_64
Number of drivers included in bootstrap: 880
...
Bootstrap image '5.14.0-427.24.1.el9_4.x86_64' is ready
Done.
```

x

Change the default kernel for nodes, reboot them.

```
[user1@sms ~]$ sudo wwsh provision set '*' \
  --bootstrap=5.14.0-427.24.1.el9_4.x86_64
Are you sure you want to make the following changes to 5
  node(s):

     SET: BOOTSTRAP              = 5.14.0-427.24.1.el9_4.x86_64

Yes/No> y
[user1@sms ~]$ sudo scontrol reboot ASAP nextstate=RESUME \
  c[1-2]
[user1@sms ~]$ sudo pdsh -w 'g[1-2],login' reboot
```

x

x

Semi-stateful node provisioning

(talking about the gparted and filesystem-related pieces here.)

Management of GPU drivers

(installing GPU drivers – mostly rsync'ing a least-common-denominator chroot into a GPU-named chroot, copying the NVIDIA installer into the chroot, mounting /proc and /sys, running the installer, umounting /proc and /sys, and building a second VNFS)

x

Configuration settings for different node types

(have been leading into this a bit with the wwsh file entries, systemd conditions, etc. But here we can also talk about nodes with two drives instead of one, nodes with and without Infiniband, nodes with different provisioning interfaces, etc.)

x

x

Automation for Warewulf3 provisioning

(here we can show some sample Python scripts where we can store node attributes and logic for managing the different VNFSes)

Configuring Slurm policies

Configuring Slurm policies

Can adapt a lot of Mike's CaRCC Emerging Centers talk from a couple years ago for this. Fair share, hard limits on resource consumption, QOSes for limiting number of GPU jobs or similar.

x



This is my note.

- It can contain Markdown
- like this list