



Version: 1.54.4067  
MAC Address: 00:21:74:00:08:19  
Ethernet: 100 Mbps Full Duplex  
Uptime: 18 days 01h 59:19

[Logout](#)[Refresh Now](#)

Every 10 sec ▼

Need help? Online FAQ available at [www.DIGI.com](http://www.DIGI.com)**Statistics**

Radio RSSI:	-38 dBm
Radio Block Error Rate:	0.0 %
Radio Total Packets:	5173552
Radio Failed Packets:	911
Radio Passed Packets:	5172641
Radio Broadcast Packets:	1675960
Radio Unicast Packets:	3497592
Radio Average TX Size:	217 bytes
Radio Average RX Size:	160 bytes

**Device Information**

Device Type:	Access Point
# of Subscriber IDs Issued:	3
Current RF Channel:	12
Connected Subscribers:	2
RF Connected:	Yes
Radio Active:	Active
Product Code:	4
Radio Version:	3
Radio Firmware Release:	075

**Device Settings**

	Description	Value
Device	Password:	<input type="text" value="password"/>
RF	Channel:	<input type="radio"/> Use DIP 3-8 selection: 0 (auto channel select mode) <input checked="" type="radio"/> 12 (overrides the current DIP 3-8 selection)
Network	IP Address:	<input type="text" value="192.168.1.229"/> (###.###)
	Network Mask:	<input type="text" value="255.255.255.0"/> (###.###)
	Default Gateway:	<input type="text" value="192.168.1.1"/> (###.###)
	HTTP Port:	<input type="text" value="8011"/> (decimal 1-65535)

[Apply](#)[Cancel](#)