POWERED BY [mikey:hexoid-sys]
the engineering identity of the owner repository

OWNER REPOSITORY
github.com/mikey-7x

MIKEY-7X

Architect · software developer · hardware developer

Vulkan capabilities on Android phones — graphics and compute drivers, the runtimes above them, and the compatibility layers that carry Windows and Linux applications onto a phone.

TARGET PLATFORM	API OF RECORD	RUNTIME	SILICON LIBRARIES	LICENCE
Snapdragon 8 Gen 3 · Adreno 750	Vulkan	Wine + WoW64 · Box64 · Termux	glibc · bionic	Strict personal & educational

01 THE BRAND

reserved for flagship work only

POWERED BY [mikey:hexoid-sys] is the mark of the owner repository. It is not a label for the account: it is applied to the few projects that carry a complete engineering build — architecture, measurement or checkable results, a reproducible path and an explicit licence. Three repositories carry it today.

APPLIED TO

flagship instruments · compiler and toolchain · biosignal acquisition chain

NOT APPLIED TO

utilities, experiments, studies and archives — including any repository that does not meet all four criteria

01 **Documented architecture**
what the system assumes and what it refuses to do

02 **Measured or checkable results**
the method is published with the number

03 **Reproducible build path**
pinned versions, scripted install, checksums

04 **Explicit limits and licence**
stated in plain language, in the repository

02 POWERED PROJECTS

03 of 33 repositories

01 mikey:hexoid v5.0.0

POWERED BY [mikey:hexoid-sys]

Universal embedded cross-compilation engine for Android (Termux) and Linux. 105 board entries, Arduino CLI 0.35.3 pinned, SDCC for 8051 and STM8, iCE40 synthesis on the OSS CAD Suite, and a library manager — driven from a numbered terminal menu, without an IDE.

Bash + Python · Arduino CLI 0.35.3 · SDCC · iCE40 / OSS CAD Suite

02 298.666 MHz frequency counter

POWERED BY [mikey:hexoid-sys]

STM32F103C8T6 counter on a TIM3:TIM2 32-bit hardware count, asynchronous ETR/8 input, a TI1F cross-check at and below 40 MHz, 100 ms and 250 ms gates, and an SSD1306 display over I2C. Companion exact-step generator and a VHF/UHF transmitter test circuit.

STM32F103C8T6 · STM32duino · SSD1306 I2C · TIM2 ETR / TI1F · 2N2222

03 Project Synapse v1

POWERED BY [mikey:hexoid-sys]

Single-channel EEG and subvocal-EMG acquisition chain: INA128 front-end at G = 501, ADS1115 16-bit conversion at 140 Hz, a framed HC-05 link, Trinx segmentation, DTW matching and CNN-LSTM / CNN-GRU decoders. An experimental study — not a medical device.

INA128 · ADS1115 16-bit · 140 Hz · HC-05 · Trinx / DTW · CNN-LSTM

03 PLATFORM

silicon to application, in six layers

WORKLOADS	Windows · Linux · Android applications
COMPATIBILITY & RUNTIME	Wine + WoW64 · Box64 · Termux · PRoot
GRAPHICS & COMPUTE APIs	Vulkan · OpenGL / GLES · OpenCL
MESA USER SPACE	Turnip · Zink · rusticl
KERNEL & LIBC	Linux DRM / MSM · glibc · bionic
SILICON	Snapdragon 8 Gen 3 · Adreno 750 · Hexagon NPU

04 METHOD

how the work is done

ARCHITECTURE
which layer owns the job, what each layer may assume, and where it will fail

DRIVERS
Vulkan, OpenGL and OpenCL paths; correctness before speed, validation on the device

HARDWARE
silicon limits, board bring-up, power and thermal budget — calculated, not guessed

EVIDENCE
measured numbers, checksums, and a self-check that runs on every push

CONTACT

EMAIL	chauhanyogesh9825@gmail.com
GITHUB	github.com/mikey-7x
YOUTUBE	youtube.com/@mikey-7x
BLOG	rtod-yv8.blogspot.com/?m=1
LINKEDIN	linkedin.com/in/yogesh-r-chauhan-780005417

LICENCE

Personal and educational use with attribution. Commercial, industrial and clinical use require a separate written licence. Technical statements on this sheet describe active work; they are not benchmark results or certifications.

POWERED BY [mikey:hexoid-sys]

Copyright © 2026 mikey-7x.
All rights reserved.

Created by mikey-7x