Production AI Engineering

A Handbook for Building Reliable LLM Systems

Michael Long, surfaces.systems

August 31, 2026 · Version 1.2

Engineering the whole system

Production AI engineering works as a system. This handbook lays out an operating model that connects the techniques instead of treating them as isolated fixes. The central idea is simple:

> *A model can propose an answer or action. The surrounding system decides whether and how it should proceed, and remains responsible for the outcome.*

Optimize for a **successful, policy-compliant user outcome that meets service-level objectives (SLOs) for latency and cost**. A prompt or model call is only one part of that outcome.

NAVIGATION

Contents

01	Build the System Around the Model	1	02	Treat Context as a Budget	5
03	Prefill and Decode Are Different Jobs	9	04	Choose the Optimization That Fits	14
05	Turn Model Output into a Contract	18	06	Put Clear Limits on Agents	23
07	Keep Retrieval Grounded	27	08	Make Evals the Release Gate	32
09	Trace the Whole User Journey	36	10	Build Safety into the Architecture	40
11	Choose What to Change	44	12	Design for Production Failure	47
A	Notes and Sources	52	I	Index of Terms	59
C	Changelog	63			

CHAPTER 01

Build the System Around the Model

A production AI system succeeds when the full workflow delivers the right outcome, follows policy, and stays inside its latency and cost targets.



1.1 The full system



Each layer has a specific job:

LAYER	PRIMARY RESPONSIBILITY	TYPICAL FAILURE
Product contract	Define success, SLOs, risk, and degraded behavior	Optimizing a proxy that users do not value
Harness	Orchestrate state, tools, retries, budgets, and termination	Runaway loops or duplicate side effects
Context	Select the smallest high-signal authorized state for this step	Context rot, stale facts, or contamination
Retrieval and memory	Supply current, attributable external knowledge	Irrelevant, stale, or unauthorized evidence
Model and serving	Produce useful tokens efficiently	Queueing, KV pressure, or quality loss
Validation and policy	Turn probabilistic proposals into safe actions	Valid JSON with invalid business meaning
Evals and observability	Detect regressions and explain production behavior	Silent quality, cost, or safety drift

SOURCES [AGT-01] [CTX-01] [OBS-01]
Author synthesis: the cited sources inform this layered operating model.

1.2 Harness engineering, not just prompt engineering

Prompt engineering handles the wording and structure of instructions. Context engineering selects and maintains every token supplied for each model step. Harness engineering runs the software system around the model.

DISCIPLINE	CONTROLS	IT DOES NOT CONTROL BY ITSELF
Prompt engineering	Instruction clarity, examples, response guidance	State, permissions, retries, side effects
Context engineering	Instructions, history, retrieved evidence, tool definitions, summaries, token allocation	Execution safety or end-to-end termination
Harness engineering	State machine, routing, tools, validators, budgets, caches, telemetry, recovery	The model's intrinsic capability ceiling

A production harness needs to own:

1. **Bind every run.**
    1.1. Request identity, tenant, authorization, and policy version.
    1.2. Prompt, tool, schema, model, and retrieval-index versions.
2. **Control execution.**
    2.1. Deterministic context assembly and compaction.
    2.2. Model routing and fallback compatibility.
    2.3. Parse, schema, semantic, and policy validation.
    2.4. Retry classification and idempotency.
3. **Bound and account for outcomes.**
    3.1. Time, token, tool, turn, cost, and risk budgets.
    3.2. Success, refusal, blocked, degraded, and failed terminal states.
    3.3. Traces, outcome metrics, and cost attribution.

Enforce any rule about safety, money, permissions, or termination in code. A sentence in a system prompt can steer the model, but it cannot serve as a security boundary.

SOURCES [AGT-01] [TOOL-01] [AUTH-01]

Author synthesis: the taxonomy separates prompt, context, and harness responsibilities.

CHAPTER 02

Treat Context as a Budget

Context is finite. Choose the smallest set of instructions, state, evidence, and tools the model needs for the current step.



2.1 Context engineering, not long prompts

Treat context as finite working memory with diminishing marginal value. Adding more can increase prefill cost and time while drawing effective attention away from the material that matters. A long context window does not justify loading everything into it.

Build the context in this order:

1. **Invariant contract:** role, hard policies, output/tool protocol, and current schema version.
2. **Current task:** the user's latest intent and explicit constraints.
3. **Authorized state:** only the tenant, resource, and conversation state needed now.
4. **Fresh evidence:** retrieved passages with source, version, timestamp, and access metadata.
5. **Available actions:** only relevant, clearly distinct tool contracts.
6. **Useful history:** compact decisions and unresolved state, not an unfiltered transcript.
7. **Examples:** only when they improve the target eval more than the tokens and anchoring risk cost.

Practical rules:

- Optimize **signal per token**, not context-window utilization.
- Retrieve details just in time. Keep durable decisions in explicit state.
- Label and separate untrusted content from instructions, but do not mistake roles, delimiters, or typed fields for isolation. Enforce a deterministic source-to-sink policy so data derived from an untrusted source cannot authorize actions, expand permissions, or select new egress destinations.
- Keep provenance attached through summarization. A summary without its source and version creates a future stale-fact bug.
- Use structured state instead of repeatedly asking the model to infer state from prose.
- Give tools concise, non-overlapping names and descriptions. Expose only the tools relevant to the current step.
- Version and hash the context manifest so the team can reproduce a bad result.
- Test context ordering and truncation. Models can use relevant information less reliably when it is buried in a long input, a behavior documented by the Lost in the Middle[CTX-02] study.

Treat a token budget as a policy, not a universal percentage. One practical version looks like this:

fixed contract	hard cap; cache-friendly prefix
task and state	enough to make the current decision
retrieved evidence	top-ranked, deduplicated, attributable
tool definitions	relevant tools only
working history	compacted decisions and open questions
output reserve	protected before adding more input

When the budget gets tight, remove redundant and low-confidence material first. Compress authoritative instructions or evidence only after those cuts.

SOURCES [CTX-01] [CTX-02]

2.2 Four caches that must not be confused

CACHE	KEY AND VALUE	MAIN BENEFIT	MAIN RISK	INVALIDATION/ISOLATION
Exact response cache	Exact normalized request to completed response	Avoids the entire workflow	Stale response if hidden state changed	Include every response-affecting version and authorization dimension
Prompt/prefix cache	Exact rendered-token prefix to reusable prefill work	Can lower TTFT and billed input cost when read/write pricing and reuse frequency are favorable	Small serialization changes destroy hits; provider write pricing and retention implications	Stable prefix first; model/prompt scoped; follow provider data controls
Semantic response cache	Embedding-near request to prior response	Captures paraphrases and reduces full calls	False positive can return a plausible but wrong, stale, or unauthorized answer	Tenant/principal, state, model, prompt, corpus, policy, locale, and freshness scoped
Runtime KV cache	Per-layer attention keys and values for an active sequence	Avoids recomputing tokens already processed within that sequence	GPU memory exhaustion and cross-request leakage if ownership is mishandled	Request ownership, active block pinning, preemption, reclamation, and quotas

Prompt caching and semantic caching do different work:

- **Prompt/prefix caching is exact and reuses prefill work.** It skips recomputation for an identical rendered prefix, while still running prefill for the uncached suffix and a full decode. Put stable system instructions, examples, and tool definitions first. Put user-specific material later. Small differences in tokenization, message order, tool serialization, or timestamps can destroy a hit. The cache can reduce TTFT and billed input cost only when provider-specific read/write pricing and reuse frequency make the tradeoff worthwhile.
- **Semantic caching is approximate and reuses an answer.** It decides whether a new request is close enough to an old one to return the old answer. The reuse decision acts as both a quality classifier and a security classifier. The critical metric is **false-hit rate by risk slice**, not hit rate alone.

Use semantic caching only when two paraphrased requests should receive the same answer. Avoid it, or require verification, for personalized, permission-sensitive, rapidly changing, transactional, high-stakes, and multi-turn-dependent answers. Azure's own semantic-cache policy warns that similarity hits can be incorrect, outdated, or unsafe; see the official policy reference[CACHE-02].

A defensible application cache key or namespace usually needs:

REQUEST SCOPE	tenant + principal/ACL scope + task type + normalized state
RUNTIME CONTRACT	model snapshot + prompt version + tool-contract version + output-schema version
POLICY	safety-policy version
RETRIEVAL CONTEXT	retrieval corpus/index version + locale + freshness window

Track cache and token hit rates; false-hit, stale-hit, and eviction rates; cache age; latency and cost saved; and cross-scope rejection count. Never share private semantic responses globally based on embedding similarity.

SOURCES [CACHE-01] [CACHE-02] [SERV-01]

Author synthesis: the four caches are grouped by what they reuse and how they fail.

CHAPTER 03

Prefill and Decode Are Different Jobs

Prefill and decode use the hardware differently. The serving plan has to account for both.



3.1 Prefill and decode optimize differently

Autoregressive inference has two phases that place different demands on the system.

PROPERTY	PREFILL	DECODE
Work	Process all input tokens and populate KV state	Generate one next token per active sequence per step
Parallelism	High within the prompt; large matrix operations	Sequential across output positions; smaller per-step operations
Common bottleneck	Usually compute-bound once prompt length or batch reaches accelerator saturation	Usually weight/KV-bandwidth-bound at low-to-moderate batch; can become compute-bound at high batch
User metric	Prefill contributes to TTFT, which also includes queueing, retrieval, cache, and network time	Decode cadence contributes to mean TPOT and the distribution of inter-token latencies and stalls
Helpful techniques	Safe context reduction, prefix cache, efficient kernels, prefill batching, chunking, or disaggregation	Continuous batching, efficient kernels, quantization, speculative decoding

Break the latency budget into its actual components:

End-to-end latency	= SUM OF
BEFORE GENERATION	queue + cache lookup + retrieval + rerank
GENERATION AND EXECUTION	prefill + decode + tools + validation and retries

Track p50, p95, and p99 for end-to-end latency, queue time, TTFT, TPOT/ITL, and tool latency. A low average can still hide an unusable tail.

Chunked prefill can reduce interference with active decodes and improve tail inter-token latency, but it can also increase TTFT for the long prompt being split. Use prefill/decode disaggregation only when its SLO benefit outweighs the cost of duplicated model weights, KV transfer, interconnect, routing, and operations.

SOURCES [SERV-03] [SERV-04] [SERV-05]

3.2 KV cache management and memory pressure

For a conventional transformer, use this approximation for KV footprint per sequence:

KV bytes	APPROXIMATELY THE PRODUCT OF
2 keys and values × layers × tokens × KV heads × head dimension × bytes per element	

Grouped-query or multi-query attention reduces `KV_heads`, which can dramatically reduce the footprint. For example, 80 layers, 8 KV heads, head dimension 128, and BF16 state use about 320 KiB per token, or roughly 10 GiB for a 32K-token sequence. Exact layouts and engine overhead vary. The scaling behavior does not: tokens, concurrency, and precision multiply.

Watch for memory pressure in:

- rising KV utilization and allocation failures;
- evictions, preemption, recomputation, or CPU offload;
- falling prefix-cache hit rate under churn;
- queue growth even when compute looks underutilized;
- throughput cliffs and out-of-memory failures on long-tail prompts;
- one tenant's long contexts starving other tenants.

Apply the controls in this order:

1. Enforce admission control and explicit maximum input/output lengths.
2. Reserve memory for active decodes and protect latency-critical traffic classes.
3. Use paged/block allocation to reduce fragmentation. Prefix sharing is a separate, explicitly keyed capability layered on top.
4. Use per-tenant concurrency and KV quotas.
5. Where prefix caching is enabled, reuse exact full-prefix blocks with ownership, refcounts, and copy-on-write semantics.
6. Evict only refcount-zero reusable blocks. Reclaim active KV by preempting whole sequences and explicitly choosing recomputation or offload; do not apply eviction only by request age without workload evidence.
7. Evaluate KV quantization or offload on long-context quality and tail latency before enabling it.
8. Shed or degrade load before allowing a node-wide OOM.

The PagedAttention paper[SERV-01] applies virtual-memory-like block management to KV state, reducing allocation waste and enabling sharing. Paging manages memory more efficiently, but the underlying KV capacity limit remains.

For bursty multi-tenant traffic, evaluate a reservation policy against real prompt-length, output-length, and arrival traces instead of reserving each request's maximum possible KV footprint. A robust policy can admit more useful work by protecting against plausible distribution shifts while keeping an explicit overload path. Cheng et al.'s robust KV-cache reservation study[SERV-06] provides one trace-driven formulation; it is a planning method, not a substitute for per-tenant quotas, active-decode reserves, or load shedding.

SOURCES [SERV-01] [SERV-04] [SERV-06]

The KV footprint example follows directly from the model architecture.

3.3 Continuous batching, paged attention, and goodput

Static batching waits for a fixed group of requests. Continuous, or iteration-level, batching releases completed sequences at each engine iteration and may admit queued work into the capacity they free, subject to token, KV, deadline, and fairness limits. The approach removes static-batch head-of-line blocking, although requests can still queue. The Orca paper[SERV-02] established iteration-level scheduling as a core serving technique.

Large prefills can still stall active decodes. Chunked prefill splits prompt processing into schedulable pieces and interleaves those pieces with decode work. The tradeoff is lower decode interference and potentially longer TTFT for the split request. Sarathi-Serve[SERV-03] analyzes this prefill/decode interference and stall-free scheduling.

The scheduler needs controls for:

- maximum batched tokens and active sequences;
- prefill chunk size and prefill/decode priority;
- request class, deadline, and fairness policy;
- maximum model length and output reservation;
- prefix locality and cache-aware routing;
- preemption and load-shedding policy.

Raw tokens per second do not tell you whether the service works for users. Optimize **goodput**: the maximum arrival rate per provisioned GPU or resource at which the required fraction of requests satisfies both TTFT and TPOT/ITL SLOs plus the application-

quality gate. A larger batch can increase throughput while pushing interactive latency past an acceptable limit.

For multi-stage agent workflows, measure task-level completion time alongside request goodput and prefix-hit rate. Evaluate dependency and critical-path progress, prefix residency, transition and preemption cost, and starvation on real traces. Optimizing prefix locality or the progress of one stage in isolation can make the complete workflow slower.

The current vLLM documentation[SERV-04] is a useful implementation reference for PagedAttention, continuous batching, prefix caching, chunked prefill, quantization, and speculative decoding. Engine defaults are starting points. Tune them against production prompt-length and output-length distributions.

SOURCES [SERV-02] [SERV-03] [SERV-04] [SERV-07]

CHAPTER 04

Choose the Optimization That Fits

Speculative decoding, quantization, and distillation solve different problems. Pick the one that matches the bottleneck and verify the quality tradeoff.



4.1 Speculative decoding, quantization, and distillation

Speculative decoding, quantization, and distillation change different parts of the inference stack and solve different bottlenecks.

TECHNIQUE	CHANGES	BEST FIT	MAIN TRADEOFF
Speculative decoding	A draft process proposes tokens; the target verifies several in parallel	Decode-bound, low-to-moderate batch workloads with high draft acceptance	Extra draft compute and memory can erase gains when acceptance is low
Quantization	Represents weights and sometimes activations/KV with fewer bits	Memory/bandwidth-constrained inference with supported kernels	Calibration and numerical error can cause task-specific tail regressions
Distillation	Trains a smaller student to imitate a larger teacher	Stable, narrow, high-volume tasks with governed training data and clear evals	Up-front teacher-data/training cost; broad and long-tail capabilities or teacher biases can transfer or regress

When the rejection sampler and target-model sampling semantics are implemented correctly, speculative decoding preserves the target distribution. Use it to reduce latency, not to approximate an answer. Floating-point or batching nondeterminism still prevents any guarantee of byte-identical runs. Benchmark acceptance, draft and verification cost, TPOT, and SLO goodput at production concurrency. Low acceptance or saturated compute can make the system slower. See Leviathan et al.[SPEC-01].

Distillation changes the deployed model and usually changes its behavior. Distillation can greatly lower steady-state cost, but the target workflow first needs to be stable enough for teacher data and evals to represent production. Hinton, Vinyals, and Dean[DIST-01] describe the foundational method.

SOURCES [SPEC-01] [QUANT-02] [DIST-01]

Author synthesis: the comparison maps each technique to the bottleneck it changes.

4.2 Quantization: formats, methods, and quality risk

AWQ and GPTQ describe quantization methods. Numeric formats are a separate choice. Always spell out the precision tuple: `W8A8`, `W8A16`, `W4A16`, or `KV8`, for example. `INT8` and `INT4` leave too much unspecified on their own.

Weight storage is approximately `parameters × bits / 8 + scales + zero-points + unquantized modules`. W4A16 reduces weight storage, but it does not shrink activations or KV. Calling a model "4-bit" therefore does not imply 4× lower total VRAM. Whether smaller storage lowers latency depends on the actual kernel and hardware.

CHOICE	WHAT IT USUALLY MEANS	WHEN IT IS ATTRACTIVE	WATCH FOR
INT8	Integer 8-bit weights and possibly activations	Broad hardware support; safer first step from FP16/BF16	Activation outliers, calibration mismatch, unsupported fast paths
FP8	8-bit floating point, commonly E4M3/E5M2 with scaling	Newer accelerators; training or W8A8-style inference where dynamic range matters	Hardware dependence, scale management, accumulation precision
INT4	Often W4A16 weight-only, though W4A8/W4A4 also exist	Model fit and bandwidth-bound decode; native low-activation kernels may also help prefill or high batch	Greater quality risk, scale/dequantization overhead, and runtime- and hardware-dependent speedups
AWQ	Activation-aware weight-only post-training quantization	Protecting salient weight channels without retraining	Representative activation calibration and kernel compatibility
GPTQ	One-shot weight quantization using approximate second-order information	Accurate 3/4-bit compression of supported decoder models	Calibration set, group size, layer sensitivity, conversion/runtime support

Primary references: FP8 formats[QUANT-01], SmoothQuant for W8A8[QUANT-02], AWQ[QUANT-03], and GPTQ[QUANT-04].

Quality risk generally rises below 4-bit, in smaller models, on harder reasoning slices, with unrepresentative calibration, and when activation or KV outliers are aggressively quantized. The risk pattern is empirical, not guaranteed. Specific risks include:

- calibration data does not match production languages, domains, lengths, or modalities;
- the task depends on small logit margins, exact numbers, code, rare tokens, or precise tool arguments;
- activation or KV outliers are aggressively quantized;
- long-context, multilingual, rare-token, safety, or tool-use behavior is more sensitive than the aggregate benchmark suggests.

Short-context or aggregate-only evals can hide regressions. Missing native kernels can erase the performance gain even when quality holds. Benchmark the exact checkpoint, packing, runtime, hardware, batch shape, and parallelism plan.

Run every quantized candidate through the same golden and adversarial suite as the baseline. Include exact structured output, function selection and arguments, safety refusals, multilingual slices, long context, and p95/p99 latency. Measure end-to-end performance. Model file size alone proves nothing.

SOURCES [QUANT-01] [QUANT-02] [QUANT-03] [QUANT-04] [SERV-04]

CHAPTER 05

Turn Model Output into a Contract

Schemas make output parseable. Authorization, validation, idempotency, and effect checks make it safe to use.



5.1 Structured outputs: syntax is only the first gate

Constrained decoding and provider structured-output features can greatly improve syntactic conformance. Syntactic conformance does not establish whether the values are true, authorized, internally consistent, current, or safe to execute.

Use this pipeline:



Build the schema so failures are explicit:

- Version the schema and reject unknown versions.
- Use required fields, enums, ranges, string formats, and `additionalProperties: false` where appropriate.
- Make invalid states hard to represent with discriminated unions rather than nullable field combinations.
- Distinguish `null`, omitted, unknown, and refused.
- Validate dates, identifiers, money, units, and cross-field relationships in deterministic code.
- Store hashes, versioned references, validation errors, and repair lineage by default. Retain raw candidates only under an explicit privacy policy with minimization or redaction, encryption, restricted access, and short retention.
- Treat schemas from providers, tool servers, or user-controlled sources as untrusted input. Do not automatically resolve network `$ref` targets. If remote resolution is explicitly enabled, allowlist hosts; block loopback, link-local, and private ranges; cap bytes and time; log every fetch; and reject unresolved references. Bound schema depth, subschema count, and validation time so composition keywords cannot turn validation into an SSRF or denial-of-service path.

Keep repair bounded:

1. Classify transport/status, refusal, incomplete/truncated, parse, schema, semantic, authorization, and policy failures separately.
2. Repair only bounded syntax or shape failures when the result is non-consequential or read-only. Never use repair to override a refusal, invent semantically missing values, or make a mutation executable.
3. Revalidate the complete normalized payload from the beginning.
4. For consequential payloads, regenerate from trusted inputs, request clarification, require review, or fail safely. Alternate models must satisfy the same data policy and contract; deterministic defaults must be explicitly product-defined and surfaced to the user.

Do not create an unbounded "please fix the JSON" loop. Track first-pass validity and final validity separately. Otherwise repair can hide a model regression. See the OpenAI structured output guide[OUT-01] and the JSON Schema documentation[OUT-02].

SOURCES [OUT-01] [OUT-02] [MCP-03]

Author synthesis: repair policy is separated from the rules for consequential actions.

5.2 Reliable function and tool calling

Treat a tool call as an untrusted proposal crossing from a probabilistic system into deterministic software.

A strong tool contract includes:

1. one clear purpose and a distinct, namespaced name;
2. typed, unambiguous arguments such as `customer_id`, not `customer`;
3. a strict input schema and documented semantic invariants;
4. explicit read/write, destructive, network, and open-world declarations for UX and discovery; make security decisions from a trusted server-side policy registry, not annotations supplied by a dynamic or untrusted tool server;
5. bounded pagination and concise high-signal output;
6. stable error codes, `retryable` status, and a typed result envelope;
7. timeouts, rate limits, authorization requirements, and audit semantics;
8. a contract version and compatibility policy.

The harness then enforces the contract:

1. Reject unknown tool names; never dynamically dispatch a hallucinated string.
2. Parse and validate all arguments.
3. Resolve identity and authorize the exact resource and action server-side.
4. Create or accept one idempotency key per logical mutation before first dispatch. Scope it to tenant, actor, and operation; persist it across retries, resumes, handoffs, and model/provider fallbacks; reject reuse with a different normalized request fingerprint.
5. Require a single-use, expiring approval for consequential actions, bound to the normalized action, actor, resource, destination, disclosed data, and state version. Reauthorize immediately before execution; any material change requires new approval.
6. Execute with least-privilege, short-lived credentials.
7. Validate tool output and treat returned text as untrusted data, not new instructions.
8. Retry only failures known to be safe, using the same idempotency key.
9. Record the proposed action, policy decision, execution result, and resulting state.

A useful response envelope is:

```
{
  "ok": false,
  "code": "VERSION_CONFLICT",
  "retryable": false,
  "recovery": "REFRESH_STATE_AND_REPLAN",
  "data": null,
  "state_version": "42"
}
```

Design for at-least-once delivery. Control it with idempotent effects, uniqueness constraints, or compare-and-swap state. Atomically record the idempotency key, normalized request fingerprint, side effect, and resulting receipt/state.

When a stable, repeated procedure is narrow enough to specify and test, compile it into a versioned deterministic tool instead of making the model re-reason through every mechanical step. Keep judgment, exception handling, and stop decisions explicit. In a production alarm-triage study, Kujanpaa et al. compiled repeated SOP steps into tools [TOOL-04] and reported lower median latency and fewer errors in that workflow; treat the result as domain evidence, not a universal performance guarantee.

A network timeout can leave the execution status unknown. Reconcile through the idempotency receipt or authoritative external state before retrying or changing routes. The HTTP specification explains why automatic retry is safe only when the semantics are idempotent or the client knows the original action was not applied; see RFC 9110 [TOOL-03].

Evaluate tool and protocol behavior directly. Test correct selection, correct non-selection, argument validity, authorization denial, duplicate delivery, timeout-after-commit, partial failure, hostile tool output, protocol-version negotiation, and session-state assumptions.

Anthropic's tool design guidance[TOOL-01] is a useful primary reference.

Give every agent and workload a distinct identity; never lend it a human credential or allow it to impersonate the delegating user. Bind short-lived, audience-restricted authority to the operating principal, attenuate it at every delegation, and let the least-authorized hop bound the chain.

Protocol migrations are architecture migrations. MCP 2026-07-28 removed protocol sessions, `Mcp-Session-Id`, and the initialization handshake. A connection or stdio process is not a conversation: carry protocol version and capabilities on every request, discover server support before selection, and pass cross-call state through explicit handles. Treat `clientInfo` and `serverInfo` as self-reported diagnostics, never authenticated identity or policy input.

Model protocol results as a state machine. `resultType: "input_required"` is nonterminal; preserve the logical operation, policy decision, approval scope, and budget across the next round. If a response stream breaks, issue a new protocol request ID, but preserve the application idempotency key and reconcile external state before repeating a mutation. Pin the protocol and SDK, test mixed-version clients and servers, and roll through a compatibility window.

Treat protocol deprecations as owned migration work, not optional cleanup. The MCP 2026-07-28 changelog[MCP-02] marks Roots, Sampling, Logging, HTTP+SSE, the `"thisServer"` and `"allServers"` `includeContext` values, and OAuth Dynamic Client Registration as Deprecated. Do not add new dependencies on them. Inventory current use, assign an owner and removal date, and test the named replacement before the compatibility window closes.

SOURCES [TOOL-01] [TOOL-02] [TOOL-03] [TOOL-04] [MCP-01] [MCP-02] [MCP-03] [AUTH-01] [AUTH-02] [AUTH-03]

Author synthesis: approval, idempotency, and execution receipts form one tool-safety contract.

CHAPTER 06

Put Clear Limits on Agents

Agents need limits you can enforce: budgets, stop conditions, compatible fallbacks, and explicit terminal states.



6.1 Agent guardrails, budgets, and termination

An agent is a state machine whose next transition is proposed by a model. Apply guardrails at every transition. Final-text checks alone are not enough.

Enforce these budgets outside the model:

BUDGET	EXAMPLE CONTROL
Turns	Maximum model decisions per run
Tools	Total calls plus lower limits for writes or expensive tools
Tokens	Input, output, reasoning, and cumulative context ceilings
Time	Wall-clock deadline and per-step timeout
Cost	Hard run limit and softer escalation threshold
Retries	Per operation, per failure class, and total
Risk	Maximum unapproved action class or data scope
Concurrency/fan-out	Maximum in-flight model, tool, and subagent work; reserve budget before dispatch
Mutations	Separate count, value, and data-scope caps for writes and destructive actions
No progress	Stop after repeated equivalent state/action cycles

Budget counters need to be hierarchical, atomic, and persistent across retries, resumes, handoffs, fallbacks, and subagents. A retry or alternate route must not reset the run's deadline, cost, risk, or mutation budget.

Give every run explicit terminal conditions:

- success predicate verified against external state;
- user cancellation, after stopping new work and reconciling any already-dispatched mutation whose commit status is unknown;
- policy or authorization denial;
- dependency unavailable or irrecoverably blocked;
- budget exhausted;
- repeated state, repeated action, or no measurable progress;
- insufficient evidence under an externally measured sufficiency check, or a calibrated product score that requires abstention; never use the model's self-reported confidence alone.

Broken or impossible tasks must terminate safely; persistence or additional reasoning may not unlock wider tools, egress, or credentials. Define severity triggers for boundary circumvention and unauthorized cross-agent coordination, provide a reliable fleet or

workload kill path, name the authority to pause, contain, restart, and restore, and fail closed when a severe alert cannot be cleared.

Treat `awaiting_input` and `awaiting_approval` as persisted, resumable interrupts rather than success or failure terminals. Keep their deadlines and reserved budgets explicit.

The model's claim that it finished does not count as the success predicate. Verify the outcome: the record exists, tests pass, the message was sent once, or the cited evidence supports the answer.

When the run ends, return a typed state such as `succeeded`, `partial`, `blocked`, `refused`, `cancelled`, `budget_exhausted`, or `failed`. Include the completed work and a safe next action. A typed result makes degraded UX and operations much clearer than a generic error.

SOURCES [AGT-01] [EVAL-02] [AUTH-02] [EVAL-05] [EVAL-06] [ORIG-05]

Author synthesis: agent limits are organized as budgets and explicit terminal states.

6.2 Model routing and degraded mode

Route against measured task requirements. Provider reputation or prompt length alone is not enough. Useful routing features include:

- task class and required capability;
- risk and consequence of error;
- modality, context length, language, and tool requirements;
- latency deadline and cost ceiling;
- tenant policy and data residency;
- current provider health and rate limits;
- router confidence and out-of-distribution detection.

Maintain a compatibility matrix for every route: exact model snapshot or negotiated protocol version; provider API, client SDK, and serving-runtime versions; lifecycle state and retirement date; supported request parameters and turn rules; tool protocol; JSON Schema support; context and output limits; refusal semantics; modality; processing geography and data policy; and tested quality slices. Treat aliases, defaults, and wrappers as mutable. Google, Anthropic, OpenAI, and AWS publish changes on different schedules, and platform-specific retirement dates can differ from a model creator's dates. A fallback that cannot honor the same contract puts the product in a different mode.

Treat provider SDK upgrades as production migrations. Diff request headers and response types, exercise every mutating method against disposable state, and canary the pinned upgrade before rollout.

Choose the fallback based on the failure class. Never route around a safety refusal, an authorization or policy denial, or a semantic validation failure. After a timeout that may have committed a mutation, reconcile through the idempotency receipt before retrying or changing routes. Every attempt shares one deadline and retry budget. Use circuit breakers to prevent retry and fallback storms.

A safe chain might be:



In degraded mode, tell the user exactly what changed: unavailable capability, reduced freshness, partial scope, read-only behavior, or delayed completion. Do not silently swap to a materially weaker model and present the output as equivalent.

Evaluate the router directly: route accuracy, unnecessary escalation, unsafe down-routing, fallback success, quality by route, added latency, and cost per successful task. Shadow new routing policies only on eligible, authorized traffic. Disable all side effects, redact where possible, and never send data to a provider or region outside the request's approved residency and retention policy.

SOURCES [OPT-01] [SERV-05] [MCP-01] [MOD-01] [MOD-02] [MOD-03] [MOD-04]
Author synthesis: routing decisions are tied to the user's degraded-mode experience.

CHAPTER 07

Keep Retrieval Grounded

Retrieval is useful only when the evidence is authorized, current, attributable, and relevant to the claim.

7.1 RAG architecture

RAG gives a generator access to an external retrieval system. If ingestion loses evidence or retrieval misses it, the generator cannot recover it.



Ingestion and chunking

- Build chunks around retrievable answer units: sections, procedures, clauses, table regions, code symbols, or conversation turns.
- Preserve title, hierarchy, source ID, version, timestamps, page/line anchors, and ACL metadata.
- Keep tables, lists, and code structures intact where splitting destroys meaning.
- Use overlap only to preserve boundary meaning; indiscriminate overlap increases duplicate retrieval and context waste.
- Consider small child chunks for recall and larger parent sections for generation context.
- Build versioned tombstones and deletion propagation. A deleted source remaining in the vector index is a security and freshness bug.

Embeddings

- Benchmark embedding models on the product's actual queries, languages, jargon, document types, and relevance units. No model dominates every retrieval task.
- Use a pinned model, version, preprocessing configuration, and distance function for both document and query vectors.

- Treat an embedding change as an index migration. Build and evaluate a side-by-side index, then switch atomically or through a measured rollout. Do not mix incomparable vector spaces.
- Dimension, precision, and index parameters trade storage and query cost against recall. Measure the full retrieval system rather than ranking embedding models by a generic leaderboard alone.

Retrieval

- Lexical retrieval is strong for exact names, identifiers, acronyms, error codes, and rare terms.
- Dense embeddings are strong for paraphrase and conceptual similarity.
- Hybrid retrieval combines complementary candidate sets. Reciprocal rank fusion is a practical starting point when raw scores are not directly comparable; see the Elastic hybrid-search guide[RAG-02].
- Enforce tenant and document ACL constraints inside the source query and before or during vector candidate generation and reranking. Post-filtering a global top-k result is not an isolation boundary and risks leakage through scores, logs, caches, or context.
- Treat retrieval queries, embeddings, candidate identities, scores, access patterns, and selected results as sensitive data. ACLs control what may be returned; they do not hide these artifacts from the retrieval operator. When that operator is outside the trust boundary, define the adversary and validate the security, latency, and bandwidth tradeoffs of the private-retrieval design.
- Rerank a wider candidate set with a more precise model, then pack a smaller nonredundant evidence set.
- Tune `k`, fusion, reranking, and context packing against end-to-end evals instead of intuition.

Freshness

Track `source_version`, `indexed_at`, validity interval, and deletion state. Measure source-to-index lag and define a freshness SLO. Use change-data capture, event-driven reindexing, or scheduled reconciliation based on the source. Invalidate retrieval and semantic caches with corpus/index versions, not only TTLs.

The foundational RAG paper[RAG-01] emphasizes non-parametric memory, provenance, and updatable knowledge. A production system also needs authorization, freshness, hybrid retrieval, reranking, context packing, and the operations that support them.

SOURCES [RAG-01] [RAG-02] [RAG-03] [RETR-06] [TEN-01]

7.2 Retrieval and answer evals

Evaluate retrieval separately from generation. A correct answer can hide a retrieval miss when the model already knew the fact. Perfect evidence can still produce a bad answer.

METRIC	DEFINITION OR QUESTION	DIAGNOSES
Recall@k	Relevant items retrieved in top k / all known relevant items	Whether evidence is being missed
Precision@k	Relevant items in top k / k	Noise and context waste
MRR	Mean over queries of 1 / rank of the first relevant result, using 0 when none is retrieved	How early one decisive item appears
nDCG@k	Rank-discounted graded relevance, normalized to the ideal ranking	Ordering when relevance is graded
Context relevance	Does each supplied passage help answer this query?	Bad fusion, excessive k, duplicate chunks
Answer correctness	Is the final answer correct against the task reference/outcome?	End-to-end quality
Claim support rate	Supported atomic answer claims / all answer claims	Hallucination beyond supplied context; does not establish evidence truth, freshness, authority, or answer correctness
Citation-pair precision	Citation-claim pairs entailed by the cited span / all citation-claim pairs	Decorative, misplaced, or non-supporting citations
Citation completeness	Citation-required claims with complete supporting evidence / all claims requiring citation under product policy	Unsupported answer coverage
Attribution accuracy	Does the source identity and anchor match the actual evidence?	Wrong-source or wrong-span citations
Selective risk and coverage	Error rate among answered cases, reported with the fraction of cases answered	Quality/abstention tradeoff
Abstention precision and recall	Whether abstentions correctly identify unanswerable, conflicting, stale, or unauthorized cases	Over- and under-abstention

Define the relevance unit for every metric: document, deduplicated source, chunk, claim, or exact evidence span. Overlapping chunks can inflate item precision and recall, so report deduplicated source recall and claim coverage as well. When relevance judgments are incomplete, Recall@k and Precision@k are estimates against the judged pool. They do not represent corpus-wide truth.

A useful golden record contains:

REQUEST CONTEXT	query • user/tenant/ACL identity • time snapshot
EXPECTED OUTCOME	expected answer or outcome • answerable/unanswerable label
EVIDENCE AND ATTRIBUTION	relevant source IDs • exact evidence spans • allowed and forbidden sources • expected citation mapping
COVERAGE AND RISK	important slice labels • risk class

Test typo, acronym, exact-identifier, paraphrase, multi-hop, conflicting-source, stale-source, newly updated, deleted, unauthorized, poisoned-document, no-answer, and long-tail queries.

Use BEIR[RETR-01] for heterogeneous retrieval evaluation, RAGAS[RETR-04] for component-level RAG evaluation, and ALCE[RETR-05] for citation quality. Treat every retrieval or evaluator score as decision-specific evidence: validate it against the comparison, training choice, system selection, downstream prediction, or filtering decision it will drive, and test whether evaluator conclusions remain stable across the relevant slices. A metric that ranks retrievers well may still fail to predict answer quality or justify a different generator. Automated metrics surface problems; calibrated human review remains part of the evaluation.

For iterative search agents, evaluate retrieval in trajectory context. Condition the retriever and its evaluation on the original task and prior search interactions, not only the latest sub-query. Measure marginal evidence gain, duplicate resurfacing, and task-level outcome; a locally relevant result can still waste a step or steer the investigation away from the remaining evidence gap.

SOURCES [RETR-01] [RETR-02] [RETR-03] [RETR-04] [RETR-05] [RETR-07] [RETR-09]

CHAPTER 08

Make Evals the Release Gate

Golden sets, adversarial tests, calibrated judges, and human review determine whether a release can ship.



8.1 Evals as the release contract

Build the evals before you optimize. Without them, every caching, routing, quantization, prompt, retrieval, or model change can quietly exchange quality for speed or cost.

Use several layers together:

1. **Deterministic unit tests:** parsers, schemas, invariants, ACL filters, idempotency, budgets, termination, and cost math.
2. **Component evals:** retrieval, reranking, routing, tool selection/arguments, structured output, safety classifiers.
3. **Golden workflow regressions:** representative production tasks and high-value slices with known outcomes.
4. **Adversarial evals:** injection, poisoned retrieval, malformed tools, duplicate delivery, timeouts, stale indexes, long contexts, conflicting evidence, and runaway-loop traps.
5. **Stochastic trials:** repeated runs to measure consistency, not one lucky completion.
6. **Human evaluation:** subjective quality, novel failures, safety, and high-stakes domain correctness.
7. **Production monitoring and A/B tests:** real distribution, user outcomes, drift, and unexpected interactions.

Keep capability evals separate from regression tests. Capability sets should stay challenging enough to measure improvement. Regression sets protect behavior already known to work and generally need a much higher pass rate.

Keep the iteration set separate from a blinded release holdout. Deduplicate related prompts, source documents, and generated variants across splits. Prevent fine-tuning data, few-shot examples, and prompt-optimizer inputs from contaminating the holdout.

For nondeterministic workflows, report both first-try success and consistency. `pass@k` answers whether at least one of k trials succeeds; `pass^k` asks whether all k trials succeed. Customer-facing reliability often depends much more on the latter than benchmark demos do. Always report pass@1, the exact k, trials per task, estimator, and confidence interval. Do not compare pass@k or pass^k across different k values. Repeated retries are not equivalent to first-attempt product reliability.

LLM-as-judge is useful when:

- the rubric is explicit and examples are calibrated;
- candidates are anonymized and pair order is randomized or swapped;
- deterministic checks grade everything they can grade;
- judge agreement is measured against domain experts;
- disputed, high-risk, and distribution-shifted cases go to humans.

An LLM judge is not an independent source of truth. Judges exhibit position, verbosity, self-preference, and reasoning biases; see the MT-Bench judge study[EVAL-01].

Release gates

Make release gates slice-aware. A one-point global gain cannot offset a large regression in safety, structured outputs, a language, a tenant type, or a critical workflow. Treat any High-severity safety, authorization, or side-effect failure as its own stop condition instead of averaging it into a global score.

Version the test data, graders, judge prompts/models, harness code, and environment. Report task count, trial count, confidence intervals, and per-slice support. Define non-inferiority margins before the run. Then read the failed traces; the score cannot tell you whether the model or the evaluation infrastructure failed.

Treat agents and model-generated code in training and evaluation as hostile workloads. Isolate every run and its writable supporting services; apply independent egress controls to the sandbox and every package mirror, cache, metadata service, relay, and shared store; and make direct escape, transitive escape, and cross-run communication tested failure modes.

Grade the trajectory and external effect, not only the reward or final answer. Include broken or impossible tasks, grader and tool tampering, unauthorized peer instructions, side channels, boundary probing, safe clarification or stop behavior, and cross-run coordination. Keep grader secrets outside agent-visible surfaces.

When model-generated code changes the system under evaluation, bind approval to an immutable artifact digest; any edit invalidates approval. Keep held-out data inaccessible to the agent through operating-system isolation, have a separate evaluator refuse unapproved artifacts, use capability regressions as hard gates, and review sampled trajectories for gaming. Monitoring is detection, not a substitute for isolation or deterministic enforcement.

Anthropic's agent-eval guidance[EVAL-02] and OpenAI's eval guide[EVAL-03] both emphasize evaluating the full system or harness instead of stopping at isolated model text.

SOURCES [EVAL-01] [EVAL-02] [EVAL-03] [EVAL-05] [EVAL-06] [ORIG-05] [EVAL-09]

CHAPTER 09

Trace the Whole User Journey

A complete trace should explain what happened, what it cost, where it slowed down, and whether the user got the intended result.



9.1 LLM observability as a first-class discipline

Give each bounded workflow execution its own trace. Use a stable journey or group ID and span links to connect retries, background jobs, queued continuations, and multi-session journeys. Do not stretch one trace across an unbounded conversation. A useful span structure looks like this:

```
request
├─ identity_and_policy
├─ route_decision
├─ cache_lookup
├─ context_build
│  ├─ retrieval_query
│  ├─ candidate_fusion
│  ├─ rerank
│  └─ context_pack
├─ model_call
│  └─ queue / prefill / decode when self-hosted
├─ output_validation
├─ repair_or_fallback
├─ tool_call
│  ├─ authorization
│  ├─ execution
│  └─ result_validation
└─ terminal_outcome
```

Capture the following data, with the right privacy controls in place:

- trace, run, and step IDs, including parent relationships;
- feature, workflow, route reason, and pseudonymous tenant/user dimensions;
- model provider, requested model, actual model snapshot, and decoding settings;
- prompt/context manifest, tool contract, schema, policy, and index versions;
- per-model-call input, cached input, cache-write, output, and reasoning-token counts when available; derive agent and workflow totals from those child spans rather than attaching rolled-up cache subtypes to an agent span;
- cache decision, similarity score, age, namespace, and invalidation reason;
- retrieval query, filters, source IDs/versions, ranks, and reranker scores;
- TTFT, mean TPOT, p95/p99 inter-token latency and stall rate, plus queue, retrieval, rerank, tool, repair, and end-to-end latency;
- validation errors, retries, the fallback path, finish reason, and terminal state;
- outcome, quality score, user feedback, and attributed cost.

Do not use source IDs, trace IDs, pseudonymous user or tenant IDs, prompts, or free-form route reasons as time-series metric labels. Keep those values in traces or analytical storage. Use bounded enumerations for metric labels, then join the high-cardinality attributes during offline analysis.

By default, do not record raw prompts, retrieved private documents, tool arguments, or model outputs. Use redaction, sampling, encryption, access control, short retention, and content-free hashes or manifests. The observability system cannot become the largest data-leak path.

Build drift dashboards from directly observed distributions and sampled, versioned evaluator estimates for retrieval relevance, citation support, grounding, and outcome quality. Show evaluation coverage, grader version, calibration status, and confidence intervals alongside input length, route mix, cache behavior, tool errors, validation and repair rate, tokens, latency, and cost. Alert on user-impacting SLOs and regression slices instead of every noisy model event.

OpenTelemetry's GenAI semantic conventions[OBS-01] provide a vendor-neutral starting vocabulary for inference, agents, tools, tokens, and timing. The conventions are evolving, so pin the version your telemetry contract uses.

Agent-, runtime-, and tool-authored transcripts are evidence, not the source of truth. Capture policy decisions, tool invocations, network events, receipts, and terminal state outside the agent-controlled environment in append-only or tamper-evident storage, then reconcile traces against authoritative external state. Reasoning traces, when available, may supplement detection, but neither hidden reasoning nor any single transcript can be a required enforcement dependency.

SOURCES [OBS-01] [OBS-03] [OBS-02] [EVAL-06] [ORIG-05]

9.2 Attribute cost to the whole workflow

Use the same reliability trace to attribute cost:

Journey cost		= SUM OF
INFERENCE	hosted usage units x provider/model/service-tier rate at event time	*or* allocated self-hosted compute cost
RETRIEVAL AND STORAGE	embeddings + vector operations + allocated storage + reranking	
EXTERNAL EXECUTION	tool/API calls + network/egress	
RELIABILITY AND REVIEW	retries/repairs + moderation + allocated human review	

Record cached-input, cache-write, reasoning, and output usage separately, but do not add a subtype again when the provider includes it in a parent total.

The dimensions you usually need are feature, workflow, tenant, user journey, route, model, environment, and terminal outcome. Use pseudonymous identifiers where possible.

Track:

- cost per successful task, not only per request;
- cost per grounded/correct answer;
- retry and repair amplification;
- semantic and prefix-cache savings net of lookup/storage cost;
- cost of fallback and escalation paths;
- idle and reserved accelerator cost for self-hosting;
- for self-hosted serving, total inference energy per request and per successful outcome alongside energy per output token, sliced by model, phase, batch, context length, and output length; a falling per-token figure can hide rising request energy;
- marginal cost and fully loaded cost separately.

Reconcile the trace-derived estimates with provider invoices or Costs APIs. Allocate reserved capacity, idle accelerators, storage, observability, and shared platform cost through documented drivers. Keep an explicit unallocated or residual bucket instead of inventing false precision. Preserve the price-table version and effective timestamp behind every calculation.

Compare complete workflows across quality, latency, cost, and reliability. Model price is only one input. A cheaper model can cost more when it doubles retries or sends more work to humans. A higher-priced model can cost less per successful outcome when it shortens the loop, uses tools correctly, or prevents failure.

SOURCES [COST-01] [COST-02] [OBS-01] [OBS-03] [COST-03]

Author synthesis: the journey-cost formula ties spend to a completed user outcome.

CHAPTER 10

Build Safety into the Architecture

Prompt injection and tenant isolation are system problems. Permissions and data boundaries must hold even when the model is wrong.



10.1 Safety engineering and permission boundaries

A stronger system prompt, fine-tuning, or RAG will not solve prompt injection. User text, web pages, documents, emails, images, and tool outputs can all carry adversarial instructions. Assume a probabilistic detector will eventually miss an attack. Deterministic controls must limit the blast radius when it does.

Build the defense in layers:

1. Authenticate the human and workload identity.
2. Authorize every data retrieval and tool action against the exact resource.
3. Label and separate untrusted content from instructions, but treat the separation as model guidance rather than isolation; enforce deterministic source-to-sink policy.
4. Expose only the tool and data surface the current step needs. Keep credentials and capability tokens inside the trusted executor.
5. Use allowlisted tools, egress destinations, and parameter constraints.
6. Never place raw secrets or bearer tokens in model context. Inject scoped, short-lived credentials server-side only after authorization.
7. Sandbox code, files, and network access.
8. Require a single-use approval bound to the exact consequential action and state version; reauthorize immediately before execution.
9. Apply data minimization and DLP at ingestion, context assembly, tool arguments and egress, final output, logs, and traces. Reauthorize sensitive data at every sink.
10. Audit proposals, policy decisions, actions, and resulting state.
11. Red-team direct, indirect, multimodal, encoded, and retrieved injections.
12. Have containment, revocation, incident response, and replay procedures.

Human approval is scarce attention and approval frequency is a security property. Use bounded action plans and risk-triggered reapproval so consent fatigue does not turn review into a rubber stamp. Never use elicitation to collect passwords, bearer tokens, or other secrets.

For OAuth or MCP tools, validate the issuer, audience, scopes, actor, and expiry. Prohibit token passthrough. Use separately issued downstream tokens and per-client consent. Treat OAuth metadata, discovery documents, and registration endpoints as untrusted network input: allowlist schemes and destinations, block private and link-local ranges after DNS

resolution, disable unsafe redirect following, and revalidate every redirect hop. The MCP authorization specification[AUTH-01] and security best practices[AUTH-02] make these boundaries explicit.

The OWASP LLM prompt-injection guidance[SAFE-01] notes that RAG and fine-tuning do not fully mitigate injection. Microsoft's defense-in-depth pattern[SAFE-02] recommends content isolation, least privilege, monitoring, and human approval. For the broader governance and risk context, use the NIST Generative AI Profile[SAFE-03].

SOURCES [SAFE-01] [SAFE-02] [SAFE-03] [AUTH-01] [AUTH-02] [AUTH-03] [EVAL-06] [ORIG-05] [SAFE-09]

10.2 Multi-tenant isolation and cache safety

Carry tenant identity through every layer of the system. Appending it at the UI does not create an isolation boundary.

Use this checklist:

- derive tenant and principal from authenticated server-side identity;
- enforce tenant and document ACL constraints inside the source query and before or during vector candidate generation and reranking; post-filtering a global top-k result is not an isolation boundary;
- use tenant-scoped credentials, storage namespaces, vector indexes or filters, and encryption boundaries appropriate to risk;
- namespace exact, semantic, and retrieval response caches by a nonempty authenticated tenant/principal or ACL scope plus every response-affecting policy, corpus, prompt, model, schema, and freshness version; reauthorize provenance on every hit and purge entries after ACL, role, user, or document changes;
- require exact-token matching plus runtime ownership and refcount isolation for prefix/KV reuse; a provider organization or project is not an application tenant boundary;
- put an authenticated and authorized ingress boundary in front of every model-server route; treat built-in API-key flags as endpoint-scoped until verified, inventory every reachable route, disable unused compatibility, administration, metrics, and profiling APIs, and negative-test access;
- treat model repositories, processor and tokenizer code, custom operators, and conversion steps as executable supply-chain inputs; allow only reviewed, digest-pinned artifacts, and load or convert them in an isolated environment without production credentials or broad egress; a runtime flag such as `trust_remote_code=false` is not a security boundary for an unreviewed loader;

- enforce decoded-byte, duration, frame, pixel, and accelerator-memory limits across every audio, image, and video path; derive limits from bounded decode output rather than trusting caller-controlled container metadata, and reject the request before it can exhaust shared worker or GPU capacity;
- do not let request fields select a decoder, kernel, plugin, adapter, or other privileged backend unless an operator allowlisted it and included it in startup resource reservation and isolation policy;
- treat agent runtimes, sandbox provisioners, gateways and proxies, bridges, installers, updaters, and inference services as privileged policy-enforcement code; pin and patch them, verify certificates and artifact integrity, normalize paths before layer-7 policy, avoid building shell commands from untrusted data, and test escape, injection, traversal, and authorization-bypass paths;
- treat the serving engine, custom kernels, and batching scheduler as tenant-isolation code; pin and inventory the runtime, monitor its security advisories, patch within the risk window, and test response ownership under concurrent tenants; a model-server flaw can cross-contaminate responses even when cache namespaces are correct;
- record the requested processing geography and the provider-resolved organization, project, workspace, and region when the API exposes them; reject unexpected resolution before sensitive data crosses the boundary;
- exclude sensitive content and identifiers from shared scheduler metadata, and address timing or resource side channels with quotas, traffic shaping, or physical silos where the threat model requires;
- bind every request, tool call, callback, queue item, and result to immutable tenant, principal, conversation, run, and call IDs; reject mismatched or late results and clear or zero pooled worker, sandbox, and request-local state before reuse;
- isolate background jobs, queues, temporary files, sandboxes, logs, traces, and eval environments;
- enforce tenant quotas for requests, context, KV memory, tools, and cost;
- test deleted users, changed roles, revoked documents, cache hits after ACL changes, and concurrent tenants;
- seed cross-tenant canaries and alert if they are retrieved, generated, logged, or cached outside their scope.

Physical isolation is not always required. The boundary still has to match the data and threat model. High-risk workloads may require separate projects or accounts, networks, encryption keys, compute, and tool servers. Google's multi-tenant agentic AI reference architecture[TEN-01] shows what that stricter topology looks like.

SOURCES [TEN-01] [AUTH-01] [AUTH-02] [SAFE-03] [SAFE-04] [SAFE-05] [SAFE-06] [SAFE-07] [SAFE-08] [SAFE-09] [SERV-08] [MOD-02] [MOD-04]

Author synthesis: the isolation checklist spans the cited permission and tenancy boundaries.

CHAPTER 11

Choose What to Change

Measure the constraint first. Change the part of the system that causes it, then verify what happened to quality, latency, cost, and reliability.



11.1 In-context learning, RAG, fine-tuning, and distillation

Choose the method based on what has to change.

METHOD	BEST WHEN	WRONG TOOL WHEN	HIDDEN COST
In-context learning	Instructions or examples change often; the task fits in context; fast iteration matters	The example set is huge or sensitive, or the examples must be applied consistently at very high volume	Repeated tokens, context interference, prompt and version complexity
RAG	Knowledge is external, mutable, permission-scoped, or needs attribution, and an authoritative retrievable corpus exists	You are using it as the sole fix for behavior or style, corpus quality is poor, or retrieval cannot locate evidence reliably	Ingestion, freshness, retrieval and rerank latency, ACL operations
Fine-tuning	Stable behavior, format, style, tool use, or domain transformation repeats, and clean representative examples exist	You are using it as the sole knowledge store when facts change or current provenance and citations are required; policy needs deterministic enforcement	Data curation, training, model lifecycle, regression, and rollback
Distillation	A narrow, stable, high-volume workflow has a validated teacher, governed teacher outputs, and a strong eval set	The task changes quickly, requires broad frontier reasoning, depends on rare cases for most of its value, or includes teacher failures that cannot be filtered	Teacher bias and error inheritance, output rights and governance, training, refresh, tail-capability loss

These methods can work together. A practical sequence is:

1. Define the evals and establish a strong-model baseline.
2. Improve the harness, context, tools, and deterministic validation.
3. Add RAG for changing or attributable knowledge.
4. Route simpler cases to smaller models only when evals show that it is safe.
5. Fine-tune persistent behavior gaps with clean representative data.
6. Distill only when the volume and task stability justify a student model.

Use each method for the job it can actually do: fine-tuning changes stable behavior rather than current facts, RAG supplies knowledge without enforcing behavior, in-context examples do not create durable state, and distillation is not lossless. OpenAI's model optimization guide[OPT-01] starts with evals because model behavior varies across families and snapshots.

SOURCES [OPT-01] [CTX-01] [RAG-01] [DIST-01]

Author synthesis: the selection matrix matches the intervention to the constraint.

11.2 Diagnosing the four-way tradeoff

Diagnose the symptom, measure the relevant stack signals, and track where the fix moves risk.

SYMPTOM	FIRST MEASUREMENTS	LIKELY ACTIONS	RISK MOVED ELSEWHERE
Slow first token	Queue, retrieval, prompt length, prefix hit, prefill time	Reduce queue/retrieval, maximize safe prefix reuse, prune context only after recall checks; when self-hosted, tune prefill chunks and admission	Lower retrieval recall, lower throughput, or more rejected/queued work
Slow token stream	Mean TPOT, p95/p99 ITL, stall rate, active batch, KV pressure, memory bandwidth, speculative acceptance	Reduce active batch/KV pressure, tune scheduler and kernels, then test quantization or speculative decoding	Lower throughput, extra memory, quality loss, or worse tails; shorter output improves completion time but not TPOT
Low throughput	Goodput, scheduler occupancy, KV utilization, length distribution	Paged allocation, continuous batching, length-aware admission, quotas	Interactive latency or tenant fairness
High model cost	Cost per success, cached tokens, retries, route mix	Prefix cache, smaller qualified route, shorter output, distillation	Router errors or capability loss
Poor answer quality	Retrieval recall, claim coverage, grounding, slice scores, plus gold-context and no-context ablations	Fix the component that fails: ingestion/retrieval when gold evidence is missing; context packing or the generator when sufficient gold evidence is present	Added latency/cost, model dependence, or index complexity
Tool failures	Selection, argument validity, auth denial, duplicate effects	Redesign contracts, validate, idempotency, narrower tools	More orchestration code
Unreliable agents	Trace loops, no-progress count, tool/time/cost budgets	Stronger state machine, success predicates, stop conditions	Less autonomy on edge cases
Safety concerns	Injection tests, permissions, egress, cross-tenant canaries	Least privilege, isolation, approvals, policy outside model	UX friction and operational cost

Change one major variable at a time when you can. If you combine a model swap with a prompt rewrite, a new retriever, quantization, and a router change, you will have almost no way to attribute a regression.

SOURCES [SERV-05] [SERV-04] [OPT-01] [OBS-01]

Author synthesis: the diagnostic matrix keeps quality, latency, cost, and reliability in one decision.

CHAPTER 12

Design for Production Failure

Production systems fail in predictable ways. The final chapter turns those patterns into checks, operating decisions, and a practical learning order.



12.1 Production failure matrix

Before launch, define a detection signal, containment path, and regression test for every known failure.

FAILURE	DETECT	CONTAIN	PREVENT/REGRESS
Hallucinated tool name	Registry lookup rejection	Do not execute; bounded replan	Tool-selection positive and negative evals
Malformed JSON	Parse and finish-reason telemetry	One bounded repair or typed fallback	Constrained output plus exact-schema regressions
Schema-valid but wrong arguments	Domain invariants and state checks	Reject before authorization/execution	Argument and cross-field golden cases
Model claims tool success without executor receipt	Missing correlated receipt or failed postcondition	Do not present success; reconcile external state	Require execution receipt and postcondition tests
Duplicate side effect	Idempotency store and uniqueness constraint	Return prior result or reconcile unknown state	Timeout-after-commit and redelivery tests
Stale retrieval	Source/index version and freshness SLO	Warn, abstain, or use authoritative live source	Update/delete/revocation evals
Wrong citation	Claim-to-evidence entailment and anchor check	Remove unsupported claim or abstain	Citation precision/completeness suite
Semantic-cache false hit	Per-hit tenant/ACL, policy, corpus, state, and freshness validation; semantic verification for every consequential hit	Bypass and invalidate; investigate cross-scope hits	Disable semantic caching for personalized, transactional, permission-sensitive, or high-stakes flows; hard-negative evals by risk slice
Cross-user contamination	Tenant canaries, ACL audit, namespace mismatch	Disable cache/route, revoke, incident response	Concurrent isolation and ACL-change tests
Runaway agent	Budget and repeated-state detection	Stop with typed partial/blocked result	Loop traps and no-progress evals
Prompt injection via retrieved/tool data	Policy/flow alerts and risky tool sequence	Isolate content, deny action, require approval	Direct/indirect/multimodal adversarial suite
KV exhaustion	KV usage, eviction/preemption, OOM forecast	Admission control, shed/degrade load	Long-context and concurrency load tests
Prefill starves decode	TTFT/TPOT by prompt length and scheduler class	Chunk/limit prefill, reserve decode budget	Mixed-length SLO load tests
Quantized tail regression	Slice deltas against baseline	Roll back format/model route	Exact, long-context, safety, multilingual gates
Router regression	Quality/cost/latency by route and confidence	Pin high-risk traffic to qualified route	Shadow traffic and route confusion matrix
Fallback bypasses refusal or policy	Fallback-reason audit and policy-state mismatch	Stop with typed refusal or denial	Failure-class routing tests and identical policy gates on every route
Silent eval regression	Versioned CI and production drift alert	Halt rollout or roll back	Required slice-aware release gates

SOURCES [OUT-01] [TOOL-01] [SERV-01] [EVAL-02] [SAFE-01] [TEN-01]
Author synthesis: the failure matrix combines the controls in sections 4–20.

12.2 Production readiness checklist

Use this checklist before launch and again after any material change.

Contract and harness

- ☐ Success, partial, refused, blocked, degraded, and failed states are defined.
- ☐ End-to-end quality, latency, cost, reliability, freshness, and safety SLOs exist.
- ☐ State, versions, retries, idempotency, budgets, and termination are harness-owned.
- ☐ Consequential actions have deterministic authorization and approval boundaries.

Context and retrieval

- ☐ Context is minimal, authorized, source-attributed, versioned, and reproducible.
- ☐ Retrieval recall and generation grounding are measured separately.
- ☐ The retrieval strategy—lexical, dense, or hybrid—plus chunking, k, fusion, and reranking when used is selected and tuned through evals.
- ☐ Updates, deletions, ACL changes, and cache invalidation meet a freshness SLO.

Inference and caching

- ☐ Queue, TTFT, mean TPOT, p95/p99 ITL, stall rate, goodput, and p95/p99 end-to-end latency are load-tested on real length distributions.
- ☐ KV capacity, fragmentation, eviction, preemption, quotas, and OOM behavior are known.
- ☐ Prefix and semantic caches have distinct policies and metrics.
- ☐ Any speculative, quantized, or distilled route passes the full regression suite.

Outputs, tools, and agents

- ☐ Structured outputs pass syntax, schema, semantic, authorization, and result checks.
- ☐ Tool names, arguments, results, errors, and risk annotations are strict and versioned.
- ☐ Retryable side effects are idempotent and tested under unknown commit status.
- ☐ Idempotency keys survive retries, resumes, handoffs, and fallbacks and are recorded atomically with mutations.
- ☐ Concurrency, fan-out, mutation, and shared fallback budgets are enforced atomically with turn, tool, token, time, cost, risk, retry, and no-progress budgets.
- ☐ Refusal, incomplete/truncated, repair, and fallback paths are tested; repair cannot authorize mutations.

Evals, operations, and economics

- ☐ Golden, regression, adversarial, stochastic, and human eval layers exist.
- ☐ Release gates are slice-aware and evaluator versions are pinned.
- ☐ Bounded traces cover routing, context, retrieval, model, validation, tools, and outcome, and linked journey IDs connect asynchronous or multi-session work.
- ☐ Cost is attributed per feature, workflow, tenant, journey, route, and successful outcome.
- ☐ Drift dashboards and rollback procedures are exercised.

Security and tenancy

- ☐ Untrusted content is never treated as authority merely because it is in context.
- ☐ Least privilege, sandboxing, egress controls, DLP, and approvals limit blast radius.
- ☐ Tenant identity scopes retrieval, caches, tools, logs, traces, queues, and quotas.
- ☐ Cross-tenant canaries, revoked-access tests, and incident procedures exist.
- ☐ Fallback cannot bypass refusal, authorization, residency, retention, or unknown-commit reconciliation.
- ☐ Credentials and bearer tokens never enter model context; OAuth audiences are validated and token passthrough is prohibited.
- ☐ Approvals are bound to the exact action and state version.
- ☐ Cache hits fail closed on missing tenant scope, are reauthorized, and are invalidated after access changes.

SOURCES [SAFE-03] [OBS-02] [EVAL-02] [TEN-01]

Author synthesis: the operating guidance is recast as a production-readiness checklist.

12.3 Recommended learning order

1. Define success and build a small golden set.
2. Build the deterministic harness: state, schemas, tools, budgets, and termination.
3. Learn context construction and retrieval with provenance and ACLs.
4. Add traces, outcome metrics, and full-workflow cost attribution.
5. Threat-model injection, leakage, side effects, and multi-tenant boundaries.
6. Load-test prefill, decode, batching, KV memory, and queue behavior.
7. Only then optimize with caching, routing, quantization, speculative decoding, fine-tuning, or distillation.

Do the optimization work after the system is measured and safe. Otherwise, the change can improve speed while leaving the outcome wrong or unsafe.

SOURCES [EVAL-02] [EVAL-03] [OPT-01]

Author synthesis: the learning order follows the sequence I would use to build the system.

APPENDIX A

Notes and Sources

This handbook grew out of my *Production AI Engineering Field Guide*, which provides the structure. The research papers, standards, security guidance, and product documentation below support the technical claims.

Notes marked *author synthesis* show where I combined sources or made a practical recommendation. Citation labels in the chapters link to the full entries here.

Section source map

§1.1 The full system — [AGT-01] [CTX-01] [OBS-01]
Author synthesis: the cited sources inform this layered operating model.

§1.2 Harness engineering, not just prompt engineering — [AGT-01] [TOOL-01] [AUTH-01]
Author synthesis: the taxonomy separates prompt, context, and harness responsibilities.

§2.1 Context engineering, not long prompts — [CTX-01] [CTX-02]

§2.2 Four caches that must not be confused — [CACHE-01] [CACHE-02] [SERV-01]
Author synthesis: the four caches are grouped by what they reuse and how they fail.

§3.1 Prefill and decode optimize differently — [SERV-03] [SERV-04] [SERV-05]

§3.2 KV cache management and memory pressure — [SERV-01] [SERV-04] [SERV-06]
The KV footprint example follows directly from the model architecture.

§3.3 Continuous batching, paged attention, and goodput — [SERV-02] [SERV-03] [SERV-04] [SERV-07]

§4.1 Speculative decoding, quantization, and distillation — [SPEC-01] [QUANT-02] [DIST-01]
Author synthesis: the comparison maps each technique to the bottleneck it changes.

§4.2 Quantization: formats, methods, and quality risk — [QUANT-01] [QUANT-02] [QUANT-03] [QUANT-04] [SERV-04]

§5.1 Structured outputs: syntax is only the first gate — [OUT-01] [OUT-02] [MCP-03]
Author synthesis: repair policy is separated from the rules for consequential actions.

§5.2 Reliable function and tool calling — [TOOL-01] [TOOL-02] [TOOL-03] [TOOL-04] [MCP-01] [MCP-02] [MCP-03] [AUTH-01] [AUTH-02] [AUTH-03]
Author synthesis: approval, idempotency, and execution receipts form one tool-safety contract.

§6.1 Agent guardrails, budgets, and termination — [AGT-01] [EVAL-02] [AUTH-02] [EVAL-05] [EVAL-06] [ORIG-05]
Author synthesis: agent limits are organized as budgets and explicit terminal states.

§6.2 Model routing and degraded mode — [OPT-01] [SERV-05] [MCP-01] [MOD-01] [MOD-02] [MOD-03] [MOD-04]
Author synthesis: routing decisions are tied to the user's degraded-mode experience.

§7.1 RAG architecture — [RAG-01] [RAG-02] [RAG-03] [RETR-06] [TEN-01]

§7.2 Retrieval and answer evals [RETR-01] [RETR-02] [RETR-03] [RETR-04] [RETR-05] [RETR-07] [RETR-09]

§8.1 Evals as the release contract [EVAL-01] [EVAL-02] [EVAL-03] [EVAL-05] [EVAL-06] [ORIG-05] [EVAL-09]

§9.1 LLM observability as a first-class discipline [OBS-01] [OBS-03] [OBS-02] [EVAL-06] [ORIG-05]

§9.2 Attribute cost to the whole workflow [COST-01] [COST-02] [OBS-01] [OBS-03] [COST-03]

Author synthesis: the journey-cost formula ties spend to a completed user outcome.

§10.1 Safety engineering and permission boundaries [SAFE-01] [SAFE-02] [SAFE-03] [AUTH-01] [AUTH-02] [AUTH-03] [EVAL-06] [ORIG-05] [SAFE-09]

§10.2 Multi-tenant isolation and cache safety [TEN-01] [AUTH-01] [AUTH-02] [SAFE-03] [SAFE-04] [SAFE-05] [SAFE-06] [SAFE-07] [SAFE-08] [SAFE-09] [SERV-08] [MOD-02] [MOD-04]

Author synthesis: the isolation checklist spans the cited permission and tenancy boundaries.

§11.1 In-context learning, RAG, fine-tuning, and distillation [OPT-01] [CTX-01] [RAG-01] [DIST-01]

Author synthesis: the selection matrix matches the intervention to the constraint.

§11.2 Diagnosing the four-way tradeoff [SERV-05] [SERV-04] [OPT-01] [OBS-01]

Author synthesis: the diagnostic matrix keeps quality, latency, cost, and reliability in one decision.

§12.1 Production failure matrix [OUT-01] [TOOL-01] [SERV-01] [EVAL-02] [SAFE-01] [TEN-01]

Author synthesis: the failure matrix combines the controls in sections 4–20.

§12.2 Production readiness checklist [SAFE-03] [OBS-02] [EVAL-02] [TEN-01]

Author synthesis: the operating guidance is recast as a production-readiness checklist.

§12.3 Recommended learning order [EVAL-02] [EVAL-03] [OPT-01]

Author synthesis: the learning order follows the sequence I would use to build the system.

Harness, context, outputs, and tools

[CTX-01] Anthropic. "Effective context engineering for AI agents." 29 September 2025. Accessed 31 August 2026.
anthropic.com/engineering/effective-context-engineering-for-ai-agents Cited in §1.1, §2.1, §11.1

[CTX-02] Liu, Nelson F., et al. "Lost in the Middle: How Language Models Use Long Contexts." Transactions of the Association for Computational Linguistics 12 (2024): 157-173.
aclanthology.org/2024.tacl-1.9 Cited in §2.1

[AGT-01] Anthropic. "Building effective agents." 19 December 2024. Accessed 31 August 2026.
anthropic.com/engineering/building-effective-agents Cited in §1.1, §1.2, §6.1

[TOOL-01] Anthropic. "Writing effective tools for AI agents: using AI agents." Accessed 31 August 2026.
anthropic.com/engineering/writing-tools-for-agents Cited in §1.2, §5.2, §12.1

[CACHE-01] OpenAI. "Prompt caching." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/prompt-caching Cited in §2.2

[CACHE-02] Microsoft. "Get cached responses of large language model API requests." Azure API Management documentation. Updated 24 February 2026. Accessed 31 August 2026.
learn.microsoft.com/en-us/azure/api-management/llm-semantic-cache-loo... Cited in §2.2

[OUT-01] OpenAI. "Structured model outputs." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/structured-outputs Cited in §5.1, §12.1

[OUT-02] JSON Schema. "Creating your first schema." Accessed 31 August 2026.
json-schema.org/learn/getting-started-step-by-step Cited in §5.1

[TOOL-02] OpenAI. "Function calling." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/function-calling Cited in §5.2

[TOOL-03] Fielding, Roy, Mark Nottingham, and Julian Reschke. "HTTP Semantics." RFC 9110, June 2022, section 9.2.2, "Idempotent Methods."
rfc-editor.org/rfc/rfc9110.html#name-idempotent-methods Cited in §5.2

[TOOL-04] Kujanpaa, Kalle, et al. "Compiling Agentic Workflows into Deterministic Tools for Production Reliability." arXiv:2607.08010, 2026.
arxiv.org/abs/2607.08010 Cited in §5.2

[MCP-01] Model Context Protocol. "Key Changes in the 2026-07-28 Specification." 28 July 2026. Accessed 31 August 2026.
blog.modelcontextprotocol.io/posts/2026-07-28 Cited in §5.2, §6.2

[MCP-02] Model Context Protocol. "Key Changes." Protocol specification, 28 July 2026. Accessed 31 August 2026.
modelcontextprotocol.io/specification/2026-07-28/changelog Cited in §5.2

[MCP-03] Model Context Protocol. "Base Protocol: Overview." Protocol specification, 28 July 2026. Accessed 31 August 2026.
modelcontextprotocol.io/specification/2026-07-28/basic/index Cited in §5.1, §5.2

[AUTH-01] Model Context Protocol. "Authorization." Protocol specification, 28 July 2026. Accessed 31 August 2026.
modelcontextprotocol.io/specification/2026-07-28/basic/authorization Cited in §1.2, §5.2, §10.1, §10.2

[AUTH-02] Model Context Protocol. "Security Best Practices." Protocol specification, 28 July 2026. Accessed 31 August 2026.
modelcontextprotocol.io/specification/2026-07-28/basic/security_best_... Cited in §5.2, §6.1, §10.1, §10.2

[AUTH-03] Fisher, Bill, and Ryan Galluzzo. "Back to the Future: Why Agentic AI Needs a Strong Identity Foundation." NIST Cybersecurity Insights, 27 August 2026. Accessed 31 August 2026.
nist.gov/blogs/cybersecurity-insights/back-future-why-agentic-ai-need... Cited in §5.2, §10.1

[MOD-01] Google. "Gemini API release notes." Google AI for Developers. Accessed 31 August 2026.
ai.google.dev/gemini-api/docs/changelog Cited in §6.2

[MOD-02] Anthropic. "Developer platform release notes." Claude API documentation. Accessed 31 August 2026.
platform.claude.com/docs/en/release-notes/overview Cited in §6.2, §10.2

[MOD-03] Amazon Web Services. "Amazon Bedrock model lifecycle." AWS documentation. Accessed 31 August 2026.
docs.aws.amazon.com/bedrock/latest/userguide/model-lifecycle.html Cited in §6.2

[MOD-04] OpenAI. "API changelog." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/changelog Cited in §6.2, §10.2

Serving and compression

[SERV-01] Kwon, Woosuk, et al. "Efficient Memory Management for Large Language Model Serving with PagedAttention." SOSP 2023.
arxiv.org/abs/2309.06180 Cited in §2.2, §3.2, §12.1

[SERV-02] Yu, Gyeong-In, et al. "Orca: A Distributed Serving System for Transformer-Based Generative Models." OSDI 2022.
usenix.org/conference/osdi22/presentation/yu Cited in §3.3

[SERV-03] Agrawal, Amey, et al. "Taming Throughput-Latency Tradeoff in LLM Inference with Sarathi-Serve." OSDI 2024.
usenix.org/conference/osdi24/presentation/agrawal Cited in §3.1, §3.3

[SERV-04] vLLM Project. "vLLM documentation." Accessed 31 August 2026.
docs.vllm.ai/en/latest Cited in §3.1, §3.2, §3.3, §4.2, §11.2

[SERV-05] OpenAI. "Latency optimization." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/latency-optimization Cited in §3.1, §6.2, §11.2

[SERV-06] Cheng, Ke, et al. "Robust KV-Cache Reservation for LLM Serving Under Workload Distribution Shifts." arXiv:2607.16892, 2026.
arxiv.org/abs/2607.16892 Cited in §3.2

[SERV-07] Ni, Hongqiu, et al. "TOPAS: Workflow-Aware Prefix-State Scheduling for Multi-Agent LLM Serving." arXiv:2608.25523, 2026.
arxiv.org/abs/2608.25523 Cited in §3.3

[SERV-08] vLLM Project. "v0.28.0." Release notes, 26 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/releases/tag/v0.28.0 Cited in §10.2

[SPEC-01] Leviathan, Yaniv, Matan Kalman, and Yossi Matias. "Fast Inference from Transformers via Speculative Decoding." ICML 2023.
proceedings.mlr.press/v202/leviathan23a.html Cited in §4.1

[QUANT-01] Micikevicius, Paulius, et al. "FP8 Formats for Deep Learning." arXiv:2209.05433, 2022.
arxiv.org/abs/2209.05433 Cited in §4.2

[QUANT-02] Xiao, Guangxuan, et al. "SmoothQuant: Accurate and Efficient Post-Training Quantization for Large Language Models." ICML 2023.
proceedings.mlr.press/v202/xiao23c.html Cited in §4.1, §4.2

[QUANT-03] Lin, Ji, et al. "AWQ: Activation-aware Weight Quantization for On-Device LLM Compression and Acceleration." MLSys 2024.
proceedings.mlsys.org/paper_files/paper/2024/hash/42a452cbafa9dd64e9b... Cited in §4.2

[QUANT-04] Frantar, Elias, et al. "GPTQ: Accurate Post-Training Quantization for Generative Pre-trained Transformers." ICLR 2023.
arxiv.org/abs/2210.17323 Cited in §4.2

[DIST-01] Hinton, Geoffrey, Oriol Vinyals, and Jeff Dean. "Distilling the Knowledge in a Neural Network." arXiv:1503.02531, 2015.
arxiv.org/abs/1503.02531 Cited in §4.1, §11.1

Retrieval and evaluation

[RAG-01] Lewis, Patrick, et al. "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks." NeurIPS 2020.
papers.neurips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Ab... Cited in §7.1, §11.1

[RAG-02] Elastic. "Hybrid search." Elastic documentation. Accessed 31 August 2026.
elastic.co/docs/solutions/search/hybrid-search Cited in §7.1

[RAG-03] Microsoft. "Grounding Data Design for AI Workloads on Azure." Azure Well-Architected Framework. Accessed 31 August 2026.
learn.microsoft.com/en-us/azure/well-architected/ai/grounding-data-de... Cited in §7.1

[RETR-06] Hua, Peichun, et al. "Pointing the Way, Hiding the Destination: Practical Private Dense Retrieval at Scale." arXiv:2608.25735, 2026.
arxiv.org/abs/2608.25735 Cited in §7.1

[RETR-07] Ghosh, Utshab Kumar, Debayan Mukhopadhyay, and Shubham Chatterjee. "Assessing the Downstream Utility of Evidence-Aware Retrieval in RAG." arXiv:2608.26379, 2026.
arxiv.org/abs/2608.26379 Cited in §7.2

[RETR-09] Chen, Haodong, et al. "ITER: Interaction-Aware Retrieval for Agentic Search." arXiv:2608.27912, 2026.
arxiv.org/abs/2608.27912 Cited in §7.2

[RETR-01] Thakur, Nandan, et al. "BEIR: A Heterogeneous Benchmark for Zero-shot Evaluation of Information Retrieval Models." NeurIPS 2021 Datasets and Benchmarks.
datasets-benchmarks-proceedings.neurips.cc/paper/2021/hash/65b9eea6e1... Cited in §7.2

[RETR-02] Muennighoff, Niklas, et al. "MTEB: Massive Text Embedding Benchmark." EACL 2023.
aclanthology.org/2023.eacl-main.148 Cited in §7.2

[RETR-03] Ru, Dongyu, et al. "RAGChecker: A Fine-grained Framework for Diagnosing Retrieval-Augmented Generation." arXiv:2408.08067, 2024.
arxiv.org/abs/2408.08067 Cited in §7.2

[RETR-04] Es, Shahul, et al. "RAGAs: Automated Evaluation of Retrieval Augmented Generation." EACL 2024 System Demonstrations.
aclanthology.org/2024.eacl-demo.16 Cited in §7.2

[RETR-05] Gao, Tianyu, et al. "Enabling Large Language Models to Generate Text with Citations." EMNLP 2023: 6465-6488.
aclanthology.org/2023.emnlp-main.398 Cited in §7.2

[EVAL-01] Zheng, Lianmin, et al. "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena." NeurIPS 2023 Datasets and Benchmarks.
papers.neurips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef225... Cited in §8.1

[EVAL-02] Anthropic. "Demystifying evals for AI agents." 9 January 2026. Accessed 31 August 2026.
anthropic.com/engineering/demystifying-evals-for-ai-agents Cited in §6.1, §8.1, §12.1, §12.2, §12.3

[EVAL-03] OpenAI. "Working with evals." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/evals Cited in §8.1, §12.3

[EVAL-05] OpenAI. "The Hugging Face incident and the road ahead." 26 August 2026. Accessed 31 August 2026.
openai.com/index/hugging-face-incident-and-the-road-ahead Cited in §6.1, §8.1

[EVAL-06] OpenAI. OpenAI - Hugging Face Incident Technical Report. 26 August 2026. Accessed 31 August 2026.
cdn.openai.com/pdf/67869394-cb91-4c12-888c-5cbd85c7814c/OpenAI-Huggin... Cited in §6.1, §8.1, §9.1, §10.1

[ORIG-05] Greenblatt, Ryan, Ajeya Cotra, and Hjalmar Wijk. "Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident." METR and Redwood Research, 26 August 2026. Accessed 31 August 2026.
metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation Cited in §6.1, §8.1, §9.1, §10.1

[EVAL-09] Chen, Yueh-Han, Jiaxin Wen, and Jan Hendrik Kirchner. "Automated Researchers Can Reliably Mitigate Alignment Failures." 28 August 2026. Accessed 31 August 2026.
anthropic.com/research/automated-researchers-mitigate-alignment-failures Cited in §8.1

Observability and economics

[OBS-01] OpenTelemetry. "Semantic conventions for generative AI systems." Accessed 31 August 2026.
github.com/open-telemetry/semantic-conventions-genai Cited in §1.1, §9.1, §9.2, §11.2

[OBS-03] OpenTelemetry. "Remove cache token usage attributes from internal agent spans." Commit 5f5ae69, 27 August 2026. Accessed 31 August 2026.
github.com/open-telemetry/semantic-conventions-genai/commit/5f5ae69e5... Cited in §9.1, §9.2

[COST-03] Vellaisamy, Prabhu, Vanessa Lam, Shawn Blanton, and John Paul Shen. "Characterization of Request and Token Energy Costs for LLM Inference Workloads on GPU Platforms." arXiv:2608.28044, 2026.
arxiv.org/abs/2608.28044 Cited in §9.2

[OBS-02] National Institute of Standards and Technology. "Measure." AI Risk Management Framework Playbook. Accessed 31 August 2026.
airc.nist.gov/airmf-resources/playbook/measure Cited in §9.1, §12.2

[COST-01] OpenAI. "Costs." Organization Usage and Costs API reference. Accessed 31 August 2026.
developers.openai.com/api/reference/resources/admin/subresources/orga... Cited in §9.2

[COST-02] FinOps Foundation. "Capability: Unit Economics." Accessed 31 August 2026.
finops.org/framework/capabilities/unit-economics Cited in §9.2

Security and tenancy

[SAFE-01] OWASP GenAI Security Project. "LLM01:2025 Prompt Injection." Accessed 31 August 2026.
genai.owasp.org/llmrisk/llm01-prompt-injection Cited in §10.1, §12.1

[SAFE-02] Microsoft. "Defend against indirect prompt injection attacks." Microsoft Learn. Accessed 31 August 2026.
learn.microsoft.com/en-us/security/zero-trust/sfi/defend-indirect-pro… Cited in §10.1

[SAFE-03] National Institute of Standards and Technology. Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile. NIST AI 600-1, July 2024.
nvlpubs.nist.gov/nistpubs/ai/NIST.AI.600-1.pdf Cited in §10.1, §10.2, §12.2

[SAFE-04] vLLM Project. "Integer overflow can lead to cross-user inference response leakage." GHSA-7m6h-x95x-82q5, 11 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/security/advisories/GHSA-7m6h-x95x-82q5 Cited in §10.2

[SAFE-05] vLLM Project. "LlavaOnevision2 processor loader executes attacker model code with trust_remote_code=False." GHSA-3c86-2m5g-59q7, 28 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/security/advisories/GHSA-3c86-2m5g-59q7 Cited in §10.2

[SAFE-06] vLLM Project. "Denial of Service NanoNemoTronVL Video Audio Extraction Bomb." GHSA-936p-m5pv-vvjf, 28 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/security/advisories/GHSA-936p-m5pv-vvjf Cited in §10.2

[SAFE-07] vLLM Project. "Speech-to-text audio decode duration limit bypass via forged header sample rate." GHSA-99f2-hwrc-gvq8, 28 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/security/advisories/GHSA-99f2-hwrc-gvq8 Cited in §10.2

[SAFE-08] vLLM Project. "Request-selected PyNvVideoCodec GPU decode bypasses static VRAM reservation." GHSA-8pw2-6jv3-mj5j, 28 August 2026. Accessed 31 August 2026.
github.com/vllm-project/vllm/security/advisories/GHSA-8pw2-6jv3-mj5j Cited in §10.2

[SAFE-09] NVIDIA. "Security Bulletin: NVIDIA NemoClaw and OpenShell - August 2026." Updated 28 August 2026. Accessed 31 August 2026.
nvidia.custhelp.com/app/answers/detail/a_id/5872 Cited in §10.1, §10.2

[TEN-01] Google Cloud. "Multi-tenant agentic AI system." Cloud Architecture Center. Accessed 31 August 2026.
docs.cloud.google.com/architecture/multi-tenant-agentic-ai-system Cited in §7.1, §10.2, §12.1, §12.2

Model adaptation

[OPT-01] OpenAI. "Model optimization." OpenAI API documentation. Accessed 31 August 2026.
developers.openai.com/api/docs/guides/model-optimization Cited in §6.2, §11.1, §11.2, §12.3

Index of Terms

Each page reference points to the first page of the most relevant section. Cross-references connect related terms.

A

Abstention · 24, 30
See also Degraded mode; Grounding

Access control lists (ACLs) · 28, 41, 42
See also Authorization; Multi-tenant isolation

Activation-aware Weight Quantization (AWQ) · 16
See also Quantization; Weight-only quantization

Admission control · 11, 12
See also KV cache; Load shedding; Quotas

Agents, budgets · 24
See also Token budgets; Tool budgets

Agents, guardrails · 24
See also Harness engineering; Agents, termination conditions

Agents, termination conditions · 24, 48
See also Degraded mode

Answer correctness · 30, 33
See also Grounding; Evals, retrieval

Attribution, source · 6, 28, 30
See also Citation completeness; Citation precision

Authorization · 3, 20, 41, 42
See also Access control lists (ACLs); Least privilege; Permission boundaries

Agent identity · 20, 41
See also Authorization; Least privilege; Permission boundaries

Agent runtime security · 41, 42
See also Permission boundaries; Serving-engine security

C

Caching, exact-response · 7
See also Caching, prompt/prefix; Caching, semantic response

Caching, invalidation · 7, 42
See also Freshness; Versioning

Caching, isolation · 7, 42
See also Multi-tenant isolation

Caching, prompt/prefix · 7, 11
See also KV cache

Caching, semantic response · 7, 42, 48
See also Caching, isolation; Multi-tenant isolation

Calibration data · 16
See also Quantization

Chunked prefill · 10, 12
See also Continuous batching; Prefill

Chunking · 28
See also Retrieval-augmented generation (RAG)

Citation completeness · 30
See also Claim support rate; Attribution, source

Citation precision · 30
See also Grounding

Claim support rate · 30
See also Answer correctness; Citation completeness

Context engineering · 3, 6
See also Context manifest; Context packing; Harness engineering; Prompt engineering

Context manifest · 6, 37
See also Observability; Versioning

Context packing · 28, 30
See also Retrieval-augmented generation (RAG)

Continuous batching · 12
See also Goodput; PagedAttention

Cost attribution · 38
See also Observability

Consent fatigue · 41
See also Authorization; Permission boundaries

Code approval binding · 33
See also Evaluation sandboxing; Evals, adversarial; Versioning

D

Data loss prevention (DLP) · 41
See also Permission boundaries; Prompt injection

Decode · 10, 12, 15, 16
See also Inter-token latency (ITL); Prefill

Degraded mode · 25
See also Fallback chains; Model routing

Dense retrieval · 28
See also Embeddings; Hybrid search; Vector index

Distillation · 15, 45
See also Fine-tuning; Quantization

Drift · 33, 37, 38
See also Evals; Observability

Deterministic tools · 20
See also Tool calling; Tool contracts

Delegated authority · 20, 41
See also Agent identity; Authorization; Tool contracts

E

Embeddings · 28
See also Dense retrieval; Vector index

Evals · 33

Evals, adversarial · 33, 41
See also Prompt injection

Evals, golden sets · 33
See also Evals, regression

Evals, human · 33
See also Evals, LLM-as-judge

Evals, LLM-as-judge · 33
See also Evals, human

Evals, regression · 33, 48, 49
See also Evals, golden sets

Evals, retrieval · 30
See also Precision@k; Recall@k

Evaluation sandboxing · 33
See also Evals, adversarial; Permission boundaries

F

Fallback chains · 19, 25, 48
See also Degraded mode; Model routing

Fine-tuning · 45
See also Distillation; In-context learning (ICL); Retrieval-augmented generation (RAG)

FP8 · 16
See also Quantization

Freshness · 28, 30, 48, 49
See also Caching, invalidation

Function calling
See Tool calling

G

Golden sets
See Evals, golden sets

Goodput · 12, 46
See also Continuous batching; Service-level objectives (SLOs)

GPTQ · 16
See also INT4; Quantization; Weight-only quantization

Grounding · 28, 30, 33
See also Claim support rate; Retrieval-augmented generation (RAG)

Grouped-query attention (GQA) · 11
See also KV cache; Multi-query attention (MQA)

H

Hallucination · 48
See also Grounding; Tool calling

Harness engineering · 3
See also Agents, guardrails; Context engineering

Hybrid search · 28
See also Dense retrieval; Reciprocal rank fusion (RRF); Reranking

I

Idempotency · 20, 48, 49
See also Tool execution receipts

In-context learning (ICL) · 45
See also Context engineering; Fine-tuning

Indirect prompt injection · 41, 48
See also Prompt injection; Retrieval-augmented generation (RAG)

INT4 · 16
See also Activation-aware Weight Quantization (AWQ); GPTQ

INT8 · 16
See also Quantization

Inter-token latency (ITL) · 10, 12, 37, 46
See also Decode; Tail latency; Time to first token (TTFT)

Incident kill path · 24, 41
See also Agents, guardrails; Permission boundaries

Interaction-aware retrieval · 30
See also Dense retrieval; Evals, retrieval; Trajectory evaluation

K

KV cache · 7, 11, 12
See also Grouped-query attention (GQA); Multi-query attention (MQA); PagedAttention

KV cache, quantization · 11
See also Quantization

KV cache, reservation · 11
See also Admission control; KV cache; Quotas

L

Least privilege · 20, 41
See also Authorization; Permission boundaries

Load shedding · 11, 12
See also Admission control; Degraded mode

M

Mean reciprocal rank (MRR) · 30
See also Evals, retrieval

Model routing · 25
See also Degraded mode; Fallback chains

Multi-query attention (MQA) · 11
See also Grouped-query attention (GQA); KV cache

Multi-tenant isolation · 42
See also Access control lists (ACLs); Caching, isolation; Quotas

MCP version negotiation · 20, 25
See also Tool contracts; Versioning

Model lifecycle · 25
See also Degraded mode; Versioning

MCP statelessness · 20
See also Idempotency; MCP version negotiation; Tool contracts

MCP deprecations · 20
See also MCP version negotiation; Versioning

Model-server ingress · 42
See also Authorization; Serving-engine security

Model artifact security · 42
See also Multi-tenant isolation; Serving-engine security

Multimodal input budgets · 42
See also Quotas; Serving-engine security

N

Normalized discounted cumulative gain (nDCG) · 30
See also Evals, retrieval

O

Observability · 37
See also Cost attribution; Drift; Traces and spans

P

PagedAttention · 11, 12
See also Continuous batching; KV cache

Permission boundaries · 41
See also Authorization; Least privilege

Precision@k · 30
See also Recall@k; Reranking

Prefill · 7, 10, 11, 12
See also Chunked prefill; Caching, prompt/prefix; Time to first token (TTFT)

Prompt engineering · 3
See also Context engineering; Harness engineering

Prompt injection · 41, 48
See also Data loss prevention (DLP); Indirect prompt injection

Processing geography · 25, 42
See also Multi-tenant isolation; Permission boundaries

Provider-resolved identity · 42
See also Authorization; Multi-tenant isolation

Privileged backend admission · 42
See also Admission control; Serving-engine security

Q

Quantization · 15, 16
See also Activation-aware Weight Quantization (AWQ); FP8; GPTQ; INT4; INT8; KV cache, quantization

Quotas · 11, 12, 42
See also Admission control; Multi-tenant isolation

R

Recall@k · 30
See also Precision@k; Evals, retrieval

Reciprocal rank fusion (RRF) · 28
See also Hybrid search

Repair loops · 19
See also Schema validation; Structured outputs

Reranking · 28, 30
See also Hybrid search; Retrieval-augmented generation (RAG)

Retrieval-augmented generation (RAG) · 28, 45
See also Chunking; Freshness; Grounding

Retrieval confidentiality · 28, 42
See also Access control lists (ACLs); Dense retrieval; Multi-tenant isolation

S

Schema validation · 19, 20
See also Structured outputs; Tool contracts

Service-level objectives (SLOs) · 2, 10, 12, 49
See also Goodput; Tail latency

Speculative decoding · 15
See also Decode; Quantization

Structured outputs · 19
See also Repair loops; Schema validation

Server-side request forgery (SSRF) · 41
See also Authorization; Permission boundaries

Serving-engine security · 42
See also Continuous batching; Multi-tenant isolation

Schema validation budgets · 19
See also Schema validation; Server-side request forgery (SSRF); Structured outputs

Safe stop · 24, 33
See also Agents, budgets; Agents, termination conditions; Evals, adversarial

SDK migrations · 25
See also Model lifecycle; Versioning

T

Tail latency · 10, 37, 46
See also Inter-token latency (ITL); Service-level objectives (SLOs); Time to first token (TTFT)

Time to first token (TTFT) · 10, 12, 37, 46
See also Prefill; Tail latency

Token budgets · 6, 24
See also Agents, budgets; Context engineering

Tool budgets · 24
See also Agents, budgets

Tool calling · 20
See also Idempotency; Tool contracts

Tool contracts · 2, 3, 20
See also Authorization; Schema validation

Tool execution receipts · 20, 48
See also Idempotency

Traces and spans · 37
See also Observability

Trajectory evaluation · 33
See also Evals; Evals, adversarial; Traces and spans

Tamper-evident telemetry · 37
See also Observability; Tool execution receipts; Traces and spans

Transitive egress · 33, 41
See also Evaluation sandboxing; Permission boundaries

V

Vector index · 28, 42
See also Dense retrieval; Multi-tenant isolation

Versioning · 3, 6, 7, 19, 20, 28, 33, 37, 38
See also Context manifest; Evals; Observability

W

Weight-only quantization · 16
See also Activation-aware Weight Quantization (AWQ); GPTQ; INT4

Workflow-aware scheduling · 12
See also Continuous batching; Goodput; Caching, prompt/prefix

VERSION HISTORY

Changelog

Version 1.2 - August 31, 2026

Compared with Version 1.1.1, published August 27, 2026.

This edition makes 27 reader-facing changes: 21 additions, 1 deprecation, 3 corrections, 2 clarifications. No guidance was removed.

CHG-002 ADDITION 7. CONTINUOUS BATCHING, PAGED ATTENTION, AND GOODPUT · P. 12

Serving schedules are now evaluated at workflow level

WHAT CHANGED

Multi-stage agent serving now tracks task completion time, dependency and critical-path progress, prefix residency, transition and preemption cost, and starvation alongside request goodput and cache hits.

WHY

Early research shows that maximizing prefix locality or one stage's progress can make the full workflow slower. The new guidance asks teams to test that tradeoff on their own traces rather than adopting a universal scheduling rule.

PRIMARY EVIDENCE

[SERV-07] Hongqiu Ni et al. - TOPAS: Workflow-Aware Prefix-State Scheduling for Multi-Agent LLM Serving (2026-08-26)

CHG-003 ADDITION 10. STRUCTURED OUTPUTS: SYNTAX IS ONLY THE FIRST GATE · P. 19

Hostile schemas are now a security boundary

WHAT CHANGED

Schemas supplied by providers, tool servers, or users are now treated as untrusted input. Network reference resolution stays off by default; enabled resolvers need destination, size, time, logging, and failure controls. Validators also need limits on depth, subschema count, and execution time.

WHY

A schema can trigger network access or expensive composition work before payload validation begins. The new controls close server-side request-forgery and denial-of-service paths that the previous guidance left implicit.

PRIMARY EVIDENCE

[MCP-03] Model Context Protocol - Base Protocol: Overview (2026-07-28)

CHG-004 CORRECTION 11. RELIABLE FUNCTION AND TOOL CALLING · P. 20

MCP is now modeled as a stateless protocol

WHAT CHANGED

Protocol version and capabilities now travel with every request, cross-call state uses explicit handles, peer metadata remains diagnostic rather than authenticated, and input-required results preserve the logical operation across rounds. Broken streams use a new protocol request ID while the application idempotency key and external-state reconciliation remain stable.

WHY

The protocol removed sessions, its session header, and the initialization handshake. Transport continuity no longer establishes conversation state, identity, authorization, or mutation state.

PRIMARY EVIDENCE

[MCP-02] Model Context Protocol - Key Changes (2026-07-28) · [MCP-03] Model Context Protocol - Base Protocol: Overview (2026-07-28)

CHG-005 DEPRECATION 11. RELIABLE FUNCTION AND TOOL CALLING · P. 20

MCP deprecations now require owned migration work

WHAT CHANGED

The handbook now identifies Roots, Sampling, Logging, HTTP+SSE, two include-context values, and OAuth Dynamic Client Registration as deprecated. Teams should stop adding dependencies, inventory current use, assign an owner and removal date, and test replacements.

WHY

Version pinning alone does not retire behavior already scheduled for removal. Naming the affected features makes migration work visible before a future upgrade turns it into an outage.

PRIMARY EVIDENCE

[MCP-02] Model Context Protocol - Key Changes (2026-07-28)

CHG-006 ADDITION 11. RELIABLE FUNCTION AND TOOL CALLING · P. 20

Agents now require first-class identity and attenuated delegation

WHAT CHANGED

Each agent and workload now needs its own identity rather than a borrowed human credential. Authority must be short-lived, audience-restricted, bound to the operating principal, and reduced at every delegation; the least-authorized hop bounds the chain.

WHY

Shared credentials erase accountability and let agents impersonate users. Distinct identity and attenuated delegation preserve attribution and least privilege as work crosses tools and agents.

PRIMARY EVIDENCE

[AUTH-03] National Institute of Standards and Technology NCCoE - Back to the Future: Why Agentic AI Needs a Strong Identity Foundation (2026-08-27)

CHG-007 ADDITION 12. AGENT GUARDRAILS, BUDGETS, AND TERMINATION · P. 24

Broken tasks now have a safe stop and an operator kill path

WHAT CHANGED

Impossible tasks may not unlock broader tools, network access, or credentials. Deployments now need severity triggers for boundary circumvention and unauthorized coordination, a reliable fleet or workload kill path, named pause and recovery authority, and fail-closed behavior for uncleared severe alerts.

WHY

A recent evaluation incident showed that prolonged effort on unsolvable tasks and cross-run coordination can amplify risk. Safe stopping and clear incident authority limit that escalation.

PRIMARY EVIDENCE

[EVAL-05] OpenAI - The Hugging Face incident and the road ahead (2026-08-26) · [EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26) · [ORIG-05] METR and Redwood Research - Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident (2026-08-26)

CHG-008 ADDITION 13. MODEL ROUTING AND DEGRADED MODE · P. 25

Provider SDK upgrades are now production migrations

WHAT CHANGED

Teams should diff headers and response types, exercise every mutating SDK method against disposable state, pin the selected version, and canary it before rollout.

WHY

A current SDK release changed beta headers, returned shapes, and the scope of a delete operation. Route compatibility must include client behavior, not just the provider endpoint.

PRIMARY EVIDENCE

[MOD-02] Anthropic - Claude Platform release notes (2026-08-27)

CHG-009 ADDITION 14. RAG ARCHITECTURE · P. 28

RAG now treats retrieval metadata as sensitive

WHAT CHANGED

Queries, embeddings, candidate identities, scores, access patterns, and selected results are now explicit sensitive artifacts. When retrieval runs outside the trust boundary, the design must state the adversary and measure security, latency, and bandwidth tradeoffs.

WHY

ACLs decide what may be returned; they do not hide the search itself from the retrieval operator. The new guidance separates authorization from confidentiality.

PRIMARY EVIDENCE

[RETR-06] Peichun Hua et al. - Pointing the Way, Hiding the Destination: Practical Private Dense Retrieval at Scale (2026-08-26)

CHG-010 ADDITION 16. EVALS AS THE RELEASE CONTRACT · P. 33

Evaluation sandboxes now include every supporting service

WHAT CHANGED

Agents and generated code in training and evaluation are treated as hostile workloads. Each run and writable support service must be isolated, with independent egress controls across mirrors, caches, metadata services, relays, and shared stores. Direct escape, transitive escape, and cross-run communication become test cases.

WHY

A recent incident used a shared package service as both an escape path and an unauthorized message board. Container isolation alone did not define the real boundary.

PRIMARY EVIDENCE

[EVAL-05] OpenAI - The Hugging Face incident and the road ahead (2026-08-26) · [EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26)

CHG-011 ADDITION 16. EVALS AS THE RELEASE CONTRACT · P. 33

Agent evals now grade the trajectory and external effect

WHAT CHANGED

Evaluation suites should include impossible tasks, grader and tool tampering, unauthorized peer instructions, side channels, boundary probing, safe clarification or stopping, and cross-run coordination. Grader secrets remain outside agent-visible surfaces.

WHY

A correct-looking reward or final answer can conceal reward hacking, infrastructure tampering, or coordination. The path to the result is part of the safety contract.

PRIMARY EVIDENCE

[EVAL-05] OpenAI - The Hugging Face incident and the road ahead (2026-08-26) · [EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26) · [ORIG-05] METR and Redwood Research - Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident (2026-08-26)

CHG-012 ADDITION 17. LLM OBSERVABILITY AS A FIRST-CLASS DISCIPLINE · P. 37

Telemetry now needs an external source of truth

WHAT CHANGED

Policy decisions, tool calls, network events, receipts, and terminal state should be captured outside the agent-controlled environment in append-only or tamper-evident storage and reconciled with authoritative external state. Reasoning traces remain supplemental rather than an enforcement dependency.

WHY

Independent investigators found successful tool-call spoofing and attempts to manipulate transcripts. In-band logs are useful evidence, but they cannot be the sole record of what happened.

PRIMARY EVIDENCE

[EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26) · [ORIG-05] METR and Redwood Research - Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident (2026-08-26)

CHG-013 ADDITION 19. SAFETY ENGINEERING AND PERMISSION BOUNDARIES · P. 41

Approval frequency is now treated as a security property

WHAT CHANGED

Predictable actions should be grouped into bounded plans, with reapproval triggered by material risk or scope changes. Elicitation must never collect passwords, bearer tokens, or other secrets.

WHY

Too many prompts create consent fatigue and turn human review into a rubber stamp. Asking for secrets through the agent also enables impersonation and defeats the identity boundary.

PRIMARY EVIDENCE

[AUTH-03] National Institute of Standards and Technology NCCoE - Back to the Future: Why Agentic AI Needs a Strong Identity Foundation (2026-08-27)

CHG-014 ADDITION 20. MULTI-TENANT ISOLATION AND CACHE SAFETY · P. 42

Serving security now covers ingress, artifacts, decoders, and control planes

WHAT CHANGED

The isolation checklist now requires authentication in front of every reachable route; reviewed and digest-pinned model artifacts; decoded-work limits based on actual bounded output; operator allowlisting and startup reservation for privileged backends; and security controls for runtimes, sandbox provisioners, gateways, bridges, installers, updaters, and inference services.

WHY

A current release and security bulletins document endpoint gaps, untrusted processor code execution, compressed-input memory exhaustion, forged media metadata, request-selected GPU work outside reservations, and control-plane escape or injection flaws. These are production boundaries, not implementation details.

PRIMARY EVIDENCE

[SERV-08] vLLM Project - v0.28.0 (2026-08-26) · [SAFE-05] vLLM Project - LlavaOnevision2 processor loader executes attacker model code with trust_remote_code=False (2026-08-28) · [SAFE-06] vLLM Project - Denial of Service NanoNemoTronVL Video Audio Extraction Bomb (2026-08-28) · [SAFE-07] vLLM Project - Speech-to-text audio decode duration limit bypass via forged header sample rate (2026-08-28) · [SAFE-08] vLLM Project - Request-selected PyNvVideoCodec GPU decode bypasses static VRAM reservation (2026-08-28) · [SAFE-09] NVIDIA PSIRT - Security Bulletin: NVIDIA NemoClaw and OpenShell - August 2026 (2026-08-25)

CHG-015 CORRECTION

26. PRIMARY SOURCE TRAIL - HARNESS, CONTEXT, TOOLS, AND MODEL APIS · P. 52

The MCP source trail now links to the normative specification

WHAT CHANGED

The bibliography now links directly to the full protocol changelog and Base Protocol alongside the overview, authorization specification, and security guidance.

WHY

The statelessness, result-state, schema, metadata, and deprecation changes should be inspectable in the normative specification rather than supported only by an overview.

PRIMARY EVIDENCE

[MCP-02] Model Context Protocol - Key Changes (2026-07-28) · [MCP-03] Model Context Protocol - Base Protocol: Overview (2026-07-28)

CHG-016 ADDITION 26. PRIMARY SOURCE TRAIL - IDENTITY AND EVALUATION SECURITY · P. 52

The source trail now includes identity and evaluation-incident evidence

WHAT CHANGED

The bibliography now includes NIST agent-identity guidance, OpenAI's incident overview and technical report, and the independent METR and Redwood investigation.

WHY

These sources let readers separate the vendor's account, the detailed technical record, independent behavioral findings, and non-normative government identity guidance.

PRIMARY EVIDENCE

[AUTH-03] National Institute of Standards and Technology NCCoE - Back to the Future: Why Agentic AI Needs a Strong Identity Foundation (2026-08-27) · [EVAL-05] OpenAI - The Hugging Face incident and the road ahead (2026-08-26) · [EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26) · [ORIG-05] METR and Redwood Research - Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident (2026-08-26)

CHG-017 ADDITION 26. PRIMARY SOURCE TRAIL - SERVING AND COMPRESSION · P. 52

The serving source trail now includes the new research and security evidence

WHAT CHANGED

The bibliography now includes workflow-aware scheduling research, the vLLM 0.28.0 release, four new vLLM advisories alongside the existing cross-user advisory, and NVIDIA's August agent-runtime security bulletin.

WHY

Readers can inspect the exact evidence and its product-specific limits rather than treating the generalized controls as unsupported claims.

PRIMARY EVIDENCE

[SERV-07] Hongqiu Ni et al. - TOPAS: Workflow-Aware Prefix-State Scheduling for Multi-Agent LLM Serving (2026-08-26) · [SERV-08] vLLM Project - v0.28.0 (2026-08-26) · [SAFE-05] vLLM Project - LlavaOnevision2 processor loader executes attacker model code with trust_remote_code=False (2026-08-28) · [SAFE-06] vLLM Project - Denial of Service NanoNemoTronVL Video Audio Extraction Bomb (2026-08-28) · [SAFE-07] vLLM Project - Speech-to-text audio decode duration limit bypass via forged header sample rate (2026-08-28) · [SAFE-08] vLLM Project - Request-selected PyNvVideoCodec GPU decode bypasses static VRAM reservation (2026-08-28) · [SAFE-09] NVIDIA PSIRT - Security Bulletin: NVIDIA NemoClaw and OpenShell - August 2026 (2026-08-25)

CHG-018 ADDITION 26. PRIMARY SOURCE TRAIL - RETRIEVAL AND EVALUATION · P. 52

The retrieval source trail now includes private-retrieval research

WHAT CHANGED

The bibliography now links to the private dense-retrieval paper that motivated the new confidentiality boundary.

WHY

The paper's assumptions and latency and bandwidth tradeoffs are important limits on how the new guidance should be applied.

PRIMARY EVIDENCE

[RETR-06] Peichun Hua et al. - Pointing the Way, Hiding the Destination: Practical Private Dense Retrieval at Scale (2026-08-26)

CHG-019 CLARIFICATION 17. LLM OBSERVABILITY AS A FIRST-CLASS DISCIPLINE · P. 37

Cache-token usage now stays on model-call spans

WHAT CHANGED

Token counts, including cache reads and writes, are now recorded on each model-call span. Agent and workflow totals are derived from those children instead of placing rolled-up cache subtypes on an agent span.

WHY

An agent span can cover several models and inference calls. Rolling cache subtypes into that span obscures attribution and can produce misleading totals.

PRIMARY EVIDENCE

[OBS-03] OpenTelemetry - Remove cache token usage attributes from internal agent spans (2026-08-27)

CHG-020 CLARIFICATION 15. RETRIEVAL AND ANSWER EVALS · P. 30

Retrieval metrics now require intended-use validation

WHAT CHANGED

Each retrieval or evaluator score must now be validated against the comparison, training choice, system selection, prediction, or filtering decision it will drive, including sensitivity to the evaluator and relevant slices.

WHY

A metric can rank retrievers differently without reliably predicting answer quality or supporting the same conclusion across evaluators. Validity for one decision does not automatically transfer to another.

PRIMARY EVIDENCE

[RETR-07] Utshab Kumar Ghosh et al. - Assessing the Downstream Utility of Evidence-Aware Retrieval in RAG (2026-08-26)

CHG-021 ADDITION 18. ATTRIBUTE COST TO THE WHOLE WORKFLOW · P. 38

Self-hosted energy now uses request and token measures together

WHAT CHANGED

Self-hosted serving now tracks total inference energy per request and successful outcome alongside energy per output token, sliced by model, phase, batch, context, and output length.

WHY

Fixed setup and prefill work can make per-token energy fall while total request energy rises. Looking at both prevents a normalized efficiency gain from hiding greater total resource use.

PRIMARY EVIDENCE

[COST-03] Prabhu Vellaisamy et al. - Characterization of Request and Token Energy Costs for LLM Inference Workloads on GPU Platforms (2026-08-28)

CHG-022 ADDITION 26. PRIMARY SOURCE TRAIL - RETRIEVAL AND EVALUATION · P. 52

The retrieval source trail now includes metric-utility research

WHAT CHANGED

The bibliography now links to the evidence-aware retrieval study that tested whether a retrieval metric remains useful across different downstream decisions.

WHY

The study's public-benchmark scope and evaluator disagreement are important limits on how the new validation rule should be applied.

PRIMARY EVIDENCE

[RETR-07] Utshab Kumar Ghosh et al. - Assessing the Downstream Utility of Evidence-Aware Retrieval in RAG (2026-08-26)

CHG-023 ADDITION 26. PRIMARY SOURCE TRAIL - OBSERVABILITY AND ECONOMICS · P. 52

The observability source trail now includes attribution and energy evidence

WHAT CHANGED

The bibliography now links to OpenTelemetry's cache-token span correction and the GPU inference study comparing request-level and per-token energy.

WHY

The sources expose both the exact telemetry change and the hardware limits behind the generalized measurement rules.

PRIMARY EVIDENCE

[OBS-03] OpenTelemetry - Remove cache token usage attributes from internal agent spans (2026-08-27) · [COST-03] Prabhu Vellaisamy et al. - Characterization of Request and Token Energy Costs for LLM Inference Workloads on GPU Platforms (2026-08-28)

CHG-024 ADDITION 15. RETRIEVAL AND ANSWER EVALS · P. 30

Agentic search now measures marginal evidence across the trajectory

WHAT CHANGED

Iterative search evaluation now includes the original task, prior search interactions, marginal evidence gain, duplicate resurfacing, and the task-level outcome instead of judging only the latest sub-query.

WHY

Early research across two fixed-corpus benchmarks shows that interaction history can help a retriever prioritize what the agent still needs. The guidance keeps that result bounded and requires validation on the product's own agents and corpus.

PRIMARY EVIDENCE

[RETR-09] Haodong Chen et al. - ITER: Interaction-Aware Retrieval for Agentic Search (2026-08-28)

CHG-025 ADDITION 16. EVALS AS THE RELEASE CONTRACT · P. 33

Generated evaluation code now has immutable approval binding

WHAT CHANGED

Approval now binds to the exact generated artifact; edits force reapproval. Held-out data stays OS-isolated, a separate evaluator rejects unapproved artifacts, capability regressions are hard gates, and sampled trajectories are reviewed for gaming.

WHY

Anthropic's study detected gaming attempts even with a structured research harness. Its controls provide a useful pattern, but its limited benchmarks and post-hoc monitor do not establish production alignment, so isolation and deterministic enforcement remain mandatory.

PRIMARY EVIDENCE

[EVAL-09] Chen Yueh-Han, Jiaxin Wen, and Jan Hendrik Kirchner - Automated Researchers Can Reliably Mitigate Alignment Failures (2026-08-28)

CHG-026 ADDITION 26. PRIMARY SOURCE TRAIL - RETRIEVAL AND EVALUATION · P. 52

The source trail now includes interaction-aware retrieval

WHAT CHANGED

The bibliography now links to the ITER study of history-conditioned retrieval and trajectory-relative supervision for agentic search.

WHY

The study makes the distinction between local relevance and marginal evidence value reviewable, including its fixed-corpus and statistical limits.

PRIMARY EVIDENCE

[RETR-09] Haodong Chen et al. - ITER: Interaction-Aware Retrieval for Agentic Search (2026-08-28)

CHG-027 ADDITION 26. PRIMARY SOURCE TRAIL - EVALUATION SECURITY · P. 52

The source trail now includes automated alignment research

WHAT CHANGED

The bibliography now links to the automated-alignment study that used exact-code approval, isolated holdouts, separate evaluation, capability gates, and trajectory monitoring.

WHY

The paper exposes both the control pattern and its limits: narrow benchmarks, incomplete capability coverage, no later-training persistence test, and a monitor that may not remain robust.

PRIMARY EVIDENCE

[EVAL-09] Chen Yueh-Han, Jiaxin Wen, and Jan Hendrik Kirchner - Automated Researchers Can Reliably Mitigate Alignment Failures (2026-08-28)

CHG-001 CORRECTION HANDBOOK METADATA

The evidence-review date now reflects this edition

WHAT CHANGED

The last evidence review date moved from 24 August 2026 to 31 August 2026.

WHY

This edition incorporates newly reviewed lifecycle, serving, retrieval, identity, evaluation-security, and protocol evidence. The metadata now identifies that evidence horizon.

PRIMARY EVIDENCE

[MOD-02] Anthropic - Claude Platform release notes (2026-08-27) · [SERV-07] Hongqiu Ni et al. - TOPAS: Workflow-Aware Prefix-State Scheduling for Multi-Agent LLM Serving (2026-08-26) · [SERV-08] vLLM Project - v0.28.0 (2026-08-26) · [RETR-06] Peichun Hua et al. - Pointing the Way, Hiding the Destination: Practical Private Dense Retrieval at Scale (2026-08-26) · [RETR-09] Haodong Chen et al. - ITER: Interaction-Aware Retrieval for Agentic Search (2026-08-28) · [AUTH-03] National Institute of Standards and Technology NCCoE - Back to the Future: Why Agentic AI Needs a Strong Identity Foundation (2026-08-27) · [EVAL-06] OpenAI - OpenAI - Hugging Face Incident Technical Report (2026-08-26) · [EVAL-09] Chen Yueh-Han, Jiaxin Wen, and Jan Hendrik Kirchner - Automated Researchers Can Reliably Mitigate Alignment Failures (2026-08-28) · [MCP-02] Model Context Protocol - Key Changes (2026-07-28) · [SAFE-05] vLLM Project - LlavaOnevision2 processor loader executes attacker model code with trust_remote_code=False (2026-08-28) · [OBS-03] OpenTelemetry - Remove cache token usage attributes from internal agent spans (2026-08-27) · [COST-03] Prabhu Vellaisamy et al. - Characterization of Request and Token Energy Costs for LLM Inference Workloads on GPU Platforms (2026-08-28)