
CLAUDE DESIGN / FIELD PRACTICE

Claude Design Field Guide

From a living design system to a production-ready handoff



Michael Long

October 2, 2026 | Version 1.0.0 | Review candidate

Orientation

Use this guide to ground a product prototype in existing components, extend a bounded screen, and prepare an engineering handoff. The worked example is a teaching scenario. The October 2 review exercised a local executable example with SDS React primitives; it did not verify Claude Design generation, system sync, export, or native Figma reuse.

Anthropic documents interactive prototyping and a Claude Code handoff in Claude Design. Design is now available in conversations and the Artifacts tab as well as at claude.ai/design. The Claude Code reference describes `/design` more narrowly: it drafts artboards on a canvas. Record the surface you use and test the required interactions and exports there. A generated artboard alone does not prove the prototype journey works. Direct native-Figma export is not established by the reviewed documentation. Use Figma MCP when editable Figma content is required. See the Design getting-started guide and Claude Code artifact guide.

This guide shows how to make that division practical. For product work, start with the current system and screen, then prepare a handoff engineers can inspect. The local exercise uses a synthetic baseline with browser-only persistence and run behavior.

DECISION: The operating model

Use Claude Design for system-grounded exploration and interaction design. Use Claude Code for repository-aware implementation. Add Figma MCP and Code Connect when the team needs native Figma editing, component mappings, or a code-to-canvas loop.

What you will build

The recurring example is **Data Pipeline Studio**, a fictional extension to a teaching baseline at `/pipelines/customer-health/edit`. The current product lets an analyst inspect a linear pipeline and edit one step at a time. The extension adds a directed acyclic graph editor, a richer node inspector, a resizable data sheet, and a file importer with mapping and recovery states.

The guide never treats the example as a blank canvas. The global shell, route, permissions, persistence, run APIs, typography, spacing, forms, buttons, tables, dialogs, notifications, and status patterns already exist. The assignment is to preserve that working product while changing a bounded part of it.

What the guide produces

By the end, you will have:

- A source-of-truth map that says which artifact governs each decision.
- A verified Claude Design system based on Figma's Simple Design System and its React codebase.
- A preservation brief for an existing screen.
- A working prompt sequence for a DAG canvas, node inspector, data sheet, and importer.
- A state matrix covering loading, error, permissions, stale data, conflicts, and recovery.
- A component-to-code map that separates reuse, composition, and legitimate extensions.
- A design review record and evidence gate.
- A Claude Code implementation prompt and handoff README.
- A Figma-native branch for teams that require editable frames.
- A guided capstone, answer key, scoring rubric, and final validation checklist.

How to use the field guide

Read Chapters 1 through 3 before opening Claude Design. Those chapters settle scope, sources, and the design-system baseline. Chapters 4 through 7 are the design loop. Chapters 8 through 10 cover review, handoff, implementation, and drift. The capstone runs the whole sequence with a single feature journey.

Each checkpoint asks for a small artifact. Keep the artifacts together. They become the handoff package; they are not homework that gets discarded after the prototype looks good.

FIELD NOTE: The core discipline

A prototype can look like the product while quietly replacing its components, losing its states, and disconnecting itself from real data. Visual resemblance is only one form of evidence. Traceability, behavior, and recovery paths are the other three.

Before you begin

You need an approved source package, repository access for implementation, and a Figma account for the native-Figma branch. Claude Design is beta on Pro, Max, Team, and Enterprise. Pro, Max, and Team have Design enabled by default; Enterprise owners enable the Design template under Organization settings > Artifacts. Design systems and standalone Claude Design have separate controls. Confirm the intended organization and surface before importing sources. See the Design admin guide.

Claude Code `/design` requires version 2.1.265 or later, an enabled Design template, and an artifact-capable session. Sign in with `/login` using claude.ai. API-key-only sessions cannot publish artifacts, and third-party cloud-provider sessions are unsupported. The artifact guide also lists organization-policy restrictions. Confirm account, provider,


and policy before treating a missing command as a setup defect. See artifact availability.

Uploaded assets persist under the applicable retention policies. Anthropic documents unsupported Design data residency and restrictions for CMEK, ZDR, and HIPAA-ready configurations in the new Artifacts experience. Standalone audit logging and integrated artifact records have different coverage. Confirm those requirements with the organization owner before uploading proprietary work. See the Artifacts admin guide.

For this guide, use the public Simple Design System Community file and Figma's open-source `figma/sds` React repository. Duplicate the Community file into your own drafts before attempting connected inspection or editing. The public source remains untouched.

The workflow at a glance

The work is a loop. Frame the change, ground it in the real system, extend one bounded surface, specify the missing behavior, map every element, hand it off, implement it, and reconcile the rendered result. Drift and new evidence restart the loop.




Rendered evidence and drift restart the loop

Stage	Working tool	Governing evidence	Exit condition
Frame	Team artifact	Product brief, current route, shipped behavior	Scope and preservation boundary approved

Stage	Working tool	Governing evidence	Exit condition
Ground	Claude Design	System code, tokens, representative screens	System test passes
Extend	Claude Design	Current screen plus interaction contract	Proposed flow works end to end
Specify	Claude Design and team review	State matrix, copy, data fixtures, accessibility notes	No critical state is missing
Map	Design and engineering	Component inventory and code paths	Every visible element has a disposition
Hand off	Claude Design to Claude Code	Bundle, README, decision log, acceptance tests	Engineer can implement without guessing intent
Implement	Claude Code and repository tools	Production conventions, tests, rendered application	Tests and visual checks pass
Reconcile	Figma MCP if required	Approved rendered behavior and native Figma file	Drift is logged and resolved

Keep the product surfaces on one state spine

The DAG canvas, node inspector, data sheet, and importer are coordinated views of the same selected node, fixture data, and document state. A change that appears on only one surface is a product defect, even when that surface looks polished in isolation.



REFERENCE MAP

Contents

The chapters move from source authority to rendered proof. Worksheets and appendices remain part of the same operating package.

Orientation ii

1. Decide what is authoritative 1

2. Prepare Simple Design System 10

3. Validate the imported system 18

4. Extend the existing screen 26

5. Design the adjacent surfaces 33

6. Specify states and transitions 41

7. Prove responsive and accessible behavior 49

8. Run the design evidence gate 56

9. Hand off to Claude Code and developers 63

10. Implement, verify, and reconcile 71

11. Guided capstone 79

Capstone answer key 94

Appendix A - Prompt sequence 97

Appendix B - Handoff README template 100

Appendix C - Final validation checklist 104

Appendix D - Simple Design System reference 108

Appendix E - Product boundaries and operating risks 111


Glossary 114

Further reading and source notes 116

CHAPTER 01

Decide what is authoritative

A clean workflow begins by deciding which source governs visual language, behavior, data, and implementation.



The phrase "use our design system" hides several different sources. A Figma library may define component anatomy and variants. A React package may define actual props and accessibility behavior. A shipped screen may reveal composition rules that appear nowhere in documentation. Product code and APIs determine what the interface can really do.

Claude can read several of these sources. It cannot resolve an unspoken conflict between them. The team needs a declared hierarchy before generation begins.

Build the source-of-truth stack

Use five layers:

1. **Production behavior.** The current application, routes, permissions, persistence, data contracts, and tested interaction rules.
2. **Production component code.** The components, props, tokens, accessibility semantics, and imports that engineers can actually ship.
3. **Published design library.** Component anatomy, variants, variables, layouts, and design guidance.
4. **Representative shipped screens.** Evidence for composition, density, hierarchy, responsive behavior, and local conventions.
5. **Product intent.** The approved problem, target user, success journey, non-goals, and acceptance tests for the change.

When two layers disagree, record the conflict. Do not let Claude select a winner through visual improvisation.

EXAMPLE: Data Pipeline Studio

In the teaching baseline, the route, Save, Run, permissions, and persistence are simulated behavior. In a real product extension, the current implementation and API contracts govern those decisions. The Simple Design System React package governs reusable primitives. The duplicated Figma file governs component anatomy and variables. The current Pipeline Detail screen governs shell and density. The capstone brief governs the new DAG journey.

Freeze the preservation boundary

An extension prompt needs two lists: what may change and what must remain stable. The second list is usually more important.

For Data Pipeline Studio, preserve:

- The global app shell and left navigation.
- Breadcrumb, pipeline name, environment badge, and last-run metadata.
- Save, Run, and overflow actions.
- Existing typography, spacing, controls, tables, dialogs, status badges, and notifications.
- Permissions, routing, persistence, and run APIs.
- Current copy outside the approved feature surface.

Change:

- The central linear editor becomes a DAG workspace.
- The right-side editor becomes a schema-driven node inspector.
- The collapsed preview becomes a resizable data sheet.
- The basic file-upload dialog becomes a multi-stage importer.

The boundary lets the team review a small diff. Without it, every generated screen becomes a redesign proposal.

Name the baseline fixture

Claude needs a stable example that can appear in every screen and state. Use one fixture pipeline:

1. `Customers CSV` - source
2. `Normalize Email` - transform
3. `Validate Customer Schema` - quality gate
4. `Publish to Warehouse` - destination
5. `Quarantine Invalid Rows` - proposed branch

Use `customers-august.csv` and its JSON equivalent for one six-record dataset. The importer proposes `customer_id` and `health_score` mappings, but leaves the required `contact_email` to `email` mapping unresolved. The final confirmation accepts all three mappings and the chosen recovery policy. No graph change occurs before confirmation.

CSV row	Customer ID	Raw contact_email	Raw health_score	Expected result
2	C001	`ALICE@EXAMPLE.COM`	82	Publish as `alice@example.com`
3	C002	`bob@example.com`	65	Publish as `bob@example.com`
4	C003	`invalid-email`	50	Invalid email
5	C004	empty	77	Email is required
6	C005	`eve@example.com`	`not-a-number`	Invalid health_score
7	C006	`FRANK@EXAMPLE.COM`	91	Publish as `frank@example.com`

`Normalize Email` trims outer whitespace and lowercases all six emails. The schema gate requires a nonempty unique customer ID, an email with a domain suffix, and a numeric health score from 0 to 100. Three records pass. C003, C004, and C005 go to quarantine or are excluded

under Reject invalid rows. CSV row numbers include the header; JSON uses the corresponding record ordinal plus one. A production parser must track physical file locations separately, including blank and multiline records.

Use the executable teaching contract

Start from the preserved linear baseline at `/pipelines/customer-health/edit?baseline=1`. Open the extension at the same route without the query. Preserve the shell text, navigation, pipeline identity, environment badge, Save, Run, permissions, and browser persistence. This baseline was authored for the exercise; it is not a shipped product or a Claude Design export.

1. Choose the fixture through the file picker or drop zone. Confirm `contact_email -> email` and all proposed mappings. Choose Send to quarantine for the main journey.
2. Confirmation replaces the unconfigured `Customers CSV` placeholder with a new source ID, `august`, named `Customers CSV (August import)`. It preserves downstream nodes, removes the placeholder's old edge, selects the new source, and opens its raw preview. Import is atomic; cancel or failure leaves the graph unchanged. The local exercise supports one committed import per reset.
3. Connect `august` to `normalize`. The normalized preview contains the same six customer IDs. Add `quarantine`, then connect `validate` to `quarantine`. Keep `normalize -> validate -> warehouse` intact.
4. Save before Run. The configured warehouse target starts as `missing-warehouse`, so the intended first run fails at `warehouse`. The fixture's required target is `customer_health`; a helper hint must not claim it is already configured. Preserve the failure across reload.
5. Select the failing node, set its target to `customer_health`, Save, and Run again. Expect three published IDs (C001, C002, C006), three quarantined IDs (C003, C004, C005), and zero rejected rows. Under Reject invalid rows, expect three published, zero quarantined, and three rejected.

6. Attempt `validate -> august` and `normalize -> quarantine`. The first would create a cycle; the second has incompatible ports. Each attempt must explain the reason and leave the graph unchanged. Deleting a required downstream edge must block Run.

Save failure must preserve the draft and keep Run disabled until Save succeeds. The local conflict control changes only a simulated revision; explicit reapply is safe for that fixture. A real concurrent edit needs a content comparison and reviewed merge. Warehouse lookup, row publication, quarantine storage, server authorization, and telemetry remain implementation requirements.

The local example exercises buttons, inputs, selects, dialogs, tags, and tables from a pinned SDS React snapshot. Its named connection list supplies the non-pointer graph path. Pointer port dragging, drawn edge geometry, virtualized large datasets, resizable columns, a complete schema-driven inspector, and screen-reader behavior remain separate acceptance work. Local screenshots and passing tests do not establish that Claude Design produced the workflow.

Define the success journey

The recurring journey is:

1. Open the existing pipeline.
2. Import `customers-august.csv`.
3. Resolve one required column mapping.
4. Create a source node from the import.
5. Connect it to `Normalize Email`.
6. Inspect transformed rows in the data sheet.
7. Add a quarantine branch for invalid records.

8 Save and run the pipeline.

9 Identify and repair a failed node.

10 Run the pipeline successfully.

Every surface in the guide serves this journey. Anything else is either a reusable system concern or a non-goal.

Write the first artifact: the extension brief

Use a one-page brief with these fields:

- Current route and baseline screen.
- Primary and secondary users.
- User problem and job to complete.
- Success journey.
- Change boundary.
- Preservation boundary.
- Supported viewports.
- Data fixture.
- Existing behavior that cannot regress.
- Open product decisions.
- Approval owner for each decision.

CLAUDE DESIGN / BASELINE ANALYSIS

```
You are preparing to extend an existing production screen. Do not
generate a new design yet.

Review the attached current screen, route context, relevant code, and
design-system sources. Produce:

1. a factual inventory of the current screen,
2. the visible component and layout patterns,
3. the behaviors and regions that should be preserved,
4. ambiguities or source conflicts,
```

CLAUDE DESIGN / BASELINE ANALYSIS

```
5. a proposed change boundary for the requested feature.

Separate direct observations from inferences. Do not invent missing
behavior. End with the questions that require a product, design, or
engineering owner.
```

Extension brief

Current route and screen

Primary user and job

Success journey

May change

Extension brief
Must remain stable
Supported viewports
Data fixture
Open decisions and owners

Chapter checkpoint


- The team can point to the authoritative source for behavior, components, Figma anatomy, and product intent.
- The existing screen has a named preservation boundary.
- One fixture carries through the complete journey.
- Non-goals are explicit.
- Claude has analyzed the baseline without generating a replacement screen.

Sources 1-4, 18-20. Author synthesis: the source-of-truth method.

CHAPTER 02

Prepare Simple Design System

Turn a public design kit and its React library into a compact, inspectable source package.



Simple Design System is a useful teaching source because the Figma library and React codebase were designed to work together. The repository includes variables, styles, primitives, compositions, icons, Storybook stories, and Code Connect mappings. It also exposes the limits of the example: it is a responsive web foundation, not a ready-made graph editor.

Duplicate before you connect

Open the Simple Design System Community file and choose **Make a copy**. Work in the copy. Figma MCP can read content the authenticated account has permission to view or edit; native writing to an existing file requires edit permission and a Full seat. The August research account could not inspect the Community source through its connected tools. That historical denial does not establish an editor-only rule for all reads. Confirm the current account and working-file access separately. See Figma access and permissions and write to canvas.

Keep the original source URL in the project record:

```
https://www.figma.com/design/AIulMBySUibjRtykdngCUp/Simple-Design-System--Community-?node-id=3-5
```

Record the duplicate's file URL separately. Do not overwrite the original URL in source notes; the two links serve different purposes.

FIELD NOTE: Why the copy matters

The public Community file is the provenance source. The duplicate is the working file. Connected agents need permissions on the working file, and your edits should never change the public source.

Pair the Figma file with the codebase

Use Figma's public `figma/sds` repository as the code counterpart. The project identifies itself as an alpha base system that demonstrates Variables, Styles, Components, Code Connect, and a React implementation.

The code is organized into:

- `src/ui/primitives` - reusable controls that should not be reduced further.
- `src/ui/compositions` - example arrangements of primitives.
- `src/ui/layout` - Flex, Grid, and Section helpers that may not have direct Figma equivalents.
- `src/ui/icons` - generated icon components.
- `src/figma` - Code Connect mappings.
- `src/stories` - Storybook examples and component states.
- `src/theme.css` - generated CSS variables from Figma tokens.

Inventory the components you can reuse

The August code inspection identified these primitives. Confirm them in the selected repository revision:

Product need	Existing Simple Design System material	Disposition
Save, Run, cancel, confirm	Button, IconButton	Reuse
Node settings fields	InputField, SelectField, TextareaField, CheckboxField, RadioGroup, SwitchField, SliderField	Reuse
Field errors and descriptions	Field, Label, Description, FieldError, Fieldset	Reuse
Inspector sections	Accordion, Tabs, Text	Reuse or compose
Table preview	Table, Pagination, Search, Tag	Reuse and compose
Menus and overflow actions	Menu, ListBox, Tooltip	Reuse

Product need	Existing Simple Design System material	Disposition
Confirmations and blocking flows	Dialog	Reuse
Status and feedback	Notification, Tag, icons	Reuse and compose
Shell navigation	Navigation, Headers, Flex, Grid, Section	Reuse where the current app already uses them
DAG nodes, ports, edges	No direct primitive	Proposed product-specific components
Resizable data sheet	No direct primitive	Proposed composition using existing primitives
File drop zone and mapping row	No direct primitive	Proposed composition or product component

The inventory prevents two opposite mistakes: inventing controls the system already has, and forcing an application-specific graph element into a generic primitive.

Inventory the tokens

Simple Design System exposes semantic color families for background, border, icon, and text across brand, default, neutral, positive, warning, danger, disabled, and utility roles. Its spacing scale runs from `space-050` through large layout values; radius, focus-ring stroke, icon sizes, and typography scales are also defined.

Use semantic tokens rather than literal values in every prompt and handoff. A node failure should resolve to the system's danger roles. A selected node may use the brand border and focus-ring rules. A canvas grid may require one new semantic token, but the grid should still derive from existing neutral primitives.

Build a compact context packet

Claude Design can import a repository, but a focused package is easier to validate than an entire monorepo. Include:

- The duplicated Figma working-file link.
- `src/ui/primitives`, `src/ui/layout`, and only the relevant compositions.
- `src/theme.css` and token-generation notes.
- Relevant `src/figma` Code Connect files.
- Relevant Storybook stories.
- The current Pipeline Detail route and nearby tests.
- Two or three representative shipped screens.
- The extension brief and fixture schema.

Exclude:

- `.git`, `node_modules`, build output, generated caches, and unrelated packages.
- Deprecated components.
- Concept work that does not match production.
- Screens containing private customer data.
- Large asset folders that do not affect the target feature.

Connect Code Connect after duplication

The Simple Design System README still documents `documentUrlSubstitutions` in `figma.config.json` and expects a fresh duplicate to preserve node IDs. Verify sample IDs in the chosen copy, then update the file keys. Record the repository revision and mapping format before validating.

Code Connect is documented for Dev or Full seats on Organization and Enterprise plans. The current CLI quickstart recommends framework-agnostic template files; existing SDS mappings remain inputs from their own repository revision. Do not migrate parsers or publish mappings merely to run the example. Follow the team's approved process if mapping publication is authorized. The CLI requires Node.js 18 or newer and a locally stored token with Code Connect Write and File content Read scopes. See the Code Connect introduction and CLI quickstart.

Code Connect can supply imports, properties, snippets, source paths, and team instructions. CLI mappings and UI mappings provide different detail: a CLI mapping can omit an import when its source/import fields are missing, and UI mappings do not include full snippets by default. Inspect one returned mapping before relying on it. Keep mappings current. See Code Connect integration.

CLAUDE CODE / INSPECT THE SYSTEM PACKAGE

```
Inspect the attached Simple Design System package and the current
Pipeline Detail implementation. Do not edit files.

Return four inventories:

1. production components available for reuse, with import paths and
relevant props,
2. semantic tokens available for color, spacing, typography, radius,
and focus,
3. current screen composition and state-management patterns,
4. missing product-specific patterns required by the Data Pipeline
Studio brief.

For every proposed missing pattern, explain why existing primitives
cannot cover it through composition. Flag any difference between Figma
naming, Code Connect mapping, and production code.
```

Design-system intake
Working Figma file and owner
Code package and revision

Design-system intake
Token source and generation path
Relevant primitives
Relevant compositions
Code Connect status
Known gaps

Design-system intake
Excluded or unsafe sources

Chapter checkpoint


- The Community source is untouched and a working duplicate exists.
- The Figma file and React package are paired.
- Components, tokens, Storybook examples, and Code Connect mappings are inspectable.
- The context package excludes unrelated or unsafe material.
- DAG-specific gaps are named before generation.

Sources 2, 6-12, 18-25. Native identity remains unverified.

CHAPTER 03

Validate the imported system

Test the system on known screens before trusting it with a new feature.



Claude Design can extract a reusable system from codebases, design files, screenshots, decks, and brand assets. The useful question is not whether extraction ran. The useful question is whether a generated screen resolves back to the system the team ships.

Validate the system before asking for Data Pipeline Studio.

Establish the system in Claude Design

Choose the setup path that matches the source. For a React product system, the current Claude Code command reference documents `/design-login` to authorize design-system access and `/design-sync [hint]` to convert and upload the repository's system to Claude Design. First-time verification can take hours for a large repository. Treat conversion and upload as part of the operation; scope the source package before running it. These commands require the Anthropic path and claude.ai access, and are unavailable through the documented cloud-provider and apps-gateway paths.

For a brand system, use chat with approved fonts, logos, files, and design references. Manage integrated systems in Settings > Design systems. A system created at claude.ai/design can move through the Design sidebar's migration banner, but the migrated guide, tokens, and components need review. See the design-system setup guide.

Standalone setup remains a separate path: select the organization at claude.ai/design, upload or link approved assets, review the generated system, and test it before using the Published toggle. In integrated Artifacts, confirm the attached system and selected organization default. Publishing a system and setting a default are separate decisions. Enterprise administrators can reserve publication, default selection, and deletion for designated users. See the Artifacts admin guide.

The August guide required manual registration of the Claude Design MCP endpoint. Current reviewed setup instructions use the built-in commands and do not establish that registration as a prerequisite. Omit

it from the default path; this is not a claim that the endpoint has been retired. If a command is absent or authorization fails, record the installed version, account/provider, enabled template, and exact error before changing configuration.

Use `/design [brief]` for the documented Claude Code artboard workflow. Inspect the returned artifact in a desktop browser. Test whether the chosen surface supports the interactive states your product example needs; broad Design help and the CLI reference describe different scopes. Do not infer complete import/export/sync parity from the command name.

Do not paste private tokens into chat or commit local credentials. Follow the repository's existing secret-handling rules.

Preserve the reviewed baseline

Anthropic documents asking Claude to save the current project before trying another direction, but also lists version history as unavailable. Export a reviewed baseline, record its date and system revision, and verify that the saved artifact opens before experimenting. Treat reliable restore and correction persistence as tests, not assumptions. See Design revisions and limitations.

Give sources a clear authority order

CLAUDE DESIGN / CREATE THE DRAFT SYSTEM

```
Build a draft design system from the attached sources.

Treat the component-library code and design tokens as authoritative.
Use the attached shipped screens to learn composition and product
patterns. Use the Figma file for component anatomy, variants,
variables, and layout intent.

Preserve existing component, token, and pattern names exactly.
Separate:

1. directly observed components and tokens,
2. inferred composition patterns,
3. missing or ambiguous areas.

Do not silently invent a component. Label any missing pattern as a
proposed addition. Generate a settings screen, a dense operational
table, and a confirmation flow. Record the selected system and source
revision. Keep the system in draft; publication and
organization-default changes need owner approval.
```

Run three known-screen tests

Choose tests that expose different parts of the system:

1. **A settings form** tests fields, labels, descriptions, errors, toggles, actions, and vertical rhythm.
2. **A dense operational table** tests data density, search, filters, pagination, status, empty states, and overflow.
3. **A confirmation flow** tests dialog anatomy, destructive language, focus handling, and notification behavior.

Do not judge the tests from memory. Compare them to the components, tokens, and representative screens in the source package.

Score system fidelity

Use a ten-point sample on each test screen. Select visible elements across the page and classify each one:

- **Exact reuse** - correct component, variant, token, and composition.
- **Valid composition** - existing primitives combined according to known patterns.
- **Cosmetic match** - looks close but does not resolve to an approved component or token.
- **Invented** - no source evidence and no explicit proposal label.
- **Unverifiable** - source package is insufficient.

The system passes when every sampled element is exact reuse or valid composition, or when an exception is explicitly documented and approved. A visual match with unverifiable implementation identity does not pass.

Test correction behavior

Deliberately introduce one correction: ask Claude to replace an invented filter control with the named `SelectField` and existing Tag pattern. Then regenerate a nearby state. If the correction holds only on one frame and disappears in the next, the system is not stable enough for feature work.

CLAUDE DESIGN / CONFORMANCE AUDIT

```
Audit the generated test screens against the linked design system and
codebase.

For every visible element, classify it as:

- reused existing component,
- existing component with an approved variant,
- composed from existing primitives,
- proposed new component,
```

CLAUDE DESIGN / CONFORMANCE AUDIT

```
- unverified.

Correct token, typography, spacing, radius, color, and component
deviations. List anything you could not verify from the sources. Do not
describe the system as production-ready. Produce a short validation
report for the design lead.
```

Decide whether to publish

Publish the organization system only when:

- Component names and variants match the source.
- Semantic tokens are used consistently.
- Known-screen composition matches the product.
- Corrections persist across regeneration.
- Missing patterns remain visibly labeled.
- A design-system owner has reviewed the output.

If the system fails, improve the sources before adding more prompt detail. Claude's own documentation says import quality depends on source quality. Prompting cannot repair an ambiguous or contradictory system indefinitely.

FIELD NOTE: Large repositories

Attach the focused component and feature directories for a large monorepo. Anthropic warns that very large repositories can cause lag or browser instability. Smaller context also makes component identity easier to audit.

System validation record

Test screen and source comparator

System validation record
Sampled elements
Exact reuse count
Valid composition count
Cosmetic-only or invented count
Unverifiable count
Correction test and result

System validation record
Decision and reviewer

Chapter checkpoint


- The imported system has been tested on known work, not only on a new concept.
- Component identity and token use have been sampled.
- One correction has persisted through regeneration.
- Missing patterns are explicit.
- A human owner has approved publication or recorded why it remains a draft.

Sources 1-4, 11, 19-20. Product-preservation synthesis.

CHAPTER 04

Extend the existing screen

Generate a bounded diff, then build the DAG flow one interaction at a time.



The first feature prompt should describe an extension, not a destination. Claude needs the baseline screen, the preservation boundary, the exact route, and a narrow first change.

Start from the current route

Create a Claude Design project with the validated system attached. Add the current Pipeline Detail screen as a screenshot, existing design asset, web capture, or linked code reference. Include the relevant feature directory and current tests.

CLAUDE DESIGN / EXTEND PIPELINE DETAIL

```
Extend the existing `/pipelines/customer-health/edit` screen into the
first version of Data Pipeline Studio.

Starting context:

- current screen: the attached Pipeline Detail baseline,
- relevant code: the attached route, shell, editor, preview, and test
files,
- existing components: the linked Simple Design System package,
- target viewport: 1440 x 900, with a supported minimum of 1024 x 768,
- mobile: view-only and out of scope for editing.

Preserve the global shell, navigation, breadcrumb, pipeline identity,
environment badge, last-run metadata, Save, Run, overflow actions,
permissions, routing, persistence, and run behavior. Preserve the
existing typography, spacing, forms, tables, dialogs, status, and
notification language.

Replace only the central linear step list with a DAG workspace. Keep
the current right-side configuration panel and collapsed data preview
in place for this first pass.

Use the fixture pipeline: Customers CSV -> Normalize Email -> Validate
Customer Schema -> Publish to Warehouse. Add a proposed branch from
Validate Customer Schema to Quarantine Invalid Rows.
```

CLAUDE DESIGN / EXTEND PIPELINE DETAIL

```
Reuse named system components. Label every proposed component or token.
Produce one interactive desktop prototype and a short change log. Do
not redesign unrelated regions.
```

Review the first diff

The first review asks five questions:

1. Did the shell remain stable?
2. Did the central editor change without moving unrelated controls?
3. Are the pipeline steps the same fixture throughout?
4. Can the user select a node and understand the graph direction?
5. Are new graph elements labeled as proposals rather than disguised system components?

Reject the first pass if the answer to either of the first two questions is no. A prettier shell is still scope drift.

Add graph behavior in small increments

The DAG interaction contract includes:

- Pan, zoom, fit-to-view, and reset.
- Pointer and keyboard node selection.
- Node movement without changing pipeline semantics.
- Edge creation between compatible ports.
- Cycle rejection and incompatible-connection explanations.
- Undo and redo for movement, connection, and deletion.
- Inspectable nodes while a run is active, with structural edits locked.
- Status communicated through icon, label, and color.

Add one group at a time. After each change, replay the baseline journey and inspect the preservation boundary.

CLAUDE DESIGN / ADD CANVAS NAVIGATION

```
Keep the approved screen and fixture unchanged. Add only canvas
navigation: pan, zoom in, zoom out, fit to view, and reset. Use
existing IconButton and Tooltip patterns for controls. Show visible
keyboard focus and accessible labels. Do not add node editing or
connection behavior yet.
```

CLAUDE DESIGN / ADD SELECTION AND MOVEMENT

```
Keep all approved regions unchanged. Add pointer and keyboard node
selection, a visible selected state, and node movement. Moving a node
changes layout only; it must not change graph semantics. Show a dirty
document state after movement and include undo and redo using existing
action patterns.
```

CLAUDE DESIGN / ADD CONNECTIONS AND REJECTION

```
Add input and output ports plus edge creation between compatible nodes.
Use the existing fixture. Demonstrate one valid connection, one
incompatible connection, and one attempted cycle. Rejected actions
must leave the graph unchanged and explain why the connection is
invalid. Use icon, label, and color for status. In this fixture,
attempt `validate -> august` for a cycle and `normalize -> quarantine`
for a type mismatch; neither may change the graph. Keep every other
surface unchanged.
```

Define proposed graph components

Do not add a generic "Card" variant for a graph node merely because both are rectangles. A pipeline node has operational semantics, ports, selection, validation, execution states, and keyboard behavior. Treat it as a product-specific component composed from system primitives.

Proposed component	Required variants or states	Reused foundation
`PipelineNode`	Source, transform, quality, destination; idle, selected, running, success, warning, failed, disabled	Text, Tag, Tooltip, icons, semantic tokens
`PipelinePort`	Input/output; compatible/incompatible; connected/unconnected; focused	Tooltip, focus-ring and semantic tokens
`PipelineEdge`	Default, selected, transferring, warning, failed	Semantic tokens; no color-only meaning
`CanvasToolbar`	Default, disabled actions, keyboard focus	IconButton, Tooltip, ButtonGroup pattern
`RunProgressSummary`	Queued, running, partial failure, success, cancelled	Notification, Tag, progress copy

Each proposed component needs a design owner, a code owner, a variant model, accessibility notes, and a production import path before the team promotes it to a shared library.

Compare alternatives without multiplying scope

Use alternatives for a specific decision, such as node density or branch readability. Do not ask for three complete product redesigns.

CLAUDE DESIGN / COMPARE NODE DENSITY

```
Before generating alternatives, export the approved baseline, record
the source revision and date, and confirm the export opens. Keep that
artifact intact. Then create two alternatives for `PipelineNode`
density only:

- compact: optimized for large graphs,
- detailed: exposes key configuration and last-run status.

Preserve the shell, canvas dimensions, fixture, inspector, and data
preview. Use the same components and tokens in both. Compare
scanability, graph capacity, error visibility, and keyboard focus.
Recommend one default and one zoom-level rule.
```

DAG review
Preserved regions verified
Graph direction and fixture
Navigation behavior
Selection and movement
Valid connection behavior

DAG review
Cycle and incompatibility rejection
Undo and redo
Proposed component disposition
Open decisions

Chapter checkpoint


- The baseline shell remains intact.
- The DAG uses the same pipeline fixture and real product language.
- Navigation, selection, movement, connections, and rejection are shown.
- Proposed graph components are visible in the system delta.
- Undo, keyboard focus, and running-state locks are part of the design.

Sources 1-3, 19. Prompts are author synthesis.

CHAPTER 05

Design the adjacent surfaces

Complete the inspector, data sheet, and importer without creating three separate products.



A graph alone does not complete the job. Data Pipeline Studio also needs a configuration surface, a data-inspection surface, and an importer. The surfaces share one selected node, one fixture, and one document state.

Upgrade the node inspector

Selecting a node opens its schema-driven configuration. The inspector must:

- Load the correct schema for the selected node.
- Show valid, dirty, invalid, testing, success, failure, and locked states.
- Preserve valid drafts when the user switches nodes.
- Warn before discarding invalid edits.
- Block Save when required fields are invalid and link the error summary to the affected controls.
- Run **Test node** against the fixture data without running the complete pipeline.
- Use the existing confirmation-dialog pattern for destructive actions.

CLAUDE DESIGN / EXTEND THE NODE INSPECTOR

```
Keep the approved DAG and shell unchanged. Replace the existing
right-side step editor with a schema-driven node inspector for the
selected node.

Reuse InputField, SelectField, TextareaField, CheckboxField,
SwitchField, FieldError, Accordion, Tabs, Button, Dialog, and
Notification patterns from the linked system where appropriate.

Show these states for `Validate Customer Schema`: no selection, loading
schema, pristine, dirty, one required-field error, testing, test
success, test failure, and locked during a pipeline run. Switching to
another node must preserve a valid draft and warn before discarding an
invalid one.

Annotate the state transitions and the data each action reads or
writes. Do not change the graph layout or application shell.
```

Turn the preview into a data sheet

The data sheet is a resizable bottom surface with collapsed, half, and expanded positions. It shows the selected node's actual input or output fixture. It supports column resizing, sorting, filtering, and cell inspection.

The sheet must distinguish:

- Live data.
- Cached data.
- Stale data.
- Truncated data.
- Sample data.
- No available data.
- Load failure.

The distinction needs language and status treatment. A green dot with no label is not sufficient.

CLAUDE DESIGN / ADD THE DATA SHEET

```
Keep the approved shell, DAG, and inspector unchanged. Replace the
collapsed preview with a resizable data sheet using existing Table,
Search, Tag, Pagination, IconButton, Tooltip, and Notification
patterns.

Support collapsed, half, and expanded positions. Show the output of
`Normalize Email` from the shared fixture. Include column resizing,
sorting, filtering, and a cell detail interaction.

Create separate states for loading, rows, empty, truncated, stale, and
error. Label whether the data is live, cached, stale, truncated, or
sample. Selecting an error row should focus the responsible node.
Annotate the connection between node selection and the rows displayed.
```

Extend the importer

The importer accepts CSV and JSON through a file picker or drop zone. It should:

- Show parsing progress and allow cancellation.
- Infer headers and types without silently committing them.
- Require mapping for mandatory fields.
- Identify malformed rows by row and column.
- Offer **Reject invalid rows** or **Send to quarantine**.
- Create a configured source node after a successful import.
- Open the imported data in the preview.

Use a staged flow because the user is making a series of consequential choices. A single overloaded dialog makes progress, validation, and recovery difficult to read.

CLAUDE DESIGN / EXTEND THE IMPORTER

```
Extend the existing file-upload dialog into a staged CSV and JSON
importer. Keep all approved product surfaces unchanged.

Use `customers-august.csv` as the fixture. Use the exact six rows from
Chapter 1. Require explicit confirmation of `contact_email -> email`
and the proposed customer ID and health-score mappings. Preserve the
three valid and three invalid record identities across every surface.

Show these stages and states:

1. initial file picker and drop zone,
2. drag-over,
3. parsing with progress and cancel,
4. inferred headers and types pending confirmation,
5. required mapping unresolved,
6. malformed rows with row and column references,
7. the choice to reject invalid rows or send them to quarantine,
8. ready to import,
9. importing,
10. partial success,
```

CLAUDE DESIGN / EXTEND THE IMPORTER

```
11. success that creates a configured source node and opens its
preview,
12. cancelled and failed.

Reuse existing Dialog, Button, Input, Select, Table, Notification,
Tag, and progress patterns. Mark FileDropzone and ColumnMappingRow as
proposed compositions if no approved pattern exists. Do not silently
accept inferred mappings.
```

Make the surfaces agree

After designing the three surfaces, run a cross-surface review:

- The selected node in the DAG matches the inspector title and data sheet source.
- Dirty state appears once at the document level and is explained locally where needed.
- Import success creates the same source node that appears in the graph.
- Mapping errors use the same field-error language as the inspector.
- A data-sheet error row focuses the exact failed node.
- Running-state locks are consistent across graph, inspector, importer, and Save actions.
- The data sheet never displays unrelated placeholder rows.

CLAUDE DESIGN / CROSS-SURFACE CONSISTENCY AUDIT

```
Audit the approved DAG, node inspector, data sheet, and importer as one
product state.

Trace the shared fixture from file selection through mapping,
source-node creation, transformation preview, schema validation,
quarantine routing, Save, Run, failure, repair, and successful re-run.

Identify every point where node selection, dirty state, run state,
fixture data, status language, or permissions disagree across
surfaces. Correct only those inconsistencies. Preserve all approved
layout and component decisions. Return a short before-and-after change
log.
```

CLAUDE DESIGN / CROSS-SURFACE CONSISTENCY AUDIT

Adjacent-surface review

Selected node consistency

Inspector state coverage

Data provenance labels

Data sheet interactions

Adjacent-surface review

Importer stages

Mapping and malformed-row recovery

Cross-surface dirty and run states

Proposed compositions

Chapter checkpoint


- The inspector, data sheet, and importer share one fixture and state model.
- The system's existing form, table, dialog, status, and feedback patterns are reused.
- Proposed product patterns are explicit.
- Import success creates a real graph consequence.
- Error rows, fields, and nodes link to one another.

Sources 1-3, 11. The local exercise is tested; Design workflow remains unverified.

CHAPTER 06

Specify states and transitions

Turn a convincing happy path into a complete product contract.



Generated prototypes often appear complete because the default state is coherent. Production work fails at the transitions: data arrives late, permission changes, Save conflicts, imports partially succeed, and runs stop between nodes.

A state matrix makes those transitions reviewable before they become implementation bugs.

Build the product state matrix

Surface	Required states
Document	Loading, pristine, dirty, saving, saved, save failed, read-only, version conflict
Canvas	Empty, populated, invalid graph, executing, stale, load failed
Node	Idle, hover, focused, selected, dragging, disabled, invalid, queued, running, success, warning, failed
Inspector	No selection, loading schema, valid, dirty, field error, testing, test success, test failed, locked
Data sheet	Closed, loading, rows, empty, truncated, stale, error
Importer	Initial, drag-over, parsing, mapping required, invalid rows, ready, importing, partial success, success, cancelled, failed
Run	Ready, validating, queued, running, partially failed, failed, cancelled, succeeded
Permissions	Editable, view-only, action forbidden, session expired

The matrix is not a request for one frame per cell. Use representative screens, component states, and annotated transitions. The goal is to prove coverage without burying the team under artboards.

Write transitions as contracts

For each consequential action, specify:

- **Trigger** - what the user or system does.
- **Precondition** - what must already be true.
- **Immediate feedback** - what changes before the result returns.

- **Success result** - data, UI, focus, and status.
- **Failure result** - what remains stable and what recovery appears.
- **Persistence** - what survives navigation or reload.
- **Telemetry** - the event or error the product records.

Example:

Field	`Create edge` **contract**
Trigger	User drags from an output port to an input port or uses the keyboard connect command
Precondition	Ports are compatible, user can edit, graph is not structurally locked
Immediate feedback	Connection preview and compatible targets appear
Success	Edge is added, document becomes dirty, focus moves to the new edge or destination node
Failure	Graph remains unchanged; explanation names cycle, type mismatch, permission, or lock
Persistence	Edge exists after Save and reload; rejected attempt does not
Telemetry	`pipeline_edge_created` or `pipeline_edge_rejected` with reason

Use named evidence for each state

Every state should connect to one of these evidence types:

- A current production pattern.
- A design-system component or token.
- A product requirement.
- An API or data contract.
- An accessibility requirement.
- A recovery rule.

If a state has only visual evidence, it is not ready for handoff.

CLAUDE DESIGN / COMPLETE THE STATE MODEL

```
Extend the approved prototype to cover the complete state model without
changing approved layout or components.

Use the supplied state matrix. For each surface, show the minimum
representative frames or component variants needed to prove coverage.
Annotate transitions rather than duplicating screens when that is
clearer.

For every consequential action, state the trigger, precondition,
immediate feedback, success result, failure result, persistence rule,
and recovery action. Preserve the shared fixture and real product
language. Mark any state that depends on an unresolved API or product
decision.
```

Specify version conflicts and stale data

Two failure modes deserve explicit treatment:

Version conflict. Another person or process changes the pipeline after the user begins editing. The product must not overwrite the newer version silently. Show what is compared, what can be reapplied, what must be reviewed, and how the user exits safely.

Stale preview. The graph or node configuration changes after preview data was generated. The data sheet must keep the rows inspectable while clearly marking them stale and offering a refresh. "Sample" and "stale" are different conditions and should not share ambiguous copy.

CLAUDE DESIGN / CONFLICT AND STALE-DATA RECOVERY

```
Using the approved Data Pipeline Studio design, add two recovery
sequences:

1. a Save version conflict after another editor changed the pipeline,
2. a stale data preview after the selected node configuration changed.

Preserve the user's work. Show the comparison or refresh action, the
```

CLAUDE DESIGN / CONFLICT AND STALE-DATA RECOVERY

```
exact status language, focus behavior, and the safe exit. Reuse
existing Dialog and Notification patterns. Do not use a generic
destructive confirmation for a merge decision.
```

Keep copy operational

Error copy should answer four questions:

1. What happened?
2. What was preserved?
3. What can the user do next?
4. Where can they get more detail?

Avoid messages such as "Something went wrong" when the product knows the failed node, row, column, connection reason, or permission rule.

Weak	Operational
Invalid connection	`Validate Customer Schema` cannot connect to `Customers CSV` because the connection would create a cycle. The graph was not changed.
Import failed	18 rows could not be parsed. Review rows 42-59 or send them to quarantine. No source node was created.
Save failed	Your changes are still in this browser. Reconnect and try Save again.
Data unavailable	Preview is unavailable because the selected node has not run. Test this node to generate sample rows.

Transition contract
Action

Trigger and precondition

Transition contract
Immediate feedback
Success result
Failure result
Persistence
Recovery
Telemetry

Chapter checkpoint


- The complete state matrix has a disposition.
- Consequential actions have transition contracts.
- Version conflict and stale data have distinct recovery paths.
- Errors say what happened, what was preserved, and what to do next.
- Unresolved API or product dependencies remain visible.

Product-state method developed for this guide. Local browser simulations, not production API proof.

CHAPTER 07

Prove responsive and accessible behavior

Design the interaction at the supported viewports and through more than one input path.



A DAG tool is a hard accessibility and responsive problem. The answer is not to promise that the generated prototype "supports accessibility." The team needs observable keyboard behavior, focus movement, labels, announcements, hit targets, and layout rules.

Set the viewport contract

Data Pipeline Studio supports:

- **Primary:** 1440 × 900 editing.
- **Minimum:** 1024 × 768 editing.
- **Mobile:** view-only; editing is explicitly out of scope.

At the minimum viewport, the canvas, inspector, and data sheet cannot all keep desktop dimensions. Define how the layout reallocates space:

- The inspector may become an overlay or a narrower dock.
- The data sheet may open to a fixed half-height with an explicit expand action.
- The canvas toolbar remains reachable and does not cover nodes.
- The selected node stays visible when adjacent surfaces open.
- Save and Run remain available without horizontal scrolling.

CLAUDE DESIGN / MINIMUM-VIEWPORT LAYOUT

```
Create the approved Data Pipeline Studio editing state at 1024 x 768.

Preserve the application shell and all required actions. Show how the
canvas, node inspector, and data sheet share space without collisions.
Keep the selected node visible when the inspector or data sheet opens.
Do not shrink text or pointer targets below the design-system
standards.

Annotate which surfaces resize, dock, overlay, collapse, or scroll.
Compare the result to the 1440 x 900 version and list every behavior
change.
```

Provide a keyboard model for the graph

The graph needs an equivalent non-pointer path. A practical contract may include:

- Tab enters the canvas toolbar and graph region in a predictable order.
- Arrow keys move focus among nearby nodes or use a documented list order.
- Enter opens the selected node in the inspector.
- A keyboard command starts connection mode; compatible destinations are announced.
- Escape cancels connection, drag, menu, or dialog states without changing the graph.
- Delete asks for confirmation when removal has downstream consequences.
- Undo and redo are available through standard shortcuts and visible actions.
- Focus returns to a sensible element after Save, import completion, deletion, or error recovery.

The exact shortcut set needs usability and assistive-technology review. The prototype should show the model and surface conflicts before implementation.

Make operational status redundant

Node and run status must use more than color. Combine:

- A semantic icon.
- A short label.
- A semantic color token.
- An accessible name or announcement.
- Optional timing or progress detail.

Animation should communicate change without becoming the only way to notice it. Respect reduced-motion preferences in implementation.

Audit fields, dialogs, and the data sheet

Check:

- Every field has a programmatic label and linked description or error.
- Required fields are identified without color alone.
- Error summaries link to the affected controls.
- Dialogs have a clear title, initial focus, trapped focus, Escape behavior, and return focus.
- Sort direction and selected rows are announced.
- Resizable columns and the sheet handle have keyboard equivalents.
- Truncated cells can be inspected without hover.
- Import progress and cancellation are announced.
- View-only and forbidden actions are explained before or when invoked.

CLAUDE DESIGN / ACCESSIBILITY BEHAVIOR REVIEW

```
Review the approved prototype for keyboard, focus, labeling, status,
dialog, table, and motion behavior.

Do not return a generic checklist. Annotate the actual flow from
opening the pipeline through import, mapping, node creation,
connection, preview, Save, Run, failure, repair, and successful
re-run.

For each step, specify the focused element, available keyboard action,
visible focus treatment, accessible name, announcement if state
changes, and focus destination after completion or error. Mark anything
the prototype cannot prove and assign it to implementation or human
testing.
```

Separate design evidence from implementation evidence

The design can prove visible focus treatment, intended tab order, status redundancy, copy, layouts, and annotated semantics. It cannot prove DOM order, ARIA behavior, screen-reader output, pointer target size in the rendered application, or reduced-motion implementation. Those become engineering acceptance tests.

DECISION: Accessibility gate
A review annotation is a specification. A rendered keyboard and assistive-technology test is evidence. The handoff must include both the intended contract and the tests that will prove it.

Responsive and accessibility review
1440 × 900 behavior
1024 × 768 behavior
Mobile view-only boundary

Responsive and accessibility review
Keyboard graph model
Focus restoration
Status redundancy
Field and dialog semantics
Table and resize behavior

Responsive and accessibility review
Implementation-only tests

Chapter checkpoint


- Both supported editing viewports are designed and compared.
- The mobile boundary is explicit.
- The graph has a non-pointer interaction model.
- Focus, status, errors, and dialog behavior are specified.
- Design evidence is separated from rendered implementation evidence.

Sources 3, 6-10, 21-25. Component-disposition synthesis.

CHAPTER 08

Run the design evidence gate

Review component identity, behavior, data, and scope before creating a handoff bundle.



The handoff begins after review, not after generation. A clean gate makes the review repeatable and produces the records engineering will need.

Review four kinds of evidence

1. Scope evidence

- Baseline and final screenshots show the approved diff.
- Preserve annotations identify regions that should not change.
- The change log names every intentional modification.
- Rejected directions are removed or clearly archived.

2. System evidence

- Every visible primitive resolves to an approved component, an approved variant, a valid composition, or a documented proposal.
- Semantic tokens replace raw color, spacing, type, radius, and focus values.
- Component names match the Figma library and code package.
- Code Connect mappings exist for shared production components where the workflow depends on them.

3. Behavior and data evidence

- The success journey is interactive from import to successful re-run.
- Invalid actions do not mutate the graph.
- The shared fixture appears consistently across surfaces.
- State and transition contracts cover failure and recovery.
- Data provenance is visible.

4. Accessibility and responsive evidence

- Keyboard and focus behavior are specified.
- Status never depends on color alone.
- The two supported viewports have collision-free layouts.
- Implementation-only tests are listed.

Use the component disposition table

Classification	Meaning	Handoff requirement
Reuse	Existing production component and approved usage	Import path, prop or variant mapping
Approved variant	Existing component with an already supported variant	Variant name and implementation evidence
Composition	Existing primitives arranged into a product pattern	Composition owner, interaction notes, code location
Proposed product component	New reusable behavior local to the product domain	State model, API proposal, accessibility contract, owner
Proposed shared component	New pattern intended for the system	Design-system review and promotion decision
Reference only	Prototype code or visual idea not suitable for production	Explicit warning and replacement plan
Unverified	No reliable mapping	Hold handoff; assign an owner to resolve the identity gap before it can pass

Audit Simple Design System precisely

The August 5 code inspection found a `Table` primitive, while its checked-in component metadata did not list a Figma Table component, only a Table icon. Until the working Figma duplicate is inspected, treat the data grid as a product-specific Figma extension even if the code can reuse the Table implementation.

This distinction is the point of the gate. "Table exists" is not one fact. It can be true in code and unverified in Figma at the same time.

Run a challenge review

Ask one reviewer to look for reasons the work should not pass. Useful challenges include:

- Show where the selected node, inspector schema, and preview data disagree.

- Find a visible value that does not resolve to a semantic token.
- Attempt to create a cycle and confirm the graph remains unchanged.
- Shrink to the minimum viewport and open both adjacent surfaces.
- Navigate the critical journey without a pointer.
- Reload after Save, failure, and repair.
- Identify every piece of prototype code that should not enter production.

CLAUDE DESIGN / FINAL DESIGN AUDIT

```
Run a final evidence audit of the approved Data Pipeline Studio
prototype.

Return five sections:

1. preservation-boundary comparison,
2. component and token disposition for every visible pattern,
3. success-journey and state coverage,
4. responsive and accessibility specification coverage,
5. unresolved or unverified items with owners.

Do not correct the design silently. List each proposed correction
first, then apply only corrections that do not change approved product
decisions. Do not call the design production-ready; state whether it is
ready for engineering handoff and why.
```

Gate decision

Use one of three outcomes:

- **Pass for handoff.** No unresolved High finding; component and behavior evidence are complete.
- **Conditional pass.** Bounded Medium or Low follow-up has a named owner and does not change the implementation approach.
- **Hold.** A High finding, unverified component identity, missing recovery path, or unresolved product decision would force engineering to guess.

Design evidence gate
Scope evidence
Component and token traceability
Behavior and data evidence
State and recovery coverage

Design evidence gate
Responsive and accessibility specification
Challenge review results
Unresolved items and owners
Gate decision and reviewers

Chapter checkpoint


- The review covers scope, system, behavior, data, accessibility, and responsiveness.
- Every visible pattern has a disposition.
- Code and Figma evidence are not conflated.
- A challenge review has tried to break the proposal.
- The gate decision and unresolved items are recorded.

Sources 1-3, 19, 22-23. Review framework is author synthesis.

CHAPTER 09

Hand off to Claude Code and developers

Package intent, mappings, fixtures, and proof so implementation starts from the approved work.



The official product-design tutorial describes a default handoff bundle containing design files, chat, and a README, with a URL-bearing prompt for a local agent and an option for Claude Code Web. Inspect the actual export before relying on those contents. Record missing decisions or files and supply them explicitly. The bundle still needs component mapping, engineering review, and repository tests.

Clean the design project first

Before export:

- Name screens, components, states, and flows clearly.
- Remove unused experiments or move them to an explicit archive.
- Record key product decisions in the conversation or decision log.
- Add edge states, data assumptions, and unresolved items.
- Confirm the final frames use the shared fixture.
- Label prototype-only code and simulated behavior.
- Run the design evidence gate.

Build the handoff bundle

Engineering should receive:

- Baseline screenshots with preserve annotations.
- Final screens and interactive flow.
- Screen-by-screen change log.
- Component-to-code import map.
- Design-system delta and token changes.
- State matrix and transition contracts.
- Exact interface and error copy.
- Keyboard and accessibility contract.
- Responsive snapshots.
- Pipeline and import fixtures.
- Scope, non-goals, and unresolved decisions.
- Suggested file and path impact map.

- Acceptance-test checklist.
- Visual-regression baselines.
- A README that says which prototype code is reference only.

Write the component-to-code map

Design element	System disposition	Production mapping	Notes
Save	Reuse	Existing route action and SDS `Button`	No behavior change
Canvas zoom	Composition	SDS `IconButton` + `Tooltip`; new toolbar container	Existing icon set
Pipeline node	Product component	Proposed `PipelineNode`	Composes Text, Tag, icons, semantic tokens
Node field	Reuse	SDS `InputField` / `SelectField`	Use schema-driven field adapter
Data preview	Composition	Existing table implementation + sheet container	Figma Table component unverified
Import mapping row	Product composition	`SelectField`, field error, sample-value text	New orchestration, existing controls
Failure notice	Reuse/composition	SDS `Notification` + focus link	Copy includes node and recovery

The final map should contain real repository import paths, not the generic examples above.

Export from Claude Design

The Design help guide lists ZIP, PDF, PPTX, standalone HTML, and handoff to a local coding agent or Claude Code Web. Google Slides export is available only at claude.ai/design. For Claude Code `/design` artboards, the artifact guide specifically documents per-artboard PNG or PDF. Choose the format and handoff on the actual surface; the lists do not prove every surface has identical controls.

When available, choose **Export > Hand off to Claude Code** and the intended local or web destination. Record the bundle URL, access scope, export time, and a file/content inventory. Test recipient access. Add the team-owned handoff template, component map, fixtures, acceptance tests, and decision log when the export does not contain them. Read/import the bundle first; allow repository edits only under the feature's implementation authority.

CLAUDE CODE / IMPLEMENT THE APPROVED HANDOFF

```
Implement the attached Claude Design handoff in the existing
repository.

Before editing:

1. Read the repository instructions.
2. Inspect the current route, application shell, component library,
tokens, tests, and nearby implementation patterns.
3. Map each design element to an existing production component.
4. Compare that map to the supplied component-to-code table.
5. Report any design element that has no valid implementation mapping.

During implementation:

- Modify the existing route and files where appropriate; do not create
a parallel UI or duplicate existing components.
- Preserve behavior outside the approved feature scope.
- Use the repository's established state, data, accessibility,
responsive, and testing patterns.
- Use the supplied fixtures for the importer, preview, validation,
quarantine, and run states.
```

CLAUDE CODE / IMPLEMENT THE APPROVED HANDOFF

```
- Treat prototype code as design intent unless the handoff explicitly
identifies a production mapping.
- Stop before broadening scope or promoting a new shared component
without approval.

After implementation:
```

CLAUDE CODE / IMPLEMENT THE APPROVED HANDOFF

```
- Run the relevant unit, integration, accessibility, type, lint, and
build checks.
- Verify the rendered states at 1440 x 900 and 1024 x 768.
- Compare the rendered feature to the preservation and
visual-regression baselines.
- Report reused components, new components, deviations from the
prototype, and anything still requiring human approval.
```

Give engineering acceptance tests, not adjectives

Critical tests:

1. The existing shell, route, permissions, Save action, and Run action remain functional.
2. Every visible primitive resolves to an approved component or documented extension.
3. A valid connection is created; a cycle and incompatible connection are rejected without modifying the graph.
4. Editing a node marks the document dirty, persists after Save and reload, and protects invalid drafts. Save failure keeps Run disabled and must not persist the unsaved draft through Run.
5. Import is blocked until all mappings and the recovery choice are confirmed; cancel and parse failure create no source. Completion replaces the placeholder with source ID `august`.
6. Preview after `Normalize Email` shows transformed fixture data.
7. The warehouse run fails with target `missing-warehouse`, focuses that node, and preserves the error after reload. Changing the target to `customer_health`, saving, and re-running yields three published and three quarantined records.
8. Undo and redo restore node position and graph structure.
9. Keyboard actions have visible focus and an equivalent non-pointer path.

10 Loading, empty, stale, truncated, permission, conflict, and error states are rendered and recoverable.

11 No raw colors, duplicate primitives, inline production styles, or undocumented components are introduced.

12 Visual checks pass at both supported viewports without inspector or sheet collisions.

Record implementation deviations

Engineering will discover constraints the prototype did not model. A deviation log keeps the design and product record honest.

Deviation	Reason	User consequence	Owner	Reconcile where?
Example: data sheet opens at 45% rather than 50%	Minimum viewport collision	More canvas remains visible	Design + engineering	Code and Figma

The goal is not pixel identity at any cost. The goal is an approved explanation for every meaningful difference.

Handoff readiness
Bundle and access
Baseline and final references

Handoff readiness
Component-to-code map
Design-system delta
State and transition package
Fixtures
Acceptance tests

Handoff readiness
Prototype-only warnings
Unresolved items
Implementation owner and review date

Chapter checkpoint


- The design project is clean and named.
- The bundle includes intent, mappings, data, states, tests, and unresolved items.
- Prototype code is visibly separated from production mappings.
- Claude Code has an inspect-before-edit prompt.
- Engineering has objective acceptance tests and a deviation log.

Sources 1, 3, 19. Local handoff inspection passed; Design export remains unverified.

CHAPTER 10

Implement, verify, and reconcile

Close the loop in the running product and update the design record without erasing evidence.



The final proof lives in the running product. Source inspection and passing tests matter, but neither proves that the right tab, route, state, and viewport render correctly.

Implement in bounded slices

A practical order is:

1. Graph data model and read-only rendering.
2. Selection, navigation, and inspector integration.
3. Movement, connection validation, undo, and redo.
4. Data sheet bound to the selected node's fixture.
5. Importer parsing, mapping, recovery, and source-node creation.
6. Save, run, failure, repair, and successful re-run.
7. Version conflict, permissions, stale data, and remaining edge states.
8. Responsive and accessibility implementation.

Each slice should pass its local tests and the preservation checks before the next slice begins.

Use four verification layers

Static checks

Run the repository's type check, lint, formatting, dependency, and build commands. Confirm that no raw design values or duplicate primitives entered the feature.

Automated behavior checks

Test graph rules, state transitions, persistence, importer parsing and mapping, fixture transformation, run errors, retry, permissions, conflict handling, and undo/redo.

Rendered visual checks

Capture the exact route and required states at 1440 × 900 and 1024 × 768. Compare the shell, major geometry, focus treatment, status, dialogs, sheet positions, and error states to approved references.

Human review

Design reviews conformance and intentional deviations. Engineering reviews architecture, state, data, and maintainability. Product reviews scope, copy, and success journey. Accessibility review covers keyboard and assistive-technology behavior in the rendered application.

Report proof boundaries directly

Use language such as:

- "Unit and integration tests passed."
- "The route rendered at both required viewports."
- "Keyboard navigation was checked through the critical journey."
- "Screen-reader output remains unverified."
- "The design-system owner approved the two proposed product components."

Do not collapse these into "production-ready" unless the team has defined and met that gate.

Use the native-Figma branch when required

Direct native-Figma export is not established by the reviewed Claude Design documentation. If editable Figma content is required, use Figma's separate remote MCP workflow. Figma recommends its Claude Code plugin, which bundles server settings and skills; manual HTTP setup is also documented. Code Connect adds implementation context where eligible and configured.

Figma documents two paths with different permissions:

1. **Figma-first:** `use_figma` creates or updates native frames, components, variables, and Auto Layout. Writing needs a Full seat; modifying an existing file also needs edit permission. Load the installed Figma write-to-canvas skills and inspect first. The tool currently has a 20kb output-response limit, no image-asset or custom-font support, and requires manual component publication before Code Connect completes. See write to canvas.

2. **Code-first:** `generate_figma_design` captures live browser UI into editable layers. Any seat can use this tool in Drafts; an existing file outside Drafts needs a Full seat and edit permission. This path is distinct from native writing. Inspect captured instances and variable bindings before claiming design-system reuse. See code to canvas.

The August `/prototype-to-figma` instruction is replaced with the documented code-to-canvas tool workflow. A client-specific prompt shortcut is not a universal Figma command. MCP read quotas vary by plan and seat; check the current access table and authenticated account before planning a full-file inventory.

FIGMA MCP / EXTEND AN EXISTING NATIVE SCREEN

```
Using the working Figma file and the selected existing Pipeline Detail
screen, add the approved Data Pipeline Studio feature beside the
current version for review.

Inspect the file and connected libraries first. Reuse existing
```

FIGMA MCP / EXTEND AN EXISTING NATIVE SCREEN

```
components, variables, styles, layer naming, and Auto Layout
conventions. Preserve the surrounding screen. Use the approved
component disposition, state matrix, and responsive rules. Create only
the documented product-specific extensions.

Return the IDs of created or changed frames and components, plus a
short list of any mapping you could not verify. Do not edit the public
Community source.
```

FIGMA MCP / CAPTURE THE IMPLEMENTED FLOW

```
Capture the complete local Data Pipeline Studio flow in the working
Figma file as editable frames.

Inspect captured component instances and variable bindings, and record
reuse or gaps separately from visual resemblance. Include each unique
critical state at 1440 x 900 and 1024 x 768. Create a summary page that
records the journey, component mappings, implementation deviations,
and unresolved differences from production.

Keep the approved source frames intact. Place captured implementation
frames in a separate named section with capture date and repository
revision.
```

Reconcile without hiding drift

At the end of implementation:

- Update the design decision record with approved changes.
- Update Figma frames if Figma is an active source of truth.
- Update Code Connect mappings for approved shared components.
- Keep the baseline, approved design, and rendered implementation distinguishable.
- Close or assign every deviation.
- Add regression baselines for the final states.

Avoid overwriting the approved design with a capture that removes the record of what changed. Reconciliation should preserve the chain of evidence.

Monitor future changes

The handoff is a starting point for ongoing maintenance. Track:

- Component or token changes that affect the feature.
- Graph-schema or API changes.
- Import error and mapping rates.
- Save conflicts and failed runs.
- Accessibility regressions.
- Layout regressions at supported viewports.
- Design/code drift and stale Code Connect mappings.

Implementation proof record
Repository revision
Static checks
Behavior tests

Implementation proof record
Rendered routes and states
Viewport evidence
Keyboard and assistive-technology evidence
Human reviewers
Approved deviations

Implementation proof record
Unverified items

Figma or Code Connect reconciliation

Chapter checkpoint


- Implementation proceeded in bounded slices.
- Static, behavioral, rendered, and human evidence are reported separately.
- The actual route and states were rendered at both supported viewports.
- The native-Figma branch was used only if the team requires it.
- Design and code drift remain visible and assigned.

Sources 6-10, 21-25. Native Figma workflow remains unverified.

CHAPTER 11

Guided capstone

Run the complete import-to-success journey and produce a handoff another team can implement.



The capstone asks you to extend the existing Pipeline Detail screen into Data Pipeline Studio without redesigning the surrounding product. Work in a small cross-functional group if possible: one product owner, one designer or design-system owner, and one engineer.

The deliverable is not a single screen. It is an evidence-backed design and handoff package for this journey:

1. Import `customers-august.csv`.
2. Resolve a required column mapping.
3. Create a source node.
4. Connect it to `Normalize Email`.
5. Preview transformed rows.
6. Add a quarantine branch after schema validation.
7. Save and run.
8. Find and repair a failed node.
9. Re-run successfully.

Capstone rules

- Work from the duplicated Simple Design System file and relevant React package.
- Keep the public Community source untouched.
- Preserve the existing shell, route, permissions, Save, Run, persistence, and unrelated copy.
- Use the exact six-row fixture and expected outputs from Chapter 1 throughout. Record CSV/JSON hashes and each invalid row and column. Label a local executable exercise separately from observed Claude Design output.
- Label new product components and tokens.
- Do not treat generated prototype code as production code without a real mapping.
- Do not pass the capstone with an unresolved High finding.

Phase 1 - Frame and ground

Produce:

- A source-of-truth stack.
- An extension brief.
- Baseline and preserve annotations.
- A compact context package.
- A design-system inventory and gap list.

Use the baseline-analysis, system-inspection, and draft-system prompts from Chapters 1 through 3. Run the settings form, dense table, and confirmation-flow tests before starting the DAG.

Capstone phase 1

Authoritative sources

Baseline and preservation boundary

Fixture and success journey

Context-package contents

Known-screen tests

Capstone phase 1
System gaps
Approval to proceed

Phase 2 - Build the bounded DAG extension

Produce:

- The approved shell with a DAG replacing only the linear editor.
- Canvas navigation.
- Node selection and movement.
- Valid and rejected connections.
- Undo and redo.
- A proposed component sheet for nodes, ports, edges, toolbar, and run status.

Demonstrate that a cycle and incompatible connection leave the graph unchanged.

Capstone phase 2
Shell preservation evidence

Capstone phase 2
DAG fixture fidelity
Canvas navigation
Selection and movement
Connection success and rejection
Undo and redo
Component proposals

Phase 3 - Complete the working surfaces

Produce:

- A schema-driven inspector for `Validate Customer Schema`.
- A data sheet showing the output of `Normalize Email`.
- A staged importer for `customers-august.csv`.
- Cross-surface consistency annotations.

The importer must block completion until the required mapping is resolved. Successful import must create the configured source node and open its preview.

Capstone phase 3
Inspector states
Data sheet states and provenance

Capstone phase 3
Importer stages
Required mapping behavior
Malformed-row recovery
Source-node creation
Cross-surface consistency

Phase 4 - Specify states, accessibility, and viewports

Produce:

- A complete state matrix.
- Transition contracts for Create edge, Import, Save, Run, and Repair.
- A version-conflict sequence.
- A stale-preview sequence.
- 1440 × 900 and 1024 × 768 layouts.
- A keyboard and focus contract.
- An implementation-only accessibility test list.

Capstone phase 4
State-matrix coverage
Transition contracts
Conflict and stale-data recovery

Capstone phase 4
Viewport layouts
Keyboard model
Focus and announcement behavior
Implementation-only tests

Phase 5 - Review and hand off

Run the design evidence gate. Produce:

- A component disposition for every visible pattern.
- A token audit.
- A challenge-review record.

- A gate decision.
- A handoff README.
- A component-to-code map with real import paths.
- The state matrix, transition contracts, fixtures, copy, responsive references, accessibility contract, acceptance tests, and unresolved items.

Export the Claude Design handoff only after the gate passes or receives a bounded conditional pass.

Capstone phase 5
Scope evidence
Component and token disposition
Challenge review
Gate decision

Capstone phase 5
Handoff README
Production import map
Fixtures, states, and tests
Unresolved items and owners

Phase 6 - Plan implementation and proof

You do not need to implement a production application to complete the design capstone, but the implementation plan must be executable.

Produce:

- The exact Claude Code implementation prompt.
- A bounded implementation sequence.
- Static, behavior, visual, and human review commands or procedures.
- Required rendered states and viewports.
- A deviation log template.
- A Figma reconciliation choice: not required, Figma-first, or code-to-canvas.

Capstone phase 6
Implementation prompt
Bounded slices
Static and behavior proof
Rendered proof

Capstone phase 6
Human review
Deviation log
Figma reconciliation choice

Capstone scoring

Category	Points
Baseline fidelity and scope discipline	15
Design-system reuse and extension quality	20
DAG, inspector, data-sheet, and importer behavior	20
State completeness and recovery	15
Data correctness and fixture traceability	10
Accessibility and responsive behavior	10
Handoff completeness and implementation readiness	10
Total	**100**

Interpretation:

- **90-100:** Production-ready candidate for implementation review.
- **80-89:** Ready for implementation with bounded follow-up.
- **70-79:** Useful prototype; handoff gaps remain.
- **Below 70:** Exploration only.

Mandatory gates apply regardless of score:

- No unresolved High finding.
- All critical acceptance tests have a design and implementation disposition.
- Production components and tokens are traceable.
- Design and engineering have reviewed the rendered implementation before release.

Capstone synthesis of Chapters 1-10 and the bounded local worked-example tests.

Capstone answer key

The answer key does not prescribe one visual layout. It defines the evidence a strong submission contains.

Phase 1 answer

A strong source stack ranks current production behavior and component code above visual inference. The duplicated Figma file and React package are paired, while shipped screens supply composition evidence. The preservation brief names the shell, route, permissions, Save, Run, persistence, and unrelated copy. The context package is focused and excludes private data, dependencies, build output, and unrelated packages.

The system test samples component identity and token use. It does not pass because the screen "looks like SDS." The record shows exact reuse, valid composition, proposals, and unverified areas.

Phase 2 answer

The DAG replaces only the current linear editor. `PipelineNode`, `PipelinePort`, and `PipelineEdge` are product-specific extensions rather than disguised card or button variants. Canvas controls reuse existing buttons, icons, and tooltips. The graph rejects a cycle and incompatible ports without mutation and explains the reason. Node status uses icon, text, and semantic color. Undo and redo cover both layout and structure.

Phase 3 answer

The selected node, inspector title, and data sheet provenance agree. Import creates source ID `august` after confirmation. `Normalize Email` produces six rows; C001 and C006 become `alice@example.com` and `frank@example.com`. Validation retains C001, C002, and C006, while C003, C004, and C005 are invalid at CSV rows 4, 5, and 6. The warehouse repair changes `missing-warehouse` to `customer_health`, then saves before re-running. The importer does not commit inferred mappings silently. The required mapping blocks completion, malformed rows point to row and column, and the user can reject them or route them to quarantine. Success creates the same source node shown on the graph.

Phase 4 answer

The state matrix covers document, canvas, node, inspector, data sheet, importer, run, and permissions. Transition contracts say what remains stable after failure. Version conflict preserves local work and supports review; stale preview remains inspectable and clearly marked. The minimum viewport uses an explicit docking or overlay rule rather than shrinking everything. Keyboard focus can complete the critical journey, and implementation-only evidence remains a test plan rather than an unsupported claim.

Phase 5 answer

Every visible element has a disposition. The record distinguishes the code Table primitive from the unverified Figma Table component. The challenge reviewer attempts invalid connections, minimum-viewport collisions, keyboard navigation, reload persistence, and data inconsistency. The handoff contains real imports, fixtures, exact copy, states, transitions, acceptance tests, prototype-only warnings, and named unresolved items.

Phase 6 answer

The Claude Code prompt requires inspection before editing, updates the current route rather than creating a parallel application, uses repository conventions, and asks for rendered proof. The implementation plan proceeds in bounded slices. The proof record separates local model tests, actual browser actions, tool observations, documentation, and human approval. A local exercise can pass its bounded tests while the Claude Design workflow remains unverified. Neither a local package nor Claude Code reading it proves that Design exported it. The team chooses a Figma reconciliation path based on whether editable Figma remains a source of truth.

Common deductions

Finding	Typical deduction
Shell or unrelated regions redesigned	10-20
Prototype code presented as production mapping	10-20
Graph cycle or incompatible connection mutates state	8-15
Importer has only a happy path	8-12
Preview data is unrelated to selected node output	8-12
New raw colors or duplicate controls	5-10
No minimum-viewport evidence	5-10
Status depends on color	5-10
No keyboard graph path	5-10
Unresolved items have no owner	3-8

Appendix A - Prompt sequence

Use prompts in order. Each prompt should preserve approved work, name the exact surface being changed, and request a small auditable result.

Use the setup path in Chapter 3 before these prompts. Record the chosen surface and system. `/design-sync` converts and uploads a React system; `/design` drafts artboards. Export a reviewed baseline before alternatives and test required interactions on the actual surface.

A1. Baseline analysis

CLAUDE DESIGN / COPY-READY PROMPT

```
Review the attached existing screen, route context, relevant code, and
design-system sources. Do not generate a new design yet.

Return a factual screen inventory, visible component and layout
patterns, preservation boundary, source conflicts, change boundary,
and unresolved questions. Separate observations from inferences. Do
not invent missing behavior.
```

A2. Draft design system

CLAUDE DESIGN / COPY-READY PROMPT

```
Build a draft system from the attached component code, tokens, Figma
working file, and representative shipped screens. Treat code and tokens
as authoritative. Preserve names. Separate directly observed
components, inferred compositions, proposed additions, and unverified
areas. Generate a settings form, dense table, and confirmation flow.
Record source revision and selected system. Keep the system in draft;
publication and default selection require owner approval.
```

A3. Bounded screen extension

CLAUDE DESIGN / COPY-READY PROMPT

```
Extend the attached existing screen with the approved feature. Preserve
the named shell, navigation, route behavior, actions, permissions,
spacing, typography, and interaction language. Change only the
approved region. Reuse existing components and variants; label every
proposal. Produce an interactive prototype and change log.
```

A4. Full state coverage

CLAUDE DESIGN / COPY-READY PROMPT

```
Apply the supplied state matrix to the approved prototype. Cover
loading, empty, populated, dirty, saving, success, validation, system
error, permission, conflict, stale, truncated, and recovery behavior.
Annotate transitions and data assumptions. Preserve approved layout
and components.
```

A5. Conformance audit

CLAUDE DESIGN / COPY-READY PROMPT

```
Audit every visible element against the linked system and codebase.
Classify it as reuse, approved variant, composition, proposed product
component, proposed shared component, reference only, or unverified.
Correct objective token and component deviations. List changes before
applying them. Return unresolved items with owners.
```

A6. Claude Code implementation

CLAUDE CODE / COPY-READY PROMPT

```
Implement the attached approved handoff in the existing repository.
Inspect repository instructions, the current route, shell, component
library, tokens, tests, data layer, and nearby patterns before editing.
Map each design element to production code and report gaps. Modify the
existing feature rather than creating a parallel UI. Preserve
out-of-scope behavior. Use the supplied fixtures and acceptance tests.
Run static, behavioral, accessibility, build, and rendered checks.
Report mappings, deviations, proof, and unverified items.
```

A7. Native Figma update

FIGMA MCP / COPY-READY PROMPT

```
Inspect the working Figma file and connected libraries. Extend the
selected current screen using approved components, variables, styles,
names, and Auto Layout. Preserve the source frame and create the
proposed version beside it. Apply the supplied component disposition
and state matrix. Return changed node IDs and unverified mappings. Do
not edit a public Community source.
```

Appendix B - Handoff README template

Feature

[Feature name and route]

Workflow and export evidence

[Design surface, organization, plan, Claude Code version/provider, selected system, source revision, sync result]

[Export format/date, actual file inventory, chat/README completeness, recipient access, missing inputs and owners]

[Reviewed baseline path/hash and open result; repository edit authority]

Inspect the bundle before implementation. Use the companion handoff template for the full evidence fields and the separate Figma write/capture eligibility checks.

Decision

[One paragraph: what is changing, for whom, and why]

Scope

Change: [Approved surfaces and behavior]

Preserve: [Shell, routes, actions, data, permissions, and unaffected behavior]

Non-goals: [Explicit exclusions]

Source-of-truth stack

1. [Production behavior and route]
2. [Component package and revision]
3. [Working Figma file and design-library revision]
4. [Representative shipped screens]
5. [Product brief and approval date]

Approved journey

[Numbered end-to-end user journey]

Design references

- Baseline: [link or path]
- Approved design: [link]
- Responsive references: [links]
- Prototype: [link]
- Claude Design bundle: [URL]

Component-to-code map

[Link to map with real imports, props, variants, and proposal owners]

Product-specific extensions

[Component, state model, accessibility contract, owner, intended code path]

Data and fixtures

[Fixture paths, schemas, expected transformations, error cases]

States and transitions

[State matrix and transition-contract links]

Copy

[Approved labels, helper text, errors, confirmations, empty states]

Accessibility and responsiveness

[Keyboard model, focus rules, announcements, viewports, mobile boundary, implementation-only tests]

Acceptance tests

[Critical numbered tests]

Prototype-code warning

Prototype code demonstrates design intent. Use only the mappings explicitly identified in the component-to-code table. Do not copy scratch components, simulated data, local styles, or generated state management into production without review.

Open decisions and deviations

[Item, severity, owner, due date, implementation consequence]

Verification record

[Commands, rendered routes and states, screenshots, reviewers, unverified items]

Appendix C - Final validation checklist

Setup and observation

- [ ] Surface, organization, plan, provider, installed version, and selected system are recorded.
- [ ] Design, Design systems, and standalone controls are checked separately.
- [ ] Sync upload destination and completed source revision are confirmed.
- [ ] Read, native-write, capture, and Code Connect eligibility are checked separately when Figma is used.
- [ ] A reviewed baseline export opens and is preserved.
- [ ] Documentation claims and observed runtime results are recorded separately.

Source and scope

- [ ] Current route and production behavior are named.
- [ ] The source-of-truth hierarchy is approved.
- [ ] The public Community file is untouched.
- [ ] A working Figma duplicate is used when connected inspection or editing is required.
- [ ] The preservation boundary is visible.
- [ ] Non-goals are explicit.
- [ ] One fixture carries through the complete journey.

Design system

- [ ] The focused code package, tokens, stories, and mappings are linked.
- [ ] Settings form, dense table, and confirmation-flow tests pass; a correction persists in a neighboring state.
- [ ] Component and token identity were sampled.
- [ ] Every visible pattern has a disposition.
- [ ] Raw values and duplicate primitives are absent.
- [ ] Proposed components have owners, states, behavior, accessibility notes, and code paths.

Behavior and data

- [ ] The complete success journey is interactive.
- [ ] Invalid graph actions do not mutate state.
- [ ] Undo and redo cover layout and structure.
- [ ] The importer blocks unresolved required mappings.
- [ ] Malformed rows have row and column references.
- [ ] Import success creates the configured source node.
- [ ] Preview data belongs to the selected node and shared fixture.
- [ ] Save, reload, failure, repair, and re-run are covered.
- [ ] Conflict, stale, permission, empty, loading, and error states recover safely.

Accessibility and responsiveness

- [ ] The 1440 × 900 and 1024 × 768 layouts are reviewed.
- [ ] Mobile editing is supported or explicitly out of scope.
- [ ] Critical actions have a non-pointer path.
- [ ] Focus is visible and restored after dialogs and state changes.
- [ ] Status uses icon, label, and color.
- [ ] Fields, errors, tables, progress, and dialogs have semantic behavior specified.
- [ ] Reduced-motion and assistive-technology tests are assigned to implementation.

Handoff

- [ ] Baseline, final design, prototype, and change log are present.
- [ ] Component-to-code map uses real import paths.
- [ ] State matrix, transition contracts, copy, and fixtures are included.
- [ ] Prototype-only code is labeled.
- [ ] Acceptance tests are objective.
- [ ] Unresolved items have severity, owner, and consequence.
- [ ] Export inventory and recipient access are checked; missing files or decisions are supplied or assigned.
- [ ] The Claude Code prompt requires inspection before editing.

Implementation proof

- [ ] Static checks pass.
- [ ] Behavior and data tests pass.
- [ ] The actual route renders in required states and viewports.
- [ ] Keyboard and assistive-technology checks are reported separately.
- [ ] Design, engineering, and product review are recorded.
- [ ] Deviations are approved or assigned.
- [ ] Figma and Code Connect are reconciled if they remain sources of truth.

Appendix D - Simple Design System reference

The following inventory retains the August 5, 2026 SDS code/metadata findings. The local review pinned SDS React commit `05525f75192a3aa5d5690c5e41277ebd19d2efe1` and used its actual primitives. Native Figma node IDs, counts, and the Table discrepancy were not re-measured; the working duplicate was unavailable. The October review rechecked the official repository README and setup guidance. Pin the repository revision used for a new experiment and verify its metadata against the working Figma copy. The August connected account could not inspect the Community source; current Figma documentation separates read access from Full-seat native writing.

Component-bearing metadata pages

The August metadata inventory recorded 396 components across 19 component-bearing pages: Accordion, Avatars, Buttons, Cards, Dialog, Examples, Forms, Icons, Inputs, Menu, Navigation, Notification, Pagination, Sections, Tabs, Tags, Text, Tooltip, and Utilities. This list is not a verified inventory of every top-level page in the live Community file.

Useful component node IDs

Family	Examples
Buttons	Button `9762:426`; Icon Button `11:11508`; Button Group `2072:9432`; Button Danger `185:852`
Inputs	Select `2136:2336`; Input `2136:2263`; Textarea `9762:3088`; Search `2236:14989`; Checkbox `9762:1441`; Radio `9762:1412`; Switch `9762:1902`
Navigation	Navigation Button `515:5459`; Button List `524:503`; Pill `7768:19970`; Pill List `2194:14984`
Feedback	Notification `124:8256`; Tooltip `315:32700`; Tag `56:8830`; Button Danger `185:852`
Structure	Accordion `7753:4779`; Tabs `3729:13362`; Dialog `192:31534`; Header `2287:22651`; Footer `321:11357`
Pagination	Root `9762:899`; Page `9762:890`; Next `9762:870`; Previous `9762:880`; Gap `9762:868`
Pipeline icons	Database `4049:13478`; Git Branch `4049:13513`; Grid `4049:13518`; Table `4049:13630`; Play `4049:13586`; Upload `4049:13656`; Settings `4049:13606`; Alert Circle `4039:13020`; Check Circle `4039:13060`

Token collections

Collection	Modes	Use
`@typography_primitives`	default	Inter, Noto Serif, Roboto Mono, scale 01-10, weights
`@responsive`	desktop, mobile, tablet	Device, device width, root size, scale
`@typography`	mode_1	Semantic title, subtitle, heading, body, and code roles
`@size`	default	Space, radius, blur, depth, stroke, icon size
`@color_primitives`	value	Brand and raw black, white, green, gray, pink, red, slate, yellow palettes
`@color`	sds_light, sds_dark, brand_b_light	Semantic background, text, border, icon roles

Use `@color` semantic roles in product design. Raw primitive palettes are inputs to the system, not interface decisions.

Product gaps for Data Pipeline Studio

SDS is a strong source for the shell, forms, controls, typography, themes, layout, and basic feedback. It does not provide the product-defining graph, port, edge, schema-mapping, importer, or operational run-state model. The August inspection found a code Table primitive but no Table component in its Figma metadata. Verify that distinction in the chosen revision and working file. Build confirmed gaps as explicit product extensions from SDS primitives and tokens.

Appendix E - Product boundaries and operating risks

Tool roles

Tool	Proper role	Boundary
Claude Design	System-grounded visual exploration and interactive prototyping	Works in its own canvas; direct native-Figma round-trip is not documented
Claude Code	Repository-aware implementation from the handoff	Requires engineering review, tests, and rendered verification
Figma MCP + Code Connect	Native Figma editing and structured design/code mapping	Separate integration with its own permissions and mappings
Figma Make	Figma's prompt-to-app product	Uses Claude models but is a different product from Claude Design

Current Claude Design limitations

1. Claude Design remains beta. Large repositories, intermittent comments, incomplete source imports, and simultaneous editing have documented limits. Mobile can request and view designs; canvas editing and sharing changes require web or desktop. Version history is not yet available. See the Design help guide.
2. Usage draws from the existing Claude allowance, including Claude Code. Confirm the organization's billing arrangement; usage-based Enterprise differs from seat-based plans. See the Artifacts admin guide.
3. Design and Design systems have separate Enterprise template controls. Standalone Design uses its own setting. An enabled organization setting is required before a custom role can grant access.
4. Uploaded assets persist under the applicable retention policies, Design data residency is unsupported, and the new Artifacts experience is unavailable for the documented CMEK, ZDR, and HIPAA-ready configurations. Confirm tenant requirements before upload.
5. Standalone Design lacks audit logs. Integrated designs in conversations and Artifacts have artifact-level Compliance API recording. Verify the event coverage required by the team; artifact-level records do not establish complete edit or comment history.
6. Generated accessibility reviews and conformance checks assist the reviewer. They do not establish human approval, component identity, or production behavior.

Figma workflow limits

The write-to-canvas documentation lists unsupported image assets and custom fonts, a 20kb output-response limit, and manual component publication before Code Connect completes. Those limits apply to that tool. The code-to-canvas path has different seat rules, and editable captured layers still need component and variable inspection. Confirm read quotas, Code Connect eligibility, and file permissions separately.

Operational controls

- Pilot with a small design-system group before broad rollout.
- Use non-sensitive fixtures and sanitize screenshots.
- Define who can publish or revise the organization system.
- Sample generated projects for system compliance.
- Keep a feedback path for source and mapping errors.
- Record the repository and design revisions used for each handoff.
- Treat field reports and vendor testimonials as adoption signals, not controlled quality evidence.

Glossary

Approved variant - A variant already supported by the design component and production implementation.

Baseline - The current screen, behavior, data, and system state before the proposed change.

Code Connect - Figma's mapping layer that can provide component imports, prop mappings, snippets, source paths, and instructions to connected agents.

Component disposition - The classification that says whether a visible pattern is reused, composed, proposed, reference-only, or unverified.

Design evidence gate - The review that checks scope, system traceability, behavior, data, accessibility, and responsiveness before handoff.

Design-system delta - The explicit list of proposed components, variants, tokens, or guidance introduced by a feature.

Deviation log - A record of meaningful differences between approved design and implementation, including reason, consequence, owner, and reconciliation path.

Fixture - Stable example data used across design, tests, and review so surfaces can be compared consistently.

Grounded prototype - A prototype generated with source evidence from the current product, design system, codebase, and requirements.

Native Figma content - Editable Figma frames, components, variables, and Auto Layout rather than a flattened image or external prototype link.

Preservation boundary - The regions and behaviors that must remain stable while a bounded feature changes.

Product component - A reusable element with product-domain behavior that is not necessarily appropriate for the shared design system.

Prototype code - Code created to demonstrate interaction or appearance; it is not production code unless it maps to repository conventions and passes implementation review.

Semantic token - A named design value based on purpose, such as danger text or default border, rather than a raw color or number.

Source-of-truth stack - The ordered set of artifacts that govern product behavior, components, design anatomy, composition, and intent.

Transition contract - A specification of trigger, precondition, immediate feedback, success, failure, persistence, recovery, and telemetry for an action.

Further reading and source notes

Primary product sources

1 Anthropic. "Get started with Claude Design." Accessed October 2, 2026. https://support.claude.com/en/articles/14604416-get-started-with-claude-design

2 Anthropic. "Set up your design system in Claude Design." Accessed October 2, 2026. https://support.claude.com/en/articles/14604397-set-up-your-design-system-in-claude-design

3 Anthropic. "Using Claude Design for prototypes and UX." Accessed October 2, 2026. https://academy.claude.com/tutorials/using-claude-design-for-prototypes-and-ux

4 Anthropic. "Claude Design admin guide for Team and Enterprise plans." Accessed October 2, 2026. https://support.claude.com/en/articles/14604406-claude-design-admin-guide-for-team-and-enterprise-plans

5 Anthropic. "Introducing Claude Design, an Anthropic Labs research preview." April 17, 2026. https://www.anthropic.com/news/claude-design-anthropic-labs

Figma and design-system sources

6 Figma. "Figma MCP Server: Introduction." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/

7 Figma. "Code Connect integration." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/code-connect-integration/

8 Figma. "Structure your Figma file for better code." Accessed August 5, 2026. https://developers.figma.com/docs/figma-mcp-server/structure-figma-file/

9 Figma. "Workflow lab: Code to canvas." May 2026. https://help.figma.com/hc/en-us/articles/40219873508247-Workflow-lab-Code-to-canvas

10 Figma. "Getting started with Code Connect CLI." Accessed October 2, 2026. https://developers.figma.com/docs/code-connect/quickstart-guide/

11 Figma. "Simple Design System" open-source repository. README accessed October 2, 2026; detailed inventory retains August 5 cutoff. https://github.com/figma/sds

12 Figma. Simple Design System Community file supplied for this guide. https://www.figma.com/design/AIulMBySUibjRtykdngCUp/Simple-Design-System--Community-?node-id=3-5

Current setup and operating references

18 Anthropic. "Commands." Accessed October 2, 2026. https://code.claude.com/docs/en/commands

19 Anthropic. "Share session output as artifacts." Accessed October 2, 2026. https://code.claude.com/docs/en/artifacts

20 Anthropic. "Artifacts admin guide for Team and Enterprise plans." Accessed October 2, 2026. https://support.claude.com/en/articles/16994751-artifacts-admin-guide-for-team-and-enterprise-plans

21 Figma. "Set up the remote server." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/remote-server-installation/

22 Figma. "Write to canvas." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/write-to-canvas/

23 Figma. "Code to canvas." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/code-to-canvas/

24 Figma. "Rate limits & access." Accessed October 2, 2026. https://developers.figma.com/docs/figma-mcp-server/rate-limits-access/

25 Figma. "Code Connect: Introduction." Accessed October 2, 2026. https://developers.figma.com/docs/code-connect/

Field evidence - directional, not governing

13 Paul Kuo. "Claude Design sync codebase" field test. https://paulkuo.tw/articles/claude-design-sync-codebase/

14 Sebastian Proost. Claude Design case study. https://blog.4dcu.be/ai/programming/2026/04/27/claude-design.html

15 byCrawford. Claude Design review. https://bycrawford.squarespace.com/blog/claude-design-review

16 Builder.io. Claude Design review. https://www.builder.io/blog/claude-design

17 Creative Bloq. Claude Code and Figma MCP review. https://www.creativebloq.com/ai/designing-using-claude-code-and-figma-mcp-how-good-are-they

The editable guidance was refreshed from official documentation accessed October 2, 2026. The original August PDF and package remain separate artifacts. This source revision is a review candidate. Its local executable worked example passed the bounded October 2 tests; Claude Design generation, system sync, export, and native Figma reuse remain unverified. SDS metadata counts and node IDs retain their labeled August cutoff. The claim ledger in review/2026-10-02 records sources, accepted changes, and open workflow tests. Field reports remain historical context and do not support current capability claims.