

License

- Open Source: AGPLv3
- Commercial:

[LICENSE](#)

Go

```
go get github.com/mikhaildadaev/ulog
```

ulog v1.26.12.

Run Test

```
go test ./...
go test -bench=. ./...
go test -cover ./...
go test -race ./...
```

Key Features

- API — API
- — context.Context node_id trace_id
- — Dark Light TEXT
- 16 — Bool Bools Duration Durations Error Errors Float64 Floats64
Int Ints Int64 Ints64 String Strings Time Times
- — gzip
- — Batching Circuit Breaker Deduplication Retry Sampling
- 8 — Discord Kafka Loki Prometheus Slack Telegram Tempo WeChat

Limits

-
- LevelDebug
- 6 — 99%
-
-
-
- HTTP

- **Kafka** REST Proxy API Kafka — Confluent REST Proxy
- **Loki** HTTP API (`/loki/api/v1/push`) —
- `context.WithValue()`
- Kafka

API / Core /

NewTelemetry

```
ctx := context.Background()
ctx = context.WithValue(ctx, "node_id", "123-abc")
ctx = context.WithValue(ctx, "trace_id", "abc-123")
telemetry := ulog.NewTelemetry(
    ulog.WithExtractor("node_id", "trace_id"),
    ulog.WithFormat(ulog.FormatJson),
    ulog.WithLevel(ulog.LevelDebug),
    ulog.WithMode(ulog.ModeAsync, ulog.DefaultWriterOut, 1000),
    ulog.WithTheme(ulog.ThemeLight),
)
defer telemetry.Close()
telemetry.InfoWithContext(ctx, ulog.DataLog,
    ulog.String("message", "text"),
)
telemetry.InfoWithContext(ctx, ulog.DataMetric,
    ulog.String("name", "payments"),
    ulog.Float64("value", 99.99),
)
telemetry.InfoWithContext(ctx, ulog.DataTrace,
    ulog.String("name", "payment_processing"),
    ulog.Int64("duration", 150),
    ulog.String("span_id", "span-456"),
)
telemetry.SetExtractor()
telemetry.SetFormat(ulog.FormatText)
telemetry.SetLevel(ulog.LevelDebug)
telemetry.SetMode(ulog.ModeSync, ulog.DefaultWriterOut)
telemetry.SetTheme(ulog.ThemeDark)
telemetry.Info(ulog.DataLog,
    ulog.String("message", "text"),
)
telemetry.Info(ulog.DataMetric,
    ulog.String("name", "payments"),
    ulog.Float64("value", 99.99),
)
telemetry.Info(ulog.DataTrace,
    ulog.String("name", "payment_processing"),
    ulog.Int64("duration", 150),
    ulog.String("span_id", "span-456"),
)
```

Output JSON:

```
{"level":"info","type":"log","message":"text","node_id":"123-abc","trace_id":"abc-123"}
{"level":"info","type":"metric","name":"payments","value":99.99,"node_id":"123-abc","trace_id":"abc-123"}
{"level":"info","type":"trace","name":"payment_processing","duration":150,"span_id":"span-456"}
```

Output TEXT:

```
[INFO] type="log" message="text"
[INFO] type="metric" name="payments" value=99.99
[INFO] type="trace" name="payment_processing" duration=150 span_id="span-456"
```

Name	Description	Values	Default
<code>WithExtractor()</code>	Auto-extract fields from <code>context.Context</code> by key names	<code>keys ...string</code>	
<code>WithFormat()</code>	Output format: structured JSON or human-readable TEXT with optional ANSI colors	<code>FormatJson</code> , <code>FormatText</code>	<code>FormatJson</code>
<code>WithLevel()</code>	Minimum log severity. Only messages at or above this level are written	<code>LevelDebug</code> , <code>LevelError</code> , <code>LevelFatal</code> , <code>LevelInfo</code> , <code>LevelWarn</code>	<code>LevelInfo</code>
<code>WithMode()</code>	Write mode: non-blocking <code>ModeAsync</code> with buffer or blocking <code>ModeSync</code>	<code>ModeAsync</code> , <code>ModeSync</code>	<code>ModeSync</code>
<code>WithTheme()</code>	ANSI color theme for TEXT optimized for dark or light terminals	<code>ThemeDark</code> , <code>ThemeLight</code>	<code>ThemeDark</code>

Name	Description	Values
<code>TypeData</code>	Log messages, Prometheus metrics, Tempo traces	<code>DataLog</code> , <code>DataMetric</code> , <code>DataTrace</code>
<code>TypeField</code>	16 type-safe field constructors	<code>Bool</code> , <code>Bools</code> , <code>Duration</code> , <code>Durations</code> , <code>Error</code> , <code>Errors</code> , <code>Float64</code> , <code>Floats64</code> , <code>Int</code> , <code>Ints</code> , <code>Int64</code> , <code>Ints64</code> , <code>String</code> , <code>Strings</code> , <code>Time</code> , <code>Times</code>

NewTelemetryLog

```
log.Logger
```

```
telemetry := ulog.NewTelemetry(  
    ulog.WithFormat(ulog.FormatText),  
    ulog.WithMode(ulog.ModeSync, ulog.DefaultWriterOut),  
)  
defer telemetry.Close()  
stdLogger := ulog.NewTelemetryLog(ulog.LevelError, telemetry)  
stdLogger.Print("this will be logged as ERROR")  
stdLogger.Printf("user %s failed to login", "john")  
stdLogger.Println("another error message")
```

Output TEXT:

```
[ERROR] type="log" message="this will be logged as ERROR"  
[ERROR] type="log" message="user john failed to login"  
[ERROR] type="log" message="another error message"
```

API / Core /

[Extractor](#) [Format](#) [Level](#) [Mode](#) [Theme](#)

WithExtractor/SetExtractor

[context.Context](#)

```

ctx := context.Background()
ctx = context.WithValue(ctx, "node_id", "123-abc")
ctx = context.WithValue(ctx, "trace_id", "abc-123")
telemetry := ulog.NewTelemetry(
    ulog.WithExtractor("node_id")
)
defer telemetry.Close()
telemetry.InfoWithContext(ctx, ulog.DataLog,
    ulog.String("message", "user login"),
)
telemetry.InfoWithContext(ctx, ulog.DataMetric,
    ulog.String("name", "logins"),
    ulog.Float64("value", 1.0),
)
telemetry.InfoWithContext(ctx, ulog.DataTrace,
    ulog.String("span_id", "def"),
    ulog.String("name", "login"),
    ulog.Int64("duration", 150),
)
telemetry.SetExtractor("trace_id")
telemetry.InfoWithContext(ctx, ulog.DataLog,
    ulog.String("message", "user login"),
)
telemetry.InfoWithContext(ctx, ulog.DataMetric,
    ulog.String("name", "logins"),
    ulog.Float64("value", 1.0),
)
telemetry.InfoWithContext(ctx, ulog.DataTrace,
    ulog.String("span_id", "def"),
    ulog.String("name", "login"),
    ulog.Int64("duration", 150),
)

```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "message":"user login",
  "node_id":"123-abc"
}
{
  "level":"info",
  "type":"metric",
  "name":"logins",
  "value":1.0,
  "node_id":"123-abc"
}
{
  "level":"info",
  "type":"trace",
  "span_id":"def",
  "name":"login",
  "duration":150,
  "node_id":"123-abc"
}
{
  "level":"info",
  "type":"log",
  "message":"user login",
  "trace_id":"abc-123"
}
{
  "level":"info",
  "type":"metric",
  "name":"logins",
  "value":1.0,
  "trace_id":"abc-123"
}
{
  "level":"info",
  "type":"trace",
  "span_id":"def",
  "name":"login",
  "duration":150,
  "trace_id":"abc-123"
}
```

WithFormat/SetFormat

TEXT JSON

```
telemetry := ulog.NewTelemetry(  
    ulog.WithFormat(ulog.FormatJson),  
)  
defer telemetry.Close()  
telemetry.Info(ulog.DataLog,  
    ulog.String("message", "json message"),  
)  
telemetry.SetFormat(ulog.FormatText)  
telemetry.Info(ulog.DataLog,  
    ulog.String("message", "text message"),  
)
```

Output JSON:

```
{"level":"info","type":"log","message":"json message"}
```

Output TEXT:

```
[INFO] type="log" message="text message"
```

WithLevel/SetLevel

```
telemetry := ulog.NewTelemetry(  
    ulog.WithLevel(ulog.LevelDebug),  
)  
defer telemetry.Close()  
telemetry.Debug(ulog.DataLog,  
    ulog.String("message", "debug message"),  
)  
telemetry.Error(ulog.DataLog,  
    ulog.String("message", "error message"),  
)  
telemetry.SetLevel(ulog.LevelInfo)  
telemetry.Info(ulog.DataLog,  
    ulog.String("message", "info message"),  
)  
telemetry.Warn(ulog.DataLog,  
    ulog.String("message", "warn message"),  
)
```

Output JSON:

```
{"level":"debug","type":"log","message":"debug message"}
{"level":"error","type":"log","message":"error message"}
{"level":"info","type":"log","message":"info message"}
{"level":"warn","type":"log","message":"warn message"}
```

WithMode/SetMode

```
telemetry := ulog.NewTelemetry(
    ulog.WithMode(ulog.ModeAsync, ulog.DefaultWriterOut, 1000),
)
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.String("message", "async message"),
)
telemetry.SetMode(ulog.ModeSync, ulog.DefaultWriterOut)
telemetry.Info(ulog.DataLog,
    ulog.String("message", "sync message"),
)
```

Output JSON:

```
{"level":"info","type":"log","message":"async message"}
{"level":"info","type":"log","message":"sync message"}
```

WithTheme/SetTheme

```
telemetry := ulog.NewTelemetry(
    ulog.WithFormat(ulog.FormatText),
    ulog.WithTheme(ulog.ThemeDark),
)
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.String("message", "dark message"),
)
telemetry.SetTheme(ulog.ThemeLight)
telemetry.Info(ulog.DataLog,
    ulog.String("message", "light message"),
)
```

Output TEXT:


```
[INFO] type="log" message="dark message"
[INFO] type="log" message="light message"
```

API / Core /

[DataLog](#) [DataMetric](#) [DataTrace](#) 16
JSON

Data

API

Log

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.String("message", "user login"),
)
```

Output JSON:

```
{
  "level": "info",
  "type": "log",
  "message": "user login"
}
```

Metric

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataMetric,
    ulog.String("name", "logins"),
    ulog.Float64("value", 1.0),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"metric",
  "name":"logins",
  "value":1.0
}
```

Trace

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataTrace,
  ulog.String("span_id", "def"),
  ulog.String("name", "login"),
  ulog.Int64("duration", 150),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"trace",
  "span_id":"def",
  "name":"login",
  "duration":150
}
```

Field

16

Bool

Boolean

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Bool("bool", true),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "bool":true
}
```

Bools

Boolean

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Bools("bools", []bool{true, false}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "bools":[true,false]
}
```

Duration

Duration

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Duration("duration", 5*time.Second),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "duration":"5s"
}
```

Durations

Duration

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Durations("durations", []time.Duration{5*time.Second, 10*time.Second}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "durations":["5s","10s"]
}
```

Error

Error

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Error(fmt.Errorf("err")),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "error":"err"
}
```

Errors

Errors

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Errors([]error{fmt.Errorf("err1"), fmt.Errorf("err2")}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "errors":["err1","err2"]
}
```

Float64

Float64

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Float64("float64", 3.14159),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "float64":3.14159
}
```

Floats64

Float64

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Floats64("floats64", []float64{1.5, 2.5}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "floats64":[1.5,2.5]
}
```

Int

Int

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Int("int", 42),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "int":42
}
```

Ints

Int

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Ints("ints", []int{10, 20, 30}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "ints":[10,20,30]
}
```

Int64

Int64

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Int64("int64", 1234567890),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "int64":1234567890
}
```

Ints64

Int64

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.Ints64("ints64", []int64{1234567890, 9876543210}),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "ints64": [1234567890,9876543210]
}
```

String

String

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
  ulog.String("string", "str"),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "string":"str"
}
```

Strings

String

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Strings("strings", []string{"str1", "str2", "str3"})
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "strings":["str1","str2","str3"]
}
```

Time

Time

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Time("time", time.Date(2026, 4, 22, 12, 0, 0, 0, time.UTC)),
)
```

Output JSON:

```
{
  "level":"info",
  "type":"log",
  "time":"2026-04-22T12:00:00.000000+00:00"
}
```

Times

Time

```
telemetry := ulog.NewTelemetry()
defer telemetry.Close()
telemetry.Info(ulog.DataLog,
    ulog.Times("times", []time.Time{time.Date(2026, 4, 22, 12, 0, 0, 0, time.UTC),time.Date(2
)})
```

Output JSON:


```
{
  "level":"info",
  "type":"log",
  "times":["2026-04-22T12:00:00.000000+00:00","2025-04-22T12:00:00.000000+00:00"]
}
```

API / SinkFile /

SinkHttp

HTTP

NewSinkFile

gzip

—

```
var writer io.Writer = ulog.DefaultWriterOut
sinkFile, err := ulog.NewSinkFile("app.log",
    ulog.WithFileMaxAge(30),
    ulog.WithFileMaxBackups(10),
    ulog.WithFileMaxSize(100),
)
if err != nil {
    fmt.Fprintf(ulog.DefaultWriterErr, "ulog: %v - using stdout instead\n", err)
} else {
    defer sinkFile.Close()
    writer = sinkFile
}
telemetry := ulog.NewTelemetry(
    ulog.WithFormat(ulog.FormatJson),
    ulog.WithMode(ulog.ModeAsync, writer, 10000),
)
defer telemetry.Close()
telemetry.Error(ulog.DataLog,
    ulog.String("message", "critical error"),
    ulog.String("service", "billing"),
)
```

Name	Description	Default
<code>WithFileMaxAge(dayCount)</code>	Maximum days to keep old log files	30
<code>WithFileMaxBackups(fileCount)</code>	Maximum number of old log files to keep	10
<code>WithFileMaxSize(fileSize)</code>	Maximum file size <i>MB</i> before rotation	100

API / SinkFile /

SinkFile

WithFileMaxAge

```
sinkFile, err := ulog.NewSinkFile("app.log",
    ulog.WithFileMaxAge(30),
)
if err != nil {
    fmt.Fprintf(ulog.DefaultWriterErr, "ulog: %v\n", err)
}
defer sinkFile.Close()
```

WithFileMaxBackups

```
sinkFile, err := ulog.NewSinkFile("app.log",
    ulog.WithFileMaxBackups(10),
)
if err != nil {
    fmt.Fprintf(ulog.DefaultWriterErr, "ulog: %v\n", err)
}
defer sinkFile.Close()
```

WithFileMaxSize

```
sinkFile, err := ulog.NewSinkFile("app.log",
    ulog.WithFileMaxSize(100),
)
if err != nil {
    fmt.Fprintf(ulog.DefaultWriterErr, "ulog: %v\n", err)
}
defer sinkFile.Close()
```

API / SinkHTTP /

SinkHttp

HTTP

NewSinkHttp

HTTP

Retry

Sampling

Batching

Circuit Breaker

Deduplication

```

sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpBatch(100, 5*time.Second),
    ulog.WithHttpCircuitBreaker(10, 10*time.Second),
    ulog.WithHttpDedupWindow(5*time.Second),
    ulog.WithHTTPHeader("Authorization", "Bearer token"),
    ulog.WithHttpRetry(3, time.Second),
    ulog.WithHttpSampleRate(100),
    ulog.WithHttpTimeout(30*time.Second),
)
defer sinkHttp.Close()
telemetry := ulog.NewTelemetry(
    ulog.WithFormat(ulog.FormatJson),
    ulog.WithMode(ulog.ModeAsync, sinkHttp, 10000),
)
defer telemetry.Close()
telemetry.Error(ulog.DataLog,
    ulog.String("message", "payment failed"),
    ulog.String("service", "billing"),
)

```

Name	Description
<code>WithHttpBatch(size, flushInterval)</code>	Batch messages: send up to <code>size</code> messages or every <code>flushInterval</code>
<code>WithHttpCircuitBreaker(maxFailures, timeout)</code>	Open circuit after <code>maxFailures</code> errors, wait <code>timeout</code> before recovery
<code>WithHttpDedupWindow(window)</code>	Ignore duplicate messages within <code>window</code> time
<code>WithHttpDisabledBatch()</code>	Disable message batching <i>send immediately</i>
<code>WithHttpDisabledCircuit()</code>	Disable Circuit Breaker
<code>WithHttpDisableKeepAlive()</code>	Disable HTTP Keep-Alive connections
<code>WithHttpFilterData(type)</code>	Filter by data type: <code>DataLog</code> , <code>DataMetric</code> , <code>DataTrace</code>
<code>WithHttpFilterLevel(level)</code>	Filter by minimum level: <code>LevelDebug</code> , <code>LevelError</code> , <code>LevelFatal</code> , <code>LevelInfo</code> , <code>LevelWarn</code>
<code>WithHttpFormatter(fn)</code>	Custom formatter function <code>func(attributes, fields) ([]byte, error)</code>
<code>WithHTTPHeader(key, value)</code>	Add custom HTTP header
<code>WithHttpMethod(method)</code>	HTTP method: <code>POST</code> , <code>PUT</code> , etc.
<code>WithHttpRetry(maxRetries, backoff)</code>	Retry failed requests up to <code>maxRetries</code> times with exponential <code>backoff</code>
<code>WithHttpSampleRate(rate)</code>	Sample 1 out of <code>rate</code> messages for non-error levels
<code>WithHttpSampleWindow(window)</code>	Reset sample counter every <code>window</code>
<code>WithHttpTimeout(timeout)</code>	HTTP client timeout

API / SinkHTTP /

[Discord](#) [Kafka](#) [Loki](#) [Prometheus](#) [Slack](#) [Telegram](#) [Tempo](#) [WeChat](#)
[SinkHttp](#)

NewSinkDiscord

Webhook

Discord

```
sinkDiscord := ulog.NewSinkDiscord("https://discord.com/api/webhooks/...", "MyBot", "")  
defer sinkDiscord.Close()
```

NewSinkKafka

REST Proxy

Apache Kafka

```
sinkKafka := ulog.NewSinkKafka("http://kafka-rest:8082", "logs")  
defer sinkKafka.Close()
```

NewSinkLoki

Grafana Loki

```
sinkLoki := ulog.NewSinkLoki("http://loki:3100", map[string]string{"app": "myapp", "env": "pro"},  
defer sinkLoki.Close())
```

NewSinkPrometheus

Exposition

Prometheus

```
sinkPrometheus := ulog.NewSinkPrometheus("http://pushgateway:9091")  
defer sinkPrometheus.Close()
```

NewSinkSlack

Webhook

Slack

```
sinkSlack := ulog.NewSinkSlack("https://hooks.slack.com/services/...", "ULog", ":robot:", "",  
defer sinkSlack.Close())
```

NewSinkTelegram

Bot API

Telegram

```
sinkTelegram := ulog.NewSinkTelegram("botToken", "chatID")
defer sinkTelegram.Close()
```

NewSinkTempo

Grafana Tempo

```
sinkTempo := ulog.NewSinkTempo("http://tempo:4318")
defer sinkTempo.Close()
```

NewSinkWechat

Webhook

```
sinkWechat := ulog.NewSinkWechat("https://qyapi.weixin.qq.com/cgi-bin/webhook/send?key=...")
defer sinkWechat.Close()
```

API / SinkHTTP /

SinkHttp

WithHttpBatch

size

flushInterval

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpBatch(100, 5*time.Second),
)
defer sinkHttp.Close()
```

WithHttpCircuitBreaker

maxFailures

timeout

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpCircuitBreaker(10, 10*time.Second),
)
defer sinkHttp.Close()
```

WithHttpDedupWindow

window

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpDedupWindow(5*time.Second),
)
defer sinkHttp.Close()
```

WithHttpDisabledBatch

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpDisabledBatch(),
)
defer sinkHttp.Close()
```

WithHttpDisabledCircuit

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpDisabledCircuit(),
)
defer sinkHttp.Close()
```

WithHttpDisableKeepAlive

HTTP Keep-Alive

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpDisableKeepAlive(),
)
defer sinkHttp.Close()
```

WithHttpFilterData

`DataLog` `DataMetric` `DataTrace`

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpFilterData(ulog.DataLog),
)
defer sinkHttp.Close()
```

WithHttpFilterLevel

`LevelDebug` `LevelError` `LevelFatal` `LevelInfo` `LevelWarn`

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpFilterLevel(ulog.LevelError),
)
defer sinkHttp.Close()
```

WithHttpFormatter

`func(attributes, fields) ([]byte, error)`

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpFormatter(func(attributes writeAttributes, fields []Field) ([]byte, error) {
        // 自定义格式化逻辑
        return json.Marshal(fields)
    }),
)
defer sinkHttp.Close()
```

WithHTTPHeader

HTTP

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHTTPHeader("Authorization", "Bearer token"),
    ulog.WithHTTPHeader("X-Custom", "value"),
)
defer sinkHttp.Close()
```

WithHttpMethod

HTTP

`POST` `PUT`

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpMethod("POST"),
)
defer sinkHttp.Close()
```

WithHttpRetry

maxRetries

backoff

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpRetry(3, time.Second),
)
defer sinkHttp.Close()
```

WithHttpSampleRate

1/ rate

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpSampleRate(100),
)
defer sinkHttp.Close()
```

WithHttpSampleWindow

window

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpSampleWindow(1*time.Minute),
)
defer sinkHttp.Close()
```

WithHttpTimeout

HTTP

```
sinkHttp := ulog.NewSinkHttp("http://localhost:8080/logs",
    ulog.WithHttpTimeout(30*time.Second),
)
defer sinkHttp.Close()
```