

License

- **Open Source:** Apache License 2.0

For full details, please see the [LICENSE](#) file in the repository.

Go

```
go get github.com/mikhaildadaev/uuid
```

`uuid` `v1.26.11.`

Run Test

```
go test ./...
go test -bench=. ./...
go test -cover ./...
go test -race ./...
```

Key Features

- UUIDv1..v8 Null — UUID SQL null UUID
- — null UUID
- — POSIX
- — Binary JSON Text /
- SQL — database/sql Scan/Value
- —

Limits

- V2: `posix` `0..255` ;
- V3/V5: `name` `1..512`
- V8: `node` `0..16383` ;

0 512 **name** null UUID

API / Core /

UUID — SQL **NULL** V7
V8 **NewV4** **NewV7**

NewNull

SQL **NULL** UUID

```
un := uuid.NewNull()  
fmt.Println(un.IsZero())  
fmt.Println(un.String())
```

Output TEXT:

```
true  
00000000-0000-0000-0000-000000000000
```

NewV1

MAC UUID 1

```
u1 := uuid.NewV1()  
fmt.Println(u1.Version())
```

Output TEXT:

```
1
```

NewV2

UUID 2 DCE MAC POSIX
UID/GID

```
u2 := uuid.NewV2(posix)
fmt.Println(u2.Version())
```

Output TEXT:

2

NewV3

MD5

UUID

3

```
u3 := uuid.NewV3(uuid.NameSpaceDNS, name)
fmt.Println(u3.Version())
```

Output TEXT:

3

NewV4

UUID

4

```
u4 := uuid.NewV4()
fmt.Println(u4.Version())
```

Output TEXT:

4

NewV5

SHA-1

UUID

5

```
u5 := uuid.NewV5(uuid.NamespaceDNS, name)
fmt.Println(u5.Version())
```

Output TEXT:

5

NewV6

MAC

MAC

UUID

6

UUIDv1

```
u6 := uuid.NewV6()
fmt.Println(u6.Version())
```

Output TEXT:

6

NewV7

UUID

7

Unix

```
u7 := uuid.NewV7()
fmt.Println(u7.Version())
```

Output TEXT:

7

NewV8

UUID 8

```
u8 := uuid.NewV8(node)
fmt.Println(u8.Version())
```

Output TEXT:

8

API / Core /

UUID	NullUUID	String	Version
Timestamp	Node	Sequence	UUID
V8			V1

NULLUUID

IsZero

NullUUID SQL NULL UUID `true`

```
var nu uuid.NullUUID
fmt.Println(nu.IsZero())
nu.Scan("01968727-8c7e-8000-87cb-bdba4f634d9f")
fmt.Println(nu.IsZero())
```

Output TEXT:

```
true  
false
```

String

UUID	8-4-4-4-12	00000000-0000-0000-0000-
000000000000		

```
var nu uuid.NullUUID  
fmt.Println(nu.String())  
nu.Scan("01968727-8c7e-8000-87cb-bdba4f634d9f")  
fmt.Println(nu.String())
```

Output TEXT:

```
00000000-0000-0000-0000-000000000000  
01968727-8c7e-8000-87cb-bdba4f634d9f
```

Validate

NullUUID	UUID	nil	SQL
UUID			

```
var nu uuid.NullUUID  
fmt.Println(nu.Validate())  
nu.Scan("01968727-8c7e-8000-87cb-bdba4f634d9f")  
fmt.Println(nu.Validate())
```

Output TEXT:

```
<nil>  
<nil>
```

UUID

Bytes

UUID 16

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Printf("%x\n", uu.Bytes())
```

Output TEXT:

```
019687278c7e800087cbbdba4f634d9f
```

Equal

UUID

UUID

true

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
other := uu
fmt.Println(uu.Equal(other))
```

Output TEXT:

```
true
```

Info

UUID

POSIX

```

uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Info())

```

Output TEXT:

```

UUID: 01968727-8c7e-8000-87cb-bdba4f634d9f
VAR.: RFC4122
VER.: 8
FORM: TTTTTTTT-TTTT-8SSS-VNNN-RRRRRRRRRRRR
INFO: TIME (1-milliseconds interval since 1970-01-01) + SEQUENCE (0-4095) + NODE
TIME: 1746024238206 [2025-04-30 14:43:58.206 +0000 UTC]
SEQ.: 0
NODE: 1995
RAND: bdba4f634d9f

```

IsZero

UUID	16	true
------	----	------

```

uu := uuid.NewNull()
fmt.Println(uu.IsZero())

```

Output TEXT:

```

true

```

Node

UUID	V1	V2	V6	V8	0
------	----	----	----	----	---

```

uuidNode := 1995
u8 := uuid.NewV8(uuidNode)
fmt.Println(u8.Node())

```


Output TEXT:

1995

Posix

UUID	V2	POSIX UID/GID	0
------	----	---------------	---

```
uuidPosType := 0
uuidPosValue := 501
u2 := uuid.NewV2(uuidPosType, uuidPosValue)
fmt.Println(u2.Posix())
```

Output TEXT:

UID 501

Sequence

UUID	V1	V2	V6	V7	0
------	----	----	----	----	---

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Sequence())
```

Output TEXT:

0

String

UUID	8-4-4-4-12
------	------------

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.String())
```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

Timestamp

UUID	V1	V2	V6	V7
------	----	----	----	----

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Timestamp())
```

Output TEXT:

```
1746024238206
```

Validate

UUID	UUID
------	------

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Validate())
```

Output TEXT:

<nil>

Variant

UUID UUID 1 RFC 4122

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Variant())
```

Output TEXT:

1

Version

UUID 1 8 null UUID 0

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.Version())
```

Output TEXT:

8

API / Marshal /

	UUID	Binary	Json	Text
UUID	— V1	V8	Null	

NULLUUID

MarshalBinary

NullUUID 16

```
var nu uuid.NullUUID
data, err := nu.MarshalBinary()
if err != nil {
    fmt.Println(err)
}
fmt.Printf("%x\n", data)
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
nu.Scan(uuidV8String)
data, err = nu.MarshalBinary()
if err != nil {
    fmt.Println(err)
}
fmt.Printf("%x\n", data)
```

Output TEXT:

019687278c7e800087cbbdba4f634d9f

MarshalJson

NullUUID Json null

```

var nu uuid.NullUUID
data, err := nu.MarshalJson()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
nu.Scan(uuidV8String)
data, err := nu.MarshalJson()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))

```

Output TEXT:

```

null
"01968727-8c7e-8000-87cb-bdba4f634d9f"

```

MarshalText

NullUUID

```

var nu uuid.NullUUID
data, err := nu.MarshalText()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
nu.Scan(uuidV8String)
data, err := nu.MarshalText()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))

```

Output TEXT:

```

01968727-8c7e-8000-87cb-bdba4f634d9f

```

UnmarshalBinary

16

NullUUID

Valid

```
var nu uuid.NullUUID
data := []byte{}
if err := nu.UnmarshalBinary(data); err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
uuidV8Binary := []byte{0x01, 0x96, 0x87, 0x27, 0x8c, 0x7e, 0x80, 0x00, 0x87, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00}
err := nu.UnmarshalBinary(uuidV8Binary)
if err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
```

Output TEXT:

```
Valid: false
UUID: 00000000-0000-0000-0000-000000000000
Valid: true
UUID: 01968727-8c7e-8000-87cb-bdba4f634d9f
```

UnmarshalJson

Json

NullUUID

null

SQL NULL

UUID

```
var nu uuid.NullUUID
data := []byte(`null`)
if err := nu.UnmarshalJson(data); err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
uuidV8Json := []byte(`"01968727-8c7e-8000-87cb-bdba4f634d9f"`)
err := nu.UnmarshalJson(uuidV8Json)
if err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
```

Output TEXT:

```
Valid: false
UUID: 00000000-0000-0000-0000-000000000000
Valid: true
UUID: 01968727-8c7e-8000-87cb-bdba4f634d9f
```

UnmarshalText

NullUUID

SQL NULL

```
var nu uuid.NullUUID
data := []byte("")
if err := nu.UnmarshalText(data); err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
uuidV8Text := []byte("01968727-8c7e-8000-87cb-bdba4f634d9f")
err := nu.UnmarshalText(uuidV8Text)
if err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
```

Output TEXT:

```
Valid: false
UUID: 00000000-0000-0000-0000-000000000000
Valid: true
UUID: 01968727-8c7e-8000-87cb-bdba4f634d9f
```

UUID

MarshalBinary

UUID

16

```

uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
data, err := uu.MarshalBinary()
if err != nil {
    fmt.Println(err)
}
fmt.Printf("%x\n", data)

```

Output TEXT:

```
019687278c7e800087cbbdba4f634d9f
```

MarshalJson

UUID	8-4-4-4-12	Json
------	------------	------

```

uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
data, err := uu.MarshalJson()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))

```

Output TEXT:

```
"01968727-8c7e-8000-87cb-bdba4f634d9f"
```

MarshalText

UUID	32
------	----


```

uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
data, err := uu.MarshalText()
if err != nil {
    fmt.Println(err)
}
fmt.Println(string(data))

```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

UnmarshalBinary

16

UUID

16

```

var uu uuid.UUID
uuidV8Binary := []byte{0x01, 0x96, 0x87, 0x27, 0x8c, 0x7e, 0x80, 0x00, 0x87, 0x
err := uu.UnmarshalBinary(uuidV8Binary)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.String())

```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

UnmarshalJson

Json

UUID

```

var uu uuid.UUID
uuidV8Json := []byte(`"01968727-8c7e-8000-87cb-bdba4f634d9f"`)
err := uu.UnmarshalJson(uuidV8Json)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.String())

```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

UnmarshalText

32

UUID

```

var uu uuid.UUID
uuidV8Text := []byte("01968727-8c7e-8000-87cb-bdba4f634d9f")
err := uu.UnmarshalText(uuidV8Text)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.String())

```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

API / SQL /

UUID

database/sql

NULL

Scan

Value

UUID

SQL

NULLUUID

Scan

UUID	sql.Scanner	nil	SQL NULL	UUID	/
UUID	Valid	true	NULL	false	

```
var nu uuid.NullUUID
if err := nu.Scan(nil); err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
if err := nu.Scan(uuidV8String); err != nil {
    fmt.Println(err)
}
fmt.Println("Valid:", nu.Valid)
fmt.Println("UUID:", nu.UUID)
```

Output TEXT:

```
Valid: false
UUID: 00000000-0000-0000-0000-000000000000
Valid: true
UUID: 01968727-8c7e-8000-87cb-bdba4f634d9f
```

Value

UUID	driver.Valuer	Valid	false	nil	Valid
true	UUID				

```
var nu uuid.NullUUID
value, _ := nu.Value()
fmt.Println(value)
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
nu.Scan(uuidV8String)
value, _ = nu.Value()
fmt.Println(value)
```

Output TEXT:

```
<nil>
01968727-8c7e-8000-87cb-bdba4f634d9f
```

UUID

Scan

`sql.Scanner`

UUID—

nil *NULL*

```
var uu uuid.UUID
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
err := uu.Scan(uuidV8String)
if err != nil {
    fmt.Println(err)
}
fmt.Println(uu.String())
```

Output TEXT:

```
01968727-8c7e-8000-87cb-bdba4f634d9f
```

Value

`driver.Valuer`

UUID

UUID

nil

```
uuidV8String := "01968727-8c7e-8000-87cb-bdba4f634d9f"
uu, err := uuid.Parse(uuidV8String)
if err != nil {
    fmt.Println(err)
}
value, err := uu.Value()
if err != nil {
    fmt.Println(err)
}
fmt.Println(value)
```

Output TEXT:

01968727-8c7e-8000-87cb-bdba4f634d9f