```
Admin@DESKTOP-U0T8F2T MINGW64 /d/danit_homework (main)
$ cd hw23; kubectl apply -f nginx-service.yaml
service/nginx1-svc created

Admin@DESKTOP-U0T8F2T MINGW64 /d/danit_homework/hw23 (main)
$ kubectl get svc nginx1-svc
NAME          TYPE       CLUSTER-IP      EXTERNAL-IP   PORT(S)        AGE
nginx1-svc    NodePort   10.97.152.226   <none>        80:30570/TCP   2m18s

Admin@DESKTOP-U0T8F2T MINGW64 /d/danit_homework/hw23 (main)
$
```

```
Admin@DESKTOP-U0T8F2T MINGW64 /d/danit_homework/hw23 (main)
$ kubectl get pod
NAME     READY   STATUS    RESTARTS   AGE
nginx1   1/1     Running   0          31m
```

```
Admin@DESKTOP-U0T8F2T MINGW64 /d/danit_homework/hw23 (main)
$ minikube service nginx1-svc
```

NAMESPACE	NAME	TARGET PORT	URL
default	nginx1-svc	80	http://192.168.49.2:30570

```
Starting tunnel for service nginx1-svc.
```

NAMESPACE	NAME	TARGET PORT	URL
default	nginx1-svc		http://127.0.0.1:50812

```
Opening service default/nginx1-svc in default browser...
Because you are using a Docker driver on windows, the terminal needs to be open to run it.
```

