

# Beautiful IO

A tour through standard library `pkg/io` and various implementations of its interfaces.

Golab 2019, 2019–10–21, Florence

Martin Czygan

# About me

SWE [@ubleipzig](#) working mostly with Python and Go.

Taming data – open source – writing.

| [Explore IO](#) workshop at Golab 2017.

# Background

- Go Proverbs (2015)

| The bigger the interface, the weaker the abstraction.

Prominent examples are `io.Reader` and `io.Writer`.

# The IO package

- contains basic, widely used interfaces (within and outside standard library)
- utility functions

# Why beautiful?

La bellezza è negli occhi di chi guarda

- small, versatile interfaces
- composable

# Praise and love

This article aims to convince you to use `io.Reader` in your own code wherever you can. -- [@matryer](#)

"Crossing Streams: a love letter to Go `io.Reader`" -- [@jmoiron](#)

Which brings me to `io.Reader`, easily my favourite Go interface. --  
[@davecheney](#)

# What's in pkg/io?

- 25 types
- 21/25 are interfaces
- 12 functions, 3 constants, 6 errors

The concrete types are: `LimitedReader`, `PipeReader`, `PipeWriter`, `SectionReader`; functions: `Copy`, `CopyN`, `CopyBuffer`, `Pipe`, `ReadAtLeast`, `ReadFull`, `WriteString`, `LimitReader`, `MultiReader`, `TeeReader`, `NewSectionReader`, `MultiWriter`

# A few Interfaces

	R	W	C	S
io.Reader	x			
io.Writer		x		
io.Closer			x	
io.Seeker				x
io.ReadWriter	x	x		
io.ReadCloser	x		x	
io.ReadSeeker	x			x
io.WriteCloser		x	x	
io.WriterSeeker		x		x
io.ReadWriteCloser	x	x	x	
io.ReadWriteSeeker	x	x		x



# Missing interfaces

You might find some missing pieces elsewhere.

```
https://github.com/go4org/go4/blob/94abd6928b1da39b1d757b60c93fb2419c409  
... 33 // A ReadSeekCloser can Read, Seek, and Close.  
34 type ReadSeekCloser interface {  
35     io.Reader  
36     io.Seeker  
37     io.Closer  
38 }  
39  
40 type ReaderAtCloser interface {  
41     io.ReaderAt  
42     io.Closer  
43 }
```

# How many readers, writers are there?

```
$ guru -json implements /usr/local/go/src/io/io.go:#3309
```

I counted over 280 implementations of `io.Reader` and X of `io.Writer`.

# What is a Reader?

```
type Reader interface {  
    Read(p []byte) (n int, err error)  
}
```

The reader implementation will populate a given byte slice.

- at most `len(p)` bytes are read
- to signal the end of a stream, return `io.EOF`

There is some flexibility around the end of a stream.

Callers should always process the  $n > 0$  bytes returned before considering the error `err`. Doing so correctly handles I/O errors that happen after reading some bytes and also both of the allowed EOF behaviors.

# Notes

```
type Reader interface {  
    Read(p []byte) (n int, err error)  
}
```

- The byte slice is under the control of the caller.

Implementations must not retain p.

This hints at the streaming nature of this interface.


# Implementations

- files
- network connections
- HTTP response bodies
- standard input and output
- compression
- hashing
- encoding
- formatting
- ...

Many uses in testing as well.

# Structural typing

- conversions are not required, a file implements `Read` and hence *is* a `io.Reader`



The screenshot shows the Stack Overflow interface. The header includes the Stack Overflow logo, a 'Products' link, a search bar, and a notification icon with '139'. The left sidebar contains navigation links: 'Home', 'PUBLIC', 'Stack Overflow' (selected), 'Tags', 'Users', 'Jobs', 'TEAMS', 'What's this?', and 'First 10 Free'. The main content area displays a question titled 'Create a io.Reader from a local file'. Below the title, it says 'Asked 5 years, 1 month ago', 'Active 1 month ago', and 'Viewed 58k times'. The question text is 'I would like to open a local file, and return a `io.Reader`. The reason is that I need to feed a `io.Reader` to a library I am using, like:'. Below the text is a code block containing a Go function signature: 

```
func read(r io.Reader) (results []string) {  
    }  
}
```

. To the left of the code block are up and down vote arrows, the number '67', a star icon, and the number '8'. At the bottom of the question are 'go' and 'Edit tags' buttons.

stackoverflow Products Search... 139,

Home

PUBLIC

Stack Overflow

Tags

Users

Jobs

TEAMS What's this?

First 10 Free

## Create a io.Reader from a local file

Asked 5 years, 1 month ago Active 1 month ago Viewed 58k times

I would like to open a local file, and return a `io.Reader`. The reason is that I need to feed a `io.Reader` to a library I am using, like:

```
func read(r io.Reader) (results []string) {  
    }  
}
```

67

8 go Edit tags

# Streams

As layed out in the *love letter*, the use of `ioutil.ReadAll` is debatable. It's in the standard library and useful, but not always necessary.

```
b, err := ioutil.ReadAll(r)
...
```

# Streams

- you may lose the advantage to use the `Reader` in other places
- you may consume more memory

Streams can trivially produce infinite output while using barely any memory at all - imagine an implementation behaving like `/dev/zero` or `/dev/urandom`.

- Memory control is an important advantage.



# Follow the stream

Instead of writing:

```
b, _ := ioutil.ReadAll(resp.Body) // Pressure on memory.  
fmt.Println(string(b))
```

You may want to connect streams:

```
_, _ = io.Copy(os.Stdout, resp.Body)
```

# Stream advantages

- memory efficient
- can work with data, that does not fit in memory
- allows to work on different protocol parts differently (e.g. HTTP header vs HTTP body)

## Another example

We often need to unmarshal JSON.

```
_ = json.Unmarshal(data, &v) // data might come from ioutil.ReadAll(resp.Body)
```

But we can decode it as well.

```
_ = json.NewDecoder(resp.Body).Decode(&v)
```

In this case, the JSON data must be fully read, so this is a weak example.

# Glipse at composition

But what is we want need to preprocess the data, e.g. decompress it. Streams compose well.

```
zr, _ = gzip.NewReader(resp.Body)
_ json.NewDecoder(zr).Decode(&
```

