

Beautiful IO

A tour through standard library `pkg/io` and various implementations of its interfaces.

Golab 2019, 2019–10–21, Florence

Martin Czygan

About me

SWE [@ubleipzig](#) working mostly with Python and Go.

Taming data – open source – writing.

| [Explore IO](#) workshop at Golab 2017.

Background

- Go Proverbs (2015)

| The bigger the interface, the weaker the abstraction.

Prominent examples are `io.Reader` and `io.Writer`.

The IO package

- contains basic, widely used interfaces (within and outside standard library)
- utility functions

Why beautiful?

La bellezza è negli occhi di chi guarda

- small, versatile interfaces
- composable

Praise and love

This article aims to convince you to use `io.Reader` in your own code wherever you can. -- [@matryer](#)

"Crossing Streams: a love letter to Go `io.Reader`" -- [@jmoiron](#)

Which brings me to `io.Reader`, easily my favourite Go interface. --
[@davecheney](#)

What's in pkg/io?

- 25 types
- 21/25 are interfaces
- 12 functions, 3 constants, 6 errors

The concrete types are: `LimitedReader`, `PipeReader`, `PipeWriter`, `SectionReader`; functions: `Copy`, `CopyN`, `CopyBuffer`, `Pipe`, `ReadAtLeast`, `ReadFull`, `WriteString`, `LimitReader`, `MultiReader`, `TeeReader`, `NewSectionReader`, `MultiWriter`

A few Interfaces

	R	W	C	S
io.Reader	x			
io.Writer		x		
io.Closer			x	
io.Seeker				x
io.ReadWriter	x	x		
io.ReadCloser	x		x	
io.ReadSeeker	x			x
io.WriteCloser		x	x	
io.WriteSeeker		x		x
io.ReadWriteCloser	x	x	x	
io.ReadWriteSeeker	x	x		x

Missing interfaces

You might find some missing pieces elsewhere.

```
https://github.com/go4org/go4/blob/94abd6928b1da39b1d757b60c93fb2419c409  
... 33 // A ReadSeekCloser can Read, Seek, and Close.  
34 type ReadSeekCloser interface {  
35     io.Reader  
36     io.Seeker  
37     io.Closer  
38 }  
39  
40 type ReaderAtCloser interface {  
41     io.ReaderAt  
42     io.Closer  
43 }
```

How many readers, writers are there?

```
$ guru -json implements /usr/local/go/src/io/io.go:#3309,#3800
```

I counted over 200 implementations of each, `io.Reader` and `io.Writer` in the Go tree and subrepositories.

What is a Reader?

```
type Reader interface {  
    Read(p []byte) (n int, err error)  
}
```

The reader implementation will populate a given byte slice.

- at most `len(p)` bytes are read
- to signal the end of a stream, return `io.EOF`

There is some flexibility around the end of a stream.

Callers should always process the $n > 0$ bytes returned before considering the error `err`. Doing so correctly handles I/O errors that happen after reading some bytes and also both of the allowed EOF behaviors.

Notes

```
type Reader interface {  
    Read(p []byte) (n int, err error)  
}
```

- The byte slice is under the control of the caller.

Implementations must not retain p.

This hints at the streaming nature of this interface.

Implementations

Readers can be:

- files
- network connections
- HTTP response bodies
- standard input
- compression
- serialization
- ...

Writers are use for hash functions, standard output, formatting, and more.

Structural typing

- conversions are not required, a file implements `Read` and hence *is* a `io.Reader`



The screenshot shows the Stack Overflow interface. The header includes the Stack Overflow logo, a 'Products' link, a search bar, and a notification icon with '139'. The left sidebar contains navigation links: 'Home', 'PUBLIC', 'Stack Overflow' (selected), 'Tags', 'Users', 'Jobs', 'TEAMS', 'What's this?', and 'First 10 Free'. The main content area displays a question titled 'Create a io.Reader from a local file'. Below the title, it says 'Asked 5 years, 1 month ago', 'Active 1 month ago', and 'Viewed 58k times'. The question text is 'I would like to open a local file, and return a `io.Reader`. The reason is that I need to feed a `io.Reader` to a library I am using, like:'. Below the text is a code block containing a Go function:

```
func read(r io.Reader) (results []string) {  
    }  
}
```

. To the left of the code block are up and down vote arrows, the number '67', a star icon, and the number '8'. At the bottom of the question are 'go' and 'Edit tags' buttons.

stackoverflow Products Search... 139,

Home

PUBLIC

Stack Overflow

Tags

Users

Jobs

TEAMS What's this?

First 10 Free

Create a io.Reader from a local file

Asked 5 years, 1 month ago Active 1 month ago Viewed 58k times

I would like to open a local file, and return a `io.Reader`. The reason is that I need to feed a `io.Reader` to a library I am using, like:

```
func read(r io.Reader) (results []string) {  
    }  
}
```

67

8 go Edit tags

Streams

As layed out in the *love letter*, the use of `ioutil.ReadAll` is debatable. It's in the standard library and useful, but not always necessary.

```
b, err := ioutil.ReadAll(r)
...
```

Streams

- you may lose the advantage to use the `Reader` in other places
- you may consume more memory

Streams can trivially produce infinite output while using barely any memory at all - imagine an implementation behaving like `/dev/zero` or `/dev/urandom`.

- Memory control is an important advantage.

Follow the stream

Instead of writing:

```
b, _ := ioutil.ReadAll(resp.Body) // Pressure on memory.  
fmt.Println(string(b))
```

You may want to connect streams:

```
_, _ = io.Copy(os.Stdout, resp.Body)
```

Stream advantages

- memory efficient
- can work with data, that does not fit in memory
- allows to work on different protocol parts differently (e.g. HTTP header vs HTTP body)

Another example

We often need to unmarshal JSON.

```
_ = json.Unmarshal(data, &v) // data might come from ioutil.ReadAll(resp.Body)
```

But we can decode it as well.

```
_ = json.NewDecoder(resp.Body).Decode(&v)
```

In this case, the JSON data must be fully read, so this is a weak example.

Glipse at composition

But what is we want need to preprocess the data, e.g. decompress it. Streams compose well.

```
zr, _ = gzip.NewReader(resp.Body)
_ json.NewDecoder(zr).Decode(&
```

How do you implement one yourself?

You only need a `Read` method with the correct signature.

- Example: `/dev/zero`

```
type devZero struct{}

func (r *devZero) Read(p []byte) (int, error) {
    for i := 0; i < len(p); i++ {
        p[i] = '\x00'
    }
    return len(p), nil
}
```

This is already an infinite stream.

Embed a reader

Often you want to transform a given data stream, so you embed it.

```
type UpperReader struct {  
    r io.Reader // Underlying stream  
}  
  
func (r *UpperReader) Read(p []byte) (int, error) {  
    n, err := r.r.Read(p)  
    copy(p, bytes.ToUpper(p))  
    return n, err  
}  
  
func main() {  
    if _, err := io.Copy(os.Stdout, &UpperReader{os.Stdin}); err != nil {  
        log.Fatal(err)  
    }  
}
```

- Also try: <https://tour.golang.org/methods/22> (Reader exercise, ROT13)

The io.Writer interface

Analogous to the `io.Reader` interface.

```
type Writer interface {  
    Write(p []byte) (n int, err error)  
}
```

Write writes `len(p)` bytes from `p` to the underlying data stream. It returns the number of bytes written from `p` ($0 \leq n \leq \text{len}(p)$) and any error encountered that caused the write to stop early.

Write must return a non-nil error if it returns $n < \text{len}(p)$. Write must not modify the slice data, even temporarily.

As with readers:

Implementations must not retain `p`.

An example

A writer that does not much, but is still useful - `/dev/null` in Go:

```
type devNull struct{}

func (w *devNull) Write(p []byte) (int, error) {
    return len(p), nil
}

func main() {
    if n, err := io.Copy(&devNull{}, strings.NewReader("Hello World")); err != nil {
        log.Fatal(err)
    } else {
        log.Printf("%d bytes copied", n)
    }
}
```

The standard library implementation is called `ioutil.Discard` (for an interesting/frustrating bug related to `ioutil.Discard`, I recommend [#4589](#)).

Use cases

Interfaces may:

- abstract a resource
- conversion to stream
- buffers
- enhance functionality (decorate)
- mock behaviour (testing)

Resource `os.File`

Prototypical stream: A file.

- `os.File`

And alternatives and substitutions, e.g. dummy files for tests or file that support atomic writes.

Historical note



A file is simply a sequence of bytes. Its main attribute is its size. By contrast, on more conventional systems, a file has a dozen or so attributes. To specify and create a file it takes endless amount of chit-chat. If you are on a UNIX system you can simply ask for a file and use it interchangeble wherever you want a file.

If a file is just a sequence of bytes, more things will look like files.

Resource net.Conn

Conn is a generic stream-oriented network connection.

```
type Conn interface {  
    // Read reads data from the connection.  
    // Read can be made to time out and return an Error with Timeout() == true  
    // after a fixed time limit; see SetDeadline and SetReadDeadline.  
    Read(b []byte) (n int, err error)  
    ...  
    // Write writes data to the connection.  
    // Write can be made to time out and return an Error with Timeout() == true  
    // after a fixed time limit; see SetDeadline and SetWriteDeadline.  
    Write(b []byte) (n int, err error)  
    ...  
}
```

Conversion: strings

Turing strings and byte slices into streams.

```
r := strings.NewReader("might help testing")
```

Buffers: `bytes.Buffer`

A Buffer is a variable-sized buffer of bytes with Read and Write methods. The zero value for Buffer is an empty buffer ready to use.

The byte slice of the streaming world.

```
var buf bytes.Buffer
_, _ = io.WriteString(&buf, "data")
```

Enhancement: bufio.Reader

Package bufio implements buffered I/O. It wraps an io.Reader or io.Writer object, creating another object (Reader or Writer) that also implements the interface but provides buffering and some help for textual I/O.

```
// Reader implements buffering for an io.Reader object.
type Reader struct {
    buf      []byte
    rd        io.Reader // reader provided by the client
    r, w      int       // buf read and write positions
    err       error
    lastByte  int // last byte read for UnreadByte; -1 means invalid
    lastRuneSize int // size of last rune read for UnreadRune; -1 means invalid
}
```

Enhancement: `bufio.Reader`

Provides simplifications, e.g. to read up to given delimiters, e.g. linewise reads.

A further abstraction, `bufio.Scanner` is built from a reader, which allows to process a stream, by splitting into a sequence of tokens.

Thanks