



QPL9058


0.5 – 6.0 GHz Ultra Low-Noise LNA

Product Overview

The QPL9058 is a high-linearity, ultra-low noise amplifier in a small 2 x 2 mm surface-mount package. At 3.6 GHz, the amplifier typically provides 18 dB gain, +36 dBm OIP3 at a 55 mA bias setting, and 0.6 dB noise figure. The LNA can be biased from a single positive supply ranging from 3.3 to 5 volts. The device is housed in a green/RoHS-compliant industry-standard 2x2 mm package.

The QPL9058 is bias adjustable and requires minimal external components to operate. It also has a power down control capability integrated into the die for TDD applications.

Functional Block Diagram



8 Pin 2X2 mm DFN Package

Key Features

- 0.5-6.0 GHz Operational Bandwidth
- Low noise figure, 0.6 dB NF @ 3.6 GHz
- 36 dBm OIP3
- 18 dB small signal gain
- Bias adjustable for linearity optimization
- Unconditionally stable
- Shut-down mode pin with 1.8V logic
- Maintains OFF state with high Pin drive

Applications

- 5G m-MIMO
- Repeaters / DAS
- Mobile Infrastructure
- LTE / WCDMA / CDMA / GSM
- General Purpose Wireless
- TDD or FDD systems

Ordering Information

| Part No. | Description |
|--------------|------------------------------|
| QPL9058TR7 | 2500 pieces on a 7" reel |
| QPL9058EVB01 | 0.5-6.0 GHz Evaluation Board |

Absolute Maximum Ratings

| Parameter | Rating |
|-------------------------------------|---------------|
| Storage Temperature | -65 to +150°C |
| Supply Voltage (V_{DD}) | 7 V |
| RF Input Power, CW, 50Ω, T=25°C | 27 dBm |
| RF Input Power, LTE 9dB PAR, T=25°C | 22 dBm |

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability.

Recommended Operating Conditions

| Parameter | Min | Typ | Max | Units |
|------------------------------------|-------|-----|-------|-------|
| Supply Voltage (V_{DD}) | +3.15 | +5 | +5.25 | V |
| T_{CASE} | -40 | | +105 | °C |
| Tj for >10 ⁶ hours MTTF | | | 190 | °C |

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.



Electrical Specifications

| Parameter | Conditions ⁽¹⁾ | Min | Typ | Max | Units |
|--------------------------------|--|------|-------|----------|-------|
| Operational Frequency Range | | 500 | | 6000 | MHz |
| Test Frequency | | | 3600 | | MHz |
| Gain | | | 18.0 | | dB |
| Input Return Loss | | | 15.0 | | dB |
| Output Return Loss | | | 19.5 | | dB |
| Noise Figure ⁽²⁾ | | | 0.59 | | dB |
| Output P1dB | | | +20.6 | | dBm |
| Output IP3 | Pout=+2 dBm/tone, Δf=1 MHz | | +36.4 | | dBm |
| Power Shutdown Control (pin 5) | On state | 0 | | 0.63 | V |
| | Off state (Power down) | 1.17 | | V_{DD} | V |
| Current, I_{DD} | On state | | 54 | | mA |
| | Off state (Power down) | | 4 | | mA |
| Shutdown pin current, I_{SD} | $V_{PD} = 1.8$ V | | 18 | | μA |
| Switching Time (LNA On) | 50% DC to 0.5dB of settled power/gain | | 60 | | ns |
| Switching Time (LNA Off) | 50% DC to -20dB from LNA On power/gain | | 41 | | ns |
| Thermal Resistance | Channel to case | | 48 | | °C/W |

Notes:

1. Test conditions unless otherwise noted: $V_{DD} = +5.0$ V, Temp = +25 °C, 50 Ω system.
2. Input trace loss de-embedded from NF data.

Evaluation Board – QPL9058EVB01



Notes:

1. See Evaluation Board PCB Information section for material and stack-up.
2. All components are of 0402 size unless otherwise mentioned.
3. For TDD Applications: R1 = 0 Ω and R2 = 220K.
4. For FDD Applications: R2 = 220K 'OR' Pin 5 tied to ground. R1 = DNP/Omitted
5. A through line is included on the evaluation board to de-embed the board losses.
6. R4 sets the current draw. Can be changed for the desired bias point.

Bill of Material – QPL9058EVB01

| Reference Des. | Value | Description | Manuf. | Part Number |
|----------------|-----------------|---------------------------------|-----------|--------------------|
| N/A | N/A | Printed Circuit Board | Qorvo | |
| U1 | n/a | Ultra Low Noise QPL9058 LNA | Qorvo | QPL9058 |
| R1, R3 | 0 Ω | Resistor, chip, 0402, 1%, 1/10W | various | |
| R2 | 220 K Ω | Resistor, chip, 0402, 5%, 1/16W | various | |
| R4 | 3.83 K Ω | Resistor, Chip, 0402, 1%, 1/16W | various | |
| C1, C2, C6, C7 | 15 pF | Cap., Chip, 0402, 2%, 50V, HI-Q | Murata | GJM1555C1H150JB01D |
| C3, C5 | 1000 pF | Cap., Chip, 0402, 10%, 50V, X7R | Murata | GRM155R71H102KA01D |
| C4 | 0.1 uF | Cap., Chip, 0402, 10%, 50V, X5R | various | |
| L1 | 18 nH | Inductor, coil, 0603, 5% | Coilcraft | 0603CS-18NXJL |

Typical Performance – QPL9058EVB01

Test conditions unless otherwise noted: $V_{DD} = +5\text{ V}$, $I_{DD} = 55\text{ mA}$ (typ.), Temp = +25°C


| Parameter | Conditions | Typical Values | | | Units |
|-----------------------------|---|----------------|------|------|-------|
| Frequency | | 2500 | 3600 | 4900 | MHz |
| Gain | | 18.2 | 18.0 | 18.9 | dB |
| Input Return Loss | | 14.3 | 14.7 | 9.8 | dB |
| Output Return Loss | | 23.1 | 20.0 | 13.5 | dB |
| Output P1dB | | 20.6 | 20.5 | 16.6 | dBm |
| OIP3 | $P_{out}=+2\text{ dBm/ tone}$, $\Delta f=1\text{ MHz}$ | 32.6 | 36.0 | 33.9 | dBm |
| Noise figure ⁽¹⁾ | | 0.47 | 0.62 | 0.56 | dB |

Notes:

1. Input trace loss de-embedded from NF data




Performance Plots – QPL9058EVB01

Test conditions unless otherwise noted: $V_{DD} = +5\text{ V}$, $I_{DD} = 55\text{ mA}$.



Performance Plots – QPL9058EVB01 Continued


Test conditions unless otherwise noted: $V_{DD} = +5\text{ V}$, $I_{DD} = 55\text{ mA}$.



Notes:

1. Input trace loss de-embedded from NF. NF at cold temp is better than 0.3dB causing measurement uncertainties. Therefore, not shown on the plot

Pad Configuration and Description




Top View


| Pad No. | Label | Description |
|-----------------|-------------------|--|
| 1 | V _{bias} | Sets the LNA bias current for the device. |
| 2 | RF In | RF Input pin, internally matched to 50 ohms. A DC block is required. |
| 5 | Shut Down | A high voltage (>1.17V) turns off the device. If the pin is pulled to ground or driven with a voltage less than 0.63V, then the device will operate under LNA ON state. |
| 7 | RF Out | RF Output pin, internally matched to 50 ohms. A DC block is required. V _{DD} supply pin. |
| 3, 4, 6, 8 | NC | Not connected internally. This pin may be left floating or connected to ground. |
| Backside Paddle | RF/DC GND | Ground connection. The back side of the package should be connected to the ground plan though as short of a connection as possible. PCB vias under the device are recommended. |

Evaluation Board PCB Information

Qorvo PCB Material and Stack-up




50 ohm line dimensions: width = 0.0182", spacing = 0.020"



Package Marking and Dimensions

Marking: Part Number – 9058


Trace Code – XXXX up to 4 Characters assigned by sub-contractor



Notes:

1. All dimensions are in millimeters. Angles are in degrees.
2. The terminal #1 identifier and terminal numbering conform to SPE-000677.
3. Contact plating: NiPdAu


Recommended PCB Layout Pattern




Notes:

1. All dimensions are in millimeters. Angles are in degrees.
2. Use 1 oz. copper minimum for top and bottom layer metal.
3. Via holes are required under the backside paddle of this device for proper RF/DC grounding and thermal dissipation. We recommend a 0.35mm (#80/.0135") diameter bit for drilling via holes and a final plated thru diameter of 0.25 mm (0.01").
4. Ensure good package backside paddle solder attach for reliable operation and best electrical performance.

Tape and Reel Information – Carrier and Cover Tape Dimensions




| Feature | Measure | Symbol | Size (in) | Size (mm) |
|---------------------|--|--------|-----------|-----------|
| Cavity | Length | A0 | 0.091 | 2.30 |
| | Width | B0 | 0.091 | 2.30 |
| | Depth | K0 | 0.039 | 1.00 |
| | Pitch | P1 | 0.157 | 4.00 |
| Centerline Distance | Cavity to Perforation - Length Direction | P2 | 0.079 | 2.00 |
| | Cavity to Perforation - Width Direction | F | 0.138 | 3.50 |
| Cover Tape | Width | C | 0.213 | 5.40 |
| Carrier Tape | Width | W | 0.315 | 8.00 |




Tape and Reel Information – Reel Dimensions

Standard T/R size = 2500 pieces on a 7" reel.



| Feature | Measure | Symbol | Size (in) | Size (mm) |
|---------|----------------------|--------|-----------|-----------|
| Flange | Diameter | A | 6.969 | 177.0 |
| | Thickness | W2 | 0.559 | 14.2 |
| | Space Between Flange | W1 | 0.346 | 8.8 |
| Hub | Outer Diameter | N | 2.283 | 58.0 |
| | Arbor Hole Diameter | C | 0.512 | 13.0 |
| | Key Slit Width | B | 0.079 | 2.0 |
| | Key Slit Diameter | D | 0.787 | 20.0 |

Tape and Reel Information – Tape Length and Label Placement



Notes:

1. Empty part cavities at the trailing and leading ends are sealed with cover tape. See EIA 481-1-A.
2. Labels are placed on the flange opposite the sprockets in the carrier tape.

Handling Precautions

| Parameter | Rating | Standard |
|----------------------------------|----------|--------------------------|
| ESD – Human Body Model (HBM) | Class 1C | ESDA / JEDEC JS-001-2017 |
| ESD – Charged Device Model (CDM) | Class C3 | JEDEC JESD22-C101F |
| MSL – Moisture Sensitivity Level | Level 1 | IPC/JEDEC J-STD-020E |



Caution!
ESD-Sensitive Device

Solderability

Compatible with both lead-free (260°C max. reflow temperature) and tin/lead (245°C max. reflow temperature) soldering processes. Solder profiles available upon request.

Contact plating: NiPdAu (*Thickness: Ni 0.508 ~ 1.524 μ m; Pd 0.023 ~ 0.1016 μ m; Au 0.00254 ~ 0.01016 μ m*)

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2020 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.