Topological Optimization Using the SIMP Method

Mikal Nelson

University of Kansas Department of Mathematics mikal.nelson@ku.edu

M.A. Thesis Defense July 26th, 2021 Zoom





Outline

- ► Heat Equation and Finite Volume Method
- Optimization and Method of Moving Asymptotes
- ► Solid Isotropic Material with Penalization (SIMP)
- ► Algorithm Results

Heat Equation

The temperature (T) at any point in such an object is a function of both space (\mathbf{x}) and time (t) coordinates: $T(\mathbf{x}, t)$.

Physical principles demand that such a temperature function must satisfy the equation

$$\frac{\partial T}{\partial t} = \nabla \cdot \left(k(\mathbf{x}) \nabla T \right), \tag{1}$$

where ∇ is the gradient operator and the function k represents the thermal diffusivity at a point in our object.




Figure 1: Heatmap for a $0.1\text{m} \times 0.1\text{m}$ object with uniform heat generation and a heat sink at the center of its west boundary. This map was produced via the Finite Volume Method using 100×100 uniform control volumes

Finite Volume Method (FVM)

Theorem (The Divergence Theorem)

Suppose that $\mathcal V$ is a compact subset of $\mathbb R^n$ that has a piecewise smooth boundary S (i.e. $\partial \mathcal{V} = S$) with outward pointing normal

vectors. If
$${f F}$$
 is a continously differentiable vector field defined on a neighborhood of ${\cal V}$, then

vectors. If
$$\mathbf{F}$$
 is a continously differentiable vector field defined on a neighborhood of \mathcal{V} , then
$$\iiint_{\mathcal{V}} (\nabla \cdot \mathbf{F}) \, \mathrm{d}\mathcal{V} = \oiint_{\mathcal{S}} (\mathbf{F} \cdot \hat{\mathbf{n}}) \, \mathrm{d}\mathcal{S} \tag{2}$$

(2)

where \hat{n} is the outwards pointing normal vector to the boundary.

Discretization of Heat Equation

$$\int_{V_i} \frac{\partial T}{\partial t} d\mathbf{x} = \int_{V_i} \nabla \cdot (k(\mathbf{x}) \nabla T) d\mathbf{x} = \int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} ds \quad (3)$$

In a square grid there are only four neighboring cells which we can label as North, South, East, West.

For a control volume V_i we'll label the North boundary as ∂V_N , the South boundary as ∂V_S , the East boundary as ∂V_E , and the West boundary as ∂V_W .

Additionally, let Δx be the length of the North and South boundaries, and Δy the length of the East and West boundaries.

Discretization of Heat Equation

$$\int_{\mathcal{M}} \frac{\partial T}{\partial t} \, d\mathbf{x} = \int_{\mathcal{M}} \nabla \cdot \left(k(\mathbf{x}) \nabla T \right) \, d\mathbf{x} = \int_{\mathcal{M}} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} \, ds$$

$$\int_{V_i} \frac{\partial T}{\partial t} d\mathbf{x} = \int_{V_i} \nabla \cdot (k(\mathbf{x}) \nabla T) d\mathbf{x} = \int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} ds$$

 $\int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} \, ds = \int_{\partial V_N} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_N \, ds + \int_{\partial V_S} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_S \, ds + \int_{\partial V_E} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_E \, ds + \int_{\partial V_W} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_W \, ds$

$$\int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} \, ds = \int_{\partial V_N} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_N \, ds + \int_{\partial V_S} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_S \, ds
+ \int_{\partial V_E} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_E \, ds + \int_{\partial V_W} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_W \, ds$$

$$\int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} \, ds = \int_{\partial V_N} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_N \, ds + \int_{\partial V_S} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_S \, ds
+ \int_{\partial V_E} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_E \, ds + \int_{\partial V_W} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_W \, ds$$

$$\approx$$

 $k_{N} \frac{T_{N} - T_{i}}{\|\mathbf{x}_{N} - \mathbf{x}_{i}\|} \Delta y + k_{S} \frac{T_{S} - T_{i}}{\|\mathbf{x}_{S} - \mathbf{x}_{i}\|} \Delta y$ $+k_{E} \frac{T_{E} - T_{i}}{\|\mathbf{x}_{E} - \mathbf{x}_{i}\|} \Delta x + k_{W} \frac{T_{W} - T_{i}}{\|\mathbf{x}_{W} - \mathbf{x}_{i}\|} \Delta x$

$$\int_{V} \frac{\partial T}{\partial t} \, \mathrm{d}\mathbf{x} \qquad \approx \qquad$$

$$\approx$$

$$\int_{\partial V_i} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}} \, ds = \int_{\partial V_N} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_N \, ds + \int_{\partial V_S} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_S \, ds + \int_{\partial V_E} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_E \, ds + \int_{\partial V_W} k(\mathbf{x}) \nabla T \cdot \hat{\mathbf{n}}_W \, ds$$

$$\int_{V_i} \frac{\partial T}{\partial t} d\mathbf{x} \approx k_N \frac{T_N - T_i}{\|\mathbf{x}_N - \mathbf{x}_i\|} \Delta y + k_S \frac{T_S - T_i}{\|\mathbf{x}_S - \mathbf{x}_i\|} \Delta y$$

$$T_E - T_i$$

 $\implies \Delta x \Delta y \frac{\mathrm{d}T_i}{\mathrm{d}t} =$

$$\frac{T}{t} d\mathbf{x} \approx k_N \frac{T_N - T_i}{\|\mathbf{x}_N - \mathbf{x}_i\|} \Delta y + k_S \frac{T_S - T_i}{\|\mathbf{x}_S - \mathbf{x}_i\|} \Delta y + k_E \frac{T_E - T_i}{\|\mathbf{x}_E - \mathbf{x}_i\|} \Delta x + k_W \frac{T_W - T_i}{\|\mathbf{x}_W - \mathbf{x}_i\|} \Delta x$$

 $\left(k_N \frac{T_N - T_i}{\|\mathbf{x}_N - \mathbf{x}_i\|} + k_S \frac{T_S - T_i}{\|\mathbf{x}_S - \mathbf{x}_i\|}\right) \Delta y + \left(k_E \frac{T_E - T_i}{\|\mathbf{x}_E - \mathbf{x}_i\|} + k_W \frac{T_W - T_i}{\|\mathbf{x}_W - \mathbf{x}_i\|}\right) \Delta x$

Bibliography



Stephen P. Boyd and Lieven Vandenberghe.

Convex Optimization.

Cambridge Univ. Pr., 2004.



Martin J. Gander and Felix Kwok.

Numerical Analysis of Partial Differential Equations Using Maple and MATLAB. Society for Industrial and Applied Mathematics, Aug 2018.



Gilles Marck, Maroun Nemer, Jean-Luc Harion, Serge Russeil, and Daniel Bougeard.

Topology optimization using the SIMP method for multiobjective conductive problems.

Numerical Heat Transfer, Part B: Fundamentals, 61(6):439-470, jun 2012.



Krister Svanberg.

The method of moving asymptotes—a new method for structural optimization.

International Journal for Numerical Methods in Engineering, 24(2):359-373, feb 1987.



H. K. Versteeg.

An Introduction to Computational Fluid Dynamics: The Finite Volume Method. Pearson Education Ltd, Harlow, England New York, 2007.