```
noname  …/C Programming/Lab 1  main  v15.2.0  11:46
❯ gcc 1.1-lab.c -o build/1.1-lab && build/1.1-lab
Enter two numbers: 10 5
Addition: 15.00
Subtraction: 5.00
Multiplication: 50.00
Division: 2.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:47
❯ gcc 1.2-lab.c -o build/1.2-lab && build/1.2-lab
Enter side length: 5
Surface area of cube: 150.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:49
❯ gcc 1.3-lab.c -o build/1.3-lab && build/1.3-lab
Enter radius: 6
Area: 113.10
Circumference: 37.70

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:51
❯ gcc 1.4-lab.c -o build/1.4-lab && build/1.4-lab
Enter length and breadth: 10 5
Area: 50.00
Perimeter: 30.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:54
❯ gcc 1.5-lab.c -o build/1.5-lab && build/1.5-lab
Enter two integers: 10 3
Quotient: 3
Remainder: 1

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:56
❯ gcc 1.6-lab.c -o build/1.6-lab && build/1.6-lab
Enter seconds: 5000
1 hours, 23 minutes, 20 seconds

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  11:58
❯ gcc 1.7-lab.c -o build/1.7-lab && build/1.7-lab
Enter number of days: 460
1 years, 3 months, 10 days

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:00
❯ gcc 1.8-lab.c -o build/1.8-lab && build/1.8-lab
Enter length in mm: 1500
km: 0.001500
m: 1.500
cm: 150.0
mm: 1500

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:00
❯ gcc 1.9-lab.c -o build/1.9-lab && build/1.9-lab
Enter a three-digit number: 123
Reversed number: 321

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:02
❯ gcc 1.10-lab.c -o build/1.10-lab && build/1.10-lab
Enter marks for 5 subjects: 75 75 60 50 50
Aggregate: 310
Percentage: 62.00%

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:04
❯ gcc 1.11-lab.c -o build/1.11-lab && build/1.11-lab
Enter temperature in Celsius: 100
Temperature in Fahrenheit: 212.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:10
❯ gcc 1.12-lab.c -lm -o build/1.12-lab && build/1.12-lab
Enter coefficients a, b, c: 1 6 8
Root 1: -2.00
Root 2: -4.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:16
❯ gcc 1.13-lab.c -lm -o build/1.13-lab && build/1.13-lab
Enter three sides of triangle: 9 9 12
Area: 40.25

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:20
❯ gcc 1.14-lab.c -o build/1.14-lab && build/1.14-lab
Enter two numbers: 5 10
After interchanging: 10 5

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:22
❯ gcc 1.15-lab.c -o build/1.15-lab && build/1.15-lab
Enter a five-digit number: 12345
Sum of digits: 15

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:22
❯ gcc 1.16-lab.c -o build/1.16-lab && build/1.16-lab
Enter two numbers: 20 10
Result: 30

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:28
❯ gcc 1.17-lab.c -o build/1.17-lab && build/1.17-lab
Enter a decimal number: 45.6
Octal: 55
Hexadecimal: 2d

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:29
❯ gcc 1.18-lab.c -o build/1.18-lab && build/1.18-lab
Enter radius of sphere: 5
Volume of sphere: 523.60

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 1  main  v15.2.0  12:33
❯ gcc 1.19-lab.c -o build/1.19-lab && build/1.19-lab
Enter a number: 12
Remainder after dividing by 5: 2

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:35
❯ gcc 2.1-lab.c -o build/2.1-lab && build/2.1-lab
Enter number of terms: 10
Fibonacci series: 0 1 1 2 3 5 8 13 21 34

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:36
❯ gcc 2.2-lab.c -o build/2.2-lab && build/2.2-lab
Armstrong numbers between 1 and 500:
1 153 370 371 407

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:38
❯ gcc 2.3-lab.c -o build/2.3-lab && build/2.3-lab
Numbers from 1 to 10: 1 2 3 4 5 6 7 8 9 10

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:41
❯ gcc 2.4-lab.c -o build/2.4-lab && build/2.4-lab
Numbers from 9 to 0: 9 8 7 6 5 4 3 2 1 0

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:41
❯ gcc 2.5-lab.c -o build/2.5-lab && build/2.5-lab
Numbers from 10 to 1: 10 9 8 7 6 5 4 3 2 1
Sum: 55

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main  v15.2.0  12:44
❯ gcc 2.6-lab.c -o build/2.6-lab && build/2.6-lab
Enter a number: 5
Factorial of 5: 120

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main !?  v15.2.0  13:49
❯ gcc 2.7-lab.c -o build/2.7-lab && build/2.7-lab
Enter a number: 10
Do you want to enter another number? (y/n): y
Enter a number: 2
Do you want to enter another number? (y/n): y
Enter a number: 0
Do you want to enter another number? (y/n): y
Enter a number: 0
Do you want to enter another number? (y/n): y
Enter a number: -1
Do you want to enter another number? (y/n): n
Positive: 2
Negative: 1
Zeros: 2

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main !?  v15.2.0  13:52
❯ gcc 2.8-lab.c -o build/2.8-lab && build/2.8-lab
Pattern:
*****
****
***
**
*

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?↑  v15.2.0  13:53
❯ gcc 2.9-lab.c -o build/2.9-lab && build/2.9-lab
Multiplication table (1-10):
1       2       3       4       5       6       7       8       9       10
2       4       6       8       10      12      14      16      18      20
3       6       9       12      15      18      21      24      27      30
4       8       12      16      20      24      28      32      36      40
5       10      15      20      25      30      35      40      45      50
6       12      18      24      30      36      42      48      54      60
7       14      21      28      35      42      49      56      63      70
8       16      24      32      40      48      56      64      72      80
9       18      27      36      45      54      63      72      81      90
10      20      30      40      50      60      70      80      90      100

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?↑  v15.2.0  13:54
❯ gcc 2.10-lab.c -o build/2.10-lab && build/2.10-lab
Enter a number: 10
Cube: 1000

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?↑  v15.2.0  13:55
❯ gcc 2.10-lab.c -o build/2.10-lab && build/2.10-lab
Enter a number: 9
Square: 81

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?↑  v15.2.0  13:57
❯ gcc 2.11-lab.c -lm -o build/2.11-lab && build/2.11-lab
Enter base and power: 10 2
10 raised to power 2: 100

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?↑  v15.2.0  13:58
❯ gcc 2.12-lab.c -lm -o build/2.12-lab && build/2.12-lab
Enter a number: 1234
Product of digits: 24

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 2  main ?⇡  v15.2.0  13:59
❯ gcc 2.13-lab.c -o build/2.13-lab && build/2.13-lab
Enter a number: 1234
Sum of digits: 10

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:09
❯ gcc 3.1-lab.c -o build/3.1-lab && build/3.1-lab
Enter 10 numbers: 1 1 5 4 3 6 2 1 3 3
Sum: 29, Product: 6480, Average: 2.90, Max: 6

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:10
❯ gcc 3.2-lab.c -o build/3.2-lab && build/3.2-lab
Enter 10 numbers: 6 2 6 4 5 8 9 6 4 8

Array variables and their addresses:
arr[0] = 6, Address = 0x7ffcb92a1970
arr[1] = 2, Address = 0x7ffcb92a1974
arr[2] = 6, Address = 0x7ffcb92a1978
arr[3] = 4, Address = 0x7ffcb92a197c
arr[4] = 5, Address = 0x7ffcb92a1980
arr[5] = 8, Address = 0x7ffcb92a1984
arr[6] = 9, Address = 0x7ffcb92a1988
arr[7] = 6, Address = 0x7ffcb92a198c
arr[8] = 4, Address = 0x7ffcb92a1990
arr[9] = 8, Address = 0x7ffcb92a1994

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:12
❯ gcc 3.3-lab.c -o build/3.3-lab && build/3.3-lab
Enter 10 numbers: 2 5 6 4 8 6 3 1 7 9
Largest: 9, Smallest: 1

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:13
❯ gcc 3.4-lab.c -o build/3.4-lab && build/3.4-lab
Enter 10 numbers: 6 4 5 2 3 1 7 8 9 10
Sorted array: 1 2 3 4 5 6 7 8 9 10

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:15
❯ gcc 3.5-lab.c -o build/3.5-lab && build/3.5-lab
Enter 10 numbers: 6 5 4 3 2 1 9 8 7 0
Sorted array: 0 1 2 3 4 5 6 7 8 9

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:15
❯ gcc 3.6-lab.c -o build/3.6-lab && build/3.6-lab
Enter marks of BscCSIT-1 semester students: 60 45 50 30 20
Descending order: 60 50 45 30 20
Maximum: 60, Minimum: 20

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:17
❯ gcc 3.7-lab.c -o build/3.7-lab && build/3.7-lab
Enter 25 numbers: 0 1 2 3 4 0 -1 -2 -3 -4 0 1 2 3 4 0 -1 -2 -3 -4 0 1 2 3 4 5
Positive: 12, Negative: 8, Even: 15, Odd: 10

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main ⇡  v15.2.0  14:21
❯ gcc 3.8-lab.c -o build/3.8-lab && build/3.8-lab
Enter 10 numbers: 4 5 6 7 8 9 1 2 3 0
Sorted array: 0 1 2 3 4 5 6 7 8 9

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !⇡  v15.2.0  14:25
❯ gcc 3.9-lab.c -o build/3.9-lab && build/3.9-lab

Matrix:
1 2 3
4 5 6

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  14:31
❯ gcc 3.10-lab.c -o build/3.10-lab && build/3.10-lab
Enter matrix dimensions: 2 2
Enter matrix A:
1 2
3 4
Enter matrix B:
3 4
1 2

Sum:
4 6
4 6

Difference:
-2 -2
2 2

Product:
5 8
13 20

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  14:32
❯ gcc 3.11-lab.c -o build/3.11-lab && build/3.11-lab
Prime numbers between 1 to 100:
2 3 5 7 11 13 17 19 23 29 31 37 41 43 47 53 59 61 67 71 73 79 83 89 97

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  14:33
❯ gcc 3.12-lab.c -o build/3.12-lab && build/3.12-lab
Enter marks of 10 students: 20 30 40 25 60 45 10 80 60 5
Top 5 marks: 80 60 60 45 40

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  14:35
❯ gcc 3.13-lab.c -o build/3.13-lab && build/3.13-lab
Enter 10 numbers: 0 1 2 3 4 5 6 7 8 9
Reversed array: 9 8 7 6 5 4 3 2 1 0

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  14:39
❯ gcc 3.15-lab.c -o build/3.15-lab && build/3.15-lab
Enter a string: kshitij
Upper case: KSHITIJ

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  14:46
❯ gcc 3.16-lab.c -o build/3.16-lab && build/3.16-lab
Enter a string: XITTIZ
Lower case: xittiz

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  14:43
❯ gcc 3.17-lab.c -o build/3.17-lab && build/3.17-lab
Enter a string: XiTtIz
Toggled case: xItTiZ

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  14:46
❯ gcc 3.18-lab.c -o build/3.18-lab && build/3.18-lab
Enter a string: level
Palindrome

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !↑  v15.2.0  15:03
❯ gcc 3.19-lab.c -o build/3.19-lab && build/3.19-lab
Enter a string: HelloWorld
Reversed without strrev: dlroWolleH
Reversed using strrev: dlroWolleH

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  15:07
❯ gcc 3.20-lab.c -o build/3.20-lab && build/3.20-lab
Enter a string: abcde
ASCII values: a=97 b=98 c=99 d=100 e=101

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  15:11
❯ gcc 3.21-lab.c -o build/3.21-lab && build/3.21-lab
Enter a string: I am IronMan
Lower case: 7, Upper case: 3, Spaces: 2

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  15:11
❯ gcc 3.22-lab.c -o build/3.22-lab && build/3.22-lab
Enter a string: CProgramming
Number of vowels: 3

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  15:13
❯ gcc 3.23-lab.c -o build/3.23-lab && build/3.23-lab
Enter first string: IronMan
Enter second string: SuperMan
Larger string: SuperMan

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main !  v15.2.0  15:22
❯ gcc 3.24-lab.c -o build/3.24-lab && build/3.24-lab
Enter first string: Bag
Enter second string: Pack
Concatenated: BagPack

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 3  main  v15.2.0  15:27
❯ gcc 3.25-lab.c -o build/3.25-lab && build/3.25-lab
Enter 10 student names:
IronMan CaptainAmerica Thor Hulk BlackWidow Hawkeye BlackPanther CaptainMarvel Vision ScarletWitch
Sorted names:
BlackPanther
BlackWidow
CaptainAmerica
CaptainMarvel
Hawkeye
Hulk
IronMan
ScarletWitch
Thor
Vision

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:37
❯ gcc 4.1-lab.c -o build/4.1-lab && build/4.1-lab
Enter two numbers: 10 2
Addition: 12
Subtraction: 8
Multiplication: 20
Division: 5.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:37
❯ gcc 4.2-lab.c -o build/4.2-lab && build/4.2-lab
Enter three numbers: 10 5 20
Largest: 20

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:41
❯ gcc 4.3-lab.c -o build/4.3-lab && build/4.3-lab
Enter a float and an int: 10.2 5
Product: 51.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:42
❯ gcc 4.4-lab.c -o build/4.4-lab && build/4.4-lab
Enter a number: 11
11 is Prime

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:43
❯ gcc 4.5-lab.c -o build/4.5-lab && build/4.5-lab
Enter a number: 10
Factorial: 3628800

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:44
❯ gcc 4.6-lab.c -o build/4.6-lab && build/4.6-lab
Enter base and power: 10 3
10 raised to 3: 1000

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:45
❯ gcc 4.7-lab.c -o build/4.7-lab && build/4.7-lab
Enter a number: 5
Factorial using recursion: 120

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:46
❯ gcc 4.8-lab.c -o build/4.8-lab && build/4.8-lab
Enter n: 5
Sum of 1+2+3+...+5: 15

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:48
❯ gcc 4.9-lab.c -o build/4.9-lab && build/4.9-lab
Enter number of terms: 10
Fibonacci series: 0 1 1 2 3 5 8 13 21 34

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:49
❯ gcc 4.10-lab.c -o build/4.10-lab && build/4.10-lab
Enter base and power: 10 3
10 raised to 3: 1000

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:50
❯ gcc 4.11-lab.c -o build/4.11-lab && build/4.11-lab
Sum of first 20 natural numbers: 210

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 4  main  v15.2.0  15:51
❯ gcc 4.12-lab.c -o build/4.12-lab && build/4.12-lab
Enter number of terms: 10
Fibonacci series: 0 1 1 2 3 5 8 13 21 34

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main  v15.2.0  15:54
❯ gcc 5.1-lab.c -o build/5.1-lab && build/5.1-lab
Name            Total Marks     Grade
====            ===========     =====
Ram             100             C
Sita            120             B
Gita            130             B
Gopal           150             A

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main  v15.2.0  15:55
❯ gcc 5.2-lab.c -o build/5.2-lab && build/5.2-lab
Enter student name: Xittiz
Enter roll number: 20
Enter marks: 90
Enter remarks: Good

Student Data:
Name: Xittiz
Roll: 20
Marks: 90
Remarks: Good

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:03
❯ gcc 5.3-lab.c -o build/5.3-lab && build/5.3-lab
Enter data for 5 students:
Student 1:
Enter Name Roll No. Marks: Tony 1 100
Student 2:
Enter Name Roll No. Marks: Peter 2 80
Student 3:
Enter Name Roll No. Marks: Bruce 3 70
Student 4:
Enter Name Roll No. Marks: Natasha 4 40
Student 5:
Enter Name Roll No. Marks: Steven 5 45

Students with marks > 50:
Name: Tony, Roll: 1
Name: Peter, Roll: 2
Name: Bruce, Roll: 3

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:05
❯ gcc 5.4-lab.c -o build/5.4-lab && build/5.4-lab
Enter data for 5 employees:
Employee 1:
Enter Name Address Salary: Man Kathmandu 15000
Employee 2:
Enter Name Address Salary: San Bhaktapur 20000
Employee 3:
Enter Name Address Salary: Pan Lalitpur 25000
Employee 4:
Enter Name Address Salary: Lan Biratnagar 30000
Employee 5:
Enter Name Address Salary: Gan Jhapa 35000

Employees in ascending order of name:
Name: Gan, Address: Jhapa, Salary: 35000.00
Name: Lan, Address: Biratnagar, Salary: 30000.00
Name: Man, Address: Kathmandu, Salary: 15000.00
Name: Pan, Address: Lalitpur, Salary: 25000.00
Name: San, Address: Bhaktapur, Salary: 20000.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:16
❯ gcc 5.5-lab.c -o build/5.5-lab && build/5.5-lab
Enter data for 3 people:
Person 1:
Enter Name Address: Man Kathmandu
Person 2:
Enter Name Address: San Bhaktapur
Person 3:
Enter Name Address: Pan Lalitpur

People in alphabetical order:
Name: Man, Address: Kathmandu
Name: Pan, Address: Lalitpur
Name: San, Address: Bhaktapur

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:39
❯ gcc 5.6-lab.c -o build/5.6-lab && build/5.6-lab
Enter book name: HarryPotter
Enter number of pages: 450
Enter price: 1500

Book Information:
Name: HarryPotter
Pages: 450
Price: 1500.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:44
❯ gcc 5.7-lab.c -o build/5.7-lab && build/5.7-lab
Enter data for 5 books:
Book 1:
Enter Name Pages Price: HarryPotter 450 1500
Book 2:
Enter Name Pages Price: SetoDharti 380 650
Book 3:
Enter Name Pages Price: MunaMadan 40 150
Book 4:
Enter Name Pages Price: AtomicHabits 320 1200
Book 5:
Enter Name Pages Price: ItStartsWithUs 336 800

Most expensive book:
Name: HarryPotter, Pages: 450, Price: 1500.00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:49
❯ gcc 5.8-lab.c -o build/5.8-lab && build/5.8-lab
Setting roll number to 101:
Roll: 101

Setting marks to 95:
Marks: 95
Roll: 95

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:53
❯ gcc 5.9-lab.c -o build/5.9-lab && build/5.9-lab
Date: 25/2/1957

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:56
❯ gcc 5.10-lab.c -o build/5.10-lab && build/5.10-lab
Enter date (day month year): 28 4 2026
Date: 28/4/2026

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  16:57
❯ gcc 5.11-lab.c -o build/5.11-lab && build/5.11-lab
Enter student username (8 chars): xittiz07
Enter student ID (9 chars): 101010101
Enter student PIN (5 digits): 12345

Student Information:
Username: xittiz07
ID: 101010101
PIN: 12345

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  17:01
❯ gcc 5.12-lab.c -o build/5.12-lab && build/5.12-lab
Enter first date (day month year): 28 4 2026
Enter second date (day month year): 24 3 2005
Difference in days: 7699

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main !  v15.2.0  17:08
❯ gcc 5.13-lab.c -o build/5.13-lab && build/5.13-lab
Flight:
Flight Number: 101
Origin: NYC
Destination: LAX
Start Time: 08:00
Arrive Time: 11:00

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main ⇡  v15.2.0  17:12
❯ gcc 5.14-lab.c -o build/5.14-lab && build/5.14-lab
Enter airport code: DEL

Flights for airport DEL:
Flight: 101, Origin: KTM, Destination: DEL, Start: 08:00, Arrive: 10:30
Flight: 102, Origin: DEL, Destination: KTM, Start: 11:00, Arrive: 13:30

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 5  main ↑  v15.2.0  17:13
❯ gcc 5.15-lab.c -o build/5.15-lab && build/5.15-lab
Employee Information:
Name: Hari
Salary: 50000.00
Hire Date: 10/3/2001

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:17
❯ gcc 6.1-lab.c -o build/6.1-lab && build/6.1-lab
Memory addresses:
char variable: 0x7ffcbc17cddf
float variable: 0x7ffcbc17cde0
int variable: 0x7ffcbc17cde4

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:18
❯ gcc 6.2-lab.c -o build/6.2-lab && build/6.2-lab
Enter array size: 5
Enter 5 elements: 1 2 3 4 5
Sum of array elements: 15

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:18
❯ gcc 6.3-lab.c -o build/6.3-lab && build/6.3-lab
Enter number of students: 10
Enter marks: 20 40 59 30 45 53 47 90 45 60
Top 5 marks: 90 60 59 53 47

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:20
❯ gcc 6.4-lab.c -o build/6.4-lab && build/6.4-lab
Size of pointer to int: 8 bytes
Size of pointer to float: 8 bytes
Size of pointer to char: 8 bytes

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:23
❯ gcc 6.5-lab.c -o build/6.5-lab && build/6.5-lab
Enter two numbers: 10 5
Before exchange: x=10, y=5
After exchange: x=5, y=10

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:25
❯ gcc 6.6-lab.c -o build/6.6-lab && build/6.6-lab
Enter matrix dimensions (m x n): 2 2
Enter matrix A:
1 2
3 4
Enter matrix B:
5 6
7 8
Sum of matrices:
6 8
10 12

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:26
❯ gcc 6.7-lab.c -o build/6.7-lab && build/6.7-lab
Enter number of elements: 5
Enter 5 elements: 4 3 6 2 7
Sorted array: 2 3 4 6 7

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ↑  v15.2.0  17:45
❯ gcc 6.8-lab.c -o build/6.8-lab && build/6.8-lab
Enter number of employees: 5
Enter age of 5 employees: 25 30 55 85 90
Employees with age > 80: 2

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 6  main ⇡  v15.2.0  17:47
❯ gcc 6.9-lab.c -o build/6.9-lab && build/6.9-lab
Enter matrix dimensions (m x n): 2 2
Enter elements of 2x2 matrix:
1 2
3 4

Transpose matrix:
1 3
2 4

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  17:50
❯ gcc 7.1-lab.c -o build/7.1-lab && build/7.1-lab
File test.txt created and text written.

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  17:53
❯ gcc 7.2-lab.c -o build/7.2-lab && build/7.2-lab
Content of test.txt:
Welcome to my college

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  17:53
❯ gcc 7.3-lab.c -o build/7.3-lab && build/7.3-lab
Enter a string: Hello, World!
String read from file: Hello, World!

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  17:54
❯ gcc 7.4-lab.c -o build/7.4-lab && build/7.4-lab
Enter filename to append to: test.txt
Enter text to append: testtext
Text appended successfully!

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  17:57
❯ gcc 7.5-lab.c -o build/7.5-lab && build/7.5-lab
Enter student name: Xittiz
Enter roll number: 20
Enter address: Bhaktapur
Enter marks: 75
Student data saved to student.txt

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  18:06
❯ gcc 7.6-lab.c -o build/7.6-lab && build/7.6-lab
Enter name: Xittiz
Enter address: Bhaktapur
Enter telephone: 01321422

Data from file:
Name: Xittiz
Address: Bhaktapur
Telephone: 01321422

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  18:09
❯ gcc 7.7-lab.c -o build/7.7-lab && build/7.7-lab
Enter a string: HelloWorld
String from new1.dat: HelloWorld

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  18:10
❯ gcc 7.8-lab.c -o build/7.8-lab && build/7.8-lab
Writing even numbers 10-50 to evennumbers.txt:
10 12 14 16 18 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50

Reading from evennumbers.txt:
10 12 14 16 18 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  18:17
❯ gcc 7.9-lab.c -o build/7.9-lab && build/7.9-lab
Writing numbers 1-20 to file:
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
Twice of stored numbers:
2 4 6 8 10 12 14 16 18 20 22 24 26 28 30 32 34 36 38 40

Programmed by Kshitij Nepali
```

```
noname  …/C Programming/Lab 7  main ?⇡  v15.2.0  18:18
❯ gcc 7.10-lab.c -o build/7.10-lab && build/7.10-lab
Enter 10 numbers: 10 11 12 13 14 15 16 17 18 19
Array from file:
10 11 12 13 14 15 16 17 18 19

Programmed by Kshitij Nepali
```