

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet1 (main)
$ g++ 1.cpp -o main && ./main
Employee Type
1. Permanent
2. Contract
Enter your choice: 1
Enter Basic Salary: 30000
```

```
=====
Salary Slip
=====
Employee Type      : Permanent
Basic Salary       : 30000.00
Net Salary         : 33000.00
=====
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet1 (main)
$ g++ 3.cpp -o main && ./main
Enter side of square: 2
Area of Square = 4
```

```
Enter length and width of rectangle: 2 4
Area of Rectangle = 8
```

```
Enter base and height of triangle: 2 6
Area of Triangle = 6
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet1 (main)
$ g++ 5.cpp -o main && ./main
Enter the number of elements: 5
Enter the array elements:
10
20
30
40
50

Sum = 150
Maximum = 50
Minimum = 10
The array is sorted.
```

```
First Complex Number: 2 + 4i
Second Complex Number: 3 - 2i
Sum: 5 + 2i
Difference: -1 + 6i
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet2 (main)
$ g++ 4.cpp -o main && ./main
Enter first complex number (real imag): 2 4
Enter second complex number (real imag): 3 -2
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet1 (main)
$ g++ 2.cpp -o main && ./main
Enter the number of students: 2
Enter marks of 2 students:
Student 1: 35
Student 2: 50
```

```
----- Result -----
Highest Marks : 50
Lowest Marks  : 35
Average Marks : 42.5
Passed Students : 1
```

```
Do you want to add more students? (y/n): Y
How many more students? 1
Enter marks of new students:
Student 3: 60
```

```
----- Result -----
Highest Marks : 60
Lowest Marks  : 35
Average Marks : 48.3333
Passed Students : 2
```

```
Do you want to add more students? (y/n): N
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet1 (main)
$ g++ 4.cpp -o main && ./main
Original values: x = 10, y = 20
```

```
Inside swapByValue: a = 20, b = 10
After swapByValue: x = 10, y = 20
```

```
Inside swapByPointer: a = 20, b = 10
After swapByPointer: x = 20, y = 10
```

```
Inside swapByReference: a = 10, b = 20
After swapByReference: x = 10, y = 20
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet2 (main)
$ g++ 2.cpp -o main && ./main
Enter Employee ID: 101
Enter Employee Name: Milan Bhandari
Enter Basic Salary: 67000

===== Salary Slip =====
Employee ID   : 101
Name          : Milan Bhandari
Basic Salary  : 67000
HRA (20%)     : 13400
DA (10%)      : 6700
Gross Salary  : 87100
Tax           : 8710
Net Salary    : 78390
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet2 (main)
$ g++ 3.cpp -o main && ./main
Enter Length, Breadth and Height: 20 15 10

Default Constructor Object
Length : 10 ft
Breadth : 10 ft
Height : 10 ft
Floor Area : 100 sq.ft
Volume : 1000 cu.ft

Parameterized Constructor Object
Length : 20 ft
Breadth : 15 ft
Height : 10 ft
Floor Area : 300 sq.ft
Volume : 3000 cu.ft

Copy Constructor Object
Length : 20 ft
Breadth : 15 ft
Height : 10 ft
Floor Area : 300 sq.ft
Volume : 3000 cu.ft
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet2 (main)
$ g++ 1.cpp -o main && ./main
Enter Roll Number: 17
Enter Name: Milan Bhandari
Enter marks of 5 subjects:
Subject 1: 80
Subject 2: 90
Subject 3: 95
Subject 4: 98
Subject 5: 99

----- Student Result -----
Roll Number : 17
Name        : Milan Bhandari
Marks: 80 90 95 98 99
Total       : 462
Percentage  : 92.4%
Grade       : A
```

```
Acer@LAPTOP-FBKS1F6L MINGW64 ~/MilanCodess/2nd-sem-oop/LabSheet2 (main)
$ g++ 5.cpp -o main && ./main
Initial Count = 0
Object Created.
Count = 1
Object Created.
Count = 2
Object Created.
Count inside block = 3
Object Created.
Count inside block = 4
Object Destroyed.
Object Destroyed.
Count after block = 2
Object Destroyed.
Object Destroyed.
```