
Cobalt

WHITE PAPER

Pentester Guide to the OWASP Top 10 for LLM Apps



Contents

Introduction 3

Overview of the OWASP Top 10 5


Why Pentesting Is Essential for Securing LLM Apps 15

How Cobalt Can Help 16

Introduction

As AI and LLMs have rapidly transitioned from research concepts to integral components across diverse applications and industries, the spectrum of associated security risks has broadened. From enhancing customer interactions, to streamlining internal operations, the deepening integration of LLMs necessitates a proactive and informed approach to application security.

However, the pace of innovation and adoption of AI risks leaving security behind. Despite widespread adoption, 36% of security leaders and practitioners surveyed admit that the demand for genAI has outpaced their security team's ability to manage its security implications.[1]



Security professionals who believe AI risks are outpacing security

The OWASP Top 10 for Large Language Model (LLM) Applications emerged in 2023 as a crucial, community-led initiative dedicated to identifying and mitigating security vulnerabilities in AI-powered applications. Originating from a growing recognition of the unique risks associated with LLM technologies, the OWASP project sought to provide developers and security professionals with a focused framework for addressing these emerging threats. In 2025, amid a dramatic evolution in AI's development and adoption, OWASP updated the top 10 list. The 2025 OWASP Top 10 list for LLM Applications reflects a deeper understanding of existing security risks and incorporates critical updates based on the practical application of LLMs in real-world environments. The 2025 version builds upon the foundational work of previous versions, incorporating lessons learned and emerging threat patterns.

This white paper provides Cobalt pentesters' expert perspectives on these changes, with examples from real penetration tests for each of the top 10 LLM vulnerability categories, and mitigation strategies.

[1]Survey of 450 security leaders and practitioners, conducted in early 2025 by Emerald Research Group, on behalf of Cobalt.

Growing LLM Security Risks

- **Unbounded consumption:** Expanding beyond the traditional denial of service vulnerability, this category now encompasses broader resource management concerns and the potential for unexpected operational costs. This is particularly relevant in large-scale LLM deployments where inefficient resource utilization can lead to significant financial impacts.
- **Vector and embeddings:** Responding directly to community feedback, the 2025 list includes guidance on securing retrieval-augmented generation (RAG) systems and other embedding-based methodologies.
- **System prompt leakage:** This new category addresses a critical area of vulnerability highlighted by recent real-world exploits. While many applications previously assumed system prompts were inherently secure, incidents have demonstrated that sensitive information contained within these prompts can be exposed. Developers can no longer assume the confidentiality of these instructions.
- **Excessive agency:** Reflecting the growing use of agentic LLM architectures, this category has been expanded to address the risks associated with granting LLMs greater autonomy. As LLMs operate more frequently as agents or within plugin ecosystems, unchecked permissions can result in unintended or potentially risky actions, elevating the importance of robust agency controls.

Overview of the OWASP Top 10

1. Prompt Injection


A prompt injection vulnerability occurs when user-supplied prompts unintentionally or maliciously alter the model's intended behavior. These injected prompts can be subtle and not necessarily visible to human readers, as long as the LLM can parse and interpret them. Malicious input can trick the model into misinterpreting prompt data, leading it to bypass guidelines, generate harmful or inappropriate content, grant unauthorized access to functionalities, or modify critical decision-making processes.

Prompt injection vulnerabilities can be broadly categorized into two main types:


1. **Direct:** This occurs when a user directly inputs a prompt that causes the LLM to behave unexpectedly. This can be intentional, where an attacker crafts a malicious prompt, or unintentional, where a user inadvertently provides input that triggers unintended behavior.
2. **Indirect:** This type arises when an LLM processes external data sources like websites or files. If these external sources contain malicious content, the LLM, upon interpreting this data, can be manipulated into unintended or harmful actions. Similar to direct injection, this can be due to intentional malicious content or unintentional data that happens to trigger the vulnerability.

Examples from Pentests

Prompt 1



Prompt 2



Prevention and Mitigation Strategies


- ☑ **Constrain model behavior:** Refine system prompts and interaction flows to better resist manipulative inputs and ensure the model operates within strict, predefined functional boundaries.
- ☑ **Implement input and output filtering:** Deploy robust input validation and sanitization to neutralize injection attempts, paired with output filtering mechanisms that prevent data leakage or the generation of harmful content.
- ☑ **Require human approval for high-risk actions:** Incorporate a verification step for sensitive operations to prevent excessive agency, where the model is manipulated into performing unauthorized functions or executing commands beyond its intended scope.
- ☑ **Enforce privilege control and least privilege access:** Apply strict access controls and granular permissioning to ensure the LLM maintains only the least-privilege access necessary for specific data fields and tools.

2. Sensitive Information Disclosure

LLMs handle a wide range of sensitive information, impacting both the model itself and the applications they power. This includes personally identifiable information (PII), financial records, healthcare data, confidential business intelligence, security credentials, and legal documents. Even the proprietary aspects of the LLM itself, such as unique training methodologies and source code, can be considered sensitive, especially in closed or foundation models.

A significant risk arises when LLMs, particularly those integrated into applications, inadvertently expose this sensitive data through their generated outputs. This can lead to unauthorized data access, serious privacy violations, and breaches of intellectual property.

Examples from Pentests



Prevention and Mitigation Strategies

- ☑ **Integrate data sanitization techniques:** Deploy robust output filtering mechanisms to sanitize responses, ensuring that any inadvertent leakage of PII or database schemas is caught and neutralized before reaching the user.
- ☑ **Enforce strict access controls:** Apply the principle of least privilege by restricting the LLM’s access to only the specific data fields and tools necessary for its function, thereby limiting the scope of data available for potential exfiltration.
- ☑ **Implement tokenization to preprocess and sanitize sensitive information:** Enhance data privacy by detecting and masking sensitive identifiers within inputs before they enter the model context, ensuring the LLM processes only sanitized data to prevent downstream leakage.

3. Supply Chain

The supply chain for LLMs presents a significant and evolving attack surface. Unlike traditional software vulnerabilities focused on code flaws and dependencies, LLM risks extend to the integrity of training data, pre-trained models, and deployment platforms, often involving third-party components. These elements are susceptible to manipulation through techniques like data tampering or model poisoning, potentially leading to biased outputs, security breaches, or system failures.

Prevention and Mitigation Strategies

- ☑ **Maintain an up-to-date inventory of components using a software bill of materials (SBOM):** Actively manage third-party and fourth-party risks by maintaining a comprehensive inventory of all AI components and enforcing a rigorous patching policy to address vulnerabilities in outdated software or dependencies.
- ☑ **Only use models from verifiable sources:** Mitigate the risks of tampering or model theft by strictly limiting deployments to models obtained from authenticated providers who can demonstrate transparency regarding their security testing and vulnerability management practices.
- ☑ **Carefully vet data sources and suppliers:** Conduct rigorous security reviews on all vendors to ensure they adhere to defined security responsibilities and incident response protocols outlined in contractual agreements.

4. Data and Model Poisoning

Data poisoning attacks target the very foundation of Large Language Models: their training data. By manipulating the datasets used during pre-training, fine-tuning, or even the creation of embedding vectors, attackers can inject vulnerabilities, backdoors, or harmful biases directly into the model. This manipulation can severely compromise an LLM's security, degrade its performance, and undermine its ethical behavior, ultimately leading to unreliable outputs and potentially harmful downstream consequences.

Examples from Pentests




Prevention and Mitigation Strategies


- ☑ **Vet data vendors rigorously, and validate model outputs against trusted sources to detect signs of poisoning:** Actively manage supply chain risk by conducting rigorous security reviews of third-party data providers and continuously monitoring model outputs against established baselines to identify anomalies that suggest training data manipulation.
- ☑ **Implement strict sandboxing to limit model exposure to unverified data sources:** Apply robust functional sandboxing and network isolation to ensure the model interacts only with authenticated, necessary data pipelines rather than broad, unverified external inputs that could introduce malicious patterns.
- ☑ **Verify data legitimacy during all model development stages:** Integrate security assessments directly into the data pipeline to continuously test the integrity and authenticity of training data.

5. Improper Output Handling

Improper output handling occurs when applications fail to adequately validate, sanitize, and manage the content generated by LLMs before using it in subsequent processes or systems. Exploiting this flaw can lead to serious consequences, including cross-site scripting (XSS) and cross-site request forgery (CSRF) in browsers, as well as server-side request forgery (SSRF), privilege escalation, and even remote code execution on backend systems.

Examples from Pentests






Prevention and Mitigation Strategies

- ☑ **Implement context-aware output encoding:** This is based on where the LLM output will be used (e.g., HTML encoding for web content, SQL escaping for database queries).
- ☑ **Encode model output back to users:** Implement effective input validation and sanitization in order to mitigate undesired code execution by JavaScript or Markdown.

6. Excessive Agency

The vulnerability of excessive agency arises when unexpected or manipulated LLM outputs trigger harmful actions, regardless of the cause of the malfunction. Triggers can include LLM hallucinations, prompt injection attacks, or compromised extensions. Root causes often stem from over-provisioning functionality, permissions, or autonomy to the LLM. Ultimately, Excessive Agency can lead to significant security breaches impacting data confidentiality, system integrity, and overall availability, depending on the connected systems.

Examples from Pentests






Prevention and Mitigation Strategies

- ☑ **Require user approval:** Utilize human-in-the-loop control to require a human to approve high-impact actions before they are taken.
- ☑ **Minimize extension permissions:** Limit the permissions that LLM extensions are granted to other systems to the minimum necessary in order to limit the scope of undesirable actions.

7. System Prompt Leakage

System prompt leakage highlights the vulnerability where the underlying instructions guiding an LLM's behavior are unintentionally revealed. These system prompts, designed to shape the model's responses, can inadvertently contain sensitive information. It's crucial to recognize that system prompts should never be considered a secure method for storing secrets or implementing security controls.

Examples from Pentests




Prevention and Mitigation Strategies

- ☑ **Separate sensitive data from system prompts:** Do not embed hard-coded secrets, proprietary business logic, or sensitive data directly into the system prompt, as attackers can often extract these instructions through prompt injection techniques.
- ☑ **Avoid reliance on system prompts for strict behavior control:** Treat system prompts as behavioral guidelines rather than absolute security barriers, acknowledging that determined adversaries can bypass these instructions using sophisticated manipulation tactics to elicit unintended responses.
- ☑ **Ensure that security controls are enforced independently from the LLM:** Implement external validation layers and strict functional sandboxing outside the model environment to verify permissions and sanitize outputs, rather than trusting the LLM to self-police its own restrictions.

8. Vector and Embedding Weaknesses

RAG systems rely heavily on vectors and embeddings to efficiently retrieve and integrate this external information. However, vulnerabilities in the generation, storage, and retrieval of these vectors and embeddings introduce significant security risks. Exploitable weaknesses can lead to malicious actors injecting harmful content, manipulating model outputs to produce inaccurate or biased information, or even gaining unauthorized access to sensitive data embedded within the vector space.

Examples from Pentests



Prevention and Mitigation Strategies


- ☑ **Implement fine-grained access controls and permission-aware vector and embedding stores:** Enforce strict, user-level permissioning within the vector database to ensure that the retrieval mechanism respects data segregation policies and only accesses embeddings the requesting user is authorized to view.
- ☑ **Implement robust data validation pipelines for knowledge sources:** Integrate continuous integrity checks into the data ingestion process to verify the authenticity of information before it is vectorized, preventing the corruption of the knowledge base through poisoned or unverified inputs.

9. Misinformation

Misinformation generated by LLMs represents a significant vulnerability for applications leveraging this technology. This occurs when LLMs produce outputs that, while seemingly credible, are factually incorrect or misleading. This can stem from hallucinations, where models fabricate content to fill gaps in their knowledge, or from biases and incomplete data within their training. The consequences of LLM-driven misinformation are serious, potentially leading to security incidents, damage to reputation, and legal liabilities. Furthermore, the issue is compounded by user overreliance on LLM outputs, where a lack of critical verification can lead to the integration of false information into crucial processes and decision-making.

Examples from Pentests





Prevention and Mitigation Strategies

- ☑ **Use retrieval-augmented generation to enhance the reliability of model outputs:** Retrieve relevant and verified information from trusted external databases during response generation.
- ☑ **Encourage users to cross-check LLM outputs:** Users should be instructed to check trusted external sources to ensure the accuracy of the information.
- ☑ **Identify the risks and possible harms associated with LLM-generated content:** Then clearly communicate these risks and limitations to users.

10. Unbounded Consumption

Unbounded Consumption in LLM applications arises when users can initiate excessive and uncontrolled inference requests. Inference, the process of generating outputs based on prompts, is computationally intensive for LLMs, particularly in cloud environments. This vulnerability allows attackers to exploit resource limitations, leading to several critical risks. Uncontrolled inference can result in denial-of-service conditions, significant financial losses due to cloud computing costs, and even the potential for model theft through behavioral cloning attempts. Furthermore, legitimate users may experience service degradation as resources are depleted.

Examples from Pentests

The attacker sends a high volume of requests to the LLM API, causing excessive consumption of computational resources and making the service unavailable to legitimate users.

Prevention and Mitigation Strategies

- ☑ **Apply rate limiting and user quotas:** Restrict the number of requests a single source entity can make in a given time period.
- ☑ **Monitor and manage resource allocation dynamically:** This can prevent any single user or request from consuming excessive resources.
- ☑ **Implement restrictions on the number of queued actions and total actions:** Incorporate dynamic scaling and load balancing.

Why Pentesting Is Essential to Securing LLM Apps

The rush to integrate AI and LLMs into enterprise ecosystems is moving at a breakneck speed, often outpacing the security controls necessary to protect them. While organizations often worry about novel threats like prompt injection, real-world testing shows that traditional vulnerabilities, such as SQL injection, remain the most prevalent entry points for attackers. This blend of new AI-specific attack vectors and classic web application flaws creates a complex attack surface that automated scanners and standard compliance checks are often unable to fully decipher.

Without a dedicated strategy to validate these systems, organizations risk deploying applications that are fundamentally insecure by design. The complexity of LLM ecosystems—where natural language is the code and logic errors can lead to massive data exposure—demands a level of ingenuity that only human expertise can provide. Pentesting as a service (PTaaS) is the critical mechanism that can help you bridge this gap between rapid innovation and operational security.

Because genAI applications are non-deterministic and highly interactive, they suffer from silent failures—such as logic bypasses and excessive agency—that static analysis tools simply cannot catch. A rigorous pentesting program provides the adversarial perspective needed to identify these nuances. It is the only way to uncover how an attacker could manipulate an LLM to exfiltrate sensitive data or poison a model, ensuring that the drive for innovation does not come at the cost of catastrophic exposure.

> “ — ”
>
> This blend of new AI-specific attack vectors and classic web application flaws creates a complex attack surface that automated scanners and standard compliance checks are often unable to fully decipher.

How Cobalt Can Help

Cobalt effectively bridges the gap between the speed of AI innovation and the rigor of offensive security by delivering a human-led, AI-powered approach to penetration testing. We recognize that while AI is a powerful accelerator, it cannot yet replace the intuition and creativity of an experienced ethical hacker.

Cobalt empowers its community of top-tier pentesters with advanced AI tools that handle the repetitive, administrative burdens of testing, such as reconnaissance and reporting. This provides a force-multiplying effect, allowing our experts to dedicate their energy to what matters most: finding the sophisticated, nuanced vulnerabilities that automated agents miss. Unlike generic solutions trained on synthetic data, Cobalt has over a decade of real-world pentesting data, ensuring our testers are equipped with unique insights into how vulnerabilities manifest in complex environments.

By combining the scalability and speed of the Cobalt platform with the unmatched expertise of the Cobalt Core, we offer a defense that evolves as fast as the threat landscape. Organizations no longer have to choose between speed-to-market and security; with Cobalt, they can innovate fearlessly, knowing their AI applications have been battle-tested by the best human minds in the industry, augmented by AI.

Quality of Our Pentesting Community

The Cobalt Core community has 500 elite pentesters, averaging 11 years of experience, holding top certifications like CISSP, OSCP, and CREST. Their specialized knowledge includes a wide range of security services and pentests from web application and API testing to AI/LMM-based apps, physical devices and IoT, social engineering, red teaming, source code review, and more. With an acceptance rate of less than 5%, the Cobalt Core ensures you receive the highest quality security assessments from the industry's best talent.

5000+
PENTESTS PER YEAR

10K+
CRITICAL OR HIGH SEVERITY VULNERABILITIES IDENTIFIED

45+
COUNTRIES

11
AVERAGE YEARS OF EXPERIENCE

About Cobalt

Cobalt is the pioneer in pentesting as a service (PTaaS) and a leader in offensive security services.

We are focused on combining talent and technology with speed, scalability, and expertise. Thousands of customers and hundreds of partners rely on the Cobalt Offensive Security Platform, along with the industry's largest exclusive community of 450+ trusted pentesters and security experts, to find and fix vulnerabilities across their environments. By enabling faster pentest launches, real-time collaboration with testers, continuous scanning, and seamless integration with remediation workflows, we help organizations identify critical issues and accelerate risk mitigation so they can operate fearlessly and innovate securely.

Discover how human-led, AI-powered pentesting can help you identify security gaps in your AI and LLM applications.

BOOK A DEMO

© 2025 Cobalt Labs, Inc. | All Rights Reserved. Whitepaper – Pentester Guide to the OWASP TOP 10 For LLM