

Subject Name Solutions

1333203 – Winter 2023

Semester 1 Study Material

Detailed Solutions and Explanations

Question 1(a) [3 marks]

Define linked list. List different types of linked list.

Solution

Definition

A linked list is a linear data structure where elements are stored in nodes, and each node points to the next node in the sequence

Types of Linked List

1. Singly Linked List
2. Doubly Linked List
3. Circular Linked List
4. Circular Doubly Linked List

Diagram:

```
1 Singly:      [Data|Next] \rightarrow [Data|Next] \rightarrow [Data|Next] \rightarrow NULL
2 Doubly:      [Prev|Data|Next]  [Prev|Data|Next]  [Prev|Data|Next] \rightarrow NULL
3 Circular:     [Data|Next] \rightarrow [Data|Next] \rightarrow [Data|Next]
```

Mnemonic

“Single, Double, Circle, Double-Circle”

Question 1(b) [4 marks]

Explain Linear and Non Linear Data structure in Python with examples.

Solution

Data Structure

Linear

Description

Elements arranged in sequential order where each element has exactly one predecessor and successor (except first and last)

Python Examples


Lists: [1, 2, 3] Tuples: (1, 2, 3)
Strings: "abc" Queue: queue.Queue()

Non-Linear

Elements not arranged sequentially; an element can connect to multiple elements

Dictionary: {"a": 1, "b": 2} Set: {1, 2, 3} Tree: Custom implementation Graph: Custom implementation

Diagram:



Mnemonic

“Linear Listens In Sequence, Non-linear Navigates Various Paths”

Question 1(c) [7 marks]

Explain class, attributes, object and class method in python with suitable example.

Solution

Diagram:

Student

-roll_no

-name

+init()

+display()

Term

Description

Class

Blueprint for creating objects with shared attributes and methods

Attributes

Variables that store data inside a class

Object

Instance of a class with specific attribute values

Class Method

Functions defined within a class that can access and modify class states

Code:

```
1 class Student:
2     # Class attribute
3     school = "GTU"
4
5     # Constructor
6     def __init__(self, roll_no, name):
7         # Instance attributes
8         self.roll_no = roll_no
9         self.name = name
10
11    # Instance method
12    def display(self):
13        print(f"Roll No: {self.roll_no}, Name: {self.name}")
14
15    # Class method
16    @classmethod
17    def change_school(cls, new_school):
18        cls.school = new_school
19
20 # Creating object
21 student1 = Student(101, "Raj")
22 student1.display() # Output: Roll No: 101, Name: Raj
```

Mnemonic

“Class Creates, Attributes Store, Objects Use, Methods Operate”


Question 1(c) OR [7 marks]

Define Data Encapsulation & Polymorphism. Develop a Python code to explain Polymorphism.

Solution

Concept	Definition
Data Encapsulation	Bundling data and methods into a single unit (class) and restricting direct access to some components
Polymorphism	Ability of different classes to provide their own implementation of methods with the same name

Diagram:



Code:

```
1 # Polymorphism example
2 class Animal:
3     def speak(self):
4         pass
5
6 class Dog(Animal):
7     def speak(self):
8         return "Woof!"
9
10 class Cat(Animal):
11     def speak(self):
12         return "Meow!"
13
14 class Duck(Animal):
15     def speak(self):
16         return "Quack!"
17
18 # Function demonstrating polymorphism
19 def animal_sound(animal):
20     return animal.speak()
21
22 # Creating objects
23 dog = Dog()
24 cat = Cat()
25 duck = Duck()
26
27 # Same function works for different animal objects
28 print(animal_sound(dog)) # Output: Woof!
29 print(animal_sound(cat)) # Output: Meow!
30 print(animal_sound(duck)) # Output: Quack!
```

Mnemonic

“Encapsulate to Protect, Polymorphism for Flexibility”

Question 2(a) [3 marks]

Differentiate between Stack and Queue.

Solution

Feature	Stack	Queue
Principle	LIFO (Last In First Out)	FIFO (First In First Out)
Operations	Push, Pop	Enqueue, Dequeue
Access	Elements can only be added/removed from one end (top)	Elements are added at rear end and removed from front end

Diagram:

```
1 Stack:      [3]      Queue: [1] \rightarrow [2] \rightarrow [3]
2              [2]      Front      Rear
3              [1]
4              ---
```

Mnemonic

“Stack Piles Up, Queue Lines Up”

Question 2(b) [4 marks]

Write an algorithm for PUSH and POP operation of stack in python.

Solution

PUSH Algorithm:

```
1 Start
2   1. Check if stack is full
3   2. If not full, increment top by 1
4   3. Add element at position 'top'
5 End
```

POP Algorithm:

```
1 Start
2   1. Check if stack is empty
3   2. If not empty, retrieve element at 'top'
4   3. Decrement top by 1
5   4. Return retrieved element
6 End
```

Code:

```
1 class Stack:
2     def __init__(self, size):
3         self.stack = []
4         self.size = size
5         self.top = -1
6
7     def push(self, element):
8         if self.top >= self.size - 1:
9             return "Stack Overflow"
10        else:
11            self.top += 1
12            self.stack.append(element)
13            return "Pushed " + str(element)
14
15    def pop(self):
16        if self.top < 0:
17            return "Stack Underflow"
18        else:
19            element = self.stack.pop()
20            self.top -= 1
21            return element
```

Mnemonic

“Push to Top, Pop from Top”

Question 2(c) [7 marks]

Convert following equation from infix to postfix using Stack. $A * (B + C) - D / (E + F)$

Solution

Diagram:

1 Infix: $A * (B + C) - D / (E + F)$
2 Postfix: $A B C + * D E F + / -$

Step	Symbol	Stack	Output
1	A		A
2	*	*	A
3	(* (A
4	B	* (A B
5	+	* (+	A B
6	C	* (+	A B C
7)	*	A B C +
8	-	-	A B C + *
9	D	-	A B C + * D
10	/	- /	A B C + * D
11	(- / (A B C + * D
12	E	- / (A B C + * D E
13	+	- / (+	A B C + * D E
14	F	- / (+	A B C + * D E F
15)	- /	A B C + * D E F +
16	end		A B C + * D E F + / -

Solution

$A B C + * D E F + / -$

Mnemonic

“Operators Stack, Operands Print”


Question 2(a) OR [3 marks]

Differentiate between simple Queue and circular Queue.

Solution

Feature	Simple Queue	Circular Queue
Structure	Linear data structure	Linear data structure with connected ends
Memory	Inefficient memory usage due to unused space after dequeue	Efficient memory usage by reusing empty spaces
Implementation	Front always at index 0, rear increases	Front and rear move in circular fashion using modulo

Diagram:



Mnemonic

“Simple Wastes, Circular Reuses”


Question 2(b) OR [4 marks]

Explain concept of recursive function with suitable example.

Solution

Key Aspects	Description
Definition	A function that calls itself to solve a smaller instance of the same problem
Base Case	The condition where the function stops calling itself
Recursive Case	The condition where the function calls itself with a simpler version of the problem

Diagram:



Code:

```
1 def factorial(n):
2     # Base case
3     if
4
5     n == 0:
6
7         return 1
8     # Recursive case
9     else:
10        return n * factorial(n-1)
11
12 # Example
13 result = factorial(5) # 5! = 120
```

Mnemonic

“Base Breaks, Recursion Returns”

Question 2(c) OR [7 marks]

Develop a python code to implement Enqueue and Dequeue operation in Queue.

Solution

Diagram:

```
1 Enqueue:  
2 [1] [2] [3] \rightarrow [1] [2] [3] [4]  
3  
4 Dequeue:  
5 [1] [2] [3] [4] \rightarrow [2] [3] [4]
```

Code:

```
1 class Queue:  
2     def __init__(self, size):  
3         self.queue = []  
4         self.size = size  
5         self.front = 0  
6         self.rear = -1  
7         self.count = 0  
8  
9     def enqueue(self, item):  
10        if self.count >= self.size:  
11            return "Queue is full"  
12        else:  
13            self.rear += 1  
14            self.queue.append(item)  
15            self.count += 1  
16            return "Enqueued " + str(item)  
17  
18        def dequeue(self):  
19            if self.count <= 0:  
20                return "Queue is empty"  
21            else:  
22                item = self.queue.pop(0)  
23                self.count -= 1  
24                return item  
25  
26        def display(self):  
27            return self.queue  
28  
29 # Test  
30 q = Queue(5)  
31 q.enqueue(10)  
32 q.enqueue(20)  
33 q.enqueue(30)  
34 print(q.display()) # [10, 20, 30]  
35 print(q.dequeue()) # 10  
36 print(q.display()) # [20, 30]
```

Mnemonic

“Enqueue at End, Dequeue from Start”

Question 3(a) [3 marks]

Give Difference between Singly linked list and Circular linked list.

Solution

Feature	Singly Linked List	Circular Linked List
Last Node	Points to NULL	Points back to the first node
Traversal	Has a definite end	Can be traversed continuously
Memory	Each node needs one pointer	Each node needs one pointer

Diagram:

```
1 Singly:  [1] \rightarrow [2] \rightarrow [3] \rightarrow NULL
2 Circular: [1] \rightarrow [2] \rightarrow [3] \rightarrow
```

Mnemonic

“Singly Stops, Circular Cycles”

Question 3(b) [4 marks]

Explain concept of Doubly linked list.

Solution

Diagram:

```
1 NULL \leftarrow [Prev|1|Next]  [Prev|2|Next]  [Prev|3|Next] \rightarrow NULL
```

Feature	Description
Node Structure	Each node contains data and two pointers (previous and next)
Navigation	Can traverse in both forward and backward directions
Operations	Insertion and deletion can be performed from both ends
Memory Usage	Requires more memory than singly linked list due to extra pointer

Code:

```
1 class Node:
2     def __init__(self, data):
3         self.data = data
4         self.prev = None
5         self.next = None
```

Mnemonic


“Double Pointers, Double Directions”

Question 3(c) [7 marks]


Write an algorithm for following operation on singly linked list: 1. To insert a node at the beginning of the list. 2. To insert the node at the end of the list.

Solution

Insert at Beginning:



Insert at End:



Code:

```

1 def insert_at_beginning(head, data):
2     new_node = Node(data)
3     new_node.next = head
4     return new_node # New head
5
6 def insert_at_end(head, data):
7     new_node = Node(data)
8     new_node.next = None
9
10    # If linked list is empty
11    if head is None:
12        return new_node
13
14    # Traverse to the last node
15    temp = head
16    while temp.next:
17        temp = temp.next
18
19    # Link the last node to new node
20    temp.next = new_node
21    return head
  
```

Mnemonic

“Begin: New Leads Old, End: Old Leads New”

Question 3(a) OR [3 marks]


List different operations performed on singly linked list.

Solution

Operations on Singly Linked List

1. Insertion (at beginning, middle, end)
2. Deletion (from beginning, middle, end)
3. Traversal (visiting each node)
4. Searching (finding a specific node)
5. Updating (modifying node data)

Diagram:



Mnemonic


“Insert Delete Traverse Search Update”

Question 3(b) OR [4 marks]

Explain concept of Circular linked list.

Solution

Diagram:



Feature	Description
Structure	Last node points to the first node instead of NULL
Advantage	Allows continuous traversal through all nodes
Applications	Round robin scheduling, circular buffer implementation
Operations	Insertion and deletion similar to singly linked list with special handling for the last node

Code:

```
1 class Node:
2     def __init__(self, data):
3         self.data = data
4         self.next = None
5
6 # Creating a circular linked list with 3 nodes
7 head = Node(1)
8 node2 = Node(2)
9 node3 = Node(3)
10
11 head.next = node2
12 node2.next = node3
13 node3.next = head # Makes it circular
```

Mnemonic

“Last Links to First”

Question 3(c) OR [7 marks]


List application of linked list. Write an algorithm to count the number of nodes in singly linked list.

Solution

Applications of Linked List

1. Implementation of stacks and queues
2. Dynamic memory allocation
3. Undo functionality in applications
4. Hash tables (chaining)
5. Adjacency lists for graphs

Algorithm to Count Nodes:



Code:

```

1 def count_nodes(head):
2     count = 0
3     temp = head
4
5     while temp:
6         count += 1
7         temp = temp.next
8
9     return count
10
11 # Example usage
12 # Assuming head points to the first node of a linked list
13 total_nodes = count_nodes(head)
14 print(f"Total nodes: {total_nodes}")
  
```

Mnemonic

“Count While Moving”

Question 4(a) [3 marks]

Compare Linear search with Binary search.

Solution

Feature	Linear Search	Binary Search
Data Arrangement	Works on both sorted and unsorted data	Works only on sorted data
Time Complexity	$O(n)$	$O(\log n)$
Implementation	Simpler	More complex
Best For	Small datasets or unsorted data	Large sorted datasets

Diagram:

```

1 Linear: [1] [2] [3] [4] [5] [6] [7] [8]
2         ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓
3         Sequential checking
4
5 Binary: [1] [2] [3] [4] [5] [6] [7] [8]
6         ↓
7         Check middle
8         /  \
9        /    \
10       /      \
11      /        \
12     /          \
13    /            \
14   /              \
15  /                \
16 /                  \
17 /                    \
18 /                      \
19 /                        \
20 /                          \
21 /                            \
22 /                              \
23 /                                \
24 /                                  \
25 /                                    \
26 /                                      \
27 /                                        \
28 /                                          \
29 /                                            \
30 /                                              \
31 /                                                \
32 /                                                  \
33 /                                                    \
34 /                                                      \
35 /                                                        \
36 /                                                          \
37 /                                                            \
38 /                                                              \
39 /                                                                \
40 /                                                                  \
41 /                                                                    \
42 /                                                                      \
43 /                                                                        \
44 /                                                                          \
45 /                                                                            \
46 /                                                                              \
47 /                                                                                \
48 /                                                                                  \
49 /                                                                                    \
50 /                                                                                      \
51 /                                                                                        \
52 /                                                                                          \
53 /                                                                                           \
54 /                                                                                             \
55 /                                                                                              \
56 /                                                                                                \
57 /                                                                                                  \
58 /                                                                                                   \
59 /                                                                                                  \
60 /                                                                                                   \
61 /                                                                                                   \
62 /                                                                                                   \
63 /                                                                                                   \
64 /                                                                                                   \
65 /                                                                                                   \
66 /                                                                                                   \
67 /                                                                                                   \
68 /                                                                                                   \
69 /                                                                                                   \
70 /                                                                                                   \
71 /                                                                                                   \
72 /                                                                                                   \
73 /                                                                                                   \
74 /                                                                                                   \
75 /                                                                                                   \
76 /                                                                                                   \
77 /                                                                                                   \
78 /                                                                                                   \
79 /                                                                                                   \
80 /                                                                                                   \
81 /                                                                                                   \
82 /                                                                                                   \
83 /                                                                                                   \
84 /                                                                                                   \
85 /                                                                                                   \
86 /                                                                                                   \
87 /                                                                                                   \
88 /                                                                                                   \
89 /                                                                                                   \
90 /                                                                                                   \
91 /                                                                                                   \
92 /                                                                                                   \
93 /                                                                                                   \
94 /                                                                                                   \
95 /                                                                                                   \
96 /                                                                                                   \
97 /                                                                                                   \
98 /                                                                                                   \
99 /                                                                                                   \
100 /                                                                                                   \
  
```

Mnemonic

“Linear Looks at All, Binary Breaks in Half”

Question 4(b) [4 marks]


Write an algorithm for selection sort method.

Solution

Diagram:

```
1 Initial: [5, 3, 8, 1, 2]
2 Pass 1:  [1, 3, 8, 5, 2] (Find min = 1, swap with 5)
3 Pass 2:  [1, 2, 8, 5, 3] (Find min = 2, swap with 3)
4 Pass 3:  [1, 2, 3, 5, 8] (Find min = 3, swap with 8)
5 Pass 4:  [1, 2, 3, 5, 8] (Find min = 5, already in place)
```

Algorithm:



Code Outline:

```
1 def selection_sort(arr):
2     n = len(arr)
3
4     for i in range(n):
5         min_idx = i
6
7         # Find the minimum element in unsorted array
8         for j in range(i+1, n):
9             if arr[j] < arr[min_idx]:
10                 min_idx = j
11
12         # Swap the found minimum element with the first element
13         arr[i], arr[min_idx] = arr[min_idx], arr[i]
```

Mnemonic

“Find Minimum, Swap Position”

Question 4(c) [7 marks]

Develop a python code to sort following list in ascending order using Bubble sort method. list1=[5,4,3,2,1,0]

Solution

Diagram:

```
1 Initial: [5, 4, 3, 2, 1, 0]
2 Pass 1:  [4, 3, 2, 1, 0, 5]
3 Pass 2:  [3, 2, 1, 0, 4, 5]
4 Pass 3:  [2, 1, 0, 3, 4, 5]
5 Pass 4:  [1, 0, 2, 3, 4, 5]
6 Pass 5:  [0, 1, 2, 3, 4, 5]
```

Code:

```
1 def bubble_sort(arr):
2     n = len(arr)
3
4     # Traverse through all array elements
5     for i in range(n):
6         # Last i elements are already in place
7         for j in range(0, n-i-1):
8             # Swap if current element is greater than next element
9             if arr[j] > arr[j+1]:
```

```

0         arr[j], arr[j+1] = arr[j+1], arr[j]
1
2     return arr
3
4 # Input list
5 list1 = [5, 4, 3, 2, 1, 0]
6
7 # Sorting the list
8 sorted_list = bubble_sort(list1)
9
10 # Displaying the result
11 print("Sorted list:", sorted_list)
12 # Output: Sorted list: [0, 1, 2, 3, 4, 5]

```

Mnemonic

“Bubble Biggest Upward”

Question 4(a) OR [3 marks]

Define sorting. List different sorting methods.

Solution


Definition

Sorting is the process of arranging data in a specified order (ascending or descending)

Sorting Methods

1. Bubble Sort 2. Selection Sort 3. Insertion Sort 4. Merge Sort 5. Quick Sort 6. Heap Sort 7. Radix Sort

Diagram:



Mnemonic

“Better Sort Improves Many Query Results”

Question 4(b) OR [4 marks]

Write an algorithm for Insertion sort method.

Solution


Diagram:

```

1 Initial: [5, 2, 4, 6, 1, 3]
2 Pass 1: [2, 5, 4, 6, 1, 3] (Insert 2 before 5)
3 Pass 2: [2, 4, 5, 6, 1, 3] (Insert 4 before 5)
4 Pass 3: [2, 4, 5, 6, 1, 3] (6 is already in place)
5 Pass 4: [1, 2, 4, 5, 6, 3] (Insert 1 at beginning)
6 Pass 5: [1, 2, 3, 4, 5, 6] (Insert 3 after 2)

```

Algorithm:



Code Outline:

```

1 def insertion_sort(arr):
2     for i in range(1, len(arr)):
3         key = arr[i]
4         j = i - 1
5
6         # Move elements that are greater than key
7         # to one position ahead of their current position
8         while j >= 0 and arr[j] > key:
9             arr[j + 1] = arr[j]
10            j -= 1
11
12    arr[j + 1] = key
  
```

Mnemonic

“Take Card, Insert In Order”

Question 4(c) OR [7 marks]

Develop a python code to sort following list in ascending order using selection sort method. list1=[6,3,25,8,-1,55,0]

Solution

Diagram:

```

1 Initial: [6, 3, 25, 8, -1, 55, 0]
2 Pass 1:  [-1, 3, 25, 8, 6, 55, 0]  (Find min = -1, swap with 6)
3 Pass 2:  [-1, 0, 25, 8, 6, 55, 3]  (Find min = 0, swap with 3)
4 Pass 3:  [-1, 0, 3, 8, 6, 55, 25]  (Find min = 3, swap with 25)
5 Pass 4:  [-1, 0, 3, 6, 8, 55, 25]  (Find min = 6, swap with 8)
6 Pass 5:  [-1, 0, 3, 6, 8, 55, 25]  (Find min = 8, already in place)
7 Pass 6:  [-1, 0, 3, 6, 8, 25, 55]  (Find min = 25, swap with 55)
  
```

Code:

```

1 def selection_sort(arr):
2     n = len(arr)
3
4     for i in range(n):
5         # Find the minimum element in remaining unsorted array
6         min_idx = i
7         for j in range(i+1, n):
8             if arr[j] < arr[min_idx]:
9                 min_idx = j
10
11        # Swap the found minimum element with the first element
12        arr[i], arr[min_idx] = arr[min_idx], arr[i]
13
14    return arr
15
16 # Input list
17 list1 = [6, 3, 25, 8, -1, 55, 0]
18
19 # Sorting the list
  
```



```

30 sorted_list = selection_sort(list1)
31
32 # Displaying the result
33 print("Sorted list:", sorted_list)
34 # Output: Sorted list: [-1, 0, 3, 6, 8, 25, 55]

```

Mnemonic

“Select Smallest, Shift to Start”


Question 5(a) [3 marks]

Define following terms regarding Tree data structure: 1. Forest 2. Root node 3. Leaf node

Solution

Term	Definition
Forest	Collection of disjoint trees (multiple trees without connections between them)
Root Node	Topmost node of a tree with no parent, from which all other nodes are descended
Leaf Node	Node with no children (terminal node at the bottom of the tree)

Diagram:



Mnemonic


“Forest has Many Roots, Roots Lead All, Leaves End All”

Question 5(b) [4 marks]

Draw Binary search tree for 78,58,82,15,66,80,99 and write In-order traversal for the tree.

Solution

Binary Search Tree:



In-order Traversal:

Step	Visit Order
1	Visit left subtree of 78

2	Visit left subtree of 58
3	Visit 15
4	Visit 58
5	Visit 66
6	Visit 78
7	Visit left subtree of 82
8	Visit 80
9	Visit 82
10	Visit 99

In-order Traversal Result: 15, 58, 66, 78, 80, 82, 99

Mnemonic


“Left, Root, Right”

Question 5(c) [7 marks]


Write an algorithm for following operation: 1. Insertion of Node in Binary Tree 2. Deletion of Node in Binary Tree

Solution

Insertion Algorithm:



Deletion Algorithm:



Code:

```

1 class Node:
2     def __init__(self, data):
3         self.data = data
4         self.left = None
5         self.right = None
6
7 # Insertion in Binary Tree
8 def insert(root, data):
9     if root is None:
10        return Node(data)
11
12    # Level order traversal to find vacant position
13    queue = []
14    queue.append(root)
15
16    while queue:
17        temp = queue.pop(0)
18
19        if temp.left is None:
20            temp.left = Node(data)
21            break
22        else:
23            queue.append(temp.left)
  
```

```

34         if temp.right is None:
35             temp.right = Node(data)
36             break
37         else:
38             queue.append(temp.right)
39
40     return root
41
42 # Deletion in Binary Tree
43 def delete_node(root, key):
44     if root is None:
45         return None
46
47     if root.left is None and root.right is None:
48         if root.data == key:
49             return None
50         else:
51             return root
52
53     # Find the node to delete
54     key_node = None
55     # Find the deepest node
56     last = None
57     parent = None
58
59     # Level order traversal
60     queue = []
61     queue.append(root)
62
63     while queue:
64         temp = queue.pop(0)
65
66         if temp.data == key:
67             key_node = temp
68
69         if temp.left:
70             parent = temp
71             queue.append(temp.left)
72             last = temp.left
73
74         if temp.right:
75             parent = temp
76             queue.append(temp.right)
77             last = temp.right
78
79     if key_node:
80         # Replace with deepest node's data
81         key_node.data = last.data
82
83         # Delete the deepest node
84         if parent.right == last:
85             parent.right = None
86         else:
87             parent.left = None
88
89     return root

```

Mnemonic

“Insert at Empty, Delete by Swap and Remove”


Question 5(a) OR [3 marks]

Define following terms regarding Tree data structure: 1. In-degree 2. Out-degree 3. Depth

Solution

Term	Definition
In-degree	Number of edges coming into a node (always 1 for each node except root node in a tree)
Out-degree	Number of edges going out from a node (number of children)
Depth	Length of the path from root to the node (number of edges in path)

Diagram:



Node	In-degree	Out-degree
A	0	2
B	1	2
C	1	1
D	1	0
E	1	0
F	1	0


Mnemonic

“In Counts Parents, Out Counts Children, Depth Counts Edges from Root”

Question 5(b) OR [4 marks]

Write Preorder and postorder traversal of following Binary tree.


Binary Tree:




Solution

Traversal	Order	Result
Preorder	Root, Left, Right	100, 20, 10, 30, 200, 150, 300
Postorder	Left, Right, Root	10, 30, 20, 150, 300, 200, 100

Preorder Visualization:



Postorder Visualization:



Mnemonic


- Preorder: "Root First, Then Children"
- Postorder: "Children First, Then Root"

Question 5(c) OR [7 marks]

Develop a program to implement construction of Binary Search Tree.

Solution

Diagram:



Code:

```
1 class Node:
2     def __init__(self, key):
3         self.key = key
4         self.left = None
5         self.right = None
6
7 def insert(root, key):
8     # If the tree is empty, return a new node
9     if root is None:
10        return Node(key)
11
12    # Otherwise, recur down the tree
13    if key < root.key:
14        root.left = insert(root.left, key)
15    else:
16        root.right = insert(root.right, key)
17
18    # Return the unchanged node pointer
19    return root
20
21 def inorder(root):
22     if root:
23         inorder(root.left)
24         print(root.key, end=" ")
25         inorder(root.right)
26
27 def preorder(root):
28     if root:
29         print(root.key, end=" ")
30         preorder(root.left)
31         preorder(root.right)
32
33 def postorder(root):
34     if root:
35         postorder(root.left)
36         postorder(root.right)
37         print(root.key, end=" ")
38
39 # Driver program to test the above functions
40 def main():
41     # Create BST with these elements: 50, 30, 20, 40, 70, 60, 80
42     root = None
```

```

3     elements = [50, 30, 20, 40, 70, 60, 80]
4
5     for element in elements:
6         root = insert(root, element)
7
8     # Print traversals
9     print("Inorder traversal: ", end="")
10    inorder(root)
11    print("\nPreorder traversal: ", end="")
12    preorder(root)
13    print("\nPostorder traversal: ", end="")
14    postorder(root)
15
16 # Run the program
17 main()

```

Example Output:

```

1 Inorder traversal: 20 30 40 50 60 70 80
2 Preorder traversal: 50 30 20 40 70 60 80
3 Postorder traversal: 20 40 30 60 80 70 50

```

Mnemonic

“Insert Smaller Left, Larger Right”