exp7

R0 G0/0   2001:AA:1::1/64

r0. g0/1. 2001:AB:12::1/64

R1. G0/0. 2001:AB:12::2/64

R1. G0/1. 2002:BB:2::1/64

Open R0 → CLI and enter:
enable
configure terminal

ipv6 unicast-routing

interface gigabitEthernet 0/0
ipv6 address 2001:AA:1::1/64
ipv6 address FE80::1 link-local
no shutdown
exit

interface gigabitEthernet 0/1
ipv6 address 2001:AB:12::1/64
ipv6 address FE80::1 link-local
no shutdown
exit

ipv6 router rip RIP1
exit

interface gigabitEthernet 0/0
ipv6 rip RIP1 enable
exit

interface gigabitEthernet 0/1
ipv6 rip RIP1 enable
exit

end
write

Open R1 → CLI:

enable
configure terminal

ipv6 unicast-routing

```
interface gigabitEthernet 0/0
ipv6 address 2001:AB:12::2/64
ipv6 address FE80::2 link-local
no shutdown
exit

interface gigabitEthernet 0/1
ipv6 address 2002:BB:2::1/64
ipv6 address FE80::2 link-local
no shutdown
exit

ipv6 router rip RIP1
exit

interface gigabitEthernet 0/0
ipv6 rip RIP1 enable
exit

interface gigabitEthernet 0/1
ipv6 rip RIP1 enable
exit

end
write
```

For each PC:

1. Click PC0.

2. Open Desktop.

3. Select IP Configuration.

4. Under IPv6 Configuration, select Auto Config.