

Glossary

Issue	04
Date	2023-06-30



Copyright © Huawei Technologies Co., Ltd. 2026. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions



HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base
Bantian, Longgang
Shenzhen 518129
People's Republic of China

Website: <https://www.huawei.com>

Email: support@huawei.com

Security Declaration

Vulnerability

Huawei's regulations on product vulnerability management are subject to the *Vul. Response Process*. For details about this process, visit the following web page:

<https://www.huawei.com/en/psirt/vul-response-process>

For vulnerability information, enterprise customers can visit the following web page:

<https://securitybulletin.huawei.com/enterprise/en/security-advisory>

Contents

1 Glossary.....1

1.1 Numerics..... 1

1.2 A..... 7

1.3 B..... 64

1.4 C..... 96

1.5 D..... 175

1.6 E..... 216

1.7 F..... 258

1.8 G..... 289

1.9 H..... 310

1.10 I..... 332

1.11 J..... 379

1.12 K..... 380

1.13 L..... 383

1.14 M..... 414

1.15 N..... 488

1.16 O..... 520

1.17 P..... 545

1.18 Q..... 611

1.19 R..... 617

1.20 S..... 674

1.21 T..... 774

1.22 U..... 820

1.23 V..... 853

1.24 W..... 874

1.25 X..... 887

1.26 Y..... 890

1.27 Z..... 891

1 Glossary

1.1 Numerics

Term	Abbreviation	Synonym	Definition	Reference
2nd Generation	2G	N/A	2 nd Generation	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Triple Data Encryption Standard	3DES	N/A	In cryptography, Triple Data Encryption Standard (3DES) is a symmetric-key block cipher, which applies the DES cipher algorithm three times to each data block. The Data Encryption Standard's (DES) 56-bit key is no longer considered adequate in the face of modern cryptanalytic techniques and supercomputing power. However, an adapted version of DES, Triple DES (3DES), uses the same algorithm to produce a more secure encryption.	Wikipedia
3rd Generation	3G	N/A	3 rd Generation	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
3rd Generation Partnership Project	3GPP	Third Generation Partnership Project	The 3rd Generation Partnership Project (3GPP) is an umbrella term for a number of standards organizations which develop protocols for mobile telecommunications.	Wikipedia
5th Generation	5G	N/A	In telecommunications, 5G is the fifth generation technology standard for broadband cellular networks, which cellular phone companies began deploying worldwide in 2019, and is the planned successor to the 4G networks which provide connectivity to most current cellphones.	Wikipedia
5G non-standalone	5G NSA	- NSA - non-standalone	The non-standalone (NSA) mode of 5G NR refers to an option of 5G NR deployment that depends on the control plane of an existing 4G LTE network for control functions, while 5G NR is exclusively focused on the user plane.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
5G Radio Access Network	5G RAN	N/A	A radio access network comprising an NG-RAN and/or non-3GPP AN connecting to a 5G Core Network.	ETSI TS 123 501 V16.6.0: "5G; System architecture for the 5G System (5GS)"
5G standalone	5G SA	- SA - standalone	The 5G standalone (5G SA) mode of 5G NR refers to using 5G cells for both signalling and information transfer. It includes the new 5G Packet Core architecture instead of relying on the 4G Evolved Packet Core, to allow the deployment of 5G without the LTE network. It is expected to have lower cost, better efficiency, and to assist development of new use cases.	Wikipedia
Fifth Generation Core network	5GC	5G core network - NGC - Next Generation Core	N/A	3GPP TR 21.905 V17.1.0: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications (Release 17)"

Term	Abbreviation	Synonym	Definition	Reference
5G QoS Identifier	5QI	N/A	A scalar that is used as a reference to a specific QoS forwarding behaviour (e.g. packet loss rate, packet delay budget) to be provided to a 5G QoS flow. This may be implemented in the access network by the 5QI referencing node specific parameters that control the QoS forwarding treatment (e.g. scheduling weights, admission thresholds, queue management thresholds, link layer protocol configuration, etc.).	ETSI TS 123 501 V16.6.0: "5G; System architecture for the 5G System (5GS)"
Institute of Electrical and Electronic Engineers Standard for Port-based Network Access Control	802.1x	N/A	N/A	ETSI TR 103 305-1 V2.1.1: "CYBER; Critical Security Controls for Effective Cyber Defence; Part 3: Service Sector Implementations"

Term	Abbreviation	Synonym	Definition	Reference
8 phase shift keying	8PSK	N/A	N/A	3GPP TR 121 905 V13.0.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Vocabulary for 3GPP Specifications"
1:N protection	N/A	N/A	This protection architecture provides multiple (N) working SNCs/paths and one protection SNC/path.	Huawei Term
4-antenna receive diversity	N/A	N/A	A type of space diversity technique based on which four routes of signals are sent to the same transceiver simultaneously. The transceiver processes the received signals using the diversity combining technique.	Huawei Term
5-tuple	N/A	quintuple	The five pieces of data found within all IP-based network packets: source IP address, source port, destination IP address, destination port, and protocol.	Wikipedia

1.2 A

Term	Abbreviation	Synonym	Definition	Reference
algorithm A3	A3	N/A	A network uses the A3 algorithm to authenticate mobile stations.	Wikipedia
encryption algorithm A5	A5	N/A	Encryption algorithms defined in GSM protocols include A5/0, A5/1, A5/2, A5/3, A5/4, A5/5, A5/6, and A5/7.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Authentication, Authorization and Accounting	AAA	N/A	AAA refers to Authentication, Authorization and Accounting. It is used to refer to a family of protocols that mediate network access.	Wikipedia
ATM Adaptation Layer	AAL	N/A	An interface between higher-layer protocols and Asynchronous Transfer Mode (ATM). The AAL provides a conversion function to and from ATM for various types of information, including voice, video, and data.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
ATM Adaptation Layer 2	AAL2	N/A	ATM Adaptation Layer 2 (AAL2) is an ATM adaptation layer for Asynchronous Transfer Mode (ATM), used primarily in telecommunications; for example, it is used for the interfaces in the Universal Mobile Telecommunications System, and is also used for transporting digital voice. The standard specifications related to AAL2 are ITU standards I.363.2 and I.366.1.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
ATM Adaptation Layer 5	AAL5	N/A	ATM Adaptation Layer 5 (AAL5) is an ATM adaptation layer used to send variable-length packets up to 65,535 octets in size across an Asynchronous Transfer Mode (ATM) network. Unlike most network frames, which place control information in the header, AAL5 places control information in an 8-octet trailer at the end of the packet. The AAL5 trailer contains a 16-bit length field, a 32-bit cyclic redundancy check (CRC) and two 8-bit fields labeled UU and CPI that are currently unused.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
active antenna system	AAS	N/A	A BS system which combines an Antenna Array with an Active Transceiver Unit Array. An AAS may include a Radio Distribution Network.	3GPP TR 37.840 V12.1.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Study of Radio Frequency (RF) and Electromagnetic Compatibility (EMC) requirements for Active Antenna Array System (AAS) base station (Release 12)"
active antenna unit	AAU	N/A	An active antenna unit that incorporates the functions of RF modules and antennas	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
available bit rate	ABR	N/A	Available bit rate (ABR) is a service used in ATM networks when source and destination don't need to be synchronized. ABR does not guarantee against delay or data loss. ABR mechanisms allow the network to allocate the available bandwidth fairly over the present ABR sources. ABR is one of five service categories defined by the ATM Forum for use in an ATM Network.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
adaptive bit rate	ABR	N/A	The adaptive bit rate (ABR) function allows the video server to provide media assets with multiple bit rates. The client selects the most appropriate bit rate for video playback based on the actual conditions, such as network congestion and player processing capability. In addition, the system automatically switches to an appropriate bit rate segment file based on the site requirements. Currently, streaming protocols that support ABR include DASH, HLS, and HSS.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
access class	AC	N/A	All UEs are members of one out of ten randomly allocated mobile populations, defined as access classes 0 to 9. The population number is stored in the SIM/USIM. In addition, UEs may be members of one or more out of 5 special categories (access classes 11 to 15), also held in the SIM/USIM. These are allocated to specific high priority users. Class 15: PLMN staff Class 14: emergency services Class 13: public utilities Class 12: security services Class 11: for PLMN use	3GPP TS 22.261 V19.3.0: "Service requirements for the 5G system"
application context	AC	N/A	An application-context is assigned for each dialogue established by a MAP-user.	ETSI TS 129 002 V9.6.0: "Universal Mobile Telecommunications System (UMTS); Mobile Application Part (MAP) specification"

Term	Abbreviation	Synonym	Definition	Reference
authentication center	AC	AuC	The authentication center (AC) is an entity which stores data for each mobile subscriber to allow the international mobile subscriber identity (IMSI) to be authenticated and to allow communication over the radio path between the mobile station and the network to be ciphered. The AC transmits the data needed for authentication and ciphering via the HLR to the VLR and MSC which need to authenticate a mobile station.	ETS 300 522 ed.3: "Mobile station conformance test system Part 3: DCS 1800 mobile station conformity specification"
alternating current	AC	N/A	Alternating current (AC) is an electric current which periodically reverses direction and changes its magnitude continuously with time in contrast to direct current (DC) which flows only in one direction.	Wikipedia
access control	AC	N/A	Protection of system resources against unauthorized access.	R. Shirey. Internet Security Glossary, Version 2, RFC 4949, August 2007

Term	Abbreviation	Synonym	Definition	Reference
adjacent channel alternate polarization	ACAP	N/A	A channel configuration method, which uses two adjacent channels (one carrying horizontally polarized waves and the other carrying vertically polarized waves) to transmit two signal streams.	Huawei Term
associated control channel	ACCH	N/A	A point-to-point, bidirectional control channel that supports both signaling and packet data. The ACCH is always associated with the traffic channel (TCH) and provides for call control mobile management and RF transmission management signaling.	Huawei Term
automatic congestion handling	ACH	N/A	In ACH, an eNodeB periodically checks cell congestion status. The eNodeB adjusts parameter settings based on congestion conditions to mitigate cell congestion, improving network performance and user experience.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
acknowledgment	ACK	N/A	Type of message sent to indicate that a previously sent message arrived at its destination.	ETSI TR 101 287 V1.2.1: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
access control list	ACL	N/A	A mechanism that implements access control for a system resource by enumerating the system entities that are permitted to access the resource and stating, either implicitly or explicitly, the access modes granted to each entity.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
adjacent channel leakage power ratio	ACLR	N/A	Adjacent channel leakage power ratio (ACLR) is the ratio of the on-channel transmit power to the power measured in one of the adjacent channels with no active channel in the adjacent channels.	EN 303 340 V1.2.1: "Digital Terrestrial TV Broadcast Receivers; Harmonised Standard for access to radio spectrum"

Term	Abbreviation	Synonym	Definition	Reference
access class restriction	ACR	N/A	N/A	3GPP TS 46.008 version 9.0.0 Release 9: "Digital cellular telecommunications system (Phase 2+); Half Rate Speech; Performance Characterization of the GSM Half Rate speech;codec"
allowed cell rate	ACR	N/A	N/A	Huawei Term
access control system	ACS	N/A	A particular set of rules for managing entitlement checking and conditional access messages	ETSI EN 300 401 V2.1.1: "Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers"
Active Codec Set	ACS	N/A	N/A	3GPP TS 26.103 version 16.0.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Speech codec list for GSM and UMTS"

Term	Abbreviation	Synonym	Definition	Reference
Antenna Database	ADB	N/A	An Antenna Database (ADB) subunit stores data about the antenna, its contained arrays, installation and site mapping. Any antenna enclosure shall contain one and only one ADB subunit.	Antenna Interface Standards Group Subunit Type Standard AISG-ST-ADB vADB3.1.3.1
automated guided vehicle	AGV	automatic guided vehicle	An automated guided vehicle or automatic guided vehicle (AGV) is a mobile robot that follows markers or wires in the floor, or uses vision, magnets, or lasers for navigation.	Wikipedia
augmented reality	AR	N/A	Augmented reality (AR) is an interactive experience that combines the real world and computer-generated content.	Wikipedia
aggregation level	N/A	N/A	N/A	3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"

Term	Abbreviation	Synonym	Definition	Reference
ambient IoT	N/A	N/A	Ambient power-enabled Internet of Things (ambient IoT) refers to an IoT service with low power consumption where IoT devices have no or little electric energy storage, but their electric energy storage modules do not need to be charged or manually replaced.	Huawei Term
antenna element	N/A	N/A	An antenna element consists of a dipole and a reflection plate. It causes signal superimposition through reflection and implements directional radiation. An antenna element is a basic unit of an antenna.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
antenna polarization	N/A	N/A	During the propagation of radio waves generated on antenna elements, the electric field and magnetic field are perpendicular to each other in the space domain, and both are perpendicular to the propagation direction. The space direction of the electric field vector is called the polarization direction of the electromagnetic waves radiated by the antenna. Using the ground as the reference plane, antenna polarization directions of one antenna element include vertical polarization and horizontal polarization. If two antenna elements are placed in a cross manner, their polarization directions are orthogonal, forming dual polarization. Dual polarization generally includes vertical/horizontal polarization and +45°/-45° polarization.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
automatic ally detected and manually cleared	ADMC	N/A	Faults are automatically detected by the system when they occur and manually cleared by the operator when they are repaired.	3GPP TS 32.111-1 version 16.0.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Fault Management; Part 1: 3G fault management requirements"

Term	Abbreviation	Synonym	Definition	Reference
asymmetrical digital subscriber line	ADSL	• asymmetrical digital subscriber line • asymmetrical digital subscriber loop	Asymmetrical digital subscriber line (ADSL) is a type of digital subscriber line (DSL) technology, a data communications technology that enables faster data transmission over copper telephone lines than a conventional voiceband modem can provide. ADSL differs from the less common symmetric digital subscriber line (SDSL). In ADSL, bandwidth and bit rate are said to be asymmetric, meaning greater toward the customer premises (downstream) than the reverse (upstream). Providers usually market ADSL as an Internet access service primarily for downloading content from the Internet, but not for serving content accessed by others.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
acoustic echo control	AEC	N/A	N/A	ETSI TS 101 376-3-14 V1.1.1: "GEO-Mobile Radio Interface Specifications; Part 3: Network specifications; Sub-part 14: Transmission Planning Aspects of the Speech Service in the GMR-1 system;GMR-1 03.050"
acoustic echo cancellation	AEC	N/A	A range of acoustic echo cancellation techniques (AEC) that are used to approximate the experience of a true full-duplex speech solution.	ETSI EG 202 848 V1.1.1: "Human Factors;Inclusive eServices for all: Optimizing the accessibility and the use of upcoming user-interaction technologies"

Term	Abbreviation	Synonym	Definition	Reference
Advanced Encryption Standard	AES	N/A	The Advanced Encryption Standard (AES) specifies a FIPS-approved cryptographic algorithm that can be used to protect electronic data. The AES algorithm is a symmetric block cipher that can encrypt (encipher) and decrypt (decipher) information. Encryption converts data to an unintelligible form called ciphertext; decrypting the ciphertext converts the data back into its original form, called plaintext.	FIPS197: Advanced Encryption Standard (AES)
application function	AF	N/A	The application function (AF) is an element offering applications that require the control of IP bearer resources. The AF is capable of communicating with the PCRF to transfer dynamic QoS-related service information. One example of an AF is the P-CSCF of the IM CN subsystem.	3GPP TS 123 207 V16.0.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; End-to-end Quality of Service (QoS) concept and architecture (3GPP TS 23.207 version 16.0.0 Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
automatic frequency control	AFC	automatic fine tuning/AFT	In radio equipment, Automatic Frequency Control (AFC), also called Automatic Fine Tuning (AFT), is a method or circuit to automatically keep a resonant circuit tuned to the frequency of an incoming radio signal. It is primarily used in radio receivers to keep the receiver tuned to the frequency of the desired station.	Wikipedia
automatic frequency planning	AFP	N/A	A function on a GSM network used to help users quickly complete frequency planning. This function shortens the planning period when a network is large-sized.	Huawei Term
access grant channel	AGCH	N/A	A channel that is used to assign resources to a user requesting access to the network. These resources will include the dedicated channel to be used along with timing advance information.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Assisted GPS	A-GPS	N/A	N/A	3GPP TS 101 513 V8.0.1: "Digital cellular telecommunications system (Phase 2+); Location Services (LCS); Location services management"
Authentication Header	AH	N/A	IPsec security protocol that provides message integrity for complete IP packets, including the IP header	ETSI TS 101 909-11 V1.2.1: "Digital Broadband Cable Access to the Public Telecommunications Network; IP Multimedia Time Critical Services; Part 11: Security"
Adaptive High Resolution	AHR	N/A	N/A	Huawei Term
acquisition indicator channel	AICH	N/A	The acquisition indicator channel (AICH) is a fixed rate (SF=256) physical channel used to carry acquisition indicators (AIs). AIs corresponds to signatures on the PRACH.	3GPP TS 25.211 version 7.2.0 Release 7: "Universal Mobile Telecommunications System (UMTS); Physical channels and mapping of transport channels onto physical channels (FDD)"

Term	Abbreviation	Synonym	Definition	Reference
application identifier	AID	N/A	An identifier that can be mapped to a specific application traffic detection rule	3GPP TS 23.501 version 16.9.0: "5G; System architecture for the 5G System (5GS)"
Antenna Interface Standards Group	AISG	N/A	The Antenna Interface Standards Group (AISG) creates and maintains standards for the control and monitoring interface between a base station and a variety of tower-top equipment. These include antennas with remote electrical tilt (RET), tower mounted amplifiers and a variety of sensors that are used to monitor the operation of tower-top equipment.	Antenna Interface Standards Group (AISG)
air interface soft synchronization	AISS	N/A	Air interface soft synchronization synchronizes time between base stations through software measurements which it uses to adjust time differences between base stations.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Antenna Information Sensor Unit	AISU	N/A	An antenna information sensor unit (AISU) consists of global navigation satellite system (GNSS) antennas and sensors. It is installed on the top of an antenna and is used to measure antenna engineering parameters such as the azimuth, mechanical tilt, longitude, latitude, and altitude.	Huawei Term
Authentication and Key Agreement	AKA	N/A	Authentication and Key Agreement (AKA) is a security protocol used in 3G networks. AKA is also used for one-time password generation mechanism for digest access authentication. AKA is a challenge-response based mechanism that uses symmetric cryptography.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
automatic level control	ALC	N/A	N/A	3GPP TS 25.420 version 9.1.1: "Universal Mobile Telecommunications System (UMTS); UTRAN Iur interface general aspects and principles"
Access Link Control Application Part	ALCAP	N/A	Generic name for the transport signalling protocols used to set-up and tear-down transport bearers	3GPP TR 21.905 V17.0.0: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
antenna line device	ALD	N/A	Antenna line device family members include: - RET (Remote electrical tilt) - TMA (Tower Mounted Amplifier) - Smart Bias-Tee - Signal splitter (passive device) - Lightning Protection Devices - Mounting hardware; grounding plates, brackets, cable clamps	Antenna Interface Standards Group (AISG)

Term	Abbreviation	Synonym	Definition	Reference
Antenna location and orientation sensor	ALS	N/A	N/A	Antenna Interface Standards Group Base Standard AISG v3.0
automatic laser shutdown	ALS	N/A	A technique (procedure) to automatically shut down the output power of laser transmitters and optical amplifiers to avoid exposure to hazardous levels.	ITU-T G.664: "Optical safety procedures and requirements for optical transmission systems"
adaptive modulation	AM	N/A	System's ability to communicate with another system using multiple burst profiles and a system's ability to subsequently communicate with multiple systems using different burst profiles.	ETSI TS 102 178: "Broadband Radio Access Networks (BRAN); HIPERMAN; Data Link Control (DLC) layer"
acknowledged mode	AM	N/A	N/A	3GPP TS 38.322: "NR; Radio Link Control (RLC) protocol specification"
aggregate maximum bit rate	AMBR	N/A	The maximum bit rate that limits the aggregate bit rate of a set of non-GBR bearers of a UE.	3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3"

Term	Abbreviation	Synonym	Definition	Reference
adaptive modulation and coding	AMC	N/A	Adaptive modulation and coding (AMC) works by measuring and feeding back the channel SINR to the transmitter, which then chooses a suitable MCS from a "codeset" to maximize throughput at that SINR.	ETSI TR 136 942 V9.3.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Frequency (RF) system scenarios"
authentication management field	AMF	N/A	A 16-bit field used authentication management. The use and format are unspecified in the architecture but examples are given in 3GPP TS 33.103.	ETSI TS 133 103 V4.2.0: "3G Security; Integration Guidelines"
access and mobility management function	AMF	N/A	Access and mobility management function (AMF) includes the following functionalities: mobility management, connection management, lawful intercept, transparent proxy, access authentication and authorization.	ETSI TR 126 919 V16.2.0: "5G; Study on media handling aspects of conversational services in 5G systems"

Term	Abbreviation	Synonym	Definition	Reference
alternate mark inversion	AMI	N/A	AMI is a code where ONEs are represented by alternate positive and negative pulses, and ZEROs by spaces.	ETSI EN 300 011-1 V1.2.2: "Integrated Services Digital Network (ISDN); Primary rate User Network Interface (UNI); Part 1: Layer 1 specification"

Term	Abbreviation	Synonym	Definition	Reference
additional maximum power reduction	A-MPR	N/A	3GPP specifications impose constraints on the indicators related to UE transmit power, including the maximum output power (MPR), and (A-MPR). A-MPR is an additional reduction in the UE maximum output power to meet the stricter requirements for spectral radiation (such as spurious emission) imposed for different frequency bands in different regions. In NR, an A-MPR is indicated via network signaling (NS). When accessing the network, a UE is notified of specific RF requirements in the service setup phase and then reduces power according to the received control signaling. The actual reduction in the UE maximum output power is equal to the larger of either MPR or A-MPR.	3GPP TS 36.521-1: "Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification Radio transmission and reception Part 1: Conformance Testing;"

Term	Abbreviation	Synonym	Definition	Reference
adaptive multi rate codec	AMR	N/A	The Adaptive Multi-Rate (AMR, AMR-NB or GSM-AMR) audio codec is an audio compression format optimized for speech coding.	3GPP TS 26.231: "Cellular text telephone modem; Minimum performance requirements"
adaptive multi-rate	AMR	N/A	The AMR speech coder consists of the multi-rate speech coder, a source controlled rate scheme including a voice activity detector and a comfort noise generation system, and an error concealment mechanism to combat the effects of transmission errors and lost packets. The multi-rate speech coder is a single integrated speech codec with eight source rates from 4.75 kbit/s to 12.2 kbit/s, and a low rate background noise encoding mode. The speech coder is capable of switching its bit-rate every 20 ms speech frame upon command.	3GPP TS 26.071: "Mandatory speech CODEC speech processing functions; AMR speech CODEC; General description"
adaptive multi-rate control	AMRC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
adaptive multi-rate wideband	AMR-WB	adaptive multirate wideband	Adaptive multi-rate wideband (AMR-WB) is a patented wideband speech audio coding standard developed based on adaptive multi-rate encoding, using similar methodology as algebraic code-excited linear prediction (ACELP). AMR-WB provides improved speech quality due to a wider speech bandwidth of 50–7000 Hz compared to narrowband speech coders which in general are optimized for POTS wireline quality of 300–3400 Hz.	Wikipedia
access network	AN	N/A	An access network comprising an RAN and/or non-3GPP AN connecting to a core network.	3GPP TS 23.501: "Technical Specification Group Services and System Aspects; System architecture for the 5G System (5GS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
access network bitrate recommendation	ANBR	N/A	The access network sends an access network bitrate recommendation (ANBR) message to a UE to recommend a proper bit rate to the UE to cope with the change in the air interface rate.	3GPP TS 26.114 V14.12.0: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction"
access network bitrate recommendation query	ANBRQ	N/A	A UE sends an access network bitrate recommendation query (ANBRQ) message to the access network to query the recommended bit rate.	3GPP TS 26.114 V14.12.0: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction"
automatic noise restraint	ANR	N/A	Processes the uplink speech signals after decoding and filters the background noise to improve the SNR and speech intelligibility. In this way, the other party of the call can clearly hear the voice.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
automatic neighbor relation	ANR	N/A	Automatic Neighbor Relation (ANR) can automatically maintain intra-RAT and inter-RAT neighbor relationships, reducing costs on network planning and optimization and improving network optimization efficiency and user experience.	Huawei Term
American National Standards Institute	ANSI	N/A	The American National Standards Institute (ANSI) is a private non-profit organization that oversees the development of voluntary consensus standards for products, services, processes, systems, and personnel in the United States. The organization also coordinates U.S. standards with international standards so that American products can be used worldwide.	Wikipedia
automatic power control	APC	N/A	Automatic power control (APC) may be used to regulate the output optical power or pump power level.	ITU-T G.977: "Characteristics of optically amplified optical fibre submarine cable system"

Term	Abbreviation	Synonym	Definition	Reference
application protocol data unit	APDU	N/A	A sequence of data elements exchanged between peer application layer entities, e.g. DSE APDUs and ROSE APDUs.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
application programming interface	API	N/A	A boundary across which a software application uses facilities of programming languages to invoke software services. These facilities may include procedures or operations, shared data objects and resolution of identifiers.	ITU-T T.174: "Application Programming Interface (API) for MHEG-1"

Term	Abbreviation	Synonym	Definition	Reference
advanced power module	APM	N/A	A standalone cabinet. It is integrated with an internal rectifier module, monitoring module, power distribution unit, surge protection unit, temperature control unit, and storage battery group consisting of 12 V storage batteries. The interior of the cabinet has a 4U to 5U space for the installation of a 19-inch user device complying with the ETSI standard. The APM provides functions such as DC power supply, storage battery management, monitoring and communication for power supply system, power distribution, surge protection, temperature control, backup power supply, user device installation, and AC maintenance power interface.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
access point name	APN	N/A	Used to identify a specific IP network and a point of interconnection to that network.	ETSI TS 102 250-1 V2.3.1: "Speech and multimedia Transmission Quality (STQ); QoS aspects for popular services in mobile networks; Part 1: Assessment of Quality of Service"
automatic protection switch	APS	N/A	Automatic protection switch (APS) channel is used to carry information between the two ends of a linear protection group to coordinate the head-end bridge with the tail-end selector for 1:n protection, and to coordinate the selectors in both directions in the case of bidirectional protection.	ITU-T G.808: "Terms and definitions for network protection and restoration"
active queue management	AQM	N/A	A technique for an Internet router that consists in dropping or marking packets before its queue is full	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
absolute radio frequency channel number	ARFCN	- absolute radio frequency channel number - absolute radio-frequency channel number	Within the spectrum allocated for cellular mobile communications, radio channels are identified by ARFCNs. If the system is operating in frequency division duplex (FDD) mode, then the channel number is associated with both the uplink and downlink radio channels.	Wikipedia
allocation and retention priority	ARP	N/A	The allocation and retention priority indicates the allocation, retention and priority of the service data flow. The ARP contains information about the priority level, the pre-emption capability and the pre-emption vulnerability. The allocation and retention priority resolves conflicts of demands for network resources.	3GPP TS 23.203: "Technical Specification Group Services and System Aspects; Policy and charging control architecture"

Term	Abbreviation	Synonym	Definition	Reference
Address Resolution Protocol	ARP	N/A	Protocol defined in RFC 826 that is used to associate network protocol addresses to 48 bit Ethernet addresses for transmission on Ethernet hardware	ETSI TS 102 460: "Satellite Earth Stations and Systems (SES); Broadband Satellite Multimedia (BSM); Address Management at the SI-SAP"
average revenue per user	ARPU	N/A	N/A	3GPP TR 38.913 version 16.0.0: "5G; Study on scenarios and requirements for next generation access technologies"
automatic repeat request	ARQ	N/A	An error-control method for data transmission. If the receiver detects errors in a packet from the sender or the sender does not receive an acknowledgment from the receiver within a specified period, the sender retransmits the packet until it receives an acknowledgment or a predefined number of retransmissions is reached.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
access stratum	AS	N/A	Functional grouping consisting of the parts in the infrastructure and in the user equipment and the protocols between these parts being specific to the access technique (i.e. the way the specific physical media between the user equipment and the infrastructure is used to carry information).	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
autonomous system boundary router	ASBR	N/A	An autonomous system boundary router is a router that is connected by using more than one routing protocol and that exchanges routing information with routers autonomous systems. ASBRs typically also run an exterior routing protocol (e.g., BGP), or use static routes, or both. An ASBR is used to distribute routes received from other external ASs throughout its own autonomous system. An ASBR creates External LSAs for external addresses and floods them to all areas via ABR. Routers in other areas use ABRs as next hops to access external addresses. Then ABRs forward packets to the ASBR that announces the external addresses.	Wikipedia
access service class	ASC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
American Standard Code for Information Interchange	ASCII	N/A	ASCII is a character encoding standard for electronic communication. ASCII codes represent text in computers, telecommunications equipment, and other devices. Most modern character-encoding schemes are based on ASCII, although they support many additional characters.	Wikipedia
amplitude-shift keying	ASK	N/A	Amplitude-shift keying (ASK) is a form of amplitude modulation that represents digital data as variations in the amplitude of a carrier wave. In an ASK system, a symbol, representing one or more bits, is sent by transmitting a fixed-amplitude carrier wave at a fixed frequency for a specific time duration. For example, if each symbol represents a single bit, then the carrier signal will be transmitted when the input value is 1, but will not be transmitted when the input value is 0.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
access security management entity	ASME	N/A	Entity which receives the top-level keys in an access network from the HSS. For E-UTRAN access networks, the role of the ASME is assumed by the MME.	3GPP TS 133 401 V10.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; 3GPP System Architecture Evolution (SAE); Security architecture (3GPP TS 33.401 version 10.0.0 Release 10)"
access network SDH transmission unit	ASU	N/A	N/A	Huawei Term
asynchronous transfer mode	ATM	N/A	A transfer mode in which the information is organized into cells. It is asynchronous in the sense that the recurrence of cells containing information from an individual user is not necessarily periodic.	TM TR 101 689-1 V1.1.1: "Transmission and Multiplexing (TM); Terms and definitions in transport networks; Part 1: Core networks"
automatic transmit power control	ATPC	N/A	A method of adjusting the transmit power based on the fading of the transmitted signals detected at the receiver.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
adaptive time recovery	ATR	N/A	Adaptive time recovery (ATR) is a PTP-based technology that allows base station to establish clock links and implement time synchronization over a third-party network using PTP packets in Layer 3 unicast mode.	Huawei Term
authentication server function	AUSF	N/A	N/A	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2 (Release 16)"
authentication response	AUTHR	N/A	An 18-bit output of the authentication algorithm. It is used to validate mobile station registrations, originations and terminations.	Huawei Term
authentication token	AUTN	N/A	Information conveyed during a strong authentication exchange, which can be used to authenticate its sender.	ITU-T X.509: "Information technology – Open systems interconnection – The Directory: Public-key and attribute certificate frameworks"

Term	Abbreviation	Synonym	Definition	Reference
Additive White Gaussian Noise	AWGN	N/A	A noise in communications characterized by a constant power spectral density (feature of white noise) and a Gaussian distribution of amplitude. It is additive because it can be added to a signal.	Wikipedia
Advanced Wireless Services	AWS	N/A	Advanced Wireless Services (AWS) is a wireless telecommunications spectrum band used for mobile voice and data services, video, and messaging. AWS is used in the United States, Argentina, Canada, Colombia, Mexico, Chile, Paraguay, Peru, Ecuador, Trinidad and Tobago, Uruguay and Venezuela. It replaces some of the spectrum formerly allocated to Multipoint Multichannel Distribution Service (MMDS), sometimes referred to as Wireless Cable, that existed from 2150 to 2162 MHz.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
A interface	N/A	N/A	Logical interface between a BSC and an MSC	ETSI EN 301 489-8: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 8: Specific conditions for GSM base stations"

Term	Abbreviation	Synonym	Definition	Reference
Abis	N/A	N/A	The Abis interface is defined between a base station controller (BSC) and a base transceiver station (BTS) for their remote communication in the base station subsystem (BSS). This interface supports all services offered to users. It also facilitates control of the radio equipment and allocation of radio frequencies in the BTS. The rate of the physical link of the Abis interface is 2 Mbit/s. The LAPD protocol is used for transmission at the data link layer, and the interface is connected to LAPDm of the Um interface. The rate over the Abis interface reaches 16 kbit/s, and it works in 4 x 16 kbit/s multiplexing mode when mapped on an E1 link. Its signal pattern adopts an open interconnection structure, with the first-, second-, and third-layer protocols meeting	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			the requirements of GSM Recommendation s 08.54, 08.56, and 08.58, respectively. The Abis interface is a proprietary interface, whose BTS and BSC protocols are subject to equipment vendors.	
Abis interface	N/A	N/A	Logical interface between a BTS and a BSC	ETSI EN 301 489-50: "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 50: Specific conditions for Cellular Communication Base Station (BS), repeater and ancillary equipment; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU"

Term	Abbreviation	Synonym	Definition	Reference
Abis MUX	N/A	N/A	A multiplexing technique that improves transmission efficiency. In Abis MUX, the transmitting end (BSC or BTS) multiplexes multiple supported UDP or IP packets into one UDP or IP packet so that they share one header. The receiving end (BTS or BSC) demultiplexes the UDP or IP packet to obtain the original UDP or IP packets.	Huawei Term
AC power supply	N/A	AC power source	The supply of electric power by alternating current.	Huawei Term
account	N/A	N/A	Structure residing in the OCS for holding dynamic subscriber data with monetary equivalence. Accounts may have a currency or a unit type. As opposed to bank accounts, transaction history is not necessarily kept in the OCS account data structure.	3GPP TS 32.296: "Telecommunication management; Charging management; Online Charging System (OCS): Applications and interfaces"

Term	Abbreviation	Synonym	Definition	Reference
active mode	N/A	N/A	A working mode of EFM OAM. The discovery and remote loopback can only be initiated by the interface in active mode.	Huawei Term
active/standby backup	N/A	N/A	A backup mechanism in which two systems with the same functions are deployed to improve the reliability.	Huawei Term
active/standby switchover	N/A	N/A	A troubleshooting technology. When an active device becomes faulty, services and control functions are automatically switched over to the standby device to ensure the normal running of the services and functions.	Huawei Term
adjacent-channel interference	N/A	N/A	Interference caused by coupling from a signal in an adjacent channel.	ETSI TR 102 580: "Terrestrial Trunked Radio (TETRA); Release 2; Designer's Guide; TETRA High-Speed Data (HSD); TETRA Enhanced Data Service (TEDS)"
aging time	N/A	N/A	The time to live before an object becomes invalid.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
air interface	N/A	N/A	Conductor-free medium, usually air, between a transmitter and the receiver through which communication, e.g. data and telemetry, is achieved by means of a modulated inductive or propagated electromagnetic field.	ETSI TR 187 020: "Radio Frequency Identification (RFID); Coordinated ESO response to Phase 1 of EU Mandate M436"
air interface load	N/A	N/A	The air interface load of a cell is defined as N/C , where N denotes the number of UEs in the cell and C denotes the air interface capability of the cell.	Huawei Term
alarm	N/A	N/A	An alarm is reported to the element management system (EMS) when a device incurs a fault or an exception that needs to be rectified manually or using automation devices. An alarm has two states: generated and cleared. If an alarm is generated, it must be cleared.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
alarm board	N/A	N/A	A pane that displays on the Network Management System (NMS) UMS client. It displays the statistics of current UMS alarms in different colors. By watching the alarm board, you can monitor the entire network in real-time and know the severity of an alarm and its related statistics.	Huawei Term
alarm filtering	N/A	N/A	An alarm management method. Alarms are detected and reported to the NMS, and whether the alarm information is displayed and saved is decided by the alarm filtering status. An alarm with the filtering status set to "Filter" is not displayed and saved on the NMS, but is monitored on the NE.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
alarm indication signal	N/A	N/A	A code sent downstream in a digital network as an indication that an upstream failure has been detected and alarmed. It is associated with multiple transport layers.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks"
alarm masking	N/A	N/A	A method to mask alarms for the alarm management purpose. Alarms that are masked are not displayed on the NMS or the NMS does not monitor unimportant alarms.	Huawei Term
alarm suppression	N/A	N/A	A method to suppress alarms for the alarm management purpose. Alarms that are suppressed are no longer reported from NEs.	Huawei Term
AMF region	N/A	N/A	An AMF region consists of one or multiple AMF sets.	3GPP TS 23.501: "Technical Specification Group Services and System Aspects; System architecture for the 5G System (5GS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
AMF set	N/A	N/A	An AMF set consists of some AMFs that serve a given area and network slice(s). AMF set is unique within an AMF region and it comprises of AMFs that support the same network slice(s). Multiple AMF sets may be defined per AMF region.	3GPP TS 23.501: "Technical Specification Group Services and System Aspects; System architecture for the 5G System (5GS); Stage 2"
analogue signal	N/A	N/A	A signal one of whose characteristic quantities follows continuously the variations of another physical quantity.	ITU-T I.112: "VOCABULARY OF TERMS FOR ISDNs"
angle measurement	N/A	N/A	Angle measurement is performed by the receive end. It uses a processing system formed by multi-sensor antenna arrays to analyze the uplink angle-of-arrival (UL-AoA) and downlink angle-of-departure (DL-AoD) of a spatial signal and estimate space-domain parameters of the signal, thereby obtaining the UE location.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
anonymization	N/A	N/A	Process that replaces an actual identifier with an attribute obtained by randomization or generalization in such a way that there is a reasonable level of confidence that no individual can be identified.	ETSI TR 103 304: "CYBER; Personally Identifiable Information (PII) Protection in mobile and cloud services"
answer	N/A	N/A	A process in which the call center platform connects a call that is distributed to an agent. Answer includes automatic answer and manual answer. Automatic answer means that the call center platform automatically connects a call. Manual answer means that a login agent clicks the answer button to connect a call.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
answer signal	N/A	N/A	An indication that a terminal is answering an incoming call.	ETSI TS 102 971 V1.1.1: "Access and Terminals (AT); Public Switched Telephone Network (PSTN); Harmonized specification of physical and electrical characteristics of a 2-wire analogue interface for short line interface"
antenna	N/A	N/A	Device that serves as a transducer between a guided wave (e.g. coaxial cable) and a free space wave, or vice versa.	ETSI TR 102 457: "Fixed Radio Systems; Evaluation of the ElectroMagnetic Field (EMF) radiated by Line-of-Sight (LoS) fixed radio stations using parabolic dish directional antennas"

Term	Abbreviation	Synonym	Definition	Reference
antenna feed	N/A	antenna feed system	The antenna feed system or antenna feed is the cable or conductor, and other associated equipment, which connects the transmitter or receiver with the antenna and makes the two devices compatible.	Wikipedia
antenna gain	N/A	N/A	In a transmitting antenna, the gain describes how well the antenna converts input power into radio waves headed in a specified direction. In a receiving antenna, the gain describes how well the antenna converts radio waves arriving from a specified direction into electrical power. When no direction is specified, gain is understood to refer to the peak value of the gain, the gain in the direction of the antenna's main lobe.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
antenna port	N/A	N/A	Port for connection of an antenna used for intentional transmission and/or reception of radiated RF energy.	ETSI EN 300 386: "Telecommunication network equipment; Harmonised Standard for ElectroMagnetic Compatibility (EMC) requirements"
antenna port*	N/A	N/A	An antenna port is defined such that the channel over which a symbol on the antenna port is conveyed can be inferred from the channel over which another symbol on the same antenna port is conveyed.	3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"
antenna switching	N/A	antenna selection	Antenna switching enables a UE to transmit SRSs on multiple antennas in turn to accurately estimate channel information.	• Huawei Term • 3GPP TS 38.214: "Physical layer procedures for data (Release 17)"

Term	Abbreviation	Synonym	Definition	Reference
ARP attack	N/A	N/A	In an ARP attack, an attacker exploits the vulnerabilities of the ARP to forge data to update the dynamic ARP table of the target host. As a result, hosts on the LAN cannot access the Internet, or sensitive information is stolen through spoofing, causing network breakdown or data leakage.	Huawei Term
array gain	N/A	N/A	In communication systems, array gain means a power gain of transmitted or received signals that is achieved by using multiple antennas or antenna elements at a transmitter or receiver, with respect to a single antenna or antenna element case.	Wikipedia
Assignment Failure	N/A	N/A	A message indicating that the channel assignment fails.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Ater	N/A	N/A	Applies to a GSM network where either the GSM Abis or Ater interfaces are used, depending on the location of the transcoder and rate adapter units.	3GPP TS 28.062 version 9.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Inband Tandem Free Operation (TFO) of speech codecs; Service description; Stage 3"
Ater connection path	N/A	N/A	The transmission path between the GMPS/GEPS and the GTCS. It is used to transmit traffic data and signaling.	Huawei Term
attenuation	N/A	N/A	Reduction in intensity of the light beam (or signal).	ETSI GR QKD 007: "Quantum Key Distribution (QKD); Vocabulary"
attenuator	N/A	N/A	An electronic device that reduces the amplitude of an electronic signal.	Wikipedia

1.3 B

Term	Abbreviation	Synonym	Definition	Reference
Backhaul Adaptation Protocol	BAP	N/A	The Backhaul Adaptation Protocol (BAP) is used for data packet routing and bearer mapping on an integrated access and backhaul (IAB) network.	• Huawei Term • 3GPP TS 38.340: "Technical Specification Group Radio Access Network; NR; Backhaul Adaptation Protocol (BAP) specification"
baseband	BB	N/A	Transmission means through which digital signals are sent without frequency shifting. In general, only one communication channel is available at any given time.	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
battery backup cabinet	BBC	N/A	A cabinet that contains a built-in battery group to back up -48 V DC power and to supply power to the base station when there is no power input. It is a component of a base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
background block error	BBE	N/A	An errored block not occurring as part of an SES.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "
baseband processing unit	BBP	baseband unit	A unit that provides CPRI ports for communication with RF modules, processes uplink and downlink baseband signals, and supports the multiplex of baseband resources among different modes, thereby implementing multimode concurrency.	Huawei Term
baseband unit	BBU	N/A	Mobile access network equipment that processes baseband signal, connected to one or more RF modules through optical fiber or metallic cabling, or by microwave links.	ETSI TS 105 200-2-3: "Access, Terminals, Transmission and Multiplexing (ATTM); Energy management; Operational infrastructures; Implementation of Global KPIs; Part 2: Specific requirements; Sub-part 3: Mobile broadband access networks"

Term	Abbreviation	Synonym	Definition	Reference
boundary clock	BC	N/A	Under both IEEE 1588-2008 and IEEE 802.1AS, a PTP clock can be designated as an ordinary clock (OC), boundary clock (BC) or transparent clock (TC), though 802.1AS transparent clocks also have some boundary clock capabilities. A device may implement one or more of these capabilities. OC may have as few as one port (network connection), while TC and BC must have two or more ports. BC and OC ports can work as a master (grandmaster) or a slave. An IEEE 1588 profile is associated with each port. TC can belong to multiple clock domains and profiles.	Wikipedia
base station color code	BCC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
broadcast control channel	BCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
binary coded decimal	BCD	N/A	Binary coded decimal (BCD) is a class of binary encodings of decimal numbers where each digit is represented by a number of bits.	Wikipedia
base station control function	BCF	N/A	The BCF provides an operations and maintenance (O&M) connection to the network management system (NMS), and manages operational states of each TRX, as well as software handling and alarm collection.	Wikipedia
broadcast channel	BCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
bandwidth combination set	BCS	N/A	N/A	3GPP TS 38.521-3: "NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios"
backward defect indication	BDI	N/A	A packet that the sink node of an LSP sends, when detecting a defect, to inform the source node of the LSP of the defect through the return path.	Huawei Term
BeiDou Navigation Satellite System	BDS	N/A	BeiDou Navigation Satellite System (BDS) is a satellite navigation system that provides global users with all-time, all-weather and high-accuracy positioning, navigation and timing services. The system has undergone three generations and has been officially called BDS since its second generation.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
bit error rate	BER	N/A	Percentage of bits that have errors relative to the total number of bits received in a transmission, usually expressed as ten to a negative power.	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"

Term	Abbreviation	Synonym	Definition	Reference
basic encoding rule	BER	N/A	The basic encoding rules were the original rules laid out by the ASN.1 standard for encoding abstract information into a concrete data stream. The rules, collectively referred to as a transfer syntax in ASN.1 parlance, specify the exact octet sequences which are used to encode a given data item. The syntax defines such elements as: the representations for basic data types, the structure of length information, and the means for defining complex or compound types based on more primitive types. The BER syntax, along with two subsets of BER (the canonical encoding rules and the distinguished encoding rules), are defined by the ITU-T's X.690 standards document, which is part of the ASN.1 document series.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
BTS E1 surge protector	BESP	N/A	The E1 surge protector is a board of the BTS and is used to connect the BTS to the BSC6900. The name of the E1 surge protector varies with the BTS type: For the BTS3012, BTS3012AE, BTS3006C, and BTS3002E, the E1 surge protector is the DELU. For the BTS3036, BTS3036A, DBS3036, BTS3900 GSM, and DBS3900 GSM, the E1 surge protection board is the UELP.	Huawei Term
beamforming	BF	N/A	Beamforming, a key technology of multiple-input multiple-output (MIMO), is a process of adjusting the amplitudes or phases of signals on radio frequency (RF) links and using strong correlation of spatial channels and wave interference to form beams with strong directional electromagnetic radiation.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Bidirectional Forwarding Detection	BFD	N/A	Bidirectional Forwarding Detection (BFD) is a network protocol that is used to detect faults between two forwarding engines connected by a link. It provides low-overhead detection of faults even on physical media that does not support failure detection of any kind, such as Ethernet, virtual circuits, tunnels and MPLS Label Switched Paths.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
baseband frequency hopping	BFH	N/A	In baseband frequency hopping, the carrier frequency assigned for the transmitter of the TRX does not participate in frequency hopping and remains unchanged. The transmit frequency hopping is achieved with the switching of baseband signals among different TRXs. The receiver of the TRX, however, must participate in frequency hopping. The carrier frequency assigned for the receiver changes with the carrier frequency used by an MS. The number of carrier frequencies assigned for frequency hopping in a cell cannot exceed the number of TRXs assigned for the cell.	Huawei Term
bad frame indication	BFI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
beam failure recovery	BFR	N/A	When the serving beam of the UE is blocked, the new optimal beam measured by the UE may not be reported. As a result, the traffic decreases to zero and even service drops may occur. Beam failure recovery (BFR) enables the UE to quickly obtain another available serving beam in the preceding scenario, enhances beam robustness, and prevents the traffic from dropping to zero due to beam blocking.	Huawei Term
Border Gateway Protocol	BGP	N/A	Border Gateway Protocol (BGP) is a standardized exterior gateway protocol designed to exchange routing and reachability information among autonomous systems (AS) on the Internet. BGP is classified as a path-vector routing protocol, and it makes routing decisions based on paths, network policies, or rule-sets configured by a network administrator.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
busy hour call attempts	BHCA	N/A	N/A	ETSI TS 101 377-1-1: "GEO-Mobile Radio Interface Specifications; Part 1: General specifications; Sub-part 1: Abbreviations and Acronyms; GMR-2 01.004"
busy hour session attempts	BHSA	N/A	The number of call attempts completed in the busiest hour. It is used to measure the processing performance of the system that uses the SIP protocol, such as the IMS.	Huawei Term
Basic Input/Output System	BIOS	• System BIOS • ROM BIOS • BIOS ROM • PC BIOS	In computing, BIOS is firmware used to perform hardware initialization during the booting process (power-on startup), and to provide runtime services for operating systems and programs.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
bit interleaved parity-X	BIP-X	N/A	BIP-X code is defined as a method of error monitoring. With even parity, an X-bit code is generated by the transmitting equipment over a specified portion of the signal in such a manner that the first bit of the code provides even parity over the first bit of all X-bit sequences in the covered portion of the signal, the second bit provides even parity over the second bit of all X-bit sequences within the specified portion, etc. Even parity is generated by setting the BIP-X bits so that there is an even number of 1s in each monitored partition of the signal. A monitored partition comprises all bits that are in the same bit position within the X-bit sequences in the covered portion of the signal. The covered portion includes the BIP-X.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks"

Term	Abbreviation	Synonym	Definition	Reference
broadband integrated services digital network	B-ISDN	N/A	In the 1980s, the telecommunications industry expected that digital services would follow much the same pattern as voice services did on the public switched telephone network, and conceived an end-to-end circuit switched service, known as broadband integrated services digital network (B-ISDN).	Wikipedia
building integrated timing supply	BITS	N/A	A standard for distributing a precision clock among telecommunications equipment.	Wikipedia
base station interface unit	BIU	N/A	N/A	Huawei Term
block error rate	BLER	N/A	The ratio of the number of blocks incorrectly received to the total number of blocks sent.	IEV 371-08-03
Broadcast /Multicast Control	BMC	N/A	In the UMTS system, this protocol adapts broadcast and multicast services on the radio interface.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
broadcast /multicast service center	BM-SC	N/A	N/A	3GPP TR 26.981 version 16.0.0 Release 16: "LTE;MBMS Extensions for Provisioning and Content Ingestion"
Bootstrap Protocol	BOOTP	N/A	This RFC describes an IP/UDP Bootstrap Protocol (BOOTP) which allows a diskless client machine to discover its own IP address, the address of a server host, and the name of a file to be loaded into memory and executed.	Bill Croft (Stanford University), and John Gilmore (Sun Microsystems), "BOOTSTRAP PROTOCOL (BOOTP)", RFC 951, September 1985
board protection switching	BPS	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
binary phase shift keying	BPSK	N/A	Form of digital modulation in which two phases separated by 180 degrees support the transmission of one bit per symbol.	ETSI TS 103 311-2 V1.1.1: "Integrated broadband cable telecommunication networks (CABLE); Fourth Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS® 3.1"
backward reporting	BR	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
broadband remote access server	BRAS	N/A	A new type of access gateway for broadband networks. As a bridge between backbone networks and broadband access networks, BRAS provides methods for fundamental access and manages the broadband access network. It is deployed at the edge of network to provide broadband access services, convergence, and forwarding of multiple services, meeting the demands for transmission capacity and bandwidth utilization of different users. BRAS is a core device for the broadband users' access to a broadband network.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
base station	BS	- base transceiver station - BTS	A base station is a network element in radio access network responsible for radio transmission and reception in one or more cells to or from the user equipment. A base station can have an integrated antenna or be connected to an antenna by feeder cables.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
base station controller	BSC	N/A	This equipment in the BSS is in charge of controlling the use and the integrity of the radio resources.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
base station identity code	BSIC	base transceiver station identity code	The base station identity code is a local colour code that allows a MS to distinguish between different neighbouring base stations.	3GPP TS 03.03: "Numbering, Addressing and Identification"
backward sequence number	BSN	N/A	The BSN is used to acknowledge the receipt of signal units by the remote signaling point.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
buffer status report	BSR	N/A	The Buffer Status reporting (BSR) procedure is used to provide the serving base station with information about UL data volume in the MAC entity.	3GPP TS 38.321 version 16.6.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Medium Access Control (MAC) protocol specification (Release 16)"
base station subsystem	BSS	N/A	Either a full network or only the access part of a GERAN offering the allocation, release and management of specific radio resources to establish means of connection between an MS and the GERAN. A Base Station Subsystem is responsible for the resources and transmission/reception in a set of cells.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
base station subsystem GPRS protocol	BSSGP	N/A	BSSGP is a protocol used in the GPRS mobile packet data system. It denotes Base Station System GPRS Protocol. It transfers information between two GPRS entities SGSN and BSS over a BSSGP Virtual Connection (BVC). This protocol provides radio-related quality of service and routing information that is required to transmit user data between a BSS and an SGSN. It does not carry out any form of error correction.	Wikipedia
Base Station Subsystem Management Application Part	BSSMAP	N/A	This is the process within the BSS that controls radio resources in response to instructions from the MSC.	3GPP TS 48.008: "Mobile Switching Centre - Base Station system (MSC-BSS) interface; Layer 3 specification"

Term	Abbreviation	Synonym	Definition	Reference
bias tee	BT	N/A	A bias tee is a three-port network used for setting the DC bias point of some electronic components without disturbing other components. The bias tee is a diplexer. The low-frequency port is used to set the bias; the high-frequency port passes the radio-frequency signals but blocks the biasing levels; the combined port connects to a device, which sees both the bias and RF. It is called a tee because the 3 ports are often arranged in the shape of a T.	Wikipedia
BitTorrent	BT	N/A	BitTorrent (BT) is a communication protocol for peer-to-peer (P2P) file sharing, which enables users to distribute data and electronic files over the Internet in a decentralized manner.	Wikipedia
base transceiver station	BTS	N/A	N/A	Antenna Interface Standards Group Base Standard AISG v3.0

Term	Abbreviation	Synonym	Definition	Reference
BSSGP virtual connection	BVC	N/A	BSSGP virtual connection (BVC): end-to-end virtual communication path between remote network service user entities.	3GPP TS 48.016: "General Packet Radio Service (GPRS); Base Station System (BSS) -Serving GPRS Support Node (SGSN) interface; Network Service"
bandwidth part	BWP	N/A	From a UE perspective, the UE is configured with one or more BWP/carriers, each with its own UE channel bandwidth. The UE does not need to be aware of the base station channel bandwidth or how the base station allocates bandwidth to different UEs.	ETSI TS 138 101-2 V16.7.0: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone"

Term	Abbreviation	Synonym	Definition	Reference
B interface	N/A	N/A	An interface between the mobile switching center (MSC) and the visitor location register (VLR). During a call connection, the MSC queries the VLR for location and service information about the roaming subscriber. During a location update, periodic registration, or power-on registration, the MSC sends location information and status of the roaming subscriber to the VLR. When a subscriber activates a supplementary service or modifies data, the MSC sends data changes to the VLR and updates the subscriber information in the VLR. Such exchanges are performed over the B interface. Generally, the MSC is integrated with the VLR, and the B interface is internal to the MSC.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
back pressure	N/A	backpressure	A traffic control method. When detecting that the transmit end transmits a large volume of traffic, the receive end sends signals to ask the transmit end to lower the transmission rate.	Huawei Term
backplane	N/A	N/A	A backplane (or "backplane system") is a group of electrical connectors in parallel with each other, so that each pin of each connector is linked to the same relative pin of all the other connectors, forming a computer bus. It is used as a backbone to connect several printed circuit boards together to make up a complete computer system. Backplanes commonly use a printed circuit board, but wire-wrapped backplanes have also been used in minicomputers and high-reliability applications.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
base station modulation model	N/A	N/A	Base station modulation model refers to the main process of modulating baseband signals into RF signals in a base station.	Huawei Term
basic cabinet	N/A	N/A	A combined cabinet that provides transmission interfaces and O&M information for all the combined cabinets.	Huawei Term
basic cabinet group	N/A	N/A	A cabinet group that provides synchronization clock signals and O&M information for all the cabinet groups.	Huawei Term
basic service	N/A	N/A	Services that can be provided using basic communications network resources, including basic bearer services or teleservice.	ETSI EN 300 207-1: "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
beam sweeping	N/A	N/A	Operation of covering a spatial area, with beams transmitted and/or received during a time interval in a predetermined way.	3GPP TS 38.804: "Study on new radio access technology Radio interface protocol aspects"
bearer	N/A	N/A	An information transmission path of defined capacity, delay and bit error rate, etc.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
bearer network	N/A	N/A	Network used to carry the messages of a transport-layer protocol between physical devices.	ETSI TR 102 469: "Digital Video Broadcasting (DVB); IP Datacast over DVB-H: Architecture"
Bi-Carrier cell group	N/A	N/A	Two cells using a shared bandwidth form a Bi-Carrier cell group.	Huawei Term
bit error	N/A	N/A	An incompatibility between a bit in a transmitted digital signal and the corresponding bit in the received digital signal.	IEV 704-18-02

Term	Abbreviation	Synonym	Definition	Reference
blacklist	N/A	N/A	List of identities or identity ranges that, for one reason or another, are being denied a particular service.	3GPP TS 22.173: "IP Multimedia Core Network Subsystem (IMS) Multimedia Telephony Service and supplementary services; Stage 1"
BladeAAU	N/A	N/A	RF module that integrates the functions of massive MIMO AAUs and passive antennas. This RF module does not need as much installation space as other modules and can be mounted at a greater height to expand the network coverage.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Blade RRU	N/A	N/A	RRU with a blade appearance. Blade RRUs outperform traditional RRUs in various aspects. For example, blade RRUs have excellent RF performance (which can support multi-band, multi-RAT, and multi-carrier operation) and support multi-RRU combined installation. In addition, their maintenance cavity structure, antenna ports, and monitoring ports are improved for simple installation and fast site construction and capacity expansion.	Huawei Term
blind handover	N/A	N/A	In blind handover, target cells are not measured and their signal quality is unknown.	Huawei Term
Book RRU	N/A	N/A	Book-like RRU that can use internal or external antennas. It is small and lightweight, and can be flexibly deployed to fill coverage holes in urban areas.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
boolean	N/A	N/A	Value which resolves to either a logical 1 or 0.	ETSI TS 102 114: "DTS Coherent Acoustics; Core and Extensions with Additional Profiles"
bridge	N/A	N/A	A gateway for traffic flowing at OSIRM Layer 2 between two networks (usually two LANs).	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
bridge protocol data unit	N/A	N/A	Bridge Protocol Data Units (BPDUs) are frames that contain information about the spanning tree protocol (STP). A switch sends BPDUs using a unique source MAC address from its origin port to a multicast address with destination MAC.	Wikipedia
broadcast	N/A	N/A	A value of the service attribute "communication configuration", which denotes unidirectional distribution to all users.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
broadcast address	N/A	N/A	A broadcast address is a network address used to transmit to all devices connected to a multiple-access communications network. A message sent to a broadcast address may be received by all network-attached hosts.	Wikipedia
broadcast domain	N/A	N/A	A broadcast domain is a logical division of a computer network, in which all nodes can reach each other by broadcast at the data link layer. A broadcast domain can be within the same LAN segment or it can be bridged to other LAN segments.	Wikipedia
broadcast storm	N/A	N/A	An incorrect packet broadcast onto a network that causes multiple hosts to respond all at once, typically with equally incorrect packets which causes the storm to grow exponentially in severity.	G. Malkin, "Internet Users' Glossary", RFC1983, August 1996

Term	Abbreviation	Synonym	Definition	Reference
BSC local switching	N/A	N/A	BSC local switching is triggered when the BSC detects that the calling and called mobile station (MSs) of a call are under the same BSC. When BSC local switching is triggered, the speech signals are looped back on the BSC side. In addition, the signaling link on the MSC side is reserved, and the transmission resources on the Ater interface and the TC resources are released.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
BTS local switching	N/A	N/A	BTS local switching is triggered when the BSC detects that the calling and called MSs of a call are under the same BTS, in the same BTS group, or in the same local switching area. When BTS local switching is triggered, the speech signals are looped back on the BTS side, in the BTS group, or in the local switching area. In addition, the signaling link on the MSC side is reserved, and the transmission resources on the Ater interface, the transmission resources on the Abis interface, and the TC resources are released.	Huawei Term
BTS ring topology	N/A	N/A	The BS ring network is connected to the BSC for improving the reliability of the network. For details about the BS ring network.	Huawei Term
busbar	N/A	N/A	Low-impedance conductor to which several electric circuits can be connected at separate points.	IEV 151-12-30

1.4 C

Term	Abbreviation	Synonym	Definition	Reference
carrier aggregation	CA	N/A	Aggregation of two or more component carriers in order to support wider transmission bandwidths.	3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception"
carrier aggregation	CA	N/A	CA aggregates multiple dispersed channels to provide a larger logical bandwidth, catering for large-capacity microwave transmission. CA that aggregates n channels is called nCA configuration. For example, 2CA configuration means that two channels are aggregated into one channel. 2CA configuration is equivalent to 2+0 configuration.	Huawei Term
Certificate Authority	CA	Certification Authority	A Certificate Authority signs all certificates that it issues with its private key.	3GPP TS 33.221: "Generic Authentication Architecture (GAA); Support for subscriber certificates"

Term	Abbreviation	Synonym	Definition	Reference
call admission control	CAC	N/A	Call admission control (CAC) prevents oversubscription of VoIP networks. CAC is used in the call set-up phase and applies to real-time media traffic as opposed to data traffic. CAC mechanisms complement and are distinct from the capabilities of quality of service tools to protect voice traffic from the negative effects of other voice traffic and to keep excess voice traffic off the network. Since it averts voice traffic congestion, it is a preventive congestion control procedure. It ensures that there is enough bandwidth for authorized flows.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
controller area network bus	CAN bus	N/A	A controller area network (CAN) bus is a robust vehicle bus standard designed to allow microcontrollers and devices to communicate with each other's applications without a host computer. It is a message-based protocol, designed originally for multiplex electrical wiring within automobiles to save on copper, but it can also be used in many other contexts. For each device, the data in a frame is transmitted sequentially but in such a way that if more than one device transmits at the same time, the highest priority device can continue while the others back off. Frames are received by all devices, including by the transmitting device.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
capital expenditure	CAPEX	capital expense	Capital expenditure or capital expense (capex or CAPEX) is the money an organization or corporate entity spends to buy, maintain, or improve its fixed assets, such as buildings, vehicles, equipment, or land.	Wikipedia
call attempts per second	CAPS	N/A	The call attempts here include both successful calls (that is, the call connection is successful and the two parties can talk) and failed calls.	Huawei Term
committed access rate	CAR	N/A	A traffic control method that applies Quality of Service (QoS) agreements to classify packets and limit incoming and outgoing IP traffic at a specified rate. CAR is configurable and usually deployed on network edge interfaces.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cell broadcast	CB	N/A	Cell broadcast (CB) is a method of sending messages to multiple mobile telephone users in a defined area at the same time. It is defined by the ETSI's GSM committee and 3GPP and is part of the 2G, 3G, 4G LTE (telecommunication) and 5G standards. It is also known as short message service-cell broadcast (SMS-CB).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
code block	CB	N/A	One or more code blocks (CBs) form one transport block (TB). A TB of a small size can consist of only one CB, while a TB of a large size can be segmented into multiple CBs. According to related LTE specifications, the number of CBs in a TB ranges from 1 to over 20, depending on the TB size. At the end of each CB, a CRC bit is added for data correctness verification after Turbo code decoding. Information in a CB includes system bits, check bit 0, and check bit 1.	• Huawei Term • 3GPP TS 38.214: "Physical layer procedures for data (Release 17)"
cipher block chaining	CBC	N/A	A block cipher mode that enhances ECB mode by chaining together blocks of cipher text it produces.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
cell broadcast center	CBC	N/A	The CBC shall be responsible for the management of CBS messages and for determining the CBS delivery parameters of the BSS/RNS. The CBC may be connected to several BSCs/RNCs. The CBC is regarded to be integrated as a node into the core network.	ITU-T Q.1741.9: "IMT-2000 references to Release 11 of GSM evolved UMTS core network"
cell broadcast center function	CBCF	N/A	In 3GPP, the CBCF is a network function in the 5G core network. The CBCF may be connected to several AMFs. The CBCF may be connected to several CBEs. The CBCF shall be responsible for the management of CBS messages.	3GPP TS 23.041: "Technical realization of Cell Broadcast Service (CBS)"
cell broadcast channel	CBCH	N/A	The CBCH, downlink only, is used to carry the short message service cell broadcast (SMSCB). The CBCH uses the same physical channel as the SDCCH.	3GPP TR 45 002 V16.0.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; GSM/EDGE Multiplexing and multiple access on the radio path"

Term	Abbreviation	Synonym	Definition	Reference
coordinated beamforming	CBF	CB	N/A	3GPP TR 36.819: "Coordinated multi-point operation for LTE physical layer aspects (Release 11)"
code block group	CBG	N/A	A code block group (CBG) consists of one or more code blocks.	3GPP TS 38.213: "Physical layer procedures for control (Release 15)"
constant bit rate	CBR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
committed burst size	CBS	N/A	The maximum committed amount of data that a user may offer to the network during a time interval.	ETS 300 399-1: "Frame relay services;Part 1: General description"
cell broadcast service	CBS	N/A	The cell broadcast service (CBS) is a teleservice, which enables an Information Provider to submit short messages for broadcasting to a specified area within the PLMN.	ITU-T Q.1741.9: "IMT-2000 references to Release 11 of GSM evolved UMTS core network"
component carrier	CC	N/A	A carrier involved in carrier aggregation (CA)	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
call control	CC	N/A	In telephony, call control refers to the software within a telephone switch that supplies its central function. Call control decodes addressing information and routes telephone calls from one end point to another. It also creates the features that can be used to adapt standard switch operation to the needs of users. These are called supplementary services and are commonly invoked by a vertical service code. Examples include "call waiting", "call forward on busy", and so on.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
country code	CC	N/A	Country codes are short alphabetic or numeric geographical codes (geocodes) developed to represent countries and dependent areas, for use in data processing and communications. Several different systems have been developed to do this. The term country code frequently refers to ISO 3166-1 alpha-2 or international dialing codes, the E.164 country calling codes.	Wikipedia
credit control answer	CCA	N/A	N/A	3GPP TS 32.299 version 9.24.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Charging management; Diameter charging applications"
call control block	CCB	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
common control channel	CCCH	N/A	The Common Control Channel (CCCH) is responsible for transferring control information between all mobiles and the BTS.	Wikipedia
Co-Channel Dual Polarization	CCDP	• co-channel dual polar • co-channel dual polarized	A channel configuration method, which uses one channel carrying both horizontally polarized and vertically polarized waves to transmit two signal streams. CCDP provides twice the transmission capacity of single polarized transmission.	Huawei Term
control channel element	CCE	N/A	A physical downlink control channel consists of one or more control-channel elements (CCEs).	3GPP TS 38.211: "NR; Physical channels and modulation"

Term	Abbreviation	Synonym	Definition	Reference
Continuity Check Message	CCM	N/A	"Heartbeating" messages for CFM. The Continuity Check Message (CCM) provides a means to detect connectivity failures in an MA. CCMs are multicast messages. CCMs are confined to a domain (MD). These messages are unidirectional and do not solicit a response. Each MEP transmits a periodic multicast Continuity Check Message inward towards the other MEPs.	Wikipedia
certificate configuration message	CCM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
current call meter	CCM	N/A	The accumulated charge as computed by the MS, expressed in terms of Home units.	3GPP TS 22.024 version 9.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Description of Charge Advice Information (CAI) "
cell change order	CCO	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
communication control port	CCP	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
capability configuration parameter	CCP	N/A	N/A	3GPP TS 101 267 V8.18.0: "Digital cellular telecommunications system (Phase 2+); Specification of the SIM Application Toolkit (SAT) for the Subscriber Identity Module - Mobile Equipment (SIM-ME) interface"
cross-connection point	CCP	N/A	In the local line network, equipment which enables an incoming pair to be connected to any of the outgoing pairs. Note: Cross-connection points are designated as primary or secondary according to their form and importance in the network. They are located between the main distribution frame and a number of distribution points.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
common control physical channel	CCPCH	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
control channel parallel interference cancellation	CCPIC	N/A	N/A	Huawei Term
Common Channel Signaling	CCS	N/A	A signaling system used in telephone networks that separates signaling information from user data. A specified channel is exclusively designated to carry signaling information for all other channels in the system.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
common-channel signaling	CCS	N/A	In telecommunications, common-channel signaling (CCS) is the transmission of control information (signaling) via a separate channel other than that used for messages. The signaling channel usually controls multiple message channels.	Wikipedia
coded composite transport channel	CCTrCH	N/A	A data stream resulting from encoding and multiplexing of one or several transport channels	3GPP TR 21.905 V17.0.0: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications (Release 17)"
cell center user	CCU	N/A	N/A	Huawei Term
cabinet control unit	CCU	N/A	A cabinet control unit (CCU) monitors the operating environment of the cabinet and manages devices in the cabinet.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
call control unit	CCU	N/A	N/A	TIPHON TS 102 228 V4.1.1: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON) Release 4; Technology Mapping; Implementation of TIPHON architecture using BICC"
cyclic delay diversity	CDD	N/A	Cyclic delay diversity (CDD) is a diversity scheme used in OFDM-based telecommunication systems, transforming spatial diversity into frequency diversity.	Wikipedia
code division multiple access	CDMA	N/A	A multiple access technique in which the various terminals having access to a link are allotted orthogonal signals for transmission, for example sequences of bits with zero or little cross-correlation, such signals being distinguishable even when they share the same frequency bands and the same time intervals	IEV 725-14-14

Term	Abbreviation	Synonym	Definition	Reference
CDMA2000 1x radio transmission technology	CDMA2000 1xRTT	N/A	CDMA2000 1xRTT (IS-2000), also known as 1x and 1xRTT, is the core CDMA2000 wireless air interface standard. The designation "1x", meaning 1 times radio transmission technology, indicates the same radio frequency (RF) bandwidth as IS-95: a duplex pair of 1.25 MHz radio channels. 1xRTT almost doubles the capacity of IS-95 by adding 64 more traffic channels to the forward link, orthogonal to (in quadrature with) the original set of 64. The 1x standard supports packet data speeds of up to 153 kbit/s with real world data transmission averaging 80–100 kbit/s in most commercial applications. IMT-2000 also made changes to the data link layer for greater use of data services, including medium and link access control protocols and quality of service (QoS). The	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			IS-95 data link layer only provided "best efforts delivery" for data and circuit switched channel for voice (i.e., a voice frame once every 20 ms).	
cell-defining synchronization signal and PBCH block	CD-SSB	N/A	A cell-defining synchronization signal and PBCH block (CD-SSB) is an SSB that is associated with an RMSI.	3GPP TS 38.300: "NR; NR and NG-RAN Overall Description; Stage 2 (Release 17)"
combining and distribution unit	CDU	N/A	A CDU includes a common output/input port, two N input/output ports and two N isolation ports.	Huawei Term
customer edge	CE	N/A	The customer edge (CE) is the router at the customer premises that is connected to the provider edge of a service provider IP/MPLS network. CE peers with the Provider Edge (PE) and exchanges routes with the corresponding VRF inside the PE. The routing protocol used could be static or dynamic (an interior gateway protocol like OSPF or an exterior gateway protocol like BGP).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
channel element	CE	N/A	Bitstream element containing one or more jointly encoded channels	ETSI TS 103 190-1: "Digital Audio Compression (AC-4) Standard; Part 1: Channel based coding"
coverage enhancement	CE	N/A	N/A	Huawei Term
channelized E1	CE1	N/A	N/A	Huawei Term
circuit emulation service	CES	N/A	Circuit emulation service (CES) is a telecommunication technology used to send information over asynchronous data networks like ATM, Ethernet or MPLS, so that it is received error-free with constant delay, similar to a leased line.	Wikipedia
cell edge user	CEU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
connectivity fault management	CFM	IEEE 802.1ag	IEEE 802.1ag (also CFM) (IEEE Standard for Local and Metropolitan Area Networks Virtual Bridged Local Area Networks Amendment 5: Connectivity Fault Management) is a standard defined by IEEE. It defines protocols and practices for OAM (Operations, Administration, and Maintenance) for paths through 802.1 bridges and local area networks (LANs). It is an amendment to IEEE 802.1Q-2005 and was approved in 2007.	Wikipedia
connection frame number	CFN	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
call forwarding unconditional	CFU	call forwarding - unconditional	The Call Forwarding Unconditional (CFU) supplementary service enables a served user to have the network redirect calls which are addressed to the served user's ISDN number to another user.	ETSI EG 201 973-1: "Access and Terminals (AT); Public Switched Telephone Network; Support of legacy terminals by Broadband IP networks and equipment; Part 1: General (common part covering both PSTN Analogue and ISDN TE)"

Term	Abbreviation	Synonym	Definition	Reference
charging gateway	CG	N/A	The portion of the CGF embedded into a single physical device is called the Charging Gateway entity. The CGF may be distributed to several physical Charging Gateways or GSNs, to facilitate redundancy. If that Charging Gateway entity that is the Primary Charging Gateway entity, does not respond to communication originating from the GSNs, the GSNs will try to send the CDR data to a Secondary Charging Gateway entity. Here each GSN will have several IP addresses (of different priority) for the Charging Gateway entities, thus avoiding downtime of the CGF.	3GPP TS 32.200: "Technical Specification Group Services and System Aspects; Telecommunication management; Charging management; Charging principles"
common gateway interface	CGI	N/A	The common gateway interface (CGI) is a standard way for a web server to pass a web user's request to an application program and to receive data back to forward to the user.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
cell global identifier	CGI	N/A	Cell global identifier (CGI) is a globally unique identifier for a cell in mobile phone networks. It consists of four parts: mobile country code (MCC), mobile network code (MNC), location area code (LAC) and cell identification (CI).	Wikipedia
CPRI Global Positioning System	CGPS	N/A	The CGPS converts GPS analog signals to digital signals, and sends the signal to the BBU through an optical fiber. The CGPS is a solution for remote GPS antennas.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Challenge-Handshake Authentication Protocol	CHAP	N/A	Challenge-Handshake Authentication Protocol (CHAP) provides protection against replay attacks by the peer through the use of an incrementally changing identifier and of a variable challenge-value. CHAP requires that both the client and server know the plaintext of the secret, although it is never sent over the network. As such, CHAP provides better security as compared to Password Authentication Protocol (PAP) which is vulnerable for both these reasons. The MS-CHAP variant does not require either peer to know the plaintext and does not transmit it, but has been broken.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
conditional handover	CHO	N/A	A conditional handover (CHO) is defined as a handover that is executed by the UE when one or more handover execution conditions are met. The UE starts evaluating the execution condition(s) upon receiving the CHO configuration, and stops evaluating the execution condition(s) once a handover is executed.	3GPP TS 38.300 V16.8.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2 (Release 16)"
call history record	CHR	N/A	A system used for identifying faults in an efficient way. It records and stores the information of all the faults occurring during a call for each user. If necessary, you can query the call history records of a specific user through the CHR client to quickly locate causes for the faults.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cell identity	CI	N/A	N/A	3GPP TS 32.293 version 16.0.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Charging management; Proxy function"
CUG index	CI	N/A	A code used to select a CUG for an outgoing call, or to indicate an incoming CUG call. Indices are passed between the user and the network and have significance only within the context of a user's subscription.	3GPP TS 23.085: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Closed User Group (CUG) supplementary service; Stage 2 (Release 16)"
congestion indication	CI	N/A	N/A	TR 101 380 V1.1.1: "Digital Terminals and Access (DTA); Definitions, abbreviations and symbols"

Term	Abbreviation	Synonym	Definition	Reference
circuit identification code	CIC	N/A	The ISDN user part (ISUP) circuit identification code (CIC) in the Signaling System #7, which is used to set up telephone calls in public switched telephone networks, is part of the initial address message (IAM). When a telephone call is set up from one subscriber to another, many telephone exchanges will be involved, possibly across international boundaries. To allow a call to be set up correctly, where ISUP is supported, a switch will signal call-related information like called or calling party number to the next switch in the network using ISUP messages. The CIC provides information about where the voice part of the call is carried - on which trunk and in which timeslot.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
classless inter-domain routing	CIDR	N/A	A routing mode in which IP addresses and masks are used to indicate network address and subnetwork address. Through CIDR, routers can flexibly aggregate routes. This reduces the size of the routing table.	Huawei Term
carrier indicator field	CIF	N/A	N/A	3GPP TS 36.300 version 16.6.0: "LTE;Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2 and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
carrier-to-interference-plus-noise ratio	CINR	carrier-to-interference-and-noise ratio	A ratio used to assess channel quality. The BS sends the REP-REQ message to the MS to request channel quality check. The MS retrieves the carrier-to-interference-plus-noise ratio (CINR) according to the received information and then returns the data to the BS through the REP-RSP message. The BS can select and adjust the transmission channel or initiate a handover according to the CINR.	Huawei Term
cell individual offset	CIO	N/A	Cell individual offset applicable to a specific cell. Value dB-24 corresponds to -24 dB, dB-22 corresponds to -22 dB and so on.	3GPP TS 36.331 V16.5.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
Cellular Internet of Things	CloT	Cellular IoT	N/A	3GPP TS 38.300 version 16.6.0: "5G; NR; NR and NG-RAN Overall description; Stage-2"
carrier to interference ratio	CIR	• C/I • signal-to-interference ratio • SIR • S/I	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
committed information rate	CIR	N/A	The information transfer rate which the network is committed to transfer under normal conditions. The rate is averaged over a minimum increment of time T_c . CIR is negotiated at virtual circuit establishment.	ETS 300 399-1: "Frame relay services; Part 1: General description"

Term	Abbreviation	Synonym	Definition	Reference
Common and Internal Spanning Tree	CIST	N/A	Identifies regions in a network and administers the CIST root bridge for the network, for each region and for each spanning tree instance in each region. It's also the default spanning tree instance of MSTP so that any VLAN which isn't a member of a particular MSTI, will be a member of the CIST. Furthermore, works as well as the spanning tree that runs between regions and between MST regions and Single Spanning Tree (SST) entities.	Wikipedia
cipher key	CK	N/A	A code used in conjunction with a security algorithm to encode and decode user and/or signalling data.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
ciphering key sequence number	CKSN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
compressed mode	CM	N/A	In compressed mode, data is not sent in slots in one or more continuous physical frames. This mode applies to inter-frequency measurement.	Huawei Term
configuration management	CM	N/A	Set of management functions which exercise control over the extensions or reductions of a system, the status of the constituent parts and the identity of their allocation (see ITU-T Recommendation I.113-604, ITU-T Recommendation M.3010)	ETSI TR 101 287 V1.2.1 (2001-09): "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
connection management	CM	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
commercial mobile alert system	CMAS	N/A	Commercial mobile alert system (now called Wireless Emergency Alert), a system for distributing geo-targeted alerts to mobile devices.	Wikipedia
Cell Multimedia Broadcast	CMB	N/A	N/A	Huawei Term
cell multimedia broadcast channel	CMBCH	N/A	The CMB bearer in cells, corresponding to the FACH of SCCPCH. It bears different program channels through configurations.	Huawei Term
Configuration Management Express	CME	N/A	A system that manages the data configuration of Huawei radio access network devices. It uses GUIs and provides integrated solutions for devices in typical O&M scenarios, such as initial deployment, transmission reconfiguration, parameter optimization, and base station reparenting.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cell misinsertion ratio	CMR	N/A	N/A	ETSI TR 101 287 V1.2.1 (2001-09): "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
central monitoring unit type A	CMUA	N/A	A unit that automatically adjusts the temperature in the cabinet based on temperature control mode and monitors Boolean values.	Huawei Term
core network	CN	N/A	An architectural term relating to the part of 3GPP system which is independent of the connection technology (radio or wired) of the terminal.	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Common Node B Application Protocol	CNBAP	C-NBAP	Signalling protocol responsible for the control of the Node B by the RNC is called NBAP (Node-B Application Part). NBAP is subdivided into Common and Dedicated NBAP (C-NBAP and D-NBAP), where Common NBAP controls overall Node B functionality and Dedicated NBAP controls separate cells or sectors of the Node B. NBAP is carried over Iub. In order for NBAP to handle common and dedicated procedures, it is divided into: NodeB Control Port (NCP) which handles common NBAP procedures and Communication Control Port (CCP) which handles dedicated NBAP procedures.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
coordinated massive MIMO	Co-MM	N/A	Coordinated massive MIMO (co-MM) is a type of PDSCH transmission with joint beamforming for two cells. It yields higher antenna array, power, and spatial multiplexing gains and increases the downlink user-perceived rates of UEs in overlapping areas.	Huawei Term
coordinated multipoint transmission/reception	CoMP	coordinated multipoint	Coordinated multi-point (CoMP) transmission/reception is considered as a tool to improve the coverage of high data rates, the cell-edge throughput and/or to increase system throughput.	3GPP TR 36.912: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Feasibility study for Further Advancements for E-UTRA (LTE-Advanced) (Release 16)"
cooperated transceiver	cooperated TRX	N/A	In TRX cooperation, the cooperated TRX is an available TRX selected through the TRX cooperation algorithm to replace the original active BCCH TRX. The selected TRX is the new BCCH TRX of the cell.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Common Object Request Broker Architecture	CORBA	N/A	The Common Object Request Broker Architecture (CORBA) is a standard defined by the Object Management Group (OMG) designed to facilitate the communication of systems that are deployed on diverse platforms. CORBA enables collaboration between systems on different operating systems, programming languages, and computing hardware. CORBA uses an object-oriented model, although the systems that use the CORBA do not have to be object-oriented. CORBA is an example of the distributed object paradigm.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
control resource set	CORESET	N/A	In the NR system, information such as the frequency range and number of OFDM symbols occupied by the PDCCH is encapsulated into a specified time-frequency zone called a CORESET.	• Huawei Term • 3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"
Common transmission resource management	Co-TRM	N/A	Co-TRM refers to the common management of transmission resources when the IP transmission bandwidth is shared by the GSM and UMTS services of the Multimode Base Station. Co-TRM improves the usage of transmission resources and ensures the transmission quality of services (QoS).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
control plane	CP	N/A	Plane that has a layered structure and performs the access control and connection control functions. It deals with the signalling necessary to access services, and set up, supervise, and release calls and connections.	ETSI TS 102 721-1: "Satellite Earth Stations and Systems; Air Interface for S-band Mobile Interactive Multimedia (S-MIM); Part 1: General System Architecture and Configurations"
cold patch	CP	N/A	A set of files, which are used to overwrite the original files for repairing a deficiency in the software without new functions added on the original software version. The new files take effect after the software is restarted. A cold patch can be installed, uninstalled, or queried.	Huawei Term
cyclic prefix	CP	N/A	In telecommunications, the term cyclic prefix (CP) refers to the prefixing of a symbol, with a repetition of the end. It provides a guard interval to eliminate intersymbol interference from the previous symbol.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
customer-premises equipment	CPE	N/A	Terminal and associated equipment located at a subscriber's premises and connected with a carrier's communication channel(s) at the demarcation point ("demarc").	Wikipedia
common pilot channel	CPICH	N/A	In WCDMA FDD cellular systems, CPICH is a downlink channel broadcast by NodeBs with constant power and of a known bit sequence. Its power is usually between 5% and 15% of the total NodeB transmit power. Commonly, the CPICH power is 10% of the typical total transmit power of 43 dBm.	3GPP TS 25.211 V16.0.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Physical channels and mapping of transport channels onto physical channels (FDD)"

Term	Abbreviation	Synonym	Definition	Reference
complex programmable logic device	CPLD	N/A	A complex programmable logic device (CPLD) is a programmable logic device with complexity between that of PALs and FPGAs, and architectural features of both. The main building block of the CPLD is a macrocell, which contains logic implementing disjunctive normal form expressions and more specialized logic operations.	Wikipedia
Common Public Radio Interface	CPRI	N/A	The Common Public Radio Interface (CPRI) standard defines an interface between Radio Equipment Control (REC) and Radio Equipment (RE). Oftentimes, CPRI links are used to carry data between cell sites and base stations.	Wikipedia
common public radio interface multiplex	CPRI MUX	N/A	With the CPRI Multiplex (CPRI MUX) feature, multiple RATs use one CPRI port to transmit data in a multi-RAT base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
central processing unit	CPU	central processor	A central processing unit (CPU), also called a central processor, main processor or just processor, is the electronic circuitry that executes instructions comprising a computer program. The CPU performs basic arithmetic, logic, controlling, and input/output (I/O) operations specified by the instructions in the program. This contrasts with external components such as main memory and I/O circuitry, and specialized processors such as graphics processing units (GPUs).	Wikipedia
class queue	CQ	N/A	N/A	Huawei Term
channel quality indicator	CQI	N/A	A measurement of the communication quality of wireless channels. CQI can be a value (or values) representing a measure of channel quality for a given channel.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
call quality test	CQT	N/A	A CQT is one method to test the quality of voice. In this kind of test, customers' subjective evaluation is counted as the major factor to judge the voice quality in the test channels.	Huawei Term
Connection Request	CR	N/A	Information sent in the forward direction on behalf of the signalling connection control part requesting the establishment of an end-to-end connection.	ITU-T Q.762: "Signalling System No. 7 – ISDN User Part general functions of messages and signals"
cell reselection	CR	N/A	Act of changing the serving cell from an old cell to a new cell. The cell reselection is performed by procedures located in the MLE and in the MAC. When the reselection is made and possible registration is performed, the MS is said to be attached to the cell.	ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)"
centralized radio access network	C-RAN	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
common resource block	CRB	N/A	As NR uses larger channel bandwidths than LTE and introduces bandwidth part (BWP), RBs in the entire channel bandwidth are defined as common resource blocks (CRBs), and RBs in a UE-specific BWP are defined as PRBs.	• Huawei Term • 3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"
cyclic redundancy check	CRC	cyclic redundancy code	A type of checksum algorithm that is not a cryptographic hash but is used to implement data integrity service where accidental changes to data are expected. Sometimes called "cyclic redundancy code".	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007

Term	Abbreviation	Synonym	Definition	Reference
cyclic redundancy code	CRC	N/A	A class of linear error detecting codes which generate parity check bits by finding the remainder of a polynomial division.	ETSI EN 301 908-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 4: Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive"
call re-establishment procedure	CRE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specification"

Term	Abbreviation	Synonym	Definition	Reference
cell range extension	CRE	N/A	N/A	3GPP TS 36.300 version 16.6.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
certificate revocation list	CRL	N/A	A CRL is a time-stamped list identifying revoked certificates that is signed by a CA or CRL issuer and made freely available in a public repository. Each revoked certificate is identified in a CRL by its certificate serial number.	D. Cooper, NIST, S. Santesson, Microsoft, S. Farrell, Trinity College Dublin, S. Boeyen, Entrust, R. Housley, Vigil Security, W. Polk, and NIST, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, May 2008.

Term	Abbreviation	Synonym	Definition	Reference
controlling RNC	CRNC	N/A	A role an RNC can take with respect to a specific set of UTRAN access points. There is only one Controlling RNC for any UTRAN access point. The Controlling RNC has the overall control of the logical resources of its UTRAN access point's.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
controlling radio network controller	CRNC	N/A	N/A	Huawei Term
cell radio network temporary identifier	C-RNTI	N/A	The C-RNTI is a UE identifier allocated by a controlling RNC and it is unique within one cell controlled by the allocating CRNC. C-RNTI can be reallocated when a UE accesses a new cell with the cell update procedure.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
cell reselect offset	CRO	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cell-specific reference signal	CRS	N/A	The UE may assume cell-specific reference signals are transmitted in - all downlink subframes for frame structure type 1, - all downlink subframes and DwPTS for frame structure type 2, - non-empty subframes for frame structure type 3 in a cell supporting PDSCH transmission.	ETSI TS 136 211 V16.6.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation"
coding scheme	CS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
coordinated scheduling	CS	N/A	N/A	3GPP TR 36.819: "Coordinated multi-point operation for LTE physical layer aspects (Release 11)"

Term	Abbreviation	Synonym	Definition	Reference
circuit service	CS	N/A	Circuit service includes leased circuit service, which provides leased point-to-point media for transmitting communication signals, and reserved circuit service, which is a telecommunications service that responds to a user's request and establishes a communication channel at a time specified by the user by means of user-network signaling.	Huawei Term
Client Signal Fail	CSF	N/A	N/A	Huawei Term
circuit-switched fallback	CSFB	- circuit switched fallback - CS fallback	Circuit switched fallback (CSFB): In this approach, LTE just provides data services, and when a voice call is to be initiated or received, it will fall back to the circuit-switched domain. When using this solution, operators just need to upgrade the MSC instead of deploying the IMS, and therefore, can provide services quickly. However, the disadvantage is longer call setup delay.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
closed subscriber group	CSG	N/A	A closed subscriber group (CSG) is a limited set of users with connectivity access to a femtocell. When a femtocell is configured in CSG mode, only those users included in the femtocell's access control list are allowed to use the femtocell resources. On the other hand, a femtocell can be also configured in open access mode, in which any user is allowed access to the femtocell.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
channel state information	CSI	N/A	In wireless communications, channel state information (CSI) refers to known channel properties of a communication link. This information describes how a signal propagates from the transmitter to the receiver and represents the combined effect of, for example, scattering, fading, and power decay with distance. The method is called channel estimation. The CSI makes it possible to adapt transmission to current channel conditions, which is crucial for achieving reliable communication with high data rates in multi-antenna systems.	Wikipedia
channel state information reference signal	CSI-RS	N/A	The network device may send, for example, a channel state information reference signal (CSI-RS) to obtain the channel state information fed back by a UE, and further determines a precoding matrix adapted to a downlink channel.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
CSI-RS for beam measurement	CSI-RS for BM	N/A	CSI-RS for BM: used for downlink beam measurement. The gNodeB transmits CSI-RS for BM within the active BWP. UEs receive and measure CSI-RS for BM to obtain the corresponding reference signal received power (RSRP), and report the RSRP and CSI-RS resource indicator (CRI) to the gNodeB. The gNodeB then obtains the RSRP information about the corresponding beam.	Huawei Term
CSI-RS for channel measurement	CSI-RS for CM	N/A	CSI-RS for CM: used for downlink channel state measurement. The gNodeB transmits CSI-RS for CM within the active BWP. UEs receive and process CSI-RS for CM to obtain corresponding information such as the CQI, RI, and PMI, and report the information to the gNodeB.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
common signaling link	CSL	N/A	SCTP is used as the data link layer protocol between the BSC and the eGBTS. When the data link layer between the BSC and the eGBTS uses SCTP, an SCTP link must be set up. The link used to send and receive O&M information is called a common signaling link (CSL).	Huawei Term
carrier sense multiple access	CSMA	N/A	N/A	ETSI TS 103 145 V1.1.1: "Reconfigurable Radio Systems (RRS); System Architecture and High Level Procedures for Coordinated and Uncoordinated Use of TV White Spaces"
coordinated scheduling-based power control	CSPC	N/A	The Coordinated Scheduling based Power Control feature coordinates transmit power configurations between cells in the time domain.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
configured scheduling RNTI	CS-RNTI	N/A	N/A	3GPP 38.331: "Radio Resource Control (RRC); Protocol specification"
Common Spanning Tree	CST	N/A	Administers the connectivity among MST regions, STP LANs and RSTP LANs in a bridged network.	Wikipedia
comma-separated values	CSV	N/A	A CSV file is a text file that stores data, generally used as an electronic table or by the database software.	Huawei Term
call transfer	CT	N/A	A feature on telephone networks that enables a user to relocate an existing call to another telephone by using the transfer button or dialing the required location.	Wikipedia
channel tester	CT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
channel type	CT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
common traffic channel	CTCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
central unit	CU	N/A	CU is a logical node hosting RRC, SDAP and PDCP protocols of the gNodeB or RRC and PDCP protocols of the en-gNB that controls the operation of one or more gNB-DUs. The gNB-CU terminates the F1 interface connected with the gNB-DU.	3GPP TS 38.401: "NG-RAN; Architecture Description"
connectivity verification	CV	N/A	A method of checking the connectivity of a path, typically, LSP validity.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
control word	CW	N/A	A 4-byte encapsulated packet header, which is used to transmit packet information in an MPLS packet switched network. It carries a sequence number for packet forwarding, pads a packet to reach the required length, and carries the Layer 2 header control information.	Huawei Term
carrier wave	CW	• carrier signal • carrier	In telecommunications, a carrier wave, carrier signal, or just carrier, is a waveform (usually sinusoidal) that is modulated (modified) with an information-bearing signal for the purpose of conveying information.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
codeword	CW	N/A	A codeword is a data code stream obtained after CRC insertion, segmentation into code blocks, code-block-specific CRC insertion, channel coding, and rate matching are performed for a TB to be sent in a TTI. Each codeword corresponds to one TB. Therefore, one UE sends a maximum of two codewords in one TTI. A codeword can be considered as a TB with protection against errors.	• Huawei Term • 3GPP TS 38.214: "Physical layer procedures for data (Release 17)"
current window alarm mode	CWA mode	N/A	N/A	Antenna Interface Standards Group Base Standard AISG v3.0
coarse wavelength division multiplexing	CWDM	N/A	N/A	ITU-T G.694.2: "Spectral grids for WDM applications: CWDM wavelength grid"
120 Gbit/s eXtended - Capability Form-Factor Pluggable	CXP	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
CA certificate chain	N/A	N/A	A list of CA certificates used to find the trusted CA that signs a peer's certificate to be authenticated. That is, a CA certificate chain is a path of certificates from a lower-branch CA to the root CA that is trusted by an entity. The chain is used to verify that the peer's certificate is trustworthy.	Huawei Term
CA Service	N/A	N/A	CA Service is a service provided by MAE that is used to issue certificates for MAE and its managed elements.	Huawei Term
cabinet	N/A	N/A	A free-standing and self-supporting enclosure for housing electrical and/or electronic equipment, usually fitted with doors and/or side panels which may or may not be removable.	EN 301 169-2: "Equipment practice; Engineering requirements for outdoor enclosures; Part 2: Unequipped enclosures"
cabinet group	N/A	N/A	Two or more base station combined cabinets are grouped to serve as one base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
call connection	N/A	N/A	Call connection completes the establishment and release of various call services, including voice calls, short messages, VGCS/VBS, CS data services, and GPRS/EDGE services. It implements BSSMAP and RR procedures, including system information, paging, immediate assignment, assignment, handover, location update, and A interface circuit management.	Huawei Term
call drop rate	N/A	service drop rate	The ratio of the number of dropped calls to the number of connected calls.	Huawei Term
call re-establishment	N/A	N/A	In the event of a radio link failure, call re-establishment is attempted (according to the procedure in GSM04.08).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
calling party	N/A	• caller • initiator	Party which initiates the call establishment.	ETSI EN 302 092-1: "Broadband Integrated Services Digital Network (B-ISDN) and Broadband Private Integrated Services Network (B-PISN); Digital Subscriber Signalling System No. two (DSS2), Broadband Inter-Exchange Signalling (B-QSIG), and Signalling System No. 7 (SS7); Call control in a separated call and bearer control environment; Part 1: Protocol specification"
candidate set	N/A	N/A	A set of pilots that have been received with sufficient strength by the mobile station to be successfully demodulated, but have not been placed in the Active Set by the base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
carrier frequency	N/A	N/A	Center frequency of the cell	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
channel calibration	N/A	N/A	Channel calibration calculates the variations of the phase, amplitude, and delay of known calibration signals transmitted on different IF and RF channels using certain algorithms and compensates these variations to obtain the phase, amplitude, and delay of the IF and RF channels. This ensures that the amplitude and phase of transmit and receive channels are the same when beamforming and close-loop MIMO are used.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
CAS multiframe	N/A	N/A	A multiframe set up based on timeslot 16. Each CAS multiframe contains 16 E1 PCM frames. Among the 8 bits of timeslot 16 in the first frame, the first 4 bits are used for multiframe synchronization. The multiframe alignment signal (MFAS) for synchronization is 0000. The last 4 bits are used as the not multiframe alignment signal (NMFAS). The NMFAS is XYXX. For the other 15 frames, timeslot 16 is used to transmit exchange and multiplexing (E&M) signaling corresponding to each timeslot.	Huawei Term
cascade connection	N/A	N/A	Connection of two-port networks such that the output port of one, except the last, is connected to the input port of the next.	IEV 131-12-77
Cb interface	N/A	N/A	The BSC and the CBC communicate with each other over the Cb interface.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
CDMA2000	N/A	• C2K • IMT Multi-Carrier • IMT-MC	CDMA2000 (also known as C2K or IMT Multi-Carrier [IMT-MC]) is a family of 3G mobile technology standards for sending voice, data, and signaling data between mobile phones and cell sites.	Wikipedia
cell	N/A	N/A	Radio network object that can be uniquely identified by a user equipment from a (cell) identification that is broadcast over a geographical area from one network access point.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
cell breathing	N/A	N/A	In CDMA-based Cellular networks, cell breathing is a mechanism which allows overloaded cells to offload subscriber traffic to neighboring cells by changing the geographic size of their service area. Heavily loaded cells decrease in size while neighboring cells increase their service area to compensate. Thus, some traffic is handed off from the overloaded cell to neighboring cells, resulting in load balancing.	Wikipedia
cell penalty	N/A	N/A	If an MS making a call is handed over to a target cell and the handover fails, another handover of the MS to the target cell may be initiated and the handover may fail again. The target cell is penalized in this case. That is, the call is forbidden to be handed over to the target cell within a specified period.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cell smearing effect	N/A	N/A	The cell smearing effect is caused by pedestrian users that transmit strong signals to the base station. In urban areas, when users and the base station are in line of sight (LOS), the smearing effect may occur. Users move out of the base station at a slow speed. Therefore, average signal energy is not attenuated quickly. Even when users are far away from the specified coverage area of the cell, the signal strength received by the base station is still higher than the handoff threshold. Therefore, the handoff is not performed. As a result, users move to neighboring cells, thus generating the interference and the problem of traffic management.	Huawei Term
CELL_PCH	N/A	N/A	An RRC connection mode where neither DCCH nor DTCH is available	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
cellular network	N/A	mobile network	A cellular network or mobile network is a communication network where the link to and from end nodes is wireless.	Wikipedia
certificate chain	N/A	N/A	Sequence of certificates where the next certificate can be authenticated by the public key of the preceding one.	ETSI GS ECI 001-5-1: "Embedded Common Interface (ECI) for exchangeable CA/DRM solutions; Part 5: The Advanced Security System; Sub-part 1: ECI specific functionalities "

Term	Abbreviation	Synonym	Definition	Reference
chain neighboring cell	N/A	N/A	A parameter of the neighboring cell relation property. During the fast movement handover, the MS can be handed over to only the neighboring cells of the serving cell. In addition, the neighboring cells and the serving cell must be configured in chain mode. Generally, the two neighboring cells in the direction of the fast movement of the MS are configured as chain neighboring cells. The configurations depend on the actual conditions.	Huawei Term
channel	N/A	N/A	A transmission path between nodes. One channel is considered to be one transmission path. Logically, a channel is an instance of a communication medium used for the purpose of passing data between two or more nodes.	ITU-T G.9960: "Unified high-speed wire-line based home networking transceivers – System architecture and physical layer specification"

Term	Abbreviation	Synonym	Definition	Reference
channel raster	N/A	N/A	The channel raster defines a subset of RF reference frequencies that can be used to identify the RF channel position in the uplink and downlink. The RF reference frequency for an RF channel maps to a resource element on the carrier.	3GPP TS 38.104: "NR; Base Station (BS) radio transmission and reception"
checksum	N/A	N/A	Computed value which is dependent upon the contents of a block of data. This value is sent along with the data block when it is transmitted. The receiving system computes a new checksum based upon the received data and compares this value with the one sent with the block. If the two values are the same, the receiver has a high degree of confidence that the data was received correctly (see IETF RFC 1983)	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"

Term	Abbreviation	Synonym	Definition	Reference
circuit switching	N/A	N/A	Circuit switching is a method of implementing a telecommunications network in which two network nodes establish a dedicated communications channel (circuit) through the network before the nodes may communicate. The circuit guarantees the full bandwidth of the channel and remains connected for the duration of the communication session.	Wikipedia
clock source	N/A	N/A	A device that provides standard time for the NTP configuration.	Huawei Term
clock synchronization	N/A	N/A	Refers to the process of updating a device's clock with other clocks in the environment.	ITU-T H.810: "Interoperability design guidelines for personal connected health systems: Introduction"
cluster	N/A	N/A	Set of loosely-coupled machines working together so that they are seen as a single computer.	ETSI TS 102 827: "GRID; Grid Component Model (GCM); GCM Interoperability Deployment"

Term	Abbreviation	Synonym	Definition	Reference
co-BBP	N/A	N/A	Co-BBP means that multiple RATs (including GSM, UMTS, LTE, and NR) of a multimode base station share one or more baseband processing units (BBPs). It can meet the service requirements of multiple RATs, reduce deployment costs, and speed up network construction.	Huawei Term
co-RF	N/A	N/A	Co-RF means that multiple RATs (including 2G, 3G, 4G, and 5G) share the same RF module. It can meet the service requirements of multiple RATs, reduce device and deployment costs, and speed up network construction.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
co-cabinet	N/A	N/A	A solution based on which RF modules and boards of different RATs are installed in one cabinet. In this manner, the cabinet supports multiple RATs. Note that the multimode base station in co-cabinet mode is not a new product but a solution. Such a base station cabinet is a combination of independent physical devices that are logically related to each other.	Huawei Term
coherence bandwidth	N/A	N/A	Coherence bandwidth is a statistical measurement of the range of frequencies over which the channel can be considered "flat", or in other words the approximate maximum bandwidth or frequency interval over which two frequencies of a signal are likely to experience comparable or correlated amplitude fading.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
coherence distance	N/A	N/A	Coherence distance is an important parameter that represents the variation of radio channel characteristics with space. It refers to a specific spatial distance range, within which the response functions of the radio channels of two antennas have stable benefits and phases.	Huawei Term
coherence time	N/A	N/A	In communications systems, a communication channel may change with time. Coherence time is the time duration over which the channel impulse response is considered to be not varying. Such channel variation is much more significant in wireless communications systems, due to Doppler effects.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
colored noise	N/A	N/A	White noise is a random signal whose power spectral density is a constant. This signal has equal power in each frequency band. White noise draws its name from white light, which is a mixture of monochromatic light of various frequencies (colors), having a flat power spectral density. Noise without this property is referred to as colored noise.	Wikipedia
combined cabinet	N/A	N/A	Two or more base station cabinets of the same type are combined to serve as one base station.	Huawei Term
combined group	N/A	N/A	Different types of BTS cabinets form a combined group.	Huawei Term
communication module	N/A	N/A	A standardized set of operations and protocols that belong to the application layer.	ITU-T T.190: "COOPERATIVE DOCUMENT HANDLING (CDH) – FRAMEWORK AND BASIC SERVICES"

Term	Abbreviation	Synonym	Definition	Reference
co-MPT	N/A	N/A	A mode of an MBTS, in which multiple RATs (possibly one RAT at the early stage of network deployment) share an O&M interface and a main control board. Such an MBTS is considered as a single logical base station.	Huawei Term
computer security	N/A	- cybersecurity or information technology security - IT security	Computer security, cybersecurity or information technology security (IT security) is the protection of computer systems and networks from information disclosure, theft of or damage to their hardware, software, or electronic data, as well as from the disruption or misdirection of the services they provide	Wikipedia
congestion	N/A	N/A	A set of one or more network elements in which the network is not able to meet the negotiated QoS objective for the already established connections and for the new connection requests.	ITU-T I.113: "Vocabulary of terms for broadband aspects of ISDN"

Term	Abbreviation	Synonym	Definition	Reference
context	N/A	N/A	The context of the compressor is the state it uses to compress a header. The context of the decompressor is the state it uses to decompress a header. Either of these or the two in combination are usually referred to as "context", when it is clear which is intended. The context contains relevant information from previous headers in the packet stream, such as static fields and possible reference values for compression and decompression. Moreover, additional information describing the packet stream is also part of the context, for example information about how the IP Identifier field changes and the typical inter-packet increase in sequence numbers or timestamps.	G. Pelletier, "RObust Header Compression", RFC 4164, August 2005

Term	Abbreviation	Synonym	Definition	Reference
control channel	N/A	N/A	A logical channel that carries system control information.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Convert Management System	N/A	N/A	A component of the LMT software. It is used to forward alarm information, alarm box control information, and alarm box status information between the OMU and the alarm box. The Convert Management System connects to the OMU through the Ethernet port and communicates with the alarm box through serial ports.	Huawei Term
correlation	N/A	N/A	Statistical measure (expressed as a number) that describes the size and direction of a relationship between two or more variables.	ETSI TR 103 477: "eHEALTH; Standardization use cases for eHealth"

Term	Abbreviation	Synonym	Definition	Reference
co-transmission	N/A	common transmission	A transmission mode in which different RATs connect to the transport network through a common transmission port by sharing the transmission resources.	Huawei Term
coupling	N/A	N/A	Linkage between two systems whereby energy is transferred from one system to another. The energy may be in a form capable of conveying information.	ETSI TR 101 767: "Human Factors (HF); Symbols to identify telecommunications facilities for deaf and hard of hearing people; Development and evaluation"

Term	Abbreviation	Synonym	Definition	Reference
CRC-4 multiframe	N/A	N/A	A multiframe recommended by ITU-T G.704 and set up based on the first bit of timeslot 0. The CRC-4 multiframe is different from the CAS multiframe in principle and implementation. Each CRC-4 multiframe contains 16 PCM frames. Each CRC-4 multiframe consists of two CRC-4 sub-multiframes. Each CRC-4 sub-multiframe is a CRC-4 check block that contains 2048 (256 x 8) bits. Bits C1 to C4 of a check block can check the previous check block.	Huawei Term
cross-certificate	N/A	N/A	A certificate that is used to establish a trust relationship between two certification authorities.	ETSI TR 119 001: "Electronic Signatures and Infrastructures (ESI); The framework for standardization of signatures; Definitions and abbreviations"

Term	Abbreviation	Synonym	Definition	Reference
cross-certification	N/A	N/A	A process undertaken by a certification authority (CA) to establish a trust relationship with another CA through the signing of another CA's public key in a certificate. When two CAs are cross-certified, they agree to trust and rely upon each other's public key certificates and keys. The two CAs exchange cross-certificates, enabling their respective users to interact securely.	Huawei Term

1.5 D

Term	Abbreviation	Synonym	Definition	Reference
DCH-to-FACH	D2F	N/A	N/A	Huawei Term
DCH-to-HSPA	D2H	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Dual Active Protocol Stack	DAPS	N/A	N/A	3GPP TS 38.300 V16.8.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2 (Release 16)"
DAPS handover	DAPS HO	N/A	A handover procedure that maintains the source gNB connection after reception of RRC message for handover and until releasing the source cell after successful random access to the target gNB.	3GPP TS 38.300 V16.8.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2 (Release 16)"
distributed base station	DBS	N/A	N/A	Huawei Term
dual connectivity	DC	N/A	Dual connectivity: mechanism whereby a device can access multiple cells/access points at the same time to bond multiple single cell/access point capabilities together to increase available throughput.	ETSI GS NGP 001 V1.1.1: "Next Generation Protocols (NGP); Scenarios Definitions"

Term	Abbreviation	Synonym	Definition	Reference
direct current	DC	N/A	Direct current (DC) is one-directional flow of electric charge.	Wikipedia
dual-carrier HSDPA	DC HSDPA	dual-cell HSDPA	N/A	Huawei Term
DC power distribution cabinet	DC PDC	N/A	High-current power supply equipment in the equipment room.	Huawei Term
common DC return	DC-C	N/A	A DC power system in which the return conductor is connected to the surrounding bonding network (BN) at many locations.	ITU-T K.27: "Bonding configurations and earthing inside a telecommunication building"
dynamic channel configuration control	DCCC	N/A	N/A	Huawei Term
dedicated control channel	DCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
direct current distribution unit	DCDU	- DC power distribution unit - DC PDU	The direct current distribution unit that distributes the -48 V DC received from an external power source to relevant components.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
dedicated channel	DCH	N/A	A channel dedicated to a specific UE	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
downlink control information	DCI	N/A	A DCI transports downlink, uplink or sidelink scheduling information, requests for aperiodic CQI reports, notifications of MCCH change or uplink power control commands for one cell and one RNTI.	ETSI TS 136 212 V12.8.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channel and modulation"
isolated DC return	DC-I	N/A	A bonding network that has a single point connection (SPC) to either the common bonding network or another isolated bonding network.	ITU-T K.27: "Bonding configurations and earthing inside a telecommunication building"
data communication network	DCN	N/A	N/A	Huawei Term
dedicated core network	DCN	N/A	N/A	Huawei Term
data coding scheme	DCS	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
digital cellular system at 1800 MHz	DCS 1800	N/A	N/A	Huawei Term
Distributed Control Unit	DCU	N/A	A signal conversion unit that converts RF signals to I/Q signals and allows for 3GPP-specifications-compliant RF signals in the LampSite solution.	Huawei Term
dynamic dedicated beam	DDB	Dynamic Massive Beam	DDB sets up an 8T8R cell to provide dedicated traffic beams for multiple UEs at the same time	Huawei Term
digital distribution frame	DDF	N/A	N/A	Wikipedia
digital data network	DDN	N/A	A data transmission network that is designed to transmit data on digital channels (such as the fiber channel, digital microwave channel, or satellite channel)	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
distributed denial-of-service attack	DDoS attack	N/A	DoS attacks, also called flood attacks, are network attacks that exhaust the network or system resources of the target computer and temporarily interrupt or stop services. As a result, normal users cannot access the target computer. DDoS attacks refer to the use of two or more compromised systems to launch a DoS attack on a specific target.	Wikipedia
direct digital synthesis	DDS	N/A	Direct digital synthesis (DDS) is a method used for creating arbitrary waveforms and frequencies from a single (or hybrid) frequency source.	Wikipedia
Data Encryption Standard	DES	N/A	The Data Encryption Standard (DES) is a symmetric-key algorithm for the encryption of digital data. Although its short key length of 56 bits makes it too insecure for applications, it has been highly influential in the advancement of cryptography.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
distribution frame	DF	N/A	In telecommunications, a distribution frame is a passive device which terminates cables, allowing arbitrary interconnections to be made.	Wikipedia
dynamic frequency selection	DFS	N/A	Ability of a system to switch to different physical RF channels based on channel measurement criteria to conform to particular regulatory requirements.	ETSI TS 102 178 V1.5.1: "Broadband Radio Access Networks (BRAN); HiperMAN; Data Link Control (DLC) layer"
Differential Global Positioning System	DGPS	N/A	N/A	ETSI TS 125 33: "Universal Mobile Telecommunications System (UMTS); Radio Resource Control (RRC); Protocol specification"
Diffie-Hellman key exchange	DH	N/A	A method for safely distributing keys that allows two parties that have no prior knowledge of each other to jointly establish a shared secret key over an insecure channel.	ETSI GR E4P 002 V1.1.1: "Europe for Privacy-Preserving Pandemic Protection (E4P); Comparison of existing pandemic contact tracing systems"

Term	Abbreviation	Synonym	Definition	Reference
Dynamic Host Configuration Protocol	DHCP	N/A	The Dynamic Host Configuration Protocol (DHCP) is a network management protocol used on Internet Protocol (IP) networks for automatically assigning IP addresses and other communication parameters to devices connected to the network using a client-server architecture.	Wikipedia
data integrity	DI	N/A	The property that data has not been altered in an unauthorized manner.	3GPP TS 33.102: " 3G security; Security architecture"

Term	Abbreviation	Synonym	Definition	Reference
differentiated services	DiffServ	DS	Differentiated services or DiffServ is a computer networking architecture that specifies a simple and scalable mechanism for classifying and managing network traffic and providing quality of service (QoS) on modern IP networks. DiffServ can, for example, be used to provide low-latency to critical network traffic such as voice or streaming media while providing simple best-effort service to non-critical services such as web traffic or file transfers.	Wikipedia
destination IP address	DIP	N/A	N/A	Huawei Term
downlink	DL	N/A	The direction from the network to UE	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
data layer	DL	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
downlink angle-of-departure	DL-AoD	N/A	N/A	3GPP TS 38.305: "Technical Specification Group Radio Access Network; NG Radio Access Network (NG-RAN); Stage 2 functional specification of User Equipment (UE) positioning in NG-RAN"
data link connection identifier	DLCI	N/A	An address conveyed in a PDU which indicates the source and destination of an intended instance of communication at the data link layer.	ETS 300 402-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Data link layer; Part 1: General aspects"

Term	Abbreviation	Synonym	Definition	Reference
data link discriminator	DLD	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
data link layer	DLL	• Layer 2 • L2	The data link layer, or Layer 2, is the second layer of the seven-layer OSI model of computer networking. This layer is the protocol layer that transfers data between nodes on a network segment across the physical layer. The data link layer provides the functional and procedural means to transfer data between network entities and may also provide the means to detect and possibly correct errors that can occur in the physical layer.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
downlink shared channel	DL-SCH	DSCH	N/A	3GPP TS 36.322 version 16.0.0: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Link Control (RLC) protocol specification"
delay measurement	DM	N/A	The delay measurement protocol measures the packet delay and packet delay variation between two R Bridges. The measurement is performed using timestamped OAM messages.	T. Mizrahi, Marvell, T. Senevirathne, S. Salam, D. Kumar, Cisco, D. Eastlake 3rd, and Huawei, "Loss and Delay Measurement in Transparent Interconnection of Lots of Links (TRILL)", RFC 7456, March 2015
dynamic MBSFN area	DMA	N/A	N/A	Huawei Term
Dynamic Massive Beam	DMB	N/A	A solution that provides dedicated traffic beams for multiple UEs in an 8T8R cell at the same time.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
demodulation reference signal	DMRS	N/A	A closed loop demodulation reference signal (DMRS) based spatial multiplexing is supported for Physical Downlink Shared Channel (PDSCH). Up to 8 and 12 orthogonal DL DMRS ports are supported for type 1 and type 2 DMRS respectively. Up to 8 orthogonal DL DMRS ports per UE are supported for SU-MIMO and up to 4 orthogonal DL DMRS ports per UE are supported for MU-MIMO. The number of SU-MIMO code words is one for 1-4 layer transmissions and two for 5-8 layer transmissions.	3GPP TS 38.300 V16.4.0: "NR; NR and NG-RAN Overall description; Stage-2"
desired Min Tx interval	DMTI	N/A	The minimum interval that the local system would like to use when transmitting BFD control packets.	Huawei Term
demilitarized zone	DMZ	N/A	N/A	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007

Term	Abbreviation	Synonym	Definition	Reference
data network name	DNN	N/A	In 5GS, the Data Network Name (DNN) is equivalent to an APN in EPS. The DNN is a reference to a data network, it may be used e.g. to select SMF or UPF.	3GPP TS 23.003 V17.2.0: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Numbering, addressing and identification; (Release 17)"
Domain Name Server	DNS	N/A	The Domain Name System (DNS) is a hierarchical and decentralized naming system for computers, services, or other resources connected to the Internet or a private network. It associates various information with domain names assigned to each of the participating entities.	Wikipedia
directory name service server	DNS server	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
direction of arrival	DoA	N/A	In signal processing, direction of arrival (DoA) denotes the direction from which a propagating wave arrives at a point, where usually a set of sensors are located. This set of sensors forms what is called a sensor array. Often there is the associated technique of beamforming which is estimating the signal from a given direction.	Wikipedia
Distributed Object-oriented Programmable Real-time Architecture	DOPRA	N/A	An OS-layer, middleware-level, highly-tailorable, component-based, open software platform developed by Huawei. It can shield the differences in OSs, hardware, networks, or system scale for upper-layer software.	Huawei Term
denial of service	DoS	N/A	Prevention of authorized access to resources or the delaying of time-critical operations	TR 101 664 V1.1.1: "Intelligent Network (IN); IN interconnect security features"

Term	Abbreviation	Synonym	Definition	Reference
downlink power balancing	DPB	N/A	The downlink code transmit power of each link drifts during soft handovers of UEs due to bit errors in transmit power control (TPC), affecting the diversity and combining gains of soft handovers. Therefore, the code transmit power of the NodeB needs to be measured periodically, and the code transmit power of each link needs to be balanced based on the transmit power difference between the links.	Huawei Term
destination point code	DPC	N/A	Information identifying the signalling point to which the message is to be routed	ITU-T Q.722: "GENERAL FUNCTION OF TELEPHONE MESSAGES AND SIGNALS"
dedicated physical control channel	DPCCH	N/A	This is the physical channel on which the signaling is transmitted, both on the uplink by the user equipment (UE) to the base transceiver station (NodeB) and on the downlink by the NodeB to the UE.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
dedicated physical channel	DPCH	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
digital pre-distortion	DPD	N/A	A pre-distortion linearization technology. It has no stability problem, works in a wide frequency band, and can process multi-carrier signals. The pre-distortion technology features a relatively low cost, simple process, and high efficiency (generally over 19%).	Huawei Term
dead peer detection	DPD	N/A	Specifies the interval for the system to send invalid detection packets to the peer to check whether the tunnel is active when the traffic mode or polling mode is adopted.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
dedicated physical data channel	DPDCH	N/A	This is the physical channel on radio interface (Uu) on which payload (such as voice and IP data) as well as higher layer signaling (RRC and non-access stratum—NAS signaling) is transmitted, both on the uplink by the user equipment (UE) to the base transceiver station (NodeB) and on the downlink by the NodeB to the UE.	Wikipedia
dynamic point selection	DPS	N/A	N/A	3GPP TR 36.819: "Coordinated multi-point operation for LTE physical layer aspects (Release 11)"
data processing unit	DPU	N/A	N/A	Huawei Term
distributed radio access network	D-RAN	N/A	N/A	Huawei Term
data radio bearer	DRB	N/A	The data radio bearer transports the packets of an E-RAB between a UE and a base station. There is a one-to-one mapping between the E-RAB and the data radio bearer.	3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)"

Term	Abbreviation	Synonym	Definition	Reference
directed retry decision	DRD	N/A	Directed retry decision (DRD) is performed by the RNC to select a suitable cell for a UE to access.	Huawei Term
drift radio network controller	DRNC	N/A	The DRNC is a UTRAN element that has an active link to the UE that shall be located. The DRNC, of course, also provides CRNC functionality regarding UE Positioning for its associated Node Bs and LMUs.	3GPP TS 25.305: "Stage 2 functional specification of User Equipment (UE) positioning in UTRAN"
drift radio network subsystem	DRNS	drift RNS	A role an RNS can take with respect to a specific connection between a UE and UTRAN. An RNS that supports the serving RNS with radio resources when the connection between the UTRAN and the user equipment need to use cells controlled by this RNS is referred to as a drift RNS.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
discovery reference signal	DRS	N/A	N/A	3GPP TS 36.300 version 16.6.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
discontinuous reception	DRX	N/A	Discontinuous reception is a method used in mobile communication to conserve the battery of the mobile device.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
data synchronization	DS	N/A	Data synchronization is the process of establishing consistency among data from a source to a target data storage and vice versa and the continuous harmonization of the data over time. It is fundamental to a wide variety of applications, including file synchronization and mobile device synchronization e.g., for PDAs. Synchronization can also be useful in encryption for synchronizing Public Key Servers.	Wikipedia
dynamic service area	DSA	N/A	N/A	Huawei Term
domain-specific access control	DSAC	N/A	DSAC is a process during which UEs of some ACs are barred from accessing the circuit-switched (CS) domain, packet-switched (PS) domain, or both domains of the core network (CN) to prevent traffic bursts and to ensure the QoS of UEs in connected mode.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Direct-Sequence Code Division Multiple Access	DS-CDMA	N/A	DS-CDMA (Direct-Sequence Code Division Multiple Access) is a multiple access scheme based on DSSS, by spreading the signals from/to different users with different codes. It is the most widely used type of CDMA.	Wikipedia
differentiated services code point	DSCP	differentiated services codepoint	The differentiated services code point (DSCP) is a value which is encoded in the DS field, and which each DS node must use to select the PHB which is to be experienced by each packet it forwards.	D. Grossman, "New Terminology and Clarifications for Diffserv", RFC 3260, April 2002
Directed Signaling Connection Re-establishment	DSCR	N/A	The RNC releases an RRC connection carried on a non-real-time RAB through the DSCR procedure, and then requests the UE to reestablish the RRC connection and set up services.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
distributed self-organizing network	D-SON	decentralized self-organizing network	Self-organizing networks are commonly divided into three major architectural types. When the SON functions are performed by the eNodeB, a distributed architecture is being used.	Wikipedia
destination signaling point	DSP	N/A	A signalling point to which a message is destined.	TU-T Q.9: "VOCABULARY OF SWITCHING AND SIGNALLING TERMS"
digital signal processor	DSP	N/A	A digital signal processor (DSP for short) is a microprocessor dedicated to digital signal processing. It is usually made of a MOSFET, and is widely applied to fields such as telecommunications, audio processing, digital image processing, radar, and sonar, as well as consumer electronic products.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
digital signal processing	DSP	N/A	Digital signal processing (DSP) is the use of digital processing, such as by computers or more specialized digital signal processors, to perform a wide variety of signal processing operations. The digital signals processed in this manner are a sequence of numbers that represent samples of a continuous variable in a domain such as time, space, or frequency. In digital electronics, a digital signal is represented as a pulse train, which is typically generated by the switching of a transistor.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
dynamic spectrum sharing	DSS	N/A	Dynamic spectrum sharing (DSS) allows LTE and NR cells to share the same spectrum resources and can dynamically allocate spectrum resources to LTE and NR cells based on their traffic volumes. When DSS is enabled, the LTE and NR cells must be configured with the same bandwidth.	Wikipedia
daylight saving time	DST	N/A	Daylight saving time (DST) is the practice of advancing clocks during part of the year so that daylight ends at a later time of the day.	ETSI TS 104 001 V2.2.1: "Open Smart Grid Protocol (OSGP); Smart Metering/ Smart Grid Communication Protocol"
dedicated traffic channel	DTCH	N/A	A dedicated traffic channel (DTCH) is a point-to-point channel, dedicated to one UE, for the transfer of user information. A DTCH can exist in both uplink and downlink.	ETSI TR 125 912 V16.0.0: "LTE; Feasibility study for evolved Universal Terrestrial Radio Access (UTRA) and Universal Terrestrial Radio Access Network (UTRAN)"

Term	Abbreviation	Synonym	Definition	Reference
DTLS	DTLS	N/A	Datagram Transport Layer Security (DTLS) is a communications protocol providing security to datagram-based applications by allowing them to communicate in a way designed to prevent eavesdropping, tampering, or message forgery.	Wikipedia
dual-tone multi-frequency	DTMF	• dual-tone multifrequency • dual tone multiple frequency	Dual-tone multi-frequency signaling (DTMF) is a telecommunication signaling system using the voice-frequency band over telephone lines between telephone equipment and other communications devices and switching centers.	Wikipedia
Transmission/ Timing/ Management Unit for DTRU BTS	DTMU	N/A	Double-transceiver main processing unit of BTS3012 and BTS3012AE	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
digital test sequence	DTS	N/A	N/A	ETSI TS 100 392-16 V1.2.1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 16: Network Performance Metrics"
discontinuous transmission	DTX	N/A	Discontinuous transmission is a means by which a mobile telephone is temporarily shut off or muted while the phone lacks a voice input.	Wikipedia
distributed unit	DU	N/A	DU is a logical node hosting RLC, MAC and PHY layers of the gNodeB or en-gNB, and its operation is partly controlled by gNB-CU. One gNB-DU supports one or multiple cells. One cell is supported by only one gNB-DU. The gNB-DU terminates the F1 interface connected with the gNB-CU.	3GPP TS 38.401: "NG-RAN; Architecture Description"

Term	Abbreviation	Synonym	Definition	Reference
duplicate acknowledgment	DupACK	N/A	The duplicate acknowledgment (DupACK) is an ACK whose sequence number is the same as that of the previous ACK. When packet disordering or packet loss occurs during transmission, the receiver returns a DupACK to the sender.	Huawei Term
dense wavelength division multiplexing	DWDM	N/A	N/A	ITU-T G.694.1: "Spectral grids for WDM applications: DWDM frequency grid"
downlink pilot timeslot	DwPTS	N/A	The downlink pilot timeslot (DwPTS) is part of a TDD special subframe used to transmit downlink signals. Same as normal downlink subframes, the DwPTS carries data of the upper layer. A DwPTS consists of 3 to 12 OFDM symbols, depending on the special subframe configuration.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
datagram	N/A	N/A	A packet with full address information enabling it to be routed to the endpoint without further information (see EG 201 898)	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
daughter board	N/A	• subboard • child board	A daughterboard, daughtercard, mezzanine board or piggyback board is an expansion card that attaches to a system directly. Daughterboards often have plugs, sockets, pins or other attachments for other boards.	Wikipedia
DCCC threshold rate	N/A	N/A	If the requested rate is lower than or equal to this rate, the dynamic allocation algorithm does not work.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
dead zone	N/A	N/A	Areas where mobile phones cannot transmit to a nearby mobile site, base station, or repeater are known as dead zones. In these areas, the mobile phones are said to be in a state of outage. Dead zones are usually areas where mobile phone service is not available because the signal between the handset and mobile site antennas is blocked or severely reduced, usually by hilly terrain, dense foliage, or physical distance.	Wikipedia
dedicated S1 connection	N/A	N/A	A logical signaling connection that is established between an MME and an eNodeB and dedicated to a specific UE. Generally, a pair of S1AP-IDs on an S1-MME connection is used to identify a dedicated S1 connection.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
de-interleaving	N/A	N/A	The process of unpermuting the symbols that were permuted by the interleaver. De-interleaving is performed on received symbols prior to decoding.	Huawei Term
delay jitter	N/A	delay variation	Difference in delay between successive packet arrivals (of the same flow) at the egress of the network.	TS 102 464 V1.2.1: "Satellite Earth Stations and Systems (SES); Broadband Satellite Multimedia (BSM); Interworking with DiffServ QoS"
demodulation	N/A	N/A	The process of recovering the original modulating signal from a modulated signal.	IEV 702-06-67
destination routing	N/A	N/A	In telecommunications, destination routing is a sequential pathway that messages must pass through to reach a target destination.	Wikipedia
Device Certificate	N/A	N/A	A device certificate is a digital certificate that identifies a device and is used to authenticate the identity of an NE during network communication.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
device status	N/A	device state	The status of a device which can be classified into available and unavailable. If the device usage of a real queue exceeds the device usage threshold (%), the real queue becomes unavailable. The virtual queue device status is determined by its associated shared device. If the shared device usage reaches 100%, the shared device becomes unavailable and the mapping virtual queue also becomes unavailable.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
digital certificate	N/A	N/A	Electronic documents that establish your credentials when doing business or other transactions on the web. They are issued by a certificate authority and contain a user's name, expiration dates, a copy of the certificate holder's public key, and the digital signature of the certificate-issuing authority so that a recipient can verify that the certificate is real. Some digital certificates conform to a standard such as X.509.	ETSI TS 102 465: "Satellite Earth Stations and Systems (SES); Broadband Satellite Multimedia (BSM) General Security Architecture"
digital modulation	N/A	N/A	Any modulation scheme with discrete constellation points (e.g. FSK, PSK).	ETSI EN 300 422-1: "Wireless Microphones; Audio PMSE up to 3 GHz; Part 1: Class A Receivers; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU"

Term	Abbreviation	Synonym	Definition	Reference
digital signal	N/A	N/A	A discretely-timed signal in which information is represented by a number of well-defined discrete values that one of its characteristic quantities may take in time.	ITU-T I.112: "VOCABULARY OF TERMS FOR ISDNs"
digital signature	N/A	N/A	Data associated to, including a cryptographic transformation of, a data unit that can be used to: (a) prove the source and integrity of the data unit; (b) protect the data unit against forgery; and (c) support signer non-repudiation of signing the data unit.	ETSI TR 119 600: "Electronic Signatures and Infrastructures (ESI); Business guidance for trust service status lists providers"

Term	Abbreviation	Synonym	Definition	Reference
dipole	N/A	half-wave element	A dipole consists of two symmetrical conducting wires. When the angle of the two wires is expanded, the distance between them increases. When the length of the entire dipole is equal to half of the wavelength, the radio sensed on the dipole is in the resonant state and the radiation efficiency is the highest. Such a dipole is also called a half-wave element.	Huawei Term
distributed massive MIMO	N/A	distributed M-MIMO	In distributed massive MIMO, multiple nTnR cells with continuous coverage corresponding to multiple TRPs working on the same frequency band are combined into one cell to eliminate cell edges and reduce inter-cell interference, and technologies such as MU-MIMO are used to improve uplink and downlink capacities and spectral efficiency.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
diversity	N/A	N/A	Diversity is technology that makes the fading characteristics of multiple signals carrying the same information independent of each other and performs specific processing on these signals to reduce the impact of fading on signals.	Wikipedia
diversity gain	N/A	N/A	The ratio of the two values of a random quantity characterizing the transmission which correspond to the same probability of exceeding these values with and without diversity reception	IEV 713-10-25
divider	N/A	N/A	An antenna subsystem component that allows for the connection of two or more receivers to a receive antenna.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Doppler effect	N/A	N/A	Doppler effect is the change in the wavelength perceived by an observer who is moving relative to the wave source. When the observer is moving towards the wave source, the wavelength perceived by the observer is compressed, the wavelength becomes shorter, increasing the frequency. Conversely, if the observer is moving away from the wave source, the wavelength perceived by the observer becomes longer, reducing the frequency. The higher the velocity of the observer relative to the wave source, the greater the Doppler effect.	Huawei Term
Doppler shift	N/A	N/A	Doppler shift is the difference between the frequency of the signal received by the receiver and that of the signal transmitted by the transmitter.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Doppler spread	N/A	N/A	Doppler spread refers to the widening of the spectrum of a narrow-band signal transmitted through a multipath propagation channel. It is due to the different Doppler shift frequencies associated with the multiple propagation paths when there is relative motion between the transmitter and the receiver.	Huawei Term
download	N/A	N/A	Transfer of data or programs from a server or host computer to one's own computer or device.	ETSI TS 102 250-1: "Speech and multimedia Transmission Quality (STQ); QoS aspects for popular services in mobile networks; Part 1: Assessment of Quality of Service"
drive testing	N/A	N/A	A testing method using vehicles equipped with network device-testing equipment.	ITU-T E.806: "Measurement campaigns, monitoring systems and sampling methodologies to monitor the quality of service in mobile networks"

Term	Abbreviation	Synonym	Definition	Reference
dry contact	N/A	N/A	The dry contact is a type of passive switch that has two states: open and closed. Two such contacts are not distinguished by polarity and therefore can be used interchangeably. Common dry contact signals are the outputs of switches, buttons, sensors, relays, and dry reed pipes.	Huawei Term
DS boundary node	N/A	N/A	A DS node that connects one DS domain to a node either in another DS domain or in a domain that is not DS-capable.	Huawei Term
DS node	N/A	N/A	A DS-compliant node, which can be a DS boundary node or a DS interior node.	Huawei Term
dual BAM servers	N/A	N/A	Two BAM servers, one active and one in standby. When the active BAM server breaks down because of a hardware or software fault, the standby BAM server takes over as the active server.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
dual-band network	N/A	N/A	In mobile phones, dual band refers to functionality that allows a mobile phone to support two frequency bands out of the four major GSM (or TDMA) bands.	Huawei Term
dual-homed	N/A	dual-homing	Dual-homed or dual-homing can refer to either an Ethernet device that has more than one network interface, for redundancy purposes, or in firewall technology, one of the firewall architectures for implementing preventive security. An example of dual-homed devices are enthusiast computing motherboards that incorporate dual Ethernet network interface cards.	Wikipedia
dual-polarized antenna	N/A	dipole antenna	An antenna intended to radiate or receive simultaneously two independent radio waves orthogonally polarized.	IEV 712-03-06

Term	Abbreviation	Synonym	Definition	Reference
dual-star topology	N/A	N/A	A type of network topology in which two switching modules form a pair of switching modules and provide a redundant interconnection network structure for all the terminals in the network	Huawei Term
duplexer	N/A	N/A	A duplexer is an electronic device that allows bi-directional (duplex) communication over a single path. In radar and radio communications systems, it isolates the receiver from the transmitter while permitting them to share a common antenna. Most radio repeater systems include a duplexer. Duplexers can be based on frequency (often a waveguide filter), polarization (such as an orthomode transducer), or timing (as is typical in radar).	Wikipedia

1.6 E

Term	Abbreviation	Synonym	Definition	Reference
extended access barring	EAB	N/A	N/A	Huawei Term
E-DCH-absolute grant channel	E-AGCH	enhanced dedicated channel-absolute grant channel	The E-DCH-absolute grant channel (E-AGCH) is a fixed rate (30 kbps, SF=256) downlink physical channel carrying the uplink E-DCH absolute grant.	3GPP TS 25.211: "Universal Mobile Telecommunications System (UMTS); Physical channels and mapping of transport channels onto physical channels (FDD)"
Ethernet aggregation	E-Aggr	N/A	A type of Ethernet service, which is based on a multipoint-to-point Ethernet virtual connection (EVC).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Extensible Authentication Protocol over LAN	EAPoL	EAP over LAN	When an authenticator works in termination mode, the authenticator terminates an EAPoL packet and transforms it into another type of authentication protocol packet, such as a RADIUS packet, and transmits user authentication information to the authentication server. The authenticator provides physical ports that each contain a controlled port and an uncontrolled port. Uncontrolled ports are always bidirectionally connected. They are used to transmit EAPoL frames to ensure that EAPoL authentication packets from supplicants can always be received. Controlled ports, however, are open only when authentication succeeds, and are used to transmit network resources and services.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Extensible Authentication Protocol Transport Layer Security	EAP-TLS	N/A	Extensible Authentication Protocol Transport Layer Security (EAP-TLS) and EAP Tunneled Transport Layer Security (EAP-TTLS) are EAP methods for authentication. As EAP is an authentication framework instead of a specific authentication mechanism, a method must be selected when Extensible Authentication Protocol over LAN (EAPoL) defined in 802.1X is used.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
E-UTRA absolute radio frequency channel number	EARFCN	N/A	A method of identifying the center carrier frequencies in E-UTRAN. The carrier frequency in the uplink and downlink is designated by the EARFCN in the range from 0 to 65535. The channel raster is 100 kHz for all bands, which means that the carrier centre frequency must be an integer multiple of 100 kHz. The relation between EARFCN and the carrier frequency in MHz for the downlink/uplink is given by an equation and associated table of frequency bands.	3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access"
event-based counter	EBC	N/A	Counters that are defined by adding filter criteria to base counters	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
excess burst size	EBS	N/A	The maximum allowed amount of data by which a user can exceed the committed burst size during the committed rate measurement interval. The excess burst size is less likely to be used for data delivery than the committed burst size. The excess burst size is negotiated at virtual circuit establishment.	ETS 300 399-1: "Frame relay services; Part 1: General description"
ratio of energy per modulating bit to the noise spectral density	Ec/No	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
embedded control channel	ECC	N/A	N/A	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks"
emergency call code	ECC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
elliptic curve cryptography	ECC	N/A	A type of asymmetric cryptography based on mathematics of groups that are defined by the points on a curve, where the curve is defined by a quadratic equation in a finite field.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
E-UTRAN cell global identifier	ECGI	• E-UTRAN cell global ID • E-UTRAN cell global identification	The E-UTRAN cell global identifier (ECGI) is used to identify cells globally. The ECGI is constructed from the mobile country code (MCC), mobile network code (MNC), and E-UTRAN cell identifier (ECI).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Enhanced Cell ID	E-CID	- Enhanced Cell ID - E-CellID	Enhanced Cell ID, E-CellID, or E-CID is a positioning feature introduced in REL9 E-UTRA (LTE radio). The UE reports to the network (E-SMLC) the serving cell ID, the timing advance (difference between its transmit and receive time) and the IDs and estimated timing and power of the detected neighbor cells. The eNodeB may report extra information to the E-SMLC like the angle of arrival. The E-SMLC estimates the UE position based on this information and its knowledge of the cells positions.	Wikipedia
error correction mode	ECM	N/A	N/A	Huawei Term
EPS connection management	ECM	N/A	ECM maintains the status of signaling connections between UEs and the EPC. The status is ECM-IDLE or ECM-CONNECTED.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Enhanced Common Public Radio Interface	eCPRI	N/A	eCPRI is published after CPRI. eCPRI standard defines specification which connects eREC (eCPRI Radio Equipment Control) and eRE (eCPRI Radio Equipment) via fronthaul transport network. It is used for 5G systems LTE-Advanced and LTE-Advanced Pro.	Huawei Term
enhanced circuit switched fallback	eCSFB	N/A	eCSFB is an enhanced version of CSFB. It enables shorter access delays and provides better user experience than CSFB.	Huawei Term
eCSPC	N/A	N/A	CSPC in IP RANs	Huawei Term
enhanced dedicated channel	E-DCH	N/A	The enhanced dedicated channel (E-DCH) is an uplink transport channel.	3GPP TS 25.211: "Universal Mobile Telecommunications System (UMTS); Physical channels and mapping of transport channels onto physical channels (FDD)"

Term	Abbreviation	Synonym	Definition	Reference
Enhanced Data rates for GSM Evolution	EDGE	N/A	Enhanced Data rates for GSM Evolution (EDGE) (also known as Enhanced GPRS (EGPRS), IMT Single Carrier (IMT-SC), or Enhanced Data rates for Global Evolution) is a digital mobile phone technology that allows improved data transmission rates as a backward-compatible extension of GSM.	Wikipedia
E-DCH dedicated physical control channel	E-DPCCH	N/A	E-DPCCH is used to carry the control information associated with the E-DCH.	Wikipedia
E-DCH dedicated physical data channel	E-DPDCH	N/A	E-DPDCH is used to carry the E-DCH transport channel.	Wikipedia
extended discontinuous reception	eDRX	N/A	N/A	Huawei Term
end entity	EE	N/A	An end entity (EE) is the end user of PKI products or services, and it can be an individual person, an organization, a device, or host process.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
EPS encryption algorithm	EEA	N/A	EPS Encryption Algorithms (EEA) is a set of 4G cryptographic algorithms. EEA1 is based on SNOW 3G, very similar to algorithms used in UMTS. EEA2 is based on the Advanced Encryption Standard (AES) with EEA2 defined by AES in CTR mode (e.g. stream cipher). Default key size will be 128. EEA3 is based on a cipher ZUC.	ETSI TR 103 637 V1.1.1: "Digital Enhanced Cordless Telecommunications (DECT); DECT-2020 New Radio (NR) interface; Study on Security Architecture"
Ethernet equipment clock	EEC	N/A	N/A	3GPP TS 36.401 version 9.2.1: "LTE; Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Architecture description"
enhanced CELL_FACH	EFACH	E-FACH	The enhanced CELL_FACH state (EFACH for short) corresponds to the CELL_FACH state, with enhanced CELL_FACH activated.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Ethernet in the First Mile	EFM	N/A	N/A	ETSI TS 102 973 V1.1.1: "Access Terminals, Transmission and Multiplexing (ATTM); Network Termination (NT) in Next Generation Network architectures"
Ethernet in the first mile OAM	EFM OAM	N/A	N/A	Huawei Term
enhanced full rate	EFR	N/A	Enhanced Full Rate or EFR or GSM-EFR or GSM 06.60 is a speech coding standard that was developed in order to improve the quite poor quality of GSM.	Wikipedia
equal gain combining	EGC	N/A	All the received signals are summed coherently.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
enhanced general packet radio service	EGPRS	EDGE	Enhanced Data rates for GSM Evolution (EDGE) (also known as Enhanced GPRS (EGPRS), IMT Single Carrier (IMT-SC), or Enhanced Data rates for Global Evolution) is a digital mobile phone technology that allows improved data transmission rates as a backward-compatible extension of GSM. EDGE is considered a pre-3G radio technology and is part of ITU's 3G definition. EDGE was deployed on GSM networks beginning in 2003 – initially by Cingular (now AT&T) in the United States.	Wikipedia
equal gain transmit	EGT	N/A	EGT is similar to EBF. The difference is that amplitude normalization is performed on the weights of each antenna in EGT. That is, only phases are weighted, but amplitudes are not.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
E-DCH HARQ Acknowledge ment Indicator Channel	E-HICH	N/A	N/A	ETSI TR 125 931: "Universal Mobile Telecommu nications System (UMTS); UTRAN functions, examples on signalling procedures"
equivalen t home PLMN	EHPLMN	• equivalent HPLMN • equivalent home PLMN	Any of the PLMN entries contained in the equivalent HPLMN list	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
evolved High Rate Packet Data	eHRPD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
equipment identity register	EIR	N/A	The Equipment Identity Register (EIR) in the GMR system is the logical entity which is responsible for storing in the network the International Mobile Equipment Identities (IMEIs), used in the GMR system. The equipment is classified as "white listed", "gray listed", "black listed" or it may be unknown as specified in GSM 02.16 and GSM 09.02.	ETSI TS 101 377-3-2: "GEO-Mobile Radio Interface Specifications; Part 3: Network specifications; Sub-part 2: Network Architecture; GMR-2 03.002"
equivalent isotropic radiated power	EIRP	effective isotropic radiated power	Product of the power supplied to the antenna and the maximum antenna gain relative to an isotropic radiator (absolute or isotropic gain)	ETSI TR 103 583 V1.1.1: "System Reference document (SRdoc); Technical characteristics of Multiple Gigabit Wireless Systems (MGWS) in radio spectrum between 57 GHz and 71 GHz"

Term	Abbreviation	Synonym	Definition	Reference
equivalent isotropic receiver sensitivity	EIRS	effective isotropic sensitivity (EIS)	Equivalent isotropic receiver sensitivity (EIRS) is defined as the ratio of the receiver sensitivity (S) of an RF module to the maximum antenna gain (Gi) relative to an isotropic antenna.	Huawei Term
32-port E1/T1 circuit Interface Unit REV:a	EIUa	N/A	N/A	Huawei Term
extremely large antenna array	ELAA	N/A	Extremely large antenna array (ELAA) is a new technology applied by Huawei in MetaAAUs. This technology increases the density of antenna elements and takes advantage of other technologies such as those related to antenna element materials and algorithms to improve coverage and reduce energy consumption at the same time.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Ethernet local area network	E-LAN	N/A	A type of Ethernet service, which is based on a multipoint-to-multipoint Ethernet virtual connection (EVC).	Huawei Term
enhanced Mobile Broadband	eMBB	N/A	Enhanced Mobile Broadband (eMBB) uses 5G as a progression from 4G LTE mobile broadband services, with faster connections, higher throughput, and more capacity.	Wikipedia
evolved multimedia broadcast/multicast service	eMBMS	N/A	eMBMS is an evolved multimedia broadcast/multicast service, which is a point-to-multipoint service. On an LTE network, data is broadcast in MBSFN subframes and can be received by all UEs supporting this function in the broadcast coverage area. This function is used to transmit data of common contents, such as live videos of football matches and hot events, with low costs.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
electromagnetic compatibility	EMC	N/A	Electromagnetic compatibility (EMC) is the ability of electrical equipment and systems to function acceptably in their electromagnetic environment, by limiting the unintentional generation, propagation and reception of electromagnetic energy which may cause unwanted effects such as electromagnetic interference (EMI) or even physical damage in operational equipment.	Wikipedia
electromagnetic field	EMF	N/A	An electromagnetic field (EMF) is a physical field formed due to the motion of charged particles. The interaction between electric and magnetic fields generates electromagnetic waves in space, which are also called electromagnetic radiations.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
electromagnetic interference	EMI	N/A	Any source of RF transmission that is within the frequency band used by a communication link, which degrades the performance of this link.	ETSI TS 103 246-5 V1.3.1: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 5: Performance Test Specification"
external machine interface	EMI	N/A	External Machine Interface (EMI), an extension to Universal Computer Protocol (UCP), is a protocol primarily used to connect to short message service centres (SMSCs) for mobile telephones.	Wikipedia
element management layer	EML	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
enhanced multi-level precedence and pre-emption	eMLPP	enhanced multi level precedence and preemption	This service has two parts: precedence and pre-emption. Precedence involves assigning a priority level to a call in combination with fast call set-up. Pre-emption involves the seizing of resources, which are in use by a call of a lower precedence, by a higher level precedence call in the absence of idle resources. Pre-emption can also involve the disconnection of an on-going call of lower precedence to accept an incoming call of higher precedence.	3GPP TS 22.067: "enhanced Multi-Level Precedence and Pre-emption Service (eMLPP); Stage 1"
EPS mobility management	EMM	N/A	The EPS (evolved packet system) mobility management (EMM) protocol provides procedures for the control of mobility when the user equipment (UE) uses the evolved universal terrestrial radio access network (E-UTRAN). It also provides control of security for the NAS protocols.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
electromagnetic shielding	EMS	N/A	In electrical engineering, electromagnetic shielding is the practice of reducing the electromagnetic field in a space by blocking the field with barriers made of conductive or magnetic materials. Shielding is typically applied to enclosures to isolate electrical devices from their surroundings, and to cables to isolate wires from the environment through which the cable runs. Electromagnetic shielding that blocks radio frequency (RF) electromagnetic radiation is also known as RF shielding.	Wikipedia
element management system	EMS	N/A	An element management system (EMS) consists of systems and applications for managing network elements (NE) on the network element-management layer (NEL) of the Telecommunications Management Network (TMN) model.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
enhanced Machine Type Communication	eMTC	N/A	eMTC (enhanced Machine Type Communication), is a type of low power wide area network (LPWAN) radio technology standard developed by 3GPP to enable a wide range of cellular devices and services, specifically, for machine-to-machine and Internet of Things applications.	Wikipedia
environment monitoring unit	EMU	N/A	A type of power and environment monitoring unit. An EMU is used to monitor the environment variables, such as the power supply and temperature. With external signal input through the relay, fire alarms, smoke alarms, burglary alarms, and others can be monitored as well. With the display on the OSS system, the change of environment can be monitored timely and accurately.	Huawei Term
environment monitoring unit type A	EMUA	N/A	An optional unit that monitors environment variable in the cabinet and processes alarms.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
E-UTRA-NR dual connectivity	EN-DC	N/A	NG-RAN supports E-UTRA-NR dual connectivity (EN-DC), in which a UE is connected to one eNodeB that acts as an MN and one gNodeB that acts as an SN.	3GPP TS 37.340: "Evolved Universal Terrestrial Radio Access (E-UTRA) and NR; Multi-connectivity; Stage 2"
E-UTRAN NodeB	eNodeB	N/A	A logical node responsible for radio transmission/reception in one or more cells to/from the User Equipment. It terminates the S1 interface towards the EPC.	3GPP TS 28.658: "Telecommunication management; Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)"
equivalent number of users	ENU	N/A	N/A	Huawei Term
endpoint	EP	N/A	Entity that can originate and terminate both signalling and media streams.	ETSI TR 102 008: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON) Release 3; Terms and Definition"
enhanced power control	EPC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
evolved packet core	EPC	N/A	A framework for an evolution or migration of the 3GPP system to a higher-data-rate, lower-latency, packet-optimized system that supports, multiple RATs.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
enhanced proportional fair	EPF	N/A	N/A	Huawei Term
Ethernet private line	EPL	N/A	Ethernet private line (EPL) and Ethernet virtual private line (EVPL) are data services defined by the MEF. EPL provides a point-to-point Ethernet virtual connection (EVC) between a pair of dedicated user-network interfaces (UNIs), with a high degree of transparency.	Wikipedia
erasable programmable logic device	EPLD	erasable programmable logical device	An Erasable programmable logic device (EPLD) is an integrated circuit that comprises an array of PLDs that do not come pre-connected; the connections are programmed electrically by the user. Most GAL and FPGA devices are examples of EPLDs.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
equivalent PLMN	EPLMN	N/A	N/A	3GPP TS 37.320: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Universal Terrestrial Radio Access (UTRA), Evolved Universal Terrestrial Radio Access (E-UTRA) and Next Generation Radio Access; Radio measurement collection for Minimization of Drive Tests (MDT); Overall description; Stage 2 (Release 16);"

Term	Abbreviation	Synonym	Definition	Reference
Ethernet passive optical network	EPON	N/A	A passive optical network based on Ethernet. It uses new generation broadband access technology, point-to-multipoint architecture, and passive optical fiber transmission. It supports symmetric upstream and downstream rates of 1.25 Gbit/s and a maximum access distance of 20 km. In the downstream direction, the bandwidth is shared based on encrypted broadcast transmission for different users. In the upstream direction, the bandwidth is shared based on TDM. In this way, the requirements for high bandwidth are met.	Huawei Term
extended processing rack	EPR	N/A	N/A	Huawei Term
energy per resource element	EPRE	N/A	A resource element (RE) occupies one symbol and one subcarrier. The EPRE is the energy per RE.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
evolved packet system	EPS	N/A	Evolved Packet System: is an evolution of the 3G UMTS characterized by higher-data-rate, lower-latency, packet-optimized system that supports multiple RATs. The Evolved Packet System comprises the Evolved Packet Core together with the evolved radio access network (EPC and E-UTRAN).	3GPP TS 22.278: "Technical Specification Group Services and System Aspects; Service requirements for the Evolved Packet System (EPS)"
E-UTRAN radio access bearer	E-RAB	N/A	An E-RAB uniquely identifies the concatenation of an S1 Bearer and the corresponding Data Radio Bearer. When an E-RAB exists, there is a one-to-one mapping between this E-RAB and an EPS bearer of the Non Access Stratum (NAS) as defined in 3GPP TS 23.401.	3GPP TS 36.401: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Architecture description"
E-DCH relative grant channel	E-RGCH	N/A	N/A	3GPP TR 25.903: "Universal Mobile Telecommunications System (UMTS); Continuous connectivity for packet data users"

Term	Abbreviation	Synonym	Definition	Reference
erlang	Erl	N/A	average number of concurrent calls carried by the circuits	ETSI ES 201 554: "Environmental Engineering (EE); Measurement method for Energy efficiency of Mobile Core network and Radio Access Control equipment"
E-DCH radio network temporary identifier	E-RNTI	N/A	N/A	ETSI TR 125 931: "Universal Mobile Telecommunications System (UMTS); UTRAN functions, examples on signalling procedures"
effective radiated power	ERP	equivalent radiated power	Effective radiated power (ERP), synonymous with equivalent radiated power, is an IEEE standardized definition of directional radio frequency (RF) power, such as that emitted by a radio transmitter.	Wikipedia
Ethernet ring protection switching	ERPS	N/A	A function that uses an APS protocol to provide protection in a ring topology at the Ethernet layer.	ITU-T G.8032: "Ethernet ring protection switching"

Term	Abbreviation	Synonym	Definition	Reference
errored second	ES	N/A	A one-second period with one or more errored blocks or at least one defect.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "
extended signaling link	ESL	N/A	A type of link that is responsible for transmitting the Abis timeslot dynamic connection message	Huawei Term
electronic serial number	ESN	N/A	An electronic serial number (ESN) is a 32-bit parameter unique to each mobile device (such as a mobile phone, a smart phone, or a tablet computer) specified by the Federal Communications Commission (FCC). ESNs were in use in as early as 1980 when the Advanced Mobile Phone System was invented. The administrative role was taken over by the Telecommunications Industry Association in 1997 and is still maintained by them. ESNs were initially used by AMPS and D-AMPS phones and are currently mainly used by CDMA phones.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
equipment serial number	ESN	N/A	Used to uniquely identify a piece of equipment.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Encapsulating Security Payload	ESP	N/A	A key protocol in the IP Security (IPsec) architecture. ESP adopts encryption and authentication mechanisms. It is used in transport mode or tunnel mode to authenticate the source of IP packets, and ensure data integrity, anti-replay, and confidentiality. ESP provides data confidentiality and integrity by encrypting the data to be protected and placing the encrypted data in the data part of the IP ESP. Based on security requirements of subscribers, this mechanism can be used to encrypt either a transport-layer segment or an IP data packet. A transport-layer segment includes Transmission Control Protocol (TCP), User Datagram Protocol (UDP), Internet Control Message Protocol (ICMP), and Internet Group Management Protocol (IGMP).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
E-DCH transport format combination indicator	E-TFCI	N/A	N/A	ETSI TS 125 222: "Universal Mobile Telecommunications System (UMTS); Multiplexing and channel coding (TDD)"
European Telecommunications Standards Institute	ETSI	N/A	ETSI (European Telecommunications Standards Institute) is an independent, not-for-profit, standardization organization in the field of information and communications. ETSI supports the development and testing of global technical standards for ICT-enabled systems, applications and services.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
earthquake and tsunami warning system	ETWS	N/A	Earthquake and Tsunami Warning System (ETWS) introduces a means to deliver Warning Notification simultaneously to many mobile users who should evacuate from approaching Earthquake or Tsunami. Mobile user who received Warning Notification is able to know a threat is approaching or already happened nearby. Then the user is able to determine where and when to evacuate according to delivered Warning Notification. Mobile phone is a kind of the closest media for people. This system helps people to prevent from disaster situation or mitigate damage.	ETSI TS 122 168 V8.2.0: "LTE; Earthquake and Tsunami Warning System (ETWS) requirements; Stage 1"

Term	Abbreviation	Synonym	Definition	Reference
evolved universal terrestrial radio access	E-UTRA	N/A	E-UTRA is the air interface of 3rd Generation Partnership Project (3GPP) Long Term Evolution (LTE) upgrade path for mobile networks. It is an acronym for evolved Universal Mobile Telecommunications System (UMTS) terrestrial radio access, also referred to as the 3GPP work item on the Long Term Evolution (LTE) also known as the Evolved Universal Terrestrial Radio Access (E-UTRA) in early drafts of the 3GPP LTE specification. E-UTRAN is the initialism of evolved UMTS terrestrial radio access network and is the combination of E-UTRA, user equipment (UE), and E-UTRAN Node B or evolved NodeB (eNodeB).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
evolved universal terrestrial radio access network	E-UTRAN	Evolved UTRAN	Evolved UTRAN is an evolution of the 3G UMTS radio-access network toward a high-data-rate, low-latency, and packet-optimized radio-access network.	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
error vector magnitude	EVM	N/A	The error vector magnitude or EVM (sometimes also called relative constellation error or RCE) is a measure used to quantify the performance of a digital radio transmitter or receiver. A signal sent by an ideal transmitter or received by a receiver would have all constellation points precisely at the ideal locations, however various imperfections in the implementation (such as carrier leakage, low image rejection ratio, phase noise etc.) cause the actual constellation points to deviate from the ideal locations. Informally, EVM is a measure of how far the points are from the ideal locations.	Wikipedia
Ethernet virtual private line	EVPL	N/A	A service connecting two customer Ethernet ports over a WAN.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
enhanced voice service	EVS	N/A	The enhanced voice service coder consists of the multi-rate audio coder optimized for operation with voice and music/mixed content signals, a source controlled rate scheme including a voice/sound activity detector and a comfort noise generation system, and an error concealment mechanism to combat the effects of transmission errors and lost packets. Jitter buffer management is also provided.	3GPP TS 26.441 version 12.0.0: "Universal Mobile Telecommunications System (UMTS); LTE; EVS Codec General Overview"
enhanced X2 interface	eX2	N/A	Similar to the X2 interface, the eX2 interface is a logical interface between eNodeBs. The difference is that the eX2 interface handles only inter-eNodeB service coordination. X2 and eX2 interfaces can coexist.	Huawei Term
eX2 control plane	eX2-C	N/A	N/A	Huawei Term
eX2 user plane	eX2-U	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
E1	N/A	N/A	A four-wire symmetrical digital transmission path carrying PCM signals at 2048 kbit/s.	3GPP TS 48.014 version 4.0.0: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Base Station System (BSS) - Serving GPRS Support Node (SGSN) interface; Gb Interface Layer 1"
earthing terminal	N/A	grounding terminal	A terminal provided on equipment and intended for the electric connection with the earthing arrangement.	IEV 195-02-31
Easy Macro	N/A	N/A	AAU with a cylinder design for use in urban areas with coverage holes and hotspots.	Huawei Term
effective bandwidth	N/A	N/A	Effective bandwidth is the bandwidth occupied by the transmission bandwidth configuration N_{RB} according to 3GPP specifications.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
electrostatic induction	N/A	N/A	Electrostatic induction, also known as "electrostatic influence" or simply "influence" in Europe and Latin America, is a redistribution of electric charge in an object, caused by the influence of nearby charges.	Wikipedia
emergency channel	N/A	escape channel	The emergency channel refers to that the Service Manager allows unauthorized terminal hosts to access network resources in the post-authentication domain. The emergency channel is enabled only when serious faults occur in the Service Controller, so that network communications remain normal during such faults. The emergency channel automatically disables itself after faults are rectified.	Huawei Term
EMI filter	N/A	N/A	A device that suppresses or reduces the level of EMI/RFI emitted by electrical or electronic equipment.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
encapsulation	N/A	N/A	The technique used by layered protocols in which a layer adds header information to the protocol data unit (PDU) from the layer above. As an example, in Internet terminology, a packet would contain a header from the physical layer, followed by a header from the network layer (IP), followed by a header from the transport layer (TCP), followed by the application protocol data.	O. Jacobsen, D. Lynch, and Interop, Inc., "A Glossary of Networking Terms", RFC 1208, March 1991
encryption	N/A	encipherment	Reversible transformation of data by a cryptographic algorithm to produce a ciphertext, i.e. to hide the information content of the data.	ETSI TS 103 532: "CYBER; Attribute Based Encryption for Attribute Based Access Control"

Term	Abbreviation	Synonym	Definition	Reference
error code	N/A	N/A	The error code element contains the reason why an operation cannot be completed successfully. It is present only in a Return Error component. As with operations, errors may be local or global. These errors and associated parameters are defined in relevant supplementary service specifications.	ITU-T Q.762: "Signalling System No. 7 – ISDN User Part general functions of messages and signals"
Ethernet	N/A	N/A	A 10-Mbit/s standard for LANs, initially developed by Xerox, and later refined by Digital, Intel and Xerox (DIX). All hosts are connected to a coaxial cable where they contend for network access using a Carrier Sense Multiple Access with Collision Detection (CSMA/CD) paradigm.	G. Malkin, "Internet Users' Glossary", RFC1983, August 1996

Term	Abbreviation	Synonym	Definition	Reference
Ethernet private LAN service	N/A	EPLAN service	A type of Ethernet service provided by SDH, PDH, ATM, MPLS, or other server layer networks. This type of service is carried over dedicated bandwidth between multipoint-to-multipoint connections.	Huawei Term
event	N/A	N/A	An event refers to the information that is generated on an NE while the network is running. Such information does not indicate a fault and does not need to be rectified manually. However, it can be used as reference for troubleshooting.	Huawei Term
event-triggered periodic reporting	N/A	N/A	After an event is reported for the first time during measurements for handover, the measurement results associated with the event are reported periodically. This reporting mode is called event-triggered periodical reporting.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
extended cell	N/A	extension cell	A cell that can work beyond the value of the maximum Timing Advance (TA). This gives it a coverage radius of greater than 35 km.	Huawei Term
extended CPRI device	N/A	• CPRI extension device • extended CPRI equipment	A device to aggregate CPRI signals on the CPRI link (e.g., RHUB)	Huawei Term
extension cabinet group	N/A	N/A	The cabinet group except for the basic cabinet group	Huawei Term
External CA	N/A	N/A	An external CA is any CA other than the LiteCA used on an operator's network. It may be a standalone CA deployed by operator or a trusted external third-party CA.	Huawei Term
energy conservation and emission reduction	N/A	N/A	Energy conservation and emission reduction aims to reduce energy waste and exhaust emissions.	Huawei Term

1.7 F

Term	Abbreviation	Synonym	Definition	Reference
fast associated control channel	FACCH	N/A	The FACCH is always paired with a traffic channel. The FACCH is a blank-and-burst channel that operates by stealing bursts from its associated traffic channel. Bursts that carry FACCH data are distinguished from traffic bursts by stealing bits at each end of the midamble. The FACCH is used for in-call signaling, including call disconnect, handover and the later stages of call setup. It has a payload data rate of 9.2 kbit/s when paired with a full-rate channel (FACCH/F) and 4.6 kbit/s when paired with a half-rate channel (FACCH/H). The FACCH uses the same interleaving and multiframe structure as its host TCH.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
forward access channel	FACH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
first article inspection	FAI	N/A	A first article inspection (FAI) is a design verification and design history file and a formal method of providing a reported measurement for each manufactured feature of a part or assembly.	Wikipedia
front administration module	FAM	N/A	The front administration module is part of RNC and consists of a switching subsystem and a service processing subsystem. It is also referred to as the main system of RNC.	Huawei Term
fronthaul aggregation unit	FAU	N/A	Fronthaul aggregation unit (FAU) is a passive multiplexer/demultiplexer used on the AAU or BBU side. It supports standardized colored wavelengths.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
NR basic feature description	FBFD	N/A	N/A	Huawei Term
flow control	FC	N/A	Mechanism that is used to regulate the flow of data between two peer entities	ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview"
fan control board	FCB	N/A	N/A	Huawei Term
Federal Communications Commission	FCC	N/A	The FCC was formed by the Communications Act of 1934 to replace the radio regulation functions of the Federal Radio Commission. The FCC took over wire communication regulation from the Interstate Commerce Commission.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
frequency correction channel	FCCH	N/A	Logical channel that contains the information defining how the resources are allocated in the current MAC frame. Its content changes in general dynamically from frame to frame.	ETSI TS 101 761-1 V1.2.1: "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) Layer; Part 1: Basic Data Transport Functions"
frame check sequence	FCS	N/A	N/A	Huawei Term
frequency diversity	FD	N/A	The signal is transmitted using several frequency channels or spread over a wide spectrum that is affected by frequency-selective fading.	Wikipedia
frequency division duplex	FDD	N/A	Duplex technique where the traffic in each direction of a two-way telecommunications link is carried on two different carriers frequencies each dedicated to the traffic in one direction.	ETSI TR 101 904: "Transmission and Multiplexing (TM); Time Division Duplex (TDD) in Point-to-Multipoint (P-MP) Fixed Wireless Access (FWA) systems; Characteristics and network applications"

Term	Abbreviation	Synonym	Definition	Reference
Fiber Distributed Data Interface	FDDI	N/A	Fiber Distributed Data Interface (FDDI) is a standard for data transmission in a local area network. It uses optical fiber as its standard underlying physical medium, although it was also later specified to use copper cable, in which case it may be called CDDI (Copper Distributed Data Interface), standardized as TP-PMD (Twisted-Pair Physical Medium-Dependent), also referred to as TP-DDI (Twisted-Pair Distributed Data Interface).	Wikipedia
frequency domain equalization	FDE	N/A	With frequency domain equalization, the uplink receiver of the NodeB performs frequency-domain equalization on HSUPA E-DPDCH. This suppresses inter-path interference increases the SNR on the E-DPDCH, improving the uplink HSUPA capacity.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
forward defect indication	FDI	N/A	A packet generated by and sent downstream from the first node detecting a defect. It includes fields to indicate the nature of the defect and its location. Its primary purpose is to suppress alarms being raised at affected client LSP layers.	Huawei Term
frequency division multiplexing	FDM	N/A	Frequency-division multiplexing (FDM) is a technique by which the total bandwidth available in a communication medium is divided into a series of non-overlapping frequency bands, each of which is used to carry a separate signal.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Frequency Division Multiple Access	FDMA	N/A	Multiple access technology that separates users by putting each traffic channel on a discrete frequency band.	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"
fractional dedicated physical channel	F-DPCH	N/A	N/A	ETSI TR 125 903: "Universal Mobile Telecommunications System (UMTS); Continuous connectivity for packet data users"
frequency diversity scheduling	FDS	N/A	Scheduling in which data is transmitted in multiple bands, based on the channel quality difference between frequency bands, to obtain frequency diversity gains	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
frame delay variation	FDV	N/A	A measurement of the variation in delay of packets transmitted between two MEPs that belong to the same CoS instance on a point-to-point Ethernet connection.	Huawei Term
fast Ethernet	FE	N/A	Any Ethernet-compliant network that supports a transmission rate of 100 Mbit/s. The Fast Ethernet is 10 times faster than 10BaseT, and inherits the frame format, MAC addressing scheme, MTU, and so on. Fast Ethernet is built on the IEEE802.3 standard, and it uses the following three types of transmission media: 100BASE-T4 (4 pairs of phone twisted-pair cables), 100BASE-TX (2 pairs of data twisted-pair cables), and 100BASE-FX (2-core optical fibers).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
forward error correction	FEC	N/A	Method of error detection and correction in which redundant information is sent with a data payload in order to allow the receiver to reconstruct the original data if an error occurs during transmission.	ETSI TS 103 311-2: "Integrated broadband cable telecommunication networks (CABLE); Fourth Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer"
frame error rate	FER	frame erasure rate	Frame error rate, corresponding to the ratio of erroneous frame including at least one erroneous bit to the total number of frames in the observation period.	ETSI TS 102 584: "Digital Video Broadcasting (DVB); DVB-SH Implementation Guidelines"
fast failure detection	FFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
fast Fourier transform	FFT	N/A	A fast Fourier transform (FFT) is an algorithm that computes the discrete Fourier transform (DFT) of a sequence, or its inverse (IDFT). Fourier analysis converts a signal from its original domain (often time or space) to a representation in the frequency domain and vice versa.	Wikipedia
8-port FE or 2-port electronic GE interface unit REV:a	FG2a	N/A	N/A	Huawei Term
12-port FE or 4-port electronic GE interface unit REV:c	FG2c	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
frequency hopping	FH	N/A	Frequency hopping (FH) is a well-known technique that is used in radars, ranging transponders, and communications links, for similar reasons. The basic idea is that a relatively narrow-band radio is re-tuned rapidly, so that a set of channels at different radio frequencies are used in succession.	ETSI TR 103 181-1: "Short Range Devices (SRD) using Ultra Wide Band (UWB); Technical Report Part 1: UWB signal characteristics and overview CEPT/ECC and EC regulation"

Term	Abbreviation	Synonym	Definition	Reference
frequency hopping bus	FH-BUS	N/A	When baseband frequency hopping and antenna hopping are enabled, a large amount of data exchange is performed between different TRXs in the cabinet. Frequency hopping bus is introduced to facilitate the data exchange. When the antenna hopping function is realized, each TRX sends the TX frequency, TX ID, and data of the current frame to the frequency hopping bus during timeslot interval. The TRX receives the corresponding frequency and data from the frequency hopping bus, and then configures the RF based on the frequency. Then, the RF sends the data to the MS over the Um interface.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
first in first out	FIFO	- first-in first-out - first in, first out	Queuing discipline in which entities in a queue leave the queue in the same order in which they arrive	ETSI TR 170 002 V3.1.1: "Project MESA; Service Specification Group - Services and Applications; Definitions, symbols and abbreviations"
frame loss ratio	FLR	N/A	The percentage of speech frames not delivered to the decoder. FLR includes speech frames that are not received in time to be used for decoding.	ETSI TS 126 114: "Universal Mobile Telecommunications System (UMTS); LTE; 5G; IP Multimedia Subsystem (IMS); Multimedia telephony; Media handling and Interaction"
fault management	FM	N/A	N/A	Huawei Term
forward monitoring	FM	N/A	N/A	Huawei Term
fan monitoring unit	FMU	N/A	N/A	Huawei Term
fan environment monitoring unit type A	FMUA	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
frame number	FN	N/A	N/A	ETSI EN 300 396-4 V1.2.1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 4: Type 1 repeater air interface"
first order	FO	N/A	In First-Order (FO) state, the compressor has detected and stored the static fields (such as IP addresses and port numbers) on both sides of the connection. The compressor is also sending dynamic packet field differences in FO state. Thus, FO state is essentially static and pseudo-dynamic compression.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
frequency offset	FO	N/A	When the transmit source of the radio wave is far from the receive party, the wavelength is long and the frequency is low. When the transmit source is close to the receive party, the wavelength is short and the frequency is high. The BTS carrying the serving cell can calculate the frequency offset (indicated by Δf) through the signals transmitted by the moving MS. If the absolute value of Δf is great, you can infer that the MS is moving fast. If Δf is a positive number, you can infer that the MS is moving toward the BTS. If Δf is a negative number, you can infer that the MS is moving away from the BTS.	Huawei Term
NR optional feature description	FOFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Frame Protocol	FP	N/A	A protocol used in UMTS on the Iur and Iub interfaces to frame channels supported between the serving radio network controller (SRNC) and the User Equipment (UE).	Huawei Term
frame protocol multiplexing	FP MUX	N/A	Frame processing multiplexing (FP MUX) encapsulates multiple FP PDUs into one FP MUX packet, reducing the UDP/IP/Layer 2/Layer 1 header transmission overhead and improving transmission efficiency.	Huawei Term
fractional power control	FPC	N/A	A power control technique used to partly compensate for path loss	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
field-programmable gate array	FPGA	N/A	A field-programmable gate array (FPGA) is an integrated circuit designed to be configured by a customer or a designer after manufacturing – hence the term "field-programmable". The FPGA configuration is generally specified using a hardware description language (HDL), similar to that used for an application-specific integrated circuit (ASIC). Circuit diagrams were previously used to specify the configuration, but this is increasingly rare due to the advent of electronic design automation tools.	Wikipedia
frequency range	FR	N/A	The range of operating frequencies over which the equipment can be adjusted.	ETS 300 328: "Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz band; Harmonised Standard for access to radio spectrum"

Term	Abbreviation	Synonym	Definition	Reference
frame relay	FR	N/A	Frame relay is a method of transporting High-Level Data Link Control (HDLC) frames within a network whereby the network nodes provide error detection without retransmission. Retransmissions are done at the endpoints of the network only.	ITU-T Rec. G.765 Appendix I: "A Guide to PCME"
frequency selective isolating and penetrating	FreSIP	N/A	Frequency selective isolating and penetrating (FreSIP) is an antenna technology exclusively innovated by Huawei. In this technology, antenna elements are redesigned based on metamaterials to create an open-air-like propagation environment, thereby achieving a penetration effect.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
fast reroute	FRR	N/A	Fast Reroute is an MPLS (Multiprotocol Label Switching) and IP resiliency technology to provide fast traffic recovery upon link or router failures for mission critical services. Upon any single link or node failures, it could be able to recover impacted traffic flows in the level of 50 ms.	Wikipedia
field replaceable unit	FRU	N/A	An FRU is defined to be a spare part or component that can be substituted / supplanted or be used to substitute / supplant an existing part or component in order to rectify a fault or any other issue which is identified by the user or technician or a diagnostic program.	3GPP TS 32.690 version 9.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Inventory Management (IM); Requirements"

Term	Abbreviation	Synonym	Definition	Reference
frequency-shift keying	FSK	N/A	Frequency-shift keying (FSK) is a frequency modulation scheme in which digital information is transmitted through discrete frequency changes of a carrier signal.	Wikipedia
frame sequence number	FSN	N/A	Frame sequencing uses a 3 bit frame number plus a 1 bit reset flag. Frame sequencing appears in AI-frames and RR-frames (i.e. only used for acknowledged data transfer).	TETRA ETS 300 393-2 ed.2: "Terrestrial Trunked Radio (TETRA); Packet Data Optimized (PDO); Part 2: Air Interface (AI)"
forward sequence number	FSN	N/A	M2PA sequence number of the User Data message being sent. The FSN and BSN values range from 0 to 16,777,215.	T. George, B. Bidulock, OpenSS7, R. Dantu, University of North Texas, H. Schwarzbauer, Siemens, K. Morneault, and Cisco Systems, "Signaling System 7 (SS7) Message Transfer Part 2 (MTP2) - User Peer-to-Peer Adaptation Layer (M2PA)", RFC 4165, September 2005

Term	Abbreviation	Synonym	Definition	Reference
frequency selective scheduling	FSS	N/A	Frequency selective scheduling gives an opportunity to benefit from channel fading. Since sub-bands fade individually, the scheduler can select which sub-band to use given their quality measure.	IEEE: "LTE frequency selective scheduling performance and improvements assessed by measurements"
frequency switched transmit diversity	FSTD	N/A	A technique in which some of multiple antennas (if configured) are selected in a specific frequency order for transmission.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
File Transfer Protocol	FTP	N/A	The File Transfer Protocol (FTP) is a standard communication protocol used for the transfer of computer files from a server to a client on a computer network. FTP is built on a client-server model architecture using separate control and data connections between the client and the server. FTP users may authenticate themselves with a clear-text sign-in protocol, normally in the form of a username and password, but can connect anonymously if the server is configured to allow it. For secure transmission that protects the username and password, and encrypts the content, FTP is often secured with SSL/TLS (FTPS) or replaced with SSH File Transfer Protocol (SFTP).	Wikipedia
File Transfer Protocol server	FTPS	N/A	A software or hardware server that responds to File Transfer Protocol.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
fixed wireless access	FWA	N/A	Fixed wireless access (FWA): wireless access application in which the location of the end-user termination and the network access point to be connected to the end-user are fixed.	ETSI TR 102 453-1 V1.1.1: "Converged Fixed-Nomadic Broadband Wireless Access (BWA); Part 1: Frequencies above 3,4 GHz - System reference document"
fan	N/A	N/A	A fan is a device that creates a current of air by movement of a surface or surfaces mainly for heat dissipation.	Huawei Term
fast fading	N/A	• small-scale fading • short-term fading	Fast fading occurs when the coherence time of the channel is small relative to the delay requirement of the application. In this case, the amplitude and phase change imposed by the channel varies considerably over the period of use.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
fault tolerance	N/A	N/A	Extent to which a functional unit will continue to operate at a defined performance level even though one or more of its components has failed.	ETSI TR 101 971: "Access and Terminals (AT); IP Cable Services for Multimedia Broadband Cable Networks; Availability and Reliability"
feature	N/A	N/A	Features refer to product software capabilities that have specific business value for customers. They are classified into basic, optional, and trial features. Basic features are included in the basic product package for sale and are generally not under license control. Optional features can be purchased as required and are under license control. Trial features are not for sale in the current version but customers may try them for free.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
feed line	N/A	• feedline • feeder	In a radio antenna, the feed line (feedline), or feeder, is the cable or other transmission line that connects the antenna with the radio transmitter or receiver. In a transmitting antenna, it feeds the radio frequency (RF) current from the transmitter to the antenna, where it is radiated as radio waves. In a receiving antenna it transfers the tiny RF voltage induced in the antenna by the radio wave to the receiver.	Wikipedia
feeder	N/A	N/A	A peripheral route or branch from a main line or trunk line. In radio engineering, a feeder connects radio equipment to an antenna.	Wikipedia
firewall	N/A	N/A	A functional entity which blocks or permits the flow of various traffic types based on a set of policy rules and definitions.	3GPP TS 22.278: "Service requirements for the Evolved Packet System (EPS)"

Term	Abbreviation	Synonym	Definition	Reference
Flexible Dense Beam	N/A	N/A	Flexible Dense Beam is an enhancement of original CSI-RS for BM beams, including beam densification and flexible sweeping. In beam densification, the number of CSI-RS for BM beams is increased to obtain more accurate CSI-RS for BM beams targeted at UEs. In this way, coverage and throughput gains are obtained. In flexible sweeping, unnecessary CSI-RS for BM beam sweeping is reduced to offset the increase in time-frequency resource overheads caused by an increase in the number of beams.	Huawei Term
floor	N/A	N/A	The authority assigned by the PTT system to speak in a PTT call.	3GPP TS 22 179: "Floor control: An arbitration system in an MCPTT Service that determines who has the authority to transmit (talk) at a point in time during an MCPTT call"

Term	Abbreviation	Synonym	Definition	Reference
forced switch	N/A	N/A	A switch action initiated by an operator command. It switches the extra traffic signal, normal traffic signal, or the null signal to the protection transport entity, unless an equal or higher priority switch command is in effect. In the case of forced switching extra traffic or null signal to the protection transport entity, a normal traffic signal that is present on the protection transport entity is transferred to and selected from its working transport entity. For the case where an APS protocol is in use, an SF on the protection transport entity (over which the APS signal is routed) has priority over the forced switch.	ITU-T G.808: "Terms and definitions for network protection and restoration"

Term	Abbreviation	Synonym	Definition	Reference
free-run mode	N/A	free running mode	An operating condition of a clock, the output signal of which is strongly influenced by the oscillating element and not controlled by servo phase-locking techniques. In this mode, the clock has never had a network reference input, or the clock has lost external reference and has no access to stored data, that could be acquired from a previously connected external reference. Free-run begins when the clock output no longer reflects the influence of a connected external reference, or transition from it. Free-run terminates when the clock output has achieved lock to an external reference.	ETSI EN 300 462-1-1: "Transmission and Multiplexing (TM); Generic requirements for synchronization networks; Part 1-1: Definitions and terminology for synchronization networks"

Term	Abbreviation	Synonym	Definition	Reference
frequency band	N/A	N/A	Interval in frequency, group of consecutive QMF subbands.	3GPP TS 26.402: "General audio codec audio processing functions; Enhanced aacPlus general audio codec; Additional decoder tools"
frequency-selective fading	N/A	N/A	In multipath propagation, as signals on different paths have different propagation delay due to signal reflection, diffraction, and scattering, the pulse widths of received signals are broadened, causing delay spread. As a result, the fading characteristics of signals on different frequencies are different, which is called frequency-selective fading.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
frequency raster	N/A	global frequency raster	The global frequency raster defines a set of RF reference frequencies F_{REF} . The RF reference frequency is used in signalling to identify the position of RF channels, SS blocks and other elements.	3GPP TS 38.104: "NR; Base Station (BS) radio transmission and reception"
frequency synchronization	N/A	N/A	Frequency synchronization is a process of adjusting the relative frequency of one or more signals based on the frequency of a reference signal.	Huawei Term
FRNction al ATM	N/A	N/A	A transmission method implemented at the TC sublayer of the physical layer. With this method, ATM cells are transmitted through some of the 32 E1/T1 timeslots. ATM cells are mapped to some of the E1/T1 timeslots, instead of all of the timeslots. At the peer end, the ATM cell stream is recovered from these E1/T1 timeslots. The timeslots that are unavailable for ATM cell transmission can transmit other information.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
fronthaul	N/A	N/A	Fronthaul refers to transmission between the BBU and RF modules.	Huawei Term
Full Rate	N/A	N/A	Full Rate (FR, GSM-FR, GSM 06.10, or sometimes simply GSM) was the first digital speech coding standard used in the GSM digital mobile phone system. It uses linear predictive coding (LPC). The bit rate of the codec is 13 kbit/s, or 1.625 bit/s/audio sample (often padded out to 33 bytes/20 ms or 13.2 kbit/s).	Wikipedia
Full-rate version 1	N/A	N/A	FR data (with the rate of 13 kbit/s).	Huawei Term
Full-rate version 2	N/A	N/A	EFR data (with the rate of 12.2 kbit/s).	Huawei Term
Full-rate version 3	N/A	N/A	FAMR data (with the rate ranging from 4.75 to 12.2 kbit/s).	Huawei Term
frequency	N/A	N/A	A frequency is within a frequency band and presented by a number. It indicates a specific frequency in terms of the number of signal cycles per time unit.	Huawei Term

1.8 G

Term	Abbreviation	Synonym	Definition	Reference
Galileo satellite navigation system	Galileo	N/A	Galileo is a global navigation satellite system (GNSS) that went live in 2016, created by the European Union through the European Space Agency (ESA), operated by the European Union Agency for the Space Programme (EUSPA), headquartered in Prague, Czech Republic, with two ground operations centres in Fucino, Italy, and Oberpfaffenhofen, Germany. The €10 billion project is named after the Italian astronomer Galileo Galilei.	Wikipedia
GSM antenna and TMA control module	GATM	N/A	A module that controls the RET antenna and feeds current to the TMA.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
gigabit	Gb	N/A	The gigabit is a multiple of the unit bit for digital information or computer storage. The prefix giga (symbol G) is defined in the International System of Units (SI) as a multiplier of 10 ⁹ (1 billion, short scale).	Wikipedia
Gigabit Ethernet	GbE	• GE • 1 GigE	In computer networking, Gigabit Ethernet (GbE or 1 GigE) is the term applied to transmitting Ethernet frames at a rate of a gigabit per second.	Wikipedia
GSM BSS feature description	GBFD	N/A	N/A	Huawei Term
guaranteed bit rate	GBR	N/A	The GBR denotes the bit rate that can be expected to be provided by a GBR bearer.	ETSI TS 123 401 V10.11.0: "LTE; General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access"

Term	Abbreviation	Synonym	Definition	Reference
GSM base transceiver station	GBTS	N/A	A GBTS is a base transceiver station (BTS) applying only to GSM networks. The operation and maintenance (O&M) of the GBTS is implemented by its base station controller (BSC), instead of the element management system (EMS). This mode of O&M is called LegacyOM. The GBTS uses GTMU as the main control board.	Huawei Term
General Clock Unit with GPS REV:a	GCGa	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
generic cell rate algorithm	GCRA	N/A	The generic cell rate algorithm (GCRA) is a leaky bucket-type scheduling algorithm for the network scheduler that is used in Asynchronous Transfer Mode (ATM) networks. It is used to measure the timing of cells on virtual channels (VCs) and or Virtual Paths (VPs) against bandwidth and jitter limits contained in a traffic contract for the VC or VP to which the cells belong.	Wikipedia
geometric dilution of precision	GDOP	N/A	N/A	Huawei Term
GSM/EDGE radio access network	GERAN	- GSM/EDGE RAN - GSM EDGE radio access network	GERAN is a conceptual term identifying that part of the network which consists of BSCs and BTSs between A/Gb or Iu and Um interfaces.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
guaranteed flow bit rate	GFBR	N/A	N/A	ETSI TS 129 061 V15.3.0: "LTE; Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN)"
Generic Framing Procedure	GFP	N/A	A generic framing procedure (GFP) provides a generic mechanism to adapt traffic from higher-layer client signals over a transport network. Client signals may be protocol data unit-(PDU)-oriented (such as Internet protocol/ point-to-point protocol [IP/PPP] or Ethernet media access control [MAC]) or block-code oriented constant bit rate stream (such as fiber channel or enterprise systems connection/single-byte command code sets connection [ESCON/SBCON]).	ITU-T G.7041/ Y.1303: "Generic framing procedure"

Term	Abbreviation	Synonym	Definition	Reference
gateway GPRS support node	GGSN	N/A	The Gateway GPRS Support Node (GGSN) is the node that is accessed by the packet data network due to evaluation of the PDP address. It contains routing information for attached GPRS users. The routing information is used to tunnel N-PDUs to the MS's current point of attachment, i.e., the Serving GPRS Support Node. The GGSN may request location information from the HLR via the optional Gc interface. The GGSN is the first point of PDN interconnection with a GSM PLMN supporting GPRS (i.e., the Gi reference point is supported by the GGSN).	3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
geographic information system	GIS	N/A	A geographic information system (GIS) is a conceptualized framework that provides the ability to capture and analyze spatial and geographic data. GIS applications (or GIS apps) are computer-based tools that allow the user to create interactive queries (user-created searches), store and edit spatial and non-spatial data, analyze spatial information output, and visually share the results of these operations by presenting them as maps.	Wikipedia
gateway mobile location center	GMLC	N/A	A functional entity that allows external LCS Clients to request real-time information about a Mobile Station.	3GPP TS 23.078: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Customised Applications for Mobile network Enhanced Logic (CAMEL) Phase 4; Stage 2 (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
Gaussian Minimum Shift Keying	GMSK	Gaussian Filtered Minimum Shift Keying	A modulation type as defined by 3GPP TS 45.004 clause 2. For GMSK modulation, a symbol is equivalent to a bit. A particular bit period within a timeslot is referenced by a bit number (BN), with the first bit period being numbered 0, and the last (1/4) bit period being numbered 156, in case of non-integer symbol timeslot.	3GPP TR 45.002: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; GSM/EDGE Multiplexing and multiple access on the radio path (Release 16)"
Greenwich Mean Time	GMT	N/A	Historically standard time for all international applications, now superseded by UTC	ETSI TS 102 693 V1.1.2: "Digital Audio Broadcasting (DAB); Encapsulation of DAB Interfaces (EDI)"
gateway network element	GNE	N/A	An NE that serves as a gateway for other NEs to communicate with a network management system.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
global navigation satellite system	GNSS	N/A	A global navigation satellite system (GNSS) consists of three functional elements: space segment (satellites), user segment (receivers), and control segment (maintenance etc.). The GNSS receiver calculates its own position based on the received time differences for several satellites. GNSSs include Global Positioning System (GPS) and GALILEO.	3GPP TS 23.271: "Functional stage 2 description of Location Services (LCS)"
grade of service	GoS	N/A	In telecommunication engineering, and in particular teletraffic engineering, the quality of voice service is specified by two measures: the grade of service (GoS) and the quality of service (QoS). Grade of service is the probability of a call in a circuit group being blocked or delayed for more than a specified interval, expressed as a vulgar fraction or decimal fraction.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
2-port packet over optical GE Ethernet interface unit REV:a	GOUa	N/A	N/A	Huawei Term
4-port packet over GE optical interface unit REV:c	GOUc	N/A	N/A	Huawei Term
guard period	GP	N/A	In TDMA, each user's timeslot ends with a guard period, to avoid data loss and to reduce interference to the following user, caused by propagation delay.	Wikipedia
gigabit passive optical network	GPON	N/A	G.984, commonly known as GPON (gigabit passive optical network), is a standard for passive optical networks (PON) published by the ITU-T. It is commonly used to implement the outermost link to the customer (Last kilometer or Last mile) of fiber-to-the-premises (FTTP) services.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
general packet radio service	GPRS	N/A	General packet radio service (GPRS) is a packet oriented mobile data standard on the 2G and 3G cellular communication network's global system for mobile communications (GSM). GPRS was established by European Telecommunications Standards Institute (ETSI) in response to the earlier CDPD and i-mode packet-switched cellular technologies. It is now maintained by the 3rd Generation Partnership Project (3GPP). GPRS is typically sold according to the total volume of data transferred during the billing cycle, in contrast with circuit switched data, which is usually billed per minute of connection time, or sometimes by one-third minute increments. Usage above the GPRS bundled data cap may be charged per MB of data, speed limited, or disallowed.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Global Positioning System	GPS	N/A	The Global Positioning System (GPS) consists of three functional elements: Space Segment (satellites), User Segment (receivers), and Control Segment (maintenance etc.). The GPS receiver calculates its own position based on the received time differences for several satellites.	3GPP TS 23.171: "Location Services (LCS); Functional description; Stage 2 (UMTS)"
Generic Routing Encapsulation	GRE	N/A	It is based on the Internet and is used for encapsulating IP datagrams tunneled through the Internet. GRE serves as a Layer 3 tunneling protocol and provides a tunnel for transparently transmitting data packets.	Huawei Term
Global Synchronization Channel Number	GSCN	N/A	N/A	3GPP TS 38.104: "NR; Base Station (BS) radio transmission and reception"

Term	Abbreviation	Synonym	Definition	Reference
Global System for Mobile Communications	GSM	2G	The Global System for Mobile Communications (GSM) is a standard developed by the European Telecommunications Standards Institute (ETSI) to describe the protocols for second-generation (2G) digital cellular networks used by mobile devices such as mobile phones and tablets. It was first deployed in Finland in December 1991. By the mid-2010s, it became a global standard for mobile communications achieving over 90% market share, and operating in over 193 countries and territories.	Wikipedia
global title	GT	N/A	A global title (GT) is an address used in the SCCP protocol for routing signaling messages on telecommunications networks. In theory, a global title is a unique address which refers to only one destination, though in practice destinations can change over time.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
GSM transmission and timing and management unit	GTMU	N/A	N/A	Huawei Term
GPRS Tunneling Protocol	GTP	N/A	A group of IP-based communications protocols used to carry general packet radio service (GPRS) within wireless networks. In 3GPP architectures, GTP and Proxy Mobile IPv6 based interfaces are specified on various interface points.	Wikipedia
GPRS Tunneling Protocol-Control Plane	GTP-C	N/A	GTP-C is used within the GPRS core network for signaling between gateway GPRS support nodes (GGSN) and serving GPRS support nodes (SGSN). This allows the SGSN to activate a session on a user's behalf (PDP context activation), to deactivate the same session, to adjust quality of service parameters, or to update a session for a subscriber who has just arrived from another SGSN.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
GPRS Tunneling Protocol-User Plane	GTP-U	N/A	GPRS Tunneling Protocol (GTP) is a group of IP-based communications protocols used to carry general packet radio service (GPRS) within GSM, UMTS and LTE networks. In 3GPP architectures, GTP and Proxy Mobile IPv6 based interfaces are specified on various interface points. GTP can be decomposed into separate protocols, GTP-C, GTP-U and GTP'. GTP-U is used for carrying user data within the GPRS core network and between the radio access network and the core network. The user data transported can be packets in any of IPv4, IPv6, or PPP formats.	Wikipedia
generic traffic shaping	GTS	N/A	A traffic control measure that proactively adjusts the output speed of the traffic. This is to adapt the traffic to network resources that can be provided by the downstream router to avoid packet discarding and congestion.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
globally unique AMF identifier	GUAMI	N/A	The globally unique AMF identifier (GUAMI) shall be constructed from the MCC, MNC and AMF identifier (AMFI).	ETSI TS 123 003 V15.10.0: "LTE; 5G; Numbering, addressing and identification"
graphical user interface	GUI	N/A	A user interface that supports graphical objects, symbols and windows, and uses direct manipulation for the control of the graphical objects. They may also support textual displays.	ETSI EG 201 024: "Human Factors (HF); User interface design principles for the Telecommunications Management Network (TMN) applicable to the "G" Interface"
globally unique MME identifier	GUMMEI	N/A	The Globally Unique MME Identifier (GUMMEI) shall be constructed from the MCC, MNC and MME Identifier (MMEI).	3GPP TS 23.003 V17.2.0: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Numbering, addressing and identification; (Release 17)"

Term	Abbreviation	Synonym	Definition	Reference
globally unique temporary identity	GUTI	N/A	The purpose of the GUTI is to provide an unambiguous identification of the UE that does not reveal the UE or the user's permanent identity in the Evolved Packet System (EPS). It also allows the identification of the MME and network. It can be used by the network and the UE to establish the UE's identity during signalling between them in the EPS. See 3GPP TS 23.401 for more details.	ETSI TS 123 003 V15.10.0: "LTE; 5G; Numbering, addressing and identification"
gateway	GW	N/A	An intermediate system (interface, relay) that attaches to two (or more) computer networks that have similar functions but dissimilar implementations and that enables either one-way or two-way communication between the networks.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007

Term	Abbreviation	Synonym	Definition	Reference
G interface	N/A	N/A	An interface between VLRs. When a UE moves from one VLR service area to another VLR service area, the UE initiates a location update. The current VLR requests the IMSI and authentication parameter group of the UE from the original VLR. The message interaction between the VLRs is performed through the G interface. The G interface is a standard protocol interface. It uses the E1 physical link and MAP protocol.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
G.711	N/A	N/A	G.711 is a narrowband audio codec originally designed for use in telephony that provides toll-quality audio at 64 kbit/s. G.711 passes audio signals in the range of 300–3400 Hz and samples them at the rate of 8,000 samples per second, with the tolerance on that rate of 50 parts per million (ppm). Non-uniform (logarithmic) quantization with 8 bits is used to represent each sample, resulting in a 64 kbit/s bit rate. There are two slightly different versions: μ -law, which is used primarily in North America and Japan, and A-law, which is in use in most other countries outside North America.	Wikipedia
gateway address	N/A	N/A	The gateway address (or default gateway) is a router interface connected to the local network that sends packets out of the local network. The gateway has a physical and a logical address.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Gb interface	N/A	N/A	Interface between an SGSN and a BSS	ETSI TR 102 491: "Electromagnetic compatibility and Radio spectrum Matters (ERM); TETRA Enhanced Data Service (TEDS); System reference document"
gNodeB	N/A	gNB	Node providing NR user plane and control plane protocol terminations towards the UE, and connected via the NG interface to the 5GC.	3GPP TS 38.300: "NR; NR and NG-RAN Overall Description; Stage 2"
grant-free	N/A	N/A	Grant-free means that once a base station activates an uplink grant to a UE, the UE can determine whether to send service data within a specified period based on the preconfigured resources in the uplink grant before receiving deactivation notification.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
group call	N/A	N/A	A communication in which several MSs can receive, but at most one may be allowed to transmit on a radio channel. Examples of group calls are those established for the voice group call service (VGCS, see 3GPP TS 43.068)	3GPP TS 43.022: "Functions related to Mobile Station (MS) in idle mode and group receive mode"
Gs interface	N/A	N/A	An interface between SGSN and MSC/VLR. This interface is optional and is used only for signaling transmission. It uses BSSAP+ to implement functions such as combined mobility management and paging, and uses No.7 signaling for transmission.	Huawei Term
guard bandwidth	N/A	N/A	Guard bandwidth is a part of the out-of-band bandwidth adjacent to the channel bandwidth.	Huawei Term

1.9 H

Term	Abbreviation	Synonym	Definition	Reference
High-frequency AAU	HAAU	N/A	AAU that can work in mmWave bands. It is referred to as HAAU in Huawei.	Huawei Term
hybrid automatic repeat request	HARQ	N/A	Hybrid automatic repeat request (hybrid ARQ or HARQ) is a combination of high-rate forward error correction (FEC) and automatic repeat request (ARQ) error-control. In standard ARQ, redundant bits are added to data to be transmitted using an error-detecting (ED) code such as a cyclic redundancy check (CRC). Receivers detecting a corrupted message will request a new message from the sender. In Hybrid ARQ, the original data is encoded with an FEC code, and the parity bits are either immediately sent along with the message or only transmitted upon request when a receiver detects an erroneous message.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Happy Bit Rate	HBR	N/A	HBR is the throughput expected by the user. Operators configure different HBRs for UEs with different priorities on the RNC side. When the data rate of a UE reaches the HBR, the HSPA scheduling function reduces the scheduling priority of the UE.	Huawei Term
hierarchical cell structure	HCS	N/A	Hierarchical cell structure ("HCS") used in mobile telecommunication means splitting of cells. This type of cell structure allows the network to effectively use the geographical area and serve an increasing population.	Wikipedia
harmonized communication and sensing	HCS	N/A	Harmonized communication and sensing (HCS) is a new scenario proposed by Huawei based on both Massive Machine-Type Communications (mMTC) and Ultra-Reliable and Low-Latency Communications (URLLC) because some applications require both mMTC and URLLC capabilities.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
high-density bipolar of order 3	HDB3	N/A	N/A	ETSI EN 300 417-5-1 V1.2.1: "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 5-1: Plesiochronous Digital Hierarchy (PDH) path layer functions"
High-Level Data Link Control	HDLC	• High-level Data Link Control • Hierarchical Data Link Control	High-Level Data Link Control (HDLC) is a bit-oriented code-transparent synchronous data link layer protocol developed by the International Organization for Standardization (ISO). The standard for HDLC is ISO/IEC 13239:2002.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
high-speed digital subscriber line	HDSL	high-bitrate digital subscriber line	High-speed digital subscriber line (HDSL) is a telecommunications protocol standardized in 1994. It was the first digital subscriber line (DSL) technology to use a higher frequency spectrum over copper, twisted pair cables. HDSL was developed to transport DS1 services at 1.544 Mbit/s and 2.048 Mbit/s over telephone local loops without a need for repeaters. Successor technology to HDSL includes HDSL2 and HDSL4, proprietary SDSL, and G.SHDSL.	Wikipedia
hybrid dynamic spectrum sharing	HDSS	N/A	Hybrid dynamic spectrum sharing (HDSS) allows LTE and NR cells to share the same spectrum resources. When HDSS is enabled, the bandwidth of the NR cell is greater than that of the LTE cell, and the shared spectrum is equal to the configured bandwidth of the LTE cell.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
home environment	HE	N/A	Responsible for overall provision and control of the personal service environment of its subscribers	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
HUAWEI Electronic Document Explorer	HedEx	N/A	N/A	Huawei Term
home eNodeB	HeNB	N/A	A HeNB is a piece of customer-premises equipment that connects a 3GPP UE over E-UTRAN wireless air interface to a mobile operator's network using a broadband IP backhaul.	3GPP TS 22.220: "Service requirements for Home Node B (HNB) and Home eNode B (HeNB)"
heat exchange unit type A	HEUA	N/A	An electronic circuit that monitors fans and reports alarms.	Huawei Term
hyper frame number	HFN	N/A	The MSBs of both the ciphering sequence numbers (COUNT-C) and integrity sequence numbers (COUNT-I), for the ciphering and integrity protection algorithms, respectively, are called the Hyper Frame Numbers (HFN).	3GPP TS 25.331: "Universal Mobile Telecommunications System (UMTS); Radio Resource Control (RRC); Protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
hard handover	HHO	N/A	Hard handover is a category of handover procedures where all the old radio links in the UE are abandoned before the new radio links are established.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
high interference indication	HII	N/A	The HII is a bitmap used to indicate high interference with each bit representing one PRB. If a bit is 1, the transmit power on the corresponding PRB is high, possibly causing high interference. If a bit is 0, the transmit power on the corresponding PRB is not high, and no high interference will be caused.	Huawei Term
High Speed Internet	HIS	N/A	N/A	ETSI GR F5G 002: "Fifth Generation Fixed Network (F5G); F5G Use Cases"

Term	Abbreviation	Synonym	Definition	Reference
home location register	HLR	N/A	The home location register (HLR) is a central database that contains details of each mobile phone subscriber that is authorized to use the GSM core network. There can be several logical, and physical, HLRs per public land mobile network (PLMN), though one international mobile subscriber identity (IMSI)/MSISDN pair can be associated with only one logical HLR (which can span several physical nodes) at a time.	Wikipedia
hash-based message authentication code	HMAC	N/A	Message authentication algorithm, based on either SHA-1 or MD5 hash and defined in IETF RFC 2104.	ETSI TS 101 909-11 V1.2.1: "Digital Broadband Cable Access to the Public Telecommunications Network; IP Multimedia Time Critical Services; Part 11: Security"

Term	Abbreviation	Synonym	Definition	Reference
handover	HO	N/A	The process in which the radio access network changes the radio transmitters or radio access mode or radio system used to provide the bearer services, while maintaining a defined bearer service QoS.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
home public land mobile network	HPLMN	N/A	N/A	Huawei Term
hierarchical QoS	HQoS	Hierarchical Quality of Service	A type of QoS that controls user traffic and schedules the traffic according to the priority of services. HQoS offers an advanced traffic statistics function, with which a network administrator can monitor the bandwidth each service occupies, analyze the traffic, and allocate bandwidth for services accordingly.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
High Rate Packet Data	HRPD	N/A	A packet data protocol in the 3G mobile communications network based on CDMA2000. It is also known as TIA/EIA IS-856 or 1xEV-DO.	3GPP TS 36.133: "Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management; "
high-power remote radio unit	hRRU	N/A	High-power remote radio unit (hRRU) is an RF unit for LampSite base stations and can be used only in the LampSite Sharing solution. Its physical parts are the same as those of an RRU for macro base stations. In LampSite Sharing scenarios, module deployment is subject to limited space, and low-power pRRUs cannot provide sufficient coverage for the traffic volume produced by a large number of UEs. The hRRU features high power and wide coverage, meeting the solution's requirements.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
high speed circuit switched data	HSCSD	N/A	High Speed Circuit Switched Data (HSCSD) is an enhancement to CSD designed to provide higher data rates by means of more efficient channel coding and/or multiple (up to 4) time slots. It requires the time slots being used to be fully reserved to a single user. A transfer rate of up to 57.6 kbit/s (i.e., 4 x 14.4 kbit/s) can be reached, or even 115 kbit/s if a network allows combining 8 slots instead of just 4.	Wikipedia
High Speed Downlink Packet Access	HSDPA	N/A	High Speed Downlink Packet Access (HSDPA) is an enhanced 3G (third-generation) mobile communications protocol in the High-Speed Packet Access (HSPA) family. HSDPA is also known as 3.5G, 3G+, or Turbo 3G. It allows networks based on the Universal Mobile Telecommunications System (UMTS) to have higher data speeds and capacity.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
high speed dedicated physical control channel	HS-DPCCH	N/A	A channel that carries feedback signalling related to HS-DSCH, including HARQ-ACK and CQI	Wikipedia
high speed downlink shared channel	HS-DSCH	N/A	An HSDPA transport channel shared by several UEs	Wikipedia
HRPD serving gateway	HSGW	N/A	N/A	3GPP TS 32.299 version 9.16.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Charging management; Diameter charging applications"
hitless switch mode	HSM	N/A	N/A	Huawei Term
hopping sequence number	HSN	N/A	Frequency hopping is employed in frequency division spread spectrum to hide the data channels in the noise or to avoid interference from other users of the common spectrum.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
High Speed Packet Access	HSPA	N/A	High Speed Packet Access (HSPA) is an amalgamation of two mobile protocols, High Speed Downlink Packet Access (HSDPA) and High Speed Uplink Packet Access (HSUPA), that extends and improves the performance of existing 3G mobile telecommunication networks using the WCDMA protocols.	Wikipedia
high speed physical downlink shared channel	HS-PDSCH	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
home subscriber server	HSS	N/A	Centralized entity containing subscription data that is required for user authentication and encryption in a 3rd generation mobile network (UMTS) on a per user basis.	3GPP TS 23.278 version 5.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Customized Applications for Mobile network Enhanced Logic (CAMEL); IP Multimedia System (IMS) interworking; Stage 2"
high speed shared control channel	HS-SCCH	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
High Speed Uplink Packet Access	HSUPA	N/A	High Speed Uplink Packet Access (HSUPA) is an enhanced 3G (third-generation) mobile communications protocol in the High-Speed Packet Access (HSPA) family. HSUPA is also known as 3.5G, 3G+, or Turbo 3G. It allows networks based on the Universal Mobile Telecommunications System (UMTS) to have higher data speeds and capacity.	Wikipedia
Hypertext Markup Language	HTML	N/A	A platform-independent system of syntax and semantics (RFC 1866) for adding characters to data files (particularly text files) to represent the data's structure and to point to related data, thus creating hypertext for use in the World Wide Web and other applications.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007

Term	Abbreviation	Synonym	Definition	Reference
Hypertext Transfer Protocol	HTTP	N/A	The Hypertext Transfer Protocol (HTTP) is an application layer protocol for distributed, collaborative, hypermedia information systems.	Wikipedia
Hypertext Transfer Protocol Secure	HTTPS	N/A	Hypertext Transfer Protocol Secure (HTTPS) is an extension of the Hypertext Transfer Protocol (HTTP). It is used for secure communication over a computer network, and is widely used on the Internet.	Wikipedia
hub base transceiver station	Hub BTS	N/A	N/A	Huawei Term
half rate	N/A	N/A	A variable of GSM. The half rate doubles system capacity through the more efficient speech coding.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
half-rate service	N/A	N/A	A service where the speech encoding rate is reduced to about half of the full-rate through a new speech coding algorithm. If the half-rate service is enabled, the physical channel carrying the service of one MS is able to bear the services of two MSs.	Huawei Term
half-static	N/A	N/A	An original configuration is generated in data configuration. This configuration can be dynamically adjusted by the resource management module.	Huawei Term
hardware address	N/A	N/A	A link layer address or physical address. It is six bytes long. It is also called physical address.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
HashBAND	N/A	N/A	HashBAND is a 5G intelligent coordination solution proposed by Huawei for multi-frequency networks. It includes features such as carrier aggregation and multi-frequency convergence. This solution is used to efficiently coordinate various resources (including spectrums, channels, and beams) of multi-frequency networks and implement intelligent convergence and mutual aid between frequency bands. By fully exploiting the characteristics and advantages of each frequency band, it can provide optimal network performance and user experience with limited spectrum resources, maximizing spectrum value.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
heartbeat between the active and standby BAMs	N/A	N/A	Packets sent between the active and standby BAMs, which are not replied to by the peer end. The active and standby BAMs send heartbeats to each other to indicate their normal work status.	Huawei Term
Hello packet	N/A	N/A	Hello packets are OSPF packet type 1. These packets are sent periodically on all interfaces (including virtual links) in order to establish and maintain neighbor relationships. In addition, Hello packets are multicast on those physical networks having a multicast or broadcast capability, enabling dynamic discovery of neighboring routers.	J. Moy, "OSPF Version 2", RFC 1583, March 1994
HeNB	N/A	N/A	A HeNB is a piece of customer-premises equipment that connects a 3GPP UE over E-UTRAN wireless air interface to a mobile operator's network using a broadband IP backhaul.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
host	N/A	N/A	A computer system uniquely identified by its Internet Protocol (IP) address, and as such addressable in a computer network. It may take both client and server roles.	ETSI TS 101 197-1: "Digital Video Broadcasting (DVB); DVB SimulCrypt; Part 1: Head-end architecture and synchronization"

Term	Abbreviation	Synonym	Definition	Reference
host name	N/A	hostname	"Host name" is often meant to be a domain name that follows the rules in Section 3.5 of RFC1034, the "preferred name syntax". Note that any label in a domain name can contain any octet value; hostnames are generally considered to be domain names where every label follows the rules in the "preferred name syntax", with the amendment that labels can start with ASCII digits (this amendment comes from Section 2.1 of [RFC1123]). People also sometimes use the term hostname to refer to just the first label of an FQDN, such as "printer" in "printer.admin.example.com". (Sometimes this is formalized in configuration in operating systems.) In addition, people sometimes use this term to describe any name that refers to a machine, and those might	P. Hoffman, ICANN, A. Sullivan, Dyn, K. Fujiwara, and JPRS, "DNS Terminology", RFC 7719, December 2015

Term	Abbreviation	Synonym	Definition	Reference
			include labels that do not conform to the "preferred name syntax".	
hot patch	N/A	- hot patching - live patching - dynamic software updating	Hot patching, also known as live patching or dynamic software updating, is the application of patches without shutting down and restarting the system or the program concerned.	Wikipedia
hotspot cell	N/A	N/A	A cell that has high traffic and a large quantity of users.	Huawei Term
Huawei CA	N/A	N/A	Huawei CA is a self-signed CA deployed by Huawei to initial digital certificates for devices during manufacturing.	Huawei Term
Huawei-issued device certificate	N/A	N/A	A Huawei-issued device certificate is a digital certificate issued by a Huawei CA and factory installed on a device during the manufacturing process. The certificate is used as a device identifier to identify a Huawei device.	Huawei Term
HW II	N/A	N/A	It is an algorithm used for channel allocation and power control.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
HW III	N/A	N/A	It is an algorithm used for power control.	Huawei Term
Hybrid microwave	N/A	N/A	Hybrid transmission of Native E1 and Native Ethernet microwave signals. Hybrid microwave supports AM.	Huawei Term
hyper cell	N/A	N/A	A hyper cell is formed by combining multiple independent TRPs working on the same frequency and having the same bandwidth. The combined cell works as a logical cell to provide radio communication services.	Huawei Term

1.10 I

Term	Abbreviation	Synonym	Definition	Reference
input/ output	I/O	• io • IO	In computing, input/output (I/O) is the communication between an information processing system, such as a computer, and the outside world, possibly a human or another information processing system. Inputs are the signals or data received by the system and outputs are the signals or data sent from it. The term can also be used as part of an action; to "perform I/O" is to perform an input or output operation.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
integrated access and backhaul	IAB	N/A	Integrated access and backhaul (IAB) enables wireless relaying in NG-RAN. The relaying node, referred to as IAB-node, supports access and backhauling via NR. The terminating node of NR backhauling on network side is referred to as the IAB-donor, which represents a gNodeB with additional functionality to support IAB.	3GPP TS 38.300: "Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description;"
intelligent access control	IAC	N/A	During the process of a UE's access to a network, intelligent access control (IAC) is performed to improve the access success rate of the UE. The following means are used by IAC: rate negotiation, preemption, queuing, directed retry, and redirection.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
intelligent access control class	IACC	N/A	When traffic congestion occurs in a cell, this function restricts the number of random access requests to increase the immediate assignment success rate.	Huawei Term
iSite access SDH unit	IASU	N/A	N/A	Huawei Term
integrated backup battery system	IBBS	N/A	N/A	Huawei Term
initial block error rate	IBLER	N/A	Initial block error rate of data packets	Huawei Term
instantaneous bandwidth	IBW	N/A	This is the range of RF frequency over which the signal may be instantaneously received and processed; for instance, its value will determine the range of radar frequency agility that can be processed.	ITU-R SM.2356-0: "Procedures for planning and optimization of spectrum-monitoring networks in the VHF/UHF frequency range"

Term	Abbreviation	Synonym	Definition	Reference
interference cancellation	IC	N/A	The basic idea of interference cancellation is to estimate the interference of UE signals through detection and reconstruction technologies and subtract some or all interference from the total received data to reduce the interference level before demodulation and decoding.	Huawei Term
interference cancellation combining	ICC	N/A	Interference cancellation combining is an optimized RF algorithm, which has satisfactory anti-interference performance and improves voice quality significantly.	Huawei Term
inter-subcarrier interference	ICI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
inter-cell interference coordination	ICIC	N/A	Inter-cell interference coordination (ICIC) techniques present a solution by applying restrictions to the radio resource management (RRM) block, improving favorable channel conditions across subsets of users that are severely impacted by the interference, and thus attaining high spectral efficiency.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Internet Control Message Protocol	ICMP	N/A	The Internet Control Message Protocol (ICMP) is a supporting protocol in the Internet protocol suite. It is used by network devices, including routers, to send error messages and operational information indicating success or failure when communicating with another IP address, for example, when an error is indicated when a requested service is not available or that a host or router could not be reached. ICMP differs from transport protocols such as TCP and UDP in that it is not typically used to exchange data between systems, nor is it regularly employed by end-user network applications (with the exception of some diagnostic tools like ping and traceroute).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Internet Control Message Protocol version 6	ICMPv6	N/A	N/A	ETSI GS AFI 002 V1.1.1: "Autonomic network engineering for the self-managing Future Internet (AFI); Generic Autonomic Network Architecture (An Architectural Reference Model for Autonomic Networking, Cognitive Networking and Self-Management)"
indoor centralized rack	ICR	N/A	A rack that is used for solutions to indoor distributed base stations. The baseband unit (BBU) and remote RF units (RRUs) in centralized mode can be installed on it. It is a component of a base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Identifier	ID	N/A	An identifier is a name that identifies (that is, labels the identity of) either a unique object or a unique class of objects, where the "object" or class may be an idea, physical countable object (or class thereof), or physical noncountable substance (or class thereof). The abbreviation ID often refers to identity, identification (the process of identifying), or an identifier (that is, an instance of identification). An identifier may be a word, number, letter, symbol, or any combination of those.	Wikipedia
intra-domain NAS node selection	IDNNS	N/A	N/A	Huawei Term
indoor unit	IDU	N/A	Indoor unit of split-mount microwave equipment. It implements functions including service access, multiplexing/demultiplexing, and IF processing.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
information element	IE	N/A	The components of a message are information elements. A particular information element type may be a component of more than one message type. An information element is composed of one or more octet groups.	ITU-T Q.2931: "Digital Subscriber Signalling System No. 2 - User-Network Interface (UNI) layer 3 specification for basic call/connection control"
International Electrotechnical Commission	IEC	N/A	Organization that prepares and publishes international standards for electrical, electronic and related technologies.	ETSI TS 103 311-2 V1.1.1: "Integrated broadband cable telecommunication networks (CABLE); Fourth Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS® 3.1"

Term	Abbreviation	Synonym	Definition	Reference
Institute of Electrical and Electronics Engineers	IEEE	N/A	The IEEE is a not-for-profit association of approximately 300,000 individual members in 150 countries. The IEEE produces nearly one third of the world's published literature in electrical engineering, computers, and control technology; holds hundreds of major, annual conferences; and maintains more than 800 active standards, with many more under development.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
Internet Engineering Task Force	IETF	N/A	The Internet Engineering Task Force (IETF) is an open standards organization, which develops and promotes voluntary Internet standards, in particular the standards that comprise the Internet protocol suite (TCP/IP).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
inverse fast Fourier transform	IFFT	N/A	Algorithm to compute the inverse discrete Fourier transform from the frequency domain to the time domain, typically far more efficiently than methods such as correlation or solving simultaneous linear equations.	ETSI TS 103 311-2: "Integrated broadband cable telecommunication networks (CABLE); Fourth Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer;"
intelligent field test system	IFTS	N/A	N/A	Huawei Term
Internet Group Management Protocol	IGMP	N/A	The Internet Group Management Protocol (IGMP) is a communications protocol used by hosts and adjacent routers on IPv4 networks to establish multicast group memberships. IGMP is an integral of IP multicast and allows the network to direct multicast transmissions only to hosts that have requested them.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Interior Gateway Protocol	IGP	N/A	An interior gateway protocol (IGP) is a type of protocol used for exchanging routing information between gateways (commonly routers) within an autonomous system (for example, a system of corporate local area networks). This routing information can then be used to route network-layer protocols like IP.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
integrity key	IK	N/A	The integrity key (IK) is 128 bits long. IK is stored in the USIM and a copy is stored in the ME. IK is sent from the USIM to the ME upon request of the ME. The USIM shall send IK under the condition that a valid IK is available. The ME shall trigger a new authentication procedure if the current value of STARTCS or STARTPS in the USIM are not up-to-date or STARTCS or STARTPS have reached THRESHOLD. The ME shall delete IK from memory after power-off as well as after removal of the USIM.	3GPP TS 33.102: "3G security; Security architecture"

Term	Abbreviation	Synonym	Definition	Reference
Internet Key Exchange	IKE	N/A	Key management mechanism used to negotiate and derive keys for SAs in IPsec.	ETSI TR 102 129 V1.1.1: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Requirements Definition Study; Interworking of TIPHON and IP-Cablecom; Architecture, Protocol, QoS and Security"
IP multimedia	IM	N/A	N/A	Huawei Term
instant messaging	IM	N/A	Differs from email primarily in that its primary focus is substantially immediate end-user delivery.	EG 202 308 V1.2.1: "User Group; User interoperability criteria"

Term	Abbreviation	Synonym	Definition	Reference
inverse multiplexing for ATM	IMA	N/A	ITU-T I.761 defines a protocol for inverse multiplexing of an ATM cell stream over multiple physical links, and to retrieve the original stream at the far end from these links. Multiplexing of the ATM cell stream is performed on a cell-by-cell basis across the multiple links. The inverse multiplexing for ATM (IMA) protocol provides a modular bandwidth for user access to ATM networks at rates between those used for UNI as defined in ITU-T Recommendation I.432 series, and for connection between ATM network elements at rates other than those defined by existing digital hierarchies. The introduction of ATM inverse multiplexers provides an effective method of combining the transport bandwidths of multiple links grouped to	ITU-T I.761: "Inverse multiplexing for ATM (IMA)"

Term	Abbreviation	Synonym	Definition	Reference
			collectively provide higher intermediate rates.	
indoor mini box	IMB	N/A	A box that is an indoor subrack with limited space. It supports external AC or DC input, and houses and protects the baseband unit (BBU). It is a component of a base station.	Huawei Term
international mobile equipment identity	IMEI	N/A	An international mobile equipment identity is a unique number which shall be allocated to each individual mobile station equipment in the GSM system and shall be unconditionally implemented by the MS manufacturer.	ETSI TS 100 508 V7.0.0: "Digital cellular telecommunications system (Phase 2+); International Mobile station Equipment Identities (IMEI) (GSM 02.16 version 7.0.0 Release 1998)"
international mobile station equipment identity and software version number	IMEISV	International Mobile Equipment Identity Software Version	N/A	3GPP TS 44.318 version 9.2.0: "Digital cellular telecommunications system (Phase 2+); Generic Access Network (GAN); Mobile GAN interface layer 3 specification"

Term	Abbreviation	Synonym	Definition	Reference
IP multimedia subsystem	IMS	N/A	The IP multimedia subsystem or IP multimedia core network subsystem (IMS) is a standardized architectural framework for delivering IP multimedia services. Historically, mobile phones have provided voice call services over a circuit-switched-style network, rather than strictly over an IP packet-switched network. Alternative methods of delivering voice (VoIP) or other multimedia services have become available on smartphones, but they have not become standardized across the industry.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
international mobile subscriber identity	IMSI	N/A	The international mobile subscriber identity (IMSI) is a number that uniquely identifies every user of a cellular network. It is stored as a 64-bit field and is sent by the mobile device to the network. It is also used for acquiring other details of the mobile device in the home location register (HLR) or as locally copied in the visitor location register.	Wikipedia
International Mobile Telecommunications-2000	IMT-2000	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
intelligent network	IN	N/A	The intelligent network (IN) is the standard network architecture specified in the ITU-T Q.1200 series recommendations. It is intended for fixed as well as mobile telecom networks. It allows operators to differentiate themselves by providing value-added services in addition to the standard telecom services such as PSTN, ISDN on fixed networks, and wireless services on mobile phones or other mobile devices.	Wikipedia
Interruption RNTI	INT-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
isolated E-UTRAN operation for public safety	IOPS	N/A	N/A	3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial; Radio Access Network (E-UTRAN) access"

Term	Abbreviation	Synonym	Definition	Reference
information security	InfoSec	N/A	The combination of confidentiality, validity, authenticity, integrity and information availability. (INFOSEC Task S2001 [15])	ETSI ETR 232: "Security Techniques Advisory Group (STAG); Glossary of security terminology"
intelligent optimum sample	IOS	N/A	N/A	Huawei Term
interference over thermal	IoT	N/A	N/A	Huawei Term
Internet of Things	IoT	N/A	Dynamic global network with (self-)configuring capabilities based on communication protocols where physical and virtual 'things' have identities, physical attributes, and virtual representation, and use interfaces to be integrated into the information network (from ETSI TR 103 582).	ETSI TS 102 181 V1.3.1: "Emergency Communications (EMTEL); Requirements for communication between authorities/organizations during emergencies"

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol	IP	N/A	Computer network protocol (analogous to written and verbal languages) that all machines on the Internet must know so that they can communicate with one another. IP is a layer 3 (network layer) protocol in the OSI model.	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"
IP performance monitoring	IP PM	N/A	Huawei introduces the proprietary protocol IP PM. IP PM detects the transmission rate, packet loss rate, delay, and jitter of user-plane data flows in real-time from end to end.	Huawei Term
IP radio access network	IP RAN	N/A	A network that uses IP technology to achieve data backhaul on a radio access network.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
IP connectivity access network	IP-CAN	N/A	N/A	3GPP TS 32.251 version 9.9.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Charging management; Packet Switched (PS) domain charging"

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol control protocol	IPCP	N/A	In computer networking, Internet Protocol control protocol (IPCP) is a network control protocol (NCP) for establishing and configuring Internet Protocol over a point-to-point protocol link. IPCP is responsible for configuring the IP addresses as well as for enabling and disabling the IP protocol modules on both ends of the point-to-point link. IPCP uses the same packet exchange mechanism as the link control protocol. IPCP packets may not be exchanged until PPP has reached the Network-Layer Protocol phase, and any IPCP packets received before this phase is reached should be silently discarded. IPCP has the NCP protocol code number 0x8021.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
idle period downlink	IPDL	N/A	N/A	ETSI TS 123 271: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Functional stage 2 description of Location Services (LCS)"
in-path equipment	IPE	N/A	The IPE can be classified into echo canceler, digital communication multiplexer equipment (DCME), dual tone multi-frequency (DTMF) generator, A-law/u-law converter, and so forth.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
IP Header Compression	IPHC	N/A	A host-host protocol used to compress real-time multimedia services such as voice and video over IP networks. To reduce bandwidth consumption, you can use the IP header compression function on links to compress TCP/IP and IP/UDT/RTP headers.	Huawei Term
IP over ATM	IPoA	N/A	N/A	ETSI TS 102 460 V1.2.1: "Satellite Earth Stations and Systems (SES); Broadband Satellite Multimedia (BSM); Address Management at the SI-SAP"

Term	Abbreviation	Synonym	Definition	Reference
IP performance metrics	IPPM	N/A	The IETF has standardized IP performance metrics (IPPM) for measuring end-to-end performance between two points. This memo defines two new categories of metrics that extend the coverage to multiple measurement points. It defines spatial metrics for measuring the performance of segments of a source to destination path, and metrics for measuring the performance between a source and many destinations in multiparty communications.	Emile Stephan, Lei Liang, Al Morton. IP Performance Metrics (IPPM): Spatial and Multicast, RFC 5644, October 2009

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol Security	IPsec	N/A	In computing, Internet Protocol Security (IPsec) is a secure network protocol suite that authenticates and encrypts the packets of data to provide secure encrypted communication between two computers over an Internet Protocol network. It is used in virtual private networks (VPNs). IPsec includes protocols for establishing mutual authentication between agents at the beginning of a session and negotiation of cryptographic keys to use during the session. IPsec can protect data flows between a pair of hosts (host-to-host), between a pair of security gateways (network-to-network), or between a security gateway and a host (network-to-host). IPsec uses cryptographic security services to protect communications over Internet Protocol (IP) networks. It	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			supports network-level peer authentication, data origin authentication, data integrity, data confidentiality (encryption), and replay protection. The initial IPv4 suite was developed with few security provisions. As a part of the IPv4 enhancement, IPsec is a layer 3 OSI model or Internet layer end-to-end security scheme. In contrast, while some other Internet security systems in widespread use operate above layer 3, such as Transport Layer Security (TLS) that operates above the Transport Layer and Secure Shell (SSH) that operates at the Application layer, IPsec can automatically secure applications at the IP layer.	

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol television	IPTV	N/A	Internet Protocol television (IPTV) is the delivery of television content over Internet Protocol (IP) networks. This is in contrast to delivery through traditional terrestrial, satellite, and cable television formats. Unlike downloaded media, IPTV offers the ability to stream the source media continuously. As a result, a client media player can begin playing the content (such as a TV channel) almost immediately. This is known as streaming media.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol version 4	IPv4	N/A	Internet Protocol version 4 (IPv4) is the fourth version of the Internet Protocol (IP). It is one of the core protocols of standards-based internetworking methods in the Internet and other packet-switched networks. IPv4 was the first version deployed for production on SATNET in 1982 and on the ARPANET in January 1983. It is still used to route most Internet traffic today, despite the ongoing deployment of a successor protocol, IPv6.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Internet Protocol version 6	IPv6	N/A	Internet Protocol version 6 (IPv6) is the most recent version of the Internet Protocol (IP), the communications protocol that provides an identification and location system for computers on networks and routes traffic across the Internet. IPv6 was developed by the Internet Engineering Task Force (IETF) to deal with the long-anticipated problem of IPv4 address exhaustion. IPv6 is intended to replace IPv4. In December 1998, IPv6 became a Draft Standard for the IETF, who subsequently ratified it as an Internet Standard on 14 July 2017.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
incremental redundancy	IR	N/A	Incremental redundancy, enables higher data rates through combining information from different transmissions of RLC data blocks when decoding. Also known as Hybrid Type II/III ARQ.	3GPP TR 44.060: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol (Release 16)"
infrared	IR	infrared light	Region of the electromagnetic spectrum bounded by the long-wavelength extreme of the visible spectrum. (approximately 0.7 μm) and the shortest microwaves (approximately 0.1 mm).	ETSI TR 170 002 V3.1.1: "Project MESA; Service Specification Group - Services and Applications; Definitions, symbols and abbreviations"

Term	Abbreviation	Synonym	Definition	Reference
initialization and refresh	IR	N/A	The state is the lowest level. In this state, the compressor sends the entire packet header information, including the static part and the dynamic part. The compressor is in this state when the static part of the context of the decompressor is not established or the decompression fails. The compressor remains in this state until the decompressor has correctly received all the static context information.	Huawei Term
Inactive RNTI	I-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
Internet Security Association and Key Management Protocol	ISAKMP	N/A	Internet Security Association and Key Management Protocol (ISAKMP) is a protocol defined by RFC 2408 for establishing Security association (SA) and cryptographic keys in an Internet environment. ISAKMP only provides a framework for authentication and key exchange and is designed to be key exchange independent; protocols such as Internet Key Exchange (IKE) and Kerberized Internet Negotiation of Keys (KINK) provide authenticated keying material for use with ISAKMP. For example: IKE describes a protocol using part of Oakley and part of SKEME in conjunction with ISAKMP to obtain authenticated keying material for use with ISAKMP.	Wikipedia
inter-site distance	ISD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Integrated Services Digital Network	ISDN	N/A	Integrated Services Digital Network (ISDN) is a set of communication standards for simultaneous digital transmission of voice, video, data, and other network services over the digitalized circuits of the public switched telephone network.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
inter-symbol interference	ISI	intersymbol interference	In telecommunication, intersymbol interference (ISI) is a form of distortion of a signal in which one symbol interferes with subsequent symbols. This is an unwanted phenomenon as the previous symbols have a similar effect as noise, thus making the communication less reliable. The spreading of the pulse beyond its allotted time interval causes it to interfere with neighboring pulses. ISI is usually caused by multipath propagation or the inherent linear or non-linear frequency response of a communication channel, causing successive symbols to blur together.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
International Organization for Standardization	ISO	N/A	The International Organization for Standardization (ISO) is an international standard-setting body composed of representatives from various national standards organizations.	Wikipedia
Internet Service Provider	ISP	N/A	An Internet service provider (ISP) is an organization that provides many different services for accessing, using, or participating in the Internet. Internet service providers can be organized in various forms, such as commercial, community-owned, non-profit, or otherwise privately owned.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
integrated services digital network user part	ISUP	ISDN user part	The ISDN (Integrated Services Digital Network) User Part or ISUP is part of Signaling System No. 7 (SS7), which is used to set up telephone calls in the public switched telephone network (PSTN). It is specified by the ITU-T as part of the Q.76x series.	Wikipedia
information technology	IT	N/A	Information technology (IT) is the use of computers to store or retrieve data and information. IT is typically used within the context of business operations as opposed to personal or entertainment technologies. IT is considered to be a subset of information and communications technology (ICT).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
International Telecommunication Union	ITU	N/A	The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs).	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks"
ITU Telecommunication Standardization Sector	ITU-T	- International Telecommunications Union, Telecommunication Standardization Sector - International Telecommunication Union-Telecommunication Standardization Sector	International Telecommunications Union, Telecommunication Standardization Sector (formerly "CCITT"), a United Nations treaty organization that is composed mainly of postal, telephone, and telegraph authorities of the member countries and that publishes standards called "Recommendations".	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
Iub interface	Iub	N/A	Interface between an RNC and a NodeB.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
lu-BC interface	lu-BC	N/A	Interface between the RNC and the CBC.	3GPP TR 25.419: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN lu-BC Interface: Service Area Broadcast Protocol (SABP) (Release 16)"
lur interface	lur	N/A	A logical interface between two RNCs. While logically representing a point to point link between RNCs, the physical realization may not be a point to point link.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
interworking function	IWF	N/A	Function that enables interworking between land mobile radio systems and 3GPP defined mission critical systems.	ETSI TS 100 392-19-2 V1.1.1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 19: Interworking between TETRA and Broadband systems; Sub-part 2: Format for the transport of TETRA speech over mission critical broadband systems"
IMA frame	N/A	N/A	A control unit in the IMA protocol. It is a logical frame defined as M consecutive cells, numbered 0 to M-1, transmitted on each of the N links in an IMA group.	Huawei Term
in-band signaling	N/A	N/A	In-band signaling is the sending of control information within the same band or channel used for data such as voice or video.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
indicator	N/A	N/A	Measure that provides an estimate or evaluation of specified attributes derived from an analytical model with respect to a defined information need.	ETSI GS ISI 001-2: "Information Security Indicators (ISI); Indicators (INC); Part 2: Guide to select operational indicators based on the full set given in part 1"
insulation test	N/A	N/A	A test that is performed to check whether the cabinet is insulated from the earth by measuring the resistance between the cabinet and the earth when the multimeter is set to the megohm range. This test helps to ensure that the required insulation parts are installed and are intact.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Intelligent RAN	N/A	N/A	IntelligentRAN is an intelligent solution proposed by Huawei to drive wireless network evolution from connectivity of everything to intelligent connectivity of everything. It provides the following features: • Intelligent service operations: Service provisioning, originally based on experience, will become real-time and agile. This feature also implements multi-service joint optimization in multi-frequency networks to select the optimal band combination and handover policy, thereby ensuring optimal multi-service experience. • Intelligent network optimization: In multi-RAT multi-site heterogeneous networking,	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
			multi-service joint prediction is performed based on service types to ensure consistent user experience and enable traffic-based adaptive networks. Intelligent network optimization involves energy saving self-optimization in multimode scenarios, independent decision-making on network resource configuration, and maximum reduction in energy consumption. With this feature, hundredfold traffic growth can be handled without much increase in energy consumption, achieving optimal user experience and energy efficiency. ● Intelligent and simplified O&M: Intelligent analysis is performed to compress	

Term	Abbreviation	Synonym	Definition	Reference
			alarms and locate faults. In addition, by predicting software and hardware faults and performance deterioration, networks can rectify faults and eliminate risks in advance. This way, post-event processing is changed to pre-event prevention, ensuring zero network faults and high network reliability.	
inter-frequency neighboring cell	N/A	N/A	A cell that has partially overlapping coverage with the serving cell and uses a different frequency from that of the serving cell.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
interference	N/A	N/A	Interference refers to noise or other external signals that affect the performance of communication channels or electromagnetic signals that affect radio broadcasting or television reception. Such signals can be generated by nature (such as lightning) or by electrical devices (such as computers).	Huawei Term
interleaving	N/A	N/A	Way to arrange data in a non-contiguous way in order to increase performance.	ETSI TR 102 300-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D): Designers' guide; Part 7: TETRA High-Speed Data (HSD); TETRA Enhanced Data Service (TEDS)"
intra-frequency neighboring cell	N/A	N/A	A cell that has partially overlapping coverage with the serving cell. In addition, this cell and the serving cell use the same frequency.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
IP path	N/A	N/A	Route that IP flow will traverse. IP path could be the shortest path determined by routing protocols (IGP or BGP), or the explicit path decided by another management entity, such as a central controller, or Path Computation Element (PCE) Communication Protocol (PCEP), etc.	ETSI GR NGP 010: "Next Generation Protocols (NGP); Recommendation for New Transport Technologies"
IQ modulation	N/A	- quadrature modulation - I/Q modulation - in-phase and quadrature modulation	In-phase and quadrature modulation (IQ modulation) is a modulation scheme that conveys two channels of signals in parallel using two orthogonal carriers.	Huawei Term
Iu Flex	N/A	N/A	Intra domain connection of RAN nodes to multiple CN nodes	Huawei Term

1.11 J

Term	Abbreviation	Synonym	Definition	Reference
joint transmission	JT	N/A	N/A	3GPP TR 36.819: "Coordinated multi-point operation for LTE physical layer aspects (Release 11)"
joint reception	JR	N/A	N/A	3GPP TR 36.819: "Coordinated multi-point operation for LTE physical layer aspects (Release 11)"
jitter	N/A	N/A	Short-term non-cumulative variations of the significant instants of a digital signal from their ideal positions in time.	ITU-T G.701: "VOCABULARY OF DIGITAL TRANSMISSION AND MULTIPLEXING, AND PULSE CODE MODULATION (PCM) TERMS"

Term	Abbreviation	Synonym	Definition	Reference
jumper	N/A	N/A	A jumper is an electrical wire, or group of them in a cable, with a connector or pin at each end (or sometimes without them – simply "tinned"). It is normally used to interconnect the components of a breadboard or other prototype or test circuit, internally or with other equipment or components, without soldering.	Wikipedia

1.12 K

Term	Abbreviation	Synonym	Definition	Reference
kilo-bit per second	kbps	kbit/s or kb/s	Kilo-bit per second (kbit/s or kb/s, often abbreviated "kbps") is a unit of data transfer rate equal to 1,000 bits per second.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
64-bit cipherring key	Kc	Kc64	N/A	3GPP TS 44.064 V16.0.0: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Mobile Station - Serving GPRS Support Node (MS-SGSN); Logical Link Control (LLC) layer specification (Release 16)"
128-bit cipherring key	Kc128	N/A	N/A	3GPP TS 44.064 V16.0.0: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Mobile Station - Serving GPRS Support Node (MS-SGSN); Logical Link Control (LLC) layer specification (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
individual subscriber authentication key	Ki	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
key performance indicator	KPI	N/A	A key performance indicator (KPI) is a type of performance measurement. KPIs evaluate the success of an organization or of a particular activity (such as projects, programs, products and other initiatives) in which it engages.	Wikipedia
key quality indicator	KQI	N/A	N/A	Huawei Term
kilo-symbols per second	ksps	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
keyboard/ video/ mouse	KVM	• keyboard, video, and mouse • keyboard video mouse	KVM originally referred to keyboard, video, and mouse. But in Agile Controller-Campus, KVM refers to a remote assistance software, through which administrators can help terminal users rectify faults by remotely viewing or accessing their desktop.	Huawei Term
K byte	N/A	N/A	A general designation of K1 byte and K2 byte in the SDH.	Huawei Term
K byte event	N/A	N/A	A switch event that is recorded in K byte format and to which the APS request is converted.	Huawei Term

1.13 L

Term	Abbreviation	Synonym	Definition	Reference
Layer 2 management link	L2ML	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Layer 2 virtual private network	L2VPN	N/A	Layer 2 Virtual Private Network: set of LANs and the L2 Forwarders between them that enable hosts attached to the LANs to communicate with L2PDUs. A single L2VPN forwards L2PDUs based only on the Destination MAC address of the L2PDU, transparent to any IP or other Layer 3 address. A cable operator administration domain supports multiple L2VPNs, one for each subscriber enterprise to which Transparent LAN Service is offered.	ETSI EN 302 878-4: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 4: MAC and Upper Layer Protocols;"
location area	LA	N/A	The coverage area in which a cordless terminal may receive and make calls as a result of a single location registration.	ETS 300 692: "Private Integrated Services Network (PISN); Cordless Terminal Mobility (CTM); Location handling services; Functional capabilities and information flows"

Term	Abbreviation	Synonym	Definition	Reference
location area code	LAC	N/A	Code to group cells together for circuit-switched mobility purposes	ETSI TR 103 293: "Broadband Radio Access Networks (BRAN); Broadband Wireless Access and Backhauling for Remote Rural Communities"
link access control	LAC	N/A	N/A	Huawei Term
Link Aggregation Control Protocol	LACP	N/A	Within the IEEE Ethernet standards, the Link Aggregation Control Protocol (LACP) provides a method to control the bundling of several physical links together to form a single logical link. LACP allows a network device to negotiate an automatic bundling of links by sending LACP packets to their peer, a directly-connected device that also implements LACP.	Wikipedia
link aggregation control protocol data unit	LACPDU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
link aggregation group	LAG	N/A	In computer networking, the term link aggregation refers to various methods of combining (aggregating) multiple network connections in parallel in order to increase throughput beyond what a single connection could sustain, and to provide redundancy in case one of the links should fail. A link aggregation group (LAG) is the collection of physical ports combined together.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
location area identity	LAI	N/A	Each location area of a public land mobile network (PLMN) has its own unique identifier which is known as its location area identity (LAI). This internationally unique identifier is used for location updating of mobile subscribers. It is composed of a three-decimal-digit mobile country code (MCC), a two- to three-digit mobile network code (MNC) that identifies a Subscriber Module Public Land Mobile Network (SM PLMN) in that country, and a location area code (LAC) which is a 16 bit number with two special values.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
local area network	LAN	N/A	Non-public data network in which serial transmission is used for direct data communication among data stations located on the user's premises	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"
LTE-A optional feature description	LAOFD	N/A	N/A	Huawei Term
Link Access Procedure Balanced	LAPB	N/A	LAPB is used to manage communication and packet framing between data terminal equipment (DTE) and the data circuit-terminating equipment (DCE) devices in the X.25 protocol stack. LAPB is essentially HDLC in asynchronous balanced mode (ABM).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Link Access Procedure on the D channel	LAPD	- Link Access Procedure for the D channel - Link Access Protocol on D channel	The Link Access Procedure on the D channel (LAPD) specification used on the Abis interface in the GSM PLMN is a subset of the ETS 300 125 which in turn has less options than the CCITT Recommendation Q.921.	3GPP TS 08.56: "Technical Specification Group GSM EDGE Radio Access Network; Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 2 specification"
Link Access Protocol on the Dm channel	LAPDm	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Link Access Protocol-SDH	LAPS	N/A	A subset of HDLC, which includes data link services and protocol standards. It mainly used to transport Internet Protocols (IPs) over SDH.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
location area update	LAU	N/A	N/A	3GPP TR 21.905: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; vocabulary for 3GPP Specifications"
LTE baseband processing unit	LBBP	N/A	Board that processes baseband signals and CPRI signals for LTE.	Huawei Term
LTE basic feature description	LBFD	N/A	N/A	Huawei Term
loopback message	LBM	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"
loopback reply	LBR	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"

Term	Abbreviation	Synonym	Definition	Reference
location based service	LBS	location-based service	A service provided either by teleoperator or a 3rd party service provider that utilises the available location information of the terminal.	3GPP TS 25.305: "Technical Specification Group Radio Access Network Stage 2 Functional Specification of Location Services in UTRAN"
listen before talk	LBT	N/A	A procedure according to which transmissions are not performed if the channel is identified as being occupied to/from another user of the spectrum.	3GPP TS 38.321 version 16.5.0 Release 16: "5G; NR; Medium Access Control (MAC) protocol specification"
link capacity adjustment scheme	LCAS	N/A	LCAS is a control mechanism for the virtual concatenation adaptation function at the source end and sink end. LCAS can increase or decrease the capacity of a link without any losses to meet bandwidth requirements.	Huawei Term
logical channel identifier	LCID	N/A	N/A	3GPP TS 26.512 version 16.0.0: "5G; 5G Media Streaming (5GMS); Protocols"

Term	Abbreviation	Synonym	Definition	Reference
LTE CloudAIR optional feature description	LCOFD	N/A	N/A	Huawei Term
Link Control Protocol	LCP	N/A	In computer networking, the Link Control Protocol (LCP) forms part of the Point-to-Point Protocol (PPP), within the family of Internet protocols. In setting up PPP communications, both the sending and receiving devices send out LCP packets to determine the standards of the ensuing data transmission.	Wikipedia
Low chip rate	LCR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
location services	LCS	N/A	LCS is a service concept in system (e.g. GSM or UMTS) standardization. LCS specifies all the necessary network elements and entities, their functionalities, interfaces, as well as communication messages, due to implement the positioning functionality in a cellular network. Note that LCS does not specify any location-based (value added) services except locating of emergency calls.	ETSI TS 123 271 V7.10.0: "LTE; Functional stage 2 description of Location Services (LCS)"
Lightweight Directory Access Protocol	LDAP	N/A	The Lightweight Directory Access Protocol (LDAP) is an Internet protocol for accessing distributed directory services that act in accordance with X.500 data and service models.	K. Zeilenga, Ed., and OpenLDAP Foundation, "Lightweight Directory Access Protocol (LDAP): Technical Specification Road Map", RFC 4510, June 2006.

Term	Abbreviation	Synonym	Definition	Reference
load control	LDC	N/A	Mechanism for controlling the workload of a system.	ETSI ES 283 039-2 V3.1.1: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Congestion and Overload Control; Part 2: Core GOCAP and NOCA Entity Behaviours"
load reshuffling	LDR	N/A	Load reshuffling is used to prevent transmission congestion, reduce transmission load, and increase the admission success rate and system capacity.	Huawei Term
local element management layer	LEML	N/A	The performance management console provided by the LMT belongs to the LEML and facilitates general analysis of the data in local NEs.	Huawei Term
4.5G optional feature description	LEOFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
length indicator	LI	N/A	A six-bit field that defines message length and that is used to differentiate between message signal units, link status signal units, and fill-in signal units.	Huawei Term
language indication	LI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
line identity	LI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
logical link	LL	N/A	End-to-end connection at layer 2.	ETSI TS 103 672 V1.1.1: "Rail Telecommunications (RT); Global System for Mobile communications (GSM); Usage of Session Initiation Protocol with ISUP encapsulation (SIP-I) and other IP based protocols for interconnection of GSM-R networks"
logical link control	LLC	N/A	In the IEEE 802 reference model of computer networking, the logical link control (LLC) data communication protocol layer is the upper sublayer of the data link layer (layer 2) of the seven-layer OSI model. The LLC sublayer acts as an interface between the media access control (MAC) sublayer and the network layer.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Link Layer Discovery Protocol	LLDP	N/A	The Link Layer Discovery Protocol (LLDP) is a vendor-neutral link layer protocol used by network devices for advertising their identity, capabilities, and neighbors on a local area network based on IEEE 802 technology, principally wired Ethernet.	Wikipedia
log management	LM	N/A	Log management is a measure that is used to find illegal operations and system fault reasons by querying and monitoring logs, and to protect network security by taking appropriate measures.	Huawei Term
location management function	LMF	N/A	N/A	3GPP TS 23.501: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; System architecture for the 5G System (5GS)"

Term	Abbreviation	Synonym	Definition	Reference
Link Management Protocol	LMP	N/A	N/A	ETSI TS 103 544-23: "Publicly Available Specification (PAS); Intelligent Transport Systems (ITS); MirrorLink®; Part 23: Bluetooth® Out-of-Band Pairing Data Service"
local maintenance terminal	LMT	N/A	Local maintenance terminal software provided by Huawei.	Huawei Term
location measurement unit	LMU	N/A	An LMU makes radio measurements to support one or more positioning methods. These measurements fall into one of two categories: - location measurements specific to one MS used to compute the location of this MS; - assistance measurements specific to all MSs in a certain geographic area.	ETSI TS 101 513: "Digital cellular telecommunications system (Phase 2+); Location Services (LCS); Location services management (GSM 12.71 version 7.0.1 Release 1998)"
logical name	LN	N/A	N/A	Huawei Term
link number	LN	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
low noise amplifier	LNA	low-noise amplifier	A low-noise amplifier (LNA) is an electronic amplifier that amplifies a very low-power signal without significantly degrading its signal-to-noise ratio. An amplifier will increase the power of both the signal and the noise present at its input, but the amplifier will also introduce some additional noise. LNAs are designed to minimize that additional noise. Designers can minimize additional noise by choosing low-noise components, operating points, and circuit topologies. Minimizing additional noise must balance with other design goals such as power gain and impedance matching.	Wikipedia
LTE evolution optional feature description	LNOFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
loss of frame	LOF	N/A	Loss of frame (LOF): An LOF state of an STM-N signal is considered to have occurred when an OOF state persists for a defined period of time.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "
LTE optional feature description	LOFD	N/A	N/A	Huawei Term
loss of signal	LOS	N/A	The LOS state is considered to have occurred when the amplitude of the relevant signal has dropped below the prescribed limits for a prescribed period.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks"
line-of-sight propagation	LOS propagation	- LOS transmission - line-of-sight transmission	Line-of-sight propagation is a characteristic of electromagnetic radiation or acoustic wave propagation which means waves travel in a direct path from the source to the receiver.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
low power high accuracy positioning	LPHAP	N/A	N/A	3GPP TS 22.104: "Technical Specification Group Services and System Aspects; Service requirements for cyber-physical control applications in vertical domains; Stage 1"
common channel signaling processing board	LPN7	N/A	N/A	Huawei Term
local primary reference	LPR	N/A	N/A	Huawei Term
link state pass through	LPT	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
link-state advertisement	LSA	N/A	The link-state advertisement (LSA) is a basic communication means of the OSPF routing protocol for the Internet Protocol (IP). It communicates the router's local routing topology to all other local routers in the same OSPF area. OSPF is designed for scalability, so some LSAs are not flooded out on all interfaces, but only on those that belong to the appropriate area. In this way, detailed information can be kept localized, while summary information is flooded to the rest of the network. The original IPv4-only OSPFv2 and the newer IPv6-compatible OSPFv3 have broadly similar LSA types.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Localised Service Area	LSA	N/A	An LSA is an operator-defined group of cells, for which specific access conditions apply. This may correspond to an area in which the core network offers specific services. An LSA may be defined within a PLMN or globally. Therefore, an LSA may offer a non-contiguous radio coverage.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
least significant bit	LSB	N/A	If not otherwise mentioned in the definition of each field, the bits in the parameters shall be interpreted as follows: the left-most bit string is the first and most significant and the right most bit is the last and least significant bit.	3GPP TS 25.322: "Radio Link Control (RLC) protocol specification"
link state database	LSDB	N/A	N/A	Huawei Term
license serial number	LSN	N/A	The license serial number uniquely identifies a license file.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
label-switched path	LSP	N/A	A label-switched path (LSP) is a path through an MPLS network, set up by the NMS or by a signaling protocol such as LDP, RSVP-TE, BGP (or the now deprecated CR-LDP). The path is set up based on criteria in the FEC.	Wikipedia
label switching router	LSR	transit router	An MPLS router that performs routing based only on the label is called a label switching router (LSR) or transit router. This is a type of router located in the middle of an MPLS network. It is responsible for switching the labels used to route packets.	Wikipedia
LTE/SAE Trial Initiative	LSTI	N/A	In May 2007, the LTE/SAE Trial Initiative (LSTI) alliance was founded as a global collaboration between vendors and operators with the goal of verifying and promoting the new standard in order to ensure the global introduction of the technology as quickly as possible.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
link trace	LT	N/A	N/A	Huawei Term
line termination	LT	N/A	Functional group containing at least the transmit and receive functions terminating one end of a digital transmission system (see ITU-T Recommendation I.112-427).	ETSI TR 101 287 V1.2.1: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
Long Term Evolution	LTE	N/A	LTE (Long Term Evolution) or the E-UTRAN (Evolved Universal Terrestrial Access Network), introduced in 3GPP R8, is the access part of the Evolved Packet System (EPS). The main requirements for the new access network are high spectral efficiency, high peak data rates, short round trip time as well as flexibility in frequency and bandwidth.	3GPP TR 25.912: "Feasibility study for evolved Universal Terrestrial Radio Access (UTRA) and Universal Terrestrial Radio Access Network (UTRAN)"
linktrace message	LTM	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"
linktrace reply	LTR	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"

Term	Abbreviation	Synonym	Definition	Reference
LiTRA optional feature description	LNOFD	N/A	N/A	Huawei Term
low voltage differential signaling	LVDS	• TIA/EIA-644 • low-voltage differential signal	Low-voltage differential signaling, or LVDS, also known as TIA/EIA-644, is a technical standard that specifies electrical characteristics of a differential, serial signaling standard, but it is not a protocol. LVDS operates at low power and can run at very high speeds using inexpensive twisted-pair copper cables. LVDS is a physical layer specification only; many data communication standards and applications use it and add a data link layer as defined in the OSI model on top of it.	Wikipedia
LAN wavelength division multiplexing	LWDM	N/A	N/A	IEEE 802.3: "Compact Optical Multiplexers for LAN WDM"

Term	Abbreviation	Synonym	Definition	Reference
LampSite	N/A	N/A	LampSite is a multiband, multimode, and indoor coverage solution launched by Huawei. It features large capacity, flexible configuration, simple engineering, and a small quantity of modules. As such, it well meets the requirements for network construction in complex indoor environments. LampSite provides four solutions: LampSite Pro, LampSite Grid, LampSite Sharing, and LampSite EE. These solutions meet indoor network deployment requirements for different users in a range of scenarios.	Huawei Term
Layer 2 multicast	N/A	L2 multicast	Layer 2 multicast refers to link layer multicast.	ETSI TS 101 545-3: "Digital Video Broadcasting (DVB); Second Generation DVB Interactive Satellite System (DVB-RCS2); Part 3: Higher Layers Satellite Specification"

Term	Abbreviation	Synonym	Definition	Reference
Layer 3 multicast	N/A	L3 multicast	Layer 3 multicast refers to network layer multicast.	ETSI TS 101 545-3: "Digital Video Broadcasting (DVB); Second Generation DVB Interactive Satellite System (DVB-RCS2); Part 3: Higher Layers Satellite Specification"
Layer-2 switching	N/A	N/A	Layer-2 switching uses the MAC address of the host's network interface cards (NICs) to decide where to forward frames. Layer-2 switching is hardware-based, which means switches use application-specific integrated circuit (ASICs) to build and maintain the forwarding information base and to perform packet forwarding at a wire speed. One way to think of Layer-2 switching is as a multiport bridge.	Wikipedia
layer	N/A	stream	Number of parallel data streams after serial-to-parallel conversion is complete during layer mapping.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
license	N/A	N/A	A permission that the vendor provides for the user with a specific function, capacity, and duration of a product. A license can be a file or a serial number. Usually the license consists of encrypted codes. The operation authority granted varies with the level of the license.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
license control item	N/A	N/A	License control items are key components in a license key file (LKF) and displayed as models consisting of uppercase letters and digits. They are used to control whether the capacity or features of a product can be used. Capacity-related license control items are used to control the quantity of available resources, such as the number of admitted UEs, NE capacity, and number of cells. Feature-related license control items are used to control whether a feature, such as Cell Combination and CoMP, can be used.	Huawei Term
link	N/A	N/A	Topological component which describes the fixed relationship between a sub-network and another sub-network or access group. It is defined by an access point on one subnetwork, which is associated with an access point on another subnetwork.	ETSI TS 101 674-2: "Technical Framework for the Provision of Interoperable ATM Services; Part 2: Network Management (X-interface) Specification for Phase 1 Implementation"

Term	Abbreviation	Synonym	Definition	Reference
LiteCA	N/A	N/A	LiteCA is a service integrated with MAE that is used to issue certificates for MAE and its managed elements.	Huawei Term
load	N/A	N/A	Loading a program involves reading the contents of the executable file containing the program instructions into memory, and then carrying out other required preparatory tasks to prepare the executable for running. Once loading is complete, the operating system starts the program by passing control to the loaded program code.	Wikipedia
load sharing topology	N/A	N/A	The load sharing topology allows two or more RRUs, RFUs, or AAUs working normally to share the load of the same tasks according to their processing capabilities. This prevents certain units from being overloaded or underused.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Local Multiple Signaling Points	N/A	N/A	The Local Multiple Signaling Points feature enables one physical BSC to function as a maximum of four logical BSCs. Each logical BSC has a Signaling System No. 7 (SS7) signaling point code. After signaling links are established between a logical BSC and the MSC, the logical BSC serves as an independent BSC and works with the MSC to process services.	Huawei Term
local signaling point	N/A	N/A	The local signaling point of the BSC is the signaling point that is assigned to the BSC and is referred to as local originating signaling point.	Huawei Term
loopback	N/A	N/A	Loopback (also written loop-back) is the routing of electronic signals or digital data streams back to their source without intentional processing or modification. It is primarily a means of testing the communications infrastructure.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
loopback test	N/A	N/A	The terminal can transmit audio or video data on a channel to simulate the actual application and test whether the output is satisfactory. A user can perform a local loopback test to check the local network connection or a remote loopback test to check the remote network connection. If a remote loopback test is performed, data is transmitted from the local site to a remote site, and then back to the local site.	Huawei Term
LTE dongle	N/A	N/A	A data card that uses LTE technology for transmission.	Huawei Term
LTE main processing unit	N/A	N/A	LTE main control transmission board, which provides the main control function and transport ports.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
LTE relay	N/A	N/A	Relay architectures for E-UTRA (LTE-Advanced)	3GPP TR 36.806: "Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Relay architectures for E-UTRA (LTE-Advanced) (Release 9)"

1.14 M

Term	Abbreviation	Synonym	Definition	Reference
machine-to-machine	M2M	N/A	Combination of devices, software and services that operate with little or no human interaction.	ETSI EN 300 175-1 V2.8.1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview"

Term	Abbreviation	Synonym	Definition	Reference
MTP2-User Adaptation Layer	M2UA	N/A	The M2UA uses the services of the Stream Control Transmission Protocol as the underlying reliable signalling common transport protocol.	Brian Bidulock, Ken Morneault, Ram Dantu, Greg Sidebottom, Jacob Heitz. Signaling System 7 (SS7) Message Transfer Part 2 (MTP2) - User Adaptation Layer, RFC 3331, September 2002
MTP3-User Adaptation Layer	M3UA	N/A	M3UA is a communication protocol of the SIGTRAN family, used in telephone networks to carry signaling over Internet Protocol (IP). M3UA enables the SS7 protocol's User Parts (e.g. ISUP, SCCP and TUP) to run over virtually any network technology breaking its limitation to telephony equipment like T-carrier, E-carrier or Asynchronous transfer mode (ATM), which highly improves scalability of the signaling networks.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
mobile allocation	MA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
maintenance association	MA	N/A	Defined as "a set of MEPs, all of which are configured with the same maintenance association identifier (MAID) and maintenance domain (MD) level, each of which is configured with a MEPID unique within that MAID and MD level, and all of which are configured with the complete list of MEPIDs."	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Media Access Control	MAC	Medium Access Control	MAC sublayer is the part of the data link layer that supports topology-dependent functions and uses the services of the Physical Layer to provide services to the Logical Link Control (LLC) sublayer. It can also be a component of a networking software stack. In the OSI 7-layer model, the Media Access Control is a part of layer 2, the data link layer.	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"
Media Access Control - common	MAC-c	N/A	The MAC-c controls access to common transport channels.	Huawei Term
Media Access Control control element	MAC CE	Media Access Control-control element	Media Access Control control element (MAC CE) is used for control signaling at the MAC layer between the gNodeB and UE.	3GPP TS 38.321 V17.5.0: "Medium Access Control (MAC) protocol specification"
maximum number of AMR codec modes	MACS	N/A	N/A	Huawei Term
Multiple Add/Drop Multiplexer	MADM	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
MBB Automati on Engine	MAE	N/A	The MAE is a 5G-oriented product that serves as the engine of wireless automation. It provides apps in all scenarios for wireless network deployment, maintenance and optimization, and service provisioning. The MAE helps operators reduce OPEX, improve service experience and operation efficiency, accelerate the workflow automation in all scenarios, and implement mobile network automation.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
mobile allocation index offset	MAIO	N/A	A mobile allocation index offset (MAIO) refers to a time delay separating traffic channels. When a GSM (Global System for Mobile Communications) mobile phone is served by a cell that is hopping over a set of frequencies, the separate traffic channels hop over the allocated frequencies according to a hopping sequence number (HSN). The traffic channels with the same HSN hop over the same frequencies in the same order but are separated in time by a mobile allocation index offset (MAIO).	Wikipedia
multi-primary antenna line device	MALD	N/A	N/A	Antenna Interface Standards Group Base Standard AISG v3.0

Term	Abbreviation	Synonym	Definition	Reference
managem ent and orchestrat ion	MANO	N/A	Network functions virtualization (also network function virtualization or NFV) is a network architecture concept that uses the technologies of IT virtualization to virtualize entire classes of network node functions into building blocks that may connect, or chain together, to create communication services.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Mobile Application Part	MAP	N/A	The Mobile Application Part (MAP) is an SS7 protocol that provides an application layer for the various nodes in GSM and UMTS mobile core networks and GPRS core networks to communicate with each other in order to provide services to users. The Mobile Application Part is the application-layer protocol used to access the home location register, visitor location register, mobile switching center, equipment identity register, authentication center, short message service center and serving GPRS support node (SGSN).	Wikipedia
maximum allowable path loss	MAPL	N/A	The maximum allowable path loss can be expressed as $L_{p,max} (dB) = \Omega_t (dB) + GT (dB) + GR (dB) - SRX (dB)$ where GT and GR are the gains of the transmitting and receiving antennas, respectively.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
multimedia authentication request	MAR	N/A	N/A	Huawei Term
massive multiple-input multiple-output	massive MIMO	large-scale MIMO	Massive MIMO, also known as large-scale MIMO, is an antenna technology that multiplies the number of antennas based on MIMO.	Huawei Term
Megabyte	MB	N/A	The megabyte is a multiple of the unit byte for digital information. Its recommended unit symbol is MB. The unit prefix mega is a multiplier of 1000000 (10 ⁶) in the International System of Units (SI). Therefore, one megabyte is one million bytes of information. This definition has been incorporated into the International System of Quantities.	Wikipedia
mobile broadband	MBB	N/A	Mobile broadband is the marketing term for wireless Internet access through a portable modem, USB wireless modem, or a tablet/smart phone or other mobile device.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
measurement-based directed retry	MBDR	N/A	N/A	Huawei Term
multimedia broadcast/multicast service	MBMS	N/A	N/A	3GPP TS 36.579-7 version 15.0.0: "LTE; Mission Critical (MC) services over LTE; Part 7: Mission Critical Data (MCData) User Equipment (UE) Protocol conformance specification"
multiband report	MBR	N/A	The information about six neighboring cells of different bands reported by the MS to the network.	Huawei Term
maximum bit rate	MBR	N/A	The MBR limits the bit rate that can be expected to be provided by a GBR bearer (e.g. excess traffic may get discarded by a rate shaping function).	ETSI TS 123 401 V10.11.0: "LTE; General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access"

Term	Abbreviation	Synonym	Definition	Reference
multicast and broadcast service	MBS	N/A	Multicast and Broadcast Service (MBS) is a point-to-multipoint service in which data is transmitted from a single source entity to multiple recipients, either to all users in a broadcast service area, or to users in a multicast group.	3GPP TS 23.247: "Technical Specification Group Services and System Aspects"
multimode base station controller	MBSC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
multimedia broadcast multicast service single frequency network	MBSFN	N/A	Multimedia broadcast multicast service single frequency network (MBSFN) is a communication channel defined in the fourth-generation cellular networking standard called long term evolution (LTE). The transmission mode is intended as a further improvement of the efficiency of the enhanced multimedia broadcast multicast service (eMBMS) service, which can deliver services such as mobile TV using the LTE infrastructure, and is expected to compete with dedicated mobile/handheld TV broadcast systems such as DVB-H and DVB-SH. This enables network operators to offer mobile TV without the need for additional expensive licensed spectrum and without requiring new infrastructure and end-user devices.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multimode base station	MBTS	multi-mode base station	A base station that adopts BBU+RF module structure and supports the co-existence of GSM, UMTS, CDMA, WiMAX, and LTE RF modules and boards in the same cabinet. The multimode base station is conducive to the convergence of multiple RATs and future evolution.	Huawei Term
mobile country code	MCC	N/A	The MCC is the first field of the IMSI and is three digits in length and identifies a country. The Director of TSB may assign more than one MCC to a country. MCCs in the 90x range are non-geographic MCCs (country-agnostic) and are administered by the Director of TSB.	ITU-T E.212: "The international identification plan for public networks and subscriptions"
Multicast Control Channel	MCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
multi-cell/multicast coordination entity	MCE	N/A	The MCE is a logical entity. This does not preclude the possibility that it may be part of another network element. Its functions include the admission control and the allocation of the radio resources used by all eNodeBs in the MBSFN area for multi-cell MBMS transmissions using MBSFN operation. The MCE decides not to establish the radio bearer(s) of the new MBMS service(s) if the radio resources are not sufficient for the corresponding MBMS service(s) or may pre-empt radio resources from other radio bearer(s) of ongoing MBMS service(s) according to ARP. Besides allocation of the time/frequency radio resources this also includes: - Deciding the further details of the radio configuration e.g. the modulation and coding scheme. - Deciding on whether to use	ETSI TS 136 300 V16.4.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
			SC-PTM or MBSFN. - Counting and acquisition of counting results for MBMS service(s). - Resumption of MBMS session(s) within MBSFN area(s) based on e.g. the ARP and/or the counting results for the corresponding MBMS service(s). - Suspension of MBMS session(s) within MBSFN area(s) based e.g. the ARP and/or the counting results for the corresponding MBMS service(s).	
master cell group	MCG	N/A	In dual connectivity, a group of serving cells associated with the MeNB, comprising of the PCell and optionally one or more SCells.	ETSI TS 136 300 V16.5.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
Multicast Channel	MCH	N/A	N/A	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
multi-carrier HSDPA	MC-HSDPA	N/A	N/A	ETSI TS 125 142: "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (TDD)"
Multi-Class Point-to-Point Protocol	MC-PPP	MCPPP	Multi-Class Point-to-Point Protocol (MCPPP) is an extended protocol based on MLPPP. MCPPP uses reserved bits in the MLPPP packet format to classify packets transmitted in link aggregation. The MCPPP technology enables preferential transmission of data packets that require high real-time performance or high priority.	C. Bormann, "The Multi-Class Extension to Multi-Link PPP", RFC 2686, September 1999

Term	Abbreviation	Synonym	Definition	Reference
minimum cell rate	MCR	N/A	A minimum cell rate (MCR) is an asynchronous transfer mode (ATM) parameter used to determine the minimum number of cells permitted in a specific time period.	Huawei Term
modulation and coding scheme	MCS	N/A	Various modulation schemes and coding rates are defined by the standard and are represented by a Modulation and Coding Scheme (MCS) index value. A base station uses different MCSs to ensure transmission efficiency and the quality of UE services. If the channel quality is good, the base station selects an MCS with a higher-order modulation scheme combined and a higher code rate. If the channel quality is poor, the base station selects one with a lower-order modulation scheme and a lower code rate (the code rate is higher if fewer redundant bits are inserted).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Modulation and Coding Scheme C-RNTI	MCS-C-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
Media Control Unit	MCU	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Mission Critical	MCX (Mission Critical)	N/A	Mission Critical (MCX) services are a set of communication services for public safety and disaster relief, and mainly come in three forms: MCPTT, MCVideo, and MCDData.	3GPP TS 22.280: "Mission Critical Services Common Requirements (MCCoRe); Stage 1"

Term	Abbreviation	Synonym	Definition	Reference
maintenance domain	MD	N/A	Maintenance domains are management space on a network, typically owned and operated by a single entity. MDs are configured with names and levels, where the eight levels range from 0 to 7. A hierarchical relationship exists between domains based on levels. The larger the domain, the higher the level value.	Wikipedia
mobile device	MD	• mobile equipment • ME	A small, hand-held computing device with a subscriber identity module (SIM) card, typically having a display screen with touch input and/or a miniature keyboard and is not heavy.	ITU-T X.1158: "Multi-factor authentication mechanisms using a mobile device"

Term	Abbreviation	Synonym	Definition	Reference
Message-Digest algorithm 5	MD5	N/A	The algorithm takes as input a message of arbitrary length and produces as output a 128-bit "fingerprint" or "message digest" of the input. It is conjectured that it is computationally infeasible to produce two messages having the same message digest, or to produce any message having a given prespecified target message digest.	R. Rivest, "The MD5 Message-Digest Algorithm", RFC 1321, April 1992
macro diversity combining	MDC	N/A	N/A	Huawei Term
message discrimination	MDC	N/A	The process which decides, for each incoming message, whether the signalling point is a destination point or if it should act as a signalling transfer point for that message and accordingly, whether the message should be handed to (signalling) message distribution or to (signalling) message routing functions.	ITU-T Q.704: "Signalling network functions and messages"

Term	Abbreviation	Synonym	Definition	Reference
medium dependent interface	MDI	N/A	A medium dependent interface (MDI) describes the interface (both physical and electrical/optical) in a computer network from a physical layer implementation to the physical medium used to carry the transmission.	Wikipedia
multimedia distribution service	MDS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
message distribution	MDT	N/A	The process of determining, upon receipt of a signalling message at its destination point, to which User Part the signalling message is to be delivered.	Marshall T. Rose (Delaware), and Einar A. Stefferud (NMA), "Proposed Standard for Message Encapsulation", RFC 934, January 1985.

Term	Abbreviation	Synonym	Definition	Reference
Minimization of Drive Tests	MDT	N/A	N/A	3GPP TS 25.422 version 9.0.1: "Universal Mobile Telecommunications System (UMTS); UTRAN Iur interface signalling transport"
maintenance entity	ME	N/A	Equipment of the telecommunication network which is defined between two or more interfaces as an object of the network management strategy. The main MEs are the paging network controller (PNC), the paging area controller (PAC) and the BS.	ETS 300 133-7: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Enhanced Radio Message System (ERMES); Part 7: Operation and maintenance aspects"
Multi-Mode Extended Digital Card	MEDC	N/A	A multi-mode extended digital card functions as an interface board in the LampSite solution.	Huawei Term
maintenance entity function	MEF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
maintenance entity group	MEG	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"
mobile equipment identifier	MEID	N/A	N/A	ETSI TS 102 671 V9.2.0: "Smart Cards; Machine to Machine UICC; Physical and logical characteristics "
master eNodeB	MeNB	N/A	In dual connectivity, the eNodeB which terminates at least S1-MME.	ETSI TS 136 300 V16.5.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
maintenance association end point	MEP	N/A	A MEP sends and receives CFM frames through the relay function, drops all CFM frames of its level or lower that come from the wire side.	Wikipedia
Multi-Mode Extended Radio Frequency Card	MERC	N/A	A multimode extended RF card that processes RF signals sent from a signal source in the LampSite solution.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
measurement gap	MG	N/A	N/A	3GPP TS 38.133 V17.3.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Requirements for support of radio resource management (Release 17)"
media gateway control function	MGCF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
media gateway control part	MGCP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
measurement gap length	MGL	N/A	N/A	3GPP TS 38.133 V17.3.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Requirements for support of radio resource management (Release 17)"
measurement gap repetition period	MGRP	N/A	N/A	3GPP TS 38.133 V17.3.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Requirements for support of radio resource management (Release 17)"
mobile global title	MGT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
measurement gap timing advance	MGTA	N/A	N/A	3GPP TS 38.331 V16.7.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Radio Resource Control (RRC) protocol specification (Release 16)"
media gateway	MGW	MG	The media gateway converts media provided in one type of network to the format required in another type of network.	ITU-T H.248.1: "Gateway control protocol: Version 3"
Multimedia and Hypermedia Information Coding Expert Group	MHEG	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
message handling system	MHS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
master information block	MIB	N/A	The MIB is always transmitted on the BCH with a periodicity of 80 ms and repetitions made within 80 ms and it includes parameters that are needed to acquire SIB1 from the cell.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
mobile interface controller	MIC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
MBMS indicator channel	MICH	N/A	The MBMS Indicator Channel (MICH) is a fixed rate (SF=256) physical channel used to carry the MBMS notification indicators. The MICH is always associated with an S-CCPCH to which a FACH transport channel is mapped.	3GPP TS 25.211 V16.0.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Physical channels and mapping of transport channels onto physical channels (FDD) (Release 16)"
management information model	MIM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
multiple-input multiple-output	MIMO	N/A	In radio, multiple-input and multiple-output, or MIMO, is a method for multiplying the capacity of a radio link using multiple transmission and receiving antennas to exploit multipath propagation.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
mobile identification number	MIN	N/A	The mobile identification number (MIN) or mobile subscription identification number (MSIN) refers to the 10-digit unique number that a wireless carrier uses to identify a mobile phone, which is the last part of the international mobile subscriber identity (IMSI).	Wikipedia
mobile IP	MIP	N/A	N/A	3GPP TS 33.108 version 9.8.0: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Handover interface for Lawful Interception (LI)"
maintenance domain intermediate point	MIP	N/A	N/A	ETSI ES 203 385 V1.1.1: "CABLE; DOCSIS® Layer 2 Virtual Private Networking"

Term	Abbreviation	Synonym	Definition	Reference
million instructions per second	MIPS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
multiple-input single-output	MISO	N/A	Multiple-input single-output (MISO) is an antenna technology for wireless communications. Based on single-input single-output (SISO), MISO uses a single receive antenna and multiple transmit antennas.	Huawei Term
mobility load balancing	MLB	N/A	N/A	Huawei Term
C-IoT basic feature description	MLBFD	N/A	N/A	Huawei Term
mobile location center	MLC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
C-IoT optional feature description	MLOFD	N/A	N/A	Huawei Term
Multilink Point-to-Point Protocol	MLPPP	• MP • MPPP • MLP	Multilink PPP (also referred to as MLPPP, MP, MPPP, MLP, or Multilink) provides a method for spreading traffic across multiple distinct PPP connections. It is defined in RFC 1990. It can be used, for example, to connect a home computer to an Internet Service Provider using two traditional 56k modems, or to connect a company through two leased lines.	Wikipedia
mobility management	MM	N/A	Mobility management is one of the major functions of a wireless network that allows mobile phones to work. The aim of mobility management is to track where the subscribers are, allowing calls, SMS and other mobile phone services to be delivered to them.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multimedia controller	MMC	N/A	N/A	Huawei Term
mobility management call control	MMCC	N/A	N/A	Huawei Term
mobility management entity	MME	N/A	The MME is the key control-node for the LTE access network. It is responsible for idle mode user equipment (UE) paging and tagging procedure including retransmissions.	Wikipedia
mobility management entity code	MMEC	MME Code	The IE MMEC identifies an MME within the scope of an MME Group within a PLMN.	3GPP TS 36.331 V16.5.0: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
multimedia message enterprise gateway	MMEG	N/A	A module, which is evolved from the multimedia message gateway, in the industry gateway system for accessing multimedia message services provided by EC/SI applications and scheduling multimedia messages.	Huawei Term
mobility management entity group identifier	MMEGI	MME group identifier	The MMEGI uniquely identifies an MME group within a PLMN.	Huawei Term
mobility management entity identifier	MMEI	MME identifier	The MMEI shall be constructed from an MME Group ID (MMEGI) and an MME Code (MMEC).	3GPP TS 23.003 V17.2.0: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Numbering, addressing and identification; (Release 17)"
Mobile Broadband Automation Engine-Mobile (MAE-M) feature description	MMFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
man-machine interface	MMI	human-machine interface (HMI)	A human-machine interface (HMI) interfaces machines with physical input hardware such as keyboards, mice, or game pads, and output hardware such as computer monitors, speakers, and printers.	Wikipedia
man-machine language	MML	MML command	Man-machine language (MML) is an operation method for abstract objects. The OSS delivers MML commands to perform operations on abstract objects.	Huawei Term
minimum mean square error	MMSE	N/A	An estimation method which minimizes the mean square error (MSE)	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multimedia message service environment	MMSE	N/A	A collection of MMS-specific network elements under the control of a single administration.	3GPP TS 23.140 version 4.3.0: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Multimedia Messaging Service (MMS); Functional description; Stage 2"
Mobility Management Short Message Service	MMSMS	N/A	N/A	Huawei Term
Mobility Management Supplement Service	MMSS	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Massive Machine Type Communication	mMTC	N/A	Massive Machine Type Communication (mMTC) is one of the three typical 5G application scenarios (of eMBB, URLLC, and mMTC). mMTC is mainly used for information exchange between people and things. It provides optimized signaling control when the connection density is high, supporting efficient access and management of massive IoT devices of low costs and low power consumption.	ETSI TR 138 913 V16.0.0: "5G; Study on scenarios and requirements for next generation access technologies"

Term	Abbreviation	Synonym	Definition	Reference
millimeter wave	mmWave	N/A	Extremely high frequency (EHF) is the International Telecommunication Union (ITU) designation for the band of radio frequencies in the electromagnetic spectrum from 30 to 300 gigahertz (GHz). It lies between the super high frequency band and the far infrared band, the lower part of which is the terahertz band. Radio waves in this band have wavelengths from ten to one millimetre, so it is also called the millimetre band and radiation in this band is called millimetre waves, sometimes abbreviated MMW or mmWave.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
mobile network code	MNC	N/A	The MNC is the second field of the IMSI, it is two or three digits in length and is administered by the respective national numbering plan administrator. MNCs under MCC ranges 90x are administered by the Director of TSB. The MNC, in combination with the MCC, provides sufficient information to identify the home network.	ITU-T E.212: "The international identification plan for public networks and subscriptions"
mobile network operator	MNO	N/A	A provider of wireless communications services that owns or controls all the elements necessary to sell and deliver services to an end user including radio spectrum allocation, wireless network infrastructure, backhaul infrastructure, billing, customer care, provisioning computer systems and marketing and repair organizations.	ETSI TS 105 200-2-3 V1.2.1: "Access, Terminals, Transmission and Multiplexing (ATTM); Energy management; Operational infrastructure s; Implementati on of Global KPIs; Part 2: Specific requirements; Sub-part 3: Mobile broadband access networks"

Term	Abbreviation	Synonym	Definition	Reference
Mobile Number Portability	MNP	N/A	The ability for a mobile subscriber to change digital mobile subscription network within the same country retaining their original DN(s). Additional regulatory constraints apply in North America.	3GPP TS 22.066: "Support of Mobile Number Portability (MNP); Service description; Stage 1; Support of Mobile Number Portability (MNP); Service description; Stage 1"
Mobile Network Signalling	MNS	N/A	N/A	ETSI TS 124 007 V10.0.0: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface signalling layer 3; General Aspects (3GPP TS 24.007 version 10.0.0 Release 10)"

Term	Abbreviation	Synonym	Definition	Reference
managed object	MO	N/A	A managed object (MO) is an abstract representation of managed network resources. In each NE, an MO can be used to indicate a physical entity (such as RET) or a logical entity or protocol object (such as UtranNCell). Users can add, remove, or modify MOs to manage base stations.	Huawei Term
mobile originated	MO	N/A	A type of messages that the mobile station (MS) submits to the short message center (SMC) and the SMC stores and forwards to destination subscribers.	Huawei Term
mobile originated call	MOC	N/A	N/A	Huawei Term
multi-operator core network	MOCN	N/A	A network-sharing configuration in which only the RAN is shared.	3GPP TS 23.251: "Technical Specification Group Services and System Aspects; Network Sharing; Architecture and functional description"

Term	Abbreviation	Synonym	Definition	Reference
mobile originated handover	MOHO	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Mobile Originating Location Request	MO-LR	Mobile Originated Location Request	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
mean opinion score	MOS	N/A	Quality is fundamentally related to the subjective assessment of the considered aspect. The KQI will be related to corresponding subjective quality assessments. The quality often is rated as an opinion score on a 5-point scale ranging from "bad" (1), "poor" (2), "fair" (3), "good" (4) to "excellent" (5). The average of these scores calculated from a group of subjects is the Mean Opinion Score (MOS).	3GPP TR 26.909: "Technical Specification Group Services and System Aspects; Study on improved streaming Quality of Experience (QoE) reporting in 3GPP services and networks"
mobile originated short message service	MO-SMS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
memorandum of understanding	MoU	N/A	N/A	Huawei Term
minute of usage	MOU	N/A	N/A	Huawei Term
maintenance point	MP	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Multilink PPP	MP	N/A	Multilink PPP (MP) is a standard for aggregating multiple PPP links that allows for multivendor interoperability, and is defined in RFC 1717. MP defines a way of sequencing and transmitting packets over multiple physical interfaces. To reduce potential latency issues, MP also defines a method of fragmenting and reassembling large packets.	Huawei Term
Moving Pictures Experts Group	MPEG	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
maintenance point identification	MPID	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Multiprotocol Label Switching	MPLS	N/A	Multiprotocol Label Switching (MPLS) is a routing technique in telecommunications networks that directs data from one node to the next based on short path labels rather than long network addresses, thus avoiding complex lookups in a routing table and speeding traffic flows. The labels identify virtual links (paths) between distant nodes rather than endpoints. MPLS can encapsulate packets of various network protocols, hence the "multiprotocol" reference on its name. MPLS supports a range of access technologies, including T1/E1, ATM, Frame Relay, and DSL.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multiprotocol label switching virtual private network	MPLS VPN	N/A	An Internet Protocol (IP) virtual private network (VPN) based on the multiprotocol label switching (MPLS) technology. It applies the MPLS technology for network routers and switches, simplifies the routing mode of core routers, and combines traditional routing technology and label switching technology. It can be used to construct the broadband Intranet and Extranet to meet various service requirements.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
maximum power reduction	MPR	N/A	3GPP specifications impose constraints on the indicators related to UE transmit power, including the maximum output power (MPR), and (A-MPR). MRP is a reduction in the UE maximum output power to meet the requirements for the transmit signal quality or spectral radiation. Such requirements may not be met when the peak-to-average power ratio (PAPR) of UE transmit signals is high or the RBs allocated to UEs are close to the bandwidth edge, due to factors such as modulation orders, transmit PRB positions, and bandwidth configurations. The MPR value is related to the modulation waveform, modulation mode, and allocated RB position.	Huawei Term
main processing subcarrier	MPS	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
main processing and transmission unit	MPT	N/A	A unit that manages configurations and devices, monitors performance, and processes signaling of a base station. It also processes signaling, manages resources for other boards in the BBU, and provides ports which are used for signal transmission, automatic software upgrade, and LMT- or MAE-based BBU maintenance.	Huawei Term
main processing unit	MPU	N/A	It is used to manage the user plane resources, control plane resources, and transmission resources of the system.	Huawei Term
measurement report	MR	N/A	N/A	3GPP TS 32.425: "Telecommunication management; Performance Management (PM); Performance measurements Evolved Universal Terrestrial Radio Access Network (E-UTRAN)"

Term	Abbreviation	Synonym	Definition	Reference
mixed reality	MR	N/A	Mixed reality (MR) is a term used to describe the merging of a real-world environment and a computer-generated one. Physical and virtual objects may co-exist in mixed reality environments and interact in real time.	Wikipedia
maximal ratio combining	MRC	N/A	N/A	3GPP TR 45.914: "Circuit switched voice capacity evolution for GSM/EDGE Radio Access Network (GERAN)"
Multi-Radio Dual Connectivity	MR-DC	multi-RAT dual connectivity	Multi-Radio Dual Connectivity (MR-DC) is a generalization of the Intra-E-UTRA Dual Connectivity (DC), where a multiple Rx/Tx capable UE may be configured to utilise resources provided by two different nodes connected via non-ideal backhaul, one providing NR access and the other one providing either E-UTRA or NR access.	3GPP TS 37.340: "Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) and NR; Multi-connectivity; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
Multimod e RAN feature descriptio n	MRFD	N/A	N/A	Huawei Term
mobility robustnes s optimizati on	MRO	N/A	N/A	3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification"
mouth reference point	MRP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
Maximum Ratio Transmission	MRT	N/A	Maximum Ratio Transmission can be considered the generalization of the maximum ratio algorithm for multiple transmitting antennas and multiple receiving antennas. It also provides a reference for the optimal performance that a system may obtain using both transmit and receive diversity.	ETSI TR 102 662: "Satellite Earth Stations and Systems (SES); Advanced satellite based scenarios and architectures for beyond 3G systems"
maximum receive unit	MRU	N/A	N/A	SPAN TR 102.16: "Potential solutions to support the transmission of PPP"
mobile station	MS	N/A	Any mobile device, such as a mobile handset or computer, which is used to access network services.	ITU-T X.1125: "Correlative Reacting System in mobile data communication"

Term	Abbreviation	Synonym	Definition	Reference
multiplex section alarm indication signal	MS-AIS	N/A	An all-ONES characteristic or adapted information signal. It is generated to replace the normal traffic signal when that signal contains a defect condition in order to prevent consequential downstream failures being declared or alarms being raised.	Huawei Term
most significant bit	MSB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile switching center	MSC	N/A	The MSC switches circuit mode MS originated or MS terminated traffic. An MSC is usually connected to at least one BS. It may connect to the other public networks (PSTN, ISDN, etc.), other MSCs in the same network, or MSCs in different networks.	ITU-T Q.1742.1: "IMT-2000 references to ANSI-41 evolved core network with cdma2000 access network"

Term	Abbreviation	Synonym	Definition	Reference
MBMS point-to-multipoint scheduling channel	MSCH	N/A	N/A	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification (Release 16)"
mobile station class mark	MSCM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile switching center server	MSC-S	MSC server	The MSC server mainly comprises the call control (CC) and mobility control parts of a MSC.	3GPP TS 23.002: "Network architecture"
mobile station control unit	MSCU	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
MExE Service Environment	MSE	N/A	Depending on the configuration of the PLMN, the operator may be able to offer support to MExE services in various ways. Examples of possible sources are from traditional GSM nodes, IN nodes, operator-specific nodes, operator franchised nodes and services provider nodes, together with access to nodes external (i.e. vendor-specific) to the PLMN depending on the nature of the MExE service. These nodes are considered to constitute the MExE service environment. The MExE service environment shall support direct MExE UE to MExE UE interaction of MExE services.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile station identifier	MSID	MSI	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
mobile station identification number	MSIN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile subscriber ISDN number	MSISDN	- mobile station international ISDN number - mobile station international subscriber directory number	An MSISDN is the phone number assigned to a user. This is mainly used by a user (i.e., calling party) to set up a call with another user (i.e., called party). Using the MSISDN number, the call request is forwarded to the called party's home subscriber server (HSS), where the MSISDN number is mapped to the IMSI to find the current location of the called party in the core network.	ITU-T Y.3031: "Identification framework in future networks"
MCH scheduling period	MSP	N/A	N/A	Huawei Term
multiplex section protection	MSP	N/A	N/A	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multi-standard radio	MSR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile station roaming number	MSRN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
maximum segment size	MSS	N/A	The maximum segment size (MSS) is a parameter of the options field of the TCP header that specifies the largest amount of data, specified in bytes, that a computer or communications device can receive in a single TCP segment. It does not count the TCP header or the IP header (unlike, for example, the MTU for IP datagrams). The IP datagram containing a TCP segment may be self-contained within a single packet, or it may be reconstructed from several fragmented pieces; either way, the MSS limit applies to the total amount of data contained in the final, reconstructed TCP segment.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
multiple spanning tree instance	MSTI	N/A	A type of spanning tree calculated through MSTP within an MST region. This type of spanning tree provides a simple and well-connected topology corresponding to one or more VLANs. A VLAN cannot be assigned to multiple MSTIs.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Multiple Spanning Tree Protocol	MSTP	N/A	The Multiple Spanning Tree Protocol (MSTP) and algorithm, provides both simple and full connectivity assigned to any given Virtual LAN (VLAN) throughout a Bridged Local Area Network. MSTP uses BPDUs to exchange information between spanning-tree compatible devices, to prevent loops in each MSTI (Multiple Spanning Tree Instances) and in the CIST (Common and Internal Spanning Tree), by selecting active and blocked paths. This is done as well as in STP without the need of manually enabling backup links and getting rid of bridge loops danger. Moreover, MSTP allows frames/packets assigned to different VLANs to follow separate paths, each based on an independent MSTI, within MST Regions composed of	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			LANs and or MST Bridges. These Regions and the other Bridges and LANs are connected into a single Common Spanning Tree (CST).	
message signal unit	MSU	N/A	A signal unit that contains service information and signaling information fields and is retransmitted by the signaling link control if it is received in error. The value of length indicator is always greater than 2.	Huawei Term
Mobile Termination	MT	N/A	Mobile Termination (MT) is the component of the Mobile Equipment (ME) which supports functions specific to management of the PLMN access interface (3GPP or non-3GPP). The MT is realized as a single functional entity.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mean time between failures	MTBF	N/A	The expectation of the time between failures.	ITU-T G.911: "Parameters and calculation methodologies for reliability and availability of fibre optic systems"

Term	Abbreviation	Synonym	Definition	Reference
MBS Traffic Channel	MTCH	N/A	A point-to-multipoint downlink channel for transmitting MBS data of either multicast session or broadcast session from the network to the UE.	3GPP TS 38.300: "Technical Specification Group Radio Access Network"
mobile terminating location request	MT-LR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
mobile-to-mobile (call)	MTM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Message Transfer Part	MTP	N/A	The Message Transfer Part (MTP) is part of the Signaling System 7 (SS7) used for communication in public switched telephone networks. MTP is responsible for reliable, unduplicated and in-sequence transport of SS7 messages between communication partners.	Wikipedia
Message Transfer Part Layer 3	MTP3	N/A	MTP3 provides routing functionality to transport signaling messages through the SS7 network to the requested endpoint.	Wikipedia
NodeB multi-carrier transceiver unit	MTRU	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
mobile terminated short message service	MT-SMS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Mean Time To Repair	MTTR	- Mean Time to Recovery - Mean Time to Restore	The total corrective maintenance time divided by the total number of corrective maintenance actions during a given period of time.	ITU-T G.911: "Parameters and calculation methodologies for reliability and availability of fibre optic systems"
maximum transmission unit	MTU	N/A	The maximum sized datagram that can be transmitted through the next network is called the maximum transmission unit (MTU).	"INTERNET PROTOCOL DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION", RFC 791, September 1981
Mark Up	MU	N/A	An increase over the basic charge e.g. to provide extra revenue or to cover additional costs	3GPP TS 22.024: "Technical Specification Group Services and System Aspects; Description of Charge Advice Information (CAI)"

Term	Abbreviation	Synonym	Definition	Reference
mobile user identifier	MUI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
multi-user multiple-input multiple-output	MU-MIMO	multi-user MIMO	Multi-user MIMO (MU-MIMO) is a MIMO technology used for multipath wireless communication. It involves multiple users or devices, each of which performs radio communication through one or more antennas.	Huawei Term
multi user mobile station	MUMS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
mobile virtual network operator	MVNO	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
M2 interface	N/A	N/A	An Application Part is defined for this interface, which conveys at least radio configuration data for the multi-cell transmission mode eNodeBs and Session Control Signaling. SCTP is used as signaling transport i.e. Point-to-Point signaling is applied.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
MAC-c	N/A	N/A	MAC-c, is the MAC entity that handles the following transport channels: - paging channel (PCH) - forward access channel (FACH) - random access channel (RACH) - downlink shared channel (DSCH). The DSCH exists only in TDD mode. - uplink shared channel (USCH). The USCH exists only in TDD mode.	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"
MAC-d	N/A	N/A	MAC-d is the MAC entity that handles the following transport channels: dedicated transport channel (DCH).	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
MAC-e	N/A	N/A	MAC-e/es is the MAC entities that handle the following transport channels: - enhanced dedicated transport channel (E-DCH).	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"
MAC-es	N/A	N/A	MAC-e/es is the MAC entities that handle the following transport channels: - enhanced dedicated transport channel (E-DCH).	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"
MAC-hs	N/A	N/A	MAC-hs is the MAC entity that handles the following transport channels: - high speed downlink shared channel (HS-DSCH)	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
MAC-i	N/A	N/A	MAC-i/is are the MAC entities that handle the following transport channel: enhanced dedicated transport channel (E-DCH).	3GPP TS 25.321: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification"
main subrack	N/A	N/A	The subrack in the center of a star topology where subracks are connected	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
manual switch	N/A	N/A	A switch action initiated by an operator command. It switches the extra traffic signal, normal traffic signal, or the null signal to the protection transport entity, unless a fault condition exists on other transport entities or an equal or higher priority switch command is in effect. In the case of a manual switch of extra traffic or null signal, a normal traffic signal present on the protection transport entity is transferred to and selected from its working transport entity.	ITU-T G.808: "Terms and definitions for network protection and restoration"

Term	Abbreviation	Synonym	Definition	Reference
Massive MIMO AAU	N/A	N/A	AAU that uses large-scale antenna arrays to jointly receive, demodulate, or transmit signals. Its TX/RX mode can reach or even exceed 32T32R, significantly improving the system link quality and transmission rate. In addition, this AAU can flexibly adjust the shape of the beams in the horizontal and vertical planes, greatly improving base stations' 3D coverage capability.	Huawei Term
master server	N/A	N/A	A master server manages backups, archives, and restores. It is responsible for media and device selection for NetBackup. Typically, a master server contains the NetBackup catalog. The catalog contains the internal databases that contain information about NetBackup backups and configuration.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
master-slave synchronization	N/A	N/A	In master-slave synchronization mode, a designated master clock periodically sends synchronization signals to all other slave clocks.	Huawei Term
measurement event	N/A	N/A	A measurement event corresponds to the signal strength or signal quality status of a cell.	• Huawei Term • 3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
message arrival rate	N/A	N/A	The number of specified messages received by the BSC in a unit time.	Huawei Term
message routing	N/A	N/A	The process for selecting, for each signalling message to be sent, the signalling link to be used.	ITU-T Q.9: "Vocabulary of switching and signalling terms"
MetaAAU	N/A	N/A	Innovative AAU with extremely large antenna array (ELAA). It supports up to 384 antenna elements, improving coverage and reducing energy consumption.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
metamaterial	N/A	N/A	A metamaterial is any material engineered to have a property that is not found in naturally occurring materials.	Wikipedia
mobility	N/A	N/A	The ability for the user to communicate whilst moving independent of location.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
modulation scheme	N/A	N/A	In electronics and telecommunications, modulation is the process of varying one or more properties of a periodic waveform, called the carrier signal, with a separate signal called the modulation signal that typically contains information to be transmitted.	Wikipedia
mounting ear	N/A	- mount angle - ear bracket - mount hanger - rack-mounting ear	A piece of angle iron or plate on a rack. The mounting ear has holes that can be used to fix network elements or components.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
MSC status	N/A	N/A	The MSC can be in the administration state and the operation state. In the administration state, data configuration and private message on the A interface can be modified. The administration state can be normal, offload, or inhibited. The operation state indicates the actual status of the CN. The operation state can be available or unavailable. For example, the CN is unavailable when the No.7 signaling link is disconnected and becomes available when the No.7 signaling link is resumed.	Huawei Term
Msg3	N/A	N/A	First scheduled transmission of the random access procedure	3GPP TS 38.300: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2 (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
multicast	N/A	N/A	Communication between a single sender and multiple receivers	ETSI GS LTN 001: "Low Throughput Networks (LTN); Use Cases for Low Throughput Networks"
multicast group	N/A	N/A	A group of users that have an activated MBMS in multicast mode and therefore are ready to or are receiving data transmitted by this service. The multicast group is a subset of the multicast subscription group. Multicast subscription group members may join the corresponding multicast group.	3GPP TS 22.146: "Multimedia Broadcast/Multicast Service (MBMS); Stage 1"
multipath delay spread	N/A	N/A	Multipath delay spread is the delay spread (broadened pulse width) of a received signal relative to the transmitted signal due to the multipath effect.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
multipath effect	N/A	N/A	Multipath effect is a propagation phenomenon that results in signals reaching the receive end by two or more paths. The length (delay) and attenuation of each path vary with time.	Huawei Term
multiple IP addresses on port	N/A	N/A	Multiple IP addresses can be configured on a physical port. These addresses are all equal. The purpose is to allow transmission of data to different IP addresses on the same port, better utilizing port resources.	Huawei Term
multiplexing	N/A	N/A	A process for combining signals from several separate tributary channels for transmission in the same direction over a common bearer channel.	ITU-T R.140: "DEFINITIONS OF ESSENTIAL TECHNICAL TERMS IN THE FIELD OF TELEGRAPH TRANSMISSION"
multiplexing gain	N/A	N/A	An increase in throughput by adding spatial channels without increasing the bandwidth or transmit power	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
minimum SI	MSI	N/A	Minimum SI comprises basic information required for initial access and information for acquiring any other SI.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage 2"
Mobile Intelligent Engine	MIE	N/A	N/A	Huawei Term

1.15 N

Term	Abbreviation	Synonym	Definition	Reference
network assisted cell change	NACC	N/A	NACC, the Network Assisted Cell Change feature introduced in Release 4 is a tool to minimize the service outage time for all QoS classes when a GPRS MS in packet transfer mode moves between GSM cells belonging to the same BSC.	3GPP TR 44.901: "GSM/EDGE External Network Assisted Cell Change (NACC)"
negative acknowledgement	NACK	N/A	The negative acknowledgement (NACK) signal is sent to reject a previously received message or to indicate some kind of error.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
node address byte	NAD	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
network access identifier	NAI	N/A	The userID submitted by the client during PPP authentication. In roaming, the purpose of the NAI is to identify the user as well as to assist in the routing of the authentication request. Please note that the NAI may not necessarily be the same as the user's e-mail address or the userID submitted in an application layer authentication.	B. Aboba, and M. Beadles, "The Network Access Identifier", RFC 2486, January 1999
non-access stratum	NAS	N/A	Non-access stratum (NAS) is a functional layer in wireless telecom protocol stacks between the core network and user equipment.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
network address translation	NAT	N/A	Network address translation (NAT) is a method of mapping an IP address space into another by modifying network address information in the IP header of packets while they are in transit across a traffic routing device.	Wikipedia
narrowband	NB	N/A	Systems delivering service to the end user with a bandwidth of 2 Mbit/s or less.	ETSI TR 101 030: "Radio Equipment and Systems (RES); Radio Local Loop (RLL) Co-ordination Group; Survey of ETSI activities and recommendations for the ETSI work programme"

Term	Abbreviation	Synonym	Definition	Reference
Normal Burst	NB	N/A	Burst containing Low Bit Rate part (LBR-part) followed by High Bit Rate part (HBR-part) data	ETSI ETS 300 836-1: "Broadband Radio Access Networks (BRAN); High PERformance Radio Local Area Network (HIPERLAN) Type 1; Conformance testing specification; Part 1: Radio type approval and Radio Frequency (RF) conformance test specification"
NodeB application part	NBAP	N/A	Signalling protocol responsible for the control of the NodeB by the RNC is called NBAP (NodeB Application Part). NBAP is subdivided into Common and Dedicated NBAP (CNBAP and DNBAP), where Common NBAP controls overall NodeB functionality and Dedicated NBAP controls separate cells or sectors of the NodeB. NBAP is carried over Iub.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
NarrowBand Internet of Things Base Station	NBBS	N/A	A base station that supports the Narrowband Internet of Things (NB-IoT) technology	Huawei Term
Narrowband Internet of Things	NB-IoT	N/A	Narrowband Internet of Things (NB-IoT) is a Low Power Wide Area Network (LPWAN) radio technology standard developed by 3GPP to enable a wide range of cellular devices and services. The specification was frozen in 3GPP Release 13 (LTE Advanced Pro), in June 2016.	Wikipedia
network control mode 2	NC2	N/A	In network control mode 2 (NC2), the network controls the cell reselection of MSs.	Huawei Term
next hop chaining count	NCC	N/A	Next hop chaining count (NCC) is a counter related to NH (i.e. the amount of Key chaining that has been performed) which allows the UE to be synchronized with the eNodeB and to determine whether the next KeNB needs to be based on the current KeNB or a fresh NH.	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
network color code	NCC	N/A	The NCC is assigned to each network provider so the MS can sort out which base stations it is allowed to camp on.	Wikipedia
non-cell-defining synchronization signal and PBCH block	NCD-SSB	N/A	A non-cell-defining synchronization signal and PBCH block (NCD-SSB) is an SSB that is not associated with an RMSI.	3GPP TS 38.300: "NR; NR and NG-RAN Overall Description; Stage 2 (Release 17)"
NR cell global identifier	NCGI	N/A	The NR cell global identifier (NCGI) is used to identify NR cells globally and is constructed from the PLMN identity the cell belongs to and the NR Cell Identity (NCI) of the cell.	3GPP TS 38.300: "Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2"
Notification Channel	NCH	N/A	Common control channel on which the notifications are sent by the network (equivalent to a paging channel)	3GPP TS 43.068: "Technical Specification Group Core Network; Voice Group Call Service (VGCS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
NR Cell Identity	NCI	N/A	The NCI shall be of fixed length of 36 bits and shall be coded using full hexadecimal representation. These 36 bits are composed of gNB ID and Cell ID, broadcasting NR cell ID within SIB1.	3GPP TS 23.003: "Technical Specification Group Core Network and Terminals; Numbering, addressing and identification"
network control key	NCK	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
neighboring cell list	NCL	N/A	An NCL refers to a list of external cells not served by the local base station. An NCL holds the information about the ECGLs, PCIs, and frequencies of external cells.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Network Control Protocol	NCP	N/A	Provides for address negotiation and compression on different network layers.	ETSI TR 101 194: "Digital Video Broadcasting (DVB); Guidelines for implementation and usage of the specification of network independent protocols for DVB interactive services"
network domain security	NDS	N/A	N/A	3GPP TS 36.401: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Architecture description"

Term	Abbreviation	Synonym	Definition	Reference
network determined user busy	NDUB	N/A	If all of the appropriate user-network interface information channels are busy (channels busy) and either the network does not support the offering of additional calls beyond the number of appropriate channels, or the maximum number of such additional calls has been reached, the network will clear the call and indicate network determined user busy.	ETSI ETS 300 392-12-13: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-Part 13: Call Completion to Busy Subscriber (CCBS)"
network element	NE	N/A	A discrete telecommunications entity which can be managed over a specific interface e.g. the RNC.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
new establishment causes indication	NECI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Network Element Function	NEF	N/A	A function block which represents the telecommunication functions and communicates with the TMN OSF function block for the purpose of being monitored and/or controlled.	Huawei Term
network exposure function	NEF	N/A	N/A	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2 (Release 16)"
network evaluated handover	NEHO	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
network element layer	NEL	N/A	Refers to the physical resources that reside in the access network.	ITU-T Q.833.1: "Asymmetric digital subscriber line (ADSL) – Network element management: CMIP model"

Term	Abbreviation	Synonym	Definition	Reference
Network Function	NF	N/A	A functional building block within a network infrastructure, which has well-defined external interfaces and a well-defined functional behaviour. In practical terms, a Network Function is today often a network node or physical appliance.	ETSI GS NFV-PER 001: "Network Functions Virtualisation (NFV); NFV Performance & Portability Best Practises"
NG Application Protocol	NGAP	N/A	NGAP provides the signalling service between the NG-RAN node and the AMF that is required to fulfil the NGAP functions described in TS 38.410.	3GPP TS 38.413: "NG-RAN; NG Application Protocol (NGAP)"

Term	Abbreviation	Synonym	Definition	Reference
NG Radio Access Network	NG-RAN	N/A	NG-RAN refers to a radio access network that supports one or more of the following options, with the common characteristics that the RAN interfaces with the next generation core. 1. Standalone New Radio, 2. Standalone New Radio is the anchor with Evolved E-UTRA extensions, 3. Evolved E-UTRA, 4. Evolved E-UTRA is the anchor with New Radio extensions.	3GPP TR 23.799: "Technical Specification Group Services and System Aspects; Study on Architecture for Next Generation System"
next hop	NH	N/A	When configuring network devices the hop may refer to next hop. Next hop is the next gateway to which packets should be forwarded along the path to their final destination. A routing table usually contains the IP address of a destination network and the IP address of the next gateway along the path to the final network destination.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
network independent clocking	NIC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
NE information collector	NIC	N/A	The NE information collector (NIC) collects NE information during routine operation and maintenance work. It helps you view and analyze NE data.	Huawei Term
network identity and time zone	NITZ	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
non-line-of-sight propagation	NLOS propagation	• NLOS transmission • non-line-of-sight transmission	Non-line-of-sight (NLOS) radio propagation occurs outside of the typical line of sight (LOS) between the transmitter and receiver, such as in ground reflections. Obstacles that commonly cause NLOS propagation include buildings, trees, hills, mountains, and, in some cases, high voltage electric power lines. Some of these obstructions reflect certain radio frequencies, while some simply absorb or garble the signals; but, in either case, they limit the use of many types of radio transmissions, especially when low on power budget.	3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz"

Term	Abbreviation	Synonym	Definition	Reference
Network Manager	NM	N/A	A Network Manager (NM) provides a package of end-user functions with the responsibility for the management of a network, mainly as supported by the EM(s) but it may also involve direct access to the Network Elements. All communication with the network is based on open and well-standardised interfaces supporting management of multi-vendor and multi-technology Network Elements.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
network management layer	NML	N/A	From a QoS monitoring perspective, the NML is responsible for the collection and processing of performance, fault, and usage data.	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements"

Term	Abbreviation	Synonym	Definition	Reference
network mode of operation	NMO	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
NodeB monitoring unit	NMON	N/A	N/A	Huawei Term
NodeB main processing and timing unit	NMPT	N/A	N/A	Huawei Term
network measurement results	NMR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
network management system	NMS	N/A	This component is responsible for monitoring and control of SIMF agents. The exact nature of this function depends on the type of host component the agent is situated in, i.e. ECMG, EMMG, PDG, etc, and the type of management function the NMS component is performing, i.e. fault, configuration, accounting, performance and security management.	ETSI TS 103 197: "Digital Video Broadcasting (DVB); Head-end implementation of DVB SimulCrypt"
National Mobile Station Identifier	NMSI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
network-to-network interface	NNI	N/A	In telecommunications, a network-to-network interface (NNI) is an interface that specifies signaling and management functions between two networks. An NNI circuit can be used for interconnection of signaling (such as SS7), Internet Protocol (IP) (such as MPLS) or ATM networks.	Wikipedia
non access stratum node selection function	NNSF	N/A	The interconnection of an eNodeB to multiple MMEs/S-GWs is supported by the LTE/SAE architecture. Therefore an NAS node selection function is located in the eNodeB to determine the MME association of the UE.	ETSI TS 136 410 V9.0.0: "LTE; Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 layer 1 general aspects and principles"
network operator	NO	N/A	A Network Operator is an entity that operates public telecommunications network in order to route calls.	ETSI TR 101 118: "Network Aspects (NA); High level network architectures and solutions to support number portability"

Term	Abbreviation	Synonym	Definition	Reference
non-guaranteed bit rate	non-GBR	N/A	N/A	ETSI TS 103 202-2 V1.1.1: "Core Network and Interoperability Testing (INT); GTPv2-C Conformance Testing for S11 Interface; (3GPPTM Release 10); Part 3: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) pro forma specification"
non-gateway network element	non-GNE	N/A	A network element that communicates with the network management application layer through the gateway NE application layer.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
network performance	NP	N/A	Network Performance' (NP) is the ability of a network or network portion to provide the functions related to communications between users; it contributes to service accessibility, service retainability and service integrity. Network performance parameter values are usually derived from quality of service (QoS) parameter values.	ETSI ETR 309: "Special Mobile Group (SMG); Vocabulary for the Universal Mobile Telecommunications System (UMTS) (UMTS 01.02)"
numbering plan area	NPA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
network protocol data unit	NPDU	N/A	A type of protocol packet of the network layer in the seven-layer model defined by the ISO. An NPDU is equal to an IP packet in TCP/IP.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Numbering Plan Identifier	NPI	N/A	An indication of the numbering plan to which a number belongs; it is separate from the number itself.	ETSI ETS 300 189: "Private Telecommunication Network (PTN); Addressing"
non-public network	NPN	N/A	N/A	3GPP TS 23.501: "System architecture for the 5G System (5GS); Stage 2"
New Radio	NR	N/A	New Radio is a new radio access technology (RAT) developed by 3GPP for the 5G (fifth generation) mobile network.	Wikipedia
NR Absolute Radio Frequency Channel Number	NR-ARFCN	N/A	N/A	3GPP TS 38.101: "NR; User Equipment (UE) radio transmission and reception"
network repository function	NRF	N/A	N/A	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2 (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
network resource identifier	NRI	N/A	A specific parameter used to identify the CN node assigned to serve a mobile station	3GPP TR 23.236: "Technical Specification Group Services and System Aspects; Intra-domain connection of Radio Access Network (RAN) nodes to multiple Core Network (CN) nodes"
Network Resource Model	NRM	N/A	A protocol independent model describing managed objects representing network resources, e.g. an RNC or NodeB.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
neighboring radio network controller	NRNC	N/A	N/A	Huawei Term
non-real-time	NRT	N/A	Non-real-time bearer services are those services associated with RABs whose traffic class is defined as interactive or background.	ETSI TS 125 423 V5.7.0: "Universal Mobile Telecommunications System (UMTS); UTRAN Iur interface Radio Network Subsystem Application Part (RNSAP) signalling"

Term	Abbreviation	Synonym	Definition	Reference
neighboring relation table	NRT	- neighboring relationship table - neighbor relation table	A table that contains the information about the neighboring relations between a cell and its neighboring cells.	Huawei Term
non-real-time variable bit rate	nrt-VBR	NRT-VBR	The nrt-VBR service category is used for connections that transport variable bit rate traffic for which there is no inherent reliance on time synchronization between the traffic source and destination, but there is a need for an attempt at a guaranteed bandwidth or latency. An application that might require an nrt-VBR service category is Frame Relay interworking, where the Frame Relay CIR (Committed Information Rate) is mapped to a bandwidth guarantee in the ATM network. No delay bounds are associated with nrt-VBR service.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
network service	NS	N/A	Composition of network function(s) and/or network service(s), defined by its functional and behavioural specification.	ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV"
network system	NS	N/A	Network system is, by means of information technology, a computer network management system capable of data information, transmission, exchange and distribution.	Huawei Term
network service access point address	NSAP address	N/A	A network service access point address (NSAP address), defined in ISO/IEC 8348, is an identifying label for a service access point (SAP) used in OSI networking.	Wikipedia
network subset control key	NSCK	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
network service entity	NSE	N/A	A network service entity provides services from the underlying network to the CSEs.	Wikipedia
network subsystem	NSS	N/A	The network subsystem is a collection of different functions, linked by standardized interfaces.	Huawei Term
Network Slice Selection Assistance Information	NSSAI	N/A	The NSSAI is a collection of S-NSSAIs. An NSSAI may be a Configured NSSAI, a Requested NSSAI or an Allowed NSSAI.	ETSI TS 123 501 V16.6.0: "5G; System architecture for the 5G System (5GS)"
network slice selection function	NSSF	N/A	N/A	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2 (Release 16)"
network service virtual connection	NSVC	N/A	N/A	Huawei Term
network termination	NT	N/A	A functional group on the network side of a user-network interface (source: ITU-T I.112)	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
New Type Approval Advisory Board	NTAAB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
narrow-band time division duplexing	NTDD	• narrow-band TDD • narrowband TDD	Narrow TDD – the 1.28 Mcps chip rate UTRA-TDD option	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
non-terrestrial network	NTN	N/A	Networks, or segments of networks, using an airborne or space-borne vehicle to embark a transmission equipment relay node or base station.	3GPP TR 38.821: "Solutions for NR to support non-terrestrial networks (NTN)"
Network Time Protocol	NTP	N/A	The Network Time Protocol (NTP) is a networking protocol for clock synchronization between computer systems over packet-switched, variable-latency data networks.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
network user access	NUA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
national user/ USIM identifier	NUI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
network user identification	NUI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
normal uplink	NUL	N/A	The supplementary uplink (SUL) carrier can be configured as a complement to the normal UL (NUL) carrier.	ETSI TS 138 321 V16.4.0: "5G; NR; Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
null network resource identifier	null-NRI	N/A	A 'null-NRI' indicates to a radio node (BSC/RNC) that the NAS Node Selection Function shall be used for selecting a CN node to receive a message. There is one unique 'null-NRI' in a PLMN supporting pool functionality. In MOCN shared networks with multiple CN Operators, there is one unique 'null-NRI' per CN operator. That is, in MOCN networks the RAN Operator handles multiple 'null-NRIs'.	3GPP TS 23.236: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Intra-domain connection of Radio Access Network (RAN) nodes to multiple Core Network (CN) nodes (Release 16)"
national user part (SS7)	NUP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
NodeB universal transmission interface unit	NUTI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
N+1 backup	N/A	N/A	A backup mode in which n similar components provide services while another component serves as a backup of the n components. If one of the n components fails, the backup component takes over the faulty component to ensure service continuity.	Huawei Term
N+1 protection	N/A	N/A	A radio link protection system composed of multiple (N) working channels and one protection channel.	Huawei Term
near-far problem	N/A	hearability problem	The near-far problem or hearability problem is the effect of a strong signal from a near signal source in making it hard for a receiver to hear a weaker signal from a further source due to adjacent-channel interference, co-channel interference, distortion, capture effect, dynamic range limitation, or the like.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
network layer	N/A	• Layer 3 • L3	In the seven-layer OSI model of computer networking, the network layer is layer 3. The network layer is responsible for packet forwarding including routing through intermediate routers.	Wikipedia
network segment	N/A	N/A	According to the defining IEEE 802.3 standards for Ethernet, a network segment is an electrical connection between networked devices using a shared medium.	Wikipedia
network sharing	N/A	• co-construction and sharing • network sharing with dedicated carrier • network sharing with common carrier	Network sharing refers to the sharing of telecom network infrastructure, network equipment, and spectrum resources among operators and involves cooperation among these operators.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
network slicing	N/A	N/A	With network slicing, an operator's physical network can be sliced into multiple E2E (RAN, transport network, and core network) virtual logical networks that are isolated from one another and provide customizable network capabilities for industry customers. These customizable network capabilities include latency, bandwidth, number of connections, and reliability. This way, multiple logical networks can run on top of an operator's network, tailoring to the specific requirements of different services.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
non-broadcast LAI	N/A	N/A	Each CN node in a pool has to be assigned one unique non-broadcast LAI that it uses in case it wants to be offloaded. Each CN node in the pool has to be aware of the non-broadcast LAIs assigned to the other CN nodes in the pool, because in the case of re-distribution, the 'target CN node' will retrieve data (e.g. IMSI, security context, MM & PDP contexts) from the 'offloaded CN node' based on the non-broadcast LAI.	3GPP TS 23.236: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Intra-domain connection of Radio Access Network (RAN) nodes to multiple Core Network (CN) nodes (Release 16)"
northbound user	N/A	N/A	A user account that the NMS uses for login to the EMS server.	Wikipedia

1.16 O

Term	Abbreviation	Synonym	Definition	Reference
operation and maintenance	O&M	OM	Operation and maintenance (O&M) refers to a series of management functions and services, such as configuration management, performance management, fault management, and software management, keeping systems running properly.	Huawei Term
off air call set up	OACSU	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
operation s, administr ation, and maintena nce	OAM	• OA&M • operations, administrat ion, and manageme nt	Operations, administration and management or operations, administration and maintenance (OA&M or OAM) are the processes, activities, tools, and standards involved with operating, administering, managing and maintaining any system. This commonly applies to telecommunicatio n, computer networks, and computer hardware.	Wikipedia
operation, administr ation, and maintena nce protocol data unit	OAMPDU	N/A	Also called OAM protocol packet, Ethernet OAM reports link status by periodically exchanging OAMPDUs between devices. This helps network administrators effectively manage the network.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
occupied bandwidth	OBW	N/A	Occupied bandwidth is a measure of the bandwidth containing 99% of the total integrated power for transmitted spectrum and is centered on the assigned channel frequency.	ETSI TS 134 122: "Universal Mobile Telecommunications System (UMTS); Terminal conformance specification; Radio transmission and reception (TDD)"
ordinary clock	OC	N/A	An ordinary clock is a device with a single network connection and is either the source of a synchronization reference (master) or destination for a synchronization reference (slave).	Wikipedia
optical carrier level 3	OC-3	N/A	OC-3 is a network line with transmission data rate of up to 155.52 Mbit/s (payload: 148.608 Mbit/s; overhead: 6.912 Mbit/s, including path overhead) using fiber optics.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
outgoing calls barred within a CUG	OCB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
ODMA common control channel	OCCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
open card framework	OCF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
outgoing call information	OCI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
orthogonal channel noise simulator	OCNS	N/A	A mechanism used to simulate the users or control signals on the other orthogonal channels of a downlink.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
outgoing call timer	OCT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
oven controlled crystal oscillator	OCXO	N/A	A crystal oven is a temperature-controlled chamber used to maintain the quartz crystal in electronic crystal oscillators at a constant temperature, in order to prevent changes in the frequency due to variations in ambient temperature. An oscillator of this type is known as an oven-controlled crystal oscillator (OCXO, where "XO" is an old abbreviation for "crystal oscillator".) This type of oscillator achieves the highest frequency stability possible with a crystal.	Wikipedia
optional for operators to implement for their aim	OD	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
operator determined barring	ODB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
ODMA dedicated control channel	ODCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
ODMA dedicated channel	ODCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
ODMA dedicated traffic channel	ODTCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
orthogonal frequency division multiplexing	OFDM	N/A	In telecommunications, orthogonal frequency-division multiplexing (OFDM) is a type of digital transmission and a method of encoding digital data on multiple carrier frequencies. OFDM has developed into a popular scheme for wideband digital communication, used in applications such as digital television and audio broadcasting, DSL internet access, wireless networks, power line networks, and 4G/5G mobile communications.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
orthogonal frequency division multiple access	OFDMA	N/A	Orthogonal frequency division multiple access (OFDMA) is a multi-user version of the popular orthogonal frequency-division multiplexing (OFDM) digital modulation scheme. Multiple access is achieved in OFDMA by assigning subsets of subcarriers to individual users. This allows simultaneous low-data-rate transmission from several users.	Wikipedia
operational feature monitor	OFM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
overload indication	OI	overload indicator	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Object Identifier	OID	N/A	A unique identifier that identifies an object stored in the MCDData message store.	3GPP TR 23.282: "Technical Specification Group Services and System Aspects; Functional architecture and information flows to support Mission Critical Data (MCDData); Stage 2"
overload control	OLC	N/A	N/A	Huawei Term
outer loop link adaptation	OLLA	N/A	N/A	Huawei Term
outer loop power control	OLPC	outer-loop power control	In outer loop power control (OLPC), the serving radio network controller (SRNC) changes the target signal-to-interference ratio (SIR) for inner loop power control based on the cyclic redundancy check indicator (CRCI) and the quality estimate of uplink frames.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
overall loudness rating	OLR	N/A	Loudness loss between the speaking subscriber's mouth and the listening subscriber's ear via a connection	ETSI TR 102 024-7: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON) Release 4; End-to-end Quality of Service in TIPHON Systems; Part 7: Design guide for elements of a TIPHON connection from an end-to-end speech transmission performance point of view"
open-loop spatial multiplexing	OL-SM	N/A	A mode in which the UE needs not report precoding matrix indication (PMI). When the rank is equal to 1, open-loop spatial multiplexing (OL-SM) is equivalent to open-loop transmit diversity (OL-TD). When the rank is equal to 2, 3, or 4, OL-SM maps data streams onto different layers and performs precoding.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
open-loop transmit diversity	OL-TD	N/A	A mode in which the diversity gain can be achieved. Space-frequency block coding (SFBC) is used in the case of two TX antennas. The combination of SFBC and frequency switched TX diversity (FSTD) is used in the case of four TX antennas.	Huawei Term
Open Mobile Alliance	OMA	N/A	N/A	3GPP TR 23.981: "Interworking aspects and migration scenarios for IPv4-based IP Multimedia Subsystem (IMS) implementations"
operation and maintenance center	OMC	N/A	In mobile networks, an operation and maintenance center is the central location to operate and maintain the network.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
O&M channel	OMCH	- operations and maintenance channel - OM channel	O&M channels are established between base stations and the OSS. These channels are used to transmit operation and maintenance information about base stations. O&M channels use Secure Shell (SSH), Secure Sockets Layer (SSL), and Datagram Transport Layer Security (DTLS) protocols to protect data transmission.	Huawei Term
ONT management and control interface	OMCI	N/A	N/A	ETSI ES 203 312: "Integrated broadband cable telecommunication networks (CABLE); Cabinet DOCSIS (C-DOCSIS) System Specification"
operation and maintenance link	OML	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Bidirectional Optimistic Mode	O-Mode	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
operation and maintenance unit	OMU	N/A	An operation and maintenance unit (OMU) is a logical concept. In the OM subsystem, it works as a bridge between the OM terminal and the host.	Huawei Term
on-off-keying	OOK	N/A	On-off keying (OOK) denotes the simplest form of amplitude-shift keying (ASK) modulation that represents digital data as the presence or absence of a carrier wave.	Wikipedia
operating expense	OPEX	N/A	OPEX is an ongoing cost for running a product, business, or system.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
operator controlled PLMN (selector list)	OPLMN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
optimal routing	OR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
ODMA random access channel	ORACH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
Open Radio Access Network	ORAN	N/A	ORAN, also known as Open Radio Access Network (Open RAN), is the concept of a fully interoperable radio access network. Its interface protocol aims to transform the RAN towards an open, intelligent, virtualized, and full interoperable RAN.	Wikipedia
optimal routing for latecall forwarding	ORLCF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
operating system	OS	N/A	An operating system (OS) is system software that manages computer hardware, software resources, and provides common services for computer programs.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
open systems interconnection	OSI	Open System Interconnection	The term Open Systems Interconnection (OSI) qualifies standards for the exchange of information among systems that are "open" to one another for this purpose by virtue of their mutual use of the applicable standards.	ITU-T X.200: "INFORMATION TECHNOLOGY - OPEN SYSTEMS INTERCONNECTION - BASIC REFERENCE MODEL: THE BASIC MODEL"
other system information	OSI	Other SI	Other SI encompasses all SIBs not broadcast in the minimum SI.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage 2"
OSI reference model	OSI RM	N/A	Seven-layer structure designed to describe computer network architectures and the way that data passes through them. This model was developed by the ISO in 1978 to clearly define the interfaces in multivendor networks, and to provide users of those networks with conceptual guidelines in the construction of such networks (see IETF RFC 1983 and ITU-T Recommendation X.200)	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"

Term	Abbreviation	Synonym	Definition	Reference
optical switch node	OSN	N/A	N/A	Huawei Term
Octet Stream Protocol	OSP	N/A	The Octet Stream Protocol (OSP) is used to carry an unstructured octet (character) stream between the MS and GGSN. It is used to provide a character pipe to allow an MS to communicate (via the GGSN) with an arbitrary Internet host, or other character-based service.	3GPP TS 23.060: "Technical Specification Group Services and System Aspects; General Packet Radio Service (GPRS); Service description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
Open Shortest Path First	OSPF	N/A	Open Shortest Path First (OSPF) is a routing protocol for Internet Protocol (IP) networks. It uses a link state routing (LSR) algorithm and falls into the group of interior gateway protocols (IGPs), operating within a single autonomous system (AS). It is defined as OSPF Version 2 in RFC 2328 (1998) for IPv4. The updates for IPv6 are specified as OSPF Version 3 in RFC 5340 (2008). OSPF supports the Classless Inter-Domain Routing (CIDR) addressing model. OSPF is a widely used IGP in large enterprise networks. IS-IS, another LSR-based protocol, is more common in large service provider networks.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
operation s support system	OSS	N/A	Operations support systems (OSS) are computer systems used by telecommunications service providers to manage their networks (e.g., telephone networks). They support management functions such as network inventory, service provisioning, network configuration and fault management.	Wikipedia
over-the-air	OTA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
observed time difference of arrival	OTDOA	N/A	The time interval that is observed by a target device between the reception of downlink signals from two different cells. If a signal from cell 1 is received at the moment t1, and a signal from cell 2 is received at the moment t2, the OTDOA is $t2 - t1$.	3GPP TR 36.355: "Technical Specification Group Services and System Aspects; Evolved Universal Terrestrial Radio Access (E-UTRA); LTE Positioning Protocol (LPP)"
optical time-domain reflectometer	OTDR	N/A	A device that sends a short pulse of light to an optical fiber communication system and measures historical pulse reflection time to determine the fiber length, loss, and faults based on the returned pulse of light.	Huawei Term
optical transport network	OTN	N/A	ITU-T defines an optical transport network (OTN) as a set of Optical Network Elements (ONE) connected by optical fiber links, able to provide functionality of transport, multiplexing, switching, management, supervision and survivability of optical channels carrying client signals.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
one-time password	OTP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
over the top	OTT	N/A	N/A	3GPP TR 26.922: "Video telephony robustness improvements extensions; Performance evaluation"
orthogonal variable spreading factor	OVSF	N/A	Orthogonal variable spreading factor (OVSF) is an implementation of code division multiple access (CDMA) where before each signal is transmitted, the signal is spread over a wide spectrum range through the use of a user's code. Users' codes are carefully chosen to be mutually orthogonal to each other.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
office direction	N/A	N/A	Office direction refers to the number of peer office equipment. The structure of a seven-digit telephone number is: office number (composed of three digits) + internal number (composed of four digits). The switching system searches the office number, connects to the office where the office number is located, searches the internal number, and then connects to the subscriber who owns the internal number. An office may have more than one office number, which can be referred to as the office direction. Most of the office numbers are adjacent, for example, 733, 734, and 735.	Huawei Term
OMUCore	N/A	N/A	A core process of the GBAM/GOMU, which is the O&M center of the BSC	Huawei Term
OMUDaemon	N/A	N/A	A monitoring process of the GBAM/GOMU, which monitors the OMUCore and the OMULocal	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
OMULocal	N/A	N/A	A local process of the GBAM/GOMU, which manages the status of the GBAM server and the GOMU.	Huawei Term
operator	N/A	N/A	Licensed telecommunication company who provides telecommunication services and services for call or message routing purposes.	ETSI TR 102 314-3: "Fixed network Multimedia Messaging Service (F-MMS); PSTN/ISDN; Part 3: Network architecture and interconnection"
Operator CA	N/A	N/A	Operator CA is a self-signed CA deployed by operator to issue certificates for network elements.	Huawei Term
Operator-issued device certificate	N/A	N/A	An operator-issued device certificate is a digital certificate issued by the operator's CA to devices on the live network. The certificate is used as a credential for device communication.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
optical fiber	N/A	N/A	An optical fiber is a flexible, transparent fiber made by drawing glass (silica) or plastic to a diameter slightly thicker than that of a human hair. Optical fibers are used most often as a means to transmit light between the two ends of the fiber and find wide usage in fiber-optic communications, where they permit transmission over longer distances and at higher bandwidths (data transfer rates) than electrical cables.	Wikipedia
original active BCCH TRX	N/A	N/A	The active BCCH TRX configured on the BSC6000 Local Maintenance Terminal for users in the cell.	Huawei Term
outdoor mini box	N/A	N/A	A box that is an outdoor subrack with limited space. It supports external AC or DC input, and houses and protects the baseband unit (BBU). It is a component of a base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
overcurrent protection	N/A	N/A	Protection intended to operate when the current is in excess of a predetermined value.	IEV 448-14-26

1.17 P

Term	Abbreviation	Synonym	Definition	Reference
point-to-point	P2P	N/A	A value of the service attribute "communication configuration", which denotes that the communication involves only two network terminations.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
peer-to-peer	P2P	N/A	A concept related to a distributed network architecture composed of participants that make a portion of their resources (such as processing power, disk/cache storage or network bandwidth) directly available to other network participants.	3GPP TR 22.906: "Study on IMS based peer-to-peer content distribution services"

Term	Abbreviation	Synonym	Definition	Reference
power amplifier	PA	N/A	A power amplifier is an amplifier designed primarily to increase the power available to a load. In practice, amplifier power gain depends on the source and load impedances, as well as the inherent voltage and current gain.	Wikipedia
private automatic branch exchange	PABX	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
packet associated control channel	PACCH	N/A	PACCH conveys signalling information related to a given MS. The signalling information includes e.g. acknowledgements and power control information. PACCH carries also resource assignment and reassignment messages, comprising the assignment of a capacity for PDTCH(s) and for further occurrences of PACCH. The PACCH shares resources with PDTCHs, that are currently assigned to one MS. Additionally, an MS that is currently involved in packet transfer, can be paged for circuit switched services on PACCH.	3GPP TS 43.064: "3rd Generation Partnership Project; Technical Specification Group GSM/EDGE Radio Access Network; General Packet Radio Service (GPRS); Overall description of the GPRS radio interface; Stage 2 (Release 9)"
packet assembler / disassembler	PAD	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
packet access grant channel	PAGCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
pulse amplitude modulation 4-level	PAM-4	N/A	N/A	ETSI TS 125 213: "Universal Mobile Telecommunications System (UMTS); Physical channels and mapping of transport channels onto; physical channels (FDD)"
perceptively adaptive modulation and coding scheme	PAMC	N/A	In addition to basic MCS selection, the uplink PAMC function introduces a cell-level SINR adjustment value. In this way, a more accurate initial SINR adjustment value can be obtained for newly accessed UEs. In addition, the UE SINR prediction process is added.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Password Authentication Protocol	PAP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
peak-to-average ratio	PAR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
PCU-BSC interface	Pb interface	N/A	A non-standard interface between the PCU and the BSC. The implementation of the Pb interface varies from manufacturer to manufacturer. The Pb interface provides the following functions: trunk circuit management, packet service radio resource management, and packet service access support.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
packet broadcast control channel	PBCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical antenna	N/A	N/A	A physical antenna refers to a 1-drive-n antenna subarray. 1-drive-n indicates that one power amplifier (PA) is connected to n antenna elements.	Huawei Term
physical broadcast channel	PBCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
power budget	PBGT	N/A	N/A	Huawei Term
phonebook identifier	PBID	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
paging block periodicity	PBP	N/A	The period of the occurrence of Paging Blocks. (For FDD, PBP = 1).	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
provided bit rate	PBR	N/A	N/A	Huawei Term
PCU-BSC interface signaling link	PBSL	N/A	A signaling link between the BSC and the PCU	Huawei Term
power boost technology	PBT	N/A	A technology that enhances the power to expand the coverage of base stations	Huawei Term
power control	PC	N/A	Power control, broadly speaking, is the intelligent selection of transmitter power output in a communication system to achieve good performance within the system.	Wikipedia
personal computer	PC	N/A	A personal computer (PC) is a multi-purpose computer whose size, capabilities, and price make it feasible for individual use.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
power control algorithm	PCA	N/A	N/A	3GPP TS 25.214: "Technical Specification Group Radio Access Network; Physical layer procedures (FDD)"
primary component carrier	PCC	N/A	When CA is configured, the UE only has one RRC connection with the network. At RRC connection establishment/reestablishment/handover, one serving cell provides the NAS mobility information (e.g. TAI), and at RRC connection reestablishment/handover, one serving cell provides the security input. This cell is referred to as the primary cell (PCell).	ETSI TS 136 300 V16.5.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
parallel concatenated convolutional code	PCCC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
packet common control channel	PCCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
paging control channel	PCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
primary common control physical channel	P-CCPCH	N/A	N/A	Huawei Term
primary cell	PCell	N/A	A primary cell (PCell) is a cell on which a CA UE camps. In the PCell, the CA UE works in the same way as it does in a single-carrier cell. The physical uplink control channel (PUCCH) of the UE exists only in the PCell.	Huawei Term
policy control function	PCF	N/A	N/A	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2 (Release 16)"

Term	Abbreviation	Synonym	Definition	Reference
physical control format indicator channel	PCFICH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Project Coordination Group	PCG	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
paging channel	PCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical cell identifier	PCI	N/A	N/A	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
protocol control information	PCI	N/A	N/A	ITU-T X.200: "Information technology - Open Systems Interconnection - Basic Reference Model: The basic model"
packet circuit identification code	PCIC	N/A	N/A	Huawei Term
pulse code modulation	PCM	N/A	Digital representation of an analog signal where the amplitude of the signal is sampled at uniform intervals	ETSI TS 103 190-1: "Digital Audio Compression (AC-4) Standard; Part 1: Channel based coding"
Personal Computer Memory Card International Association	PCMCIA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical common packet channel	PCPCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
primary common pilot channel	P-CPICH	PCPICH	The primary common pilot channel is used by the UEs to first complete identification of the primary scrambling code used for scrambling primary common control physical channel (P-CCPCH) transmissions from the NodeB.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
policy and charging rules function	PCRF	N/A	Policy and charging rules function (PCRF) is the software node designated in real-time to determine policy rules in a multimedia network. As a policy tool, the PCRF plays a central role in next-generation networks. Unlike earlier policy engines that were added onto an existing network to enforce policy, the PCRF is a software component that operates at the network core and accesses subscriber databases and other specialized functions, such as a charging system, in a centralized manner. Because it operates in real time, the PCRF has an increased strategic significance and broader potential role than traditional policy engines. This has led to a proliferation of PCRF products since 2008	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
proxy call session control function	P-CSCF	N/A	A proxy CSCF (P-CSCF) is a SIP proxy that is the first point of contact for the IMS terminal. It can be located either in the visited network (in full IMS networks) or in the home network (when the visited network is not IMS compliant yet). Some networks may use a Session Border Controller (SBC) for this function. The P-CSCF is at its core a specialized SBC for the user-network interface which not only protects the network, but also the IMS terminal. The use of an additional SBC between the IMS terminal and the P-CSCF is unnecessary and infeasible due to the signaling being encrypted on this leg. The terminal discovers its P-CSCF with DHCP, or it may be configured (e.g. during initial provisioning or via a 3GPP IMS Management Object (MO)) in the ISIM or assigned in the PDP context (in General Packet Radio Service (GPRS)).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
packet control unit	PCU	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
packet delay budget	PDB	N/A	To ensure that carrier traffic in LTE/NR networks is appropriately handled, a mechanism is needed to classify the different types of carriers into different classes, with each class having appropriate QoS parameters for the traffic type. Examples of the QoS parameters include guaranteed bit rate (GBR) or non-guaranteed bit rate (non-GBR), priority handling, packet delay budget (PDB) and packet error loss rate.	Wikipedia
physical downlink control channel	PDCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
packet data channel	PDCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Packet Data Convergence Protocol	PDCP	N/A	Packet Data Convergence Protocol (PDCP) is specified by 3GPP in TS 25.323 for UMTS, TS 36.323 for LTE and TS 38.323 for 5G New Radio (NR). PDCP is located in the Radio Protocol Stack in the UMTS/LTE/5G Air interface on top of the RLC layer. PDCP provides its services to the RRC and user plane upper layers, e.g. IP at the UE or to the relay at the base station.	Wikipedia
policy decision function	PDF	N/A	N/A	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements"

Term	Abbreviation	Synonym	Definition	Reference
power distribution frame	PDF	N/A	N/A	ETSI TR 100 283: "Environmental Engineering (EE); Transient voltages at Interface "A" on telecommunications direct current (dc) power distributions"
plesiochronous digital hierarchy	PDH	N/A	The plesiochronous digital hierarchy (PDH) is a technology used in telecommunications networks to transport large quantities of data over digital transport equipment such as fiber optic and microwave radio systems.	Wikipedia
Public Data Network	PDN	N/A	A network established and operated by a telecommunications administration, or a recognized private operating agency, for the specific purpose of providing data transmission services for the public.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
packet data network	PDN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Packet Data Protocol	PDP	N/A	The packet data protocol context is a data structure present on both the serving GPRS support node (SGSN) and the gateway GPRS support node (GGSN) which contains the subscriber's session information when the subscriber has an active session. When a mobile wants to use GPRS, it must first attach and then activate a PDP context. This allocates a PDP context data structure in the SGSN that the subscriber is currently visiting and the GGSN serving the subscriber's access point.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
physical downlink shared channel	PDSCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
packet data serving node	PDSN	N/A	The Packet Data Serving Node, or PDSN, is a component of a CDMA2000 mobile network. It acts as the connection point between the radio access and IP networks. This component is responsible for managing PPP sessions between the mobile provider's core IP network and the mobile station (mobile phone). It is similar in function to the GGSN (GPRS Gateway Support Node) that is found in GSM and UMTS networks.	Wikipedia
packet data traffic channel	PDTCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
protocol data unit	PDU	N/A	In telecommunications, a protocol data unit (PDU) is a single unit of information transmitted among peer entities of a computer network. A PDU is composed of protocol-specific control information and user data. In the layered architectures of communication protocol stacks, each layer implements protocols tailored to the specific type or mode of data exchange.	Wikipedia
power distribution unit	PDU	N/A	N/A	Huawei Term
provider edge	PE	N/A	A device located in the backbone network of the MPLS VPN structure. A PE is responsible for managing VPN users, establishing LSPs between PEs, and exchanging routing information between users of the same VPN. A PE also performs the mapping and forwarding of packets between the private network and the public channel. A PE can be a UPE, an SPE, or an NPE.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
packet error loss rate	PELR	N/A	Packet error loss rate (PELR) defines an upper bound for the rate of SDUs (e.g. IP packets) that have been processed by the sender of a link layer protocol (e.g. RLC in E UTRAN) but that are not successfully delivered by the corresponding receiver to the upper layer (e.g. PDCP in E UTRAN).	3GPP TS 23.203: "Policy and charging control architecture"
packet error rate	PER	packet error ratio	The packet error ratio (PER) is the number of incorrectly received data packets divided by the total number of received packets.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
proportional fair	PF	N/A	Proportional fair is a compromise-based scheduling algorithm. It is based upon maintaining a balance between two competing interests: Trying to maximize total throughput of the network (wired or not) while at the same time allowing all users at least a minimal level of service. This is done by assigning each data flow a data rate or a scheduling priority (depending on the implementation) that is inversely proportional to its anticipated resource consumption.	Wikipedia
paging frame	PF	N/A	N/A	ETSI TS 138 470 V16.2.0: "5G; NG-RAN; F1 general aspects and principles"
protocol field compression	PFC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
packet data network gateway	P-GW	N/A	A packet data network gateway (PDN gateway) provides connectivity from the User Equipment (UE) to external packet data networks (PDNs) by its point of exit and entry of traffic. A piece of User Equipment may have simultaneous connectivity with more than one P-GW for accessing multiple packet data networks. The P-GW performs policy enforcement, packet filtering for each user, charging support, lawful interception and packet screening. Another key role of the P-GW is to act as the anchor for mobility between 3GPP and non-3GPP technologies such as WiMAX and 3GPP2 (CDMA 1X and EV-DO).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
per-hop behavior	PHB	N/A	In computer networking, per-hop behaviour (PHB) is a term used in differentiated services (DiffServ) or multiprotocol label switching (MPLS). It defines the policy and priority applied to a packet when traversing a hop (such as a router) in a DiffServ network.	Wikipedia
packet handler function	PHF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
packet handler interface	PHI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical HARQ indicator channel	PHICH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
power headroom report	PHR	N/A	N/A	ETSI TS 138 321 V16.4.0: "5G; NR; Medium Access Control (MAC) protocol specification"
personal handyphone system	PHS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical layer	PHY	• Layer 1 • L1	Layer 1 in the open systems interconnection (OSI) architecture; the layer that provides services to transmit bits or groups of bits over a transmission link between open systems and which entails electrical, mechanical and handshaking procedures (PHY).	ETSI EN 302 878-2: "Access, Terminals, Transmission and Multiplexing (ATM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0"
physical network element	physical NE	N/A	The communication equipment that is physically connected to and managed by the management system.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
page indicator	PI	N/A	Indicators are means of fast low-level signalling entities that are transmitted without using information blocks sent over transport channels. The meaning of indicators is implicit to the receiver. The indicators defined in the current version of the specifications are: Page Indicator (PI). Indicators may be either Boolean (two-valued) or three-valued. Their mapping to indicator channels is channel specific. Indicators are transmitted on those physical channels that are indicator channels (ICH).	ETSI TS 101 851-1: "Satellite Component of UMTS/IMT 2000; A-family; Part 1: Physical channels and mapping of transport channels into physical channels"
pilot contamination	PiC	pilot pollution	Pilot contamination is a situation in which a mobile station receives four or more pilot signals whose E_c/I_o is larger than the T_{add} but none of them is dominant enough for the mobile station to track it.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
parallel interference cancellation	PIC	N/A	N/A	ETSI TR 101 534: "Broadband Radio Access Networks (BRAN); Very high capacity density BWA networks; System architecture, economic model and derivation of technical requirements"
page indicator channel	PICH	N/A	The page indicator channel (PICH) is a physical channel used to carry the paging indicators.	3GPP TS 25.221: "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Physical channels and mapping of transport channels onto physical channels (TDD) (Release 9)"
process identifier	PID	process ID	In computing, the process identifier (a.k.a. process ID or PID) is a number used by most operating system kernels—such as those of Unix, macOS and Windows—to uniquely identify an active process.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Protocol Independent Multicast	PIM	N/A	Protocol-Independent Multicast (PIM) is a family of multicast routing protocols for Internet Protocol (IP) networks that provide one-to-many and many-to-many distribution of data over a LAN, WAN or the Internet. It is termed protocol-independent because PIM does not include its own topology discovery mechanism, but instead uses routing information supplied by other routing protocols. PIM is not dependent on a specific unicast routing protocol; it can make use of any unicast routing protocol in use on the network. PIM does not build its own routing tables. PIM uses the unicast routing table for reverse-path forwarding.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
passive intermodulation	PIM	- passive intermodulation - intermodulation distortion	Passive intermodulation (PIM) refers to the intermodulation effect caused by nonlinearities in the passive components of an antenna system when high-power signals of multiple frequencies are transmitted. This intermodulation effect decreases uplink sensitivity, affecting network quality. Generally, third-order passive intermodulation (PIM3) has the largest impact on the communications system as the component signals causing PIM3 interference have the highest power among PIM cases.	Huawei Term
personal identification number	PIN	PIN number	A personal identification number (PIN), or sometimes redundantly a PIN number, is a numeric (sometimes alpha-numeric) passcode used in the process of authenticating a user accessing a system.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Packet Internet Groper	PING	N/A	Ping is a computer network administration software utility used to test the reachability of a host on an Internet Protocol (IP) network. It is available for virtually all operating systems that have networking capability, including most embedded network administration software.	Wikipedia
peak information rate	PIR	N/A	Peak information rate (PIR) is a burstable rate set on routers and/or switches that allows throughput overhead. It is related to committed information rate (CIR), which is a committed rate speed guaranteed/capped.	Wikipedia
Public Key Cryptography Standards	PKCS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
public key infrastructure	PKI	N/A	A public-key infrastructure (PKI) is a set of roles, policies, hardware, software and procedures needed to create, manage, distribute, use, store and revoke digital certificates and manage public-key encryption. The purpose of a PKI is to facilitate the secure electronic transfer of information for a range of network activities such as e-commerce, internet banking and confidential email. It is required for activities where simple passwords are an inadequate authentication method and more rigorous proof is required to confirm the identity of the parties involved in the communication and to validate the information being transferred.	Wikipedia
preferred languages	PL	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
physical link aggregation	PLA	N/A	A form of load balancing that aggregates links based on physical-layer bandwidths. Ethernet channels in the integrated IP microwave links between two NEs can be aggregated to form a logical large-bandwidth Ethernet link. In this way, PLA can effectively improve the bandwidth and reliability of Ethernet services transmitted over integrated IP microwave.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
power line communication	PLC	N/A	Power-line communication (also known as power-line carrier) carries data on a conductor that is also used simultaneously for AC electric power transmission or electric power distribution to consumers. A wide range of power-line communication technologies are needed for different applications, ranging from home automation to Internet access which is often called broadband over power lines (BPL). Most PLC technologies limit themselves to one type of wires (such as premises wiring within a single building), but some can cross between two levels (for example, the distribution network and premises wiring).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
phase-locked loop	PLL	• phase lock loop • phase locked loop	A phase-locked loop (PLL) circuit can be used for synchronization to the symbol clock and according to the loop bandwidth, timing jitter is suppressed and low frequency drift (wander) is still present at the output of the loop oscillator.	ETR 290: "Digital Video Broadcasting (DVB); Measurement guidelines for DVB systems"
public land mobile network	PLMN	N/A	A public land mobile network (PLMN) is a network established and operated by an Administration or RPOA for the specific purpose of providing land mobile communication services to the public. It provides communication possibilities for mobile users.	3GPP TS 22.011: "Service accessibility"
Performance Management	PM	N/A	Set of management functions which enable the performance of the network services to be measured and corrective actions to be taken.	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions" (see ITU-T Recommendation I.113-617)

Term	Abbreviation	Synonym	Definition	Reference
physical multicast channel	PMCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
power monitoring interface	PMI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
precoding matrix indication	PMI	precoding matrix indicator	For transmission modes 4, 5 and 6, precoding feedback is used for channel-dependent-codebook-based precoding and relies on UEs reporting PMIs. For transmission mode 8, the UE shall report PMI if configured with PMI/RI reporting. For transmission modes 9 and 10, the non-BL/CE UE shall report PMI if configured with PMI/RI reporting and the number of CSI-RS ports is larger than 1. For transmission modes 9, the BL/CE UE shall report PMI based on CSI-RS if configured with the higher layer parameter ce-CSI-RS-Feedback and the number of CSI-RS ports is 8, otherwise based on CRS. A UE shall report PMI based on the feedback modes described in 7.2.1 and 7.2.2. For other transmission modes, PMI reporting is not supported.	ETSI TS 136 213 V16.5.0: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures"

Term	Abbreviation	Synonym	Definition	Reference
path maximum transmission unit	PMTU	N/A	A method of discovering the supported MTU on a specific path by using ICMPv6 Datagram Too Big messages.	Huawei Term
path MTU discovery	PMTUD	N/A	Path MTU discovery (PMTUD) is a standardized technique in computer networking for determining the maximum transmission unit (MTU) size on the network path between two Internet Protocol (IP) hosts, usually with the goal of avoiding IP fragmentation. PMTUD was originally intended for routers in Internet Protocol Version 4 (IPv4). However, all modern operating systems use it on endpoints. In IPv6, this function has been explicitly delegated to the endpoints of a communications session.	Wikipedia
power monitoring unit	PMU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
phase noise	PN	N/A	In signal processing, phase noise is the frequency domain representation of rapid, short-term, random fluctuations in the phase of a waveform, caused by time domain instabilities ("jitter"). Generally speaking, radio frequency engineers speak of the phase noise of an oscillator, whereas digital system engineers work with the jitter of a clock.	Huawei Term
Presentation of European Norm	PNE	Présentation des Normes Européennes	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
public network integrated non-public network	PNI-NPN	N/A	N/A	3GPP TS 23.501: "System architecture for the 5G System (5GS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
plug and play	PnP	N/A	In computing, a plug and play (PnP) device or computer bus is one with a specification that facilitates the discovery of a hardware component in a system without the need for physical device configuration or user intervention in resolving resource conflicts. The term "plug and play" has since been expanded to a wide variety of applications to which the same lack of user setup applies.	Wikipedia
private numbering plan	PNP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
power offset	PO	N/A	N/A	Huawei Term
paging occasion	PO	N/A	The frame where the UE monitors in FDD or the paging block, which consists of several frames, for TDD. For a paging block, the value of paging occasion is equal to the first frame of the paging block.	ETSI TR 121 905 V10.3.0: "LTE; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
push-to-talk over cellular	PoC	N/A	Push-to-talk over cellular (PoC) is a service option for a cellular phone network that enables subscribers to use their phones as walkie-talkies with unlimited range. A typical push-to-talk connection connects almost instantly.	Wikipedia
proof of receipt	PoR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
point of synchronization	POS	N/A	N/A	ETSI EN 301 931-1: "Intelligent Network (IN); Intelligent Network Capability Set 3 (CS3); Intelligent Network Application Protocol (INAP); Protocol specification; Part 1: Common aspects"
positioning system information block	posSIB	N/A	N/A	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
packet paging channel	PPCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
primitive procedure entity	PPE	N/A	N/A	ETSI TS 101 377-1-1: "GEO-Mobile Radio Interface Specifications; Part 1: General specifications; Sub-part 1: Abbreviations and Acronyms; GMR-2 01.004"
paging proceed flag	PPF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
parts per million	ppm	N/A	In science and engineering, the parts-per notation is a set of pseudo-units to describe small values of miscellaneous dimensionless quantities. Commonly used are parts-per-million (ppm, 10^{-6}), parts-per-billion (ppb, 10^{-9}), parts-per-trillion (ppt, 10^{-12}) and parts-per-quadrillion (ppq, 10^{-15}).	Wikipedia
Point-to-Point Protocol	PPP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Point-to-Point Protocol multiplexing	PPP MUX	PPP multiplexing	A method that sends multiple PPP encapsulated packets (subframes) in a single PPP frame. As a result, the PPP overhead per packet is reduced. It is applicable to transmit small packets such as voice and data over slow links.	3GPP TR 25.933: "IP Transport in UTRAN Work Task Technical Report"

Term	Abbreviation	Synonym	Definition	Reference
Point-to-Point Protocol over Ethernet	PPPoE	N/A	The Point-to-Point Protocol over Ethernet (PPPoE) is a network protocol for encapsulating Point-to-Point Protocol (PPP) frames inside Ethernet frames.	Wikipedia
priority queue	PQ	N/A	In computer science, a priority queue is an abstract data type similar to a regular queue or stack data structure in which each element additionally has a "priority" associated with it. In a priority queue, an element with high priority is served before an element with low priority. In some implementations, if two elements have the same priority, they are served according to the order in which they were enqueued, while in other implementations, ordering of elements with the same priority is undefined.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
physical random access channel	PRACH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical resource block	PRB	N/A	A physical resource block (PRB) is the basic unit for allocating 5G and LTE data channel resources. In LTE, because resources within an entire channel bandwidth can be allocated to a UE, an RB equals a PRB. As NR uses larger channel bandwidths than LTE and introduces bandwidth part (BWP), RBs in the entire channel bandwidth are defined as common resource blocks (CRBs), and RBs in a UE-specific BWP are defined as PRBs.	• Huawei Term • 3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"

Term	Abbreviation	Synonym	Definition	Reference
pseudorandom binary sequence	PRBS	• pseudorandom binary code • pseudorandom bitstream	A pseudorandom binary sequence (PRBS), pseudorandom binary code or pseudorandom bitstream is a binary sequence that, while generated with a deterministic algorithm, is difficult to predict and exhibits statistical behavior similar to a truly random sequence. PRBS generators are used in telecommunication, such as in analog-to-information conversion, but also in encryption, simulation, correlation technique and time-of-flight spectroscopy. The most common example is the maximum length sequence generated by a (maximal) linear feedback shift register (LFSR). Other examples are Gold sequences (used in CDMA and GPS), Kasami sequences and JPL sequences, all based on LFSRs.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
primary reference clock	PRC	N/A	A reference clock that provides a reference timing signal compliant with EN 300 462-6-1, in order to synchronize all or a large part of a network.	EN 300 462-1-1: "Transmission and Multiplexing (TM); Generic requirements for synchronization networks; Part 1-1: Definitions and terminology for synchronization networks"
Primary Rate Interface	PRI	N/A	N/A	ETSI TS 183 036: "Core Network and Interoperability Testing (INT); ISDN/SIP interworking; Protocol specification"
Paging RNTI	P-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
Proximity-based Service	ProSe	D2D Device to Device	Proximity-based Services (ProSe) are services that can be provided for ProSe-enabled UEs in proximity to each other. In ProSe communication, the data traffic is directly exchanged between these UEs without going through the cellular network, but the cellular network can still directly control communication between these UEs. ProSe communication is also known as device-to-device (D2D) communication.	Huawei Term
pico remote radio unit	pRRU	N/A	Pico remote radio unit (pRRU) is an RF unit for LampSite base stations and can be used in all LampSite solutions. Compared with RRUs for macro base stations, pRRUs feature lower power consumption and lighter weight.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
positioning reference signal	PRS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
performance report system	PRS	N/A	N/A	Huawei Term
primary reference time clock	PRTC	N/A	A reference time generator that provides a reference timing signal traceable to an internationally recognized time standard [e.g., Coordinated Universal Time (UTC)].	ITU-T G.8260: "Definitions and terminology for synchronization in packet networks"
packet switched	PS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
physical shared channel	PSCH	N/A	N/A	Huawei Term
primary synchronization channel	P-SCH	N/A	The P-SCH is a pure downlink physical channel broadcast over the entire cell in UMTS.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
phase-shift keying	PSK	N/A	Phase-shift keying (PSK) is a digital modulation process which conveys data by changing (modulating) the phase of a constant frequency reference signal (the carrier wave). The modulation is accomplished by varying the sine and cosine inputs at a precise time. It is widely used for wireless LANs, RFID and Bluetooth communication.	Wikipedia
pre-shared key	PSK	N/A	In cryptography, a pre-shared key (PSK) is a shared secret which was previously shared between the two parties using some secure channel before it needs to be used.	Wikipedia
power saving mode	PSM	N/A	A mode of operation similar to power-off, allowing a UE to greatly reduce its power consumption while remaining registered with the network, without the need to re-attach or to re-establish PDN connections.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
packet switched network	PSN	N/A	A telecommunication network which works in packet switching mode.	IEV 715-11-02

Term	Abbreviation	Synonym	Definition	Reference
packet switched public data network	PSPDN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
primary synchronization signal	PSS	N/A	N/A	3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception" 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone"
power supply unit	PSU	N/A	Self-contained device, physically separable from the motherboard of the computer server, that converts AC or DC input power to one or more DC power outputs for powering the computer server via a removable or hard-wired electrical connection.	ETSI EN 303 470: "Environmental Engineering (EE); Energy Efficiency measurement methodology and metrics for servers"

Term	Abbreviation	Synonym	Definition	Reference
Potential User Control	PSU	N/A	Potential User Control (PSU) enables UEs to reselect lightly-loaded cells by controlling parameters of the system information broadcast. This relieves heavily-loaded cells from a large number of calls and makes full use of the entire system resources.	Huawei Term
packet timing advance control channel	PTCCH	N/A	PTCCH/U is used to transmit random access burst to allow estimation of the timing advance for one MS in packet transfer mode. PTCCH/D is used to transmit timing advance information updates to several MS. One PTCCH/D is paired with several PTCCH/U's.	3GPP TS 03.64: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Overall description of the GPRS radio interface; Stage 2 (GSM 03.64 version 6.2.0 Release 1997)"
Point-to-Multipoint	PTM	• P2MP • PMP • PTMP	A network configuration which has one input/output at one end with multiple inputs/outputs at the other end.	ETSI ETS 300 681: "Transmission and Multiplexing (TM); Optical Distribution Network (ODN) for Optical Access Network (OAN)"

Term	Abbreviation	Synonym	Definition	Reference
Packet Temporary Mobile Subscriber Identity	P-TMSI	• Packet-TMSI • Packet-Temporary Mobile Subscriber Identity • Packet TMSI • PTMSI	The TMSI/P-TMSI, when available, is normally used to identify the user on the radio access path, for instance in paging requests, location update requests, attach requests, service requests, connection re-establishment requests and detach requests.	3GPP TS 33.102: "Technical Specification Group Services and System Aspects; 3G Security; Security architecture"
public telecommunications network	PTN	N/A	N/A	ETSI EG 202 057-4: "Speech Processing, Transmission and Quality Aspects (STQ); User related QoS parameter definitions and measurements; Part 4: Internet access"
packet transport network	PTN	N/A	N/A	ETSI GS ENI 001: "Experiential Networked Intelligence (ENI); ENI use cases"

Term	Abbreviation	Synonym	Definition	Reference
Precision Time Protocol	PTP	N/A	The Precision Time Protocol (PTP) is a protocol used to synchronize clocks throughout a computer network. On a local area network, it achieves clock accuracy in the sub-microsecond range, making it suitable for measurement and control systems.	Wikipedia
phase-tracking reference signal	PT-RS	N/A	N/A	3GPP TS 38.211: "NR; Physical channels and modulation"
push to talk	PTT	N/A	Push-to-talk (PTT), also known as press-to-transmit, is a method of having conversations or talking on half-duplex communication lines, including two-way radio, using a momentary button to switch from voice reception mode to transmit mode.	Wikipedia
physical uplink control channel	PUCCH	N/A	N/A	3GPP TR 21.905: "Vocabulary for 3GPP Specifications"
physical uplink shared channel	PUSCH	N/A	N/A	3GPP TR 21.905: "Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
permanent virtual channel	PVC	N/A	Similar to a leased line on a telephone network, the PVC is pre-established through an OSS. No matter whether it is for service or terminal access, the pre-established PVC is retained until the PVC is released by the NMS.	Huawei Term
permanent virtual connection	PVC	N/A	N/A	ITU-T Q.933: "ISDN Digital Subscriber Signalling System No. 1 (DSS1) – Signalling specifications for frame mode switched and permanent virtual connection control and status monitoring"
permanent virtual circuit	PVC	N/A	A permanent virtual circuit (PVC) is a virtual circuit established for repeated/continuous use between the same DTE. In a PVC, the long-term association is identical to the data transfer phase of a virtual call. Permanent virtual circuits eliminate the need for repeated call set-up and clearing.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
preemption vulnerability indicator	PVI	pre-emption vulnerability indicator	N/A	Huawei Term
permanent virtual path	PVP	N/A	Permanent virtual path that consists of PVCs.	Huawei Term
pseudowire	PW	pseudo-wire	In computer networking and telecommunications, a pseudowire (or pseudo-wire) is an emulation of a point-to-point connection over a packet-switching network (PSN).	Wikipedia
Pseudo Wire Emulation Edge-to-Edge	PWE3	N/A	PWE3 is a mechanism that emulates the essential attributes of a telecommunications service (such as a T1 leased line or Frame Relay) over a PSN. PWE3 is intended to provide only the minimum necessary functionality to emulate the wire with the required degree of faithfulness for the given service definition.	S. Bryant, Ed, "Pseudo Wire Emulation Edge-to-Edge (PWE3) Architecture", RFC3985, March 2005

Term	Abbreviation	Synonym	Definition	Reference
Public Warning System-Interworking Function	PWS-IWF	N/A	The PWS-IWF is a logical function which functionality is to translate from N50 to SBc. The PWS-IWF may interface to one or multiple AMFs. The PWS-IWF may interface to one or multiple CBCs.	3GPP TS 23.041: "Technical realization of Cell Broadcast Service (CBS)"
P/N criterion	N/A	N/A	It is a criterion against which a certain operation is performed when the criteria last within an acceptable statistical period.	Huawei Term
packet filtering	N/A	N/A	A packet filter processes network traffic on a packet-by-packet basis. Its main job is to filter traffic from a remote IP host.	Wikipedia
packet loss	N/A	N/A	Loss of one or more packet that can be described using a certain statistical model.	ETSI EG 202 670: "Human Factors (HF); User Experience Guidelines for real-time communication services expressed in Quality of Service terms"
paging	N/A	N/A	The act of seeking a User Equipment.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
paging group	N/A	N/A	For UTRA TDD, a time division of the PCH has been proposed in such a way that two consecutive time slots of the CCPCH carrying the PCH form a paging sub-channel. Each paging sub-channel corresponds to a paging group of UEs. There exists a fixed association between a paging group, i.e. a paging sub-channel, and the UE, which is given by the UE ID for example. In each paging sub-channel, a paging indicator is transmitted to indicate the presence of a paging message in this particular sub-channel.	3GPP TSGR1#5(99)863: "Proposal for PCH Modifications in TDD"
parameter	N/A	N/A	A parameter indicates an attribute of an abstract object. Parameters can be used to configure object attributes and display object status.	Huawei Term
passive IoT	N/A	N/A	Passive Internet of Things (IoT) refers to a network of IoT devices that are powered without external energy sources or built-in batteries.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
patch	N/A	N/A	A patch is a set of changes to a computer program or its supporting data designed to update, fix, or improve it.	Wikipedia
path loss	N/A	path attenuation	Path loss, or path attenuation, is the reduction in power density (attenuation) of an electromagnetic wave as it propagates through space.	Wikipedia
penetration	N/A	N/A	An attack that circumvents security controls and gains access to a system.	Huawei Term
performance browser tool	N/A	N/A	A component of the LMT software. It is used to import and export performance description files for you to view and analyze.	Huawei Term
performance counter	N/A	counter	A performance counter is used to measure the performance of a project and the quality of a device. It is also termed as a counter, indicating the number or amount (such as service request times and traffic) collected for a measurement purpose.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
performance measurement	N/A	traffic statistics	An activity of measuring and collecting statistics of various data on devices and telecommunications networks. With the statistics, operators can be aware of the operating status, signaling, users, system resource usage of the devices or networks. The statistics also help the operators manage the device operating, locate problems, monitor and maintain the networks, and plan the networks.	Huawei Term
phase	N/A	N/A	The relative position in time within a single period of a signal.	Huawei Term
physical link	N/A	N/A	The link between two physical NEs. When the user creates NEs or refreshes the device status, the system automatically creates the physical link according to the topology structure information on the device. The remark information of a physical link can be modified, but the physical link cannot be deleted.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
physical network	N/A	N/A	A network of physical machines (plus cabling, switches, routers, and so on) that are connected so that they can send data to and receive data from each other. See also virtual network.	Huawei Term
pico cells	N/A	N/A	Small cells with a typical cell radius of less than 50 m that are predominantly situated indoors. Pico cells are characterized by medium to high traffic density support for mobile low speed stations and wide band services.	ITU-R M.1224-1: "Vocabulary of terms for International Mobile Telecommunications (IMT)"
ping-pong handover	N/A	ping-pong effect	The ping-pong effect arises when a mobile node is located at the borderline of the cell or decision point and a handover procedure is frequently executed. This results in higher call drop probability, lower connection quality, increased signaling traffic, and waste of resources. All of these affect mobility optimization.	A. Dutta, Ed., V. Fajardo, NIKSUN, Y. Ohba, K. Taniuchi, Toshiba, H. Schulzrinne, and Columbia Univ., "A Framework of Media-Independent Pre-Authentication (MPA) for Inter-Domain Handover Optimization", RFC 6252, June 2011

Term	Abbreviation	Synonym	Definition	Reference
ping-pong reselection	N/A	N/A	A cell reselection method for preventing ping-pong in a mobile communications system, comprising the steps of: acquiring first and second duration thresholds and first and second occurrence number thresholds for controlling a cell reselection procedure, the second duration threshold being shorter than the first duration threshold and the second occurrence number threshold being less than the first occurrence number threshold; setting a user equipment (UE) to a high-speed state if the number of cell reselections of the UE to the same cell during the second duration threshold exceeds the second occurrence number threshold; setting the UE to a non-high-speed state if the number of cell changes of the UE during the first duration threshold is equal to or less than the first occurrence number threshold; setting the UE to the high-speed state if the	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
			number of cell reselections of the UE to the same cell during the second duration threshold is equal to or less than the second occurrence number threshold and if the number of cell changes of the UE during the first duration threshold exceeds the first occurrence number threshold; selectively performing cell reselection according to a predetermined cell reselection time limit in the non-high-speed state in the UE; and selectively performing cell reselection according to a scaled-down value of the predetermined cell reselection time limit in the high-speed state in the UE.	
plaintext	N/A	N/A	Information or data which is intelligible to everyone	ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features"

Term	Abbreviation	Synonym	Definition	Reference
plug-in frame	N/A	plug-in shelf	A frame where circuit cards for microwave transmission are plugged and played.	Huawei Term
Point A	N/A	N/A	Point A serves as a common reference point for resource block grids and is obtained from offsetToPointA and absoluteFrequency-PointA.	3GPP TS 38.211: "Physical channels and modulation (Release 17)"
point-to-point service	N/A	N/A	A service type in which data is sent from a single network termination to another network termination.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
polarization	N/A	N/A	Locus of the tip of the electrical field vector in a plane perpendicular to the direction of transmission. Examples are horizontal and vertical linear polarization and left and right hand circular polarization.	ETSI EN 300 674-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Road Transport and Traffic Telematics (RTTT); Dedicated Short Range Communication (DSRC) transmission equipment (500 kbit/s / 250 kbit/s) operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band; Part 1: General characteristics and test methods for Road Side Units (RSU) and On-Board Units (OBU)"

Term	Abbreviation	Synonym	Definition	Reference
port IP	N/A	N/A	The port IP is also called the physical port IP address. It is used by the BSC/RNC to communicate with other NEs such as the MGW/MSC/BTS. This IP address is used as the source IP address on the BSC/RNC and as the destination IP address on the peer NE. The port IP is associated with a specific physical port on the interface board. Only the associated port can receive and send packets with the port IP address.	Huawei Term
power sharing	N/A	N/A	Power sharing allows the unused power of an instantaneous idle carrier to be shared with another carrier with its entire bandwidth instantaneously occupied and requiring further data scheduling.	Huawei Term
preamble	N/A	random access preamble	A preamble is a signal sent by a UE on the PRACH during random access.	Huawei Term
precoding	N/A	N/A	A process of mapping layered data onto physical antennas	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
primary band	N/A	N/A	The frequency band containing the main BCCH frequency in a Co-BCCH cell.	Huawei Term
private key certificate	N/A	N/A	A key pair, which needs to be used together with a public key. The private key file is used to decrypt the information encrypted by the public key.	Huawei Term
pseudonymization	N/A	N/A	Process that replaces an actual identifier with an alias ensuring that it cannot be reverted by reasonable effort of anyone (other than the party providing them).	ETSI TR 103 304: "CYBER; Personally Identifiable Information (PII) Protection in mobile and cloud services"
public key	N/A	N/A	A key of an entity's asymmetric key pair which can be made public (ISO/IEC 9798-1, ISO/IEC 11770-1 and ISO/IEC 11770-3).	ETSI EN 301 099-1: "Telecommunications Security; Trusted Third Parties (TTP); Specification for TTP services; Part 1: Key management and key escrow/recovery"

Term	Abbreviation	Synonym	Definition	Reference
pulse	N/A	N/A	Short transient signal whose time duration is nominally the reciprocal of its -10 dB bandwidth.	ETSI EN 302 065: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Ultra WideBand (UWB) technologies for communication purposes; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive"

1.18 Q

Term	Abbreviation	Synonym	Definition	Reference
queuing allowed indicator	QA	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
quadrature amplitude modulation	QAM	N/A	Quadrature amplitude modulation (QAM) is the name of a family of digital modulation methods and a related family of analog modulation methods widely used in modern telecommunications to transmit information. It conveys two analog message signals, or two digital bit streams, by changing (modulating) the amplitudes of two carrier waves, using the amplitude-shift keying (ASK) digital modulation scheme or amplitude modulation (AM) analog modulation scheme. The two carrier waves of the same frequency are out of phase with each other by 90°, a condition known as orthogonality or quadrature. The transmitted signal is created by adding the two carrier waves together. At the receiver, the two	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			waves can be coherently separated (demodulated) because of their orthogonality property. Another key property is that the modulations are low-frequency/ low-bandwidth waveforms compared to the carrier frequency, which is known as the narrowband assumption. The simplest and most commonly used QAM constellations consist of points arranged in a square, such as 16QAM, 64QAM and 256QAM (even powers of two).	
QoS class identifier	QCI	N/A	Scalar that is used as a reference to a specific packet forwarding behaviour (e.g. packet loss rate, packet delay budget) to be provided to a SDF.	ETSI TS 103 029: "IMS Network Testing (INT); IMS & EPC Interoperability test descriptions"

Term	Abbreviation	Synonym	Definition	Reference
quasi-colocation	QCL	N/A	Two antenna ports are said to be quasi co-located if properties of the channel over which a symbol on one antenna port is conveyed can be inferred from the channel over which a symbol on the other antenna port is conveyed.	3GPP TR 38.912: "Study on New Radio (NR) access technology"
QoS Flow Identifier	QFI	N/A	When present this parameter indicates the QoS Flow Identifier of the QoS flow to which the transferred packet belongs.	3GPP TS 38.415: "NG-RAN; PDU session user plane protocol"
802.1Q-in-802.1Q	QinQ	N/A	A Layer 2 tunneling protocol based on IEEE 802.1Q encapsulation. It encapsulates the VLAN tag of a user's private network into the VLAN tag of the public network. The packet carrying these VLAN tags, for both the private and public networks, is transmitted over the service provider's backbone network to provide a Layer 2 VPN tunnel for the user.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
quality of experience	QoE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
quality of service	QoS	N/A	The collective effect of service performances, which determine the degree of satisfaction of a user of a service. It is characterized by the combined aspects of performance factors applicable to all services, such as: – service operability performance; – service accessibility performance; – service retainability performance; – service integrity performance; and – other factors specific to each service.	ITU-T Q.1743: "IMT-Advanced references to Release 11 of LTE-Advanced evolved packet core network"

Term	Abbreviation	Synonym	Definition	Reference
quadrature phase shift keying	QPSK	N/A	Sometimes this is known as quadriphase PSK, 4-PSK, or 4-QAM. (Although the root concepts of QPSK and 4-QAM are different, the resulting modulated radio waves are exactly the same.) QPSK uses four points on the constellation diagram, equispaced around a circle. With four phases, QPSK can encode two bits per symbol to minimize the bit error rate (BER) – sometimes misperceived as twice the BER of BPSK.	Wikipedia
Quick UDP Internet Connections	QUIC	N/A	QUIC improves performance of connection-oriented web applications that are currently using TCP. It does this by establishing a number of multiplexed connections between two endpoints using User Datagram Protocol (UDP), and is designed to obsolete TCP at the network layer for many applications.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Quintet, UMTS authentication vector	N/A	N/A	A temporary protocol of authentication, which enables UMTS AKA function for a certain user in a VLR/SGSN. A quintet consists of five elements: random number (RAND), expected response (XRES), cipher key (CK), integrity key (IK), and authentication token (AUTN).	Huawei Term

1.19 R

Term	Abbreviation	Synonym	Definition	Reference
registration authority	RA	N/A	Functional entity responsible for verifying certificate signing requests and authorizing a certification authority to issue a corresponding certificate	ETSI TS 118 103: "oneM2M; Security solutions (oneM2M TS-0003 version 3.13.0 Release 3)"
random access	RA	N/A	Capability of receiving a service from an arbitrary point in its timeline rather than being confined to progressively receiving it from its beginning.	ETSI TS 102 428: "Digital Audio Broadcasting (DAB); DMB video service; User Application Specification"

Term	Abbreviation	Synonym	Definition	Reference
routing area	RA	N/A	The Routing Area (RA) is defined as an area in which a mobile station, in certain operation modes, may move freely without updating the SGSN. A routing area may include one or several cells. A RA is always contained within a location area.	3GPP TS 23.002: "Network architecture"
rate adaptation	RA	N/A	N/A	3GPP TS 44.021: "Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface"
random access burst	RAB	N/A	The physical layer random access burst consists of a cyclic prefix, a preamble, and a guard time during which nothing is transmitted.	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
radio access bearer	RAB	N/A	The service that the access stratum provides to the non-access stratum for transfer of user data between User Equipment and CN.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
routing area code	RAC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
random access channel	RACH	N/A	N/A	3GPP TR 21.905: "Vocabulary for 3GPP Specifications"
Remote Authentication Dial-In User Service	RADIUS	N/A	A protocol for carrying authentication, authorization, and configuration information between a Network Access Server which desires to authenticate its links and a shared Authentication Server	C. Rigney, S. Willens, Livingston, A. Rubens, Merit, W. Simpson, and Daydreamer, "Remote Authentication Dial In User Service (RADIUS)", RFC 2865, June 2000
remote alarm indication	RAI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
routing area identity	RAI	N/A	The routing area identity (RAI) consists of a RAC, LAC, MNC and MCC.	ETSI TS 123 003: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Numbering, addressing and identification"
radio access network	RAN	N/A	The network that connects radio base stations to the core network. The RAN provides and maintains radio-specific functions, which may be unique to a given radio access technology, that allow users to access the core network.	ITU-T Q.1742.1: "IMT-2000 references to ANSI-41 evolved core network with cdma2000 access network"
Radio Access Network Application Part	RANAP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
random number	RAND	N/A	A number generated by a non-deterministic process.	EN 300 175-7 V1.4.2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features"
random access response	RAR	N/A	N/A	3GPP TS 38.321: "NR; Medium Access Control (MAC) protocol specification"
Random Access RNTI	RA-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
radio access technology (RAT)	RAT	N/A	Type of technology used for radio access, for instance E-UTRA, UTRA, GSM, CDMA2000 1xEV-DO (HRPD) or CDMA2000 1x (1xRTT).	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
routing area update	RAU	N/A	A GPRS mobile will perform a routing area update (RAU) in the Ready and Standby state. The RAU is triggered when the mobile crosses a routing area (RA) boundary, or periodically. The time interval being set by the network. A RAU is also performed when the mobile moves from the Idle to the Standby state. This will typically happen when the mobile is powered on.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
resource block	RB	N/A	A physical resource consisting of a number of symbols in the time domain and a number of consecutive subcarriers in the frequency domain.	ETSI EN 301 908-14: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 14: Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive"
radio bearer	RB	N/A	The service provided by the Layer 2 for transfer of user data between User Equipment and UTRAN.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
resource block group	RBG	N/A	N/A	3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures"
residual block error rate	RBLER	N/A	The ratio of the number of transport blocks (TBs) failing to be transmitted after HARQ retransmissions to the number of TBs initially transmitted.	Huawei Term
receive-ready block	R-Block	N/A	Receive-ready block, R-block, which is used to transfer acknowledgements.	3G TS 31.101: "Technical Specification Group Core Network and Terminals; UICC-terminal interface; Physical and logical characteristics"

Term	Abbreviation	Synonym	Definition	Reference
resolution bandwidth	RBW	N/A	Measured in Hz and represents the frequency over which power is integrated in a spectrum analyser to display the amplitude at the centre of the integration frequency range	ETSI EN 301 908-12: "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 12: CDMA Multi-Carrier (cdma2000) Repeaters"
remote control unit	RCU	N/A	A driving motor of the phase shifter in a remote electrical tilt (RET) antenna.	Huawei Term
resource description format	RDF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
remote defect indication	RDI	N/A	Signal which conveys the defect status of the characteristic information received by the Trail Termination sink function back to the network element which contains the characteristic information originating trail termination source function. Examples of RDI signals are the Far End Receive Failure (FERF) bit(s) in SDH signals, the A-bit in ITU-T Recommendation G.704 structured 2048 kbit/s signals and the alarm indication bit in other PDH multiplex signals.	ETSI TR 101 689-1: "Transmission and Multiplexing (TM); Terms and definitions in transport networks; Part 1: Core networks"
resource element	RE	N/A	Resources defined by one subcarrier and one symbol are called as resource elements (REs).	3GPP TR 38.912: "Study on New Radio (NR) access technology"

Term	Abbreviation	Synonym	Definition	Reference
reduced capability	RedCap	N/A	The reduced capability (RedCap) technology is introduced in 3GPP Release 17 and used in NR Massive Machine-Type Communications (mMTC), aiming to reduce UE costs by reducing the supported bandwidth, number of antennas, and modulation and demodulation capabilities.	3GPP TR 38.875, Study on support of reduced capability NR devices (Release 17)
resource element group	REG	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
remote electrical tilt	RET	N/A	RET or remote electrical tilt is a feature found in sector and base station antennas that allow the tilt angle of the antenna to be controlled remotely. This way a technician does not need to climb a tower to adjust the angle of the antenna and can do so from the base station or a computer.	Huawei Term
remote electrical tilt antenna	RET antenna	N/A	The electrical downtilt can be continuously adjusted using the mechanically-adjustable phase shifter built in the antenna.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
radio frequency	RF	N/A	Portion of the electromagnetic spectrum from a few kilohertz to just below the frequency of infrared light.	ETSI EN 302 878-3: "Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 3: Downstream Radio Frequency Interface; DOCSIS 3.0"
radio frequency chain	RF chain	N/A	An RF chain is a cascade of electronic components and sub-units which may include amplifiers, filters, mixers, attenuators and detectors.	wikipedia
radio frequency filter	RF filter	N/A	A radio frequency filter (RF filter) consists of capacitors, inductors, and resistors. It filters out frequencies in a specified frequency band of a communication channel and attenuates or suppresses other frequencies to obtain valid signals.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
radio frequency phase-lock loop	RF PLL	RF phase-lock loop	Radio frequency phase-lock loop is a mechanism whereby timing information is transferred within a data stream and the receiver derives the signal element timing by locking its local clock source to the received timing information.	Huawei Term
Radio Frequency Access	RFA	N/A	Radio Frequency Access (RFA) is an application mode designed by Huawei. It complies with "UTRA repeater radio transmission and reception" defined in 3GPP and applies only to LampSite. With RFA, RF signals are converted to digital signals, which then experience CPRI MUX with GSM/UMTS/LTE digital signals before being transmitted to the RHUB.	Huawei Term
remote service control	RSC	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Request For Comments	RFC	N/A	Name of specification published by the Internet Engineering Task Force (IETF). Used for publication of Internet standards.	ETSI ES 201 735: "Digital Audio Broadcasting (DAB); Internet Protocol (IP) datagram tunnelling"
radio frequency channel	RF	- RF channel - RFCH	A radio frequency (RF) channel represents a specified portion of the RF spectrum with a defined bandwidth and a carrier frequency and is capable of carrying information over the radio interface.	ITU-T Q.1711: "Network functional model for IMT-2000"
routing functional identity	RFE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
RNC frame number	RFN	N/A	N/A	3GPP TR 25.902: "Technical Specification Group Radio Access Network; Iub/Iur congestion control"

Term	Abbreviation	Synonym	Definition	Reference
reduced TDMA frame number	RFN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
RAT/ Frequency Selection Priority	RFSP	N/A	N/A	3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access"
radio frequency unit	RFU	RF unit	Radio frequency unit (RFU) is used to transmit and receive baseband signals, modulate and demodulate RF signals, process data, and amplify the power of signals. The RFU is generally installed inside the cabinet.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Reserved for future use	RFU	N/A	N/A	3GPP TS 31.121: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; UICC-terminal interface; Universal Subscriber Identity Module (USIM) application test specification (Release 14)"
resource grid	RG	N/A	A resource grid (RG) is a set of REs contained in a channel bandwidth defined in 5G and LTE. RGs are defined per transmission direction (uplink or downlink).	• Huawei Term • 3GPP TS 38.211: "Technical Specification Group Radio Access Network; Physical channels and modulation"
remote global positioning system	RGPS	N/A	N/A	Huawei Term
relative humidity	RH	N/A	Ratio of the partial pressure p of water vapour in moist air to its partial pressure p_{sat} at saturation, at the same temperature.	IEV 113-04-65

Term	Abbreviation	Synonym	Definition	Reference
Radio HUB	RHUB	N/A	A CPRI signal convergence unit used in the LampSite solution. The RHUB also supplies power to pRRUs remotely.	Huawei Term
rank indication	RI	rank indicator	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
radio access network information management	RIM	RAN information management	RIM (RAN Information Management) for functions associated with generic procedures to communicate between two BSSs over the core network. If the RAN Information Management (RIM) feature is supported by both the BSS and the SGSN, the RIM procedures can be used by any RIM application running on this BSS and requiring information transfer between two BSSs via the core network.	3GPP TS 48.018: "Technical Specification Group GSM EDGE Radio Access Network; General Packet Radio Service (GPRS); Base Station System (BSS) - Serving GPRS Support Node (SGSN); BSS GPRS Protocol (BSSGP)"

Term	Abbreviation	Synonym	Definition	Reference
remote interference management	RIM	N/A	N/A	3GPP TR 38.866: "Technical Specification Group Radio Access Network; Study on remote interference management for NR"
remote interference management reference signal	RIM-RS	N/A	N/A	3GPP TS 38.211: "Physical channels and modulation (Release 17)"
Routing Information Protocol	RIP	N/A	The Routing Information Protocol (RIP) is one of the oldest distance-vector routing protocols which employs the hop count as a routing metric. RIP prevents routing loops by implementing a limit on the number of hops allowed in a path from source to destination. The largest number of hops allowed for RIP is 15, which limits the size of networks that RIP can support.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Registered Jack 45	RJ45	N/A	The "RJ" in RJ45 stands for Registered Jack, a standard designation that originated with the Universal Service Ordering Code (USOC) scheme of the Bell System back in the 1970s for telephone interfaces. The RJ designation technically only pertains to the wiring of the jack (that is, the number of positions and the number of wires connected). In the current industry, 8P8C twisted-pair Ethernet connectors are usually referred to as RJ45, which contains eight positions and eight contacts (8P8C).	Huawei Term
radio link	RL	N/A	A radio link (RL) is a bi-directional connection between a terminal and a base station sector.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
radio link control	RLC	N/A	A sublayer of radio interface layer 2 providing transparent, unacknowledged and acknowledged data transfer service.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
Radio Link Control Protocol	RLCP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
radio link failure	RLF	N/A	N/A	3GPP TS 37.320: "Universal Terrestrial Radio Access (UTRA) and Evolved Universal Terrestrial Radio Access (E-UTRA); Radio measurement collection for Minimization of Drive Tests (MDT); Overall description; Stage 2"
radio link management	RLM	N/A	The management performed for the radio links and radio interfaces.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Radio Link Protocol	RLP	N/A	RLP is intended for use with non-transparent data-transfer. Protocol conversion may be provided for a variety of protocol configurations.	3GPP TS 24.022: "Technical Specification Group Core Network and Terminals; Radio Link Protocol (RLP) for circuit switched bearer and teleservices"
resource management	RM	N/A	Oriented to Huawei complicated applications, the resource management module provides resources for applications and services based on defined specifications, and applies for, allocates, and releases resources through the InterCloud.	Huawei Term
rate matching attribute	RMA	N/A	The rate match attribute acts like a weighting factor. The higher the attribute relative to the attribute for all of the other transport channels, the more likely data will be repeated.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
remote network monitoring	RMON	N/A	The Remote Network Monitoring (RMON) MIB was developed by the IETF to support monitoring and protocol analysis of LANs. The original version (sometimes referred to as RMON1) focused on OSI layer 1 and layer 2 information in Ethernet and Token Ring networks.	Wikipedia
Remaining Minimum SI	RMSI	Remaining Minimum System Information	SIB1 defines the scheduling of other system information blocks and contains information required for initial access. SIB1 is also referred to as Remaining Minimum SI (RMSI) and is periodically broadcast on DL-SCH or sent in a dedicated manner on DL-SCH to UEs in RRC_CONNECTED.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage-2"
radio multiplex unit	RMU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
rack monitoring unit	RMU	N/A	A common hardware device used for monitoring the environment of a cabinet and managing the devices in an equipment room. It supports external sensors (such as analog sensors and Boolean sensors) and completes controls.	Huawei Term
relay node	RN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
roaming number	RN	N/A	N/A	EG 201 027: "Business Telecommunications (BTC); Cordless Terminal Mobility (CTM); Interworking between private and public networks; General principles"

Term	Abbreviation	Synonym	Definition	Reference
RAN-based Notification Area	RNA	N/A	RNA, smaller than TA, is used to further reduce the overheads resulting from paging message transmissions to UEs in the RRC_INACTIVE state. An RNA is managed on the gNodeB. The gNodeB locates UEs by paging them at the level of RNA. Cells are grouped into larger RNAs, each identified by an RNA ID. RNAs are grouped into larger TAs, each identified by a TAI.	Huawei Term
radio network controller	RNC	N/A	This equipment in the RNS is in charge of controlling the use and the integrity of the radio resources.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
radio network subsystem	RNS	N/A	Either a full network or only the access part of a UTRAN offering the allocation and the release of specific radio resources to establish means of connection in between a UE and the UTRAN. A Radio Network Subsystem is responsible for the resources and transmission/reception in a set of cells.	ITU-T Q.1741.9: "IMT-2000 references to Release 11 of GSM evolved UMTS core network"
Radio Network Subsystem Application Part	RNSAP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
table of 128 integers in the hopping sequence	RNTABLE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
radio network temporary identifier	RNTI	radio network temporary identity	A radio network temporary identifier is a generic term of an identifier for a UE when an RRC connection exists. Following types of RNTI are defined: cell RNTI (C-RNTI), serving RNC RNTI (S-RNTI), UTRAN RNTI (U-RNTI), and GERAN RNTI (G-RNTI).	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
robust header compression	ROHC	N/A	A highly robust and efficient header compression scheme for RTP/UDP/IP (Real-Time Transport Protocol, User Datagram Protocol, Internet Protocol), UDP/IP, and ESP/IP (Encapsulating Security Payload) headers	C. Bormann, Editor, TZI/Uni Bremen, C. Burmeister, Matsushita, M. Degermark, Univ. of Arizona, H. Fukushima, Matsushita, H. Hannu, Ericsson, L-E. Jonsson, Ericsson, R. Hakenberg, Matsushita, T. Koren, Cisco, K. Le, Nokia, Z. Liu, Nokia, A. Martensson, Ericsson, A. Miyazaki, Matsushita, K. Svanbro, Ericsson, T. Wiebke, Matsushita, T. Yoshimura, NTT DoCoMo, and H. Zheng, Nokia, "RObust Header Compression (ROHC): Framework and four profiles: RTP, UDP, ESP, and uncompressed ", RFC 3095, July 2001.

Term	Abbreviation	Synonym	Definition	Reference
restriction of the use of certain hazardous substances	RoHS	N/A	N/A	ETSI TS 103 247: "Access, Terminals, Transmission and Multiplexing (ATTM); Singlemode Optical Fibre System Specifications for Home Cabling"
recovery period	RP	N/A	N/A	Huawei Term
Registered PLMN	RPLMN	N/A	This is the PLMN on which certain location registration (LR) outcomes have occurred (see table 1 in 3GPP TS 23.122). In a shared network the RPLMN is the PLMN defined by the PLMN identity of the CN operator that has accepted the LR.	3GPP TS 23.122: "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Non-Access-Stratum (NAS) functions related to Mobile Station (MS) in idle mode"

Term	Abbreviation	Synonym	Definition	Reference
radio quality indication	RQI	N/A	Based on the received signal quality in the measurement report, the MS and BTS automatically adjust the current speech coding rate according to the related algorithm. The coding rate threshold is the RQI threshold, which is the carrier-to-interference ratio of a call.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
round robin	RR	N/A	Round robin (RR) is one of the algorithms employed by process and network schedulers in computing. As the term is generally used, time slices (also known as time quanta) are assigned to each process in equal portions and in circular order, handling all processes without priority (also known as cyclic executive). Round-robin scheduling is simple, easy to implement, and starvation-free. Round-robin scheduling can be applied to other scheduling problems, such as data packet scheduling in computer networks. It is an operating system concept.	Wikipedia
radio resource	RR	N/A	A portion of spectrum available in a limited geographical area (cell). This portion of spectrum can be further divided into radio frequency channels.	ITU-T Q.1711: "Network functional model for IMT-2000"

Term	Abbreviation	Synonym	Definition	Reference
radio resource control	RRC	N/A	A sublayer of radio interface Layer 3 existing in the control plane only which provides information transfer service to the non-access stratum. RRC is responsible for controlling the configuration of radio interface Layers 1 and 2.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
radio resource management	RRM	N/A	Radio resource management (RRM) ensures the efficient use of the available radio resources and also provides mechanisms to meet radio resource related requirements.	3GPP TS 38.533: "NR; User Equipment (UE) conformance specification; Radio Resource Management (RRM)"
remote radio unit	RRU	radio remote unit	Remote radio unit (RRU) is used to transmit and receive baseband signals, modulate and demodulate RF signals, process data, and amplify the power of signals. The RRU is installed closer to the antenna than the RFU, reducing feeder loss.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
reference signal	RS	N/A	Used for the transmission of framing, training and supervisory signals and do not carry user payload.	ETSI EN 302 326-2: "Fixed Radio Systems; Multipoint Equipment and Antennas; Part 2: Harmonised Standard for access to radio spectrum"
Recommended Standard 232	RS-232	N/A	An interface standard for serial communications. The original full name is EIA-RS-232, also called RS232. It defines connecting cables, mechanical characteristics, electrical characteristics, signal functions, and signal transmission procedures.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Recommended Standard 422	RS-422	N/A	A series of data transmission protocols for multi-point communications using four wires, full-duplex, and differential transmission. It is also known as EIA-422. It applies to transmissions using balanced, unidirectional/ non-reversible, and terminated/ non-terminated transmission lines. Unlike RS-485, EIA-422 does not allow multiple transmit ends but allows multiple receive ends. In terms of hardware, an EIA-422 (RS-422) is equivalent to two EIA-485 (RS-485). That is, two half-duplex EIA-485 (RS-485) form a full-duplex EIA-422 (RS-422).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Recommended Standard 485	RS-485	N/A	A standard that defines the electrical characteristics of the physical layer in the OSI model for multi-point communications using two wires, half-duplex, and balanced lines. It is also known as EIA-485 or RS485. EIA-485 defines only the electrical characteristics of receive and transmit ends. It does not specify or recommend any data protocol. EIA-485 applies to inexpensive local networks and communications links with one transmitter and multiple receivers, using differential twisted pairs similar to EIA-422.	Wikipedia
Rivest-Shamir-Adleman algorithm	RSA algorithm	N/A	Public-key cryptosystem for both encryption and authentication; invented by Ron Rivest, Adi Shamir, and Leonard Adleman	ETSI TS 101 323: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Interoperable security profiles"

Term	Abbreviation	Synonym	Definition	Reference
received signal code power	RSCP	N/A	Given only signal power is received, the average power of the received signal after despreading and combining.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
radio system entity	RSE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
received scheduled E-DCH power share	RSEPS	N/A	RSEPS is the ratio of the receive power of all scheduled users to the RTWP in the current cell. RSEPS is measured by the NodeB and periodically reported to the RNC.	Huawei Term
roaming signaling gateway	R-SGW	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
radio signalling link	RSL	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
reference signal received power	RSRP	N/A	Reference signal received power (RSRP), is defined as the linear average over the power contributions (in [W]) of the resource elements within the considered measurement frequency bandwidth.	3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements"
reference signal received quality	RSRQ	N/A	Reference signal received quality (RSRQ) is defined as the ratio $N \times \text{RSRP} / (\text{carrier RSSI})$, where N is the number of RBs of the carrier RSSI measurement bandwidth.	3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements"

Term	Abbreviation	Synonym	Definition	Reference
received signal strength indicator	RSSI	received signal strength indication	RSSI is the root mean squared (RMS) value of the signal received at the receiver antenna. The RSSI estimate is compensated for all the time-varying processes (such as automatic gain control) that affect the estimation procedure for obtaining a relative measure to use in comparing the strength of signals received at different times.	ETSI TS 101 376-5-6: "GEO-Mobile Radio Interface Specifications; Part 5: Radio interface physical layer specifications; Sub-part 6: Radio Subsystem Link Control"
Rapid Spanning Tree Protocol	RSTP	N/A	An evolution of the Spanning Tree Protocol (STP) that provides faster spanning tree convergence after a topology change. The RSTP protocol is backward compatible with the STP protocol.	Huawei Term
road side unit	RSU	N/A	N/A	3GPP TS 23.287: "Architecture enhancements for 5G System (5GS) to support Vehicle-to-Everything (V2X) services"

Term	Abbreviation	Synonym	Definition	Reference
radio transmission control	RT	N/A	A control function to set, maintain and switch (change) the radio channel.	ITU-R M.1224: "VOCABULARY OF TERMS FOR INTERNATIONAL MOBILE TELECOMMUNICATIONS-2000 (IMT-2000)"
real time	RT	N/A	Time, typically in number of seconds, to perform an on-line mechanism	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
real-time broadband communication	RTBC	N/A	Real-time broadband communication (RTBC) is a new scenario proposed by Huawei based on both enhanced Mobile Broadband (eMBB) and Ultra-Reliable and Low-Latency Communications (URLLC) because some applications require not only high bandwidth and high rate for data transmission but also high-reliability and low-latency transmission performance.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Real-Time Transport Control Protocol	RTCP	RTP Control Protocol	Real-Time Transport Control Protocol (RTCP) is a sister protocol of the Real-time Transport Protocol (RTP). Its basic functionality and packet structure is defined in RFC 3550. RTCP provides out-of-band statistics and control information for an RTP session. It partners with RTP in the delivery and packaging of multimedia data, but does not transport any media data itself.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
round-trip delay	RTD	N/A	In telecommunications, round-trip delay (RTD) or round-trip time (RTT) is the amount of time it takes for a signal to be sent plus the amount of time it takes for acknowledgement of that signal having been received. This time delay includes propagation times for the paths between the two communication endpoints. In the context of computer networks, the signal is typically a data packet. RTT is also known as ping time, and can be determined with the ping command. End-to-end delay is the length of time it takes for a signal to travel in one direction and is often approximated as half the RTT.	Wikipedia
relative time difference	RTD	N/A	N/A	3GPP TS RAN R2.03: "Report on Location Services (LCS)"

Term	Abbreviation	Synonym	Definition	Reference
remote terminal emulator	RTE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
radio transmission node	RTN	N/A	N/A	Huawei Term
retransmission timeout	RTO	N/A	N/A	ETSI TR 102 676: "Satellite Earth Stations and Systems (SES); Broadband Satellite Multimedia (BSM); Performance Enhancing Proxies (PEPs)"
real-time transport protocol	RTP	N/A	RTP provides end-to-end network transport functions suitable for applications transmitting real-time data, such as audio, video or simulation data, over multicast or unicast network services.	H. Schulzrinne, Columbia University, S. Casner, Packet Design, R. Frederick, Blue Coat Systems Inc., V. Jacobson, and Packet Design, "RTP: A Transport Protocol for Real-Time Applications", RFC 3550, July 2003

Term	Abbreviation	Synonym	Definition	Reference
response TPDU	R-TPDU	• Response-TPDU • Response - Transfer Protocol Data Unit	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
registration termination request	RTR	N/A	N/A	3GPP TS 32.409: "Telecommunication management; Performance Management (PM); Performance measurements; IP Multimedia Subsystem (IMS)"
round-trip time	RTT	• round-trip delay • round-trip delay time	Time required for a network communication to travel from the source to the destination and back.	ETSI TR 102 479: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Review of available material on QoS requirements of Multimedia Services"

Term	Abbreviation	Synonym	Definition	Reference
real-time variable bit rate	rt-VBR	N/A	Real-time variable bit rate (rt-VBR) is intended for real-time applications, such as compressed voice over IP (VoIP) and video conferencing. The rt-VBR is characterized by a peak cell rate (PCR), sustained cell rate (SCR), and maximum burst size (MBS). The source device can transmit signals whose rates vary with time in bursts.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Received Total Wideband Power	RTWP	received wide band power	The received wide band power, including noise generated in the receiver, within the bandwidth defined by the receiver pulse shaping filter. The reference point for the measurement shall be the Rx antenna connector. In case of receiver diversity the reported value shall be linear average of the power in the diversity branches. When cell portions are defined in the cell, the total received wideband power shall be measured for each cell portion.	3GPP TS 25.215: "Technical Specification Group Radio Access Network; Physical layer; Measurements (FDD)"

Term	Abbreviation	Synonym	Definition	Reference
Resource Unit	RU	N/A	A resource unit, schedulable for single-tone NPUSCH with UL-SCH transmission, is defined as a single 3.75 kHz sub-carrier for 32 ms or a single 15 kHz sub-carrier for 8 ms. A resource unit, schedulable for multi-tone NPUSCH with UL-SCH transmission is defined as 3 sub-carriers for 4 ms; or 6 sub-carriers for 2 ms; or 12 sub-carriers for 1 ms. A resource unit, schedulable for NPUSCH with ACK/NAK transmission, is defined as a single 3.75 kHz sub-carrier for 8 ms or a single 15 kHz sub-carrier for 2 ms. A UL-SCH transport block can be scheduled over one or more than one resource unit in time.	3GPP TS 36.300: "Technical Specification Group Services and System Aspects; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
redundancy version	RV	N/A	N/A	3GPP TS 25.212: "Technical Specification Group (TSG) Radio Access Network (RAN); Working Group 1 (WG1); Multiplexing and channel coding (FDD)"
remote vendor-defined antenna line device	RVD	N/A	A remote vendor-defined antenna line device (RVD) is used to adjust the vertical beamwidth of an antenna.	Huawei Term
receive diversity	RX Diversity	N/A	N/A	Huawei Term
received signal quality	RxQual	N/A	N/A	Huawei Term
reception-transmission	RX-TX	N/A	N/A	ETSI TS 103 636-1: "DECT-2020 New Radio (NR); Part 1: Overview;

Term	Abbreviation	Synonym	Definition	Reference
radio frame	N/A	N/A	A radio frame is a numbered time interval of 10 ms duration used for data transmission on the radio physical channel. A radio frame is divided into 15 time slots of 0.666 ms duration. The unit of data that is mapped to a radio frame (10 ms time interval) may also be referred to as radio frame.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
RADIUS accounting	N/A	N/A	A method of accounting in which the BRAS sends accounting packets to the RADIUS server. The RADIUS server uses these packets to perform accounting for users.	Huawei Term
RADIUS authentication	N/A	N/A	An authentication mode in which the BRAS sends the user name and the password to the RADIUS server by using the RADIUS protocol. The RADIUS server authenticates the user, and then returns the result to the BRAS.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
RADIUS server	N/A	N/A	A server that responds to and processes devices' RADIUS authentication and accounting packets to control user authentication and login.	Huawei Term
rake receiver	N/A	N/A	A rake receiver is a radio receiver designed to counter the effects of multipath fading. It does this by using several "sub-receivers" called fingers, that is, several correlators each assigned to a different multipath component.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
random early detection	N/A	- random early discard - random early drop	Random early detection (RED), also known as random early discard or random early drop is a queuing discipline for a network scheduler suited for congestion avoidance. In the conventional tail drop algorithm, a router or other network component buffers as many packets as it can, and simply drops the ones it cannot buffer. If buffers are constantly full, the network is congested. Tail drop distributes buffer space unfairly among traffic flows. Tail drop can also lead to TCP global synchronization as all TCP connections "hold back" simultaneously, and then step forward simultaneously. Networks become under-utilized and flooded-alternately, in waves.	Wikipedia
rank	N/A	N/A	Maximum number of layers or streams in a multi-antenna system.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
rate matching	N/A	N/A	Rate matching allows bits on the transport channel to be retransmitted or punctured to match the bearing capability of the physical channel, and enables the bit rate to reach the level required by the transport format in channel mapping.	Huawei Term
Rayleigh fading	N/A	N/A	Rayleigh fading is a statistical model for the effect of a propagation environment on a radio signal, such as that used by wireless devices. Rayleigh fading models assume that the magnitude of a signal that has passed through such a transmission medium (also called a communication channel) will vary randomly, or fade, according to a Rayleigh distribution — the radial component of the sum of two uncorrelated Gaussian random variables.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
receiver sensitivity	N/A	N/A	The sensitivity of an electronic device, such as a communications system receiver, or detection device, such as a PIN diode, is the minimum magnitude of input signal required to produce a specified output signal having a specified signal-to-noise ratio or other specified criteria. The receiver sensitivity indicates how faint an input signal can be to be successfully received by the receiver. The lower the power level of the successfully received signal, the higher the receiver sensitivity.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Recommendation ITU-T G.8013/Y.1731	N/A	N/A	Recommendation ITU-T G.8013/Y.1731 provides mechanisms for user-plane OAM functionality in Ethernet networks according to the requirements and principles given in Recommendation ITU T Y.1730. This Recommendation is designed specifically to support point-to-point connections and multipoint connectivity in the ETH layer as identified in Recommendation ITU T G.8010/Y.1306.	ITU-T G.8013/Y.1731: "Operation, administration and maintenance (OAM) functions and mechanisms for Ethernet based networks"
reference clock	N/A	N/A	A clock of very high stability and accuracy that may be completely autonomous and whose frequency serves as a basis of comparison for the frequency of other clocks.	ITU-T G.701: "VOCABULARY OF DIGITAL TRANSMISSION AND MULTIPLEXING, AND PULSE CODE MODULATION (PCM) TERMS"
regeneration	N/A	N/A	The process of receiving and reconstructing a digital signal so that the amplitudes, waveforms and timing of its signal elements are constrained within specified limits.	ITU-T G.701: "VOCABULARY OF DIGITAL TRANSMISSION AND MULTIPLEXING, AND PULSE CODE MODULATION (PCM) TERMS"

Term	Abbreviation	Synonym	Definition	Reference
relay	N/A	N/A	Terminal devices capable of ODMA relay communications.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
relay*	N/A	N/A	Relay is a technology in which nodes are added between a transmit end and a receive end to forward signals so as to improve network coverage or capacity.	Huawei Term
remote error indication	N/A	N/A	Remote error indication (REI) or formerly far end block error (FEBE) is an alarm signal used in synchronous optical networking (SONET). It indicates to the transmitting node that the receiver has detected a block error.	Wikipedia
retransmission	N/A	N/A	Retransmission refers to the process in which the receiver fails to receive data and requests the sender to retransmit the failed data.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
reversion mode	N/A	recover mode	The 1+1 reversion mode is classified into revertive mode and non-revertive mode.	Huawei Term
RF circulator	N/A	N/A	An RF circulator is a three-port passive device used to control the direction of signal flow in a circuit	Huawei Term
ring network	N/A	N/A	A ring network is a network topology in which each node connects to exactly two other nodes, forming a single continuous pathway for signals through each node – a ring. Data travels from node to node, with each node along the way handling every packet.	Wikipedia
ring networking	N/A	N/A	A ring network is a network topology in which each node connects to exactly two other nodes, forming a single continuous pathway for signals through each node – a ring. Data travels from node to node, with each node along the way handling every packet.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
roaming	N/A	N/A	Ability of the users to access services according their user profile while moving outside of their subscribed home network.	ETSI TR 180 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Release 1; Release definition"
robustness	N/A	N/A	Degree to which a system or component can function correctly in the presence of invalid inputs or stressful environmental conditions (IEEE St. 610.12-1990)	ETSI TR 101 583: "Methods for Testing and Specification (MTS); Security Testing; Basic Terminology"
root alarm	N/A	N/A	An alarm at the top of an alarm chain. Alarms may have association relationships or parent-child relationships between them. Assume that alarm A causes alarm B and alarm B causes alarm C. Then, the root alarm is alarm A, and alarms B and C are correlative alarms of alarm A.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
root certificate	N/A	N/A	A certificate that an entity explicitly trusts, typically a self-signed CA certificate.	3GPP TS 24.109: "Bootstrapping interface (Ub) and network application function interface (Ua); Protocol details"
route	N/A	N/A	A path through one or more networks between connection endpoints.	ETSI TR 101 287: "Network Aspects (NA); Terms and definitions"
routing protocol	N/A	N/A	A routing protocol specifies how routers communicate with each other to distribute information that enables them to select routes between nodes on a computer network.	Wikipedia
radio-on-a-chip	RoC	N/A	Radio-on-a-chip or RoC systems are single-chip devices that incorporate a receiver, an amplifier, and power management into a single chip, which can thus be embedded into very small or even portable electronics.	Huawei Term

1.20 S

Term	Abbreviation	Synonym	Definition	Reference
S1 Application Protocol	S1AP	N/A	N/A	Huawei Term
service area	SA	N/A	N/A	3GPP TS 25.419: "UTRAN Iu-BC interface: Service Area Broadcast Protocol (SABP)"
standalone	SA	N/A	N/A	3GPP TS 38.533: "NR; User Equipment (UE) conformance specification; Radio Resource Management (RRM)"

Term	Abbreviation	Synonym	Definition	Reference
security association	SA	N/A	A security association (SA) is the establishment of shared security attributes between two network entities to support secure communication. An SA may include attributes such as: cryptographic algorithm and mode; traffic encryption key; and parameters for the network data to be passed over the connection. The framework for establishing security associations is provided by the Internet Security Association and Key Management Protocol (ISAKMP). Protocols such as Internet Key Exchange (IKE) and Kerberized Internet Negotiation of Keys (KINK) provide authenticated keying material.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Signalling ATM Adaptatio n Layer	SAAL	Signalling AAL	AAL used for the bi-directional transfer of layer 3 signalling information.	ETSI EN 301 776: "Broadband Private Integrated Services Networks (B- PISNs); Inter- exchange signalling protocol; Separated Bearer Control (SBC)"
service area code	SAC	N/A	N/A	3GPP TS 32.293: "Telecommuni cation management; Charging management; Proxy function"
Slow Associate d Control Channel	SACCH	N/A	The base station transmits power control information and frame adjustment information to the mobile station through this channel. Furthermore, the base station uses this channel to receive the signal strength report and the link quality report sent by the mobile station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
slow associated control channel/traffic channel	SACCH/T	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
slow associated control channel/traffic channel full rate	SACCH/TF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
slow associated control channel/traffic channel half rate	SACCH/TH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
source address	SAD	N/A	The part of a message which indicates who sent the message.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
System Architecture Evolution	SAE	N/A	The 3GPP system architecture evolution (SAE) is an all-IP architecture that uses IP protocols and functions to transport both voice and data packets through the evolved packet core (EPC) network.	ITU-T Y.3031: "Identification framework in future networks"
service area identifier	SAI	N/A	N/A	3GPP TS 32.250: "Telecommunication management; Charging management; Circuit Switched (CS) domain charging"
secret access key	SAK	N/A	An authentication key for a user to access an object-based storage system. A secret access key and a request header form a set of authentication information for a user. Secret access keys and access key IDs are in one-to-one match.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
single-primary antenna line device	SALD	single-primary ALD	An ALD type supporting only one layer 2 link. A SALD is controlled by a single primary, it can have only one control port. A SALD may have multiple AISG ports. Each port can simultaneously have an assigned ALDAddress. At any time, only one primary can establish a layer 2 link and activate layer 7 to a SALD.	Antenna Interface Standards Group Base Standard AISG v3.0.0.10
service access point	SAP	N/A	A conceptual point where a protocol layer offers access to its services to upper layer.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
service access point identifier	SAPI	N/A	Identifies the Service Access Point that the SN-PDU is using at the LLC layer.	3GPP TS 44.065: "Technical Specification Group Core Network; Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Serving GPRS Support Node (SGSN); Subnetwork Dependent Convergence Protocol (SNDCP)"

Term	Abbreviation	Synonym	Definition	Reference
Stand-Alone Serving Mobile Location Center	SAS	Stand-Alone SMLC	The SAS communicates with the RNC over the Iurc interface enabling it to forward UE Positioning assistance data to UEs and to receive UE Positioning measurement data from the RNC. When timing assistance is needed, the SAS may rely on associated LMUs or on the RNC (and on the possibility to have GNSS receivers co-located with the RNC, the NodeBs and/or present in the UEs) to obtain that.	3GPP TS 25.305: "Technical Specification Group Radio Access Network Stage 2 Functional Specification of Location Services in UTRAN"
SIM application toolkit	SAT	N/A	A set of applications and related procedures which may be used during a GSM session	3GPP TS 11.14: "Specification of the SIM Application Toolkit for the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface"
Structure-Agnostic Time Division Multiplexing over Packet	SAToP	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
signaling access unit	SAU	N/A	A unified narrowband signaling access platform that is based on the Compact Peripheral Component Interconnect (CPCI) platform.	Huawei Term
stop and wait	SAW	N/A	A sender using stop-and-wait ARQ (sometimes known as 'Idle ARQ') transmits a single frame and then waits for an acknowledgement from the receiver for that frame. The sender then either continues transmission with the next frame, or repeats transmission of the same frame if the acknowledgement indicates that the original frame was lost or corrupted.	G. Fairhurst, University of Aberdeen, L. Wood, and Cisco Systems Ltd, "Advice to link designers on link Automatic Repeat reQuest (ARQ)", RFC 3366, August 2002
scheduling block	SB	N/A	N/A	3GPP TS 25.433: "Technical Specification Group Radio Access Network; UTRAN Iub interface Node B Application Part (NBAP) signalling "

Term	Abbreviation	Synonym	Definition	Reference
synchroni zation burst	SB	sync burst	VDL Mode 4 burst type containing, as a minimum, information on the station's identity, position and time.	ETSI EN 302 842-2: "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 2: General description and data link layer"
session boarder controller	SBC	N/A	N/A	ETSI TR 102 719: "Speech and multimedia Transmission Quality (STQ); Perceptual Impact of End-to-End Delay and End-to-End Delay Variation on Fax-over-IP (FoIP) and Modem-over-IP (MoIP)"

Term	Abbreviation	Synonym	Definition	Reference
Supervisory Block	S-Block	N/A	Supervisory block, S-block, which is used to send control information.	3G TS 31.101: "Technical Specification Group Core Network and Terminals; UICC-terminal interface; Physical and logical characteristics "
service-based local policy	SBLP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
serving base station controller	SBSC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
serving base station subsystem	SBSS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
Smart Bias Tee	SBT	Smart Bias-Tee	N/A	Huawei Term
service classification	SC	N/A	N/A	Huawei Term
service center	SC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
service code	SC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
selection combining	SC	N/A	Of the N received signals, the strongest signal is selected.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
secondary component carrier	SCC	N/A	In the downlink, the carrier corresponding to an SCell is a downlink secondary component carrier (DL SCC) while in the uplink it is an uplink secondary component carrier (UL SCC).	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
synchronization control channel	SCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Signalling Connection Control Part	SCCP	N/A	SS7 protocol that enhances MTP routing functionality for efficient use of the network to transport non-circuit control related information. Interfaces to the SCCP are consistent with the OSI Network Layer.	ETSI TR 101 338: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Analysis of existing roaming techniques applicable to TIPHON mobility services"

Term	Abbreviation	Synonym	Definition	Reference
secondary common control physical channel	S-CCPCH	N/A	N/A	Huawei Term
secondary cell	SCell	N/A	A cell, operating on a secondary frequency, which may be configured once an RRC connection is established and which may be used to provide additional radio resources.	3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification"
single-carrier frequency division multiple access	SC-FDMA	N/A	Single-carrier FDMA (SC-FDMA) is a frequency-division multiple access scheme. It is also called linearly precoded OFDMA (LP-OFDMA). Like other multiple access schemes (TDMA, FDMA, CDMA, OFDMA), it deals with the assignment of multiple users to a shared communication resource. SC-FDMA can be interpreted as a linearly precoded OFDMA scheme, in the sense that it has an additional DFT processing step preceding the conventional OFDMA processing.	3GPP TS 36.300: "Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN);"

Term	Abbreviation	Synonym	Definition	Reference
secondary cell group	SCG	N/A	In dual connectivity, a group of serving cells associated with the SeNB, comprising of PSCell and optionally one or more SCells.	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
synchronization channel	SCH	N/A	Part of the transmission frame providing a phase reference	ETSI EN 300 401: "Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers"
single carrier HSDPA	SC-HSDPA	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
switched circuit network	SCN	N/A	Telecommunications network, e.g. Public Switched Telephone Network (PSTN), Integrated Services Digital Network (ISDN), and General System for Mobile communications (GSM), that uses circuit-switched technologies for the support of voice calls. The SCN maybe a public network or a private network.	ETSI TR 101 300: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Description of Technical Issues"
sub-channel number	SCN	N/A	Number identifying a specific Sub-Channel.	ETSI EN 301 958: "Digital Video Broadcasting (DVB); Interaction channel for Digital Terrestrial Television (RCT) incorporating Multiple Access OFDM"
service control point	SCP	N/A	The SCP is an entity that acts as a real-time database and transaction processing system that provides service control and service data functionality.	ITU-T Q.1742.1: "IMT-2000 references to ANSI-41 evolved core network with cdma2000 access network"

Term	Abbreviation	Synonym	Definition	Reference
secondary common pilot channel	S-CPICH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
sustainable cell rate	SCR	N/A	N/A	ETSI TR 101 173: "Broadband Radio Access Networks (BRAN); Inventory of broadband radio technologies and techniques"
subcarrier spacing	SCS	N/A	The difference between frequencies of any two adjacent orthogonal frequency division multiplexing (OFDM) subcarriers.	ITU-T G.9960: "Unified high-speed wire-line based home networking transceivers – System architecture and physical layer specification"
Small Computer System Interface	SCSI	N/A	Small Computer System Interface (SCSI) is a set of standards for physically connecting and transferring data between computers and peripheral devices.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Stream Control Transmission Protocol	SCTP	N/A	The Stream Control Transmission Protocol (SCTP) is a new IP transport protocol, existing at an equivalent level with UDP (User Datagram Protocol) and TCP (Transmission Control Protocol), which provide transport layer functions to many Internet applications.	L. Ong, Ciena Corporation, J. Yoakum, and Nortel Networks, "An Introduction to the Stream Control Transmission Protocol (SCTP)", RFC 3286, May 2002
space diversity reception	SD	• antenna diversity • spatial diversity	Antenna diversity, also known as space diversity or spatial diversity, is any one of several wireless diversity schemes that uses two or more antennas to improve the quality and reliability of a wireless link.	Wikipedia
Slice Differentiator	SD	N/A	An S-NSSAI is comprised of: - A slice/service type (SST), - A Slice Differentiator (SD), which is optional information that complements the slice/service(s) to differentiate amongst multiple network slices.	3GPP TS 23.003: "Numbering, addressing and identification"

Term	Abbreviation	Synonym	Definition	Reference
signal degrade	SD	N/A	A signal indicating the associated data has degraded in the sense that a degraded defect (dDEG) condition is active.	ETSI EN 300 417-1-1: "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 1-1: Generic processes and performance"

Term	Abbreviation	Synonym	Definition	Reference
standard definition	SD	N/A	Standard Definition (SD) Media Profile: Video streams conforming to this Media Profile are (i) preferably encoded using the color parameters defined by BT.709; and (ii) encoded with the following color parameters: • for 24 Hz, 30 Hz & 60 Hz content: the color parameters defined by BT.709, or the color parameters defined for 525 - line video systems as per BT.601. • for 25 Hz & 50 Hz content: the color parameters defined by BT.709, or the color parameters defined for 625 - PAL video systems as per BT.1700.	3GPP TR 26.949: "Video formats for 3GPP services"
software-defined antenna	SDA	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Service Data Adaptation Protocol	SDAP	N/A	The main services and functions of SDAP include: - Mapping between a QoS flow and a data radio bearer; - Marking QoS flow ID (QFI) in both DL and UL packets. A single protocol entity of SDAP is configured for each individual PDU session.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage-2"
standalone dedicated control channel	SDCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
service data flow	SDF	N/A	N/A	3GPP TS 36.509: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Special conformance testing functions for User Equipment (UE)"

Term	Abbreviation	Synonym	Definition	Reference
synchronous digital hierarchy	SDH	N/A	The SDH is a hierarchical set of digital transport structures, standardized for the transport of suitably adapted payloads over physical transmission networks.	ITU-T G.780/Y.1351: "Terms and definitions for synchronous digital hierarchy (SDH) networks"
specification and description language	SDL	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
supplementary downlink	SDL	supplemental downlink	N/A	3GPP TS 38.104, NR; Base Station (BS) radio transmission and reception (Release 17)

Term	Abbreviation	Synonym	Definition	Reference
space division multiple access	SDMA	- space-division multiple access - spatial division multiple access	Space division multiple access (SDMA) is a channel access method based on creating parallel spatial pipes (focused signal beams) using advanced antenna technology next to higher capacity pipes through spatial multiplexing and/or diversity, by which it is able to offer superior performance in radio multiple access communication systems (where multiple users may need to use the communication media simultaneously).	Wikipedia
service dialing number	SDN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Session Description Protocol	SDP	N/A	SDP is intended for describing multimedia sessions for the purposes of session announcement, session invitation, and other forms of multimedia session initiation.	M. Handley, V. Jacobson, and C. Perkins, "SDP: Session Description Protocol", July 2006.
software-defined radio	SDR	N/A	Radio transmitter and/or receiver employing a technology that allows the RF operating parameters including, but not limited to, frequency range, modulation type, or output power to be set or altered by software, excluding changes to operating parameters which occur during the normal pre-installed and predetermined operation of a radio according to a system specification or standard.	ETSI TR 102 802: "Reconfigurable Radio Systems (RRS); Cognitive Radio System Concept"

Term	Abbreviation	Synonym	Definition	Reference
structured data transfer	SDT	N/A	N/A	ETSI TR 101 689-1: "Transmission and Multiplexing (TM); Terms and definitions in transport networks; Part 1: Core networks"
SDL development tool	SDT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
small data transmission	SDT	N/A	Small data transmission (SDT) is a procedure allowing data and/or signalling transmission while remaining in RRC_INACTIVE state (i.e. without transitioning to RRC_CONNECTED state).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
service data unit	SDU	N/A	In the reference model for OSI, an amount of information whose identity is preserved when transferred between peer (N+1)-layer entities and which is not interpreted by the supporting (N)-layer entities.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
Sending Entity	SE	N/A	This is the entity from which the Secured Packet originates (e.g. SMS-SC, SIM, USSD entry point, or dedicated SIM Toolkit Server) and where the security mechanisms are invoked. The Sending Entity generates the Secured Packets to be sent.	3GPP TS 03.48: "Technical Specification Group Terminals; Security mechanisms for the SIM application toolkit; Stage 2"
support entity	SE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
support entity function	SEF	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
security gateway	SeGW	N/A	N/A	3GPP TS 44.318: "Generic Access Network (GAN); Mobile GAN interface layer 3 specification"
shadow fading	SF	N/A	N/A	3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz (Release 16)"
signal fail	SF	N/A	A signal indicating that the associated data has failed in the sense that a near-end defect condition (not being the degraded defect) is active.	ITU-T G.806: "Characteristics of transport equipment – Description methodology and generic functionality"

Term	Abbreviation	Synonym	Definition	Reference
spreading factor	SF	N/A	In a Code Division Multiple Access (CDMA) system, the number of chips per data symbol is called the spreading factor (SF). The lower the spreading factor, the higher the data rate.	Huawei Term
space-frequency block coding	SFBC	N/A	N/A	3GPP TS 36.521-1: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing"
synthesized frequency hopping	SFH	N/A	A hopping method in which the radios keep synchronized with the transmission frequency of the TDMA frame. In this method a voice call remains associated with one transmitter.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
slow frequency hopping	SFH	N/A	FH technique where the hopping period is larger than the symbol period.	ETSI EN 301 179: "Transmission and Multiplexing (TM); Digital Radio Relay Systems (DRRS); Frequency Hopping Code Division Multiple Access (FH-CDMA); Point-to-multipoint DRRS in the bands within the range 1 GHz to 3 GHz"
Short EF Identifier	SFI	Short elementary File Identifier	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
Slot Format Indication RNTI	SFI-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
system frame number	SFN	N/A	The system frame number is used to uniquely identify a random access.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
single frequency network	SFN	N/A	Network of transmitters sharing the same radio frequency to achieve a large area coverage.	ETSI ES 201 980: "Digital Radio Mondiale (DRM); System Specification"
security function policy	SFP	N/A	N/A	ETSI TR 170 002: "Project MESA; Service Specification Group - Services and Applications; Definitions, symbols and abbreviations"
small form-factor pluggable	SFP	N/A	The small form-factor pluggable (SFP) is a compact, hot-pluggable network interface module used for both telecommunication and data communications applications.	Wikipedia
Secure File Transfer Protocol	SFTP	SSH File Transfer Protocol	In computing, the SSH File Transfer Protocol (also Secure File Transfer Protocol, or SFTP) is a network protocol that provides file access, file transfer, and file management over any reliable data stream.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
secondary gNodeB	SgNB	N/A	In dual connectivity, the gNodeB that is providing additional radio resources for the UE but is not the master node.	Huawei Term
signaling gateway process	SGP	N/A	A process instance of a signaling gateway. It serves as an active, backup, load-sharing, or broadcast process of a signaling gateway.	K. Morneault., "Signaling System 7 (SS7) Message Transfer Part 3 (MTP3) - User Adaptation Layer (M3UA)", RFC 4666, September 2006.
serving GPRS support node	SGSN	N/A	The serving GPRS support node is an exchange which performs packet switching functions for mobile stations located in a geographical area designated as the SGSN area.	3GPP TS 03.40: "Technical realization of the Short Message Service (SMS)"

Term	Abbreviation	Synonym	Definition	Reference
serving gateway	S-GW	N/A	A mobile core network element with the functions of the local mobility anchor point for inter-eNodeB handover, mobility anchoring for inter-3GPP mobility, packet routing and forwarding, transport level packet marking, accounting for inter-operator charging etc. Note: For details about the functions listed in this definition, refer to ETSI TS 123 401.	ITU-T X.1364: "Security requirements and framework for narrowband Internet of things"

Term	Abbreviation	Synonym	Definition	Reference
secure hash algorithm	SHA	N/A	When a message of any length $< 2^{64}$ bits (for SHA-224 and SHA-256) or $< 2^{128}$ bits (for SHA-384 and SHA-512) is input to one of these algorithms, the result is an output called a message digest. The message digests range in length from 224 to 512 bits, depending on the algorithm. Secure hash algorithms are typically used with other cryptographic algorithms, such as digital signature algorithms and keyed-hash authentication codes, the generation of random numbers [RFC4086], or in key derivation functions.	D. Eastlake 3rd, Huawei, T. Hansen, and AT&T Labs, "US Secure Hash Algorithms (SHA and SHA-based HMAC and HKDF)", RFC 6234, May 2011
shared channel control channel	SHCCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
soft handover	SHO	N/A	Soft handover is a category of handover procedures where the radio links are added and abandoned in such manner that the UE always keeps at least one radio link to the UTRAN.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
system information	SI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
screening indicator	SI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
system information RNTI	SI-RNTI	N/A	An SI-RNTI is used by a UE to parse system information.	3GPP TS 38.321: "NR; Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
system information block	SIB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
System Information Block 1	SIB1	N/A	SIB1 contains information relevant when evaluating if a UE is allowed to access a cell and defines the scheduling of other system information. It also contains radio resource configuration information that is common for all UEs and barring information applied to the unified access control.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
System Information Block 2	SIB2	N/A	SIB2 contains cell re-selection information common for intra-frequency, inter-frequency and/or inter-RAT cell re-selection (i.e. applicable for more than one type of cell re-selection but not necessarily all) as well as intra-frequency cell re-selection information other than neighbouring cell related.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
System Information Block 3	SIB3	N/A	SIB3 contains neighbouring cell related information relevant only for intra-frequency cell re-selection. The IE includes cells with specific re-selection parameters as well as exc	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
System Information Block 4	SIB4	N/A	SIB4 contains information relevant for inter-frequency cell re-selection (i.e. information about other NR frequencies and inter-frequency neighbouring cells relevant for cell re-selection), which can also be used for NR idle/inactive measurements. The IE includes cell re-selection parameters common for a frequency as well as cell specific re-selection parameters.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
System Information Block 5	SIB5	N/A	SIB5 contains information relevant only for inter-RAT cell re-selection i.e. information about E-UTRA frequencies and E-UTRAs neighbouring cells relevant for cell re-selection. The IE includes cell re-selection parameters common for a frequency.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
System Information Block 8	SIB8	N/A	SIB8 contains a CMAS notification.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
System Information Block 9	SIB9	N/A	SIB9 contains information related to GPS time and Coordinated Universal Time (UTC). The UE may use the parameters provided in this system information block to obtain the UTC, the GPS and the local time.	3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
successive interference cancellation	SIC	N/A	A physical layer capability that allows a receiver to decode packets that arrive simultaneously.	Huawei Term
Service Implementation Capabilities	SIC	N/A	Set of implementation capabilities, in each technical domain, required to enable a UE to support a set of UE Service Capabilities.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
silence insertion descriptor	SID	silence insertion description	A compressed representation of the audio background noise that can be sent during silent intervals. SIDs may not be continuous and may only be sent when there is a change in noise characteristics. Playing out received SIDs is known as Comfort Noise Generation.	ITU-T Y.1261: "Service requirements and architecture for voice services over Multi-Protocol Label Switching"
signal tone board	SIG	N/A	N/A	Huawei Term
signaling transport	SIG	SIGTRAN/ signaling transmission	SIG refers to a protocol stack for transport of SCN signaling protocols over an IP network. It will support standard primitives to interface with an unmodified SCN signaling application being transported, and supplements a standard IP transport protocol underneath with functions designed to meet transport requirements for SCN signaling.	L. Ong, Nortel Networks, I. Rytina, M. Garcia, Ericsson, H. Schwarzbauer, L. Coene, Siemens, H. Lin, Telcordia, I. Juhasz, Telia, M. Holdrege, Lucent, C. Sharp, and Cisco Systems, "Framework Architecture for Signaling Transport", RFC 2719, October 1999

Term	Abbreviation	Synonym	Definition	Reference
subscriber identity module	SIM	N/A	An integrated chip used mostly in mobile device that operates in the global system for mobile communications (GSM) network. It securely stores the international mobile subscriber identity (IMSI) and the related key used to identify and authenticate subscribers in mobile telephony devices.	ITU-T X.1158: "Multi-factor authentication mechanisms using a mobile device"
single-input multiple-output	SIMO	Single Input Multiple Output	N/A	3GPP TR 37.901: "User Equipment (UE) application layer data throughput performance"
signal to interference plus noise ratio	SINR	- signal-to-noise-plus-interference ratio - signal-to-interference-plus-noise ratio	N/A	3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures"
Session Initiation Protocol	SIP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
signal-to-interference ratio	SIR	- carrier-to-interference ratio - CIR	The signal-to-interference ratio (SIR or S/I), also known as the carrier-to-interference ratio (CIR or C/I), is the quotient between the average received modulated carrier power S or C and the average received co-channel interference power I, i.e. crosstalk, from other transmitters than the useful signal.	Wikipedia
single-input single-output	SISO	Single Input Single Output	N/A	3GPP TR 37.976: "Measurement of radiated performance for Multiple Input Multiple Output (MIMO) and multi-antenna reception for High Speed Packet Access (HSPA) and LTE terminals"

Term	Abbreviation	Synonym	Definition	Reference
shared interworking function	SIWF	N/A	A shared interworking function is a network function that may be used by any MSC in the same PLMN to provide interworking for a data/fax call.	3G TS 23.054: "3rd Generation Partnership Project; Technical Specification Group Core Network; Description for the use of a Shared Inter Working Function (SIWF) in a GSM PLMN - Stage 2 (3G TS 23.054 version 3.0.0)"
sidelink	SL	N/A	The term sidelink, frequently abbreviated as SL, refers to a link that is used for direct communication between UEs in ProSe communication. The counterparts to SL in wireless communication are uplink (UL) and downlink (DL), which are used for communication between the base station and a UE. SL is often used to refer to ProSe in 3GPP specifications.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Service Level Agreement	SLA	service-level agreement	Negotiated agreement between two or more parties, recording a common understanding about the service and/or service behaviour (e.g. availability, performance, service continuity, responsiveness to anomalies, security, serviceability, operation) offered by one party to another, and the measurable target values characterizing the level of services.	ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV"
signaling link code	SLC	N/A	The Signalling Link Code (SLC) is used to distinguish signalling link in the signalling link set. It is the same value (between 0 and 15) at each end of the link, and is different from that of any other link between the same two adjacent signalling point.	3GPP TS 28.735: "Telecommunication management; Signalling Transport Network (STN) interface Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)"

Term	Abbreviation	Synonym	Definition	Reference
subscriber LCS privacy profile	SLPP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
signaling link test message	SLTM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
short message	SM	N/A	N/A	3GPP TS 31.121: "UICC- terminal interface; Universal Subscriber Identity Module (USIM) application test specification"

Term	Abbreviation	Synonym	Definition	Reference
session management	SM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
service management access point	SMAP	N/A	N/A	ETSI TR 101 365: "Intelligent Network (IN); IN interconnect threat analysis"
smart tower-mounted amplifier	smart TMA	N/A	N/A	Huawei Term
Static Multiple Beam	SMB	N/A	A solution that generates multiple fixed beams on the vertical plane, for example, generates two 4T4R cells on an 8T8R AAU.	Huawei Term
security mode command	SMC	N/A	This message is sent by the network to the UE to establish NAS signalling security.	3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3"

Term	Abbreviation	Synonym	Definition	Reference
session management function	SMF	N/A	The session management function (SMF) hosts the following main functions (see 3GPP TS 23.501): - Session management; - UE IP address allocation and management; - Selection and control of UP function; - Configures traffic steering at UPF to route traffic to proper destination; - Control part of policy enforcement and QoS; - Downlink data notification.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage-2"
Special Mobile Group	SMG	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
serving mobile location center	SMLC	N/A	In GSM networks, the SMLC is a network element that resides in the base station controller (BSC) and calculates network-based location of mobile stations (handsets). The SMLC may control several location measurement units (LMUs), which measure radio signals to help find mobile stations in the area served by the SMLC. It can calculate location using the timing advance (TA) method. The SMLC communicates with the GMLC, which is the interface to external LCS clients.	Wikipedia
short message service	SMS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
SMS Cell Broadcast	SMS-CB	- Short Message Service Cell Broadcast - Short Message Service - Cell Broadcast	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
site maintenance terminal	SMT	N/A	A component of GBSS LMT software. It is used for local maintenance and management of sites.	Huawei Term
short message terminal	SMT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
SSB-based measurement timing configuration	SMTc	SS/PBCH block measurement timing configuration	An SSB-based measurement timing configuration configured by SSB-MeasurementTimingConfiguration as specified in 3GPP TS 38.331.	3GPP TS 38.133: "NR; Requirements for support of radio resource management"

Term	Abbreviation	Synonym	Definition	Reference
Simple Mail Transfer Protocol	SMTP	N/A	Widely used protocol for transferring E-mails between computers.	ETSI TS 102 232-2: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 2: Service-specific details for messaging services"
service management unit	SMU	N/A	Genetic name of all BSC boards except the GBAM server and the GOMU. A unit that manages users, organizations, and rights in the IVS system.	Huawei Term
serial number	SN	SNR	A two octet field which identifies a particular message. It is linked to the Message Identifier and is altered every time the message is changed.	3GPP TS 03.48: "Security mechanisms for SIM application toolkit; Stage 2"
shared network area	SNA	N/A	Area consisting of one or more LA's to which access can be controlled.	3GPP TS 25.401: "Technical Specification Group Radio Access Network; UTRAN overall description"

Term	Abbreviation	Synonym	Definition	Reference
shared network area code	SNAC	N/A	Used to mark a shared network area	Huawei Term
subnetwork connection protection	SNCP	N/A	A working subnetwork connection is replaced by a protection subnetwork connection if the working subnetwork connection fails, or if its performance falls below a required level.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "
Simple Network Management Protocol	SNMP	N/A	A (usually) UDP-based, application-layer, Internet standard protocol (RFCs 3410-3418) for conveying management information between system components that act as managers and agents.	R. Shirey, "Internet Security Glossary, Version 2", RFC 4949, August 2007
stand-alone non-public network	SNPN	N/A	N/A	3GPP TS 23.501: "System architecture for the 5G System (5GS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
signal-to-noise ratio	SNR	S/N	Ratio between the average power of signal and the average power of noise in a given point.	ETSI TS 105 175-1-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Plastic Optical Fibres; Part 1: Plastic Optical Fibre System Specifications for 100 Mbit/s and 1 Gbit/s; Sub-part 2: 1 Gbit/s and 100 Mbit/s physical layer for Plastic Optical Fibres"
Single Network Slice Selection Assistance Information	S-NSSAI	N/A	Within a PLMN or SNPN, a network slice is identified by an S-NSSAI, which is comprised of a slice/service type (SST) and a slice differentiator (SD). Inclusion of an SD in an S-NSSAI is optional. A set of one or more S-NSSAIs is called the NSSAI.	3GPP TS 24.501: "Non-Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3"

Term	Abbreviation	Synonym	Definition	Reference
Simple Network Time Protocol	SNTP	N/A	This memorandum describes the Simple Network Time Protocol Version 4 (SNTPv4), which is a subset of the Network Time Protocol (NTP) used to synchronize computer clocks in the Internet.	D. Mills, and University of Delaware, "Simple Network Time Protocol (SNTP) Version 4 for IPv4, IPv6 and OSI", RFC 4330, January 2006
second order	SO	N/A	The optimal compression state a ROHC compressor is in to compress IP headers, in which the compressor sends the data packets with the maximum compression efficiency. The compressor operates in this state in most cases.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
self-organizing network	SON	N/A	In order to reduce the operating expenditure (OPEX) associated with the management of this larger number of nodes from more than one vendor the concept of the self-organizing network (SON) is introduced. Automation of some network planning, configuration and optimization processes via the use of SON functions can help the network operator to reduce OPEX by reducing manual involvement in such tasks.	3GPP TS 32.500: "Telecommunication management; Self-Organizing Networks (SON); Concepts and requirements"

Term	Abbreviation	Synonym	Definition	Reference
synchronous optical network	SONET	N/A	Synchronous optical networking (SONET) and synchronous digital hierarchy (SDH) are standardized protocols that transfer multiple digital bit streams synchronously over optical fiber using lasers or highly coherent light from light-emitting diodes (LEDs). At low transmission rates data can also be transferred via an electrical interface. The method was developed to replace the plesiochronous digital hierarchy (PDH) system for transporting large amounts of telephone calls and data traffic over the same fiber without the problems of synchronization.	Wikipedia
standard operating procedure	SOP	N/A	N/A	ETSI GR CDM 001: "Common Information Sharing Environment Service and Data Model (CDM); Use Cases definition"

Term	Abbreviation	Synonym	Definition	Reference
Steering of Roaming	SoR	N/A	A technique whereby a roaming UE is encouraged to roam to a preferred VPLMN by the HPLMN.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
signalling point	SP	N/A	A node in a signalling network which either originates and receives signal messages, or transfers signal messages from one signalling link to another, or both.	ITU-T Q.9: "Vocabulary of Switching and Signalling Terms"

Term	Abbreviation	Synonym	Definition	Reference
service provider	SP	N/A	A service provider (SP) provides organizations with consulting, legal, real estate, communications, storage, processing. Although a service provider can be an organizational sub-unit, it is usually a third party or outsourced supplier, including telecommunications service providers (TSPs), application service providers (ASPs), storage service providers (SSPs), and internet service providers (ISPs). A more traditional term is service bureau (esp. 1960s to 1980s).	Wikipedia
signaling point code	SPC	N/A	A binary code uniquely identifying a signalling point in a signalling network. This code is used, according to its position in the label, either as destination point code or as originating point code.	ITU-T Q.9: "Vocabulary of Switching and Signalling Terms"

Term	Abbreviation	Synonym	Definition	Reference
service provider control key	SPCK	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Semi-Persistent CSI RNTI	SP-CSI-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
security policy database	SPD	N/A	N/A	3GPP TS 33.204: "3G Security; Network Domain Security (NDS); Transaction Capabilities Application Part (TCAP) user security"
shortest path first	SPF	N/A	N/A	ETSI TR 101 569: "Access, Terminals, Transmission and Multiplexing (ATTM); Integrated Broadband Cable and Television Networks; Cable Network Transition to IPv6"

Term	Abbreviation	Synonym	Definition	Reference
service priority group	SPG	N/A	N/A	Huawei Term
security parameters indication	SPI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
scheduling priority indicator	SPI	N/A	N/A	Huawei Term
Security Parameter Index	SPI	N/A	The Security Parameter Index (SPI) is an identification tag added to the header while using IPsec for tunneling the IP traffic. This tag helps the kernel discern between two traffic streams where different encryption rules and algorithms may be in use.	Wikipedia
subscriber profile ID	SPID	N/A	N/A	ETSI GS MEC 002: "Multi-access Edge Computing (MEC); Phase 2: Use Cases and Requirements"

Term	Abbreviation	Synonym	Definition	Reference
semi-persistent scheduling	SPS	N/A	Semi-persistent scheduling is a process where one user uses the same time-frequency resources in a specified semi-persistent scheduling period until they are released.	Huawei Term
signaling processing unit	SPU	N/A	A signaling processing unit is used in producing a prediction signal and comprises three prediction circuits (22, 23, 31) and a selection circuit (24) coupled to the prediction circuits.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Signaling Processing Unit REV:a	SPUa	N/A	The SPUa board is functionally divided into main control SPUa board and non-main control SPUa board based on the software loaded. The main control SPUa board is used to manage the UMTS user plane resources, control plane resources, and transmission resources in the system and process the UMTS services on the control plane. The non-main control SPUa board is used to process only the UMTS services on the control plane.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Structured Query Language	SQL	N/A	Structured Query Language (SQL) is a domain-specific language used in programming and designed for managing data held in a relational database management system (RDBMS), or for stream processing in a relational data stream management system (RDSMS). It is particularly useful in handling structured data, i.e. data incorporating relations among entities and variables.	Wikipedia
scheduling request	SR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
strict routing	SR	N/A	A proxy is said to be strict routing if it follows the Route processing rules of RFC 2543 and much prior work in progress versions of this RFC. This caused proxies to destroy the contents of the Request-URI when a Route header field was present. Strict routing behavior is not used in RFC 3261, in favor of a loose routing behavior. Proxies that perform strict routing are also known as strict routers.	J. Rosenberg, dynamicsoft, H. Schulzrinne, Columbia U., G. Camarillo, Ericsson, A. Johnston, WorldCom, J. Peterson, Neustar, R. Sparks, dynamicsoft, M. Handley, ICIR, E. Schooler, and AT&T, "SIP: Session Initiation Protocol", RFC 3261, June 2002
signaling radio bearer	SRB	N/A	RAN level bearer for RRC and NAS signalling. User plane signalling bearer (e.g., the bearer for SIP signalling) is not SRB, but RB.	3GPP TR 25.993: "Typical examples of Radio Access Bearers (RABs) and Radio Bearers (RBs) supported by Universal Terrestrial Radio Access (UTRA)"
scheduling request indicator	SRI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
SRS resource indicator	SRI	N/A	N/A	3GPP TS 38.213: "Technical Specification Group Radio Access Network; Physical layer procedures for control"
serving radio network controller	SRNC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
serving radio network subsystem	SRNS	serving RNS	It provides a connection to UTRAN for each UE. The SRNS is in charge of the radio connection between a UE and the UTRAN.	Huawei Term
Serving-Radio Network Temporary Identifier	S-RNTI	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
single radio LTE	SRLTE	N/A	Single radio LTE (SRLTE) is a single radio voice solution for CDMA/LTE dual-mode UEs. It is an intermediate product of the transition from CDMA2000 1X to VoIP. SRLTE and simultaneous voice and LTE (SVLTE) are two major voice solutions for CDMA/LTE dual-mode networks. When an SRLTE UE camps on or is activated in an LTE cell, the UE periodically leaves the LTE network to listen to the paging channel on the CDMA2000 1X network. The SRLTE UE does not notify the eNodeB when performing paging listening. The eNodeB schedules the UE even if the UE is currently listening to the paging channel on the CDMA2000 1X network. As a result, the cell throughput decreases in multi-user scenarios.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
sounding reference signal	SRS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
single radio voice call continuity	SRVCC	N/A	Voice call continuity between IMS over PS access and CS access for calls that are anchored in IMS when the UE is capable of transmitting/receiving on only one of those access networks at a given time.	3GPP TS 23.216: "Single Radio Voice Call Continuity (SRVCC); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
supplementary service	SS	N/A	A service which modifies or supplements a basic telecommunication service. A supplementary service must be offered together with or in association with a basic telecommunication service. It includes call forwarding services, call barring services, line identification services, call completion services, multiparty services, unstructured supplementary service data, and closed user group services.	Huawei Term
search space	SS	N/A	A search space consists of a set of PDCCH candidates of the same CCE aggregation level in a control zone (CORESET in NR).	• Huawei Term • 3GPP TS 38.213: "Technical Specification Group Radio Access Network; NR; Physical layer procedures for control"
Signaling System No. 7	SS7	N/A	N/A	3GPP TR 25.990: "Vocabulary for UTRAN"

Term	Abbreviation	Synonym	Definition	Reference
synchronization signal and PBCH block	SSB	SS/PBCH block	The synchronization signal and PBCH block (SSB) consists of primary and secondary synchronization signals (PSS, SSS), each occupying 1 symbol and 127 subcarriers, and PBCH spanning across 3 OFDM symbols and 240 subcarriers, but on one symbol leaving an unused part in the middle for SSS.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage-2"
supplementary service control string	SSC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
service specific coordination function	SSCF	special service coordination function	In the Asynchronous Transfer Mode (ATM) signaling layer the SSCF maps the requirements of the layer above to the requirements of SSCOP (Service Specific Connection Oriented Protocol).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
service specific coordination function – network node interface	SSCF-NNI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
secondary synchronization channel	S-SCH	N/A	S-SCH stands for "Secondary Synchronization Channel in UMTS" (Universal Mobile Telecommunications System). S-SCH is a pure downlink physical channel broadcast over the entire cell. It is transmitted unscrambled during the first 256 chips of each time slot, in time multiplex with Primary Common Control Physical Channel (P-CCPCH). It is the only channel that is not spread over the entire radio frame. The S-SCH is repeated at the beginning of each time slot and the same code is used by all the cells and enables the UE to detect the existence of the UMTS cell. The slot synchronization is done using the P-SCH but S-SCH is used to synchronize the UE with the frame boundaries. It also enables the UE to identify the Primary Scrambling Code Group for the cell.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			There are sixteen different codes for the 256 chips that are transmitted at the start of each time slot. Using these sixteen unique codes, 64 different code sequences are transmitted which serve two purposes. First, the UE can identify the frame boundaries since the 64 sequences are known to a user equipment. Second, the UE can identify the Primary Scrambling Code (PSC) group of the cell as every code sequence is assigned to a PSC group	
Service-Specific Connection-Oriented Protocol	SSCOP	Service Specific Connection Oriented Protocol	The Service Specific Connection Oriented Protocol (SSCOP), provides assured data delivery between AAL connection endpoints.	ITU-T Q.2110: "B-ISDN ATM ADAPTATION LAYER - SERVICE SPECIFIC CONNECTION ORIENTED PROTOCOL (SSCOP)"

Term	Abbreviation	Synonym	Definition	Reference
service specific convergence sublayer	SSCS	service specific convergence sub-layer	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Site Selection Diversity Transmission	SSDT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
system subframe number	SSFN	N/A	The long DRX cycle starts at the time specified by the system frame number (SFN) and system subframe number (SSFN).	Huawei Term
Secure Shell	SSH	- Secure Shell Protocol - SSH Protocol	The Secure Shell Protocol (SSH) is a protocol for secure remote login and other secure network services over an insecure network.	T. Ylonen, SSH Communications Security Corp, C. Lonvick, Ed., and Cisco Systems, Inc., "The Secure Shell (SSH) Authentication Protocol", RFC 4252, January 2006

Term	Abbreviation	Synonym	Definition	Reference
service set identifier	SSID	N/A	A service set identifier (SSID) defines a service set or extended service set. Normally it is broadcast in the clear by stations in beacon packets to announce the presence of a network and seen by users as a wireless network name.	Wikipedia
Secure Sockets Layer	SSL	N/A	A security protocol that works at a socket level. This layer exists between the TCP layer and the application layer to encrypt/decode data and authenticate concerned entities.	ITU-T J.296: "Specifications for a hybrid cable set-top box"
Synchronization Status Message	SSM	N/A	A Synchronization Status Message (SSM) provides information regarding the quality of the clock source being used by the SSM source.	ITU-T G.7041/Y.1303: "Generic framing procedure"
subsystem number	SSN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
special subframe pattern	SSP	N/A	N/A	Huawei Term
secondary synchronization signal	SSS	N/A	N/A	3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception"
search space set group	SSSG	N/A	N/A	3GPP TS 38.213: "NR; Physical layer procedures for control"
slice/service type	SST	N/A	An S-NSSAI is comprised of: - A slice/service type (SST), which refers to the expected network slice behaviour in terms of features and services; - A Slice Differentiator (SD), which is optional information that complements the slice/service type(s) to differentiate amongst multiple network slices of the same slice/service type.	3GPP TS 23.501: "System architecture for the 5G System (5GS)"

Term	Abbreviation	Synonym	Definition	Reference
synchroni zation supply unit	SSU	N/A	Synchronization supply units (SSU) are used to ensure reliable synchronization distribution. They have a number of key functions: 1. They filter the synchronization signal they receive to remove the higher frequency phase noise. 2. They provide distribution by providing a scalable number of outputs to synchronize other local equipment. 3. They provide a capability to carry on producing a high quality output even when their input reference is lost. This is referred to as holdover mode.	Wikipedia
security target	ST	N/A	N/A	ETSI TR 170 002: "Project MESA; Service Specification Group - Services and Applications; Definitions, symbols and abbreviations"

Term	Abbreviation	Synonym	Definition	Reference
space time coding	STC	N/A	Space time coding is a method employed to improve the reliability of data transmission in wireless communication systems using multiple transmit antennas.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
synchronous transport module	STM	N/A	An STM is the information structure used to support section layer connections in the SDH. It consists of information payload and section overhead (SOH) information fields organized in a block frame structure that repeats every 125 μ s. The information is suitably conditioned for serial transmission on the selected media at a rate which is synchronized to the network. A basic STM is defined at 155 520 Kbit/s. This is termed STM-1. Higher capacity STMs are formed at rates equivalent to N times this basic rate. STM capacities for N = 4, N = 16, N = 64 and N = 256 are defined; higher values are under consideration.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "

Term	Abbreviation	Synonym	Definition	Reference
Synchronous Transport Module level-1	STM-1	N/A	Synchronous Transport Module level-1 (STM-1) is the SDH ITU-T fiber optic network transmission standard. It has a bit rate of 155.52 Mbit/s. Higher levels go up by a factor of 4 at a time: the other currently supported levels are STM-4, STM-16, STM-64 and STM-256. Above STM-256 wavelength-division multiplexing (WDM) is commonly used in submarine cabling.	Wikipedia
Spanning Tree Protocol	STP	N/A	With the Spanning Tree Protocol (STP), a spanning tree will be formed over connected bridges by blocking some links between these bridges so that forwarding loops are avoided.	M. Zhang, H. Wen, Huawei, J. Hu, and China Telecom, "Spanning Tree Protocol (STP) Application of the Inter-Chassis Communication Protocol (ICCP)", RFC 7727, January 2016

Term	Abbreviation	Synonym	Definition	Reference
signal transfer point	STP	signaling transfer point	This is a node in an SS7 network that routes signaling messages based on their destination point code in the SS7 network.	L. Ong, Nortel Networks, I. Rytina, M. Garcia, Ericsson, H. Schwarzbauer, L. Coene, Siemens, H. Lin, Telcordia, I. Juhasz, Telia, M. Holdrege, Lucent, C. Sharp, and Cisco Systems, "Framework Architecture for Signaling Transport", RFC 2719, October 1999
shielded twisted pair	STP	N/A	An electrically conducting cable, comprising one or more elements, each of which is individually shielded. There may be an overall shield, in which case the cable is referred to as shielded twisted-pair cable with an overall shield.	ITU-T K.93: "Immunity of home network devices to electromagnetic disturbances"
System Test Report	STR	N/A	A report output from a system test	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
space time transmit diversity	STTD	N/A	Space time transmit diversity (STTD) is a method of transmit diversity used in UMTS third-generation cellular systems. STTD is optional in the UTRAN air interface but mandatory for user equipment (UE). STTD utilizes space-time block code (STBC) in order to exploit redundancy in multiple transmitted versions of a signal.	Wikipedia
supplementary uplink	SUL	• supplemental uplink • uplink enhancement	In conjunction with a UL/DL carrier pair (FDD band) or a bidirectional carrier (TDD band), a UE may be configured with additional, supplementary uplink (SUL). SUL differs from the aggregated uplink in that the UE may be scheduled to transmit either on the supplementary uplink or on the uplink of the carrier being supplemented, but not on both at the same time.	3GPP TS 38.300: "NR; NR and NG-RAN Overall description; Stage-2"

Term	Abbreviation	Synonym	Definition	Reference
subscription management	SuM	N/A	Set of capabilities that allow Operators, Service Providers, and indirectly subscribers, to provision, control, monitor the Subscription Profile.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
single-user multiple-input multiple-output	SU-MIMO	Single User Multiple Input Multiple Output	Single-user MIMO (SU-MIMO) involves a single multi-antenna-equipped user or terminal communicating with precisely one other similarly equipped node.	Wikipedia
super uplink	SUL	N/A	Super uplink enables the use of a supplementary uplink (SUL) for an NR TDD cell. Given the unchanged downlink bandwidth, data is transmitted over the original uplink for NR TDD (referred to as normal uplink, NUL for short) and SUL through time division multiplexing (TDM).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Secure User Plane Location	SUPL	N/A	The SUPL (Secure User Plane Location) protocol, unlike its control-plane equivalents restricted to mobile networks, runs on the Internet's TCP/IP infrastructure. As a result, its application goes beyond the original intended use of mobile devices and may be used by general-purpose computers. SUPL 3.0 legitimizes such use by adding allowance for WLAN and broadband connections	Wikipedia
schedule variance	SV	N/A	N/A	Huawei Term
software version number	SVN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
status word	SW	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
status word 1/ status word 2	SW1/SW2	Status Word 1 / Status Word 2	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
software radio	SWR	N/A	The software radio (SWR) is an open, standardized, and modular universal hardware platform. It uses software to define various radio parameters, such as the operating frequency band, modulation/demodulation scheme, data format, encryption mode, and communication protocol.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
synchroni- zation	SYN	N/A	Synchronization is the coordination of events to operate a system in unison. For example, the conductor of an orchestra keeps the orchestra synchronized in time. Systems that operate with all parts in synchrony are said to be synchronous or in sync—and those that are not are asynchronous. Today, time synchronization can occur between systems around the world through satellite navigation signals and other time and frequency transfer techniques.	Wikipedia
S frame	N/A	N/A	RLP frame that contains supervisory information in the absence of user information.	3GPP TS 24.022: "Radio Link Protocol (RLP) for circuit switched bearer and teleservices"

Term	Abbreviation	Synonym	Definition	Reference
S1 interface	N/A	S1	The interface between an eNodeB and an EPC.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
S1-MME connection	N/A	N/A	A connection that is established between an MME and an eNodeB and not dedicated to a specific UE.	Huawei Term
S1-U interface	N/A	N/A	S-GW supports the S1-U interface with eNodeB and S5/S8 data plane interface with P-GW.	Wikipedia
satellite transmission	N/A	N/A	Transmission via an earth orbiting satellite.	ETSI EN 300 247: "Access and Terminals (AT); 2 048 kbit/s digital unstructured leased line (D2048U); Connection characteristics"

Term	Abbreviation	Synonym	Definition	Reference
SCG bearer	N/A	N/A	In dual connectivity, a bearer whose radio protocols are only located in the SeNB to use SeNB resources.	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
scheduling	N/A	N/A	The method of controlling the timing of the execution of a scheduled activity within or represented by a managed object.	ITU-T X.746: "Information technology – Open Systems Interconnection – Systems management: Scheduling function"
scrambling	N/A	N/A	Scrambling is a process in which the base station uses scrambling code sequences to randomize codewords in order to suppress inter-cell and inter-UE interference.	Huawei Term
script file	N/A	N/A	The script file is a text file that records a batch of MML commands for one NE or multiple NEs of the same type. You need to create a script file before using a script command function.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
SCTP dual-homing	N/A	N/A	A networking of 3GPP R4 or later in which one MGW belongs to two MSC servers.	Huawei Term
secondary subrack	N/A	N/A	When subracks are connected in a star topology, the subrack connected to the primary subrack is called a secondary subrack.	Huawei Term
sector	N/A	N/A	Sector is a physical concept that refers to the geographical area covered by the antenna of a base station.	Huawei Term
self-configuration	N/A	N/A	Automatic configuration during self-setup or running of NEs	Huawei Term
self-maintenance	N/A	N/A	Detection of network problems by checking alarms and performance events and elimination of some or all problems based on the detection and location results	Huawei Term
self-optimization	N/A	N/A	Adaptive optimization of network parameters based on the network running status	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
self-planning	N/A	N/A	Dynamic and automatic planning of radio network parameters	Huawei Term
sensor	N/A	N/A	A sensor is a device, module, machine, or subsystem whose purpose is to detect events or changes in its environment and send the information to other electronics, frequently a computer processor. A sensor is always used with other electronics.	Wikipedia
separate-MPT	N/A	N/A	Separate-MPT means that multiple RATs (including GSM, UMTS, LTE, and NR) are deployed on different main control boards and each RAT corresponds to one main control board. The resource configuration and O&M of different RATs are independent and correspond to different logical base stations.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
separate-MPT base station	N/A	N/A	In a separate-MPT multimode base station, RATs are deployed on different main control boards and services of each RAT are deployed on its own BTS node.	Huawei Term
session	N/A	N/A	Set of inter-related exchange of packets occupying one or several windows or part thereof (if applicable). It corresponds to a complete interactive procedure for interchanging data between users, comprising initiation, data transmission and termination procedures. The session can be short (e.g. 2 packets), or long (e.g. one full page of text).	ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and speech) and having an antenna connector; Part 1: Technical characteristics and methods of measurement "

Term	Abbreviation	Synonym	Definition	Reference
session key	N/A	N/A	A key which is used only for a single session; a session may be a single connection or call, or it may be a number of calls made by a particular user through a particular system (e.g. the calls made by a roaming portable with a particular visited network).	ETSI EG 201 027: "Business TeleCommunications (BTC); Cordless Terminal Mobility (CTM); Interworking between private and public networks; General principles"
signalling	N/A	N/A	The exchange of information (other than by speech) specifically concerned with the establishment, release and other control of calls, and network management, in automatic telecommunications operation.	ITU-T Q.9: "Vocabulary of Switching and Signalling Terms"
signalling link	N/A	N/A	A transmission means which consists of a signalling data link and its transfer control functions, used for reliable transfer of signalling messages.	ITU-T Q.9: "Vocabulary of Switching and Signalling Terms"

Term	Abbreviation	Synonym	Definition	Reference
signalling network	N/A	N/A	A network used for transfer of signalling messages and consisting of signalling points and connecting common channel signalling links.	ITU-T Q.9: "VOCABULARY OF SWITCHING AND SIGNALLING TERMS"
signal fading	N/A	N/A	In wireless communications, fading is variation of the attenuation of a signal with various variables.	Wikipedia
single-hop/ multi-hop	N/A	N/A	A hop in an IP network refers to every step that a packet makes in route forwarding to arrive at its destination. Single-hop means that a packet arrives at its destination after only one hop. Multi-hop means that a packet arrives at its destination after several hops.	Huawei Term
site	N/A	N/A	A group of servers at the same physical location.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
sliding window	N/A	N/A	DLL confirmed data transmission flow control procedure that requires the target to store multiple data packets and provide a confirmed response on all the stored data upon request from the source.	ETSI TS 102 361-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Digital Mobile Radio (DMR) Systems; Part 3: DMR Data protocol"
slow fading	N/A	- large-scale fading - long-term fading	Slow fading arises when the coherence time of the channel is large relative to the delay requirement of the application.	Wikipedia
slow start	N/A	N/A	Slow start is part of the congestion control strategy used by TCP in conjunction with other algorithms to avoid sending more data than the network is capable of forwarding, that is, to avoid causing network congestion. The algorithm is specified by RFC 5681.	Wikipedia
softer handover	N/A	N/A	A special form of soft handover. It occurs between intra-frequency cells served by the same base station.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
solution	N/A	N/A	A solution refers to a certain type of features applied in the same domain.	Huawei Term
source routing	N/A	path addressing	Source routing is one of the three basic forms of algorithm for dynamic path control. Its connection control process is implemented by a federation of distributed connection and routing controllers. The significant difference is that connection controllers invoke a different sequence of path computation functions between routing levels for hierarchical versus source routing. In order to reduce the amount of network topology each controller needs to share, only that portion of the topology that applies to its own routing area is made available. See [ITU-T G.8080].	ITU-T G.8081/Y.1353: "Terms and definitions for automatically switched optical networks"

Term	Abbreviation	Synonym	Definition	Reference
space-selective fading	N/A	N/A	As the angle of arrival of a receive antenna is spread due to signal reflection, diffraction, and scattering, the angle spread causes different fading characteristics of signals at different spacial locations. This phenomenon is space-selective fading.	Huawei Term
spatial multiplexing	N/A	N/A	Spatial multiplexing uses the multi-antenna technology at the receive and transmit ends and fully utilizes multipath components in spatial propagation to transmit multiple independent data streams on the same frequency band, enabling the capacity to increase with the number of antennas.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
spectral efficiency	N/A	spectrum efficiency	Spectral efficiency, spectrum efficiency or bandwidth efficiency refers to the information rate that can be transmitted over a given bandwidth in a specific communication system. It is a measure of how efficiently a limited frequency spectrum is utilized by the physical layer protocol, and sometimes by the medium access control.	Wikipedia
spectrum reallocation	N/A	N/A	Reallocation of government-regulated electromagnetic spectrum for services with higher value (for example, the reallocation of spectrum originally for GSM to LTE with higher capacity).	Huawei Term
speech intelligibility	N/A	N/A	Measure of how comprehensible speech is in given conditions.	ETSI TR 103 225: "Speech and multimedia Transmission Quality (STQ); Transmission quality and speech intelligibility for hearing impaired people"

Term	Abbreviation	Synonym	Definition	Reference
speech version	N/A	N/A	The versions of the speech coding/decoding algorithms in the GSM communications system, which are categorized into full-rate speech versions 1, 2, and 3, and half-rate speech versions 1, 2, and 3.	Huawei Term
split bearer	N/A	N/A	In dual connectivity, a bearer whose radio protocols are located in both the MeNB and the SeNB to use both MeNB and SeNB resources.	3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2"
standing wave	N/A	N/A	A wave resulting from the superposition of two traveling waves of the same frequency and same amplitude propagating in opposite directions in the same media	IEV 705-01-40

Term	Abbreviation	Synonym	Definition	Reference
star network	N/A	star topology	A star network is an implementation of a spoke-hub distribution paradigm in computer networks. In a star network, every host is connected to a central hub. In its simplest form, one central hub acts as a conduit to transmit messages. The star network is one of the most common computer network topologies.	Wikipedia
static routing	N/A	N/A	Static routing is a form of routing that occurs when a router uses a manually-configured routing entry, rather than information from dynamic routing traffic.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
statistical multiplexing	N/A	N/A	Statistical multiplexing is a type of communication link sharing, very similar to dynamic bandwidth allocation (DBA). In statistical multiplexing, a communication channel is divided into an arbitrary number of variable bitrate digital channels or data streams. The link sharing is adapted to the instantaneous traffic demands of the data streams that are transferred over each channel. This is an alternative to creating a fixed sharing of a link, such as in general time division multiplexing (TDM) and frequency division multiplexing (FDM). When performed correctly, statistical multiplexing can provide a link utilization improvement, called the statistical multiplexing gain.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
streaming media	N/A	N/A	Streaming media is, for instance, video on demand or audio live streaming.	H. Schulzrinne, A. Rao, Cisco, R. Lanphier, M. Westerlund, Ericsson, M. Stiemerling, Ed., and University of Applied Sciences Darmstadt, "Real-Time Streaming Protocol Version 2.0", RFC 7826, December 2016
stream	N/A	layer	Number of parallel data streams after serial-to-parallel conversion is complete during layer mapping.	Huawei Term
string	N/A	N/A	Sequence of data elements of the same nature, such as characters or binary digits, treated as a whole.	IEV 171-02-26
subframe	N/A	N/A	Subframe is a time unit in a 3G/4G/5G system. The length of a subframe is 2 ms in UMTS and 1 ms in LTE and NR.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
subnet	N/A	N/A	Logical group of connected network nodes. In IP networks, nodes in a subnet share a common network mask (in IPV4) or a network prefix (in IPv6).	ETSI GS NGP 001: "Next Generation Protocols (NGP); Scenarios Definitions"
subnet mask	N/A	address mask	A bit mask used to identify which bits in an IP address correspond to the network and subnet portions of the address. This mask is often referred to as the subnet mask because the network portion of the address (i.e., the network mask) can be determined by the encoding inherent in an IP address.	G. Malkin, "Internet Users' Glossary", RFC1983, August 1996
subrack	N/A	chassis	Structural unit for housing printed boards with components inserted, and plug-in units.	IEV 581-25-01
switching mode	N/A	N/A	The 1+1 protect mode is classified into unidirectional mode and 1+1 bidirectional mode.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
symbol	N/A	N/A	A symbol is a state or significant condition of the communication channel that persists for a fixed period of time. A sending device places symbols on the channel at a fixed and known symbol rate, and the receiving device has the job of detecting the sequence of symbols in order to reconstruct the transmitted data.	Wikipedia
synchronization raster	N/A	N/A	The synchronization raster indicates the frequency positions of the synchronization block that can be used by the UE for system acquisition when explicit signalling of the synchronization block position is not present.	3GPP TS 38.104: "NR; Base Station (BS) radio transmission and reception"
system data backup	N/A	N/A	Backup of the operating system of the server, which is used to restore the original operating system.	Huawei Term

1.21 T

Term	Abbreviation	Synonym	Definition	Reference
Transmission System 1	T1	N/A	The T-carrier is a member of the series of carrier systems developed by AT&T Bell Laboratories for digital transmission of multiplexed telephone calls. The first version, the Transmission System 1 (T1), was introduced in 1962 in the Bell System, and could transmit up to 24 telephone calls simultaneously over a single transmission line of copper wire. Subsequent specifications carried multiples of the basic T1 (1.544 Mbit/s) data rates, such as T2 (6.312 Mbit/s) with 96 channels, T3 (44.736 Mbit/s) with 672 channels, and others.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
terminal adapter	TA	N/A	An equipment intended to match a non-ISDN terminal to an ISDN network termination	IEC-International Electrotechnical Vocabulary-Electropedias: 716 Integrated services digital network (ISDN) - Part 1: General aspects
tracking area	TA	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
timing advance	TA*	N/A	Signal sent by the BTS to the MS which the MS uses to advance its timings of transmissions to the BTS so as to compensate for propagation delay.	3GPP TS 05.10: "Radio subsystem synchronization"
tracking area code	TAC	N/A	N/A	3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3"

Term	Abbreviation	Synonym	Definition	Reference
type allocation code	TAC	N/A	The Type Allocation Code (TAC) is the initial eight-digit portion of the 15-digit IMEI and 16-digit MEISV codes used to uniquely identify wireless devices. The Type Allocation Code identifies a particular model (and often revision) of wireless telephone for use on a GSM, UMTS or other IMEI-employing wireless network.	Wikipedia
tracking area identity	TAI	N/A	N/A	3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3"
tracking area list	TAL	TA list	List of multiple tracking areas (TAs)	Huawei Term
tracking area update	TAU	N/A	N/A	3GPP TS 33.401: "3GPP System Architecture Evolution (SAE); Security architecture"

Term	Abbreviation	Synonym	Definition	Reference
transport block	TB	N/A	The basic data unit exchanged between L1 and MAC. An equivalent term MAC PDU.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
token bucket	TB	Generic Byte Rate Algorithm	The Generic Byte Rate Algorithm (GBRA) or token bucket (TB) is used to characterize a rate and the associated burstiness. Both concepts are equivalent and use the following set of two parameters: – the rate R expressed in byte/s; – the bucket size B expressed in byte.	ITU-T Y.1221: "Traffic control and congestion control in IP based networks"

Term	Abbreviation	Synonym	Definition	Reference
temporary block flow	TBF	N/A	A Temporary Block Flow is, in A/Gb mode, a physical connection used by the two RR peer entities to support the unidirectional transfer of LLC PDUs on packet data physical channels. In Iu mode, a TBF is a logical connection offered by two MAC entities to support the unidirectional transfer of RLC PDUs on basic physical subchannels.	3GPP TS 44.060: "General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol"
transport block size	TBS	N/A	N/A	3GPP TR 37.901: "User Equipment (UE) application layer data throughput performance"

Term	Abbreviation	Synonym	Definition	Reference
traffic classification	TC	N/A	Traffic classification is an automated process which categorizes computer network traffic according to various parameters (for example, port number or protocol) into a number of traffic classes. Each resulting traffic class can be treated differently to differentiate the service implied for the data generator or consumer.	Wikipedia
transparent clock	TC	N/A	Transparent clocks are devices (network elements) that modify the content of PTP packets, permitting the PTP "source" and PTP "destination" to factor out the delay introduced by the device. Strictly speaking a "transparent clock" is not a clock but a means for providing on-path support for packet-based timing based on PTP.	ITU-T G.8273/Y.1368: "Framework of phase and time clocks"

Term	Abbreviation	Synonym	Definition	Reference
transmission convergence	TC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
transcoder	TC	N/A	Device to change the encoding of information from one particular encoding scheme to a different one, most commonly to/from a compressed speech algorithm from/to PCM.	3GPP TS 23.153: "Out of band transcoder control; Stage 2"
traffic channel	TCH	N/A	A logical channel, which carries user information.	ITU-T Q.1741.9: "IMT-2000 references to Release 11 of GSM evolved UMTS core network"
full rate TCH	TCH/F	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
full rate speech TCH	TCH/FS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
half-rate traffic channel	TCH/H	TCHH	A GSM half rate channel uses 12 frames out of a 26-multiframe. The channel bit rate of a half-rate GSM channel is 11.4 kbit/s, although the actual data capacity is 4.8-7 kbit/s, depending on the channel coding. This channel is normally used with the GSM 06.20 Half Rate or GSM 06.90 Adaptive Multi-Rate speech codec.	Wikipedia
half rate speech TCH	TCH/HS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
transceiver control interface	TCI	N/A	N/A	Huawei Term
total cost of ownership	TCO	N/A	Total cost of ownership (TCO) is a financial estimate intended to help buyers and owners determine the direct and indirect costs of a product or service.	Wikipedia
Transmission Control Protocol	TCP	N/A	Protocol for connection-oriented transmission that corresponds approximately to a protocol within the transport layer of the OSI reference model.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Transmission Control Protocol/Internet Protocol	TCP/IP	N/A	The protocol suite used on Internet.	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements"
transcoder rack	TCR	N/A	A TCR (only for the BSC6900 GSM and the BSC6900 GU) contains one to three TC subracks. Up to two TCRs can be configured in BM/TC separated mode.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Temporary C-RNTI	TC-RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"
terminal customer service system	TCS	N/A	N/A	Huawei Term
transcoder subrack	TCS	N/A	N/A	Huawei Term
target channel type field	TCTF	N/A	N/A	Huawei Term
Technical Committee Technical Report	TC-TR	Technical Committee-Technical Report	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
temperature control unit	TCU	N/A	N/A	Huawei Term
time division-code division multiple access	TD-CDMA	time division code division multiple access	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
time division duplex	TDD	time-division duplexing	Time-division duplexing (TDD) is the application of time-division multiplexing to separate outward and return signals. It emulates full-duplex communication over a half-duplex communication link.	Wikipedia
LTE TDD LTE-A optional feature description	TDLAOFD	N/A	N/A	Huawei Term
LTE TDD basic feature description	TDLBFD	N/A	N/A	Huawei Term
LTE TDD CloudAIR optional feature description	TDLCOFD	N/A	N/A	Huawei Term
LTE TDD 4.5G optional feature description	TDLEOFD	N/A	N/A	Huawei Term
LTE TDD evolution optional feature description	TDLNOFD	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
LTE TDD optional feature description	TDLOFD	N/A	N/A	Huawei Term
time division multiplexing	TDM	N/A	Multiplexing in which several independent signals are allotted separate periodic time intervals for transmission over a common transmission channel.	3GPP TS 25.142: "Base Station (BS) conformance testing (TDD)"
time division multiple access	TDMA	N/A	A multiple access technique in which the various terminals having access to a link are allotted separate recurrent time intervals for transmission.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
time difference of arrival	TDOA	N/A	Time difference of arrival (TDOA) is the difference between TOAs. Time of arrival (TOA or ToA) is the absolute time instant when a radio signal emanating from a transmitter reaches a remote receiver.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
temporary document	TDoc	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Time Division-Synchronous Code Division Multiple Access	TD-SCDMA	N/A	Time-Division Synchronous Code-Division Multiple Access (TD-SCDMA) or UTRA TDD 1.28 Mcps low chip rate (UTRA-TDD LCR) is an air interface found in UMTS mobile telecommunications networks in China as an alternative to W-CDMA. TD-SCDMA uses the TDMA channel access method combined with an adaptive synchronous CDMA component on 1.6 MHz slices of spectrum, allowing deployment in even tighter frequency bands than TD-CDMA. It is standardized by the 3GPP and also referred to as "UTRA-TDD LCR".	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
terminal equipment 9	TE9	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
total E-DCH buffer status	TEBS	N/A	N/A	Huawei Term
total electron content	TEC	N/A	Total electron content (TEC) is an important descriptive quantity for the ionosphere of the Earth. TEC is the total number of electrons integrated between two points, along a tube of one meter squared cross section, i.e., the electron columnar number density.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
traffic engineering database	TEDB	N/A	A type of database generated by every router after a route has collected TE information about all links between all routers in the area. TEDB is used to calculate optimal routes and form the dynamic TE paths on MPLS TE networks.	Huawei Term
terminal equipment identifier	TEI	N/A	N/A	ETSI TR 101 973-3: "Access and Terminals (AT); Public Switched Telephone Network; Support of legacy terminals by BroadBand IP equipment; Listing of the most relevant features and functionalities ; Part 3: ISDN terminals"
tunnel endpoint identifier	TEID	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
transport format	TF	N/A	A transport format is defined as a format offered by L1 to MAC for the delivery of a Transport Block Set during a Transmission Time Interval on a Transport Channel. The Transport Format constitutes of two parts – one dynamic part and one semi-static part.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
transport format combination	TFC	N/A	A combination of currently valid transport formats on all transport channels of a UE. That is, the combination contains one transport format from each transport channel.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
transport format combination indicator	TFCI	N/A	Transport format combination indicator (TFCI): layer one header that indicates the transport channel combination that has been selected for each radio packet	3GPP TS 44.118: "3rd Generation Partnership Project; Technical Specification Group GSM/EDGE Radio Access Network; Mobile radio interface layer 3 specification; Radio Resource Control (RRC) protocol; Iu Mode (Release 6)"
transport format combination set	TFCS	N/A	Transport format combination set (TFCS): set of allowed transport format combinations on a basic physical subchannel	3GPP TS 44.118: "3rd Generation Partnership Project; Technical Specification Group GSM/EDGE Radio Access Network; Mobile radio interface layer 3 specification; Radio Resource Control (RRC) protocol; Iu Mode (Release 6)"

Term	Abbreviation	Synonym	Definition	Reference
transport format indicator	TFI	TFIN	Index identifying a particular transport format within the transport format set.	3GPP TR 45.902: "Technical Specification Group Radio Access Network; GSM/EDGE Flexible Layer One (FLO)"
Tandem Free Operation	TFO	N/A	Configuration of a connection with two transcoders that support TFO protocol and whose external coding schemes are compatible, thus enabling compressed speech to pass between them.	3GPP TS 23.153: "Out of band transcoder control; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
transfer prohibited	TFP	N/A	The transfer-prohibited procedure is performed at a signalling point acting as a signalling transfer point for messages relating to a given destination, when it has to notify one or more adjacent signalling points that they must no longer route the concerned messages via that signalling transfer point. Transfer-prohibited messages are always addressed to an adjacent signalling point. They may use any available signalling route that leads to that signalling point.	ITU-T Q.704: "Signalling network functions and messages"
transport format resource combination	TFRC	N/A	N/A	3GPP TS 25.308: "Technical Specification Group Radio Access Network; UTRA High Speed Downlink Packet Access; Overall Description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
transport format set	TFS	N/A	A set of Transport Formats. For example, a variable rate DCH has a Transport Format Set (one Transport Format for each rate), whereas a fixed rate DCH has a single Transport Format.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
traffic flow template	TFT	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
traffic handling priority	THP	N/A	N/A	Huawei Term
Transport Layer Security	TLS	N/A	The TLS protocol provides communications privacy over the Internet. The protocol allows client/server applications to communicate in a way that is designed to prevent eavesdropping, tampering, or message forgery.	T. Dierks, Certicom, C. Allen, and Certicom, "The TLS Protocol Version 1.0", RFC 2246, January 1999

Term	Abbreviation	Synonym	Definition	Reference
Type, Length, Value	TLV	- Type-Length-Value - Type/Length/Value	N/A	Huawei Term
transmission mode	TM	N/A	A transmission mode is a specific set of transmission parameters (e.g. number of carriers, OFDM symbol duration). Transmission modes are defined to allow the system to be used for different network configurations and a range of operating frequencies.	ETSI TR 101 496-1: "Digital Audio Broadcasting (DAB); Guidelines and rules for implementation and operation; Part 1: System outline"
telecom management	TM	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
terminal multiplexer	TM	N/A	A TM is a device used at a network terminal either to multiplex multiple channels of low rate signals into one channel of high rate signals, or to demultiplex one channel of high rate signals into multiple channels of low rate signals.	Wikipedia
transparent mode	TM	N/A	RLC provides three different reliability modes for data transport - Acknowledged Mode (AM), Unacknowledged Mode (UM), or Transparent Mode (TM). The TM mode is used when the PDU sizes are known a priori such as for broadcasting system information.	ETSI TR 102 662: "Satellite Earth Stations and Systems (SES); Advanced satellite based scenarios and architectures for beyond 3G systems"
tower-mounted amplifier	TMA	N/A	A TMA comprises a low noise amplifier together with its control and monitoring electronics and optional antenna modem.	3GPP TS 25.466: "UTRAN luant interface: Application part"
transmission cabinet	TMC	N/A	N/A	Huawei Term
telecom management forum	TMF	telecommunication management forum	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
telecommunications management network	TMN	N/A	A TMN provides management functions for telecommunication networks and services, and offers communications between itself and managed telecommunication networks or services and other TMNs.	ITU-T M.3010: "Principles for a telecommunications management network"
temporary mobile subscriber identity	TMSI	temporary mobile station identity	The temporary mobile subscriber identity (TMSI) is the identity that is most commonly sent between the mobile and the network. TMSI is randomly assigned by the VLR to every mobile in the area, the moment it is switched on. The number is local to a location area, and so it has to be updated each time the mobile moves to a new geographical area.	Wikipedia
termination node	TN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
timeslot number	TN	N/A	Timing of timeslots within a TDMA frame	ETSI TS 100 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)"
Transport Network Layer	TNL	N/A	A layer, or transport network layer, is defined as ITU-T Recommendation G.805 a topological component solely concerned with the generation and transfer of characteristic information	ETSI I-ETS 300 653: "Telecommunications Management Network (TMN); Generic managed object class library for the network level view"
Transport Network Layer Association	TNLA	N/A	N/A	3GPP TS 23.501: "System architecture for the 5G System (5GS)"
time of arrival	TOA	ToA	Time of arrival (TOA or ToA) is the travel time of a radio signal from a single transmitter to a remote single receiver.	Wikipedia
Business to Business	ToB	N/A	NA	Huawei Term
Business to Consumer	ToC	N/A	NA	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
time of day	ToD	N/A	N/A	3GPP TS 25.172: "Requirements for support of Assisted Galileo and Additional Navigation Satellite Systems (A-GANSS) Frequency Division Duplex (FDD)"
type of service	ToS	N/A	The type of service is used to indicate the quality of the service desired. The type of service is an abstract or generalized set of parameters which characterize the service choices provided in the networks that make up the internet. This type of service indication is to be used by gateways to select the actual transmission parameters for a particular network, the network to be used for the next hop, or the next gateway when routing an internet datagram.	"INTERNET PROTOCOL DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION", RFC 791, September 1981

Term	Abbreviation	Synonym	Definition	Reference
time of week	TOW	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
transmit power control	TPC	N/A	Transmit power control is a technical mechanism used within some networking devices in order to prevent too much unwanted interference between different wireless networks (e.g. the owner's network and the neighbour's network). It is also essential component in case of cognitive radio networks deployed in a distributed fashion, aka distributed power control.	Wikipedia
Transmission Power Control RNTI	TPC RNTI	N/A	N/A	3GPP TS 38.321: "Medium Access Control (MAC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
transport protocol data unit	TPDU	N/A	It is used in the Short Messages Service.	ETSI ETS 300 901: "Digital cellular telecommunications system (Phase 2+); Technical realization of the Short Message Service (SMS); Point-to-Point (PP)"

Term	Abbreviation	Synonym	Definition	Reference
TCP Performance Enhancer	TPE	N/A	The original TCP mechanism cannot well adapt to the wireless network's characteristics such as high bit error rate and long delay, which leads to unsatisfactory transmission performance. To improve the transmission performance, the TCP Performance Enhancer (TPE) is introduced. The TPE is also known as TCP accelerator. The TPE is a functional entity in the RNC and works independently of other network elements (NEs). It works as a proxy between the sender and the receiver. It buffers and processes data to accelerate data transmission and to improve transmission performance.	Huawei Term
transmitted precoding matrix indicator	TPMI	N/A	N/A	3GPP TS 38.214: "Technical Specification Group Radio Access Network; Physical layer procedures for data"

Term	Abbreviation	Synonym	Definition	Reference
tributary protection switching	TPS	N/A	A function that uses a standby tributary processing board to protect multiple (N) tributary processing boards	Huawei Term
transaction reliability	TR	N/A	The probability that the transaction can be completed without failure from initiation at node S1, to local access to the data at node S2, and back to node S1 with the result.	Huawei Term
Things-Radio Access Network	T-RAN	N/A	A new type of radio access network architecture proposed in 3GPP Release 13. T-RAN is characterized by large capacity, small bandwidth, low terminal power consumption, and other features. T-RAN consists of multiple NBBSS and provides user plane (PHY/MAC) and control plane (RRC) protocols that are terminated at terminals.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
transcode r and rate adaptatio n unit	TRAU	N/A	Transcoder and rate adaptation unit, or TRAU, performs transcoding function for speech channels and RA (rate adaptation) for data channels in the GSM network.	Wikipedia
traffic radio bearer	TRB	N/A	A traffic radio bearer is a logical connection provided by the protocol layer immediately below the PDP layer for transporting user packets between a mobile and an RNC (or a BSC).	Huawei Term
transport channel	TrCH	N/A	The channels offered by the physical layer to Layer 2 for data transport between peer L1 entities are denoted as Transport Channels. Different types of transport channels are defined by how and with which characteristics data is transferred on the physical layer, e.g. whether using dedicated or common physical channels.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Transcoder Free Operation	TrFO	N/A	Configuration of a speech or multimedia call for which no transcoder device is physically present in the communication path and hence no control or conversion or other functions can be associated with it.	3GPP TS 23.153: "Technical Specification Group Core Network; Out of band transcoder control; Stage 2"
transmission resource management	TRM	N/A	Management of transmission resources, including configuration, discovery, allocation, reuse, and check of transmission resources, and detection and control of resource congestion.	Huawei Term
target radio network controller	TRNC	target RNC	Target RNC is the RNC belonging to target RNS.	3GPP TS 25.413: "UTRAN Iu interface Radio Access Network Application Part (RANAP) signalling"
transmission reception point	TRP	N/A	Antenna array with one or more antenna elements available to the network located at a specific geographical location for a specific area.	3GPP TR 38.913: "Study on Scenarios and Requirements for Next Generation Access Technologies"

Term	Abbreviation	Synonym	Definition	Reference
tracking reference signal	TRS	N/A	N/A	3GPP TS 38.214: "NR; Physical layer procedures for data"
transmit receive unit	TRU	N/A	N/A	Huawei Term
transceiver	TRX	N/A	In radio communication, a transceiver is an electronic device which is a combination of a radio transmitter and a receiver, hence the name. It can both transmit and receive radio waves using an antenna, for communication purposes. These two related functions are often combined in a single device to reduce manufacturing costs.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
transmit and receive channel	TRX	TX/RX channel	Transmit and receive channels (TX/RX channels), also called TRXs, process RF signals in the communications system. At the TX end, baseband signals are modulated on high-frequency carriers and then sent to the radio propagation environment. At the RX end, a reverse process is performed. A TRX consists of digital and analog RF chains.	Huawei Term
technical specification	TS	N/A	A specification contained in a document that lays down the characteristics required of a product, such as levels of quality, performance, safety or dimensions, and including the requirements applicable to the product as regards terminology, symbols, testing and test methods, packaging, marking or labelling.	ETSI ETR 238: "CENELEC/ETSI Standardization Programme for the Development of Harmonized Standards Related to Electro-Magnetic Compatibility (EMC) in the Field of Telecommunications"

Term	Abbreviation	Synonym	Definition	Reference
training sequence code	TSC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
transceiver speech & data interface	TSDI	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Technical Specification Group	TSG	N/A	The Technical Specification Groups (TSGs) prepare, approve and maintain the 3GPP Technical Specifications and Technical Reports.	ETSI TR 101 374-2: "Satellite Earth Stations and Systems (SES); Broadband satellite multimedia; Part 2: Scenario for standardization"

Term	Abbreviation	Synonym	Definition	Reference
transport signaling gateway	T-SGW	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
transmission sequence number	TSN	N/A	It is short for transmission sequence number. The SCTP uses a TSN mechanism to acknowledge data transmission. An endpoint of an association assigns a 32-bit sequence number, which is based on an initial TSN, to each data chunk sent by the local end to permit the receiving SCTP endpoint to acknowledge its receipt.	Huawei Term
time switched transmit diversity	TSTD	N/A	A technique that utilizes multiple transmit stations to originate the downlink signal and improve performance. The transmit station used is determined by a fixed selection pattern similar to frequency hopping.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Tree and Tabular Combined Notation	TTCN	Tree & Tabular Combined Notation	ISO/IEC 9646 provides a formal syntax to describe test-suites for communication equipment. This syntax is called the Tree and Tabular Combined Notation (TTCN). The use of TTCN is recommended by ISO/IEC 9646 but not mandated. TTCN is a powerful semi-formal language defined to facilitate computerized test tools for any kind of communication equipment. However, TTCN is, due to its abstractness, not so human friendly as plain text. In order to keep the test cases readable to a maximum extent while making them as formal as necessary, it has been decided to use a simpler formal notation in the description of the test cases.	ETSI EN 302 842-2: "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 2: General description and data link layer"

Term	Abbreviation	Synonym	Definition	Reference
transmission time interval	TTI	N/A	Transmission time interval is defined as the inter-arrival time of transport block sets, i.e. the time it shall take to transmit a transport block set.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "
time to live	TTL	N/A	N/A	3GPP TS 29.333: "Multimedia Resource Function Controller (MRFC) - Multimedia Resource Function Processor (MRFP) Mp interface; Stage 3"
tributary unit	TU	N/A	A tributary unit is an information structure that provides adaptation between the lower-order path layer and the higher-order path layer. It consists of an information payload (the lower-order virtual container) and a tributary unit pointer that indicates the offset of the payload frame start relative to the higher-order virtual container frame start.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "

Term	Abbreviation	Synonym	Definition	Reference
tributary unit group	TUG	N/A	One or more tributary units, occupying fixed, defined positions in a higher-order VC-n payload, is termed a tributary unit group (TUG). TUGs are defined in such a way that mixed capacity payloads made up of different size tributary units can be constructed to increase flexibility of the transport network. A TUG-2 consists of a homogeneous assembly of identical TU-11s, TU-12s or a TU-2. A TUG-3 consists of a homogeneous assembly of TUG-2s or a TU-3.	ITU-T G.780: "Terms and definitions for synchronous digital hierarchy (SDH) networks "
traffic volume measurement	TVM	N/A	N/A	Huawei Term
transmission	TX	N/A	TX stands for transmit and refers to the sending of data.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
tail drop	N/A	N/A	Tail drop is a simple queue management algorithm used by network schedulers in network equipment to decide when to drop packets. With tail drop, when the queue is filled to its maximum capacity, the newly arriving packets are dropped until the queue has enough room to accept incoming traffic.	Wikipedia
target RNS	N/A	N/A	Role an RNS gets with respect to a specific connection between UTRAN and CN when it is being a subject of a relocation of SRNS which is being made towards that RNS.	3GPP TS 25.413: "UTRAN Iu interface Radio Access Network Application Part (RANAP) signalling"
terminal	N/A	N/A	A device into which a UICC can be inserted or embedded and which is capable of providing access to 3GPP System services to users, either alone or in conjunction with a UICC.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
throughput	N/A	N/A	The number of data bits contained in a block (e.g. between the address field and the CRC field of the LAPD-based frames) which are successfully transferred per unit time in one direction across a section.	ITU-T I.113: "Vocabulary of terms for broadband aspects of ISDN"
tight BCCH	N/A	N/A	In tight BCCH frequency reuse mode, the TCHs on the BCCH frequency are assigned to the MSs near the BTS. This decreases the requirements for the BCCH frequency reuse intensity and improves the frequency utilization.	Huawei Term
tilt	N/A	• downtilt • tilt angle • beamtilt	The angle between the direction with maximum radiation and the horizon. The smaller the width of the lobe on the vertical plane, the faster attenuation of signals that deviate from the main beam. In this situation, it will be easier to control the coverage by adjusting the downtilt.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
timer	N/A	N/A	A timer is an item owned by an agent that causes a timer signal stimulus to occur at a specified time.	ITU-T Z.100: "Specification and Description Language – Overview of SDL-2010"
time-selective fading	N/A	N/A	When there is relative movement between a UE and a base station, Doppler effect occurs in the frequency domain. The signal spectrum of received signals is broadened, causing Doppler spread. As a result, the fading characteristics of signals vary with time, which is called time-selective fading.	Huawei Term
timeslot	N/A	slot	A timeslot shall have a duration of 3/5200 seconds ($\approx 577 \mu\text{s}$). Eight timeslots shall form a TDMA frame ($\approx 4,62 \text{ ms}$ in duration).	GSM 05.02: "Multiplexing and multiple access on the radio path"

Term	Abbreviation	Synonym	Definition	Reference
timeslot cross	N/A	N/A	A function that enables crossing of E1/T1 timeslots on the physical medium sublayer of the physical layer so as to provide an exchange path between transport devices. For example, timeslots 2, 3, 4, and 5 can be crossed to timeslots 12, 13, 14, and 15 through an interface board.	Huawei Term
timeslot demultiplex	N/A	N/A	A process for separating signals that have been combined so that they can be transmitted over a communications channel as a single signal	Huawei Term
timeslot interval	N/A	N/A	Hardware interruption every 577 μ s.	Huawei Term
timeslot multiplex	N/A	timeslot multiplexing	A process for combining signals from several separate slots for transmission in the same direction over a common bearer channel	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
time synchronization	N/A	moment synchronization	Time synchronization, also known as moment synchronization, refers to the synchronization of absolute time, which requires that the start time of signals must be consistent with the universal time coordinated (UTC).	Huawei Term
topology	N/A	N/A	Physical arrangement of network nodes and media within a networking structure.	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
topology view	N/A	N/A	A basic component for the man-machine interface. The topology view directly displays the networking of a network as well as the alarm and communication status of each network element and subnet. The topology view reflects the basic running conditions of the network.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
traffic shaping	N/A	N/A	Traffic shaping is a bandwidth management technique used on computer networks which delays some or all datagrams to bring them into compliance with a desired traffic profile. Traffic shaping is used to optimize or guarantee performance, improve latency, or increase usable bandwidth for some kinds of packets by delaying other kinds. It is often confused with traffic policing, the distinct but related practice of packet dropping and packet marking. The most common type of traffic shaping is application-based traffic shaping. In application-based traffic shaping, fingerprinting tools are first used to identify applications of interest, which are then subject to shaping policies. Some controversial cases of application-based traffic shaping include	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			bandwidth throttling of peer-to-peer file sharing traffic. Many application protocols use encryption to circumvent application-based traffic shaping. Another type of traffic shaping is route-based traffic shaping. Route-based traffic shaping is conducted based on previous-hop or next-hop information.	
traffic volume	N/A	N/A	Used to indicate the load of telecom devices and the communication requirements of users.	Huawei Term
transmission delay	N/A	N/A	The sum of the times necessary for an octet to pass in both directions on a connection through a digital exchange due to buffering, frame alignment and time-slot interchange functions for digital-to-digital connections and in addition, for analogue-to-analogue connections, to the A/D conversions.	ITU-T Q.9: "VOCABULARY OF SWITCHING AND SIGNALLING TERMS"

Term	Abbreviation	Synonym	Definition	Reference
transport block set	N/A	N/A	A transport block set is a group of transport blocks exchanged between the physical layer and the MAC layer at the same time using the same transport channel.	• Huawei Term • 3GPP TS 38.214: "Physical layer procedures for data (Release 17)"
tributary loopback	N/A	N/A	A fault can be located for each service path by performing loopback to each path of the tributary board. There are three kinds of loopback modes: no loopback, outloop, and inloop.	Huawei Term
Triplet, GSM authentication vector	N/A	N/A	A temporary protocol data of authentication, which enables GSM AKA function for a particular user in a VLR/SGSN. A triplet consists of three elements: random number (RAND), signed response (SRES), and cipher key (CK).	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
trunk chain topology	N/A	N/A	In the trunk chain topology, radio multiplex units (RMUs) are deployed on the side of remote RF modules to converge data from RF modules, so that a small number of optical fibers are used for long-distance transmission.	Huawei Term
tunnel	N/A	N/A	It refers to an IPsec security association used in WLAN 3GPP IP access to protect the communications from the WLAN UE to the 3GPP network. It is preceded by an IKE negotiation.	3GPP TS 33.234: "3G security; Wireless Local Area Network (WLAN) interworking security"

1.22 U

Term	Abbreviation	Synonym	Definition	Reference
unified access control	UAC	N/A	N/A	3GPP TS 38.331: "Technical Specification Group Radio Access Network; NR; Radio Resource Control (RRC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
UTRA absolute radio frequency channel number	UARFCN	N/A	The carrier frequency is designated by the UTRA Absolute Radio Frequency Channel Number (UARFCN). The channel number is derived from the frequency through the formula Channel Number = Frequency x 5.	3GPP TS 25.104: "Technical Specification Group Radio Access Network; Base Station (BS) radio transmission and reception (FDD)"
UTRA absolute radio frequency number	UARFN	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
universal asynchronous receiver-transmitter	UART	N/A	A universal asynchronous receiver-transmitter is a computer hardware device for asynchronous serial communication in which the data format and transmission speeds are configurable. It sends data bits one by one, from the least significant to the most significant, framed by start and stop bits so that precise timing is handled by the communication channel. The electric signaling levels are handled by a driver circuit external to the UART. Two common signal levels are RS-232, a 12-volt system, and RS-485, a 5-volt system.	Wikipedia
unavailable second	UAS	N/A	TUG-2 consists of homogeneous components equivalent to TU-11, TU-12, or TU-2.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Unmanned Aircraft System	UAS	uncrewed aerial system	Systems encompassing Tethered UAS (TUA), Lighter Than Air UAS (LTA), Heavier Than Air UAS (HTA), all operating in altitudes typically between 8 and 50 km including High Altitude Platforms (HAPs)	3GPP TR 38.821: "Solutions for NR to support non-terrestrial networks (NTN)"
unavailable time event	UAT	unavailable time	An unavailable time event is reported when the monitored object generates 10 consecutive severely errored seconds.	Huawei Term
universal baseband processing unit	UBBP	N/A	N/A	Huawei Term
Universal BBU Fan Unit Type A	UBFA	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
unspecified bit rate	UBR	N/A	The UBR service category also is similar to nrt-VBR, because it is used for connections that transport variable bit rate traffic for which there is no reliance on time synchronization between the traffic source and destination. However, unlike ABR, there are no flow-control mechanisms to dynamically adjust the amount of bandwidth available to the user. UBR generally is used for applications that are very tolerant of delay and cell loss. UBR has enjoyed success in the Internet LAN and WAN environments for store-and-forward traffic, such as file-transfers and e-mail. Similar to the way in which upper-layer protocols react to ABR's traffic-control mechanisms, TCP/IP and other LAN-based traffic protocols can modify their transmission behaviour in response to	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			latency or cell loss in the ATM network.	
Unspecified Bit Rate Plus	UBR+	N/A	N/A	Huawei Term
uplink centric broadband communication	UCBC	N/A	Uplink centric broadband communication (UCBC) is a new scenario proposed by Huawei based on both enhanced Mobile Broadband (eMBB) and Massive Machine-Type Communications (mMTC) because some applications require both massive connections and uplink high bandwidth.	Huawei Term
uplink control information	UCI	N/A	N/A	3GPP TR 38.212: "NR; Multiplexing and channel coding"
user-centric network	UCN	user-centered network	N/A	Huawei Term
User Centric No Cell	UCNC	User Centric and No Cell	Novel radio access framework evolved from the classical cell-centric access protocol to a user-centric protocol with hyper-cell abstraction.	Huawei Term
Universal Character Set 2	UCS2	N/A	Two octet form	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
uplink data compression	UDC	N/A	When uplink data compression (UDC) is enabled, uplink data is compressed and only the non-repetitive contents of the original data are transmitted in the uplink over the air interface, thereby minimizing the amount of data to be transmitted over the air interface and increasing the radio resource efficiency for transmitting application-layer data. As a result, the uplink transmission rate at the application layer is increased.	Huawei Term
user-plane dedicated channel	UDCH	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
unconstrained delay data	UDD	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
unified data management	UDM	N/A	N/A	3GPP TR 23.973: "User data interworking, coexistence and migration"
User Datagram Protocol	UDP	N/A	This User Datagram Protocol (UDP) is defined to make available a datagram mode of packet-switched computer communication in the environment of an interconnected set of computer networks. This protocol assumes that the Internet Protocol (IP) is used as the underlying protocol. This protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism.	J. Postel, and ISI, "User Datagram Protocol", RFC 768, 28 August 1980

Term	Abbreviation	Synonym	Definition	Reference
user equipment	UE	N/A	Allows a user access to network services. A user equipment can be subdivided into a number of domains, the domains being separated by reference points. Currently the user equipment is subdivided into the UICC domain and the ME Domain. The ME Domain can further be subdivided into one or more mobile termination (MT) and terminal equipment (TE) components showing the connectivity between multiple functional groups.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
UE-aggregate maximum bit rate	UE-AMBR	N/A	N/A	3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2"
universal environment interface unit	UEIU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
universal E1/T1 lightning protection unit	UELP	N/A	Each universal E1/T1 lightning protection unit (UELP) provides surge protection for four channels of E1/T1 signals.	Huawei Term
user equipment with ODMA relay operation enabled	UE _R	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
universal FE lightning protection unit	UFLP	N/A	N/A	Huawei Term
user interface	UI	N/A	All components of an interactive system (software or hardware) that provide information and/or controls for the user to accomplish specific tasks with the interactive system	ETSI EG 203 350: "Human Factors (HF); Guidelines for the design of mobile ICT devices and their related applications for people with cognitive disabilities"

Term	Abbreviation	Synonym	Definition	Reference
unnumbered information	UI	N/A	The information field is to be interpreted as unnumbered information. Unnumbered Information (UI) frames can be sent in both ADM and ABM. There is no acknowledgement of receipt of UI-frames within RLP.	3GPP TS 24.022: "Technical Specification Group Core Network; Radio Link Protocol (RLP) for circuit switched bearer and teleservices"
UMTS integrity algorithm	UIA	N/A	N/A	3GPP TS 25.413: "Technical Specification Group (TSG) RAN RANAP Specification"
International Union of Railways	UIC	- International Rail Union - Union Internationale des Chemins de Fer	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
ultra low band	UL	N/A	N/A	Huawei Term
uplink	UL	N/A	An "uplink" is a unidirectional radio link for the transmission of signals from a UE to a base station, from a Mobile Station to a mobile base station or from a mobile base station to a base station.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
uplink angle-of-arrival	UL-AoA	uplink angle of arrival	N/A	3GPP TS 38.305: "Technical Specification Group Radio Access Network; NG Radio Access Network (NG-RAN); Stage 2 functional specification of User Equipment (UE) positioning in NG-RAN"
uplink coordinated multipoint reception	UL CoMP	N/A	UL CoMP is a multipoint reception technology. It coordinates the antennas of multiple cells to combine signals from a UE. UL CoMP provides signal combining gains, interference mitigation gains, or both. UL CoMP is similar to joint reception by the antennas of a single cell, with the following differences: 1. UL CoMP reuses existing antennas, without adding new antennas to cells. 2. UL CoMP provides lower gains, as the signal power received in each cell varies.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
uplink interference-based coordinated scheduling	UL IICS	N/A	UL IICS is a technology used for coordinated scheduling of uplink cell resources. It is used with the interference rejection combining (IRC) algorithm to improve uplink coverage for cell edge users (CEUs).	Huawei Term
uplink shared channel	UL-SCH	USCH	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
unacknowledged mode	UM	N/A	The RLC sublayer consists of RLC entities, of which there are three types: transparent mode (TM), unacknowledged mode (UM), and acknowledged mode (AM) RLC entities.	3GPP TS 25.322: "Radio Link Control (RLC) protocol specification"

Term	Abbreviation	Synonym	Definition	Reference
Ultra Mobile Broadband	UMB	N/A	UMB was intended to be a fourth-generation technology, which would make it compete with LTE and WiMAX. These technologies use a high-bandwidth, low-latency, underlying TCP/IP network with high-level services such as voice built on top.	Wikipedia
Unified Modelling Language	UML	N/A	UML is a widely used and accepted language. This is a major difference, compared to SDL and MSC, which are mostly known and used in parts of the real-time software industry (especially the communication industry).	ETSI TR 102 205: "Methods for Testing and Specification (MTS); UML 2.0 action syntax feasibility study"
universal main processing and transmission unit	UMPT	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
user mobility server	UMS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
UMTS Mobile Services Switching Centre	UMSC	• UMTS Mobile Switching Center • UMTS Mobile Switching Centre • UMTS MSC	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Universal Mobile Telecommunications System	UMTS	3G	The Universal Mobile Telecommunications System (UMTS) is a third generation mobile cellular system for networks based on the GSM standard. UMTS uses wideband code-division multiple access (W-CDMA) radio access technology to offer greater spectral efficiency and bandwidth to mobile network operators.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
user-network interface	UNI	N/A	The interface between the terminal equipment and a network termination at which interface the access protocols apply.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
user plane	UP	• forwarding plane • data plane	In routing, the forwarding plane, sometimes called the data plane or user plane, defines the part of the router architecture that decides what to do with packets arriving on an inbound interface. Most commonly, it refers to a table in which the router looks up the destination address of the incoming packet and retrieves the information necessary to determine the path from the receiving element, through the internal forwarding fabric of the router, and to the proper outgoing interface(s).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Uniform PCM Interface	UPCMI	N/A	The UPCMI is introduced for design purposes in order to separate the speech transcoder impairments from the basic audio impairments of the MS.	3GPP TS 43.050: "Transmission planning aspects of the speech service in the GSM Public Land Mobile Network (PLMN) system"
universal power and environment interface unit	UPEU	N/A	N/A	Huawei Term
User Plane Function	UPF	N/A	User Plane Function(s) handle the user plane path of PDU sessions.	3GPP TS 23.501: "System architecture for the 5G System (5GS)"
User Plane Gateway	UPGW	N/A	N/A	3GPP TR 38.912: "Study on New Radio (NR) access technology"
uplink pilot timeslot	UpPTS	N/A	Uplink part of a special subframe (for TDD operation)	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Universal Personal Telecommunication	UPT	N/A	Access to telecommunications services while allowing personal mobility. It enables each UPT user to participate in a user-defined set of subscribed services and to initiate and receive calls on the basis of a personal, network-transparent, UPT number across multiple networks on any fixed or mobile terminal, irrespective of geographical location, limited only by terminal and network capabilities and restrictions imposed by the network operator.	ETSI ETR 329: "Human Factors (HF); Guidelines for procedures and announcements in Stored Voice Services (SVS) and Universal Personal Telecommunication (UPT)"
UTRAN registration area	URA	user registration area	The UTRAN Registration Area is an area covered by a number of cells. The URA is only internally known in the UTRAN.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
user radio bearer	URB	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Uniform Resource Identifier	URI	N/A	Address of the resource and identification of the resource	ETSI EG 203 647: "Methods for Testing and Specification (MTS); Methodology for RESTful APIs specifications and testing"
Uniform Resource Locator	URL	N/A	Uniform Resource Locator (URL) refers to the subset of URI that identify resources via a representation of their primary access mechanism (e.g., their network "location"), rather than identifying the resource by name or by some other attribute(s) of that resource.	ETSI TS 102 051: "ENUM Administration in Europe"

Term	Abbreviation	Synonym	Definition	Reference
Ultra-Reliable Low Latency Communication	URLLC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
UTRAN radio network temporary identifier	U-RNTI	• UTRAN-RNTI • UTRAN RNTI	The U-RNTI is a unique UE identifier that consists of two parts, an SRNC identifier and a C-RNTI. U-RNTI is allocated to a UE having an RRC connection. It identifies the UE within UTRAN and is used as a UE identifier in cell update, URA update, RRC connection reestablishment and (UTRAN originated) paging messages and associated responses on the radio interface.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
USIM Application Toolkit	USAT	Universal SIM Application Toolkit	The USAT provides mechanisms which allow applications, existing in the UICC, to interact and operate with any ME which supports the specific mechanism(s) required by the application.	3GPP TS 31.111: "Technical Specification Group Terminals; USIM Application Toolkit (USAT)"
Universal Serial Bus	USB	N/A	Common interface that enables communication between devices and a host controller.	ETSI TS 103 429: "Integrated broadband cable telecommunication networks (CABLE); Cable Customer Premises Equipment (CPE) with Integrated Radio and Non-Radio Interfaces; Technical Specification covering the cable equipment technical requirements in support of Harmonised Standards for the essential requirements of article 3.1b of the Directive 2014/53/EU"

Term	Abbreviation	Synonym	Definition	Reference
UE Service Capabilities	USC	N/A	Capabilities that can be used either singly or in combination to deliver services to the user. The characteristic of UE Service Capabilities is that their logical function can be defined in a way that is independent of the implementation of the UMTS system (although all UE Service Capabilities are of course constrained by the implementation of UMTS). Examples: a data bearer of 144 kbps; a high quality speech teleservice; an IP teleservice; a capability to forward a speech call.	3GPP TR 21.904: "Technical Specification Group (TSG) Terminals; UE capability requirements"
universal satellite card and clock unit	USCU	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
uplink state flag	USF	N/A	Uplink State Flag (USF) is used on PDCH channel(s) to allow multiplexing of uplink Radio blocks from different mobile stations	3GPP TS 44.060: "Technical Specification Group Radio Access Network; General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol"
Universal Subscriber Identity Module	USIM	N/A	An application residing on the UICC used for accessing services provided by mobile networks, which the application is able to register on with the appropriate security.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
Unstructured Supplementary Service Data	USSD	N/A	There are two modes of USSD: MMI-mode and application mode. MMI-mode USSD is for the transparent transport of MMI strings entered by the user to the network and for the transparent transport of text strings from the network that are displayed by the mobile for user information. Application mode USSD is for the transparent transport of data between the network and the UE. Application mode USSD is intended to be used by applications in the network and their peer applications in the UE.	3GPP TS 22.090: "Technical Specification Group Services and System Aspects; Unstructured Supplementary Service Data (USSD); Stage 1"

Term	Abbreviation	Synonym	Definition	Reference
universal time	UT	N/A	Universal time is the general designation of time scales based on the rotation of the Earth. In applications in which an imprecision of a few hundredths of a second cannot be tolerated, it is necessary to specify the form of UT which should be used: - UT0 is the mean solar time of the prime meridian obtained from direct astronomical observation. - UT1 is UT0 corrected for the effects of small movements of the Earth relative to the axis of rotation (polar variation). - UT2 is UT1 corrected for the effects of a small seasonal fluctuation in the rate of rotation of the Earth. (See Recommendation ITU-R TF. 460.)	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Coordinated Universal Time	UTC	N/A	Because the daylight saving rules for local time zones are so convoluted and can change based on local law at unpredictable times, true interoperability is best achieved by using Coordinated Universal Time (UTC).	G. Klyne, Clearswift Corporation, C. Newman, and Sun Microsystems, "Date and Time on the Internet: Timestamps", RFC 3339, July 2002

Term	Abbreviation	Synonym	Definition	Reference
uplink time difference of arrival	U-TDOA	UL-TDOA	The U-TDOA positioning method is based on network measurements of the Time Of Arrival (TOA) of a known signal sent from the mobile and received at three or more LMUs. The known signal is the normal bursts generated by a mobile while in the dedicated mode; either on the SDCCH or TCH. The method requires LMUs in the geographic vicinity of the mobile to be positioned to accurately measure the TOA of the bursts. Since the geographical coordinates of the measurement units are known, the mobile position can be calculated via hyperbolic trilateration. This method will work with existing mobiles without any modification.	3GPP TS 43.059: "Technical Specification Group Radio Access Network; Functional stage 2 description of Location Services (LCS) in GERAN"

Term	Abbreviation	Synonym	Definition	Reference
UMTS Terrestrial Radio Access	UTRA	N/A	A standard specified by 3GPP for 3G mobile communications services. UTRA is based on WCDMA, which uses direct sequence spread spectrum, and TD-CDMA, a hybrid access technology. Both technologies are designed to meet the requirements of spectral efficiency, mobility, and service quality in 3G.	Huawei Term
Universal Terrestrial Radio Access	UTRA	UMTS Terrestrial Radio Access	A standard specified by 3GPP for 3G mobile communications services. UTRA is based on WCDMA, which uses direct sequence spread spectrum, and TD-CDMA, a hybrid access technology. Both technologies are designed to meet the requirements of spectral efficiency, mobility, and service quality in 3G.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
UMTS Terrestrial Radio Access Network	UTRAN	Universal Terrestrial Radio Access Network	UTRAN is a conceptual term identifying that part of the network which consists of RNCs and NodeBs between Iu and Uu interfaces.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
universal transmission processing unit	UTRP	N/A	N/A	Huawei Term
User-to-User Information	UUI	N/A	Information transferred by using the UUS supplementary service	3GPP TS 23.087: "Technical Specification Group Core Network; User-to-User Signalling (UUS) supplementary service; Stage 2"
Uu load reshuffling	UULDR	N/A	LDR is performed on the air-interface.	Huawei Term
Uu stratum	UUS	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"

Term	Abbreviation	Synonym	Definition	Reference
user-to-user signaling	UUS	user to user signaling	The User-to-User Signalling (UUS) supplementary service allows a mobile subscriber to send/receive a limited amount of information to/from another PLMN or ISDN subscriber over the signalling channel in association with a call to the other subscriber.	3GPP TS 22.087: "Technical Specification Group Services and System Aspects; User-to-User Signalling (UUS); Service description; Stage 1"
UE context management	N/A	N/A	N/A	3GPP TS 38.413: "NR; NG Application Protocol"
UE security capability	N/A	N/A	A set of identifiers corresponding to the ciphering and integrity algorithms implemented in the UE.	Huawei Term
UNI mode	N/A	N/A	A mode where an ATM cell is directly carried on a E1/T1 and the bits of the ATM cell are sequentially mapped to the valid timeslots on the E1/T1.	Huawei Term
unicast	N/A	N/A	Communication between a single sender and a single receiver over a network.	ETSI GS LTN 001: "Low Throughput Networks (LTN); Use Cases for Low Throughput Networks"

Term	Abbreviation	Synonym	Definition	Reference
upgrade process	N/A	N/A	A process running on the GBAM server or the GOMU to implement remote upgrade of the BSC software.	Huawei Term
uplink preallocation	N/A	N/A	Uplink preallocation means that the base station proactively sends an uplink scheduling indication to a UE and schedules the UE at a given interval regardless of whether the UE sends an SR to the base station. This reduces the time from when the UE sends an SR to when it obtains the uplink scheduling grant.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
URA_PCH	N/A	N/A	This state is similar to CELL_PCH, but the UE sends URA updates instead of cell updates, i.e. the serving RNC is known. That means that much less control signalling is necessary, but also that the UE has to perform a cell update for data transmission. The UE has to be paged for downlink transmissions, but the cell update procedure is faster than the complete bearer setup from Idle state.	ETSI TR 102 962: "Intelligent Transport Systems (ITS); Framework for Public Mobile Networks in Cooperative ITS (C-ITS)"
user data	N/A	N/A	"User data" is the data that is created or stored in terminals or network entities by the users, and is related to the private information, historical operations performed by the user, personal tendencies or favorite user settings. It is independent of whether this data is transported by terminal or network entities, and has no correlation with the counterpart of "Control data".	ITU-T F.746.2: "Service description for user data exchange between functional components in network entities and terminals"

Term	Abbreviation	Synonym	Definition	Reference
user group	N/A	N/A	End-users who with respect to their usage of communication service may be grouped together (e.g. business executives, university students, grandparents, deaf people, etc.)	ETSI TR 102 274: "Human Factors (HF); Guidelines for real-time person-to-person communication services"
Uu interface	N/A	N/A	An interface between user equipment and base station in 3GPP systems.	ETSI TR 103 630: "Intelligent Transport Systems (ITS); Security; Pre-standardization Study on ITS Facility Layer Security for C-ITS Communication Using Cellular Uu Interface"

1.23 V

Term	Abbreviation	Synonym	Definition	Reference
vehicle-to-everything	V2X	N/A	Vehicle-to-everything (V2X) is the communication between a vehicle and another vehicle or a device that may affect the vehicle. It is an automobile communication system that includes vehicle-to-infrastructure (V2I), vehicle-to-network (V2N), vehicle-to-vehicle (V2V), vehicle-to-pedestrian (V2P), and vehicle-to-device (V2D).	Huawei Term
virtual antenna mapping	VAM	N/A	VAM is used to achieve the goal of balancing the power between the physical channels across the multiple physical antennas especially when MIMO is deployed in the downlink.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
value-added service	VAS	N/A	A service that is offered in addition to or in conjunction with basic telecommunication services such as voice call, short message service (SMS), multimedia messaging service (MMS) and data access. These value-added services allow operators to drive up their average revenue per user (ARPU). Typical value-added services include mobile office automation, e-reading and e-commerce.	ITU-T X.1146: "Secure protection guidelines for value-added services provided by telecommunication operators"
value-added service provider	VASP	N/A	Provides services other than basic telecommunication service for which additional charges may be incurred	ETSI ES 201 915-1: "Open Service Access (OSA); Application Programming Interface (API); Part 1: Overview"

Term	Abbreviation	Synonym	Definition	Reference
variable bit rate	VBR	N/A	ATM service whose bit rate is characterised by the average and peak bit rates. These parameters remain constant for the duration of a connection.	ETSI TS 101 207-2: "Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 2: Transceiver specification"
voice broadcast service	VBS	N/A	Voice Broadcast Service (VBS) which allows the distribution of speech (or other signals can be transmitted via the speech codec), generated by a service subscriber, into a predefined geographical area to all or a group of service subscribers located in this area.	3GPP TS 42.069: "Technical Specification Group Services and system Aspects; Voice Broadcast Service (VBS) - Stage 1"
video coding	VC	N/A	N/A	ETSI TS 102 826: "Digital Video Broadcasting (DVB); DVB-IPTV Profiles for TS 102 034"

Term	Abbreviation	Synonym	Definition	Reference
video over NR	ViNR	Video over New Radio	Video over NR (ViNR) refers to video calls over the NR network. It requires QoS flows with a 5QI of 2 to carry video services in addition to QoS flows with a 5QI of 1 set up for VoNR to carry voice services. ViNR UEs are also called VoNR UEs performing video services.	Huawei Term
virtual channel	VC	N/A	N/A	ETSI TR 100 815: "Digital Video Broadcasting (DVB); Guidelines for the handling of Asynchronous Transfer Mode (ATM) signals in DVB systems"
virtual circuit	VC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
virtual container	VC	N/A	N/A	ETSI ETS 300 814: "Digital Video Broadcasting (DVB); DVB interfaces to Synchronous Digital Hierarchy (SDH) networks"
virtual channel connection	VCC	N/A	Virtual channel links are concatenated to form a virtual channel connection (VCC). A VCC extends between two VCC endpoints or, in the case of point-to-multipoint arrangements, more than two VCC endpoints. A VCC endpoint is the point where the cell information field is exchanged between the ATM layer and the user of the ATM layer service.	ITU-T I.311: "B-ISDN general network aspects"
virtual circuit connectivity verification	VCCV	N/A	VCCV is, in its simplest description, a control channel between a pseudowire's ingress and egress points over which connectivity verification messages can be sent.	T. Nadeau, "Pseudowire Virtual Circuit Connectivity Verification (VCCV): A Control Channel for Pseudowires", RFC 5085, December 2007

Term	Abbreviation	Synonym	Definition	Reference
virtual concatenation group	VCG	N/A	A group of co-located member trail termination functions that are connected to the same virtual concatenation link.	Huawei Term
virtual channel identifier	VCI	N/A	A virtual channel connection across a switch is formed by connecting an incoming virtual channel to one or more outgoing virtual channels. Virtual channel connections are referenced by the input port on which they arrive and the virtual path and virtual channel identifiers (VPI/VCI) of their incoming virtual channel.	P. Newman, Nokia, W. Edwards, Sprint, R. Hinden, Nokia, E. Hoffman, Nokia, F. Ching Liaw, T. Lyon, Nokia, and G. Minshall, and Fiberlane, "Ipsilon's General Switch Management Protocol Specification Version 2.0", RFC 2297, March 1998

Term	Abbreviation	Synonym	Definition	Reference
virtual channel link	VCL	N/A	There are two distinct types of ATM virtual connections: virtual channel connections (VCCs) and virtual path connection (VPCs). ATM virtual connections consist of concatenated series of virtual links which forms a path between two end points, with each concatenation occurring at an ATM switch. Virtual links of VCCs are called virtual channel links (VCLs).	ETSI TR 101 287: "Network Aspects (NA); Terms and definitions"
Internal port of the EFP8/ EMS6	VCTRUNK	N/A	A virtual concatenation group applied in data service mapping, also called the internal port of a data service processing board.	Huawei Term
voice group call service	VGCS	N/A	Voice Group Call Service (VGCS) allows speech conversation of a predefined group of service subscribers in half duplex mode on the radio link taking into account multiple subscribers involved in the group call per cell.	3GPP TS 03.68: "Technical Specification Group Core Network; Voice Group Call Service (VGCS); Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
Virtual Home Environment	VHE	N/A	Virtual Home Environment (VHE) is defined as a concept for Personal Service Environment (PSE) portability across network boundaries and between terminals. The concept of VHE is such that users are consistently presented with the same personalised features, User Interface customisation and services in whatever network and whatever terminal (within the capabilities of the terminal and the network), wherever the user may be located.	3GPP TR 22.121: "Technical Specification Group Services and System Aspects Service aspects; The Virtual Home Environment"
very important person	VIP	N/A	A person who is accorded special privileges due to their high social status, influence or importance.	Wikipedia
virtual internet protocol	VIP	N/A	Virtual Internet Protocol [VIP] has two basic ideas. First, a packet carries both Identifier and Locator; second, the Identifier is an IP address that leads to the home network where the mapping is kept.	Z. Zhu, UCLA, R. Wakikawa, Toyota ITC, L. Zhang, and UCLA, "A Survey of Mobility Support in the Internet", RFC 6301, July 2011

Term	Abbreviation	Synonym	Definition	Reference
virtual LAN	VLAN	N/A	A virtual LAN (VLAN) is any broadcast domain that is partitioned and isolated in a computer network at the data link layer (OSI layer 2).	Wikipedia
visitor location register	VLR	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
virtual MBSFN area	VMA	N/A	N/A	Huawei Term
virtual multiple-input multiple-output	VMIMO	virtual MIMO	Virtual MIMO is the scenario when both ends of the communication consist of virtual antenna arrays. Forming a virtual antenna array is the process of grouping multiple communication terminals into one (at least virtually one). All these communication terminals contribute their antennas to form a virtual antenna array.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
video mean opinion score	vMOS	N/A	Video mean opinion score (vMOS) is a video quality assessment method and represents a subjective evaluation from the perspective of user perception to video quality.	Huawei Term
visited MSC	VMSC	• Visited Mobile-service Switching Centre • Visited Mobile Switching Centre	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
virtual network-network interface	V-NNI	N/A	A virtual network-network interface (V-NNI) is a network-side interface.	Huawei Term
video on demand	VoD	N/A	N/A	3GPP TR 26.981: "MBMS Extensions for Provisioning and Content Ingestion"

Term	Abbreviation	Synonym	Definition	Reference
Voice over Internet Protocol	VoIP	• voice-over-IP • Voice Over IP • IP telephony	Voice over Internet Protocol (VoIP), also called IP telephony, is a method and group of technologies for the delivery of voice communications and multimedia sessions over Internet Protocol (IP) networks, such as the Internet. The terms Internet telephony, broadband telephony, and broadband phone service specifically refer to the provisioning of communications services (voice, fax, SMS, voice-messaging) over the Internet, rather than via the public switched telephone network (PSTN), also known as plain old telephone service (POTS).	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
Voice over LTE	VoLTE	N/A	Voice over Long Term Evolution (VoLTE) is a high-speed wireless communication standard for mobile phones and data terminals, including Internet of things (IoT) devices and wearables.	Wikipedia
Voice over NR	VoNR	N/A	N/A	3GPP TR 26.919: "Study on media handling aspects of conversational services in 5G systems"
virtual path	VP	N/A	N/A	ITU-T I.311: "B-ISDN general network aspects"

Term	Abbreviation	Synonym	Definition	Reference
virtual path identifier	VPI	N/A	A virtual path connection across a switch is formed by connecting an incoming virtual path to one or more outgoing virtual paths. Virtual path connections are referenced by the input port on which they arrive and their virtual path identifier (VPI).	P. Newman, Nokia, W. Edwards, Sprint, R. Hinden, Nokia, E. Hoffman, Nokia, F. Ching Liaw, T. Lyon, Nokia, and G. Minshall, and Fiberlane, "Ipsilon's General Switch Management Protocol Specification Version 2.0", RFC 2297, March 1998
virtual public land mobile network	VPLMN	N/A	N/A	Huawei Term
visited public land mobile network	VPLMN	visited PLMN	This is a PLMN different from the HPLMN (if the EHPLMN list is not present or is empty) or different from an EHPLMN (if the EHPLMN list is present).	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications "

Term	Abbreviation	Synonym	Definition	Reference
virtual private LAN service	VPLS	N/A	Virtual private LAN service (VPLS) is a way to provide Ethernet-based multipoint to multipoint communication over IP or MPLS networks. It allows geographically dispersed sites to share an Ethernet broadcast domain by connecting sites through pseudo-wires. The sites include multiplicities of both servers and clients. The technologies that can be used as pseudo-wire can be Ethernet over MPLS, L2TPv3 or even GRE. There are two IETF standards track RFCs (RFC 4761 and RFC 4762) describing VPLS establishment. VPLS is a virtual private network (VPN) technology. In contrast to L2TPv3, which allows only point-to-point layer 2 tunnels, VPLS allows any-to-any (multipoint) connectivity. In a VPLS, the local area network (LAN) at each site is extended to the edge of the provider network.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
			The provider network then emulates a switch or bridge to connect all of the customer LANs to create a single bridged LAN.	
virtual private network	VPN	N/A	A virtual private network (VPN) is a collection of service access groups that form a private network for reconfigurable leased circuit services. Any service access point can be connected to any other service access point in the VPN.	ITU-T M.3208.3: "TMN management services for dedicated and reconfigurable circuits network: Virtual private network service"
voice quality monitoring	VQM	N/A	Mainly used for network monitoring, network optimization, VIP guarantee, and user complaint handling under AMR speech coding. VQM reduces the necessity of drive tests required for obtaining voice quality.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
virtual reality	VR	N/A	Virtual reality (VR) is a simulated experience that employs pose tracking and 3D near-eye displays to give the user an immersive feel of a virtual world. Applications of virtual reality include entertainment (particularly video games), education (such as medical or military training) and business (such as virtual meetings). Other distinct types of VR-style technology include augmented reality and mixed reality, sometimes referred to as extended reality or XR, although definitions are currently changing due to the nascence of the industry.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
VPN routing and forwarding	VRF	N/A	Each PE router maintains a number of separate forwarding tables. One of the forwarding tables is the "default forwarding table". The others are "VPN Routing and Forwarding tables", or "VRFs".	E. Rosen, Cisco Systems, Inc., Y. Rekhter, and Juniper Networks, Inc., "BGP/MPLS IP Virtual Private Networks (VPNs)", RFC 4364, February 2006
Virtual Router Redundancy Protocol	VRRP	N/A	The Virtual Router Redundancy Protocol (VRRP) is designed to eliminate the single point of failure inherent in the static default routed environment. VRRP specifies an election protocol that dynamically assigns responsibility for a virtual router to one of the VRRP routers on a LAN.	R. Hinden, Ed., and Nokia, "Virtual Router Redundancy Protocol (VRRP)", RFC 3768, April 2004

Term	Abbreviation	Synonym	Definition	Reference
very small aperture terminal	VSAT	N/A	A very small aperture terminal (VSAT) is a two-way satellite ground station with a dish antenna that is smaller than 3.8 meters. The majority of VSAT antennas range from 75 cm to 1.2 m. Data rates, in most cases, range from 4 kbit/s up to 16 Mbit/s. VSATs access satellites in geosynchronous orbit or geostationary orbit to relay data from small remote Earth stations (terminals) to other terminals (in mesh topology) or master Earth station "hubs" (in star topology).	Wikipedia
voltage standing wave ratio	VSWR	N/A	The ratio, along a transmission line, of a maximum to an adjacent minimum magnitude of a particular field component of a standing wave.	3GPP TS 37.544: "Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA); User Equipment (UE) Over The Air (OTA) performance; Conformance testing"

Term	Abbreviation	Synonym	Definition	Reference
verification code	N/A	N/A	The identity of a user is usually verified through verification codes sent to their mobile phones or email addresses. In other scenarios, a figure containing numbers and letters generated randomly when a user accesses a page. The user must enter the numbers and letters. This avoids violent cracking and malicious ads.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
virtual grid	N/A	N/A	A virtual grid refers to a cell's signal grid. Measurement reports (MRs) of different UEs on the network are collected to obtain information such as the reference signal received power (RSRP) and spectral efficiency of different frequencies and the obtained information is used to construct a virtual-grid-based mapping between signal characteristics and frequencies. Virtual grids are used for carrier selection, inter-frequency handovers, or inter-RAT handovers on multi-frequency networks. Unlike traditional geographic grids, virtual grids are classified by signal strength instead of geographic location.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
virtual tunnel	N/A	N/A	Virtual tunnel can group data flows by dividing all data flows into multiple virtual tunnels according to certain conditions, and managing the virtual tunnels as independent links. The conditions for grouping data flows include the IP quintuple, ToS/DSCP, VLAN, MPLS, and link. Meanwhile, the data flows of a group of users can be classified into virtual tunnels. Users can be grouped according to the user area and dynamic attribute.	Huawei Term
virtualization	N/A	N/A	Software that separates applications from the physical hardware on which they run, allowing a piece of physical server to support one application, instead of requiring a full server.	ETSI TS 105 174-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Broadband Deployment and Energy Management; Part 2: ICT sites"

1.24 W

Term	Abbreviation	Synonym	Definition	Reference
wireless application environment	WAE	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
wide area network	WAN	N/A	Wide area network, or interconnected LANs providing a computer data network between PLMN elements.	3GPP TR 41.033: "Lawful Interception requirements for GSM"

Term	Abbreviation	Synonym	Definition	Reference
Wireless Application Protocol	WAP	N/A	Wireless Application Protocol (WAP) is a technical standard for accessing information over a mobile wireless network. A WAP browser is a web browser for mobile devices such as mobile phones that use the protocol. Introduced in 1999, WAP achieved some popularity in the early 2000s, but by the 2010s it had been largely superseded by more modern standards. Almost all modern handset internet browsers now fully support HTML, so they do not need to use WAP markup for web page compatibility, and therefore, most are no longer able to render and display pages written in WML, WAP's markup language.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
wideband	WB	N/A	A classification for the spectral width of a transmission system. Generally considered if the fractional BW is > 1% of the carrier frequency.	ETSI TR 101 982: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radio equipment to be used in the 24 GHz band; System Reference Document for Short Range Radar"
Wideband Code Division Multiple Access	WCDMA	N/A	W-CDMA (WCDMA; Wideband Code Division Multiple Access), along with UMTS-FDD, UTRA-FDD, or IMT-2000 CDMA Direct Spread is an air interface standard found in 3G mobile telecommunications networks. It supports conventional cellular voice, text and MMS services, but can also carry data at high speeds, allowing mobile operators to deliver higher bandwidth applications including streaming and broadband Internet access.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
wireless datagram protocol	WDP	N/A	A kind of communication protocol describing the format of datagram in wireless networks	Huawei Term
Web Local Maintenance Terminal	Web LMT	N/A	A local maintenance terminal, consisting of the Web LMT server and Web LMT client, used to run MML commands and perform batch operations. Users can log in to the Web LMT server using a web browser. Data is transferred through HTTP/HTTPS between the browser and the Web LMT server. Users can load the Web LMT client from the Web LMT server to a local PC using the browser. The Web LMT server sets up TCP connections with NEs to exchange data.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
waste electrical and electronic equipment	WEEE	N/A	Electrical or electronic equipment which is waste within the meaning of Article 3(1) of Directive 2008/98/EC, including all components, sub-assemblies and consumables which are part of the product at the time of discarding.	ETSI EN 305 174-8: "Access, Terminals, Transmission and Multiplexing (ATTM); Broadband Deployment and Lifecycle Resource Management; Part 8: Management of end of life of ICT equipment"
weighted fair queuing	WFQ	N/A	Weighted fair queueing (WFQ) is a network scheduling algorithm. WFQ is both a packet-based implementation of the generalized processor sharing (GPS) policy, and a natural extension of fair queuing (FQ). Whereas FQ shares the link's capacity in equal subparts, WFQ allows schedulers to specify, for each flow, which fraction of the capacity will be given.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
working group	WG	N/A	Official subgroup of a TSG reporting to that TSG	3GPP TR 21.900: "Technical Specification Group Services and System Aspects; Technical Specification Group working methods"
Wireless Fidelity	Wi-Fi	N/A	N/A	3GPP/PCG#13(04)21: "WLAN Spectrum Report after-WRC-03"
Worldwide Interoperability for Microwave Access	WiMAX	N/A	World Interoperability for Microwave Access is a broadband wireless access technology based on IEEE 802.16 standard.	ETSI TR 181 011: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Fixed Mobile Convergence; Requirements analysis"
wireless intelligent network	WIN	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
wireless local area network	WLAN	N/A	Local area network in which data are transferred without the use of wires.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
WLAN user equipment	WLAN UE	N/A	A UE (equipped with UICC card including (U)SIM) utilized by a subscriber capable of accessing a WLAN network. A WLAN UE may include entities whose configuration, operation and software environment are not under the exclusive control of the 3GPP system operator, such as a laptop computer or PDA with a WLAN card, UICC card reader and suitable software applications.	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
WCDMA main processing and transmission unit	WMPT	N/A	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
warning notification provider	WNP	N/A	It is an agency (e.g. government, local government, public service organizations) that provides Warning Notifications and requests PLMN operators to deliver them.	3GPP TS 22.168: "Earthquake and Tsunami Warning System (ETWS) requirements; Stage 1"
weighted random early detection	WRED	Weighted RED	N/A	Huawei Term
WCDMA RAN feature description	WRFD	N/A	N/A	Huawei Term
weighted round robin	WRR	N/A	One class of implementation approaches, generically referred to as weighted round robin (WRR), implements the structure of the queue as an array or ring of subqueues associated with flows for whatever definition of a flow is important.	F. Baker, R. Pan, and Cisco Systems, "On Queuing, Marking, and Dropping", RFC 7806, April 2016

Term	Abbreviation	Synonym	Definition	Reference
Wireless Session Protocol	WSP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
wideband time division duplexing	WTDD	N/A	Wide TDD – the 3.84 Mcps chip rate UTRA-TDD option	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
Wireless Transport Layer Security	WTLS	N/A	The WTLS security model provides a flexible framework based on TLS, which is independent of the GSM security model.	ETSI TS 101 438: "Digital cellular telecommunications system (Phase 2+); Mobile Station Application Execution Environment (MExE); Functional description; Stage 2"

Term	Abbreviation	Synonym	Definition	Reference
wireless transaction protocol	WTP	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"
wait to restore	WTR	N/A	The condition in which a working trail/sub-network connection meets the restoral threshold after a signal degrade (SD) or signal fail (SF) condition. The transport of working traffic is ready to be reverted to the working trail/sub-network connection from the protection trail/sub-network connection	ETSI TS 101 009: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH); Network protection schemes; Types and characteristics"
wireless to the x	WTTx	N/A	N/A	Huawei Term
waiting time extension	WTX	N/A	WTX is a parameter used to ask for more time to process a command.	3GPP TS 31.120: "Technical Specification Group Terminals; UICC-terminal interface; Physical, electrical and logical test specification"

Term	Abbreviation	Synonym	Definition	Reference
wake-up signal	WUS	N/A	A wake-up signal (WUS) is a signal used to indicate whether to wake up a UE in the DRX On Duration period to monitor the PDCCH.	Huawei Term
work waiting time	WWT	N/A	The Work Waiting Time (WWT) is the maximum interval between the start leading edge of any character sent by the UICC and the start leading edge of the previous character sent by either the UICC or the terminal.	3GPP TS 31.120: "Technical Specification Group Terminals; UICC-terminal interface; Physical, electrical and logical test specification"
World Wide Web	WWW	W3	A hypertext-based, distributed information system created by researchers at CERN in Switzerland. Users may create, edit or browse hypertext documents. The clients and servers are freely available. (See IETF RFC 1983.)	ETSI TR 101 287: "Services and Protocols for Advanced Networks (SPAN); Terms and definitions"
Web LCT	N/A	N/A	The local maintenance terminal of a transport network. This is part of the NE management layer of a transport network.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
Web service	N/A	N/A	A web service defined in terms of an XML-based protocol, often transported over SOAP, and/or a service whose instances, and possible data objects managed therein, are concisely addressable via URIs.	3GPP TR 33.980: "Liberty Alliance and 3GPP security interworking; Interworking of Liberty Alliance Identity Federation Framework (ID-FF), Identity Web Services Framework (ID-WSF) and Generic Authentication Architecture (GAA)"
weight	N/A	N/A	In wireless communications, the width or direction of a beam can be adjusted by changing the amplitude or phase of the signals on the radio frequency link. The adjusted amplitude or phase of the signals or the combination of the adjusted amplitude and phase of the signals is referred to as the weight of these signals.	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
white noise	N/A	N/A	White noise is a random signal having equal intensity at different frequencies, giving it a constant power spectral density.	Wikipedia
whitelist	N/A	N/A	List of identities or identity ranges that are provided particular services.	3GPP TS 22.173: "IP Multimedia Core Network Subsystem (IMS) Multimedia Telephony Service and supplementary services; Stage 1"
wind load	N/A	N/A	Air flow pressure on an engineering structure	Huawei Term
windowing	N/A	N/A	Process of multiplying a waveform signal segment by a time window of given shape, to emphasize pre-defined characteristics of the signal.	ETSI ES 201 108: "Speech Processing, Transmission and Quality Aspects (STQ); Distributed speech recognition; Front-end feature extraction algorithm; Compression algorithms"
wiring terminal	N/A	connecting terminal	A point to which a wire can be connected in a circuit	Huawei Term

1.25 X

Term	Abbreviation	Synonym	Definition	Reference
X2 Application Protocol	X2AP	N/A	The protocol responsible for providing signalling information across the X2 interface is called the X2 Application Protocol (X2AP). The X2AP is terminated by the two eNodeBs inter-connected via the X2 interface X2AP Procedure Modules.	3GPP TS 36.420: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); X2 general aspects and principles"
x digital subscriber line (xDSL)	xDSL	N/A	N/A	3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3"
exchange identification	XID	N/A	N/A	Huawei Term
expected message authentication code	XMAC	expected MAC	N/A	Huawei Term

Term	Abbreviation	Synonym	Definition	Reference
expected message authentication code for integrity	XMAC-I	expected MAC-I	N/A	Huawei Term
Extensible Markup Language	XML	N/A	Universal file format for storing and exchanging structured data	ETSI ES 203 259: "Integrated broadband cable telecommunication networks (CABLE); Converged Cable Access Platform; Operational Support System Interface"
Xn Application Protocol	XnAP	N/A	The transport network layer is built on IP transport. For the reliable transport of signalling messages, SCTP is added on top of IP. The application layer signalling protocol is referred to as XnAP (Xn Application Protocol).	3GPP TS 38.420: "NG-RAN; Xn general aspects and principles"

Term	Abbreviation	Synonym	Definition	Reference
crystal oscillator	XO	COSC	A crystal oscillator is an electronic oscillator circuit that uses the mechanical resonance of a vibrating crystal of piezoelectric material to create an electrical signal with a constant frequency.	Wikipedia
cross-polarization interference cancellation	XPIC	cross-polarization interference cancelling	XPIC, or cross-polarization interference cancelling technology, is an algorithm to suppress mutual interference between two received streams in a polarization-division multiplexing communication system.	Wikipedia
extended reality	XR	N/A	Extended reality (XR) is a catch-all term to refer to augmented reality (AR), virtual reality (VR), and mixed reality (MR). The technology is intended to combine or mirror the physical world with a "digital twin world" able to interact with it.	Wikipedia

Term	Abbreviation	Synonym	Definition	Reference
expected response	XRES	N/A	In the UMTS authentication process, the network sends RAND (Random Number) to a UMTS subscriber. XRES is the value that the network is looking for to indicate a positive response.	Huawei Term
X2 interface	N/A	X2	The interface between eNodeBs.	3GPP TR 25.912: "Technical Specification Group Radio Access Network; Feasibility study for evolved Universal Terrestrial Radio Access (UTRA) and Universal Terrestrial Radio Access Network (UTRAN)"

1.26 Y

N/A

1.27 Z

Term	Abbreviation	Synonym	Definition	Reference
zone code	ZC	N/A	N/A	3GPP TR 21.905: "Technical Specification Group Services and System Aspects; Vocabulary for 3GPP Specifications"