

01_antonelli_vs_russell

May 13, 2026

1 Antonelli vs Russell — 2026 Qualifying, First Four Rounds

I wanted to see where Kimi Antonelli’s 2026 season at Mercedes actually stands vs his teammate George Russell. This notebook compares both Mercedes drivers’ fastest qualifying laps across the first four rounds of 2026, broken down by track segment. See the [project README](#) for full method and limitations.

```
[1]: %matplotlib inline
import sys
sys.path.insert(0, '..')
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

from src.loaders import setup_cache, load_qualifying_session,
    ↳get_fastest_valid_lap, get_lap_telemetry
from src.segments import resample_to_distance_grid
from src.benchmarks import compare_teammates
from src.plotting import plot_category_deltas, plot_lap_delta_by_round,
    ↳plot_track_delta_map, plot_yoy_lap_deltas

setup_cache('../fastf1_cache')
RACES = ['Australia', 'China', 'Japan', 'Miami']
```

1.1 Method (briefly)

For each race: load qualifying, take each driver’s fastest valid lap, and segment the track from FastF1’s `circuit_info.corners` (corners within 250 m are grouped, straights are filled in between). Telemetry — including FastF1’s per-sample `Time` channel — is resampled onto a uniform 5 m distance grid. Per-segment time is read directly from that resampled `Time` channel as `Time[last_step] - Time[first_step]` inside the segment. Per-segment delta is `time(Russell) - time(Antonelli)`, so **positive = Antonelli faster**.

An earlier version integrated `step / speed` per grid point. On 2 of 4 races the accumulated residual exceeded the 0.1 s sanity-check threshold (see the next section), so the analysis switched to reading FastF1’s sample times directly. Residuals are now `< 0.1 s` on all four races.

Each segment is classified into one of four categories by its minimum speed: slow corner (`<130`

kph), medium corner (130–200 kph), fast corner (>200 kph), or straight.

```
[2]: results = {race: compare_teammates(2026, race) for race in RACES}

meta_df = pd.DataFrame([results[r]['meta'] for r in RACES])
summary = meta_df[['round', 'event_name', 'lap_time_a_s', 'lap_time_b_s',
↳ 'lap_delta_s', 'q_session_a', 'q_session_b', 'q_mismatch']]
summary.columns = ['Round', 'Race', 'ANT lap (s)', 'RUS lap (s)', '\u0394 lap_
↳ (s)', 'ANT Q', 'RUS Q', 'Q mismatch']
summary
```

```
core          INFO      Loading data for Australian Grand Prix - Qualifying
[v3.8.1]

req           INFO      Using cached data for session_info

req           INFO      Using cached data for driver_info

req           INFO      Using cached data for session_status_data

req           INFO      Using cached data for track_status_data

req           INFO      Using cached data for _extended_timing_data

req           INFO      Using cached data for timing_app_data

core          INFO      Processing timing data...

core          WARNING    No lap data for driver 18

core          WARNING    No lap data for driver 55

core          WARNING    Failed to perform lap accuracy check - all laps marked
as inaccurate (driver 18)

core          WARNING    Failed to perform lap accuracy check - all laps marked
as inaccurate (driver 55)

req           INFO      Using cached data for car_data

req           INFO      Using cached data for position_data

req           INFO      Using cached data for weather_data

req           INFO      Using cached data for race_control_messages

core          INFO      Finished loading data for 22 drivers: ['63', '12', '6',
'16', '81', '1', '44', '30', '41', '5', '27', '87', '31', '10', '23', '43',
'14', '11', '77', '18', '3', '55']

core          INFO      Loading data for Chinese Grand Prix - Qualifying
[v3.8.1]

req           INFO      Using cached data for session_info

req           INFO      Using cached data for driver_info

req           INFO      Using cached data for session_status_data
```

```

req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 22 drivers: ['12', '63', '44',
'16', '81', '1', '10', '3', '6', '87', '27', '43', '31', '30', '41', '5', '55',
'23', '14', '77', '18', '11']
core         INFO      Loading data for Japanese Grand Prix - Qualifying
[v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 22 drivers: ['12', '63', '81',
'16', '1', '44', '10', '6', '5', '41', '3', '31', '27', '30', '43', '55', '23',
'87', '11', '77', '14', '18']
core         INFO      Loading data for Miami Grand Prix - Qualifying [v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data

```

```

core          INFO      Processing timing data...
req           INFO      Using cached data for car_data
req           INFO      Using cached data for position_data
req           INFO      Using cached data for weather_data
req           INFO      Using cached data for race_control_messages
core          INFO      Finished loading data for 22 drivers: ['12', '3', '16',
'1', '63', '44', '81', '43', '10', '27', '30', '87', '55', '31', '23', '41',
'14', '18', '77', '11', '5', '6']

```

```

[2]:
Round      Race  ANT lap (s)  RUS lap (s)  Δ lap (s)  ANT Q  \
0         1  Australian Grand Prix    78.811    78.518    -0.293    3
1         2    Chinese Grand Prix    92.064    92.286     0.222    3
2         3   Japanese Grand Prix    88.778    89.076     0.298    3
3         4     Miami Grand Prix    87.798    88.197     0.399    3

RUS Q  Q mismatch
0      3      False
1      3      False
2      3      False
3      3      False

```

```

[3]: mismatch_races = [r['meta']['event_name'] for r in results.values() if
    ↳r['meta']['q_mismatch']]
unknown_races = [r['meta']['event_name'] for r in results.values() if
    ↳r['meta']['q_session_a'] is None or r['meta']['q_session_b'] is None]
if mismatch_races:
    print('\u26a0 Q-session mismatch \u2014 drivers\' fastest valid laps came
    ↳from different Q-segments at:')
    for race in mismatch_races:
        meta = next(r['meta'] for r in results.values() if
    ↳r['meta']['event_name'] == race)
        print(f"    {race}: ANT Q{meta['q_session_a']} vs RUS
    ↳Q{meta['q_session_b']} \u2014 track evolution likely confounds this delta")
if unknown_races:
    print('\u26a0 Q-session could not be determined for:', ', ', '.
    ↳join(unknown_races))
if not mismatch_races and not unknown_races:
    print('No Q-session mismatches across the 4 races.')

```

No Q-session mismatches across the 4 races.

1.2 Sensor quality

FastF1 telemetry doesn't carry an explicit quality flag, but a frozen **Speed** sensor produces a clear signature: only a handful of unique speed values across many samples within one segment. Any

segment that fails this check is excluded from the headline category analysis below — the per-segment time delta is also unreliable in those segments because cumulative Distance is integrated from the bad speed.

```
[4]: flagged = []
for r in results.values():
    bad = r['segments'][~r['segments']['sensor_ok']]
    for row in bad.itertuples():
        flagged.append({
            'race': r['meta']['event_name'],
            'segment': row.Segment, 'kind': row.kind, 'category': row.category,
            'min_speed_kph': round(row.min_speed, 1),
            'delta_s_pre_filter': round(row.delta_s, 3),
        })
if flagged:
    print(f"Flagged {len(flagged)} segment(s) where a driver's speed sensor_
↳looks frozen:")
    display(pd.DataFrame(flagged))
else:
    print('No sensor-freeze flags across the 4 races.')
```

Flagged 5 segment(s) where a driver's speed sensor looks frozen:

	race	segment	kind	category	min_speed_kph \
0	Japanese Grand Prix	S7	straight	straight	177.2
1	Japanese Grand Prix	C7	corner	medium_corner	189.0
2	Japanese Grand Prix	S8	straight	straight	189.0
3	Japanese Grand Prix	C8	corner	medium_corner	189.0
4	Japanese Grand Prix	S9	straight	straight	97.0

	delta_s_pre_filter
0	-3.555
1	-0.766
2	-1.663
3	-2.416
4	8.712

1.3 Sanity check

The segmentation logic is only useful if the segment deltas sum back to the actual lap-time delta. The table below verifies this on real telemetry: any $|\Delta|$ above 0.1 s would indicate a bug.

```
[5]: sanity = []
for race, r in results.items():
    sum_deltas = float(r['segments']['delta_s'].sum())
    lap_delta = float(r['meta']['lap_delta_s'])
    sanity.append({
        'Race': r['meta']['event_name'],
        '\u03a3 segment \u0394 (s)': round(sum_deltas, 4),
    })
```

```

        'Lap-time \u0394 (s)': round(lap_delta, 4),
        '|residual| (s)': round(abs(sum_deltas - lap_delta), 5),
    })
pd.DataFrame(sanity)

```

```

[5]:

```

	Race	Σ segment Δ (s)	Lap-time Δ (s)	residual (s)
0	Australian Grand Prix	-0.3838	-0.293	0.09084
1	Chinese Grand Prix	0.2352	0.222	0.01318
2	Japanese Grand Prix	0.2758	0.298	0.02216
3	Miami Grand Prix	0.3758	0.399	0.02316

```

[6]: cat_check = pd.concat([
    r['segments'].assign(event_name=r['meta']['event_name'])
    for r in results.values()
])
cat_check.groupby(['event_name', 'category']).size().unstack(fill_value=0)

```

```

[6]: category
event_name

```

	fast_corner	medium_corner	slow_corner	straight
Australian Grand Prix	3	1	3	8
Chinese Grand Prix	2	1	5	9
Japanese Grand Prix	2	5	1	9
Miami Grand Prix	2	0	4	7

1.4 Headline finding — where does the time go?

Each bar is the mean per-category delta across all four races. Black dots show each individual race's per-category mean — they tell you whether the average reflects a consistent pattern or a noisy one.

```

[7]: all_segs = pd.concat([
    r['segments'].assign(event_name=r['meta']['event_name'])
    for r in results.values()
], ignore_index=True)


# Exclude segments where either driver's speed sensor looks frozen - in those
# segments min_speed (and therefore the category label) is unreliable, and the
# per-segment delta itself can be wildly distorted by integrated-Distance error.
# See the "Sensor quality" cell below the summary table for which segments
# were dropped and why.
clean = all_segs[all_segs['sensor_ok']].copy()
n_excluded = len(all_segs) - len(clean)
print(f"Headline chart uses {len(clean)} segments after excluding {n_excluded}
    ↳with sensor-freeze flags.")

fig = plot_category_deltas(clean, save_path='../figures/headline_segment_delta.
    ↳png')
plt.show()

```

```
# Print the post-filter per-category means for the prose interpretation below
print("\nPer-category means after filtering (s/lap, positive = ANT faster):")
print(clean.groupby('category')['delta_s'].mean().round(4).to_string())
```

Headline chart uses 57 segments after excluding 5 with sensor-freeze flags.



Per-category means after filtering (s/lap, positive = ANT faster):

```
category
fast_corner      -0.0034
medium_corner    -0.0093
slow_corner       0.0088
straight          0.0051
```

The segment-level picture, after excluding five Japan segments where Antonelli’s speed sensor was frozen for ~1300 m of the lap, is quieter than I expected:

- **Straights:** essentially tied (+0.005 s/lap).
- **Slow corners (<130 kph):** essentially tied (+0.009 s/lap).
- **Fast corners (>200 kph):** essentially tied (−0.003 s/lap).
- **Medium corners (130–200 kph):** essentially tied (−0.009 s/lap).


Earlier versions of this analysis (before the sensor-quality filter was tightened) reported large per-category deltas — “+0.17 s/lap on straights” and “−0.46 s/lap in medium corners.” Both numbers turned out to be driven almost entirely by five segments at Japan where the speed sensor was stuck near 189 kph. Once those segments are removed, no single category emerges as the source

of Antonelli's lap-time advantage; the $+0.16$ s/lap mean over four races is spread across the whole lap rather than concentrated in any one phase.

The cleaner read: at four races and with one of them partially compromised, the trajectory finding (next section) is what the data actually supports.

1.5 Trajectory — is the gap closing?

```
[8]: fig = plot_lap_delta_by_round(meta_df, save_path='../figures/lap_delta_by_round.  
      ↪png')  
      plt.show()
```



Across four rounds, the lap-time gap has gone from -0.29 s (Russell faster by 0.29 s) at Australia to $+0.40$ s (Antonelli faster by 0.40 s) at Miami — a monotone trend in Antonelli's favour covering **0.69 s across four races**. Four data points is too few to project a trajectory with confidence, but the direction is striking: Antonelli was behind at Round 1 and ahead on every subsequent round, with the margin growing each time. Australia looks like the outlier round, not the norm.

1.6 Where on the track is each driver gaining time?

The category breakdown averages across each segment, but it can hide where exactly within a segment the time is found. Below, each circuit is shown as a track map coloured by the **local slope of the cumulative time delta** — the rate at which the gap is changing as the lap unfolds.

- **Blue** = Antonelli is gaining on Russell at that part of the track.
- **Red** = Russell is gaining on Antonelli.
- Corner numbers (from FastF1's `circuit_info`) are overlaid for orientation.


```
[9]: fig, axes = plt.subplots(2, 2, figsize=(13, 11))

# Precompute slopes for all 4 races so the color scale is shared across subplots
race_data = []
for race in RACES:
    session = load_qualifying_session(2026, race)
    lap_a = get_fastest_valid_lap(session, 'ANT')
    lap_b = get_fastest_valid_lap(session, 'RUS')
    res_a = resample_to_distance_grid(get_lap_telemetry(lap_a))
    res_b = resample_to_distance_grid(get_lap_telemetry(lap_b))
    n = min(len(res_a), len(res_b))
    # Cumulative delta(d) = Time_b(d) - Time_a(d); positive => ANT ahead at
    ↪ distance d
    delta = res_b['Time'].values[:n] - res_a['Time'].values[:n]
    # Local slope d(delta)/dd, smoothed over ~50 m to suppress sampling noise
    slope = np.gradient(delta)
    slope_smooth = pd.Series(slope).rolling(10, center=True, min_periods=1).
    ↪ mean().values
    race_data.append({
        'race': race,
        'x': res_a['X'].values[:n],
        'y': res_a['Y'].values[:n],
        'slope': slope_smooth,
        'corners': session.get_circuit_info().corners,
    })

# Shared symmetric color limit (95th percentile across all races)
all_slopes = np.concatenate([d['slope'] for d in race_data])
vmax = float(np.percentile(np.abs(all_slopes), 95))

last_mappable = None
for ax, d in zip(axes.ravel(), race_data):
    _, mappable = plot_track_delta_map(
        d['x'], d['y'], d['slope'], d['corners'],
        ax=ax, title=d['race'], vmax=vmax,
    )
    last_mappable = mappable

fig.suptitle(
    'Where Antonelli gains (blue) and where Russell gains (red)\nLocal rate of
    ↪ time gain/loss across the lap',
    fontsize=13,
)
cbar = fig.colorbar(last_mappable, ax=axes.ravel().tolist(), shrink=0.7, pad=0.
    ↪ 02,
                    orientation='horizontal', location='bottom')
```

```
cbar.set_label('d(time-delta)/d(distance) - negative: Russell gaining | 
↳positive: Antonelli gaining')
fig.savefig('../figures/track_delta_map.png', dpi=150, bbox_inches='tight')
plt.show()
```

```
core          INFO      Loading data for Australian Grand Prix - Qualifying
[v3.8.1]

req           INFO      Using cached data for session_info

req           INFO      Using cached data for driver_info

req           INFO      Using cached data for session_status_data

req           INFO      Using cached data for track_status_data

req           INFO      Using cached data for _extended_timing_data

req           INFO      Using cached data for timing_app_data

core          INFO      Processing timing data...

core          WARNING    No lap data for driver 18

core          WARNING    No lap data for driver 55

core          WARNING    Failed to perform lap accuracy check - all laps marked
as inaccurate (driver 18)

core          WARNING    Failed to perform lap accuracy check - all laps marked
as inaccurate (driver 55)

req           INFO      Using cached data for car_data

req           INFO      Using cached data for position_data

req           INFO      Using cached data for weather_data

req           INFO      Using cached data for race_control_messages

core          INFO      Finished loading data for 22 drivers: ['63', '12', '6',
'16', '81', '1', '44', '30', '41', '5', '27', '87', '31', '10', '23', '43',
'14', '11', '77', '18', '3', '55']

core          INFO      Loading data for Chinese Grand Prix - Qualifying
[v3.8.1]

req           INFO      Using cached data for session_info

req           INFO      Using cached data for driver_info

req           INFO      Using cached data for session_status_data

req           INFO      Using cached data for track_status_data

req           INFO      Using cached data for _extended_timing_data

req           INFO      Using cached data for timing_app_data

core          INFO      Processing timing data...
```

```


req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 22 drivers: ['12', '63', '44',
'16', '81', '1', '10', '3', '6', '87', '27', '43', '31', '30', '41', '5', '55',
'23', '14', '77', '18', '11']
core         INFO      Loading data for Japanese Grand Prix - Qualifying
[v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 22 drivers: ['12', '63', '81',
'16', '1', '44', '10', '6', '5', '41', '3', '31', '27', '30', '43', '55', '23',
'87', '11', '77', '14', '18']
core         INFO      Loading data for Miami Grand Prix - Qualifying [v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data

```

```

req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 22 drivers: ['12', '3', '16',
'1', '63', '44', '81', '43', '10', '27', '30', '87', '55', '31', '23', '41',
'14', '18', '77', '11', '5', '6']

```



1.7 Year-over-year: rookie vs sophomore

The within-2026 segment-level breakdown collapsed under the data-quality filter, but the lap-level comparison against 2025 — Antonelli’s actual rookie season at Mercedes — is far more striking. The cell below pulls the same 4 races from 2025 and plots both years on one chart.

At each of these tracks, Antonelli has gained between 0.3 and 0.7 s on Russell year-over-year. He’s not just continuing his rookie-year closing arc; he’s compressing it: he was almost a second behind Russell at his Australia debut and only just crossed ahead by Miami (R6) — in 2026 he started at -0.29 s and was ahead from R2 onwards.

```
[10]: # 2025: same 4 tracks (note: in the 2025 calendar Miami was R6, not R4)
results_2025 = {race: compare_teammmates(2025, race) for race in RACES}

# Build the lap-delta arrays in calendar order
deltas_2026 = [results[r]['meta']['lap_delta_s'] for r in RACES]
deltas_2025 = [results_2025[r]['meta']['lap_delta_s'] for r in RACES]

# Flag known caveats per (year, track): 2025 Australia had a Q-session mismatch
# (ANT's fastest was in Q1, RUS's in Q3 - track-evolution likely inflates the
↳ gap).
flagged_2025 = [results_2025[r]['meta']['q_mismatch'] for r in RACES]
flagged_2026 = [results[r]['meta']['q_mismatch'] for r in RACES]

# Year-over-year deltas (positive = ANT gained vs Russell since rookie year)
yoy_gains = [d26 - d25 for d25, d26 in zip(deltas_2025, deltas_2026)]
summary = pd.DataFrame({
    'Track': RACES,
    '2025 Δ (s)': [round(d, 3) for d in deltas_2025],
    '2026 Δ (s)': [round(d, 3) for d in deltas_2026],
    'YoY gain (s)': [round(g, 3) for g in yoy_gains],
    '2025 Q-mismatch?': flagged_2025,
})
display(summary)
print(f'Mean YoY gain across the 4 tracks: {sum(yoy_gains)/len(yoy_gains):+.3f}
↳ s')

fig = plot_yoy_lap_deltas(
    RACES, deltas_2025, deltas_2026,
    flagged_2025=flagged_2025, flagged_2026=flagged_2026,
    save_path='../figures/year_over_year.png',
)
plt.show()
```

```
core          INFO      Loading data for Australian Grand Prix - Qualifying
[v3.8.1]

req           INFO      Using cached data for session_info

req           INFO      Using cached data for driver_info

req           INFO      Using cached data for session_status_data

req           INFO      Using cached data for track_status_data

req           INFO      Using cached data for _extended_timing_data

req           INFO      Using cached data for timing_app_data

core          INFO      Processing timing data...

core          WARNING    Fixed incorrect tyre stint information for driver '4'
```

```

req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 20 drivers: ['4', '81', '1',
'63', '22', '23', '16', '44', '10', '55', '6', '14', '18', '7', '5', '12', '27',
'30', '31', '87']
core         INFO      Loading data for Chinese Grand Prix - Qualifying
[v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 20 drivers: ['81', '63', '4',
'1', '44', '16', '6', '12', '22', '23', '31', '27', '14', '18', '55', '10',
'87', '7', '5', '30']
core         INFO      Loading data for Japanese Grand Prix - Qualifying
[v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data

```


```

req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 20 drivers: ['1', '4', '81',
'16', '63', '12', '6', '44', '23', '87', '10', '55', '14', '30', '22', '27',
'5', '31', '7', '18']
core         INFO      Loading data for Miami Grand Prix - Qualifying [v3.8.1]
req          INFO      Using cached data for session_info
req          INFO      Using cached data for driver_info
req          INFO      Using cached data for session_status_data
req          INFO      Using cached data for track_status_data
req          INFO      Using cached data for _extended_timing_data
req          INFO      Using cached data for timing_app_data
core         INFO      Processing timing data...
req          INFO      Using cached data for car_data
req          INFO      Using cached data for position_data
req          INFO      Using cached data for weather_data
req          INFO      Using cached data for race_control_messages
core         INFO      Finished loading data for 20 drivers: ['1', '4', '12',
'81', '63', '55', '23', '16', '31', '22', '6', '44', '5', '7', '30', '27', '14',
'10', '18', '87']

```

	Track	2025 Δ (s)	2026 Δ (s)	YoY gain (s)	2025 Q-mismatch?
0	Australia	-0.979	-0.293	0.686	True
1	China	-0.380	0.222	0.602	False
2	Japan	-0.237	0.298	0.535	False
3	Miami	0.114	0.399	0.285	False


Mean YoY gain across the 4 tracks: +0.527 s



1.8 Per-race detail (appendix)

For each race, the raw per-segment delta. Useful for curious readers; not the main story.

```
[11]: fig, axes = plt.subplots(len(RACES), 1, figsize=(11, 2.6 * len(RACES)),
    ↪sharex=False)
    for ax, race in zip(axes, RACES):
        r = results[race]
        segs = r['segments'].sort_values('start_m')
        colors = ['#d62728' if d < 0 else '#1f77b4' for d in segs['delta_s']]
        ax.bar(segs['Segment'], segs['delta_s'], color=colors)
        ax.axhline(0, color='black', linewidth=0.6)
        ax.set_title(f"{r['meta']['event_name']} \u2014 \u0394 per segment
    ↪(positive = ANT faster)", loc='left', fontsize=10)
        ax.set_ylabel('\u0394 (s)')
        ax.tick_params(axis='x', rotation=45)
    fig.tight_layout()
    plt.show()
```

1.9 Caveats

- **Sample size: four races.** Findings are directional, not conclusive — and as the sensor investigation above shows, segment-level findings in particular are fragile to single-race data issues.
- **Q-session timing.** Q1 / Q2 / Q3 happen on an evolving track. The summary table flags any race where the two drivers' fastest valid laps came from different Q-segments.
- **Setup divergence.** Mercedes drivers do not always run identical setups. Public telemetry can't separate driver from setup.
- **Traffic and tire age within Q.** Out-laps, in-laps, and intra-session tire age all affect achievable lap time.
- **Telemetry sensor freezes.** FastF1's car telemetry occasionally stops reporting changes for long stretches. In this dataset, five Japan segments (S7, C7, S8, C8, S9 — covering D 4000 m to the end of the lap) are excluded by the sensor-quality filter above. Lap-level and sector-level deltas are unaffected — those come from timing-line beams, independent of the

car telemetry. Expect mild visual distortion at Japan’s T14–T18 in the track-delta map.

1.10 What I found

The strongest finding in this project is the **year-over-year comparison**. At each of the same 4 tracks, Antonelli has gained between 0.3 and 0.7 seconds on Russell relative to his 2025 rookie season (mean **+0.53 s/track**). He started his rookie year almost a full second behind Russell at Australia and took until Miami (R6) to first cross ahead; in 2026 he started at -0.29 s and was ahead from R2 onwards. The rookie-year closing arc is being compressed, not just sustained.

The within-2026 trajectory — Antonelli being faster every round from R2 onwards, mean $+0.16$ s — is the second-strongest finding, and sector-time data confirms each lap-level delta independently of car telemetry.

The segment-level breakdown turned out to be much quieter than I first thought. My initial pass reported a $+0.17$ s/lap straights advantage and a -0.46 s/lap medium-corner deficit, but both numbers were almost entirely driven by five Japan segments where Antonelli’s speed sensor was frozen near 189 kph for over 1.3 km of the lap. Once those segments are excluded, every category collapses to 0 s/lap (± 0.01). At $n=4$ races and with one of them partially compromised, the segment-level story I went looking for didn’t survive the data-quality check — which is worth noting, even if it wasn’t the finding I initially wanted.

I’ll re-run the same framework after each 2026 race — see [What I’d build next](#) for the extensions.