

THESIS TITLE CENTERED ON THE PAGE VERTICALLY AND HORIZONTALLY,
IN ALL UPPER CASE LETTERS AND IN AN INVERTED PYRAMID

SHAPE. MATH MODE: $\frac{2^{15}}{\pi}$

by

Student Name

Copyright by Student Name 2020

All Rights Reserved

A thesis submitted to the Faculty and the Board of Trustees of the Colorado School of Mines in partial fulfillment of the requirements for the degree of Doctor of Philosophy (Computer Science).

Golden, Colorado

Date _____

Signed: _____

Student Name

Signed: _____

Dr. Thesis Advisor
Thesis Advisor

Golden, Colorado

Date _____

Signed: _____

Dr. Department Head
Professor and Head
Department of XXX

ABSTRACT

The abstract is a concise, one to three sentence statement of the thesis problem, a brief description consisting of no more than a few sentences describing the research method or design, and a report of the major findings and conclusions.

The abstract submitted online at the time of thesis submission should be the same as the abstract inside the thesis. ProQuest continues to publish print indexes that have maximum abstract lengths of 150 words for Masters and 350 words for PhDs. Abstracts exceeding these limits will be truncated in the print indexes so it may be wise to work within those word limits in most cases.

THESIS TITLE CENTERED ON THE
PAGE VERTICALLY AND HORIZONTALLY,
IN ALL UPPER CASE LETTERS AND IN AN INVERTED PYRAMID SHAPE. MATH

MODE: $\frac{2^{15}}{\pi}$

Thesis title centered on the page vertically and horizontally,
in all upper case letters and in an inverted

pyramid shape. Math mode: $\frac{2^{15}}{\pi}$

THESIS TITLE CENTERED ON THE
PAGE VERTICALLY AND HORIZONTALLY,
IN ALL UPPER CASE LETTERS AND IN AN INVERTED PYRAMID SHAPE. MATH

MODE: $\frac{2^{15}}{\pi}$

Thesis title centered on the page vertically and horizontally,
in all upper case letters and in an inverted
pyramid shape. Math mode: $\frac{2^{15}}{\pi}$

by
author

calibrating the response of a GPR system is essential for making measurements of subsurface materials properties. Duke (1990) calibrated the overall response of a GPR system by making measurements of the . . . 1.1 Background and Previous Work This chapter describes the methodology that has been used to determine the response of an impulse GPR. The characterization includes a response function for the receiving electronics, simulations . . . 1.2 Signal Processing Tools There are many techniques for making high frequency electrical measurements in electrical networks and antenna systems, and there are also many methods for manipulating the data from these measurements . . . 1.2.1 Convolution and Deconvolution Methods Convolution is a mathematical operation that can be used to describe how a linear network element modifies a signal as the signal passes through it . . . 1.2.2 Scattering Parameters

calibrating the response of a GPR system is essential for making measurements of subsurface materials properties. Duke (1990) calibrated the overall response of a GPR system by making measurements of the . . . 1.1 Background and Previous Work This chapter describes the methodology that has been used to determine the response of an impulse GPR. The characterization includes a response function for the receiving electronics, simulations . . . 1.2 Signal Processing Tools There are many techniques for making high frequency electrical measurements in electrical networks and antenna systems, and there are also many methods for manipulating the data from these measurements . . . 1.2.1 Convolution and Deconvolution Methods Convolution is a mathematical operation that can be used to describe how a linear network element modifies a signal as the signal passes through it . . . 1.2.2 Scattering Parameters