Using an LLM to retrieve text, tables and images in a chatbot with RAG

Using an LLM to retrieve text, tables **and** images in a chatbot with RAG — the multi-modal, grounded, self-hosted rewrite
- The problem this solves (still the whole point)
- The big picture (how it works in three parts)
- What changed since the 2025 article (the honest changelog)
- Part 1: Ingestion — now smarter, and format-agnostic
- Part 2: The chatbot — grounded, conversational, and inline
- Part 3 (new): An embeddable chat widget for any website
- Security: defending a RAG app from the documents themselves
- Running it (so much simpler now)
- Proving it works: an offline evaluation harness
- Observability: you can finally see what the bot did
- Honest limitations (the questions a sharp reader will ask)
- How it compares to other RAG approaches
- Why bother keeping tables and images?
- Toolset (2026)
- References

Using an LLM to retrieve text, tables and images in a chatbot with RAG — the multi-modal, grounded, self-hosted rewrite

By Milind Agarwal · ~15 min read

> **A note on this edition.** I first published this article in January 2025 with a simple idea: a technical document is more than text, so a chatbot that answers questions about it shouldn't throw away the tables and images during ingestion. That core idea still stands — but almost everything around it has grown up since. What started as two Python files and an `http.server` for avatars is now a self-hostable product: local offline


> embeddings, a pluggable answer engine (cloud **or** a local offline model **or** no model at all), PowerPoint support, grounded “I don’t know” answers with per-claim citations, an embeddable one-line chat widget for any website, a Docker Compose stack, Postgres Q&A logging, prompt-injection defense, and an offline evaluation harness. This is the 2026 rewrite. If you read the original, you’ll recognize the heart of it — it just wears a lot more armor now.

The problem this solves (still the whole point)

In a technical document there is not just text, but images and tables too. Those images carry important information — architecture diagrams, formulas, flowcharts. The tables carry specifications, parameters, limits. Very often these images and tables convey more value than the prose around them.

If you build a chatbot to query such documents with a plain RAG approach, you first create a vector database — embeddings of chunks of the document’s **text**. During that embedding step the image and table information is simply ignored and lost. Even if you scrape the text out of a table, you lose the table’s **structure**. So when you query that store, all you get back is text — minus the images, minus the tables. Which is frequently unhelpful to the end user, and doesn’t exactly inspire confidence in the answer.

What if we could retrieve the tables and images too? That was the original ask, and the approach is the same: be a little **smart during ingestion** (extract and save the tables/images, keyed by document + page), and use a little **ingenuity at query time** (reconstruct those assets from metadata and render them inline next to the answer). Keep the page number and document name attached to everything, so every answer is **explainable** — the user can jump straight to the source page. That’s the XAI (explainable AI) angle, and it matters more than ever.



The same source document, two pipelines. Plain RAG (left) embeds only text, so tables are flattened and images are discarded — the query returns text alone. This approach (right) keeps the tables and images and even embeds each table's content as its own searchable chunk, so the answer comes back grounded, with the real table/figure inline and a page citation.

What's new is how well we can do all of this now, and how production-ready the whole thing has become. Let me walk you through it. As before — bear with me to the end.


The big picture (how it works in three parts)

The original article had two parts: ingestion and the chatbot. There's now a third.

- **Part 1 — Ingestion (`embeddingEngine.py`).** For each **PDF page or PPTX slide**, extract text, tables, and images. Embed the text — and the table content itself — into a Chroma vector store with metadata. Save tables and images to disk keyed by document + page. A small dispatcher routes `.pdf` and `.pptx` to the right extractor; **slides map to page numbers**, so everything downstream treats a deck exactly like a PDF.
- **Part 2 — Chatbot (`chatBOT_engine.py`).** A Streamlit chat app. For a follow-up question it first **rewrites** the question into a standalone query using recent history, runs MMR vector search,

then **streams a single synthesized answer** grounded in the retrieved context with inline `[document p.N]` citations. Based on sidebar toggles it also reconstructs and renders the images/tables from the **cited** pages, offers a download of each cited source, and suggests clickable follow-ups.

- **Part 3 — Embeddable widget (`api_server.py` + `widget/`).** The same retrieval and answer logic (via a shared, UI-free `generate_answer()`) exposed over an HTTP API (FastAPI) plus a one-line JavaScript widget that drops a floating chat bubble onto any website.



The whole pipeline at a glance: ingestion (left) extracts text, tables, and images and splits them between the Chroma vector store and an on-disk sidecar store; the query side (right) retrieves, generates a grounded answer with a pluggable engine, and renders it — the same *`generate_answer()`* core feeding both the Streamlit app and the embeddable widget.



Ask a question → get a synthesized answer with the **actual table from the source page** rendered inline, and a `[document p.N]` citation. Most RAG apps would have lost that table during ingestion.

What changed since the 2025 article (the honest changelog)

If you only read one section, read this one.

Area	2025 (original)	2026 (now)
Embeddings	`sentence-transformers` (`all-mpnet-base-v2`), PyTorch	`fastembed` ONNX (`BAAI/bge-small-en-v1.5`) — **local, offline, no PyTorch**
Answer generation	`facebook/bart-large-cnn` summarizer per chunk (no synthesis)	**Pluggable, single-select:** Claude (API) · Qwen 1.5B (local, offline) · None (extractive). One synthesized, streamed answer
Formats	PDF only	PDF **and PowerPoint (PPTX/PPT)** — slides map to pages
Table searchability	Table saved, but only prose was embedded	Each table's **content is embedded as its own chunk** — a query matching cell values finds the page
Citations	Page links appended per chunk	**Inline** `[document p.N]` per claim; assets scoped to cited pages only
Groundedness	Summaries, could drift	**Grounded refusal** ("I don't know") + a **low-confidence banner**
Conversation	Flat history map	**Follow-up rewriting** ("what about at 85°C?") + **suggested follow-ups**
Asset serving	`python -m http.server 8000`, `http://localhost:8000/...` links	Images/PDFs/tables **inlined as base64/HTML** — no companion server
Admin	CLI only	**Web admin console** — upload/delete, pick engine, tune everything
Re-ingest	`reset_collection()` every run	**Content-hash upsert** — identical bytes skipped, changed bytes replaced, no duplicates
Deployment	Run two terminals by hand	**Docker Compose** — 5 services, one command
Logging	`print()` for debugging	**Structured per-query logs** + **Postgres Q&A history**
Security	—	**Prompt-injection defense** (fenced untrusted context), path-traversal-safe source serving
Quality proof	—	**Offline evaluation harness** (recall@k + confidence calibration), CI-gating

Let’s go through the ones that change how you’d build this.

Part 1: Ingestion — now smarter, and format-agnostic

Local, offline embeddings (goodbye PyTorch)

The original used `SentenceTransformerEmbeddings(model_name="all-mpnet-base-v2")`, which pulls in PyTorch. The rewrite uses **`fastembed`**, which runs the embedding model as ONNX — no PyTorch, smaller install, fully offline after a one-time ~130 MB model download. The vector store construction is centralized in one function that ingestion and the chatbot both call, so the embedding model can never drift between write and read (a classic “empty answers / dimension mismatch” footgun):

```
def
    """Return the shared Chroma vector store (same config everywhere)."""
                    =                              ="BAAI/bge-small-en-v1.5"
    return
        "Project_NAME"

        "./chroma_Name"
                        = "hnsw:space"  "cosine"
```

One dispatcher, two formats (PDF and PowerPoint)

The original was PDF-only and noted you could extend it. I did. A tiny dispatcher routes files to the right extractor, and — this is the trick that keeps everything downstream simple — **a slide’s index is treated as its page number**. So a deck behaves exactly like a PDF everywhere else in the app:

```
def
          =
    if              ".pdf"
        return
    if               ".pptx"  ".ppt"
        return
    raise ValueError f"Unsupported file type: {       }"
```

`python-pptx` gives us slide text, **native PowerPoint tables**, and **inserted raster pictures**. (Charts, SmartArt, and vector graphics aren't raster images, so they aren't extracted — reference them in text, or paste them as a picture if you need them rendered.)

The "page-as-anchor" sidecar store (unchanged idea, cleaner code)

The join key between embedded text and non-text assets is still **`file_name` + `pagenumber`**. Every text chunk is embedded with metadata flags saying whether its page has an image/table, and the assets live on disk at predictable paths:

Asset	Extracted with (PDF / PPTX)	Stored as
Text	`pymupdf4llm` / `python-pptx` text frames	embedding in Chroma
Tables	`pymupdf find_tables` / `python-pptx` table shapes	pickled DataFrame `table/<doc>/<page>/tableN.pkl`
Images	`Spire.PDF` ImageHelper / `python-pptx` pictures	PNG `pdf/<doc>/<page>/imageN.png`

Tables are now semantically searchable (not just stored)

This is one of my favorite upgrades. In 2025 I saved the table to disk but only embedded the prose on the page — so if the answer lived **inside** the table, a content query might never pull that page. Now each extracted table is flattened to a label-rich text form and embedded as its **own** chunk (`contentType: "table"`):

```
        def
            """Convert an extracted table to a flat text representation for embedding —
            cell values matter more than exact layout. The first row is the header, so
            we emit lines like '<header>: <value> | <header>: <value>' and a query
            matching cell values retrieves the table's page."""
                 =
            if not
                return ""
                   =   "" if   is None else               "\n"  " "           for   in      0
                  =  "Table columns: " + " | "        for   in        if
            for     in      1
                      =
                for          in
                         = "" if     is None else                  "\n"  " "
                    if not
                        continue
                          =             if     <             and             else f"col{   }"
                                f"{     }: {    }"
                if
                                " | "
            return "\n"
```

So now “what’s the VBUS current?” can retrieve a page because the number is in a table cell, not because the prose happened to mention it.

Re-embedding is a safe upsert (no more `reset_collection()`)

The original reset the whole collection on every run to avoid duplicates — fine for a full rebuild, terrible for incrementally adding one document. Now every document is content-addressed by a SHA-256 of its bytes, stored on each chunk as `doc_hash`:

```
        def
            """A content-addressed ID: SHA-256 of the raw bytes. Same bytes (even under a
            different name) → same hash, so a no-op re-embed is detected and skipped.
            Streamed in blocks so big files don't load fully into memory."""
              =
            with                "rb"
                for       in      lambda         1024 * 1024   b""

            return
```

Re-embedding **identical** content is a no-op. Re-embedding **changed** content (or the same filename with new bytes) deletes the old chunks + stale assets first, then re-adds. Duplicates never accumulate — and you never nuke your whole store to add one file.

Part 2: The chatbot — grounded, conversational, and inline

From per-chunk summaries to one synthesized, grounded answer

The 2025 version ran each retrieved chunk through a BART summarizer and concatenated the results. It was honest about the trade-off — detailed but not clean. The rewrite retrieves with **MMR** (`k=8, fetch_k=24, lambda_mult=0.6`, for better recall and less near-duplicate noise) and produces **one** synthesized answer that **streams in**, with inline `[document p.N]` citations for each claim.

Crucially, it's **grounded**: if the retrieved context doesn't contain the answer, the assistant says it doesn't know rather than inventing something. On such a refusal it shows **no** source downloads, figures, or follow-ups (those would reflect off-topic chunks, not your question). A **low-confidence banner** appears when the best retrieval score falls below a configurable threshold (default **0.63**, which — nice touch — is backed by the evaluation harness, not guessed).

The answer engine is pluggable (and can be no engine)

This is the biggest conceptual change. The answer backend is **single-select**, chosen in the admin GUI and stored in `config.json`. The chatbot reads it once per session and uses it transparently — chat users never see or pick the engine:

Provider	What it does	Requirements	Notes
Claude (Anthropic API)	Streamed synthesis, reliable inline citations — best quality	`ANTHROPIC_API_KEY`	Fast
Qwen 1.5B (local SLM)	Same synthesis, **fully offline**	`llama-cpp-python` + a ~1 GB GGUF	Slow on CPU (~1–2 min/answer); may omit citation markers
None (extractive)	No generation — shows retrieved passages verbatim under `[file p.N]` headers	nothing	Instant, zero-cost, no key

And there's an **auto-fallback**: if the selected provider isn't actually available at runtime (missing key, missing GGUF), it silently falls back to extractive so the app never breaks. A fresh clone defaults to `none` and runs with no key and no model download. This means the whole thing can run **100% offline** (local embeddings + Qwen or extractive = no outbound calls) — which matters a lot for confidential docs.

Follow-ups that actually understand context

Ask "What's the Pico's VBUS current?" then "What about at 85°C?" — the second question is meaningless to a retriever on its own. So before searching, the app **rewrites** it into a standalone query using recent history:

```
        def
            """Rewrite a context-dependent follow-up into a standalone retrieval query
            using recent chat history. No-ops for the first turn, clearly self-contained
            questions, or extractive mode."""
            if          == "none"
                return
            if not
                return
                    =
            if not
                return
                   =
                "You rewrite a user's latest message into a single standalone search "
                "query by resolving pronouns and references using the conversation. "
                "Output ONLY the rewritten query as one line — no preamble, no quotes. "
                "If the message is already self-contained, output it unchanged."

                 = f"Conversation:\n{       }\n\nLatest message: {        }\n\nStandalone query:"
                      =                                          =80
                  =             for    in            or ""              if
                      =       0        '"'          if       else ""
            if not           or               > 300    # guard against junk rewrites
                return
            return
```

The app also suggests clickable follow-up questions under each answer (suppressed when the question was out of context or low-confidence).

Assets render inline — no more companion web server

In 2025 the templates linked to `http://localhost:8000/AI.png` and friends, so you had to run `python -m http.server 8000` in a second terminal just to see avatars and download links. Now **images, source PDFs, and tables are inlined directly into the page** — images and PDFs as base64 `data:` URIs, tables as HTML — so **no static file server is needed**. One service runs the whole chatbot. (Very large source PDFs >8 MB are shown as a plain filename label instead of an inline download, to keep the page light.) And attribution is scoped to the pages the answer **actually cited**, so a chunk retrieval pulled in but the answer didn't use won't leave a stray asset behind.


There's also a **"Prepare PDF of chat"** button that exports the whole conversation — images and tables included — via `xhtml2pdf`.

Part 3 (new): An embeddable chat widget for any website

The same RAG backend is now exposed as a one-line embeddable widget. A site owner adds a single tag before `</body>`:

```
<script src="https://YOUR_HOST/widget/widget.js"
        data-api="https://YOUR_HOST/api"></script>
```

That drops a floating chat bubble on the page which talks to a **FastAPI** backend (`POST /api/chat`, `GET /api/health`, `GET /api/source/{name}`) and renders answers with clickable source citations and suggested follow-ups. The widget and the Streamlit app share the **exact same** `generate_answer()` core — there's no second implementation to keep in sync.



The embeddable widget open on a host page with inline citations and suggested follow-ups

The `/api/source/{name}` endpoint only serves whitelisted document types by basename, with path-traversal protection. A demo site (a fake third-party page on a different origin) is included to prove the cross-origin embed works.

> **Honest caveat (and my top roadmap item):** the API and Streamlit app are currently **open and unauthenticated**, with open CORS. That's fine for a local demo, but before any public or multi-user deployment you must add auth, an origin allowlist, rate limiting, and request-size caps — especially for internal/confidential material.

Security: defending a RAG app from the documents themselves

A RAG app pastes retrieved document text straight into the LLM prompt. So a poisoned document could carry text like “ignore previous instructions and…” — an **indirect prompt injection**. The rewrite defends against this by fencing the retrieved context as untrusted data and establishing an instruction hierarchy in the system prompt (everything inside the fence is data to quote and cite, never instructions to obey):

```
        def
            """Wrap retrieved context in untrusted-data delimiters referenced by the
            system prompt. Any occurrence of the delimiter tokens *inside* the document
            is stripped first, so a malicious document can't forge the closing marker to
            escape the data region and inject trusted instructions."""
                 =          or ""                       ""                    ""
            return f"{          }\n{    }\n{       }"
```

The defense applies to both generative providers (extractive mode has no LLM, so it’s inherently immune), and it’s regression-tested. Output rendering is injection-safe too: the widget inserts text via `textContent` (HTML-escaped), and the Streamlit app only uses `unsafe_allow_html` for its own figure/table HTML built from local files — never for model output.

Running it (so much simpler now)

One command, locally

```
                -m            &&
                    --upgrade     &&            -r                  # there IS a requirements.txt
now
        cp                                # add ANTHROPIC_API_KEY only if you want Claude
        mkdir -p          && cp            *          && cp          *
                                          # build store + extract images/tables
                                          # → http://localhost:8501
```

No second terminal for a file server. No PyTorch. No API key unless you opt into Claude.


The whole stack in Docker

```
cp
                    --build
```

That brings up **five services**: the chatbot (`:8501`), the admin GUI (`:8502`), the widget API (`:8000`), a demo site (`:9000`), and a Postgres `db` for Q&A logging. Config lives in a mounted `config.json`, so you can retune the app without a redeploy.

A web admin console (no CLI required)

Upload or delete documents (with a pages/tables/images summary), pick the answer engine, tune the confidence threshold, edit every piece of user-facing text, set the widget theme, configure logging, and browse the Q&A history — all from a tabbed Streamlit UI.



The admin console on the Documents tab

Proving it works: an offline evaluation harness

I added something the original lacked entirely — a way to **measure** retrieval quality with evidence, so I can catch regressions and tune settings instead of guessing. It's **embedding-only (no LLM calls, no API cost)** and drives the same functions the chatbot uses:

```
            -m                          # human-readable report + pass/fail
            -m              --json
```

It reports two things:

- **Retrieval recall@k** — for each ground-truth question, is the expected page in the top-k retrieved chunks? It exits non-zero below a `recall_floor`, so retrieval regressions are caught in CI before users see them.
- **Confidence calibration** — the score distributions for in-corpus vs off-topic questions, and a **suggested `low_confidence_threshold`** sitting in the gap between them. (That's where the 0.63 default came from: in-corpus min ≈0.65, off-topic max ≈0.61.)

The reference set is plain JSON of human-asserted question→page pairs, and it adapts to a changing store — a question whose document isn't currently embedded is skipped, not failed.

Observability: you can finally see what the bot did

Every answered question logs **one structured line** (provider, retrieval breadth, best relevance score, low-confidence/refusal flags, source count, latency), and — for both the chatbot and the widget — a row in a Postgres `qa_log` table (`asked_at`, `source`, `question`, `answer`, `provider`, `best_score`, `sources` as JSONB, `latency_ms`, …). Logging is **fail-safe**: if Postgres is unreachable, answering still works and the write silently no-ops, failing fast so it never adds latency. The admin console's Q&A History tab gives you stats, filters, a read-only table, CSV export, and retention purge.


Honest limitations (the questions a sharp reader will ask)

- **No authentication yet.** The app and widget API are open — top-priority before any public/multi-user deployment.
- **The widget is text + citations only** today — no streaming, no inline figures/tables (the Streamlit app has all three).
- **No OCR** — scanned/image-only PDFs aren't text-extracted.

- **Non-raster graphics** (charts, SmartArt, vector art) aren't extracted as images.
- **Local Qwen is slow on CPU** (~1–2 min/answer) and may omit inline citation markers — use Claude when speed and strict citations matter.

How it compares to other RAG approaches

People reasonably ask: why not just use a hosted upload-and-chat SaaS, assemble something with LangChain yourself, buy an enterprise RAG platform, or paste the PDF into a general LLM chat? Each of those is a legitimate choice — they just optimize for different things. Here's the honest positioning across the capabilities this project leads with (these are general category characteristics; verify specifics against any given vendor's current docs):



Capability comparison: this project vs hosted SaaS doc-chat, DIY framework, enterprise RAG platform, and general LLM chat with file upload

The short version:

- **vs. hosted SaaS doc-chat** — this wins on data residency (fully self-hosted, can be offline), table/figure fidelity (most SaaS flatten to text), no per-seat/token bill, and a white-labelable widget. They win on turnkey auth/SSO and multi-tenant user management out of the box — which is still a roadmap item here.

- **vs. a DIY framework stack** — this is a finished, runnable product (ingestion + chat + admin GUI + widget + Docker + eval harness), not a toolkit you assemble. They win on unlimited flexibility and a huge connector ecosystem.
- **vs. an enterprise RAG platform** — this wins on footprint, cost, transparency (open, inspectable code and prompts), and offline capability. They win on enterprise auth/RBAC, SharePoint/Confluence connectors, compliance certs, SLAs, and scale/HA.
- **vs. general LLM chat with file upload** — this wins on a persistent indexed corpus (no re-uploading per chat), exact-page attribution, rendered tables/figures, and grounded refusal. They win on general reasoning breadth and zero setup for a one-off.

The one row where this project is honestly behind is **enterprise auth** — it's the top of my roadmap, and I'd rather state it plainly than hide it.

Why bother keeping tables and images?

Same reason as 2025, and it's held up: for technical readers, the artifact often **is** the answer. A spec table or an architecture diagram tells them what they need far faster than a paragraph summarizing it — and seeing the real table, on the real cited page, builds the trust that a bare generated sentence never will. What's new is that the whole thing is now grounded (it refuses when it doesn't know), self-hostable and offline-capable (nothing has to leave your machine), embeddable anywhere, and provable (the eval harness).

If you read the original: thank you, and the heart of it is unchanged. It just grew up.

Toolset (2026)

- **Embeddings:** `fastembed` ONNX, `BAAI/bge-small-en-v1.5` (local, offline, no PyTorch)
- **Answer engine:** Claude (API) · Qwen 1.5B GGUF via `llama-cpp-python` (local) · None (extractive)
- **Retrieval / store:** Chroma with MMR (`k=8, fetch_k=24, lambda_mult=0.6`)

- **PDF:** `pymupdf4llm` (text), `pymupdf` / `fitz` (tables), `Spire.PDF` (images)
- **PPTX:** `python-pptx` (text, native tables, pictures)
- **UI:** Streamlit chat primitives · **Widget:** vanilla JS · **API:** FastAPI
- **Chat-to-PDF:** `xhtml2pdf` · **Q&A logging:** Postgres via `psycopg` 3
- **Deployment:** Docker Compose (5 services)

References

- Streamlit — https://docs.streamlit.io/
- LangChain — https://python.langchain.com/docs/introduction/
- Chroma — https://www.trychroma.com/
- PyMuPDF / pymupdf4llm — https://pymupdf.readthedocs.io/en/latest/pymupdf4llm/index.html
- fastembed — https://github.com/qdrant/fastembed
- llama.cpp / llama-cpp-python — https://github.com/abetlen/llama-cpp-python

GitHub: Naina2023/ChatBOT