

Zida Wu

<https://milkytip.github.io/>

Address: 200240 Jianchuan Road, Minhang, Shanghai

Phone: (+86)18616548805 Email: wuzida@sjtu.edu.cn

EDUCATION

Shanghai Jiao Tong University

September 2017 - Present

Master of Electronics and Communication Engineering
Department of Electronic and Electrical Engineering

Xidian University

September 2013 - July 2017

Bachelor of Telecommunication Engineering
Department of Telecommunication Engineering

AWARDS

Third prize of the 15th China Graduate Mathematical Modelling Contest	<i>December 2018</i>
Chinese National Graduate Scholarship (top 3%)	<i>November 2018</i>
Merit Student Prize of Shanghai Jiao Tong University (top 5%)	<i>October 2018</i>
First Prize Scholarship of Shanghai Jiao Tong University (top 20%)	<i>September 2017</i>
Outstanding Graduates of Xidian University (top 5%)	<i>July 2017</i>
Pacesetter of Outstanding Volunteer (top 1‰)	<i>September 2016</i>
Second Prize Scholarship of Xidian University	<i>September 2015</i>
First Prize Scholarship of Xidian University	<i>September 2014</i>

PUBLICATIONS

Z. Wu, and P. Liu, “Pseudorange Double Difference and PDR Fusion Algorithm Using Smartphone GNSS Raw Measurements”, in *2019 China Satellite Navigation Conference (CSNC) (Oral)*.

A. Rehman, Q. Liu, Z. Wu, H. Zhu, J. Qian, et al. “PDR/GNSS Fusion Algorithm Based on Joint Heading Estimation”, in *2019 China Satellite Navigation Conference (CSNC)*.

Z. Wu, P. Liu, Q. Liu, et al. “MEMS-based IMU Assisted Real Time Difference Using Raw Measurements from Smartphone”, in *2018 International Technical Meeting of The Satellite Division of the Institute of Navigation (ION GNSS+)*.

A Positioning System under GNSS Double Difference for Portable Intelligent Devices [P]. *Chinese National Invention Patent. (Patent No. CN201810091248.1)*.

RESEARCH

Intelligent Robotic Navigation and Manipulation System

*Agency for Science, Technology and Research (A*STAR) of Singapore July 2019 - September 2019*

- Developed a docking SLAM method that tracks moving objects with cm-grade docking accuracy for autonomous vehicles.
- Constructed an images fusion module to combine the masks of object and depth geometry segmentation, and used omnidirectional wheels to avoid large rotation under close range.
- Such a system may be deployed in autonomous factories, to dynamically follow mobile target and then implement docking and mechanical grab.

Multi-sensor Fusion for Inspection Robot

Shanghai Jiao Tong University

December 2018 - Present

- Introduced a loose-coupled framework that fuses IMU, SLAM, GNSS and other sensors separately, which tolerates single sensor failure during operation.
- Applied an error-state Kalman Filter to optimize the independent poses from SLAM and IMU, and fed back into the nominal states to acquire the genuine pose.
- A second error-state filter was utilized to fuse the GNSS measurements to prevent state estimation drift in long-term operation.
- This algorithm achieved seamless and continuous positioning at large-distance scale (km-grade) across the indoor and outdoor environments.

Bluetooth Indoor Positioning System

Shanghai Jiao Tong University

August 2018 - October 2018

- Aimed to realize accurate Bluetooth signal arrival-of-angle (AOA) estimation, using single channel 6-antenna array.
- Solved the phase drift problem caused by antenna switch and multipath by dynamic signal polarization switch and intermittent sampling with frequency compensation.
- The algorithm achieved 5-degree accuracy in estimating the AOA of Bluetooth signal, which means cm-grade localization accuracy could be achieved with this system.

High-accuracy GNSS Positioning on Portable Smartphone

Shanghai Jiao Tong University

July 2017 - August 2018

- Developed an algorithm which achieved high-accuracy and reliable positioning of smartphones under complex environment using GNSS-IMU fusion.
- Utilized the pseudorange double-difference (PDD) to eliminate the atmosphere, satellite, and phone clock error, as well as decoupled the pseudorange and velocity measurements based on the short-baseline hypothesis.
- Joint heading estimation using Pedestrian Dead Reckoning (PDR) and GNSS Doppler.
- This algorithm calibrated the PDR gait length loss and heading drift in the long-term, and maintained high smooth and accuracy in the short-term.

TEACHING EXPERIENCE

Teaching assistant of Digital Signal Processing

Autumn 2018

Instructor: Prof. Xiangming Geng

TECHNICAL STRENGTHS

Programming Languages

C/C++, Python, MATLAB, Java, LaTeX, Markdown

Software Platforms

ROS, Linux, Android, Windows

Hardware Platforms

Jetson, Arduino, NUC, eZdsp 5535