

クラス LineWidthPanel

java.lang.Object

java.awt.Component

java.awt.Container

javax.swing.JComponent

javax.swing.JPanel

LineWidthPanel

すべての実装されたインタフェース:

java.awt.image.ImageObserver, java.awt.MenuContainer, java.io.Serializable,

javax.accessibility.Accessible

class **LineWidthPanel**

extends javax.swing.JPanel

線の太さと塗りつぶしを設定する Panel

ネストされたクラスのサマリー

ネストされたクラス	
修飾子とタイプ	クラスと説明
(package private) class	LineWidthPanel.CbxListener
(package private) class	LineWidthPanel.SldListener
(package private) class	LineWidthPanel.SpnListener

クラスから継承されたネストされたクラス/インタフェース javax.swing.JPanel

javax.swing.JPanel.AccessibleJPanel

クラスから継承されたネストされたクラス/インタフェース javax.swing.JComponent

javax.swing.JComponent.AccessibleJComponent

クラスから継承されたネストされたクラス/インタフェース java.awt.Container

java.awt.Container.AccessibleAWTContainer

クラスから継承されたネストされたクラス/インタフェース java.awt.Component

java.awt.Component.AccessibleAWTComponent, java.awt.Component.BaselineResizeBehavior, java.awt.Component.BltBufferStrategy, java.awt.Component.FlipBufferStrategy

フィールドのサマリー

フィールド

修飾子とタイプ	フィールドと説明
private javax.swing.JCheckBox	cbx 塗りつぶすかどうかを設定する CheckBox
private boolean	fill 塗りつぶすかどうか
private DrawModel	model
private Pen	pen
private javax.swing.JSlider	sld 線の太さを設定する Slider
private int	SLD_MAX
private javax.swing.JSpinner	spn 線の太さを設定する Spinner

クラスから継承されたフィールド javax.swing.JComponent

listenerList, TOOL_TIP_TEXT_KEY, ui, UNDEFINED_CONDITION, WHEN_ANCESTOR_OF_FOCUSED_COMPONENT, WHEN_FOCUSED, WHEN_IN_FOCUSED_WINDOW

クラスから継承されたフィールド java.awt.Component

accessibleContext, BOTTOM_ALIGNMENT, CENTER_ALIGNMENT, LEFT_ALIGNMENT, RIGHT_ALIGNMENT, TOP_ALIGNMENT

インタフェースから継承されたフィールド java.awt.image.ImageObserver

ABORT, ALLBITS, ERROR, FRAMEBITS, HEIGHT, PROPERTIES, SOMEBITS, WIDTH

コンストラクタのサマリー

コンストラクタ

LineWidthPanel(**DrawModel** model, **Pen** pen)

新しい LineWidthPanel を作成します

メソッドのサマリー

クラスから継承されたメソッド javax.swing.JPanel

getAccessibleContext, getUI, getUIClassID, paramString, setUI, updateUI

クラスから継承されたメソッド javax.swing.JComponent

addAncestorListener, addNotify, addVetoableChangeListener, computeVisibleRect, contains, createToolTip, disable, enable, firePropertyChange, firePropertyChange, firePropertyChange, fireVetoableChange, getActionForKeyStroke, getActionMap, getAlignmentX, getAlignmentY, getAncestorListeners, getAutoscrolls, getBaseline, getBaselineResizeBehavior, getBorder, getBounds, getClientProperty, getComponentGraphics, getComponentPopupMenu, getConditionForKeyStroke, getDebugGraphicsOptions, getDefaultLocale, getFontMetrics, getGraphics, getHeight, getInheritsPopupMenu, getInputMap, getInputMap, getInputVerifier, getInsets, getInsets, getListeners, getLocation, getMaximumSize, getMinimumSize, getNextFocusableComponent, getPopupLocation, getPreferredSize, getRegisteredKeyStrokes, getRootPane, getSize, getToolTipLocation, getToolTipText, getToolTipText, getTopLevelAncestor, getTransferHandler, getVerifyInputWhenFocusTarget, getVetoableChangeListeners, getVisibleRect, getWidth, getX, getY, grabFocus, hide, isDoubleBuffered, isLightweightComponent, isManagingFocus, isOpaque, isOptimizedDrawingEnabled, isPaintingForPrint, isPaintingOrigin, isPaintingTile, isRequestFocusEnabled, isValidRoot, paint, paintBorder, paintChildren, paintComponent, paintImmediately, paintImmediately, print, printAll, printBorder, printChildren, printComponent, processComponentKeyEvent, processKeyBinding, processKeyEvent, processMouseEvent, processMouseMotionEvent, putClientProperty, registerKeyboardAction, registerKeyboardAction, removeAncestorListener, removeNotify, removeVetoableChangeListener, repaint, repaint, requestDefaultFocus, requestFocus, requestFocus, requestFocusInWindow, requestFocusInWindow, resetKeyboardActions, reshape, revalidate, scrollRectToVisible, setActionMap, setAlignmentX, setAlignmentY, setAutoscrolls, setBackground, setBorder, setComponentPopupMenu, setDebugGraphicsOptions, setDefaultLocale, setDoubleBuffered, setEnabled, setFocusTraversalKeys, setFont, setForeground, setInheritsPopupMenu, setInputMap, setInputVerifier, setMaximumSize, setMinimumSize, setNextFocusableComponent, setOpaque, setPreferredSize, setRequestFocusEnabled, setToolTipText, setTransferHandler, setUI, setVerifyInputWhenFocusTarget, setVisible, unregisterKeyboardAction, update

クラスから継承されたメソッド java.awt.Container

add, add, add, add, add, addContainerListener, addImpl, addPropertyChangeListener, addPropertyChangeListener, applyComponentOrientation, areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout, findComponentAt, findComponentAt, getComponent, getComponentAt, getComponentAt, getComponentCount, getComponents, getComponentZOrder,

getContainerListeners, getFocusTraversalKeys, getFocusTraversalPolicy, getLayout, getMousePosition, insets, invalidate, isAncestorOf, isFocusCycleRoot, isFocusCycleRoot, isFocusTraversalPolicyProvider, isFocusTraversalPolicySet, layout, list, list, locate, minimumSize, paintComponents, preferredSize, printComponents, processContainerEvent, processEvent, remove, remove, removeAll, removeContainerListener, setComponentZOrder, setFocusCycleRoot, setFocusTraversalPolicy, setFocusTraversalPolicyProvider, setLayout, transferFocusDownCycle, validate, validateTree

クラスから継承されたメソッド java.awt.Component

action, add, addComponentListener, addFocusListener, addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener, addKeyListener, addMouseListener, addMouseMotionListener, addMouseWheelListener, bounds, checkImage, checkImage, coalesceEvents, contains, createImage, createImage, createVolatileImage, createVolatileImage, disableEvents, dispatchEvent, enable, enableEvents, enableInputMethods, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, getBackground, getBounds, getColorModel, getComponentListeners, getComponentOrientation, getCursor, getDropTarget, getFocusCycleRootAncestor, getFocusListeners, getFocusTraversalKeysEnabled, getFont, getForeground, getGraphicsConfiguration, getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint, getInputContext, getInputMethodListeners, getInputMethodRequests, getKeyListeners, getLocale, getLocation, getLocationOnScreen, getMouseListeners, getMouseMotionListeners, getMousePosition, getMouseWheelListeners, getName, getParent, getPeer, getPropertyChangeListeners, getPropertyChangeListeners, getSize, getToolkit, getTreeLock, gotFocus, handleEvent, hasFocus, imageUpdate, inside, isBackgroundSet, isCursorSet, isDisplayable, isEnabled, isFocusable, isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight, isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isShowing, isValid, isVisible, keyDown, keyUp, list, list, list, location, lostFocus, mouseDown, mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus, paintAll, postEvent, prepareImage, prepareImage, processComponentEvent, processFocusEvent, processHierarchyBoundsEvent, processHierarchyEvent, processInputMethodEvent, processMouseWheelEvent, remove, removeComponentListener, removeFocusListener, removeHierarchyBoundsListener, removeHierarchyListener, removeInputMethodListener, removeKeyListener, removeMouseListener, removeMouseMotionListener, removeMouseWheelListener, removePropertyChangeListener, removePropertyChangeListener, repaint, repaint, repaint, resize, resize, setBounds, setBounds, setComponentOrientation, setCursor, setDropTarget, setFocusable, setFocusTraversalKeysEnabled, setIgnoreRepaint, setLocale, setLocation, setLocation, setName, setSize, setSize, show, show, size, toString, transferFocus, transferFocusBackward, transferFocusUpCycle

クラスから継承されたメソッド java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

フィールドの詳細

SLD_MAX

```
private final int SLD_MAX
```

関連項目:

[定数フィールド値](#)

model

```
private DrawModel model
```

pen

```
private Pen pen
```

fill

```
private boolean fill
```

塗りつぶすかどうか

cbx

```
private javax.swing.JCheckBox cbx
```

塗りつぶすかどうかを設定する CheckBox

sld

```
private javax.swing.JSlider sld
```

線の太さを設定する Slider

spn

```
private javax.swing.JSpinner spn
```

線の太さを設定する Spinner

コンストラクタの詳細

LineWidthPanel

```
public LineWidthPanel(DrawModel model,  
                      Pen pen)
```

新しい LineWidthPanel を作成します

パラメータ:

model - DrawModel

pen - Pen

[パッケージ](#)[クラス](#)[使用](#)[階層ツリー](#)[非推奨](#)[索引](#)[ヘルプ](#)

[前のクラス](#)[次のクラス](#)[フレーム](#)[フレームなし](#)[すべてのクラス](#)

[サマリー: ネスト | フィールド | コンストラクタ | メソッド](#)[詳細: フィールド | コンストラクタ | メソッド](#)