


# クラス DatabaseButton



すべての実装されたインタフェース:

java.awt.event.ActionListener, java.awt.image.ImageObserver, java.awt.ItemSelectable, java.awt.MenuContainer, java.io.Serializable, java.util.EventListener, java.util.Observer, javax.accessibility.Accessible, javax.swing.SwingConstants

```
class DatabaseButton
extends SShapeButton
```

ネストされたクラスのサマリー

クラスから継承されたネストされたクラス/インタフェース javax.swing.JButton

javax.swing.JButton.AccessibleJButton

クラスから継承されたネストされたクラス/インタフェース javax.swing.AbstractButton

javax.swing.AbstractButton.AccessibleAbstractButton,  
javax.swing.AbstractButton.ButtonChangeListener

クラスから継承されたネストされたクラス/インタフェース javax.swing.JComponent

javax.swing.JComponent.AccessibleJComponent

クラスから継承されたネストされたクラス/インタフェース java.awt.Container

java.awt.Container.AccessibleAWTContainer

## クラスから継承されたネストされたクラス/インタフェース **java.awt.Component**

java.awt.Component.AccessibleAWTComponent, java.awt.Component.BaselineResizeBehavior, java.awt.Component.BltBufferStrategy, java.awt.Component.FlipBufferStrategy

## フィールドのサマリー

### クラスから継承されたフィールド **ShapeButton**

icon, pen

### クラスから継承されたフィールド **javax.swing.AbstractButton**

actionListener, BORDER\_PAINTED\_CHANGED\_PROPERTY, changeEvent, changeListener, CONTENT\_AREA\_FILLED\_CHANGED\_PROPERTY, DISABLED\_ICON\_CHANGED\_PROPERTY, DISABLED\_SELECTED\_ICON\_CHANGED\_PROPERTY, FOCUS\_PAINTED\_CHANGED\_PROPERTY, HORIZONTAL\_ALIGNMENT\_CHANGED\_PROPERTY, HORIZONTAL\_TEXT\_POSITION\_CHANGED\_PROPERTY, ICON\_CHANGED\_PROPERTY, itemListener, MARGIN\_CHANGED\_PROPERTY, MNEMONIC\_CHANGED\_PROPERTY, model, MODEL\_CHANGED\_PROPERTY, PRESSED\_ICON\_CHANGED\_PROPERTY, ROLLOVER\_ENABLED\_CHANGED\_PROPERTY, ROLLOVER\_ICON\_CHANGED\_PROPERTY, ROLLOVER\_SELECTED\_ICON\_CHANGED\_PROPERTY, SELECTED\_ICON\_CHANGED\_PROPERTY, TEXT\_CHANGED\_PROPERTY, VERTICAL\_ALIGNMENT\_CHANGED\_PROPERTY, VERTICAL\_TEXT\_POSITION\_CHANGED\_PROPERTY

### クラスから継承されたフィールド **javax.swing.JComponent**

listenerList, TOOL\_TIP\_TEXT\_KEY, ui, UNDEFINED\_CONDITION, WHEN\_ANCESTOR\_OF\_FOCUSED\_COMPONENT, WHEN\_FOCUSED, WHEN\_IN\_FOCUSED\_WINDOW

### クラスから継承されたフィールド **java.awt.Component**

accessibleContext, BOTTOM\_ALIGNMENT, CENTER\_ALIGNMENT, LEFT\_ALIGNMENT, RIGHT\_ALIGNMENT, TOP\_ALIGNMENT

### インタフェースから継承されたフィールド **javax.swing.SwingConstants**

BOTTOM, CENTER, EAST, HORIZONTAL, LEADING, LEFT, NEXT, NORTH, NORTH\_EAST, NORTH\_WEST, PREVIOUS, RIGHT, SOUTH, SOUTH\_EAST, SOUTH\_WEST, TOP, TRAILING, VERTICAL, WEST

### インタフェースから継承されたフィールド **java.awt.image.ImageObserver**

ABORT, ALLBITS, ERROR, FRAMEBITS, HEIGHT, PROPERTIES, SOMEBITS, WIDTH

## コンストラクタのサマリー

## コンストラクタ

### コンストラクタと説明

**DatabaseButton**(**Pen** pen, java.lang.String icon, java.lang.String name)

## メソッドのサマリー

### すべてのメソッド

### インスタンス・メソッド

### concreteメソッド

#### 修飾子とタイプ

#### メソッドと説明

#### Figure

**createFigure**(**Figure** f)  
ボタンに応じた新しいFigureを作成して返します.

### クラスから継承されたメソッド **SShapeButton**

paintComponent

### クラスから継承されたメソッド **ShapeButton**

actionPerformed, setIconFig, update

### クラスから継承されたメソッド javax.swing.JButton

getAccessibleContext, getUIClassID, isDefaultButton, isDefaultCapable, paramString, removeNotify, setDefaultCapable, updateUI

### クラスから継承されたメソッド javax.swing.AbstractButton

actionPropertyChanged, addActionListener, addChangeListener, addImpl, addItemListener, checkHorizontalKey, checkVerticalKey, configurePropertiesFromAction, createActionListener, createActionPropertyChangeListener, createChangeListener, createItemListener, doClick, doClick, fireActionPerformed, fireItemStateChanged, fireStateChanged, getAction, getActionCommand, getActionListeners, getChangeListeners, getDisabledIcon, getDisabledSelectedIcon, getDisplayedMnemonicIndex, getHideActionText, getHorizontalAlignment, getHorizontalTextPosition, getIcon, getIconTextGap, getItemListeners, getLabel, getMargin, getMnemonic, getModel, getMultiClickThreshold, getPressedIcon, getRolloverIcon, getRolloverSelectedIcon, getSelectedIcon, getSelectedObjects, getText, getUI, getVerticalAlignment, getVerticalTextPosition, imageUpdate, init, isBorderPainted, isContentAreaFilled, isFocusPainted, isRolloverEnabled, isSelected, paintBorder, removeActionListener, removeChangeListener, removeItemListener, setAction, setActionCommand, setBorderPainted, setContentAreaFilled, setDisabledIcon, setDisabledSelectedIcon, setDisplayedMnemonicIndex, setEnabled, setFocusPainted, setHideActionText, setHorizontalAlignment, setHorizontalTextPosition, setIcon, setIconTextGap, setLabel, setLayout, setMargin, setMnemonic, setMnemonic, setModel, setMultiClickThreshold, setPressedIcon, setRolloverEnabled, setRolloverIcon, setRolloverSelectedIcon, setSelected, setSelectedIcon, setText, setUI, setVerticalAlignment, setVerticalTextPosition

## クラスから継承されたメソッド javax.swing.JComponent

addAncestorListener, addNotify, addVetoableChangeListener, computeVisibleRect, contains, createToolTip, disable, enable, firePropertyChange, firePropertyChange, firePropertyChange, fireVetoableChange, getActionForKeyStroke, getActionMap, getAlignmentX, getAlignmentY, getAncestorListeners, getAutoscrolls, getBaseline, getBaselineResizeBehavior, getBorder, getBounds, getClientProperty, getComponentGraphics, getComponentPopupMenu, getConditionForKeyStroke, getDebugGraphicsOptions, getDefaultLocale, getFontMetrics, getGraphics, getHeight, getInheritsPopupMenu, getInputMap, getInputMap, getInputVerifier, getInsets, getInsets, getListeners, getLocation, getMaximumSize, getMinimumSize, getNextFocusableComponent, getPopupLocation, getPreferredSize, getRegisteredKeyStrokes, getRootPane, getSize, getToolTipLocation, getToolTipText, getToolTipText, getTopLevelAncestor, getTransferHandler, getVerifyInputWhenFocusTarget, getVetoableChangeListeners, getVisibleRect, getWidth, getX, getY, grabFocus, hide, isDoubleBuffered, isLightweightComponent, isManagingFocus, isOpaque, isOptimizedDrawingEnabled, isPaintingForPrint, isPaintingOrigin, isPaintingTile, isRequestFocusEnabled, isValidRoot, paint, paintChildren, paintImmediately, paintImmediately, print, printAll, printBorder, printChildren, printComponent, processComponentKeyEvent, processKeyBinding, processKeyEvent, processMouseEvent, processMouseMotionEvent, putClientProperty, registerKeyboardAction, registerKeyboardAction, removeAncestorListener, removeVetoableChangeListener, repaint, repaint, requestDefaultFocus, requestFocus, requestFocus, requestFocusInWindow, requestFocusInWindow, resetKeyboardActions, reshape, revalidate, scrollRectToVisible, setActionMap, setAlignmentX, setAlignmentY, setAutoscrolls, setBackground, setBorder, setComponentPopupMenu, setDebugGraphicsOptions, setDefaultLocale, setDoubleBuffered, setFocusTraversalKeys, setFont, setForeground, setInheritsPopupMenu, setInputMap, setInputVerifier, setMaximumSize, setMinimumSize, setNextFocusableComponent, setOpaque, setPreferredSize, setRequestFocusEnabled, setToolTipText, setTransferHandler, setUI, setVerifyInputWhenFocusTarget, setVisible, unregisterKeyboardAction, update

## クラスから継承されたメソッド java.awt.Container

add, add, add, add, add, addContainerListener, addPropertyChangeListener, addPropertyChangeListener, applyComponentOrientation, areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout, findComponentAt, findComponentAt, getComponent, getComponentAt, getComponentAt, getComponentCount, getComponents, getComponentZOrder, getContainerListeners, getFocusTraversalKeys, getFocusTraversalPolicy, getLayout, getMousePosition, insets, invalidate, isAncestorOf, isFocusCycleRoot, isFocusCycleRoot, isFocusTraversalPolicyProvider, isFocusTraversalPolicySet, layout, list, list, locate, minimumSize, paintComponents, preferredSize, printComponents, processContainerEvent, processEvent, remove, remove, removeAll, removeContainerListener, setComponentZOrder, setFocusCycleRoot, setFocusTraversalPolicy, setFocusTraversalPolicyProvider, transferFocusDownCycle, validate, validateTree

## クラスから継承されたメソッド java.awt.Component

action, add, addComponentListener, addFocusListener, addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener, addKeyListener, addMouseListener,

addMouseListener, addMouseWheelListener, bounds, checkImage, checkImage, coalesceEvents, contains, createImage, createImage, createVolatileImage, createVolatileImage, disableEvents, dispatchEvent, enable, enableEvents, enableInputMethods, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, getBackground, getBounds, getColorModel, getComponentListeners, getComponentOrientation, getCursor, getDropTarget, getFocusCycleRootAncestor, getFocusListeners, getFocusTraversalKeysEnabled, getFont, getForeground, getGraphicsConfiguration, getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint, getInputContext, getInputMethodListeners, getInputMethodRequests, getKeyListeners, getLocale, getLocation, getLocationOnScreen, getMouseListeners, getMouseMotionListeners, getMousePosition, getMouseWheelListeners, getName, getParent, getPeer, getPropertyChangeListeners, getPropertyChangeListeners, getSize, getToolkit, getTreeLock, gotFocus, handleEvent, hasFocus, inside, isBackgroundSet, isCursorSet, isDisplayable, isEnabled, isFocusable, isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight, isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isShowing, isValid, isVisible, keyDown, keyUp, list, list, list, location, lostFocus, mouseDown, mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus, paintAll, postEvent, prepareImage, prepareImage, processComponentEvent, processFocusEvent, processHierarchyBoundsEvent, processHierarchyEvent, processInputMethodEvent, processMouseWheelEvent, remove, removeComponentListener, removeFocusListener, removeHierarchyBoundsListener, removeHierarchyListener, removeInputMethodListener, removeKeyListener, removeMouseListener, removeMouseMotionListener, removeMouseWheelListener, removePropertyChangeListener, removePropertyChangeListener, repaint, repaint, repaint, resize, resize, setBounds, setBounds, setComponentOrientation, setCursor, setDropTarget, setFocusable, setFocusTraversalKeysEnabled, setIgnoreRepaint, setLocale, setLocation, setLocation, setName, setSize, setSize, show, show, size, toString, transferFocus, transferFocusBackward, transferFocusUpCycle

クラスから継承されたメソッド java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

コンストラクタの詳細

DatabaseButton

```
public DatabaseButton(Pen pen,  
                      java.lang.String icon,  
                      java.lang.String name)
```

メソッドの詳細

createFigure

public Figure createFigure(Figure f)

クラスからコピーされた説明: **ShapeButton**

ボタンに応じた新しいFigureを作成して返します.

オーバーライド:

createFigure クラス内 ShapeButton

パラメータ:

f - 初期化に使用する Figure

戻り値:

新しい Figure