

クラス StringFigure.ResponseStringDialog

java.lang.Object

java.awt.Component

java.awt.Container

java.awt.Window

java.awt.Dialog

javax.swing.JDialog

StringFigure.ResponseStringDialog

すべての実装されたインタフェース:

java.awt.event.ActionListener, java.awt.image.ImageObserver, java.awt.MenuContainer, java.io.Serializable, java.util.EventListener, javax.accessibility.Accessible, javax.swing.RootPaneContainer, javax.swing.WindowConstants

含まれているクラス:

[StringFigure](#)

```
class StringFigure.ResponseStringDialog
  extends javax.swing.JDialog
  implements java.awt.event.ActionListener
```

文字を入力するダイアログ

ネストされたクラスのサマリー

クラスから継承されたネストされたクラス/インタフェース javax.swing.JDialog

javax.swing.JDialog.AccessibleJDialog

クラスから継承されたネストされたクラス/インタフェース java.awt.Dialog

java.awt.Dialog.AccessibleAWTDialog, java.awt.Dialog.ModalExclusionType, java.awt.Dialog.ModalityType

クラスから継承されたネストされたクラス/インタフェース java.awt.Window

java.awt.Window.AccessibleAWTWindow, java.awt.Window.Type

クラスから継承されたネストされたクラス/インタフェース java.awt.Container

java.awt.Container.AccessibleAWTContainer

クラスから継承されたネストされたクラス/インタフェース java.awt.Component

java.awt.Component.AccessibleAWTComponent, java.awt.Component.BaselineResizeBehavior, java.awt.Component.BltBufferStrategy, java.awt.Component.FlipBufferStrategy

フィールドのサマリー

フィールド

修飾子とタイプ	フィールドと説明
private javax.swing.JCheckBox	bl
private javax.swing.JButton	btn
private javax.swing.JComboBox<java.lang.String>	cmb
private javax.swing.JTextField	fld
private javax.swing.JCheckBox	it
private javax.swing.JLabel	lbl
private javax.swing.JSpinner	spn

クラスから継承されたフィールド javax.swing.JDialog

accessibleContext, rootPane, rootPaneCheckingEnabled

クラスから継承されたフィールド java.awt.Dialog

DEFAULT_MODALITY_TYPE

クラスから継承されたフィールド java.awt.Component

BOTTOM_ALIGNMENT, CENTER_ALIGNMENT, LEFT_ALIGNMENT, RIGHT_ALIGNMENT, TOP_ALIGNMENT

インタフェースから継承されたフィールド javax.swing.WindowConstants

DISPOSE_ON_CLOSE, DO_NOTHING_ON_CLOSE, EXIT_ON_CLOSE, HIDE_ON_CLOSE

インタフェースから継承されたフィールド java.awt.image.ImageObserver

ABORT, ALLBITS, ERROR, FRAMEBITS, HEIGHT, PROPERTIES, SOMEBITS, WIDTH

コンストラクタのサマリー

コンストラクタ

コンストラクタと説明

ResponseStringDialog()

メソッドのサマリー

すべてのメソッド

インスタンス・メソッド

concreteメソッド

修飾子とタイプ

メソッドと説明

void

actionPerformed(java.awt.event.ActionEvent e)

クラスから継承されたメソッド javax.swing.JDialog

addImpl, createRootPane, dialogInit, getAccessibleContext, getContentPane, getDefaultCloseOperation, getGlassPane, getGraphics, getJMenuBar, getLayeredPane, getRootPane, getTransferHandler, isDefaultLookAndFeelDecorated, isRootPaneCheckingEnabled, paramString, processWindowEvent, remove, repaint, setContentPane, setDefaultCloseOperation, setDefaultLookAndFeelDecorated, setGlassPane, setJMenuBar, setLayeredPane, setLayout, setRootPane, setRootPaneCheckingEnabled, setTransferHandler, update

クラスから継承されたメソッド java.awt.Dialog

addNotify, getModalityType, getTitle, hide, isModal, isResizable, isUndecorated, setBackground, setModal, setModalityType, setOpacity, setResizable, setShape, setTitle, setUndecorated, setVisible, show, toBack

クラスから継承されたメソッド java.awt.Window

addPropertyChangeListener, addPropertyChangeListener, addWindowFocusListener, addWindowListener, addWindowStateListener, applyResourceBundle, applyResourceBundle, createBufferStrategy, createBufferStrategy, dispose, getBackground, getBufferStrategy, getFocusableWindowState, getFocusCycleRootAncestor, getFocusOwner, getFocusTraversalKeys, getIconImages, getInputContext, getListeners, getLocale, getModalExclusionType, getMostRecentFocusOwner, getOpacity, getOwnedWindows, getOwner, getOwnerlessWindows, getShape, getToolkit, getType, getWarningString, getWindowFocusListeners, getWindowListeners, getWindows, getWindowStateListeners, isActive, isAlwaysOnTop, isAlwaysOnTopSupported, isAutoRequestFocus, isFocusableWindow, isFocusCycleRoot, isFocused, isLocationByPlatform, isOpaque, isShowing, isValidRoot, pack, paint, postEvent, processEvent, processWindowFocusEvent, processWindowStateEvent, removeNotify, removeWindowFocusListener, removeWindowListener, removeWindowStateListener, reshape, setAlwaysOnTop, setAutoRequestFocus, setBounds, setBounds, setCursor, setFocusableWindowState, setFocusCycleRoot, setIconImage, setIconImages, setLocation, setLocation, setLocationByPlatform, setLocationRelativeTo, setMinimumSize, setModalExclusionType, setSize, setSize, setType, toFront

クラスから継承されたメソッド java.awt.Container

add, add, add, add, add, add, addContainerListener, applyComponentOrientation, areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout, findComponentAt, findComponentAt, getAlignmentX, getAlignmentY, getComponent, getComponentAt, getComponentAt, getComponentCount, getComponents, getComponentZOrder, getContainerListeners, getFocusTraversalPolicy, getInsets, getLayout, getMaximumSize, getMinimumSize, getMousePosition, getPreferredSize, insets, invalidate, isAncestorOf, isFocusCycleRoot, isFocusTraversalPolicyProvider, isFocusTraversalPolicySet, layout, list, list, locate, minimumSize, paintComponents, preferredSize, print, printComponents, processContainerEvent, remove, removeAll, removeContainerListener, setComponentZOrder, setFocusTraversalKeys, setFocusTraversalPolicy, setFocusTraversalPolicyProvider, setFont, transferFocusDownCycle, validate, validateTree

クラスから継承されたメソッド java.awt.Component

action, add, addComponentListener, addFocusListener, addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener, addKeyListener, addMouseListener, addMouseMotionListener, addMouseWheelListener, bounds, checkImage, checkImage, coalesceEvents, contains, contains, createImage, createImage, createVolatileImage, createVolatileImage, disable, disableEvents, dispatchEvent, enable, enable, enableEvents, enableInputMethods, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, getBaseline, getBaselineResizeBehavior, getBounds, getBounds, getColorModel, getComponentListeners, getComponentOrientation, getCursor, getDropTarget, getFocusListeners, getFocusTraversalKeysEnabled, getFont, getFontMetrics, getForeground, getGraphicsConfiguration, getHeight, getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint, getInputMethodListeners, getInputMethodRequests, getKeyListeners, getLocation, getLocation, getLocationOnScreen, getMouseListeners, getMouseMotionListeners, getMousePosition, getMouseWheelListeners, getName, getParent, getPeer, getPropertyChangeListeners, getPropertyChangeListeners, getSize, getSize, getTreeLock, getWidth, getX, getY, gotFocus, handleEvent, hasFocus, imageUpdate, inside, isBackgroundSet, isCursorSet, isDisplayable, isDoubleBuffered, isEnabled, isFocusable, isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight, isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isValid, isVisible, keyDown, keyUp, list, list, list, location, lostFocus, mouseDown, mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus, paintAll, prepareImage, prepareImage, printAll, processComponentEvent, processFocusEvent, processHierarchyBoundsEvent, processHierarchyEvent, processInputMethodEvent, processKeyEvent, processMouseEvent, processMouseMotionEvent, processMouseWheelEvent, remove, removeComponentListener, removeFocusListener, removeHierarchyBoundsListener, removeHierarchyListener, removeInputMethodListener, removeKeyListener, removeMouseListener, removeMouseMotionListener, removeMouseWheelListener, removePropertyChangeListener, removePropertyChangeListener, repaint, repaint, repaint, requestFocus, requestFocus, requestFocusInWindow, requestFocusInWindow, resize, resize, revalidate, setComponentOrientation, setDropTarget, setEnabled, setFocusable, setFocusTraversalKeysEnabled, setForeground, setIgnoreRepaint, setLocale, setMaximumSize, setName, setPreferredSize, show, size, toString, transferFocus, transferFocusBackward, transferFocusUpCycle

クラスから継承されたメソッド java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

フィールドの詳細

lbl

```
private javax.swing.JLabel lbl
```

fld

```
private javax.swing.JTextField fld
```

cmb

```
private javax.swing.JComboBox<java.lang.String> cmb
```

bl

```
private javax.swing.JCheckBox bl
```

it

```
private javax.swing.JCheckBox it
```

spn

```
private javax.swing.JSpinner spn
```

btn

```
private javax.swing.JButton btn
```

コンストラクタの詳細

ResponseStringDialog

```
public ResponseStringDialog()
```

メソッドの詳細

actionPerformed

```
public void actionPerformed(java.awt.event.ActionEvent e)
```

定義:

actionPerformed インタフェース内 java.awt.event.ActionListener

[パッケージ](#) [クラス](#) [使用](#) [階層ツリー](#) [非推奨](#) [索引](#) [ヘルプ](#)

[前のクラス](#) [次のクラス](#) [フレーム](#) [フレームなし](#) [すべてのクラス](#)

サマリー: [ネスト](#) | [フィールド](#) | [コンストラクタ](#) | [メソッド](#) 詳細: [フィールド](#) | [コンストラクタ](#) | [メソッド](#)