CONSTANT TEMPERATURE

Water baths

Constant-temperature baths in T-304 stainless steel, from ambient to 60 °C without lid and up to 100 °C with lid, an electronic thermostat with 0.05 °C sensitivity and ± 0.1 °C accuracy. Digital control on every model.



Features

- 0.05 °C sensitivity, ± 0.1 °C accuracy
- Low-density heater for long life
- Fibreglass insulation

Specifications

Model	Description	Inner dimensions
BD-020	For 20 tubes	14 × 13 × 15 cm
BD-040	For 40 tubes	23 × 13 × 15 cm
BD-050	For 50 tubes	29 × 14 × 15 cm
BD-100	For 100 tubes	29 × 23 × 15 cm
BD-160	For 160 tubes	50 × 29 × 15 cm
BCD-100	With circulation pump	29 × 23 × 13 cm
BCD-160	With circulation pump	50 × 29 × 15 cm
BCRD-100	Circulating, refrigerated	29 × 14 × 15 cm
BAD-415	4 concentric rings, 15 cm	—
BAD-420	4 concentric rings, 20 cm	—
BFD-230	Tissue flotation	—
BMOD-200	Oscillating motion, acrylic lid	—
BMRD-400	Reciprocating motion, acrylic lid	—

Applications

- Tube incubation
- Histology section flotation
- Shaken reactions

Specifications subject to change without notice. Request the current version with your quote.