DRYING

Drying ovens

Ovens with solid-state electronic control from ambient up to 200, 220, 250 or 300 °C, ± 0.1 °C sensitivity, insulated double wall and two adjustable shelves. Forced-air and vacuum options.



Features

- Up to 300 °C depending on model
- ± 0.1 °C sensitivity
- NiCr heater with ceramic insulators
- Top vent for vapours

Specifications

Model	Series	Inner dimensions	Capacity
HD-35	Stainless steel	35 × 35 × 35 cm	42 L
HD-40	Stainless steel	45 × 45 × 40 cm	72 L
HD-55	Stainless steel	60 × 50 × 50 cm	137.5 L
HFD-28	Forced air	28 × 30 × 35 cm	30 L
HFD-33	Forced air	33 × 40 × 40 cm	53 L
HFD-48	Forced air	48 × 45 × 50 cm	108 L
HFD-60	Forced air	60 × 45 × 45 cm	122 L
HFD-88	Forced air	88 × 75 × 60 cm	396 L
HE-35	Economy series, aluminium	35 × 35 × 35 cm	42 L
HE-40	Economy series, aluminium	45 × 45 × 40 cm	72 L
HE-55	Economy series, aluminium	60 × 50 × 50 cm	137.5 L

Vacuum oven with vacuum-line connections and needle gauge, on request.

Applications

- Drying of labware and samples
- Moisture determination
- Vacuum drying

Specifications subject to change without notice. Request the current version with your quote.