



The Papyrus Handbook

A guide to Markdown books with Papyrus

milon/papyrus

The Papyrus Handbook

Markdown to PDF, EPUB, HTML sites, and KDP

Nuruzzaman Milon

Welcome

Thanks for opening **The Papyrus Handbook**. Use the sidebar groups to browse chapters, or continue from Introduction. The home page has the project banner, a **Downloads** link for PDF previews from GitHub, and links to GitHub and Packagist. On chapter pages you will also see **On this page**, code **Copy**, and **Edit this page** linking back to this Markdown on GitHub.

This guide is the companion for [milon/papyrus](https://github.com/milon/papyrus) — a PHP CLI that turns Markdown into PDF, EPUB, HTML, a multi-page site, and Amazon KDP exports. You are reading those same chapters as a Papyrus site.

How to use this guide

1. **Introduction** — what Papyrus is and the project layout
2. **Install** — Composer setup and `papyrus init`
3. **Configuration** — every `papyrus.php` option
4. **Writing** — Markdown, front matter (`pretoc`, `draft`), asides, Mermaid, linting
5. **Themes** — PDF / HTML themes and fonts
6. **build** — all-in-one export, watch, caches
7. **build:pdf / epub / html / site / sample** — one chapter each (`serve` is covered with site)
8. **kdp** and **kdp:*** — Kindle, print, covers, metadata, package
9. **Migration and CI** — ibis-next migration and GitHub Actions
10. **Command reference** — full CLI tables
11. **Downloads** — light and dark PDF previews from GitHub

Copyright © 2026 [Nuruzzaman Milon](#) / [Papyrus](#). Released under the same terms as the Papyrus project ([MIT](#)).

Table of Contents

Welcome	3
How to use this guide	4
Introduction	18
Who it is for	19
Project shape	20
Next steps	21
Install and project layout	22
Requirements	23
macOS (Homebrew)	23
npm / Linux	24
Check the toolchain	24

Install per project	25
Install globally	26
Scaffold a book	27
Scaffold a documentation site	28
Import an existing README	29
Typical docs-site config	29
Config without PHP (YAML or JSON)	32
Layout	36
Configuration	38
Identity and paths	39
Page size and margins	41
Table of contents	42

Cover images	43
Running header	44
Fonts	45
Faces	46
Script rules	46
Site home (build:site)	48
Mermaid	52
Sample PDF	53
KDP	54
Break level	55
CommonMark hook	56
Writing content	57

Front matter	58
Pretoc chapters	59
Markdown features	61
Emphasis and code	61
Callouts	61
Page breaks	62
Mermaid	62
PHP fence linting	65
Themes and assets	66
PDF themes	67
HTML theme	68
EPUB styles	69
Covers and fonts	70

build	71
Options	72
What it builds	73
Failures	74
Validate first	75
Watch mode	76
Caching	77
Related chapters	78
build:pdf	79
Options	80
Output	81

Config that affects PDF	82
Parallel builds	84
Covers	85
build:epub	86
Options	87
Output	88
What goes in the package	89
Config that affects EPUB	90
Kindle upload	91
build:html	92
Options	93

Output	94
Config that affects HTML	95
Site vs HTML	96
build:site	97
Options	99
Output	100
Site config	101
Sidebar groups (site.nav)	103
On this page	104
Edit on GitHub	104
Copy on code fences	104
Version switcher	105
Images and other assets	106
Home CTA	106
Hosting this handbook	108

Mermaid on the site	109
build:sample	110
Options	111
Config	112
Output	114
kdp	115
Options	116
Enable flags	117
Typical artifacts	119
Package for upload	120
kdp:ebook	121

Options	122
Output	123
Cover	124
Metadata	125
Versus build:epub	126
kdp:print	127
Options	128
Output	129
Print config	130
Bleed	130
Margin presets (mm, before bleed)	130
Paper	131
Trim size	132

Cover	133
kdp:cover	134
Options	135
Sources and outputs	136
Example	137
kdp:metadata	139
Options	140
Output	141
Config	142
JSON shape	143
Migration and CI	146

Migrating from ibis-next	147
Continuous integration	149
Programmatic use	150
Checklist before release	151
Command reference	152
Build	153
KDP	154
Project tooling	155
Shared book options	157
Output filenames	158
Downloads	159

Full PDF 160

Sample PDF 161

Other previews 162

Introduction

Papyrus is a Composer package and CLI for authors who write books in Markdown and need more than one delivery format from a single tree of chapters.

One project layout yields:

- **PDF** — print interiors and shareable digital books
- **EPUB** — stores, e-readers, and Kindle upload
- **HTML** — a single file with light / dark mode
- **Site** — a multi-page static website with grouped nav, **On this page** outline, popup search, code **Copy**, and **Edit this page** (this handbook)
- **KDP helpers** — Kindle EPUB, print PDF, covers, wrap estimates, metadata, package zip

This handbook is itself a Papyrus book. The Markdown source lives in [examples/the-papyrus-handbook/](#) on GitHub. Prebuilt PDF, HTML, and site outputs are published from that example so you can read without installing anything. Chapter pages link back to the source via **Edit this page**.

Who it is for

- Authors shipping a technical or long-form book from Markdown
- Teams migrating off [ibis-next](#)
- Anyone who wants PDF and a hosted docs site from the same chapters

Project shape

Every book is a directory with:

Path	Role
<code>papyrus.php</code>	Title, trim, themes, Mermaid, samples, KDP
<code>content/</code>	Markdown chapters (natural filename order)
<code>assets/</code>	Your overrides (covers, banner, custom themes/fonts); bundled defaults used when absent
<code>export/</code>	Build outputs (usually gitignored)

Next steps

Install Papyrus (next chapter), run `papyrus doctor`, then `papyrus build` or `papyrus build:site`. Later chapters document every build and KDP command and the full `papyrus.php` option set.

Source and releases: github.com/milon/papyrus.

Install and project layout

Requirements

Required

- PHP 8.2+ with extensions `dom`, `gd`, `mbstring`, `zip`, and `zlib`
- Composer

Optional

Tool	Used by	Notes
<code>mmdc</code> (<code>@mermaid-js/mermaid-cli</code> or Homebrew <code>mermaid-cli</code>)	Mermaid diagrams	Needs Chrome/Chromium for Puppeteer
Chrome or Chromium	Mermaid CLI	Set <code>PUPPETEER_EXECUTABLE_PATH</code> if needed
<code>epubcheck</code>	<code>kdp:ebook</code>	Extra validation; skipped with a warning when absent

macOS (Homebrew)

```
brew install php composer
brew install mermaid-cli
brew install --cask google-chrome
brew install epubcheck
```

```
export PUPPETEER_EXECUTABLE_PATH="/Applications/Google  
Chrome.app/Contents/MacOS/Google Chrome"
```

npm / Linux

```
npm install -g @mermaid-js/mermaid-cli  
# Debian/Ubuntu example:  
sudo apt-get install -y chromium-browser  
export PUPPETEER_EXECUTABLE_PATH="$(command -v chromium-browser  
|| command -v google-chrome || command -v chromium)"
```

Install [epubcheck](#) and put it on **PATH**, or use **brew install epubcheck** on macOS.

Check the toolchain

```
php -m | grep -E 'dom|gd|mbstring|zip|zlib'  
mmdc --version  
epubcheck --version  
papyrus doctor
```

Install per project

In your book repository:

```
composer require milon/papyrus
```

```
vendor/bin/papyrus --version  
vendor/bin/papyrus init  
vendor/bin/papyrus doctor
```

Wire Composer scripts (example):

```
{  
  "scripts": {  
    "build": "papyrus build",  
    "build:pdf": "papyrus build:pdf --theme light,dark",  
    "build:epub": "papyrus build:epub",  
    "build:html": "papyrus build:html",  
    "build:site": "papyrus build:site",  
    "build:sample": "papyrus build:sample",  
    "build:kdp": "papyrus kdp",  
    "doctor": "papyrus doctor"  
  }  
}
```

Package page: packagist.org/packages/milon/papyrus.

Install globally

```
composer global require milon/papyrus  
export PATH="$(composer global config bin-dir --absolute):$PATH"  
papyrus list
```

Scaffold a book

```
papyrus init
papyrus init -d my-book
papyrus init --format=yml
papyrus init --format=yaml
papyrus init --format=json
```

init creates a book config (**papyrus.php** by default, or YAML / JSON via **--format**), **content/**, and an empty **assets/** directory. Papyrus uses bundled themes, CSS, and fonts by default. Publish those files into your project only when you want to customize them:

```
papyrus asset:publish
papyrus asset:publish --only=themes,css
```

Use **--force** / **-f** to overwrite files during **init**, or with **asset:publish** to overwrite published assets. **--only** limits publishing to **themes**, **css**, and/or **fonts**.

Scaffold a documentation site

For a library or tool (not a print book), use the **docs** preset:

```
papyrus init --preset=docs
papyrus init --preset=docs -d docs
```

That writes **papyrus.yml** by default (override with **--format=php|json**), starter chapters (welcome, install, usage, reference, changelog), an empty **assets/**, and a sample GitHub Actions workflow under **github/workflows/docs-site.yml** (copy it to **.github/workflows/**).

If a **composer.json** is found in the target directory or its parent, Papyrus fills **title**, **site.lead**, **site.links** (GitHub / Packagist), **site.repository** / **site.edit** (for **Edit this page**), and a suggested **site.base_path** (e.g. **/barcode** for **milon/barcode**). There is no KDP or sample-PDF config in this preset.

```
papyrus build:site -e docs
papyrus serve -s docs/<slug>-site
```

The site home always uses a **Get started** CTA (preferring Install / quick-start chapters) with secondary links below. Set **author** on the project if you want the author line on Home. Older **site.mode: book|docs** values are ignored.

Import an existing README

Most PHP packages start as one fat **README.md**. Split it into chapters on **##** headings:

```
papyrus import-readme
papyrus import-readme --file ../README.md --dry-run
papyrus import-readme -d docs --force
```

Then update **site.nav** to match the new files.

Typical docs-site config

After **init --preset=docs** (or **import-readme**), a package docs root usually looks like:

```
# papyrus.yml
title: milon/barcode
site:
  lead: Short pitch for the home page.
  base_path: /barcode          # omit with a custom domain /
  cname
  repository: https://github.com/milon/barcode
  edit:
    link: true                  # default false
    path: docs-src/content      # path from repo root to content/
    branch: master              # default main
  links:
    - { label: GitHub, url: https://github.com/milon/barcode }
    - { label: Packagist, url:
https://packagist.org/packages/milon/barcode }
  nav:
    - group: Getting started
      chapters: [00-welcome.md, 01-installation.md, 02-quick-
start.md]
    - group: API
      chapters: [04-output-methods.md, 06-examples-with-
screenshots.md]
```

Optional multi-version peers (each version is its own **build:site**):

```
site:
  version: v12
  versions:
    - { label: v12, path: /barcode/v12 }
    - { label: v11, path: /barcode/v11 }
```

Full key tables live in [Configuration](#) and [build:site](#).

Config without PHP (YAML or JSON)

You still need PHP installed to *run* Papyrus — but you do **not** need to edit PHP to configure a book. If you are more comfortable with YAML or JSON, scaffold that way:

```
papyrus init --format=yml      # writes papyrus.yml (--format=yaml
is the same)
papyrus init --format=json     # writes papyrus.json
```

Same keys as the PHP stub, without the `<?php return [...]` wrapper.
Example YAML:

```
title: My Book
subtitle: A short subtitle
author: Author Name
themes:
  - light
  - dark

document:
  size: crown-quarto
  margin_left: 27
  margin_right: 27
  margin_top: 14
  margin_bottom: 14

toc:
  h1: 0
  h2: 0
  h3: 1

mermaid:
  enabled: true
  format: svg
  theme: auto
```

Or JSON:

```
{
  "title": "My Book",
  "subtitle": "A short subtitle",
  "author": "Author Name",
  "themes": ["light", "dark"],
  "document": {
    "size": "crown-quarto",
    "margin_left": 27,
    "margin_right": 27,
    "margin_top": 14,
    "margin_bottom": 14
  }
}
```

Rules of thumb:

- Keep **exactly one** config file in the book root (`papyrus.php`, `papyrus.yml` / `papyrus.yaml`, or `papyrus.json`).
- `--format=yml` and `--format=yaml` both write `papyrus.yml`.
- You can also name the file `papyrus.yaml` by hand; Papyrus loads either extension.
- Full option tables live in the Configuration chapter — they apply to every format.
- One PHP-only escape hatch: `configure_commonmark` (a callable). If you need that hook, use `papyrus.php`; otherwise YAML/JSON are enough.

Coming from `ibis-next`, the same choice exists on migrate:

```
papyrus migrate-ibis --format=yml\  
papyrus migrate-ibis --format=json
```

Layout

Path	Role
<code>papyrus.php</code> / <code>.yaml</code> / <code>.yaml</code> / <code>.json</code>	Book settings (exactly one)
<code>content/</code>	Markdown chapters
<code>assets/</code>	Your overrides: themes, CSS, covers, fonts, banner
<code>export/</code>	Built artifacts
<code>.papyrus/</code>	Incremental caches

Only one config file is allowed. See [Config without PHP](#) above if you prefer YAML or JSON. Use `papyrus.php` when you need PHP callables such as `configure_commonmark`.

Always run from the book root, or pass `-d` / `--dir`. Override where artifacts are written with `-e` / `--export` (default: `<book>/export`):

```
papyrus doctor -d /path/to/book
papyrus build --dir /path/to/book
papyrus build:site -d /path/to/book -e /path/to/out
```

Browse the Papyrus source on [GitHub](#) if you want to follow along with this

handbook's own project under `examples/the-papyrus-handbook/`.

Configuration

Book settings live in **one** of:

- `papyrus.php` — PHP array (default; supports callables like `configure_commonmark`)
- `papyrus.yml` / `papyrus.yaml`
- `papyrus.json`

Papyrus auto-discovers which file is present and errors if more than one exists. Examples below use PHP; the same keys work in YAML/JSON.

Identity and paths

```
return [
    'title' => 'My Book',
    'subtitle' => 'A short subtitle',
    'author' => 'Author Name',
    'language' => 'en',
    'themes' => ['light', 'dark'],

    'content_dir' => 'content',
    'assets_dir' => 'assets',
    'export_dir' => 'export',
];
```

Key	Default	Notes
<code>title</code>	<code>Untitled</code>	Drives the export filename slug
<code>subtitle</code>	<code>''</code>	
<code>author</code>	<code>''</code>	
<code>language</code>	<code>en</code>	EPUB / KDP metadata fallback
<code>themes</code>	<code>['light', 'dark']</code>	Each needs <code>assets/theme-{name}.html</code>
<code>content_dir</code>	<code>content</code>	Relative to the book root

Key	Default	Notes
<code>assets_dir</code>	<code>assets</code>	
<code>export_dir</code>	<code>export</code>	Overridden by <code>-e</code> / <code>--export</code>

The slug is the title lowercased with non-alphanumeric runs turned into `-`. This handbook is *The Papyrus Handbook*, so outputs look like `the-papyrus-handbook-light.pdf`.

Page size and margins

```
'document' => [  
  'size' => 'crown-quarto',  
  'margin_left' => 27,  
  'margin_right' => 27,  
  'margin_top' => 14,  
  'margin_bottom' => 14,  
],
```

List presets with **papyrus sizes**. Custom trim:

```
'document' => [  
  'format' => [152.4, 228.6], // width_mm, height_mm  
],
```

Table of contents

```
'toc' => [  
  'h1' => 0,  
  'h2' => 0,  
  'h3' => 1,  
],
```

Values follow mPDF **h2toc** conventions used by Papyrus (**0** include, **1** exclude).

Cover images

```
'cover' => [  
  'image' => 'cover.png',  
  'light' => 'cover-light.png',  
  'dark' => 'cover-dark.png',  
  // 'width' => 188.976, // mm; defaults to page width  
  // 'height' => 246.126, // mm; defaults to page height  
],
```

Paths are relative to **assets/**. Missing per-theme covers fall back to **cover.image**. KDP print PDFs omit the cover page entirely.

Running header

```
'header' => [  
  'style' => 'font-style: italic; text-align: right; border-  
bottom: solid 1px #808080;',  
],
```

Pretoc chapters suppress folios differently from body chapters.

Fonts

Declare faces under **assets/fonts/** and optional **script routing** (PDF only). First matching **script** rule wins.

```
'fonts' => [
  'default' => 'librelibertine', // optional; else first face,
  else mPDF default
  'faces' => [
    [
      'name' => 'librelibertine',
      'regular' => 'LinLibertine_R.ttf',
      'bold' => 'LinLibertine_RB.ttf',
      'italic' => 'LinLibertine_RI.ttf',
      'bold_italic' => 'LinLibertine_RBI.ttf',
    ],
    [
      'name' => 'notosansbengali',
      'regular' => 'NotoSansBengali-Regular.ttf',
      'otl' => true, // OpenType layout – needed for
complex scripts
    ],
  ],
  'script' => [
    // When mPDF tags a run as Bengali, use this face instead
of the default
    ['match' => ['bn', 'ben', 'bengali'], 'face' =>
'notosansbengali'],
  ],
],
```

Faces

Each face needs a **name** and a **regular** file that exists under **assets/fonts/**. Optional keys: **bold**, **italic**, **bold_italic**, and **otl** (sets mPDF **useOTL** when true — common for code fonts and Indic / Arabic scripts).

Papyrus merges these into mPDF's **fontdata** when building PDF (**FontRegistry** → **MpdfFactory**).

Script rules

fonts.script is a list of { **match**, **face** } rules used only for **PDF**. They do not change EPUB or HTML typography.

When any applicable rule exists, Papyrus turns on mPDF's **autoScriptToLang** and **autoLangToFont**, and installs a custom **languageToFont** resolver (**ScriptLanguageToFont**). mPDF then:

1. Detects script runs in the HTML (e.g. Bengali glyphs).
2. Tags them with a language / script code (e.g. **bn**, or ***-beng**).
3. Asks Papyrus which face to use; the first rule whose **match** list hits that code wins.

match aliases are lowercased. Built-in aliases include:

Aliases you can list	Resolves as
bn , ben , beng , bengali	Bengali

Aliases you can list	Resolves as
<code>ar, arab, arabic</code>	Arabic
<code>hi, hin, deva, devanagari, hindi</code>	Devanagari
any 4-letter ISO script code	that script as-is

The `face` string must be a name from `fonts.faces` and that face must actually load (regular file present). Rules pointing at a missing face are skipped (`FontRegistry::applicableScriptRules()`). Unmatched languages fall through to mPDF's built-in `LanguageToFont`.

Example: body text in Latin uses `librelibertine`; a paragraph containing বন্ধন is auto-tagged Bengali and rendered with `notosansbengali` if that face is registered.

Notice: Without both a registered face and a matching `script` rule, non-Latin runs often show as tofu (missing glyphs) in the default font.

Site home (**build:site**)

```
'site' => [
  'banner' => 'banner.jpg',
  'lead' => 'A one-line pitch for the home page.',
  'cname' => 'docs.example.com',
  'base_path' => '/my-repo', // project Pages path; omit for
custom domains at /
  'repository' => 'https://github.com/you/your-book',
  'edit' => [
    'link' => true, // default false - set true to show Edit
this page
    'path' => 'content',
    'branch' => 'main',
  ],
  'links' => [
    ['label' => 'Downloads', 'chapter' => '19-downloads.md'],
    ['label' => 'Source on GitHub', 'url' =>
'https://github.com/you/your-book'],
    ['label' => 'Issues', 'url' =>
'https://github.com/you/your-book/issues'],
  ],
  'nav' => [
    [
      'group' => 'Start here',
      'chapters' => ['00-welcome.md', '01-
introduction.md'],
    ],
    [
      'group' => 'Build',
      'chapters' => ['10-build-site.md'],
    ],
  ],
]
```

```
1,
1,
```

Key	Default	Notes
<code>banner</code>	auto <code>banner.jpg</code> / <code>banner.png</code> if present	Under <code>assets/</code>
<code>lead</code>	unset	Home page pitch
<code>cname</code>	unset	Custom domain; writes a <code>CNAME</code> file in the site root for GitHub Pages; absolute <code>sitemap.xml</code> / <code>robots.txt</code> Sitemap URL
<code>base_path</code>	unset (site at <code>/</code>)	Path prefix for project GitHub Pages (e.g. <code>/my-repo</code>); injects <code><base href></code> ; also prefixes sitemap locs
<code>links</code>	unset	Explicit home-page links; each item needs <code>label</code> plus either <code>url</code> or <code>chapter</code>
<code>nav</code>	unset	Grouped sidebar: list of <code>{ group, chapters: [...] }</code> ; orders Prev/Next too

Key	Default	Notes
<code>repository</code>	unset	GitHub repo URL; used for Edit this page and legacy home links when <code>links</code> is unset
<code>edit</code>	unset	Nested edit-link settings; see below
<code>copy_code</code>	<code>true</code>	Set <code>false</code> to disable the Copy control on code fences
<code>page_toc</code>	<code>true</code>	Set <code>false</code> to hide the On this page rail
<code>version</code>	unset	Current version label for the switcher (e.g. <code>v12</code>)
<code>versions</code>	unset	Peer builds for the version switcher; see below

`site.edit` (optional):

Key	Default	Notes
<code>link</code>	<code>false</code>	Set <code>true</code> to show Edit this page (also accepts <code>enabled</code>)
<code>path</code>	<code>content</code>	Path from repo root to <code>content/</code> (e.g. <code>docs/content</code>)

Key	Default	Notes
<code>branch</code>	<code>main</code>	Branch used in edit URLs

`chapter` matches a chapter source name like `19-downloads.md`, `19-downloads`, or a full relative source path, and links to that generated page. `repository` still works as a legacy fallback that auto-adds GitHub, Packagist, and Issues links when `links` is not set. Chapters are never linked automatically; add them explicitly through `links`. Older `site.mode` values (`book` / `docs`) are ignored — every site home uses **Get started**.

```
'site' => [
  'base_path' => '/barcode/v12',
  'version' => 'v12',
  'versions' => [
    ['label' => 'v12', 'path' => '/barcode/v12'],
    ['label' => 'v11', 'path' => '/barcode/v11'],
  ],
],
```

`versions` drives the sidebar version switcher (two or more entries). Each item needs a `label` (or `version`) plus either `path` (like `base_path`) or absolute `url`. Mark the current build with `site.version` and/or a matching `base_path`. Each listed build is a separate `build:site` deploy under that path prefix. See the `build:site` chapter for navigation behaviour and filename conventions.

Mermaid

```
'mermaid' => [
  'enabled' => true,
  'format' => 'svg',           // svg | png
  'theme' => 'auto',          // auto = book colours; or
                              default|dark|forest|neutral
  'max_width_mm' => 130,
  // 'command' => '/usr/local/bin/mmdc', // optional override
],
```

Key	Default	Notes
enabled	false	Requires mmdc on PATH (or command)
format	svg	Anything other than png becomes svg
theme	auto	Book-matched palettes for PDF; HTML/site embed light + dark
max_width_mm	130	PDF figure width cap
command	auto-resolve mmdc	Explicit CLI path

Sample PDF

```
'sample' => [  
  'ranges' => [  
    ['from' => 1, 'to' => 3],  
  ],  
  'chapters' => [  
    '01-introduction.md',  
  ],  
],  
'sample_notice' => 'This is a sample from My Book.'
```

Ranges are 1-based inclusive pages of the finished theme PDF. **chapters** lists content filenames (or stems) to include in full. Notice text also accepts **sample.notice** / **sample.text** as fallbacks. See the **build:sample** chapter.

KDP

```
'kdp' => [
  'ebook' => [
    'enabled' => true,
    'cover' => 'cover-ebook.jpg',
  ],
  'print' => [
    'enabled' => true,
    'bleed_mm' => 3,
    'margin_preset' => 'recommended', // or minimum
    'paper' => 'white',                // or cream – spine
width
    'back_cover' => 'back-cover.png', // optional wrap
artwork
    'spine_color' => '#1a1a1a',       // optional wrap spine
fill
  ],
  'metadata' => [
    'description' => 'Bookstore blurb...',
    'keywords' => ['laravel', 'filament'],
    'language' => 'en',
  ],
],
```

Full option tables live in the **kdp** and **kdp:*** chapters. **papyrus build** only runs KDP when ebook or print is enabled; **papyrus kdp** errors if neither is.

Break level

```
'break_level' => 2,
```

Automatic page breaks before headings (**1** = H1, **2** = H1 and H2). Explicit **[break]** markers always insert a break.

CommonMark hook

```
'configure_commonmark' => function (  
    \League\CommonMark\Environment\Environment $environment  
) : void {  
    // register custom extensions  
},
```

Writing content

Chapters are Markdown under **content/**, loaded in natural filename order (**00-...**, **01-...**, **10-...**).

Front matter

```

---
title: My chapter
pretoc: true
---

Body starts here.
```

Key	Meaning
<code>title</code>	Chapter title for EPUB / site sidebar / running headers
<code>pretoc</code>	<code>true</code> places the chapter before the PDF table of contents
<code>draft</code>	<code>true</code> omits the chapter from PDF, EPUB, HTML, site, sample, and KDP builds

Accepted truthy values for `pretoc` and `draft`: `true`, `"true"`, `1`, `"1"`.

Pass `--include-drafts` on any book build command (or `watch`) when you want draft chapters in the output. `doctor` lists drafts and warns if `site.links` points at one.

Pretoc chapters

In the PDF, Papyrus splits the book into three bands around the theme's TOC marker (`<!-- PAPYRUS:TOC -->`):

1. **Pretoc** chapters (`pretoc: true`) — title page material, copyright, dedication, welcome, etc.
2. **Table of contents** — generated from body headings (see `toc` in config)
3. **Body** chapters — everything else, with folios and the running header

Pretoc chapters:

- Appear in EPUB, HTML, and the site like any other chapter
- Do **not** get normal body folios the same way (front matter styling)
- Are omitted from the auto-generated PDF TOC as body entries
- Still sort by filename — use a low prefix such as `00-` so they come first

This handbook's Welcome page is the example:

```
---
title: Welcome
pretoc: true
---

# Welcome

...
```

File: `content/00-welcome.md`. Introduction and later chapters omit

`pretoc` (or set it false) so they sit after the TOC in the PDF.

You can have several pretoc files (`00-copyright.md`, `00-dedication.md`, `00-welcome.md`); all of them render before the TOC, in filename order.

Markdown features

CommonMark + GFM, fenced code highlighting, and book extras.

Emphasis and code

```
Hello, world.

`inline code`

```php
$user = User::factory()->create();
```
```

Callouts

```
> {notice} Something helpful.
> {warning} Something risky.
```

```
::: note
A note aside.
:::

::: warning
A warning aside.
:::
```

Page breaks

```
[break]
```

Mermaid

Write a **mermaid** fence in your chapter. Papyrus runs **mmdc** at build time and replaces the fence with an SVG (or PNG) figure in PDF, EPUB, HTML, and site exports.

Source:

```
```mermaid
flowchart TB
 subgraph Authoring
 MD[Markdown chapters]
 CFG[papyrus.php]
 ASSETS[Themes and fonts]
 end

 subgraph Papyrus
 CONVERT[BookConverter]
 MERMAID[MermaidRenderer]
 PDF[build:pdf]
 EPUB[build:epub]
 HTML[build:html]
 SITE[build:site]
 end

 MD --> CONVERT
 CFG --> CONVERT
 ASSETS --> PDF
 ASSETS --> HTML
 ASSETS --> SITE
 CONVERT --> MERMAID
 MERMAID --> PDF
 MERMAID --> EPUB
 MERMAID --> HTML
 MERMAID --> SITE
```
```

Rendered output:



Enable in `papyrus.php` (theme defaults to `auto` — book colours; HTML and site embeds both light and dark variants):

```
'mermaid' => [  
  'enabled' => true,  
],
```

Optional knobs: `format` (`svg` / `png`), `theme` (`auto` or a Mermaid stock theme like `default` / `dark` / `forest`), `max_width_mm`.

Requires `@mermaid-js/mermaid-cli` (`mmdc`) on `PATH`. Diagrams cache under `.papyrus/cache/mermaid`.

PHP fence linting

```
papyrus lint
papyrus lint --fix
papyrus lint --max-width=66
```

| Option | Short | Default | Meaning |
|-------------------------------|----------------------|-----------------|--|
| <code>--fix</code> | <code>-f</code> | off | Apply auto-fixes for open tags and comment runs |
| <code>--max-width</code> | — | <code>66</code> | Maximum line width for PHP fences |
| <code>--dir / --export</code> | <code>-d / -e</code> | book defaults | Shared book options (<code>--export</code> unused for lint) |

Themes and assets

Everything visual can live under **assets/**, but it does not have to. New projects from **papyrus init** start with an empty **assets/** directory and use the bundled Papyrus defaults: Linux Libertine for body and headings, 0xProto for code, github-gist highlight colors, notice / tip / caution asides, and matching font files.

Publish the bundled assets into your project when you want to edit them:

```
papyrus asset:publish
papyrus asset:publish --only=themes,css
papyrus asset:publish --only=fonts --force
```

--only accepts **themes**, **css**, and/or **fonts**. Omit it to publish everything.

PDF themes

For each name in **themes**, Papyrus looks for **assets/theme-{name}.html** first, then falls back to the bundled copy. Split the theme on the TOC marker:

```
<!-- PAPYRUS:TOC -->
```

Papyrus writes pretoc chapters, then the TOC, then body chapters around that marker. A legacy **<!-- IBIS:TOC -->** marker is still accepted. **migrate-ibis** rewrites that marker only in **your assets/theme*.html** files, not in the bundled defaults.

Typical theme responsibilities: **@page** / typography, code blocks, callout colors, title page, and running header styles (often paired with **header.style** in config).

HTML theme

`theme-html.html` is a full HTML document with placeholders `{{ $title }}`, `{{ $subtitle }}`, `{{ $author }}`, and `{{ $body }}`. The default template mirrors the light PDF theme (same typefaces, colors, code blocks, and callouts), with a fixed moon/sun icon toggle that switches to the dark PDF palette. The reading column follows Tailwind screen widths (640 → 1536px). `@font-face` rules in the theme use `../assets/fonts/`. For `build:html`, Papyrus embeds those font files as base64 data URIs so the export is self-contained. For `build:site`, fonts are copied into the site `assets/fonts/` folder.

```
papyrus build:html
papyrus build:site
```

`build:site` writes `export/<slug>-site/` with one HTML page per chapter, a Home index, shared CSS/JS (fonts copied into the site), a collapsible chapter sidebar, and the same light/dark toggle as the single-file HTML export. That folder is what this handbook deploys to GitHub Pages.

EPUB styles

`style.css` (and optional `highlight.codeblock.min.css`) are loaded from your project `assets/` first, then from Papyrus's bundled defaults, and ship inside the EPUB. Prefer simple `pre/code` rules for e-ink readers.

Covers and fonts

Place cover images and font files under `assets/` (fonts usually in `assets/fonts/`). Reference them from `cover` and `fonts.faces` in `papyrus.php`.

This handbook keeps only book-specific assets in `assets/` — `cover.jpg` for the PDF cover and `banner.jpg` for the site home page. Themes, CSS, and fonts come from Papyrus's bundled defaults; run `papyrus asset:publish` when you want local copies to customize. The wide banner image in the Papyrus repo README lives at [assets/papyrus-banner.jpg](#).

build

papyrus build is the all-in-one export command. From the book root (or with **-d**), it runs every configured PDF theme, then EPUB, then single-file HTML, then every **enabled** KDP output. Site and sample builds are opt-in.

```
papyrus build
papyrus build --with-site --with-sample
papyrus build -d /path/to/book
papyrus build -d examples/the-papyrus-handbook -e docs --with-site --with-sample
```

Options

| Option | Short | Default | Meaning |
|-------------------------------|-----------------|---|--|
| <code>--dir</code> | <code>-d</code> | current directory | Book root (must contain <code>papyrus.php</code>) |
| <code>--export</code> | <code>-e</code> | <code>export_dir</code> from config (<code>export</code>) | Where artifacts are written |
| <code>--with-site</code> | | off | Also run <code>build:site</code> |
| <code>--with-sample</code> | | off | Also run <code>build:sample</code> for every theme |
| <code>--include-drafts</code> | | off | Include chapters with <code>draft: true</code> |

Global Symfony options also apply (`-v` / `--verbose`, `-q`, `--no-ansi`, ...).
 With `-v`, Papyrus prints third-party notices from mPDF and the EPUB zipper.

What it builds

| Step | Always? | Output |
|---|---|---|
| PDF
(each themes entry) | yes | <code>export/<slug>-<theme>.pdf</code> |
| EPUB | yes | <code>export/<slug>.epub</code> |
| HTML | yes | <code>export/<slug>.html</code> |
| KDP
ebook /
print /
covers /
metadata | only if
kdp.ebook.enabled
or
kdp.print.enabled | see KDP chapters |
| Site | only with --with-site | <code>export/<slug>-site/</code> |
| Sample
PDF | only with --with-sample | <code>export/sample-<slug>-<theme>.pdf</code> |

Slug comes from **title** (lowercased, non-alphanumeric → -).

watch invokes **build** on each change. Pass **--with-site** and/or **--with-sample** to include those outputs in every rebuild. Pass **--include-drafts** to keep **draft: true** chapters in the rebuild.

Failures

Each step is independent. If one format fails, Papyrus continues with the others and exits non-zero if any step failed. When no KDP outputs are enabled, the KDP block is skipped silently (unlike `papyrus kdp`, which errors).

Validate first

```
papyrus doctor  
papyrus build
```

Watch mode

Rebuild on changes to `papyrus.php`, `content/`, and `assets/`:

```
papyrus watch
papyrus watch --interval 3
papyrus watch --with-site --with-sample
```

| Option | Short | Default | Meaning |
|-------------------------------|----------------------|----------------------------|--|
| <code>--interval</code> | <code>-i</code> | <code>2</code> | Poll interval in seconds (minimum <code>1</code>) |
| <code>--dir / --export</code> | <code>-d / -e</code> | same as <code>build</code> | Passed through to each rebuild |
| <code>--with-site</code> | | off | Also run <code>build:site</code> |
| <code>--with-sample</code> | | off | Also run <code>build:sample</code> |

Caching

Chapter HTML caches under `.papyrus/cache/markdown`. Mermaid figures use `.papyrus/cache/mermaid`. Delete `.papyrus/` for a cold rebuild.

Related chapters

The next chapters cover each `build:*` command and every KDP command in turn.

build:pdf

Build one PDF per theme (or a subset). Each theme needs `assets/theme-{name}.html` and an entry in `themes`.

```
papyrus build:pdf
papyrus build:pdf --theme light
papyrus build:pdf --theme light,dark --parallel
papyrus build:pdf -d /path/to/book -e /path/to/out
```

Options

| Option | Short | Default | Meaning |
|-------------------------|-----------------|-----------------------|-----------------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--theme</code> | <code>-t</code> | all configured themes | Comma-separated theme names |
| <code>--parallel</code> | <code>-p</code> | off | One process per theme |

Output

```
export/<slug>-<theme>.pdf
```

Example for this handbook: **the-papyrus-handbook-light.pdf**.

Config that affects PDF

| Key | Role |
|--|---|
| <code>themes</code> | Which theme names to build by default |
| <code>document.size / document.format</code> | Trim size |
| <code>document.margin_*</code> | Margins in millimetres |
| <code>cover</code> | Cover image(s) under <code>assets/</code> |
| <code>header.style</code> | Running header CSS |
| <code>toc</code> | Which heading levels enter the TOC |
| <code>break_level</code> | Auto page breaks before headings |
| <code>fonts</code> | Faces and script routing |
| <code>mermaid</code> | Diagram rendering |

List trim presets with `papyrus sizes`. Custom trim:

```
'document' => [  
  'format' => [152.4, 228.6], // width_mm, height_mm  
],
```

Parallel builds

`--parallel` / `-p` spawns one PHP process per theme. Useful when `themes` has both `light` and `dark`. Sequential is the default (and what `papyrus build` uses).

Covers

```
'cover' => [  
  'image' => 'cover.png',          // fallback for every theme  
  'light' => 'cover-light.png',    // optional per-theme  
  'dark' => 'cover-dark.png',  
  // 'width' / 'height' - mm; default to page size  
],
```

Paths are relative to **assets/**. Missing per-theme covers fall back to **cover.image**.

build:epub

Build an EPUB3 package from the same Markdown chapters as PDF and HTML.

```
papyrus build:epub  
papyrus build:epub -d /path/to/book  
papyrus build:epub -e /path/to/out
```

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|----------------------|------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |

Output

export/<slug>.epub

What goes in the package

- Chapter HTML derived from `content/`
- `assets/style.css` and optional `highlight.codeblock.min.css`
- Embedded images referenced from chapters
- Cover from `cover` (theme fallback → `cover.image`)
- Metadata from `title`, `subtitle`, `author`, and `language`

Config that affects EPUB

| Key | Role |
|---|--|
| <code>title</code> , <code>subtitle</code> ,
<code>author</code> | Package identity |
| <code>language</code> | EPUB language (default <code>en</code>) |
| <code>cover</code> | Cover image under <code>assets/</code> |
| <code>mermaid</code> | Pre-rendered figures |
| <code>fonts</code> | Faces are PDF-oriented; EPUB relies on CSS |

Prefer simple `pre` / `code` rules in `assets/style.css` for e-ink readers.

Kindle upload

For Amazon KDP's Kindle pipeline, prefer `kdp:ebook` (validates and names the file for upload). `build:epub` is the general-purpose store / archive build.

build:html

Build a **single-file** HTML book with light / dark mode.

```
papyrus build:html  
papyrus build:html -d /path/to/book -e docs
```

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|----------------------|------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |

Output

```
export/<slug>.html
```

Requires `theme-html.html` (project `assets/` or bundled default).

Placeholders in the theme:

| Placeholder | Source |
|-------------------------------|-----------------------|
| <code>{{ \$title }}</code> | <code>title</code> |
| <code>{{ \$subtitle }}</code> | <code>subtitle</code> |
| <code>{{ \$author }}</code> | <code>author</code> |
| <code>{{ \$body }}</code> | Rendered chapters |

The default stub theme mirrors the light PDF palette, with a moon/sun toggle that switches to the dark PDF colours. The reading column follows Tailwind screen widths (640 → 1536px).

`@font-face` rules that point at `../assets/fonts/` are embedded as base64 data URIs at build time, so the single HTML file is self-contained even when fonts come from Papyrus's bundled defaults.

Config that affects HTML

| Key | Role |
|---|--|
| <code>title</code> , <code>subtitle</code> ,
<code>author</code> | Document chrome |
| <code>mermaid</code> | Figures; <code>theme</code> $\Rightarrow$ <code>auto</code> embeds light + dark SVGs |
| <code>fonts</code> | Loaded via the HTML theme's <code>@font-face</code> rules |

Site vs HTML

| Command | Result |
|-------------------------|---|
| <code>build:html</code> | One self-contained <code>.html</code> file |
| <code>build:site</code> | Multi-page folder with sidebar, Home, shared CSS/JS |

Use `build:html` for emailing or archiving a single document; use `build:site` for hosting.

build:site

Build a multi-page static site: Home index, one HTML page per chapter, sidebar navigation, light / dark mode, Prev / Next links, and an **On this page** outline of **h2** / **h3** headings on wide screens.

```
papyrus build:site
papyrus build:site -d examples/the-papyrus-handbook -e docs
```

papyrus build does **not** run this by default — pass **--with-site** on **build**, or call **build:site** directly.

Preview the site (including popup search) with PHP's built-in server:

```
papyrus serve
papyrus serve --build
papyrus serve --port 8080
papyrus serve -s docs/the-papyrus-handbook-site
papyrus serve -d examples/the-papyrus-handbook -e docs --build
```

By default **serve** reads **export/<slug>-site/**. Pass **--site** / **-s** to point at another folder (for example the handbook under **docs/**) — no book project is required in that case. **--export** / **-e** still changes the default parent (**<export>/<slug>-site**). Pass **--build** to run **build:site** first (into that same site directory; needs **-d** / a book root). If **site.base_path** is set

on a loaded project, the printed URL includes that prefix so `<base href>` and `assets/search.json` resolve correctly.

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|----------------------|--------------------------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Parent directory for the site folder |

Output

```
export/<slug>-site/
  index.html
  404.html
  <chapter-slug>.html
  sitemap.xml
  robots.txt
  .nojekyll
  CNAME          # when site.cname is set
  assets/site.css
  assets/site.js
  assets/search.json
  assets/fonts/...
  assets/<banner> # when configured
```

Point any static host (GitHub Pages, Netlify, S3, ...) at that folder. `.nojekyll` tells GitHub Pages not to run Jekyll. `CNAME` (from `site.cname`) sets a custom domain. GitHub Pages and Netlify serve `404.html` for missing URLs. Press `/` or the topbar search button for popup search (`↑/↓` moves through results, Enter opens the hit, Escape closes). Results are ranked: title and heading matches outrank body hits, whole-word matches beat substrings, and pretoc chapters are demoted so Welcome/copyright noise sinks. Excerpts centre on the first matching term. `sitemap.xml` uses `https:// {cname}` when `site.cname` is set, otherwise the `site.base_path` prefix. `robots.txt` points at the sitemap when a CNAME is configured. Each `##` heading gets an id and a `#` permalink; search hits for those headings open the chapter at that section.

Site config

Optional **site** block in **papyrus.php**:

```
'site' => [
    'banner' => 'banner.jpg',           // under assets/; auto-
    detects banner.jpg / banner.png
    'lead' => 'A one-line pitch for the home page.',
    'cname' => 'docs.example.com',      // GitHub Pages custom
    domain
    'base_path' => '/my-repo',          // project Pages under
    github.io/my-repo/; omit with cname
    'links' => [
        ['label' => 'Downloads', 'chapter' => '19-downloads.md'],
        ['label' => 'Source on GitHub', 'url' =>
        'https://github.com/you/your-book'],
    ],
],
```

| Key | Default | Meaning |
|---------------|--|--|
| banner | banner.jpg
then
banner.png if
present | Hero image on Home |
| lead | unset | Short pitch under the title on
Home |

| Key | Default | Meaning |
|-------------------------|------------------------|--|
| <code>cname</code> | unset | Writes <code>CNAME</code> in the site root for a GitHub Pages custom domain |
| <code>base_path</code> | unset | URL prefix for project Pages (writes <code><base href="/prefix/"></code>) |
| <code>links</code> | unset | Home-page links; each item needs <code>label</code> plus either <code>url</code> or <code>chapter</code> |
| <code>nav</code> | unset (filename order) | Grouped sidebar sections; see below |
| <code>repository</code> | unset | GitHub URL; used with <code>edit</code> for Edit this page |
| <code>edit</code> | unset | <code>{ link, path, branch }</code> — see Edit on GitHub below |
| <code>copy_code</code> | <code>true</code> | Set <code>false</code> to hide the Copy control on fences |
| <code>page_toc</code> | <code>true</code> | Set <code>false</code> to hide the On this page rail |
| <code>version</code> | unset | Current label for the version switcher |

| Key | Default | Meaning |
|-----------------|---------|--|
| versions | unset | Peer deploys for the version switcher (needs 2+) |

Sidebar groups (**site.nav**)

```
'site' => [
  'nav' => [
    [
      'group' => 'Getting started',
      'chapters' => ['01-install.md', '02-usage.md'],
    ],
    [
      'group' => 'Reference',
      'chapters' => ['03-api.md', '04-changelog.md'],
    ],
  ],
],
```

Chapter names match the same way as **links.chapter** (filename, stem, or path). When **nav** is set, the sidebar shows labeled groups and Prev/Next follow that order. Chapters not listed still appear under **More**. Omit **nav** to keep the default natural filename order. Group headings are collapsible (chevron toggle); open/closed state is remembered in the browser, and the group containing the current page always starts expanded.

On this page

Chapter pages get a sticky right-rail outline on wide viewports (Laravel-style: list icon, left border rail, active-section indicator). When the chapter has `##` / `###` headings, those appear as links; when it has none, the rail still shows with the page title linking to the top. Set `site.page_toc: false` to hide the rail entirely.

Edit on GitHub

```
'site' => [  
  'repository' => 'https://github.com/milon/papyrus',  
  'edit' => [  
    'link' => true, // default false  
    'path' => 'examples/the-papyrus-handbook/content',  
    'branch' => 'master', // optional; default main  
  ],  
],
```

Each chapter page then shows **Edit this page** (pencil icon) linking to the file on GitHub when `edit.link` is `true`. This handbook uses the settings above. `init --preset=docs` fills `repository` / `edit` from `composer.json` when possible (often `path` → `docs/content`, `branch` → `main`, `link` → `true`).

Copy on code fences

Site pages wrap fenced code blocks with an icon **Copy** button (clipboard

API). Set `site.copy_code: false` to disable it.

Version switcher

Each matrix version is its own Papyrus build (own `content/` + `base_path`).
List peers so the sidebar shows a version select:

```
'site' => [
  'base_path' => '/barcode/v12',
  'version' => 'v12',
  'versions' => [
    ['label' => 'v12', 'path' => '/barcode/v12'],
    ['label' => 'v11', 'path' => '/barcode/v11'],
    // Or absolute: ['label' => 'v10', 'url' =>
'https://docs.example.com/v10'],
  ],
],
```

| Entry key | Required | Meaning |
|--------------------|---|--|
| <code>label</code> | yes | Shown in the select (also accepted as <code>version</code>) |
| <code>path</code> | one of <code>path</code> / <code>url</code> | Absolute site path prefix (same rules as <code>base_path</code>) |
| <code>url</code> | one of <code>path</code> / <code>url</code> | Full <code>https://...</code> override when peers live on another host |

Current build: match `site.version` to a label, else match `site.base_path` to a `path`, else the first entry. The control appears only when `versions` has two or more valid entries.

Switching keeps the same page filename when it exists in the other build (e.g. `01-install.html` → `/barcode/v11/01-install.html`); otherwise it opens that version's home. Use the same chapter filenames across versions when you can.

Images and other assets

`build:site` copies everything under project `assets/` into the site's `assets/` folder **except** `fonts/` (fonts are published separately). Put screenshots at `assets/examples/foo.png` and reference them from Markdown as `assets/examples/foo.png` so they work with `site.base_path` and `<base href>`.

Home CTA

The home page primary button prefers a chapter whose slug or title contains “install”, “quick start”, or “getting started”; otherwise it skips a Welcome/`00-` chapter and links to the next page. Secondary `links` stay below the CTA (GitHub, Packagist, ...). Author is shown when `author` is set on the project.

Nothing is inferred from chapter titles for `links`. If you want a Downloads link on Home, add it explicitly with `['label' ⇒ 'Downloads', 'chapter' ⇒ '19-downloads.md']`.

Use `base_path` when the site is not at the domain root (for example `https://user.github.io/my-repo/`). Leave it unset when using a

custom domain via **cname**.

Hosting this handbook

In the Papyrus repository, pushes to **main** rebuild the handbook site and publish it to **gh-pages** via **.github/workflows/pages.yml**. Locally:

```
composer build:handbook
# or just:
papyrus build:site -d examples/the-papyrus-handbook -e docs
```

Mermaid on the site

With `mermaid.theme => auto`, each diagram embeds light and dark SVG variants; CSS swaps them with `data-theme`. Diagrams stay within the reading column (same max-width ladder as the HTML theme).

build:sample

Build a **sample** PDF for marketing downloads or review copies. Select content with page ranges, whole chapters by filename, or both.

```
papyrus build:sample  
papyrus build:sample --theme light  
papyrus build:sample -t light,dark
```

papyrus build does **not** run this by default — pass **--with-sample**, or call **build:sample** directly.

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|-----------------------|-----------------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--theme</code> | <code>-t</code> | all configured themes | Comma-separated theme names |

Config

```
'sample' => [
  'ranges' => [
    ['from' => 1, 'to' => 4],
    ['from' => 10, 'to' => 12],
  ],
  'chapters' => [
    '01-introduction.md',
    '04-writing-content', // stem or basename also works
  ],
  // Optional notice text (also accepted as sample.notice /
  sample.text):
  // 'notice' => 'This is a sample...',
],

'sample_notice' => 'This is a sample from My Book.',
```

| Key | Meaning |
|------------------------------|---|
| <code>sample.ranges</code> | List of <code>{from, to}</code> 1-based inclusive page ranges against the finished PDF |
| <code>sample.chapters</code> | Chapter files to include in full (config order). Match by source path, basename (01-intro.md), or stem (01-intro). Rendered as body pages only — no extra cover, title page, or TOC |

| `sample_notice` | Extra notice page (preferred) | | `sample.notice` /
`sample.text` | Fallbacks if `sample_notice` is empty |

Invalid ranges are dropped. Unknown chapter names fail the build.
`build:sample` requires at least one of `ranges` or `chapters`.

When both are set, page-range slices from the full theme PDF come first, then chapter pages (in config order).

Output

```
export/sample-<slug>-<theme>.pdf
```

When a notice is set, it is appended after the selected content.

kdp

papyrus kdp builds every **enabled** Amazon KDP artifact in one shot: Kindle EPUB (if enabled), print interior PDF (if enabled), cover asset copies, and the metadata JSON sidecar.

```
papyrus kdp
papyrus kdp --require-epubcheck
papyrus kdp --package
papyrus kdp --wrap
papyrus kdp -d /path/to/book -e /path/to/out
```

Unlike **papyrus build**, this command **fails** when neither **kdp.ebook.enabled** nor **kdp.print.enabled** is true.

Options

| Option | Short | Default | Meaning |
|----------------------------------|-----------------|----------------------|---|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--require-epubcheck</code> | | off | Fail ebook build if <code>epubcheck</code> is missing |
| <code>--package</code> | | off | Also write <code>export/<slug>-kdp-package.zip</code> |
| <code>--wrap</code> | | off | Also generate wraparound cover PDF + PNG |

Print uses the **first** configured theme (same as `kdp:print` without `--theme`).

Enable flags

```
'kdp' => [
  'ebook' => [
    'enabled' => true,
    'cover' => 'cover-ebook.jpg',
  ],
  'print' => [
    'enabled' => true,
    'bleed_mm' => 3,
    'margin_preset' => 'recommended', // or minimum
    'paper' => 'white',                // metadata + spine
    formula (e.g. cream)
    'back_cover' => 'back-cover.png', // optional wrap
    artwork
    'spine_color' => '#1a1a1a',        // optional wrap spine
    fill
  ],
  'metadata' => [
    'description' => 'Bookstore blurb...',
    'keywords' => ['papyrus', 'markdown'],
    'language' => 'en',
  ],
],
```

| Key | Default | Notes |
|----------------------------|--------------------|------------------|
| <code>ebook.enabled</code> | <code>false</code> | Gates ebook EPUB |

| Key | Default | Notes |
|----------------------------------|----------------------|--|
| <code>ebook.cover</code> | unset | Asset under <code>assets/</code> |
| <code>print.enabled</code> | <code>false</code> | Gates print PDF |
| <code>print.bleed_mm</code> | 3 | Added to trim and each margin |
| <code>print.margin_preset</code> | recommended | <code>recommended</code> or <code>minimum</code> |
| <code>print.paper</code> | <code>white</code> | Spine formula + metadata (<code>cream</code> allowed) |
| <code>print.back_cover</code> | unset | Optional back panel for <code>--wrap</code> |
| <code>print.spine_color</code> | sample front cover | Hex fill for spine / generated back |
| <code>metadata.*</code> | see metadata chapter | Sidecar + EPUB description fallback |

Typical artifacts

| Artifact | Filename |
|--------------------|---|
| Kindle EPUB | <code><slug>-kdp.epub</code> |
| Print PDF | <code><slug>-kdp-print.pdf</code> |
| Ebook cover copy | <code><slug>-kdp-ebook-cover.<ext></code> |
| Print cover copies | <code><slug>-kdp-print-cover-<theme>.<ext></code> |
| Wrap cover | <code><slug>-kdp-print-wrap.pdf</code> (+ <code>.png</code> preview via <code>-wrap</code>) |
| Metadata | <code><slug>-kdp-metadata.json</code> |
| Package zip | <code><slug>-kdp-package.zip</code> (via <code>kdp:package</code> or <code>kdp --package</code>) |

After `kdp:print`, Papyrus prints a wrap-cover size estimate (spine + full bleed dimensions). Confirm trim with `papyrus sizes` and Amazon's current KDP print specs before uploading.

Package for upload

After the artifacts exist:

```
papyrus kdp:package  
# or fold it into the all-in-one run:  
papyrus kdp --package
```

That writes `export/<slug>-kdp-package.zip` containing the enabled ebook / print / cover / metadata files plus a `KDP-CHECKLIST.txt` reminder. It does not talk to Amazon — upload the zip contents through KDP's web UI.

The next chapters document each `kdp:*` command.

kdp:ebook

Build a Kindle-oriented EPUB for Amazon KDP upload.

```
papyrus kdp:ebook  
papyrus kdp:ebook --require-epubcheck  
papyrus kdp:ebook -d /path/to/book -e /path/to/out
```

Requires `kdp.ebook.enabled => true`.

Options

| Option | Short | Default | Meaning |
|----------------------------------|-----------------|----------------------|--|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--require-epubcheck</code> | | off | Fail if <code>epubcheck</code> is not on <code>PATH</code> |

Output

```
export/<slug>-kdp.epub
```

Papyrus runs an internal KDP-oriented check and, when available on **PATH**, **epubcheck** (install with **brew install epubcheck**, or from [w3c/epubcheck](https://w3c.github.io/epubcheck/)). Warnings from those checks are printed to the console. Without epubcheck, the build still succeeds with a warning unless you pass **-require-epubcheck**.

Cover

```
'kdp' => [  
  'ebook' => [  
    'enabled' => true,  
    'cover' => 'cover-ebook.jpg', // under assets/  
  ],  
],
```

If `kdp.ebook.cover` is unset, Papyrus falls back to the light theme cover (`cover.light` or `cover.image`).

Metadata

Description falls back to "{title} - {author}" when `kdp.metadata.description` is empty. Language uses `kdp.metadata.language` when set, otherwise project `language` (default `en`).

Versus build:epub

| | build:epub | kdp:ebook |
|---------------------|--------------------------|------------------------------------|
| Filename | <slug>.epub | <slug>-kdp.epub |
| Enable flag | always | kdp.ebook.enabled |
| Validation | packaging only | KDP checks + optional
epubcheck |
| Cover
preference | theme cover | kdp.ebook.cover first |

Internal checks also warn on an empty **kdp.metadata.description** and on eBook cover images smaller than 1600 px on the shortest side (when GD can read the file).

kdp:print

Build a **print interior** PDF sized for Amazon KDP: no cover page, KDP margin presets, and bleed applied around the project trim.

```
papyrus kdp:print  
papyrus kdp:print --theme light  
papyrus kdp:print -t dark -e /path/to/out
```

Requires `kdp.print.enabled => true`.

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|------------------------|-------------------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--theme</code> | <code>-t</code> | first configured theme | PDF theme for interior layout |

Output

export/<slug>-kdp-print.pdf

Print config

```
'kdp' => [
  'print' => [
    'enabled' => true,
    'bleed_mm' => 3,
    'margin_preset' => 'recommended', // or 'minimum'
    'paper' => 'white',                // cream, etc. -
  ],
  metadata only
],
```

Bleed

Bleed expands the page and margins:

- Page width / height each increase by $2 \times \text{bleed_mm}$
- Every margin increases by bleed_mm

Default `bleed_mm` is 3.

Margin presets (mm, before bleed)

| Preset | Left | Right | Top | Bottom |
|-------------|------|-------|------|--------|
| recommended | 12.7 | 9.525 | 12.7 | 12.7 |

| Preset | Left | Right | Top | Bottom |
|----------------|-------|-------|-------|--------|
| minimum | 9.525 | 6.35 | 9.525 | 9.525 |

Unknown preset names fall back to **recommended**.

Paper

print.paper is written into the KDP metadata sidecar and used for wrap-cover spine estimates (**white** or **cream**). It does not change PDF colour or stock — choose white vs cream in the KDP dashboard to match.

After a successful build, Papyrus prints a wrap-cover estimate from the interior page count (Amazon's published inches-per-page formula + 0.125" bleed). Use **kdp:cover --dimensions** to recalculate later.

Trim size

Uses the same `document.size` / `document.format` as your regular PDFs. `papyrus doctor` warns when trim falls outside KDP bounds (width 101.6–215.9 mm, height 152.4–279.4 mm). List presets with `papyrus sizes`.

Cover

The print PDF **omits** the cover page. Export wraparound / ebook cover files with **kdp:cover**.

kdp:cover

Copy configured cover images from **assets/** into **export/** with KDP-oriented filenames. No enable flag — safe to run anytime.

```
papyrus kdp:cover
papyrus kdp:cover -d /path/to/book -e /path/to/out
papyrus kdp:cover --dimensions --pages=220
papyrus kdp:cover --wrap --pages=220
papyrus kdp:cover --wrap --theme=light
```

Options

| Option | Short | Default | Meaning |
|---------------------------|-----------------|----------------------|--|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |
| <code>--dimensions</code> | | off | Print wrap-cover size estimate (spine + full bleed) |
| <code>--wrap</code> | | off | Generate wraparound cover PDF + PNG preview |
| <code>--pages</code> | | from print PDF | Page count for <code>--dimensions</code> / <code>--wrap</code> |
| <code>--theme</code> | | first theme | Front-cover theme used by <code>--wrap</code> |

Sources and outputs

| Source | Export name |
|---------------------------------------|---|
| kdp.ebook.cover
→
assets/<file> | <slug>-kdp-ebook-cover.<ext> |
| cover[<theme>]
or cover.image | <slug>-kdp-print-cover-<theme>.<ext>
(one per theme) |

Missing source files are skipped (no error). If nothing is copied, the command still succeeds with a comment.

Example

```
'cover' => [  
  'image' => 'cover.png',  
  'light' => 'cover-light.png',  
],  
'kdp' => [  
  'ebook' => [  
    'cover' => 'cover-ebook.jpg',  
  ],  
],
```

With themes **light** and **dark**, a typical export folder might contain:

```
export/my-book-kdp-ebook-cover.jpg  
export/my-book-kdp-print-cover-light.png  
export/my-book-kdp-print-cover-dark.png  # if dark cover  
resolves
```

Papyrus copies files as-is for ebook/front covers. With **--wrap** it also composes a **paperback wraparound** PDF (back | spine | front, plus bleed) using Amazon's spine formula and your front cover image:

```
papyrus kdp:cover --wrap  
papyrus kdp:cover --wrap --pages=220
```

Outputs:

```
export/<slug>-kdp-print-wrap.pdf    # upload to KDP as the cover
export/<slug>-kdp-print-wrap.png    # preview
```

Optional config:

```
'cover' => [
  'image' => 'cover.png',
  'back' => 'back-cover.png',    // optional; otherwise a text
back panel is drawn
],
'kdp' => [
  'print' => [
    'paper' => 'white',          // or cream - affects spine
width
    'back_cover' => 'back-cover.png', // preferred over
cover.back
    'spine_color' => '#1a1a1a',    // optional; default
samples the front cover
  ],
],
```

Without `--pages`, Papyrus counts pages in `export/<slug>-kdp-print.pdf` (build `kdp:print` first). Spine text is drawn only when Amazon allows it (≥ 79 pages). Always verify with Amazon's cover calculator before upload.

kdp:metadata

Emit a JSON sidecar you can keep next to KDP uploads or feed into your own publishing scripts. Always writes — no enable flag.

```
papyrus kdp:metadata  
papyrus kdp:metadata -d /path/to/book -e /path/to/out
```

Options

| Option | Short | Default | Meaning |
|-----------------------|-----------------|----------------------|------------------|
| <code>--dir</code> | <code>-d</code> | current directory | Book root |
| <code>--export</code> | <code>-e</code> | <code>export/</code> | Output directory |

Output

```
export/<slug>-kdp-metadata.json
```

Config

```
'language' => 'en',

'kdp' => [
  'print' => [
    'paper' => 'white',
    'bleed_mm' => 3,
    'margin_preset' => 'recommended',
  ],
  'metadata' => [
    'description' => 'Bookstore blurb...',
    'keywords' => ['papyrus', 'markdown', 'ebook'],
    'language' => 'en', // optional; else project language
  ],
],
```

JSON shape

```
{
  "title": "...",
  "subtitle": "...",
  "author": "...",
  "language": "en",
  "description": "...",
  "keywords": [...],
  "ebook": {
    "enabled": true,
    "cover": "cover-ebook.jpg",
    "artifact": "<slug>-kdp.epub"
  },
  "print": {
    "enabled": true,
    "paper": "white",
    "bleed_mm": 3,
    "margin_preset": "recommended",
    "margin_preset_known": true,
    "trim": {
      "width_mm": 152.4,
      "height_mm": 228.6,
      "width_in": 6.0,
      "height_in": 9.0,
      "preset": "6x9",
      "within_kdp_bounds": true
    },
    "artifact": "<slug>-kdp-print.pdf"
  },
  "artifacts": {
    "ebook": "<slug>-kdp.epub",
```

```

    "print": "<slug>-kdp-print.pdf",
    "metadata": "<slug>-kdp-metadata.json",
    "ebook_cover": "<slug>-kdp-ebook-cover.jpg",
    "print_covers": ["<slug>-kdp-print-cover-light.jpg"]
  }
}

```

| Field | Source |
|--|---|
| <code>title / subtitle / author</code> | Project identity |
| <code>language</code> | <code>kdp.metadata.language</code> → <code>language</code> → <code>en</code> |
| <code>description</code> | <code>kdp.metadata.description</code> (may be empty) |
| <code>keywords</code> | <code>kdp.metadata.keywords</code> (string list) |
| <code>ebook.* / print.*</code> | Enable flags, paper, bleed, margin preset, trim size; optional wrap <code>cover</code> estimate when print PDF exists |
| <code>artifacts.*</code> | Expected export filenames for uploads |

When `export/<slug>-kdp-print.pdf` exists, `print.cover` includes page count, spine width, and full wrap dimensions. Rebuild metadata after `kdp:print` to refresh those numbers.

This file is a helper for your workflow — it is not uploaded automatically to

Amazon. Run **papyrus doctor** to check KDP readiness (covers, margin preset, epubcheck on **PATH**). Package uploads with **papyrus kdp:package**.

Migration and CI

Migrating from ibis-next

```
papyrus migrate-ibis
papyrus migrate-ibis -d /path/to/book
papyrus migrate-ibis --force
papyrus migrate-ibis --format=yml
```

| Option | Short | Meaning |
|-----------------------|-----------------|---|
| <code>--dir</code> | <code>-d</code> | Book root |
| <code>--force</code> | <code>-f</code> | Overwrite an existing Papyrus config file |
| <code>--format</code> | | <code>php</code> (default), <code>yml</code> / <code>yaml</code> , or <code>json</code> |

This writes `papyrus.php` (or `.yml` / `.json`) from `ibis.php`. If you still have custom `assets/theme*.html` files from ibis, it rewrites `<!-- IBIS:TOC -->` to `<!-- PAPYRUS:TOC -->` in those **project** files only. Bundled Papyrus themes (used when `assets/` has no theme override) already use the Papyrus marker — `migrate-ibis` does not copy or rewrite vendor assets.

YAML/JSON migrations drop `configure_commonmark` (callables need `papyrus.php`).

After migration:

1. Remove `hi-folks/ibis-next` and any Composer patches for

ibis/mPDF.

2. Point scripts at `papyrus` (`build`, `build:pdf`, `build:site`, ...).
3. Decide on themes: keep your ibis HTML under `assets/` as overrides, or delete those copies and use Papyrus defaults (optional `papyrus asset:publish` later if you want local copies to edit).
4. Run `papyrus doctor` and a full `papyrus build`.

Continuous integration

Copy the stub workflow from the Papyrus package:

```
stubs/github/workflows/book-build.yml
```

A typical book job installs PHP with `dom`, `gd`, `mbstring`, `zip`, `zlib`, runs `composer install`, `papyrus doctor`, optional `papyrus lint`, then `composer build`.

To publish a `build:site` output on GitHub Pages, add a job that runs `papyrus build:site` and deploys the site directory to a `gh-pages` branch (see [pages.yml](#) in this repository for a working example, including Chromium for Mermaid).

Programmatic use

```
use Milton\Papyrus\Config\Project;  
  
$project = Project::load($bookDir);  
$book =  
$project->bookConverter()->convertDirectory($project->contentDir)  
;
```

Checklist before release

1. `papyrus doctor` is clean
2. `papyrus build` succeeds for every theme
3. `papyrus build:site` looks right on phone and desktop (try light and dark)
4. Sample ranges still make sense after reflows (`build:sample`)
5. KDP EPUB opens in Kindle Previewer; print PDF matches trim/bleed
6. Pin a Papyrus version in the book's `composer.json`

Report problems at github.com/milon/papyrus/issues.

Command reference

Build

| Command | Purpose | Notable options |
|---------------------------|--|---|
| <code>build</code> | PDF themes, EPUB, HTML, enabled KDP | <code>-d, -e, --with-site, --with-sample, --include-drafts</code> |
| <code>build:pdf</code> | PDF themes | <code>--theme, --parallel</code> |
| <code>build:epub</code> | EPUB3 | <code>-d, -e</code> |
| <code>build:html</code> | Single-file HTML | <code>-d, -e</code> |
| <code>build:site</code> | Multi-page HTML site | <code>-d, -e</code> |
| <code>build:sample</code> | Sample PDF from <code>sample.ranges</code> and/or <code>sample.chapters</code> | <code>--theme</code> |

KDP

| Command | Purpose | Notable options |
|---------------------------|-------------------------------|---|
| <code>kdp</code> | All enabled KDP outputs | <code>-d</code> , <code>-e</code> , <code>--require-epubcheck</code> , <code>--package</code> , <code>--wrap</code> |
| <code>kdp:ebook</code> | Kindle EPUB | <code>--require-epubcheck</code> ; requires <code>kdp.ebook.enabled</code> |
| <code>kdp:print</code> | Print interior PDF | <code>--theme</code> ; requires <code>kdp.print.enabled</code> |
| <code>kdp:cover</code> | Cover assets + optional wrap | <code>--dimensions</code> , <code>--wrap</code> , <code>--pages</code> , <code>--theme</code> |
| <code>kdp:metadata</code> | Metadata JSON sidecar | no enable flag |
| <code>kdp:package</code> | Zip KDP artifacts + checklist | requires enabled outputs + built files |

Project tooling

| Command | Purpose | Notable options |
|----------------------------|---|---|
| <code>init</code> | Scaffold book or docs site | <code>--force</code> , <code>--preset=book docs</code> , <code>--format=php yaml yml json</code> |
| <code>import-readme</code> | Split <code>README.md</code> into <code>content/</code> chapters on <code>##</code> | <code>--file</code> , <code>--force</code> , <code>--dry-run</code> |
| <code>asset:publish</code> | Publish bundled themes, CSS, and fonts into <code>assets/</code> | <code>--force</code> , <code>--only=themes,css,fonts</code> |
| <code>doctor</code> | Validate config, paths, Mermaid, KDP readiness | <code>-d</code> |
| <code>sizes</code> | List page-size presets (+ KDP in-bounds) | (no <code>-d</code> / <code>-e</code>) |
| <code>lint</code> | Lint PHP fences in <code>content/</code> | <code>--fix</code> , <code>--max-width=66</code> |
| <code>watch</code> | Rebuild via <code>build</code> on file changes | <code>--interval</code> , <code>--with-site</code> , <code>--with-sample</code> , <code>--include-drafts</code> |
| <code>serve</code> | Preview the generated site in a browser | <code>--host</code> , <code>-p/--port</code> , <code>--build</code> , <code>-s/--site</code> |

| Command | Purpose | Notable options |
|---------------------------|---|---|
| <code>migrate-ibis</code> | <code>ibis.php</code> → Papyrus
config; TOC markers in
local
<code>assets/theme*.html</code> | <code>--force</code> , <code>--
format=php yml yaml json</code> |

Shared book options

Most book commands accept:

| Option | Short | Default | Meaning |
|-------------------------------|-----------------|----------------------------------|--|
| <code>--dir</code> | <code>-d</code> | current directory | Book root
(contains <code>papyrus.php</code>) |
| <code>--export</code> | <code>-e</code> | <code><book>/export</code> | Override
export
directory |
| <code>--include-drafts</code> | | off | Include
chapters with
<code>draft: true</code> |

Also useful globally: `-v` / `--verbose` (include third-party vendor notices), `-q` / `--quiet`, `--no-ansi`.

Output filenames

| Command | Path under export |
|----------------------------|---|
| <code>build:pdf</code> | <code><slug>-<theme>.pdf</code> |
| <code>build:html</code> | <code><slug>.html</code> |
| <code>build:epub</code> | <code><slug>.epub</code> |
| <code>build:site</code> | <code><slug>-site/</code> |
| <code>build:sample</code> | <code>sample-<slug>-<theme>.pdf</code> |
| <code>kdp:ebook</code> | <code><slug>-kdp.epub</code> |
| <code>kdp:print</code> | <code><slug>-kdp-print.pdf</code> |
| <code>kdp:cover</code> | <code><slug>-kdp-ebook-cover.*, <slug>-kdp-print-cover-<theme>.*</code> |
| <code>wrap (--wrap)</code> | <code><slug>-kdp-print-wrap.pdf, <slug>-kdp-print-wrap.png</code> |
| <code>kdp:metadata</code> | <code><slug>-kdp-metadata.json</code> |
| <code>kdp:package</code> | <code><slug>-kdp-package.zip</code> |

Packagist: [milon/papyrus](https://packagist.org/packages/milon/papyrus). Source: github.com/milon/papyrus. Releases: github.com/milon/papyrus/releases.

Downloads

Preview this handbook without building locally. Files live in the Papyrus repository under [docs/](#) and update when the handbook is rebuilt.

Full PDF

| Theme | Download |
|-------|---|
| Light | <u>the-papyrus-handbook-light.pdf</u> |
| Dark | <u>the-papyrus-handbook-dark.pdf</u> |

On GitHub: [light](#) · [dark](#)

Sample PDF

A shorter preview built with **build:sample**: cover through Welcome (before the table of contents), then the **build:html** and **kdp:cover** chapters.

| Theme | Download |
|-------|---|
| Light | sample-the-papyrus-handbook-light.pdf |
| Dark | sample-the-papyrus-handbook-dark.pdf |

Configured in this book's **papyrus.php** as:

```
'sample' => [  
    'ranges' => [  
        ['from' => 1, 'to' => 5], // cover ... Welcome (before TOC)  
    ],  
    'chapters' => [  
        '09-build-html.md',  
        '15-kdp-cover.md',  
    ],  
],
```

Other previews

| Format | Link |
|------------------|--|
| This site | papyrus.milon.im |
| Single-file HTML | the-papyrus-handbook.html |

Rebuild everything from the Papyrus repo with:

```
composer build:handbook
```