## Week 2. Classifying AI Tasks


Russell & Norvig, Chapter 2.

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

# **Wumpus World**



COMP9414/9814/3411 17s1 Tasks & Agent Types

## **Examples of AI Tasks**

- Week 2: Wumpus World, Robocup Soccer
- Week 3: Path Planning (mazes, graph search)
- Week 4: Path Search Puzzles (8-puzzle, Rubik's cube)
- Week 5: Games (board games, dice games, card games)
- Week 6: Constraint Satisfaction (N-queens, Sudoku)

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types


3


### **Robocup Soccer**



COMP9414/9814/3411 17s1 Tasks & Agent Types 4 COMP9414/9814/3411 17s1 Tasks & Agent Types

# Week 3: Path Planning





Trajectory Planning


Traveling in Romania

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1 Tasks & Agent Types 6

#### Week 5: Games









board games

dice games

card games

#### Week 4: Path Search Puzzles







8-Puzzle

Rubik's Cube


UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

\_

#### **Week 6: Constraint Satisfaction Problems**





N-queens

Sudoku

UNSW

© Alan Blair, 2013-17

UNSW

10

# **Specifying and Classifying Tasks**

We want a unified framework that can be used to specify, characterize, compare and contrast different AI tasks.

Tasks & Agent Types

UNSW ©Alan Blair, 2013-17

Tasks & Agent Types

# Agents as functions


COMP9414/9814/3411 17s1

Agents can be evaluated empirically, sometimes analysed mathematically

Agent is a function from percept sequences to actions

Ideal rational agent would pick actions which are expected to maximise the performance measure.

## **Agent Model**



UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

nt Types 11

### The PEAS model of an Agent

- Performance measure
- Environment
- Actuators
- Sensors

UNSW

© Alan Blair, 2013-17

UNSW

## **Example: Playing Chess**



Performance measure: +1 for a Win,  $+\frac{1}{2}$  for a Draw, 0 for a Loss.

Environment: board, pieces

Actuators: move piece to new square Sensors: which piece is on which square

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

14

COMP9414/9814/3411 17s1

Tasks & Agent Types

Tasks & Agent Types

15

© Alan Blair, 2013-17

#### **Robots**



#### **Example: Automated Taxi**

COMP9414/9814/3411 17s1

Performance measure: safety, reach destination, maximize profits, obey laws, passenger comfort, . . .

Environment: city streets, freeways, traffic, pedestrians, weather, customers, ...

Actuators: steer, accelerate, brake, horn, speak/display, ...

Sensors: video, accelerometers, gauges, engine sensors, keyboard, GPS,

UNSW

### **DARPA Grand Challenge**



COMP9414/9814/3411 17s1

Tasks & Agent Types 10

#### 16

### **DARPA Grand Challenge**



UNSW © Alan Blair, 2013-17

**Example AI Environment - Wumpus World** 

#### Environment

- ▶ Squares adjacent to Wumpus are Smelly
- ► Squares adjacent to Pit are Breezy
- ▶ Glitter iff Gold is in the same square
- ▶ Shoot
  - kills Wumpus if you are facing it
  - uses up the only arrow
- ▶ Grab
  - picks up Gold if in same square

SS SSSS SStench S		Breeze	PIT
(10 pm)	S S S S S S S S S S S S S S S S S S S	PIT	Breeze
SS SSS S Stench S		Breeze	
START	Breeze	PIT	Breeze
1	2	3	4

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

18

COMP9414/9814/3411 17s1

Tasks & Agent Types

19

## **Wumpus World PEAS description**

#### Performance measure

- ▶ Return with Gold +1000, death -1000
- ▶ -1 per step, -10 for using the arrow


#### Actuators

► Left, Right, Forward, Grab, Shoot


#### Sensors

▶ Breeze, Glitter, Stench

## **Exploring a Wumpus World**




# **Exploring a Wumpus World**



© Alan Blair, 2013-17 UNSW

**Exploring a Wumpus World** 



UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types


22

COMP9414/9814/3411 17s1


Tasks & Agent Types

23

# **Exploring a Wumpus World**




# **Exploring a Wumpus World**



COMP9414/9814/3411 17s1 Tasks & Agent Types 24 COMP9414/9814/3411 17s1 Tasks & Agent Types 2

## **Exploring a Wumpus World**



UNSW © Alan Blair, 2013-17

UNSW © Alan Blair, 2013-17

ок

oĸ

W

COMP9414/9814/3411 17s1

Tasks & Agent Types

COMP9414/9814/3411 17s1


UNSW

26

Tasks & Agent Types

27

## **Exploring a Wumpus World**



### **Classifying Tasks**

**Exploring a Wumpus World** 

P

ΟK

Α

Ток

Simulated vs. Situated or Embodied

Static vs. Dynamic

Discrete vs. Continuous

Fully Observable vs. Partially Observable

Deterministic vs. Stochastic

Episodic vs. Sequential

Known vs. Unknown

Single-Agent vs. Multi-Agent

UNSW © Alan Blair, 2013-17

# **Environment Types**

Simulated: a separate program is used to simulate an environment, feed percepts to agents, evaluate performance, etc.

Static: environment doesn't change while the agent is deliberating

Discrete: finite (or countable) number of possible percepts/actions

Fully Observable: percept contains all relevant information about the world

Deterministic: current state of world uniquely determines the next

Episodic: every action by the agent is evaluated independently

Known: the rules of the game, or physics/dynamics of the environment are known to the agent

Single-Agent: only one agent acting in the environment

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1 Tasks & Agent Types

#### Simulated vs. Situated or Embodied

■ Chess is Simulated, Robocup is Situated and Embodied

Simulated: a separate program is used to simulate an environment,

feed percepts to agents, evaluate performance, etc.

Situated: the agent acts directly on the actual environment

Embodied: the agent has a physical body in the world

Question: If Chess is played on a physical board with actual

pieces, would it become embodied?

### COMP9414/9814/3411 17s1 Tasks & Agent Types

#### Chess vs. Robocup Soccer





Chess

Robocup Soccer

UNSW © Alan Blair. 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

31

#### Simulated vs. Situated or Embodied

■ Chess is Simulated, Robocup is Situated and Embodied

Simulated: a separate program is used to simulate an environment,

feed percepts to agents, evaluate performance, etc.

Situated: the agent acts directly on the actual environment

Embodied: the agent has a physical body in the world

Question: If Chess is played on a physical board with actual pieces, would it become embodied?

Answer: Yes it would; however, we normally "abstract" away the game itself (choice of moves), and treat the movement of the pieces as a separate task.

UNSW

© Alan Blair, 2013-17

30

UNSW

#### Static vs. Dynamic

- Chess is Simulated, Robocup is Situated and Embodied
- Chess is Static, Robocup is Dynamic

Static: the environment does not change while the agent is thinking

Dynamic: the environment may change while the agent is thinking e.g. if the ball is in front of you but you take too long to act, another player may come in and kick it away

#### Notes:

- 1. In a multi-player game, Static environment will obviously change when the opponent moves, but cannot change once it is "our turn".
- 2. In tournament Chess, the clock will tick down while the player is thinking (thus making it slightly non-static).

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1 Tasks & Agent Types

#### Fully Observable vs. Partially Observable

- Chess is simulated, Robocup is Situated and Embodied
- Chess is Static, Robocup is Dynamic
- Chess is Discrete, Robocup is Continuous
- Chess is Fully Observable, Robocup (Legged) is Partially Observable

Fully Observable: agent percept contains all relevant information about the world

Partially Observable: some relevant information is hidden from the agent

[watch Dog's Eye View video] [watch Melbourne vs. Cornell video]

#### Note:

The Robocup F180 League is close to fully observable, because the robots have access to an external computer connected to an overhead camera. Discrete vs. Continuous

COMP9414/9814/3411 17s1

Chess is Simulated, Robocup is Situated and Embodied

■ Chess is Static, Robocup is Dynamic

■ Chess is Discrete, Robocup is Continuous

Discrete: only a finite (or countable) number of discrete percepts/actions

Tasks & Agent Types

Continuous: states, percepts or actions can vary continuously

e.g. each piece must be on one square or the other, not half way in between.

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

34

Tasks & Agent Types

35

#### **Deterministic vs. Stochastic**

■ Chess is Simulated, Robocup is Situated and Embodied

■ Chess is Static, Robocup is Dynamic

■ Chess is Discrete, Robocup is Continuous

■ Chess is fully observable, Robocup (Legged) is Partially Observable

■ Chess is Deterministic, Robocup is Stochastic

Deterministic: the current state uniquely determines the next state

Stochastic: there is some random element involved

Note:

UNSW

The non-determinisim partly arises because the physics can only be modeled with limited precision. But, even if it could be modeled perfectly, there would still be randomness due to quantum mechanical effects.

UNSW © Alan Blair, 2013-17

#### **Episodic vs. Sequential**

- Chess is Simulated, Robocup is Situated and Embodied
- Chess is Static, Robocup is Dynamic
- Chess is Discrete, Robocup is Continuous
- Chess is Fully Observable, Robocup (Legged) is Partially Observable
- Chess is Deterministic, Robocup is Stochastic
- Both Chess and Robocup are Sequential

Episodic: every action by the agent is evaluated independently

Sequential: the agent is evaluated based on a long sequence of actions

Both Chess and Robocup are considered Sequential, because evaluation only happens at the end of a game, and it is necessary to plan several steps ahead in order to play the game well.

UNSW (c) Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

38

# Single-Agent vs. Multi-Agent

- Chess is Simulated, Robocup is Situated and Embodied
- Chess is Static, Robocup is Dynamic
- Chess is Discrete, Robocup is Continuous
- Chess is Fully Observable, Robocup (Legged) is Partially Observable
- Chess is Deterministic, Robocup is Stochastic
- Both Chess and Robocup are Sequential
- Both Chess and Robocup are Known
- Both Chess and Robocup are Multi-Agent

Examples of Single-Agent tasks include:

- solving puzzles like Sudoku, or Rubik's cube
- Solitaire card games

#### Known vs. Unknown

COMP9414/9814/3411 17s1

- Chess is Simulated, Robocup is Situated and Embodied
- Chess is Static, Robocup is Dynamic
- Chess is Discrete, Robocup is Continuous
- Chess is Fully Observable, Robocup (Legged) is Partially Observable
- Chess is Deterministic, Robocup is Stochastic
- Both Chess and Robocup are Sequential
- Both Chess and Robocup are Known

Known: the rules of the game, or physics/dynamics of the environment, are known to the agent.

Note:

Video Games like Infinite Mario are sometimes set up in such a way that the dynamics of the environment are Unknown to the agent.

UNSW (C) Alan Blair, 2013-17


COMP9414/9814/3411 17s1

Tasks & Agent Types

Tasks & Agent Types

39

## **Wumpus World**



Simulated?

Static?

Discrete?

Fully Observable?

Deterministic ?

Episodic?

Known?

Single-Agent?

UNSW

© Alan Blair, 2013-17

UNSW

COMP9414/9814/3411 17s1 Tasks & Agent Types 40 COMP9414/9814/3411 17s1 Tasks & Agent Types

#### **Wumpus World**

- Like Chess, Wumpus World is Simulated, Static, Discrete, Sequential and Known.
- Wumpus World is Partially Observable for example, you don't know where the Wumpus is.
- Wumpus World is normally considered Deterministic, because the location of the Wumpus, Gold and Pits are determined at the beginning and don't change after that.
- Wumpus World is Single-Agent. We consider the Wumpus as a "natural feature", because it doesn't move and can't make any choices.

UNSW © Alan Blair, 2013-17


Tasks & Agent Types

#### **Dice Games (Backgammon)**

COMP9414/9814/3411 17s1

- Like Chess, Backgammon is Simulated, Static, Discrete, Sequential and Known and Multi-Agent.
- Normally, we consider Backgammon to be Fully Observable and Stochastic. The dice rolls are random, but all players can see them.
- If instead the dice rolls are generated by a computer using a pseudorandom number generator, with a specified seed, the game could be considered Deterministic but Partially Observable. In this case, the sequence of dice rolls is fully determined by the seed, but future dice rolls are not observable by the players.

#### **Dice Games (Backgammon)**



IINSW

COMP9414/9814/3411 17s1

Simulated?

Static?

Discrete?

Fully Observable?

Deterministic?

Episodic?

Known?

Single-Agent?

© Alan Blair, 2013-17

## Card Games (Poker, Rummy, Mahjong)



Simulated?

43

Tasks & Agent Types

Static?

Discrete?

Fully Observable?

Deterministic?

Episodic?

Known?

Single-Agent?

UNSW ©Alan Blair, 2013-17 UNSW ©Alan Blair, 2013-17

#### Card Games (Poker, Rummy, Mahjong)

- Card Games like Poker, Rummy or Mahjong are Simulated, Static, Discrete, Sequential, Known and Multi-Agent.
- Card Games are Stochastic if the cards are shuffled during the game, but can be considered Deterministic if the cards are shuffled only once, before the game begins.
- Card Games are Partially Observable and involve Asymmetric Information in the sense that each player can see their own cards but not those of other players.

UNSW © Alan Blair, 2013-17

Tasks & Agent Types

#### **Situated and Embodied Cognition**

#### Rodney Brooks 1991:

COMP9414/9814/3411 17s1

- Situatedness: The robots are situated in the world they do not deal with abstract descriptions, but with the "here" and "now" of the environment which directly influences the behaviour of the system.
- Embodiment: The robots have bodies and experience the world directly their actions are part of a dynamics with the world, and actions have immediate feedback on the robot's own sensations.

#### Robots



UNSW © Alan Blair. 2013-17

COMP9414/9814/3411 17s1

HNSW

Tasks & Agent Types

47

#### Situated vs. Embodied

- Situated but not Embodied: High frequency stock trading system:
  - ▶ it deals with thousands of buy/sell bids per second and its responses vary as its database changes.
  - ▶ but it interacts with the world only through sending and receiving messages.
- Embodied but not Situated: an industrial spray painting robot:
  - ▶ does not perceive any aspects of the shape of an object presented to it for painting; simply goes through a pre-programmed series of actions
  - but it has physical extent and its servo routines must correct for its interactions with gravity and noise present in the system.

UNSW © Alan Blair, 2013-17

COMP9414/9814/3411 17s1

Tasks & Agent Types

# **Summary**

- AI tasks or environments can be classified in terms of whether they are simulated, static, discrete, fully observable, deterministic, episodic, known, single- or multi- agent.
- The environment type strongly influences the agent design (discussed in the next section..)

UNSW © Alan Blair, 2013-17