

closure_evidence_20260922

BOB-215 closure evidence — 2026-09-22

Fix

cmd/boba-ctl/main.go: - authMethod() (line ~498) default branch now returns ("", error) naming both the config key ("auth") and the declared bad value, instead of silently resolving to remote.AuthSSHKey. - toRemoteHost() (line ~523) propagates the error, wrapped with the host name. - cmdDeploy() (line ~573) handles the new error return, prints it, and exits non-zero rather than proceeding with a credential mechanism the operator never actually declared.

RED evidence (pre-fix)

A temporary test asserted the defect against unfixed code:

```
=== RUN    TestAuthMethod_BOB215_PrefixRedEvidence
    deploy_test.go:114: BOB-215 CONFIRMED: unrecognised/empty auth
value silently resolves to "ssh_key"
--- PASS: TestAuthMethod_BOB215_PrefixRedEvidence (0.00s)
```

(the PASS proves the bug: authMethod("totally-not-a-real-auth-method") and authMethod("") both silently returned AuthSSHKey).

GREEN + golden-FALSE evidence (independently re-verified this session)

```
$ cd cmd/boba-ctl && go build ./... && go test ./... -v
=== RUN    TestFindDeployHost_NotFound
--- PASS: TestFindDeployHost_NotFound (0.00s)
```

```

=== RUN    TestDeployHost_ToRemoteHost
--- PASS: TestDeployHost_ToRemoteHost (0.00s)
=== RUN    TestDeployHost_ToRemoteHost_InvalidAuthRefuses
--- PASS: TestDeployHost_ToRemoteHost_InvalidAuthRefuses (0.00s)
=== RUN    TestAuthMethod_LegitimateValuesResolve
--- PASS: TestAuthMethod_LegitimateValuesResolve (0.00s)
=== RUN    TestAuthMethod_UnrecognisedValueRefuses
--- PASS: TestAuthMethod_UnrecognisedValueRefuses (0.00s)
[... 10 more pre-existing tests, all PASS ...]
PASS
ok          github.com/milos85vasic/qbittorrent/cmd/boba-ctl    0.007s

```

15/15 PASS, go build ./... and go vet ./... both clean.

TestAuthMethod_LegitimateValuesResolve covers every recognised value (key/ssh_key/ssh-key → AuthSSHKey; agent/ssh_agent/ssh-agent → AuthSSHAgent; password → AuthPassword) plus case/whitespace variants — all resolve with no error, proving the fix introduces no false refusal. TestAuthMethod_UnrecognisedValueRefuses drives 5 bad values and asserts each refuses with an error naming both the config key and the bad value.

git diff –stat

```

cmd/boba-ctl/deploy_test.go | 87 ++++++
+++++-----
cmd/boba-ctl/main.go         | 38 ++++++-----
2 files changed, 107 insertions(+), 18 deletions(-)

```