

USER_MANUAL

qBitTorrent-Fixed User Manual

Revision: 1 Last modified: 2026-06-06T00:00:00Z

Complete Guide to Using All 12 Search Plugins

Table of Contents

1. [Quick Start](#)
 2. [Plugin Overview](#)
 3. [Configuration](#)
 4. [Using the WebUI](#)
 5. [Using Private Trackers](#)
 6. [Merge Search Service](#)
 7. [Troubleshooting](#)
 8. [Testing](#)
 9. [FAQ](#)
-

Quick Start

1. Installation

Clone and setup

```
git clone https://github.com/yourusername/qBitTorrent-Fixed.git
cd qBitTorrent-Fixed
```

Run automated setup

```
./setup.sh
```

```
# Configure credentials (optional, for private trackers)
vim .env
```

2. Start Everything

```
# Terminal 1: Start qBittorrent
./start.sh
```

```
# Terminal 2: Start WebUI Bridge (for private trackers)
python3 webui-bridge.py
```

```
# Access WebUI
http://localhost:7186
# Login: admin / admin
```

Go Backend (Optional)

The Go/Gin backend replaces the Python FastAPI merge service and webui-bridge:

```
# Start with Go backend instead of Python
podman compose --profile go up -d
```

```
# Or build and run locally
cd qBitTorrent-go && ./scripts/build.sh
./qbittorrent-proxy # Starts merge service on port 7187
./webui-bridge      # Starts bridge on port 7188
```

3. Verify Installation

```
# Run all tests
./run-all-tests.sh
```

```
# Check plugin status
python3 tests/final_verification.py
```

Plugin Overview

Public Trackers (9 plugins)

These work immediately without configuration:

Plugin	Content Type	WebUI	Magnet Links	Notes
The Pirate Bay	General			Most popular

Plugin	Content Type	WebUI	Magnet Links	Notes
EZTV	TV Shows	✔	✗	Best for TV
Rutor	Russian	✔	✗	Russian content
LimeTorrents	General	✔	✔	Verified torrents
Solid Torrents	General	✔	✔	Fast search
TorrentProject	General	✔	✗	Comprehensive
torrents-csv	General			Open database
TorLock	General			No fake torrents
Jackett	Meta			Aggregates multiple

Private Trackers (3 plugins)

These require credentials:

Plugin	Content Type	Credentials Required	Best For
RuTracker	Russian	Username/Password	Russian content
Kinozal	Movies/TV	Username/Password	Movies and TV
NNMClub	General	Cookies	General content

Configuration

Setting Up Credentials

Edit `.env` file:

```
# Public trackers (no configuration needed)

# Private trackers (optional, for WebUI support)
RUTRACKER_USERNAME=your_rutracker_username
RUTRACKER_PASSWORD=your_rutracker_password

KINOZAL_USERNAME=your_kinozal_username
KINOZAL_PASSWORD=your_kinozal_password
```

```
# For NNMClub, get cookies from browser:
# 1. Login to nmclub.to in browser
# 2. Open developer tools (F12)
# 3. Go to Application/Storage > Cookies
# 4. Copy uid and pass cookies
NNMCLUB_COOKIES="uid=123456;
                 pass=abcdef1234567890abcdef1234567890"
```

Environment Variables

Variable	Default	Description
QBITTORRENT_DATA_DIR	/mnt/DATA	Download directory
QBITTORRENT_HOST	localhost	qBittorrent host
QBITTORRENT_PORT	7185	qBittorrent WebUI port
MERGE_SERVICE_PORT	7187	Merge Search Service port
MERGE_SERVICE_HOST	0.0.0.0	Merge service bind address
PROXY_PORT	7186	Download proxy port
BRIDGE_PORT	7188	WebUI Bridge port
LOG_LEVEL	INFO	Logging level
ALLOWED_ORIGINS	—	CORS origins (comma-separated, no wildcards in prod)
MAX_CONCURRENT_SEARCHES	5	Concurrent tracker search cap
DISABLE_THEME_INJECTION	—	Set to 1 to disable cross-app theme
OMDB_API_KEY	—	OMDb metadata API key
TMDB_API_KEY	—	TMDB metadata API key
ANILIST_CLIENT_ID	—	AniList API client ID

Install Paths

Path	Purpose
config/qBittorrent/	qBittorrent configuration (auto-created by container)
config/qBittorrent/nova3/engines/	Search plugin engine files
config/download-proxy/	Download proxy config + hooks
config/merge-service/	

Path	Purpose
	Scheduler persistence (scheduling.json)
plugins/	Plugin source of truth (canonical)
plugins/community/	Non-canonical/community plugins
frontend/	Angular 21 dashboard source

CLI Flags

```

./start.sh -p      # Pull images before starting
./start.sh -s      # Show container status after starting
./start.sh -v      # Verbose output

./stop.sh -r       # Remove containers after stopping
./stop.sh --purge  # Remove containers AND images

./ci.sh            # Full CI pipeline
./ci.sh --quick    # Syntax + unit tests only
./ci.sh --tests-only # Skip syntax checks

scripts/run-tests.sh hermetic # Fast tests (no services)
scripts/run-tests.sh live     # Tests requiring running
                             containers
scripts/run-tests.sh all      # Everything

scripts/scan.sh --all         # Run all security scanners
scripts/scan.sh pip-audit ruff # Run specific scanners

```

Plugin Installation

```

./install-plugin.sh --all          # Install all plugins
./install-plugin.sh rutracker rutor # Install specific plugins
./install-plugin.sh --verify       # Verify all plugins
                             installed
./install-plugin.sh --local --all  # Install for desktop app

```

Plugins are copied from plugins/X.py → config/qBittorrent/nova3/engines/X.py. Always edit the source in plugins/ — the engines directory is clobbered on reinstall.

Using the WebUI

Basic Search

1. Open <http://localhost:7186>
2. Login with admin/admin

3. Click "Search" tab
4. Enter search term (e.g., "ubuntu")
5. Select plugin from dropdown
6. Click "Search"

Downloading Torrents

Public Trackers (PirateBay, EZTV, etc.)

1. Search for content
2. Click download icon ()
3. Torrent appears in Transfer list
4. Download starts automatically

Private Trackers (RuTracker, Kinozal, NNMClub)

Option A: Using WebUI Bridge (Recommended)

1. Start WebUI Bridge: `python3 webui-bridge.py`
2. Search for content
3. Click download icon
4. Bridge handles authentication automatically

Option B: Using Desktop App

1. Install plugins locally: `./install-plugin.sh --local --all`
2. Open qBittorrent Desktop App
3. Go to View → Search Engine
4. Downloads work without bridge

Option C: Manual Download

1. Search in WebUI
 2. Note the torrent name
 3. Go to tracker website directly
 4. Download .torrent file
 5. Upload to qBittorrent WebUI
-

Using Private Trackers

RuTracker

Requirements: - Active account on rutracker.org - Valid username and password

Setup:

```
# Add to .env
RUTRACKER_USERNAME=your_username
RUTRACKER_PASSWORD=your_password
```

```
# Restart container
./restart.sh
```

Usage: 1. Enable RuTracker in Search Plugins 2. Search for Russian content 3. Click download (works with WebUI Bridge)

Tips: - RuTracker has the best Russian content - Very reliable for software and movies - Works best with WebUI Bridge

Kinozal

Requirements: - Active account on kinozal.tv - Valid username and password

Setup:

```
# Add to .env
KINOZAL_USERNAME=your_username
KINOZAL_PASSWORD=your_password
```

Usage: 1. Enable Kinozal in Search Plugins 2. Search for movies/TV shows 3. Works with WebUI Bridge

NNMClub

Requirements: - Active account on nnmclub.to - Cookie-based authentication

Setup:

```
# Get cookies from browser
# Add to .env
NNMCLUB_COOKIES="uid=your_uid; pass=your_pass_hash"
```

Getting Cookies: 1. Login to nnmclub.to in browser 2. Press F12 (Developer Tools) 3. Go to Application/Storage → Cookies 4. Find uid and pass cookies 5. Copy values to .env

Merge Search Service

The Merge Search Service is a unified search interface that queries multiple private trackers simultaneously, deduplicates results, and presents them in a single dashboard.

What It Does

- Searches **RuTracker**, **Kinozal**, and **NNMClub** in parallel
- Deduplicates results that appear on multiple trackers
- Detects quality tags (e.g., 1080p, 4K, WEB-DL, Blu-ray) automatically
- Proxied downloads handle authentication cookies transparently

Accessing the Dashboard

Open your browser to:

`http://localhost:7187/`

The dashboard runs inside the qbittorrent-proxy container and is available whenever containers are running. With the Go backend (`--profile go`), the same dashboard is served by the Go binary.

Dashboard Usage

1. **Search** — Enter a query and press Search. Results from all configured trackers appear in a single list.
2. **Download** — Click the download button on any result. The proxy intercepts the tracker URL and fetches the .torrent file using stored credentials.
3. **Active Torrents** — The dashboard shows currently active downloads from the qBittorrent instance.

API Endpoints (Power Users)

Endpoint	Method	Description
<code>/api/search?q=<query></code>	GET	Search all configured trackers
<code>/api/search?q=<query>&tracker=rutracker</code>	GET	Search a specific tracker
<code>/api/download</code>	POST	Download a torrent by URL
<code>/api/torrents/active</code>	GET	List active downloads
<code>/api/health</code>	GET	Service health check

Example:

```
curl "http://localhost:7187/api/search?q=ubuntu&tracker=rutracker"
```


Configuration

The merge service uses the same environment variables as the plugins. Set these in `.env`:

```
RUTRACKER_USERNAME=your_username  
RUTRACKER_PASSWORD=your_password
```

```
KINOZAL_USERNAME=your_username  
KINOZAL_PASSWORD=your_password
```

```
NNMCLUB_COOKIES="uid=123456; pass=abcdef1234567890"
```

Restart containers after changing credentials: `./stop.sh -r && ./start.sh`

Quality Detection

The service automatically detects quality tags from torrent names:

- **Resolution:** 4K, 2160p, 1080p, 720p, 480p
- **Source:** Blu-ray, WEB-DL, WEBRip, HDTV, CAM, TS
- **Codec:** HEVC, H.265, H.264, x265, x264
- **Audio:** Atmos, DTS-HD, DTS, AAC, FLAC

Results are tagged and can be filtered by quality in the dashboard.

Known Limitations

- **Credentials required** — RuTracker and Kinozal need valid username/password. NNMClub needs browser cookies. Trackers without configured credentials are skipped.
 - **RuTracker CAPTCHA** — If RuTracker presents a CAPTCHA, login will fail. Solve it in a browser first, then retry.
 - **Rate limiting** — Tracker websites may rate-limit frequent requests. The service includes basic throttling.
 - **No public trackers** — The merge service only covers private trackers. Use the qBittorrent search tab for public tracker plugins.
-

Troubleshooting

Issue: Plugin Not Showing in WebUI

Solution:

```
./install-plugin.sh --all  
podman restart qbittorrent  
# Hard refresh browser (Ctrl+Shift+R)
```

Issue: Download Doesn't Start (Private Trackers)

Cause: WebUI bypasses authentication

Solutions:

1. Use WebUI Bridge (Recommended)

```
python3 webui-bridge.py
```

2. Use Desktop App

```
./install-plugin.sh --local --all  
# Then use Desktop App
```

3. Check Credentials

```
cat .env  
# Verify username/password are correct
```

Issue: Search Returns No Results

Check: 1. Internet connection 2. Plugin is enabled in Search tab
3. Try different search terms 4. Check container logs: `podman logs qbittorrent`
5. Check proxy logs: `podman logs qbittorrent-proxy` 6. Verify tracker credentials: `curl http://localhost:7187/health`

Issue: Merge Service Returns 503

Cause: Service shutting down or not started

Check:

```
podman logs qbittorrent-proxy | tail -20  
curl http://localhost:7187/health
```

Issue: CORS Errors in Browser Console

Fix: Set `ALLOWED_ORIGINS` in `.env`:

```
ALLOWED_ORIGINS=http://localhost:4200,http://localhost:7187
```

Issue: Column Data Shows Zeros

Status: Fixed in this version. All plugins return real data for seeds, leech, and size.

Issue: Container Won't Start

Solution:

```
# Full reset
./stop.sh -r
podman system prune -f
./start.sh
```

Issue: RuTracker Login Fails (CAPTCHA)

Fix: Solve the CAPTCHA in a browser first, then retry. Cookies expire periodically.

Issue: Security Scan Failures

Fix: Run scanners individually to identify the issue:

```
scripts/scan.sh pip-audit ruff
# Check artifacts/scans/ for SARIF reports
```

Testing

Run All Tests

```
# Comprehensive test suite
./run-all-tests.sh

# Individual tests
python3 -m pytest tests/unit/ tests/e2e/ --import-mode=importlib
python3 tests/final_verification.py
python3 -m pytest tests/unit/ --import-mode=importlib
```

Test Results

Tests cover: - Plugin structure validation - Search
functionality - Download functionality - Column data
validation (seeds, leech, size) - Authentication handling

Expected result: **100% success rate**

FAQ

Q: Why create a fork instead of fixing upstream?

A: The WebUI limitation is in qBittorrent's core design. This fork provides a working solution while maintaining compatibility.

Q: Do I need to run WebUI Bridge?

A: Only if you want to use private trackers (RuTracker, Kinozal, NNMClub) in WebUI. Public trackers work without it.

Q: Is this legal?

A: The software itself is legal (Apache 2.0 license). Usage depends on your local laws and the content you download.

Q: Will this break with qBittorrent updates?

A: The plugin API is stable. Updates to qBittorrent should not break functionality.

Q: Can I add more plugins?

A: Yes! See docs/PLUGINS.md for adding custom plugins.

Q: Why does RuTracker work in Desktop App but not WebUI?

A: Desktop App uses nova2dl.py with authentication. WebUI sends URLs directly without auth. The WebUI Bridge fixes this.

Q: How do I update plugins?

A:

```
./install-plugin.sh --all  
./restart.sh
```

Q: Where are downloads saved?

A: Default: /mnt/DATA (configurable in .env)

Structure:

```
/mnt/DATA/  
├─ Incomplete/          # Partial downloads
```

```
|— Torrents/
|   |— All/           # All .torrent files
|   |— Completed/     # Completed .torrent files
|— [completed files]  # Finished downloads
```

Advanced Topics

Custom Plugin Development

See docs/PLUGIN_DEVELOPMENT.md for creating custom search plugins.

WebUI Bridge Configuration

Edit webui-bridge.py:

```
QBITTORRENT_HOST = 'localhost' # Change if remote
QBITTORRENT_PORT = 7186        # WebUI port
BRIDGE_PORT = 7188             # Bridge port
```

Backup and Restore

Backup:

```
# Config
tar czf qbittorrent-backup-$(date +%Y%m%d).tar.gz config/

# Plugins
tar czf plugins-backup-$(date +%Y%m%d).tar.gz plugins/
```

Restore:

```
tar xzf qbittorrent-backup-YYYYMMDD.tar.gz
tar xzf plugins-backup-YYYYMMDD.tar.gz
./restart.sh
```

Support

Getting Help

1. **Documentation:** Read all docs in docs/ folder
2. **Tests:** Run ./run-all-tests.sh to diagnose issues
3. **Logs:** Check podman logs qbittorrent
4. **Issues:** Report on GitHub

Contributing

1. Fork the repository
 2. Create a feature branch
 3. Make changes
 4. Run tests: `./run-all-tests.sh`
 5. Submit pull request
-

Version History

v2.0.0 (Current)

- All 12 plugins working
- WebUI Bridge for private trackers
- Comprehensive test suite
- Full documentation

v1.0.0

- Initial release
 - 4 Russian trackers
-

Last Updated: March 2025

Version: 2.0.0

License: Apache 2.0