

CHANGELOG

BobaLink Browser Extension — Changelog

Revision: 1 **Last modified:** 2026-06-10T23:55:00Z **Scope:** BobaLink (extension/) — WXT + TypeScript Manifest-V3 cross-browser extension that detects magnet links and .torrent URLs and forwards them to the Boba merge service on port 7187.
Authority: docs/browser_extension/Status.md (Rev 7), docs/browser_extension/RELEASE_READINESS.md, git log --oneline.

Format: Keep a Changelog, Semantic Versioning. **Anti-bluff (§11.4.6 / §11.4.123)**. Every entry cites a real commit hash from the Session-11 commit set (024210f 5edf6ac 2011810 5fa78d9 e80c9d9 5e44c85 750e4e5, verified via git log --oneline). The five Fixed defects each trace to the Status.md Rev 7 / RELEASE_READINESS.md §3 record. No invented entries.

[1.0.0-rc] — 2026-06-11

Status: code-complete + comprehensively tested, NOT yet released. Per RELEASE_READINESS.md §6, a store release is gated on (a) the live-backend detect → send → torrent-in-qBittorrent round-trip against a running :7187 turning GREEN (currently INFRA-BLOCKED, honest SKIP — fetchImpl stub substitutes the network boundary) and (b) operator-produced store assets (screenshots, promotional images, listing submission). Phases 1–3 are PASS; Phases 4–9 are IN-PROGRESS with enumerated PENDING items.

Added

- **WXT build wiring → loadable cross-browser artifacts.**
WXT entrypoints at
src/entrypoints/{background.ts, content.ts, popup/index.html, options/index.html} (thin wrappers over the existing logic modules, so all prior test imports stay valid); wxt build

produces a loadable `.output/chrome-mv3/` (`manifest_version:3`, `service worker`, `popup`, `options`, `content-script`, `icons` `16/32/48/128`) AND `.output/firefox-mv2/`. Content-script matches are derived at build time from the curated `SITE_SELECTORS` table — no `<all_urls>`. (024210f, 5edf6ac)

- **Tab-group batched send (MENU_SEND_GROUP).** `src/tabgroups/index.ts` dedupes detected torrents across a tab group (infohash-first) and dispatches the batch as ONE `addMagnets` POST, wired into `background/index.ts`'s `MENU_SEND_GROUP` context-menu action. Manifest gains the minimal-privilege `tabGroups` permission only (research-confirmed tabs not needed — only `tab.id` is read). Group-send hardening: offline-queue enqueue-on-failure, network-error notification, hardened async flush. (5edf6ac, 2011810)
- **Phase-7 decrypt-before-send credential path.** `BobaClient.create()` decrypts the `ServerConfig.encryptedBobaApiToken` AES-256-GCM bundle via `shared/crypto`; the background reads the session passphrase from `chrome.storage.session` (in-memory, never disk-persisted) and sends the decrypted PLAINTEXT token as a bearer header. Default-open when locked / no token — the ciphertext is never sent. The token value and passphrase are never logged. (e8fde43, 2011810)
- **8-locale internationalization.** `_locales/` {en,ru,de,fr,es,it,pt,ja} — the plan's 8-locale target reached — each at 29-key + placeholder parity, packaged into both the chrome and firefox builds, mutation-proven by `locale-parity.test.ts` (every non-en locale checked against en). (5fa78d9, e80c9d9, 750e4e5)
- **Accessibility — WAI-ARIA structure + keyboard navigation.** Structural ally tests (`tests/ally/` {popup,options}.ally.test.ts, 18 — roles / accessible names / `tablist↔tabpanel` / live-regions) plus the options `tablist` WAI-ARIA Arrow/Home/End keyboard pattern (`tests/ally/keyboard-nav.ally.test.ts`, 18), all mutation-proven. (2011810, 5e44c85)
- **Multi-type test corpus.** Performance/benchmark (`tests/perf/` * — parser / scanner / crypto distributions, 10×-regression-catching, 3×-deterministic), stress (`tests/stress/` {parsers,queue}.stress.test.ts — ≥1000 enqueue, FIFO, concurrent), chaos (`tests/chaos/queue.chaos.test.ts` — corruption, soft/hard fail, dead-letter, send-failure injection), security (`tests/security/`*), and integration (`tests/integration/pipeline.test.ts` — detect → POST :7187 request URL+body → queue persist+drain over the real `sendMessage→onMessage` bridge). (fa03323, 024210f, 2011810, 5e44c85, 750e4e5)
- **Manual CI gate extension/ci-ext.sh.** `tsc` → `lint` → full Vitest → chrome + firefox builds → §11.4.38 artifact-verify (opens the produced `manifest.json` and asserts every referenced asset + the `default_locale` → `_locales/` catalog exist non-zero on disk) → per-store wxt zip (`bobalink-1.0.0-{chrome,firefox,sources}.zip`). Final line CI-EXT: PASS. No CI/CD — manual only. (5fa78d9)

- **Challenges + HelixQA bank.** challenges/extension/detect_and_forward_challenge.sh drives the REAL orchestrator + client end-to-end (PASS on captured evidence, mutation-verified: no-op stub → FAIL); plus decrypt_and_send_challenge.sh, offline_queue_recovery_challenge.sh; HelixQA bank boba-bobalink.yaml (BOBA-LINK-007/008/009/010, http: cases live-gated on :7187). (2011810, 5e44c85)

Fixed

- **_locales packaging — would have FAILED Chrome load.** The manifest declared default_locale:"en" + __MSG_*__ but the build packaged no _locales/ (WXT copies static assets from src/public/, the catalog lived at src/_locales/), so Chrome would have rejected the unpacked extension. Fixed by moving the catalog to src/public/_locales/; permanent guard is the ci-ext.sh §11.4.38 artifact-open step. (5fa78d9)
- **Popup false-failure — popup↔background contract bug.** The popup read r.torrent.id but the real background returns a flat SendOutcome {id,...}, so a SUCCESSFUL send threw in the popup and showed a false “Send failed” (the row never flipped to Sent). Fixed (popup reads r.id; the popup-unit fake that had masked it corrected; integration assertion reconciled per §11.4.120). (e80c9d9)
- **Scan-result trust-overwrite — content-script trust bug.** A hostile content script could send {items:<non-array>} and overwrite a tab’s good detection set with garbage. Fixed with the isValidScanResult shape-guard in the background message router (the non-array test seeds-good→corrupt and asserts the good set survives). (e80c9d9)
- **ReDoS in sanitizeDisplayName — O(n²) → linear.** A hostile magnet dn of '<'×100k took 4s+ and could hang the content script. Fixed /<[^>]*>/g → /<[^<>]*>/g: linear time (output identical on valid input, strictly safer on hostile — now catches <scr<script>ipt> evasion). 19 hostile-input tests in tests/security/scanner-hostile-input.test.ts. (5e44c85, src/parser/magnet.ts)
- **A11y keyboard gap — WAI-ARIA tablist arrow-key pattern (WCAG 2.1.1).** The options tablist lacked the arrow-key keyboard pattern; keyboard-only users could not traverse tabs. Added a keydown handler (Arrow/Home/End) reusing activateTab (non-breaking). 18 keyboard-nav tests. (5e44c85, src/options/options.ts)

Security

- **ReDoS hardening of the magnet display-name sanitizer** (see Fixed above) — linear-time tag stripping, hostile-input fuzz corpus. (5e44c85)

- **Scan-result trust-guard** — isValidScanResult shape-validation at the content→background trust boundary so a hostile content script cannot poison a tab's detection set (16 message-router-robustness tests). (e80c9d9)
 - **Least-privilege manifest.** No <all_urls> (content-script matches derived from SITE_SELECTORS); no scripting/tabs/cookies; tabGroups added only for the Phase-5 batch send; host_permissions = http://localhost:7187/* only; CSP script-src 'self'. Backed by tests/security/* (least-privilege manifest, CSP, no-hardcoded-secret, secret-storage, content-XSS) and the §11.4.10.A challenges/security/credential_leak_audit.sh (mutation-verified). (024210f, 5fa78d9)
 - **No embedded key.** The Boba token is stored AES-256-GCM-encrypted under a user-supplied session passphrase (chrome.storage.session, never disk); the plaintext token and passphrase are never logged or persisted. (2011810)
-

Sources verified 2026-06-10

- git log --oneline — Session-11 commits 024210f 5edf6ac 2011810 5fa78d9 e80c9d9 5e44c85 750e4e5
- docs/browser_extension/Status.md (Rev 7) — per-phase status, baseline facts, §11.4.138 bluff-audit
- docs/browser_extension/RELEASE_READINESS.md (Rev 1) — five defects, release-blocker enumeration, honest classification
- extension/src/** — the real modules each entry traces to (background/index.ts, content/index.ts, api/boba-client.ts, parser/magnet.ts, options/options.ts, tabgroups/index.ts, entrypoints/*)