

README

E2E Live-Stack QA Run — e2e-live-20260606

Revision: 1 **Last modified:** 2026-06-06T15:00:00Z

Fully-automated end-to-end run (§11.4.83, §11.4.98) driving the LIVE Boba merge-search stack at <http://localhost:7187> over real HTTP — no human in the loop, re-runnable. Test source: `tests/e2e/test_live_stack_evidence.py`.

Anti-bluff posture (§11.4): every assertion targets a **user-observable outcome** (response-body fields a real dashboard/client consumes), not a bare status code. Flaky public-tracker specifics are deliberately NOT asserted (false-result risk); only deterministic facts are pinned. When the service is unreachable, tests SKIP-with-reason (§11.4.3) — never fake-pass.

What was exercised + observed

#	Endpoint / behaviour	User-observable assertion	Evidence file
1	GET /health	body status=="healthy" + service identity present	health.json
2	POST /api/v1/search/sync query debian	status=="completed", total_results>0, real result objects carry name/size/tracker/download_urls	search_debian.json
2b	same search — genuine fan-out	≥1 tracker status=="success" WITH rows; every tracker_stats.query=="debian"	search_debian_successful_tracker_stats.json
3	Credentialed path (IPTorrents)	iptorrents authenticated==true in tracker_stats (logged in with .env creds)	iptorrents_stat.json
4	GET /api/v1/auth/status		auth_status.json

#	Endpoint / behaviour	User-observable assertion	Evidence file
		structure lists rutracker/ iptorrents/nnmclub/kinozal each with bool has_session	
5	GET /api/v1/ auth/ nnmclub/ status (BOB-006)	body has bool authenticated field	nnmclub_status_DEPLOYMENT_DRIFT
6	GET /api/v1/ config w/ custom Host	qbittorrent_url derives from Host header, NOT hardcoded localhost (CONST-XII)	config_custom_host.json
7	SSE POST / search + GET /search/ stream/{id}? token=	real lifecycle SSE frames (search_start/ tracker_started/ search_complete) reach an EventSource client	sse_frames_sample.txt, sse_events_observed.json

Observed facts (from captured evidence)

- total_results for debian = **1303** (varies per run; deterministic floor asserted is >0).
- Successful trackers this run included academictorrents, bitsearch, iptorrents, limetorrents, linuxtracker, nyaa, piratebay, pirateiro, rutor, snowfl (specific set is non-deterministic; ≥ 1 asserted).
- IPTorrents: status=success, authenticated=true, results_count=49 — the credentialed login path genuinely works end-to-end.
- /api/v1/config with Host: boba.example.com:9999 returned qbittorrent_url=http://boba.example.com:7186 — derived from the request Host, no localhost leak (CONST-XII satisfied).
- SSE stream delivered live event: search_start (+ tracker_started) frames to a streaming client.

SKIP (legitimate, §11.4.3 + §11.4.108 finding)

GET /api/v1/auth/nnmclub/status → 404 on the LIVE service. The route exists in source (download-proxy/src/api/auth.py, @router.get("/nnmclub/status"), BOB-006), but the running qbittorrent-proxy container exposes only /auth/rutracker/* + /auth/status (per live /openapi.json). This is a genuine

SOURCE→ARTIFACT deployment drift (§11.4.108): the fix is committed but not yet deployed. The test captures the drift as evidence and SKIPS rather than fake-passing; once the container is rebuilt/restarted the assertion fires for real.

Re-run

```
source /tmp/boba-venv/bin/activate
python3 -m pytest tests/e2e/test_live_stack_evidence.py -v --
import-mode=importlib
```