

E2E Live-Stack QA Run “ e2e - live - 20260606

Revision: 1 Last modified: 2026-06-06T15:00:00Z

Fully-automated end-to-end run (Â§11.4.83, Â§11.4.98) driving the LIVE Boba merge-search stack at <http://localhost:7187> over real HTTP “ no human in the loop, re-runnable. Test source: `tests/e2e/test_live_stack_evidence.py`.

Anti-bluff posture (Â§11.4): every assertion targets a **user-observable outcome** (response-body fields a real dashboard/client consumes), not a bare status code. Flaky public-tracker specifics are deliberately NOT asserted (false-result risk); only deterministic facts are pinned. When the service is unreachable, tests SKIP-with-reason (Â§11.4.3) “ never fake-pass.

What was exercised + observed

#	Endpoint / behaviour	User-observable assertion	Evidence file
1	GET / health	body status=="healthy" + service identity present	health.json
2	POST / api/v1/search/sync query debian	status=="completed", total_results>0, real result objects carry name/size/tracker/download_urls	search_debian.json
2b	same search “ genuine fan-out	â‰¥1 tracker status=="success" WITH rows; every tracker_stats.query=="debian"	search_debian_successful_trackers
3	Credentialed path (IPTorrents) creds	iptorrents authenticated==true in tracker_stats (logged in with .env)	iptorrents_stat.json
4	GET / api/v1/auth/status	structure lists rutracker/iptorrents/nmclub/kinozal each with bool has_session	auth_status.json
5	GET / api/v1/auth/nmclub/status (BOB-006)	body has bool authenticated field	nmclub_status_DEPLOYMENT_DRIFT.t
6	GET / api/v1/config w/ custom Host	qbittorrent_url derives from Host header, NOT hardcoded localhost (CONST-XII)	config_custom_host.json
7	SSE POST /search + (search_start/tracker_started/	real lifecycle SSE frames	sse_frames_sample.txt, sse_events_observed.json

#	Endpoint / behaviour	User-observable assertion	Evidence file
	GET / search/ stream/ {id}? token=	search_complete) reach an EventSource client	

Observed facts (from captured evidence)

- `total_results` for `debian` = **1303** (varies per run; deterministic floor asserted is >0).
- Successful trackers this run included `academictorrents`, `bitsearch`, `iptorrents`, `limetorrents`, `linuxtracker`, `nyaa`, `piratebay`, `pirateiro`, `rutor`, `snowfl` (specific set is non-deterministic; $\hat{\%}$ asserted).
- IPTorrents: `status=success`, `authenticated=true`, `results_count=49` $\hat{\%}$ the credentialed login path genuinely works end-to-end.
- `/api/v1/config` with `Host: boba.example.com:9999` returned `qbittorrent_url=http://boba.example.com:7186` $\hat{\%}$ derived from the request `Host`, no `localhost` leak (CONST-XII satisfied).
- SSE stream delivered live event: `search_start` (+ `tracker_started`) frames to a streaming client.

SKIP (legitimate, $\hat{\%}$ 11.4.3 + $\hat{\%}$ 11.4.108 finding)

GET `/api/v1/auth/nmclub/status` $\hat{\%}$ **404 on the LIVE service**. The route exists in source (`download-proxy/src/api/auth.py`, `@router.get("/nmclub/status")`, BOB-006), but the running `qbittorrent-proxy` container exposes only `/auth/rutracker/*` + `/auth/status` (per live `/openapi.json`). This is a genuine SOURCE $\hat{\%}$ ARTIFACT deployment drift ($\hat{\%}$ 11.4.108): the fix is committed but not yet deployed. The test captures the drift as evidence and SKIPS rather than fake-passing; once the container is rebuilt/restarted the assertion fires for real.

Re-run

```
source /tmp/boba-venv/bin/activate
python3 -m pytest tests/e2e/test_live_stack_evidence.py -v --import-mode=i
```