

Tokens, API Keys & Environment Variables

Revision: 1 Last modified: 2026-06-06T00:00:00Z

Single source of truth for every credential, token, and API key the platform consumes.

Mandatory rows fail the service at boot if unset; **Optional** rows gate specific features and degrade silently.

Every value is read from either:

1. `./ .env` (gitignored “ project-local)
2. `~/ .qbitt .env` (user-level fallback)
3. Shell environment (highest priority)
4. `docker -compose .yml` defaults (lowest)

Loading order is defined in `.specify/memory/constitution.md` §III.

1. qBittorrent WebUI (built in)

Variable	Default	Required	Where to get it
WEBUI_USERNAME	admin	No	Hardcoded default per constitution III .
WEBUI_PASSWORD	admin	No	Same. Change in qBittorrent WebUI “ Options “ Web UI.

Portal: <http://localhost:7186/> **Change password:** qBittorrent WebUI “ Options “ Web UI “ Authentication “ Password.

2. Private tracker credentials

Each of these unlocks exactly one tracker in the merge search. None of them are mandatory “ the service simply skips the tracker if the variable is unset.

2.1 RuTracker (rutracker)

Variable	Required	Notes
RUTRACKER_USERNAME	Mandatory for RuTracker	Forum username.
RUTRACKER_PASSWORD	Mandatory for RuTracker	Account password.

Register: <https://rutracker.org/forum/register.php> **CAPTCHA refresh:** `GET /api/v1/auth/rutracker/captcha` (the dashboard surfaces this from the tracker chip “ see [SECURITY.md](#)).

2.2 Kinozal (kinozal)

Variable	Required	Fallback
KINOZAL_USERNAME	Mandatory for Kinozal	Falls back to IPTORRENTS_USERNAME if unset (shared-account rigs).
KINOZAL_PASSWORD	Mandatory for Kinozal	Falls back to IPTORRENTS_PASSWORD.

Register: <https://kinozal.tv/signup.php> (may require invite).

2.3 NNM-Club (nnmclub)

Variable	Required	Notes
NNMCLUB_COOKIES	Mandatory for NNM-Club	Full phpbb2mysql_* cookie string; copy from browser devtools after login.

Register: <https://nnmclub.to/forum/ucp.php?mode=register> **How to extract cookies:** sign in â†’ DevTools â†’ Application â†’ Cookies â†’ copy all phpbb2mysql_* entries into one name=value; name2=value2 string.

2.4 IPTorrents (iptorrents)

Variable	Required	Notes
IPTORRENTS_USERNAME	Mandatory for IPTorrents	Ratio-sensitive â€” see constitution VIII .
IPTORRENTS_PASSWORD	Mandatory for IPTorrents	

Register: <https://iptorrents.com/> (invite-only; apply via iptorrents.ooooo.io or similar). **Freeleech safety net:** automated downloads are restricted to &free=on results by the platform (constitution VIII).

3. Public tracker API keys (optional)

The 40+ public-tracker engines ship without authentication. A handful can use an API key for rate-limit uplift:

Variable	Used by	Required	Register
JACKETT_API_KEY	plugins/ jackett.py	Auto-discovered â€” start.sh extracts it from Jackettâ€™s config automatically. Manual override optional.	https://github.com/Jackett/Jackett#installation â†’ Admin â†’ Jackett API Key
JACKETT_URL	plugins/ jackett.py	Optional (default http://localhost:9117)	Your Jackett host
TORRENTSCSV_API_KEY		Optional	

Variable	Used by	Required	Register
	plugins/ torrentscsv.py		https://torrents-csv.com/ (no auth typically)

4. Metadata enrichment APIs (optional)

The merge service decorates results with poster/year/genre when these keys are present. Unset = no enrichment, service runs normally.

Variable	Required	Register	Purpose
TMDB_API_KEY	Optional	https://www.themoviedb.org/signup â†’ Settings â†’ API â†’ Request API Key (v3 auth)	Movie / TV posters + metadata
TVDB_API_KEY	Optional	https://thetvdb.com/api-information â†’ Subscribe	TV series metadata
MUSICBRAINZ_USER_AGENT	Optional (default qbittorrent-fixed/0.1 (milos85vasic@))	https://musicbrainz.org/doc/MusicBrainz_API â€” free, requires UA only	Music album lookup
ANIDB_CLIENT	Optional	https://anidb.net/software/add (register a client)	Anime metadata
OPENLIBRARY_USER_AGENT	Optional	https://openlibrary.org/dev/docs/api/ â€” free, UA only	eBook / audiobook metadata

5. Security scanner tokens (opt-in CI / local scans)

`./scripts/scan.sh` skips scanners whose tokens are missing. None of these are mandatory for the platform to function.

Variable	Required	Register
SNYK_TOKEN	Optional	https://app.snyk.io/ â†’ Account Settings â†’ Auth Token
SONAR_TOKEN	Optional	https://sonarcloud.io/account/security/ or your SonarQube instance
SONAR_HOST_URL	Optional	Default <code>http://localhost:9000</code> (the compose profile runs SonarQube there)
GITLEAKS_LICENSE	Optional	https://gitleaks.io/ for commercial use; the OSS scan runs without it

6. Observability endpoints (opt-in compose profile)

Start with `$COMPOSE_CMD -f docker-compose.yml -f docker-compose.quality.yml --profile observability up -d`.

Variable	Default	Required
GRAFANA_USER	admin	Optional
GRAFANA_PASSWORD	admin	Optional (change for anything beyond localhost)
PROMETHEUS_PORT	9090	Optional
GRAFANA_PORT	3000	Optional

Portals (after compose up): - Prometheus: <http://localhost:9090/> - Grafana: <http://localhost:3000/>

7. Orchestrator tuning (optional “Phase 3”)

All have safe defaults; tune for your workload.

Variable	Default	Purpose
ALLOWED_ORIGINS	* (with startup warning)	CORS whitelist. Comma-separated. Set this in production to avoid the wildcard warning.
MAX_CONCURRENT_TRACKERS	5	Semaphore cap on tracker fan-out.
MAX_ACTIVE_SEARCHES	256	TTLCache maxsize for in-flight searches.
ACTIVE_SEARCH_TTL_SECONDS	3600	Per-search metadata retention.
PENDING_CAPTCHAS_MAX	1024	CAPTCHA session TTLCache maxsize.
PENDING_CAPTCHAS_TTL_SECONDS	900	CAPTCHA session lifetime.
HOOK_LOG_MAXLEN	500	Deque cap for hook-execution logs.
MERGE_SERVICE_HOST	0.0.0.0	Bind interface for the merge service.
MERGE_SERVICE_PORT	7187	HTTP port.
MERGE_SERVICE_URL	http://localhost:7187	Where the download-proxy (and the injected theme bridge) find the merge service. Embedded verbatim into <code>__qbit_theme__</code> bootstrap.js.
PROXY_PORT	7186	Download proxy port.
BRIDGE_PORT	7188	WebUI bridge port.
THEME_STATE_PATH	/config/merge-service/theme.json	JSON file the merge service uses to persist the active palette + mode (see docs/CROSS_APP_THEME_PLAN.md).
DISABLE_THEME_INJECTION	(unset)	

Variable	Default	Purpose
		Escape hatch for the cross-app theme bridge. Set to 1 to make the download proxy stop injecting <code>__qbit_theme__/*</code> into qBittorrent's HTML responses and stop rewriting CSP. Useful if a qBittorrent upgrade ever breaks the bridge and you need to fall back to the untouched WebUI.

8. Data directory

Variable	Default	Required	Notes
QBITTORRENT_DATA_DIR	/mnt/DATA	No	Where qBittorrent stores torrents + incomplete + finished subdirs. Must be writable by PUID/PGID.
PUID	1000	No	Container user ID.
PGID	1000	No	Container group ID.

Quick-start matrix

Minimum-viable `.env` for *public-tracker-only* deployment:

```
# No credentials required â€” service runs out of the box.
QBITTORRENT_DATA_DIR=/mnt/DATA
```

Minimum-viable `.env` for *private-tracker* deployment:

```
# Pick the trackers you have accounts on.
RUTRACKER_USERNAME=your-user
RUTRACKER_PASSWORD=your-password

KINOZAL_USERNAME=your-user
KINOZAL_PASSWORD=your-password

NMCLUB_COOKIES="phpbb2mysql_data=...; phpbb2mysql_sid=..."

IPTORRENTS_USERNAME=your-user
IPTORRENTS_PASSWORD=your-password

QBITTORRENT_DATA_DIR=/mnt/DATA
```

Minimum-viable `.env` for *CI / scanner uplift*:

```
SNYK_TOKEN=your-token
SONAR_TOKEN=your-token
```

SONAR_HOST_URL=https://sonarcloud.io
ALLOWED_ORIGINS=https://qbit.example.com

Verification

After editing `.env`, restart the stack and probe auth:

```
./stop.sh && ./start.sh  
curl -s http://localhost:7187/api/v1/auth/status | python3 -m json.tool
```

Every tracker with `has_session: true` is live; anything with `has_session: false` either has wrong credentials or the tracker's login flow changed. For rutracker + iptorrents you can then trigger CAPTCHA refresh from the dashboard chip.

Related

- [SECURITY.md](#) – threat model and credential storage.
- [SCANNING.md](#) – scanner config that uses \$5 tokens.
- [OBSERVABILITY.md](#) – \$6 endpoints.
- [USER_MANUAL.md](#) – walk-through per tracker.
- [.specify/memory/constitution.md](#) – legal binding of the above.