

BOB-138 “ health check now covers every served port: closure evidence

Revision: 1 Last modified: 2026-08-20T15:02:00Z

The defect

docker-compose.yml service download-proxy (container qbittorrent-proxy) serves BOTH 7186 and 7187 from a single process, but its health check probed only 7186. Measured 2026-08-20 while the container reported Up 4 hours (healthy):

```
curl --max-time 6 http://localhost:7186/ -> HTTP 200 in 0.096s
curl --max-time 6 http://localhost:7187/ -> HTTP 000 after 6.004s
```

The merge search service “ the product’s primary capability “ had been dead for roughly two hours and no signal in the stack could observe it. §11.4.201: the guard asserted a PROXY signal (one port answers) instead of the real condition.

The fix

The health check now probes both ports. curl is ABSENT from the python:3.12-alpine image (verified in-container), so the python -c urllib probe is deliberate; urlopen raises on non-2xx or timeout, so either port failing exits non-zero.

Polarity evidence “ BOTH directions (§11.4.201(1))

A guard must refuse the broken state AND accept the healthy one. Goldenbad is port 7199, verified unbound (ss -ltn shows no listener), executed inside the real container:

#	command	state	exit	meaning
A	new two-probe	both ports live	0	accepts a genuinely healthy service
B	new two-probe	second port dead	1	the second probe is load-bearing
C			0	

#	command	state	exit	meaning
	old single-probe	second port dead		the false pass " i.e. the bug

Row C is the defect reproduced; row B is the same state refused after the fix; row A proves the fix does not refuse legitimate traffic.

A note on an INVALID earlier attempt (§11.4.6)

A first polarity run was executed against the live 7187 wedge, intending to use it as the golden-bad. Between the forensics and that run the wedge SELF-CLEARED (7187 returned to HTTP 200 in 0.021s), so both the old and the new command exited 0 " not because they behave alike, but because nothing was broken. That run proved nothing and is recorded here as void rather than quietly dropped. The table above is the re-run against a port that is genuinely dead.

Static guard

scripts/pre_build/check_cm_healthcheck_covers_served_ports.sh asserts every port declared in config/served_ports.yaml appears in that service's health check.

- RED (pre-fix): FAIL " download-proxy: serves [7186, 7187] but its healthcheck probes none of [7187], with the other services passing (so it is not a gate that simply refuses everything).
- GREEN (post-fix): PASS (5 services verified).

The gate also refuses to report success when it checked zero services, because a quiet zero from a blind instrument is indistinguishable from a clean tree (§11.4.201(6)).

A false positive the gate caught in its own input data

The manifest first declared qbittorrent-proxy-go: serves [7186, 7187, 7188], taken from CLAUDE.md prose. That is wrong: qBitTorrent-go/Dockerfile:16 runs a single binary (CMD ["/app/qbittorrent-proxy"]) which binds one port (ServerPort = MERGE_SERVICE_PORT = 7187). The gate consequently failed a service whose health check was already correct " the §11.4.201(1) false refusal this gate exists to prevent, committed in its own DATA. The manifest was corrected against source rather than prose, and the entry now carries that provenance.

Residual (tracked, not silently skipped)

- The gate is boba-local. Its logic carries no boba literal and belongs in constitution/scripts/gates/ per §11.4.177, but a concurrent agent

- is editing that directory and a two-writer race there risks losing work. Upstreaming is tracked, not skipped (Â§11.4.197).
- CLAUDE.md states the Go profile replaces the Python proxy on 7186, 7187, 7188â€¢, which the Dockerfile contradicts. Documentation defect, filed separately.

Live verification â€” and a restart-level trap worth recording

The fix was first applied with `./start.sh --reload-python`. The container came back healthy and both ports answered, which looked like success. The cache-bust check CLAUDE.md mandates (â€œVERIFY served content matches committed codeâ€¢) showed otherwise:

```
$ podman inspect qbittorrent-proxy --format '{{json .Config.Healthcheck.Test
["CMD-SHELL","python -c \"import urllib.request; urllib.request.urlopen(
'http://localhost:7186/', timeout=5)\" || exit 1"]'          <- STILL THE OL
```

`--reload-python` only RESTARTS the container, so a `docker-compose.yml` change is not applied. CLAUDE.md states this explicitly: a compose change requires `./start.sh --recreate`. Without the served-vs-committed check, this would have been reported as fixed while the old single-probe check was still running â€” the exact Â§11.4.108 SOURCE-vs-RUNTIME gap the guard exists to catch.

After `./start.sh --recreate`:

```
$ podman inspect qbittorrent-proxy --format '{{json .Config.Healthcheck.Test
["CMD-SHELL","python -c \"import urllib.request as u;
u.urlopen('http://localhost:7186/', timeout=5);
u.urlopen('http://localhost:7187/health', timeout=5)\" || exit 1"]
```

```
$ podman ps --filter name=qbittorrent-proxy --format '{{.Status}}'
Up 40 seconds (healthy)
```

```
$ curl --max-time 8 localhost:7186/          -> HTTP 200
$ curl --max-time 8 localhost:7187/health  -> HTTP 200
```

The two-probe check is now the one actually running, and the container reaches (healthy) through it â€” so the health signal now depends on the merge service being alive.

Also observed during the restart (feeds BOB-137)

```
level=warning msg="StopSignal SIGTERM failed to stop container qbittorrent
in 10 seconds, resorting to SIGKILL"
```

The service does not shut down cleanly on SIGTERM. That is consistent with the BOB-137 blocked-thread evidence and is recorded there as an additional symptom.