

Tokens, API Keys & Environment Variables

Revision: 2 **Last modified:** 2026-08-09T00:00:00Z

Single source of truth for every credential, token, and API key the platform consumes. **Mandatory** rows fail the service at boot if unset; **Optional** rows gate specific features and degrade silently.

Every value is read from either:

- 1. `./.env` (gitignored “project-local”)
- 2. `~/.qbit.env` (user-level fallback)
- 3. Shell environment (highest priority)
- 4. `docker-compose.yml` defaults (lowest)

Loading order is defined in `.specify/memory/constitution.md` §III.

1. qBittorrent WebUI (built in)

Variable	Default	Required	Where to get it
WEBUI_USERNAME	admin	No	Hardcoded default per constitution III .
WEBUI_PASSWORD	admin	No	Same. Change in qBittorrent WebUI “Options” Web UI.

Portal: <http://localhost:7186/> **Change password:** qBittorrent WebUI “Options” Web UI “Authentication” Password.

2. Private tracker credentials

Each of these unlocks exactly one tracker in the merge search. None of them are mandatory “the service simply skips the tracker if the variable is unset.”

2.1 RuTracker (rutracker)

Variable	Required	Notes
RUTRACKER_USERNAME	Mandatory for RuTracker	Forum username.
RUTRACKER_PASSWORD		Account password.

Variable	Required	Notes
	Mandatory for RuTracker	

Register: <https://rutracker.org/forum/register.php> **CAPTCHA refresh:** GET /api/v1/auth/rutracker/captcha (the dashboard surfaces this from the tracker chip â€” see [SECURITY.md](#)).

2.2 Kinozal (kinozal)

Variable	Required	Fallback
KINOZAL_USERNAME	Mandatory for Kinozal	Falls back to IPTORRENTS_USERNAME if unset (shared-account rigs).
KINOZAL_PASSWORD	Mandatory for Kinozal	Falls back to IPTORRENTS_PASSWORD.

Register: <https://kinozal.tv/signup.php> (may require invite).

2.3 NNM-Club (nnmclub)

Variable	Required	Notes
NNMCLUB_COOKIES	Mandatory for NNM-Club	Full phpbb2mysql_* cookie string; copy from browser devtools after login.

Register: <https://nnmclub.to/forum/ucp.php?mode=register> **How to extract cookies:** sign in â†’ DevTools â†’ Application â†’ Cookies â†’ copy all phpbb2mysql_* entries into one name=value; name2=value2 string.

2.4 IPTorrents (iptorrents)

Variable	Required	Notes
IPTORRENTS_USERNAME	Mandatory for IPTorrents	Ratio-sensitive â€” see constitution VIII .
IPTORRENTS_PASSWORD	Mandatory for IPTorrents	

Register: <https://iptorrents.com/> (invite-only; apply via iptorrents.ooooo.io or similar). **Freeleech safety net:** automated downloads are restricted to &free=on results by the platform (constitution VIII).

3. Public tracker API keys (optional)

The 40+ public-tracker engines ship without authentication. A handful can use an API key for rate-limit uplift:

Variable	Used by	Required	Register
JACKETT_API_KEY	plugins/ jackett.py	Auto-discovered â€” start.sh extracts it from Jackettâ€™s config automatically. Manual override optional.	https://github.com/Jackett/Jackett#installation â†’ Admin â†’ Jackett API Key
JACKETT_URL	plugins/ jackett.py	Optional (default http:// localhost:9117)	Your Jackett host
TORRENTSCSV_API_KEY	plugins/ torrentscsv.py	Optional	https://torrents-csv.com/ (no auth typically)

4. Metadata enrichment APIs (optional)

The merge service decorates results with poster/year/genre when these keys are present. Unset = no enrichment, service runs normally.

MetadataEnricher.resolve() tries every source in order until one returns a hit (download-proxy/src/merge_service/enricher.py): TMDB â†’ OMDb â†’ TVMaze â†’ AniList â†’ OpenLibrary â†’ MusicBrainz.

Variable	Required	Register	Purpose
TMDB_API_KEY	Optional	https://www.themoviedb.org/signup â†’ Settings â†’ API â†’ Request API Key (v3 auth)	Movie / TV posters + metadata (enricher.py:73,163,172)
OMDB_API_KEY	Optional	http://www.omdbapi.com/apikey.aspx	Movie metadata via OMDb, tried after TMDB (enricher.py:72,102,133-135)
ANILIST_CLIENT_ID	Optional	https://anilist.co/settings/developer	Anime metadata via the AniList GraphQL API (enricher.py:74,225-228)

The **TVMaze** (TV shows), **MusicBrainz** (music), and **OpenLibrary** (books) lookups (enricher.py:_lookup_tvmaze, _lookup_musicbrainz, _lookup_openlibrary) always run automatically as fallback sources â€” they read **no** environment variable, require **no** API key, and send no configurable User-Agent header. There is no TVDB_API_KEY, MUSICBRAINZ_USER_AGENT, ANIDB_CLIENT, or OPENLIBRARY_USER_AGENT env var anywhere in the codebase; a prior revision of this table documented those four as configuration knobs that do not exist in code (RD2-05 / RD2-37 â€” see [GOVERNANCE_AUDIT_2026-08-08_ROUND2.md](#)). There is no AniDB integration â€” anime metadata comes from AniList, gated by

ANILIST_CLIENT_ID above. There is no TVDB integration â€” TV-show fallback is TVMaze, which is keyless.

5. Security scanner tokens (opt-in CI / local scans)

./scripts/scan.sh skips scanners whose tokens are missing. None of these are mandatory for the platform to function.

Variable	Required	Register
SNYK_TOKEN	Optional	https://app.snyk.io/ â†’ Account Settings â†’ Auth Token
SONAR_TOKEN	Optional	https://sonarcloud.io/account/security/ or your SonarQube instance Default <code>http://localhost:9000</code> (the compose profile runs SonarQube there)
SONAR_HOST_URL	Optional	
GITLEAKS_LICENSE	Optional	https://gitleaks.io/ for commercial use; the OSS scan runs without it

6. Observability endpoints (opt-in compose profile)

Start with `$COMPOSE_CMD -f docker-compose.yml -f docker-compose.quality.yml --profile observability up -d`.

Variable	Default	Required
GRAFANA_USER	admin	Optional
GRAFANA_PASSWORD	admin	Optional (change for anything beyond localhost)
PROMETHEUS_PORT	9090	Optional
GRAFANA_PORT	3000	Optional

Portals (after compose up): - Prometheus: <http://localhost:9090/> - Grafana: <http://localhost:3000/>

7. Orchestrator tuning (optional â€” Phase 3)

All have safe defaults; tune for your workload.

Variable	Default	Purpose
ALLOWED_ORIGINS	* (with startup warning)	CORS whitelist. Comma-separated. Set this in production to avoid the wildcard warning.
MAX_CONCURRENT_TRACKERS	5	Semaphore cap on tracker fan-out.
MAX_ACTIVE_SEARCHES	256	TTLCache maxsize for in-flight searches.
ACTIVE_SEARCH_TTL_SECONDS	3600	Per-search metadata retention.
PENDING_CAPTCHAS_MAX	1024	CAPTCHA session TTLCache maxsize.
PENDING_CAPTCHAS_TTL_SECONDS	900	CAPTCHA session lifetime.
HOOK_LOG_MAXLEN	500	Deque cap for hook-execution logs.
MERGE_SERVICE_HOST	0.0.0.0	Bind interface for the merge service.
MERGE_SERVICE_PORT	7187	HTTP port.
MERGE_SERVICE_URL	http://localhost:7187	Where the download-proxy (and the injected theme bridge) find the merge service. Embedded verbatim into <code>__qbit_theme__/bootstrap.js</code> .
PROXY_PORT	7186	Download proxy port.
BRIDGE_PORT	7188	WebUI bridge port.
THEME_STATE_PATH	/config/merge-service/theme.json	JSON file the merge service uses to persist the active palette + mode (see docs/CROSS_APP_THEME_PLAN.md).
DISABLE_THEME_INJECTION	(unset)	Escape hatch for the cross-app theme bridge. Set to 1 to make the download proxy stop injecting <code>__qbit_theme__/*</code> into qBittorrent's HTML responses and stop rewriting CSP. Useful if a qBittorrent upgrade ever breaks the bridge and you need to fall back to the untouched WebUI.

8. Data directory

Variable	Default	Required	Notes
QBITTORRENT_DATA_DIR	/mnt/DATA	No	Where qBittorrent stores torrents + incomplete + finished subdirs. Must be writable by PUID/PGID.
PUID	1000	No	Container user ID.
PGID	1000	No	Container group ID.

Quick-start matrix

Minimum-viable `.env` for *public-tracker-only* deployment:

```
# No credentials required â€” service runs out of the box.  
QBITTORRENT_DATA_DIR=/mnt/DATA
```

Minimum-viable `.env` for *private-tracker* deployment:

```
# Pick the trackers you have accounts on.  
RUTRACKER_USERNAME=your-user  
RUTRACKER_PASSWORD=your-password  
  
KINOZAL_USERNAME=your-user  
KINOZAL_PASSWORD=your-password  
  
NNMCLUB_COOKIES="phpbb2mysql_data=...; phpbb2mysql_sid=..."  
  
IPTORRENTS_USERNAME=your-user  
IPTORRENTS_PASSWORD=your-password  
  
QBITTORRENT_DATA_DIR=/mnt/DATA
```

Minimum-viable `.env` for *CI / scanner uplift*:

```
SNYK_TOKEN=your-token  
SONAR_TOKEN=your-token  
SONAR_HOST_URL=https://sonarcloud.io  
ALLOWED_ORIGINS=https://qbit.example.com
```

Verification

After editing `.env`, restart the stack and probe auth:

```
./stop.sh && ./start.sh  
curl -s http://localhost:7187/api/v1/auth/status | python3 -m json.tool
```

Every tracker with `has_session: true` is live; anything with `has_session: false` either has wrong credentials or the tracker's login flow changed. For rutracker + iptorrents you can then trigger CAPTCHA refresh from the dashboard chip.

Related

- [SECURITY.md](#) " threat model and credential storage.
- [SCANNING.md](#) " scanner config that uses "5 tokens.
- [OBSERVABILITY.md](#) " "6 endpoints.
- [USER_MANUAL.md](#) " walk-through per tracker.
- [.specify/memory/constitution.md](#) " legal binding of the above.