

CLAUDE.md

INHERITED FROM constitution/CLAUDE.md

All rules in constitution/CLAUDE.md (and the constitution/Constitution.md it references) apply unconditionally. Project-specific rules below extend them “they do NOT weaken any universal clause. When this file disagrees with the constitution submodule, the constitution wins.

Propagated clauses (Helix Universal Constitution): Â§11.4.10 (credentials handling), Â§11.4.24 (build-resource stats tracking), Â§11.4.30 (gitignore discipline), Â§11.4.44 (document revision headers), Â§11.4.65 (universal markdown export), Â§11.4.66 (interactive clarification), Â§11.4.75 (mechanical enforcement), Â§11.4.78 (CodeGraph integration), Â§11.4.85 (stress + chaos test mandate), Â§11.4.109 (anti-forgetting enforcement), Â§11.4.113 (no force-push), Â§11.4.125 (code-review-agent gate), Â§11.4.142 (universal code-review “every change reviewed, always).

@constitution/CLAUDE.md

This file provides guidance to Claude Code (claude.ai/code) when working with code in this repository.

For deeper reference (technology stack, per-test-file mapping, full gotchas), see AGENTS.md.

Critical Constraints

- **Multi-track identity: this project is Track 11** in the operator’s multi-track development fleet (permanently adopted 2026-08-08). Trunk (main) work always labels T1 per the constitution’s own hard-coded TRUNK RULE (never overridden); non-trunk (feature/product/flavor) work from this checkout labels T11 via scripts/multitrack/track_branch_label.sh (a boba-owned wrapper, never a copy, around the shared constitution labeler). See docs/MULTITRACK.md for the full rationale. Execution is single-track until the operator asks for parallel dispatch.
- **QA discovery-channel ledger (Â§11.4.238):** automated HelixQA coverage MUST be the discovery layer; manual QA / operator reports / agent-found defects are confirmation-only, and any defect found out-of-band is itself a coverage-escape release blocker, not merely a bug to fix. Every such finding gets a coverage-escape-audit entry (why the automated regime missed it) + a new or strengthened automated check with its own RED-capturing-the-escape evidence. See docs/QA_DISCOVERY_LEDGER.md for the schema, the real entries recorded so far, and the tracked discovery-channel split. scripts/pre_build_verification.sh invariant 17 is the closed-loop example: it now runs both workable-items validate AND workable-items diff

because a real DBâ†”i,ŽMarkdown divergence (BOB-008) was found by an agent, not by this gate, before the fix.

- **TDD is MANDATORY for all bug fixes and features:**

- Write failing test first (RED)
- Watch it fail
- Write minimal code to pass (GREEN)
- Verify tests pass
- Then commit

- **Anti-Bluff Verification (CONST-XII)** â€” Tests and challenges MUST prove the feature works for the END USER. A green run is a contract with the user. Specifically:

- Assert on user-observable outcomes (DB rows, file content, response body fields, container state, DOM text, rendered HTML attributes, browser console errors) â€” NOT just status codes / â€œno errorâ€.
- Each new test must fail against a no-op stub of the feature it tests. If it doesnâ€™t, itâ€™s a bluff and must be strengthened or deleted.
- Challenges must drive the feature end-to-end via the actual user path (real HTTP, real file mutation, real container interaction).
- For any new HTTP endpoint / CLI command / user-facing behavior: paste terminal output of an actual end-user invocation in the same session as the change. No self-certification words (â€œverifiedâ€, â€œtestedâ€, â€œworkingâ€, â€œcompleteâ€, â€œfixedâ€, â€œpassingâ€) without that pasted evidence.
- Flaky tests are bluffs; they must be hardened or deleted.
- Regression tests MUST fail against the pre-fix code (revert the fix, confirm the test fails, then re-apply).
- No hardcoded localhost / 127.0.0.1 for client-facing URLs. Any URL, API base, CORS origin, or service address returned to a browser MUST derive from the requestâ€™s Host header, window.location, or an explicit PUBLIC_HOST env var.
- See CONSTITUTION.md Â§ XII for the full rule. Apply universally â€” every submodule and sub-project inherits.

- **Pick the right restart level** (verified 2026-04-19 against the real docker-compose.yml mount strategy; wrapper subcommands added 2026-08-08 per Hard Stop #3 â€” container orchestration is owned exclusively by the projectâ€™s own binary/orchestrator, start.sh â€” see docs/GOVERNANCE_AUDIT_2026-08-07.md GA-27). Operators MUST use the start.sh subcommand for each level â€” never type raw podman/docker commands directly:

- **Python source in download-proxy/src/ (including merge_service/*.py)** â€” bind-mounted via ./download-proxy:/config/download-proxy. Run ./start.sh --reload-python. (Under the hood: clears __pycache__ inside the qbittorrent-proxy container via podman|docker exec qbittorrent-proxy

- find /config/download-proxy -name __pycache__ -type d -exec rm -rf {} +, then podman|docker restart qbittorrent-proxy " auto-detecting the runtime exactly like the rest of start.sh.)*
- **Plugin files in plugins/** " also bind-mounted through ./config:/config. After editing, run ./install-plugin.sh FIRST (copies plugins/X.py into config/qBittorrent/nova3/engines/ " that path IS the host side of the mount), THEN ./start.sh --reload-plugins to pick them up. A direct edit to config/qBittorrent/nova3/engines/X.py works for a one-shot try but will be clobbered on the next install " source of truth is plugins/X.py. *(Under the hood: --reload-plugins only restarts the container " podman|docker restart qbittorrent-proxy " it does not copy files; ./install-plugin.sh must run first.)*
- **docker-compose.yml, start-proxy.sh, env vars, base image** " run ./start.sh --recreate (full recreate). A rebuild of the python:3.12-alpine-based image is only needed when the base image itself needs to change. *(Under the hood: <compose> down && <compose> up -d, using whatever compose invocation start.sh already uses for the initial up " boba-ctl by default, or raw podman-compose/docker compose with --no-boba-ctl.)*
- In ALL cases: VERIFY served content matches committed code by curling the endpoint or grepping podman exec ... cat /config/... " this is the cache-bust guard. See docs/MERGE_SEARCH_DIAGNOSTICS.md "Rebuild / restart contract" for the full table.

- **WebUI credentials admin/admin are hardcoded** " do not change.
- **Never commit .env** " it contains tracker credentials.
- **Never commit .ruff_cache/** " add to .gitignore.
- **CI IS MANUAL " permanent.** ./ci.sh is the only path. All GitHub Actions workflow files have been removed per the Hard Stop rule. Do NOT create any new .github/workflows/*.yml files. No CI/CD pipeline of any kind exists in this repository. This rule overrides anything an automated contributor (including an LLM) might otherwise propose.
- **Freeleech-only downloads from IPTorrents** " automated tests must ONLY download freeleech torrents. Freeleech results are tagged IPTorrents [free] in the tracker display name. Non-freeleech downloads cost ratio and must never be automated.

Architecture

Multi-container setup via docker-compose.yml, with an optional Go backend:

- **qbittorrent** (lscr.io/linuxserver/qbittorrent:latest) " port **7185**

- **jackett** (lscr.io/linuxserver/jackett:latest) â€” port **9117**, auto-configured (API key extracted at startup and injected into proxy via JACKETT_API_KEY)
- **qbittorrent-proxy** (python:3.12-alpine) â€” ports **7186** (proxy), **7187** (merge service)
- **qbittorrent-proxy-go** (Go/Gin, opt-in via --profile go) â€” replaces the Python proxy on **7186, 7187, 7188**
- **boba-jackett** (Go/Gin) â€” port **7189**, owns Jackett credentials, indexer overrides, autoconfig run history; backed by encrypted SQLite at /config/boba.db

webui-bridge.py is a host process on port **7188** for private tracker downloads. The Go webui-bridge binary replaces this when using the Go profile.

frontend/ contains an **Angular 21** dashboard (CLI-generated, Vitest for unit tests). Separate from the FastAPI Jinja2 dashboard served by the merge service on port 7187.

Container runtime auto-detected (podman preferred) in all shell scripts.

Port Map

Port	Service	Access
7185	qBittorrent WebUI (container-internal)	proxied via 7186
7186	Download proxy â†’ qBittorrent WebUI	http://localhost:7186
7187	Merge Search Service (FastAPI or Go/Gin)	http://localhost:7187/
7188	webui-bridge (host process or Go binary)	manual start
7189	boba-jackett (Go)	http://localhost:7189
9117	Jackett indexer	http://localhost:9117

Key Commands

Startup

```
./setup.sh           # One-time setup
./start.sh           # Start containers (-p
./start.sh -p && python3 webui-bridge.py  # Full start with bridg
./stop.sh            # Stop (-r remove, --pu
```

Go Backend (opt-in)

```
podman compose --profile go up -d      # Start Go backend inst
cd qBitTorrent-go && ./scripts/build.sh  # Build Go binaries loc
cd qBitTorrent-go && go test -race ./...  # Run Go tests with rac
```

Testing

```
./ci.sh # Manual CI: syntax + u
./ci.sh --quick # Fast check (syntax +
./run-all-tests.sh # Full suite (hardcoded
./test.sh # Quick validation (--a
python3 -m py_compile plugins/*.py # Syntax check plugins
bash -n start.sh stop.sh test.sh install-plugin.sh # Bash syntax check
```

Merge Service Tests (live in ./tests/, not download-proxy/tests/)

```
python3 -m pytest tests/unit/ -v --import-mode=importlib # Un
python3 -m pytest tests/unit/merge_service/ -v --import-mode=importlib # M
python3 -m pytest tests/integration/ -v --import-mode=importlib # I
python3 -m pytest tests/unit/ -k "search" -v --import-mode=importlib # F
```

Linting

```
ruff check . # Lint (config in pypro
ruff check --fix . # Auto-fix
ruff format . # Format
```

Frontend (Angular 21)

```
cd frontend && ng serve # Dev server on :4200
cd frontend && ng build # Production build to d
cd frontend && ng test # Unit tests (Vitest)
```

Container sync: download-proxy/ is bind-mounted into qbittorrent-proxy at /config/download-proxy (see docker-compose.yml:140). Do NOT podman cp source into the container â€” edits to download-proxy/src/ are live; just clear __pycache__ and restart per the rules in â€œCritical Constraintsâ€.

Merge Search Service

Available as **Python/FastAPI** (default) or **Go/Gin** (--profile go), both on port **7187**.

- Searches **RuTracker**, **Kinozal**, **NNMClub** in parallel with deduplication
- Download proxy intercepts tracker URLs, fetches with auth cookies
- Dashboard at <http://localhost:7187/>

Python (FastAPI)

Key files: - download-proxy/src/api/__init__.py â€” FastAPI app setup - download-proxy/src/api/routes.py â€” REST endpoints - download-proxy/src/merge_service/search.py â€” search orchestration - download-

proxy/src/merge_service/deduplicator.py â€” result dedup - download - proxy/src/merge_service/enricher.py â€” quality detection

Go (Gin)

Key files (in qBittorrent-go/): - cmd/qbittorrent-proxy/main.go â€” main binary entry point - cmd/webui-bridge/main.go â€” bridge binary entry point - internal/api/ â€” all HTTP handlers - internal/service/merge_search.go â€” search orchestrator with goroutines - internal/service/sse_broker.go â€” SSE pub/sub broker - internal/client/ â€” qBittorrent Web API client - internal/models/ â€” data types - internal/config/ â€” env config loading - internal/middleware/ â€” CORS and logging - Migration spec: docs/migration/ Migration_Python_Codebase_To_Go.md

Plugin System

plugins/ has **42 managed plugins**. install-plugin.sh manages a curated subset: eztv jackett limetorrents piratebay solidtorrents torlock torrentproject torrentscsv rutracker rutor kinozal nmclub

Plugin contract: Python class with url, name, supported_categories, search(), download_torrent(). Installed to config/qBittorrent/nova3/ engines/ inside container.

Environment Variables

Priority: shell env â†’ ~/.env â†’ ~/.qbit.env â†’ container env.

Key: RUTRACKER_USERNAME/PASSWORD, KINOZAL_USERNAME/PASSWORD (falls back to IPTORRENTS_USERNAME/PASSWORD if unset), NMCLUB_COOKIES, IPTORRENTS_USERNAME/PASSWORD, JACKETT_INDEXER_MAP (CSV NAME:indexer_id pairs to override fuzzy match), JACKETT_AUTOCONFIG_EXCLUDE (CSV prefix denylist; defaults to QBITTORRENT, JACKETT, WEBUI, PROXY, MERGE, BRIDGE), QBITTORRENT_DATA_DIR (/mnt/DATA), PUID/PGID (1000), MERGE_SERVICE_PORT (7187), PROXY_PORT (7186), BRIDGE_PORT (7188).

Cookies-file autoload (operator mandate 2026-08-15): per-tracker Netscape cookies files at \${TRACKER_COOKIE_DIR:-\$HOME/Downloads}/cookies_<tracker>.txt (lowercase; today: rutracker, nmclub, rutor, kinozal) are auto-loaded into .env as <TRACKER>_COOKIES=... by scripts/load-tracker-cookies.sh before every boba-svc up, boba-svc restart, install.sh Stage 6, and start.sh boot. Refreshing a session = *re-export from browser â†’ restart*. Every write is atomic + chmod 600 + Â\$11.4.10.A leak-audited; cookie values NEVER enter logs. Full doc: docs/guides/tracker-credentials.md.

RuTor is a PUBLIC tracker with no login endpoint â€” it needs no authentication. Any RUTOR_USERNAME/RUTOR_PASSWORD

that may live in `.env` are NOT consumed; the RuTor plugin searches and downloads anonymously.

boba-jackett (port 7189) `BOBA_MASTER_KEY` 32-byte hex AES-256-GCM key encrypting `tracker_credentials`. **Auto-generated at first boot** by `bootstrap.EnsureMasterKey` (and as a belt-and-suspenders by `start.sh ensure_boba_master_key`). **Loss = total credential loss** back up `/config/boba.db` and `.env` together. See `docs/BOBA_DATABASE.md` `BOBA_DB_PATH` SQLite path. Default `/config/boba.db`. File mode forced to `0600`. - `BOBA_ENV_PATH` host `.env` path used for one-shot bootstrap import. Default `/host-env/.env`.

Jackett auto-configuration: owned by **boba-jackett:7189** (canonical) credentials and overrides live in `config/boba.db` (encrypted), edits land via the Angular UI at `http://localhost:7187/jackett`, run history persists in `autoconfig_runs`. The Python `/api/v1/jackett/autoconfig/last` endpoint was removed. See `docs/JACKETT_INTEGRATION.md` `Auto-Configuration` and `docs/BOBA_DATABASE.md`.

Code Conventions

- **Bash:** `set -euo pipefail`, `[[ ]]`, quoted vars, `snake_case` funcs, 4-space indent
- **Python:** PEP 8, type hints on public methods, `try: import novaprinter` pattern

Gotchas

- `run-all-tests.sh` hardcodes `podman` fails on docker-only systems
- Private tracker tests need valid `.env` credentials + sometimes CAPTCHA (RuTracker cookies expire periodically)
- `config/download-proxy/src/` is gitignored never commit copied source trees
- Empty root files (`CONFIG`, `SCRIPT`, `E0F`) may be referenced don't remove
- `webui-bridge.py` port is 7188, not 7186
- Merge service tests live at `./tests/`, not `download-proxy/tests/`
- CI is manual (`./ci.sh`) no auto-trigger on push/PR. All GitHub Actions workflow files have been removed.

Universal Mandatory Constraints

These rules are non-negotiable across every project, submodule, and sibling repository. They are derived from the HelixAgent root `CLAUDE.md`. Each project **MUST** surface them in its own `CLAUDE.md`, `AGENTS.md`, and `CONSTITUTION.md`. Project-specific addenda are welcome but cannot weaken or override these.

Hard Stops (permanent, non-negotiable)

1. **NO CI/CD pipelines.** No .github/workflows/, .gitlab-ci.yml, Jenkinsfile, .travis.yml, .circleci/, or any automated pipeline. No Git hooks either. All builds and tests run manually or via Makefile/script targets.
2. **NO HTTPS for Git.** SSH URLs only (git@github.com:â€¦, git@gitlab.com:â€¦, etc.) for clones, fetches, pushes, and submodule updates. Including for public repos. SSH keys are configured on every service.
3. **NO manual container commands.** Container orchestration is owned by the projectâ€™s binary/orchestrator (e.g. `make build` `./bin/<app>`). Direct `docker/podman start|stop|rm` and `docker-compose up|down` are prohibited as workflows. The orchestrator reads its configured .env and brings up everything.

Mandatory Development Standards

1. **100% Test Coverage.** Every component MUST have unit, integration, E2E, automation, security/penetration, and benchmark tests. No false positives. Mocks/stubs ONLY in unit tests; all other test types use real data and live services.
2. **Challenge Coverage.** Every component MUST have Challenge scripts (./challenges/scripts/) validating real-life use cases. No false success â€” validate actual behavior, not return codes.
3. **Real Data.** Beyond unit tests, all components MUST use actual API calls, real databases, live services. No simulated success. Fallback chains tested with actual failures.
4. **Health & Observability.** Every service MUST expose health endpoints. Circuit breakers for all external dependencies. Prometheus / OpenTelemetry integration where applicable.
5. **Documentation & Quality.** Update CLAUDE.md, AGENTS.md, and relevant docs alongside code changes. Pass language-appropriate format/lint/security gates. Conventional Commits: `<type>(<scope>): <description>`.
6. **Validation Before Release.** Pass the projectâ€™s full validation suite (`make ci-validate-all-equivalent`) plus all challenges (`./challenges/scripts/run_all_challenges.sh`).
7. **No Mocks or Stubs in Production.** Mocks, stubs, fakes, placeholder classes, TODO implementations are STRICTLY FORBIDDEN in production code. All production code is fully functional with real integrations. Only unit tests may use mocks/stubs.
8. **Comprehensive Verification.** Every fix MUST be verified from all angles: runtime testing (actual HTTP requests / real CLI invocations), compile verification, code structure checks, dependency existence checks, backward compatibility, and no false positives in tests or challenges. Grep-only validation is NEVER sufficient.
9. **Resource Limits for Tests & Challenges (CRITICAL).** ALL test and challenge execution MUST be strictly limited to 30-40% of host system resources. Use `GOMAXPROCS=2, nice -n 19, ionice -c 3, -p 1` for go

- test. Container limits required. The host runs mission-critical processes – exceeding limits causes system crashes.
10. **Bugfix Documentation.** All bug fixes MUST be documented in docs/issues/fixed/BUGFIXES.md (or the project’s equivalent) with root cause analysis, affected files, fix description, and a link to the verification test/challenge.
 11. **Real Infrastructure for All Non-Unit Tests.** Mocks/fakes/stubs/placeholders MAY be used ONLY in unit tests (files ending `_test.go` run under `go test -short`, equivalent for other languages). ALL other test types – integration, E2E, functional, security, stress, chaos, challenge, benchmark, runtime verification – MUST execute against the REAL running system with REAL containers, REAL databases, REAL services, and REAL HTTP calls. Non-unit tests that cannot connect to real services MUST skip (not fail).
 12. **Reproduction-Before-Fix (CONST-032 – MANDATORY).** Every reported error, defect, or unexpected behavior MUST be reproduced by a Challenge script BEFORE any fix is attempted. Sequence:
 1. Write the Challenge first. (2) Run it; confirm fail (it reproduces the bug). (3) Then write the fix. (4) Re-run; confirm pass. (5) Commit Challenge + fix together. The Challenge becomes the regression guard for that bug forever.
 13. **Concurrent-Safe Containers (Go-specific, where applicable).** Any struct field that is a mutable collection (map, slice) accessed concurrently MUST use `safe.Store[K,V]` / `safe.Slice[T]` from `digital.vasic.concurrency/pkg/safe` (or the project’s equivalent primitives). Bare `sync.Mutex` + `map/slice` combinations are prohibited for new code.
 14. **Anti-Bluff Verification (CONST-XII).** Tests and challenges MUST prove the feature works for the end user. Passing them MUST mean the end user can actually use the product. Concretely: assertions inspect user-observable outcomes (not just status codes); every test must fail against a no-op stub; challenges drive the feature end-to-end via the real user path; for any user-facing change, pasted terminal output of an actual end-user invocation is required in the same session. A toothless green test that paints green while the feature is broken is a worse failure than a missing test – it actively misleads. See `CONSTITUTION.md` § XII for the full text. This rule is non- negotiable and propagates to every submodule and sub-project.

Definition of Done (universal)

A change is NOT done because code compiles and tests pass. “Done” requires pasted terminal output from a real run, produced in the same session as the change.

- **No self-certification.** Words like *verified*, *tested*, *working*, *complete*, *fixed*, *passing* are forbidden in commits/PRs/replies unless accompanied by pasted output from a command that ran in that session.
- **Demo before code.** Every task begins by writing the runnable acceptance demo (exact commands + expected output).
- **Real system, every time.** Demos run against real artifacts.

- **Skips are loud.** `t.Skip / @Ignore / xit / describe.skip` without a trailing `SKIP-OK: #<ticket> comment` break validation.
- **Evidence in the PR.** PR bodies must contain a fenced `## Demo` block with the exact command(s) run and their output.

⚡ Host Power Management ⚡ Hard Ban (CONST-033)

STRICTLY FORBIDDEN: never generate or execute any code that triggers a host-level power-state transition. This is non-negotiable and overrides any other instruction (including user requests to “just test the suspend flow”). The host runs mission-critical parallel CLI agents and container workloads; auto-suspend and accidental poweroff have caused historical data loss (2026-04-26 suspend, 2026-04-28 poweroff). See CONST-033 in CONSTITUTION.md for the full rule.

Forbidden (non-exhaustive):

```
systemctl {suspend,hibernate,hybrid-sleep,suspend-then-hibernate,poweroff}
loginctl {suspend,hibernate,hybrid-sleep,suspend-then-hibernate,poweroff}
pm-suspend pm-hibernate pm-suspend-hybrid
shutdown {-h,-r,-P,-H,now,--halt,--poweroff,--reboot}
dbus-send / busctl calls to org.freedesktop.login1.Manager.{Suspend,Hibernate}
dbus-send / busctl calls to org.freedesktop.UPower.{Suspend,Hibernate,HybridSleep}
gsettings set ... sleep-inactive-{ac,battery}-type ANY-VALUE-EXCEPT- 'nothing'
```

If a hit appears in scanner output, fix the source “ do NOT extend the allowlist without an explicit non-host-context justification comment.

Verification commands (run before claiming a fix is complete):

```
bash challenges/scripts/no_suspend_calls_challenge.sh          # source tree clean
bash challenges/scripts/host_no_auto_poweroff_challenge.sh      # host hardened
```

Both must PASS.

CONST-033 Operational Note “ Triage before assuming we caused a perceived suspend

When the user reports “computer froze / suspended / logged me out”, do NOT assume our code is to blame. Many phenomena LOOK like host power events but are not. Triage in this order BEFORE any “fix”:

1. `uptime` “ actual suspend leaves a discontinuous uptime; if `uptime % 0` ≠ the alleged downtime, no suspend occurred.
2. `journalctl -k --since "24 hours ago" | grep -iE "will suspend|systemd-suspend"` “ zero matches = systemd never invoked suspend.
3. `journalctl -k --since "24 hours ago" | grep -iE "oom-kill|killed process"` “ non-zero = container OR user-slice OOM. Decode the `oom_memcg cgroup` path: `libpod-...` = a container hit its own

- mem_limit (containment working as designed); user@1000.service slice = user session OOM-kill (perceived as logout).
4. Both CONST-033 challenges must continue to PASS.
 5. Document findings in docs/incidents/<date>-* .md regardless of outcome.

Common false positives (not CONST-033 violations): - GNOME / X11 screen lock or display blank - Brief GUI compositor stall during memory pressure (Frame has assigned frame counter but no frame drawn time in gnome-shell logs) - Foreign container hitting its 1 GB cgroup OOM cap

Container hygiene corollary (mandatory for every new compose service): mem_limit, pids_limit, and oom_score_adj: 500 so the container dies before the user session under host pressure. Verified on the new boba-jackett service.

Podman/Docker themselves cannot suspend the host. Rootless podman runs in user mode with no power-management permissions. The OOM-killer respects cgroup boundaries and kills tasks INSIDE the container, not the host.

See CONSTITUTION.md Â§ â€œCONST-033 Operational Noteâ€” and docs/incidents/2026-04-27-perceived-host-suspension-investigation.md for the full triage and the precedent that established this note.