

BobaLink “ Store Listing & Submission Checklist

Revision: 1 **Last modified:** 2026-06-10T22:00:00Z **Scope:** Chrome Web Store + Firefox AMO listing content and a manual submission checklist for BobaLink, the Boba Project browser extension (extension/). **Authority:** extension/wxt.config.ts, extension/package.json, docs/browser_extension/Status.md (Rev 5), docs/browser_extension/USER_GUIDE.md.

Accuracy note (Â§11.4.6): every permission justification, feature claim, and privacy statement below was traced to the real extension source/config “ the generated wxt.config.ts manifest (permissions / host_permissions / CSP / commands), package.json (version 1.0.0), the _locales/en/messages.json store-description string, and src/shared/constants.ts (SITE_SELECTORS, DEFAULT_URLS). Nothing reads as shipped that is not. Items not yet produced (screenshots, promo tiles) are marked (**TODO “ operator asset**).

Listing identity

Field	Value	Source
Name	BobaLink	_locales/en/messages.json extName; wxt.config.ts name: " __MSG_extName__ "
Version	1.0.0	wxt.config.ts version; package.json version
Category (suggested)	Productivity / Developer Tools	“
Default locale	English (en)	wxt.config.ts default_locale: "en"
Minimum Chrome version	109	wxt.config.ts minimum_chrome_version
Manifest version	MV3 (Chrome); MV2 build also produced for Firefox AMO	wxt.config.ts; ci-ext.sh builds chrome-mv3/ + firefox-mv2/
License	MIT	package.json

Short description (â‰‰ 132 characters)

This is the verbatim store-description string the extension already ships (_locales/en/messages.json extDescription) “ 91 characters, within both the Chrome (132) and Firefox (132) short-description limits:

Detects torrent files and magnet links, sending them to Boba Project's qBitTorrent dashboard

(Length: 91 characters.)

Detailed description

BobaLink finds magnet links and `.torrent` files on the pages you visit and forwards them to your own self-hosted Boba Project merge service, which adds them to qBittorrent for you. It is a privacy-first, least-privilege Manifest V3 extension: it never talks to qBittorrent directly, never collects your data, and only ever contacts the Boba merge service running on your own machine at `http://localhost:7187`.

What it does

- **Detects** magnet links and `.torrent` file URLs on any page, with an extra-tuned selector table for popular trackers.
- **Parses** each item to its BitTorrent infohash (`magnet bti h / .torrent â†’ SHA-1`) and **deduplicates by infohash**, so the same torrent is never sent twice.
- **Forwards** them to your local Boba merge service on port 7187, which adds them to qBittorrent server-side.
- **Tab-group batch send** (Chrome family): scan every tab in a tab group, deduplicate across the whole group, and send them as one batch.
- **Context-menu actions**: "Send magnet to Boba", "Send all on page", "Send tab group".
- **Keyboard shortcuts**: Send to Boba (`Ctrl/Cmd+Shift+B`), Scan page (`Ctrl/Cmd+Shift+S`), Open dashboard (`Ctrl/Cmd+Shift+D`).
- **A configurable options page** (7 tabs: Server, Download Prefs, Queue, Notifications, Detection, UI, Security) with an optional offline queue for failed sends.

Privacy & security first

- **No data collection.** BobaLink sends nothing to any third party. The only network destination is your own Boba merge service at `http://localhost:7187`.
- **Least privilege.** No tabs, no scripting, no cookies, no `<all_urls>`. The content script only runs on the curated tracker host list, not every site.
- **Delegate-by-default credentials.** In the normal localhost deployment BobaLink stores no decryptable secret â€” your Boba service already owns the qBittorrent and tracker credentials. The one optional secret (a Boba API token, only needed if your backend sets `BOBA_API_TOKEN`) is encrypted with AES-GCM-256 under a session passphrase you type, held only in `chrome.storage.session` and never written to disk or logged.
- **Tight CSP:** `script-src 'self'` (no `unsafe-inline / unsafe-eval`), `connect-src` scoped to `http://localhost:7187`.

Internationalization & accessibility

- UI message catalogs for English, Russian, German, and French; the browser auto-selects by UI language, falling back to English.
- The popup and options UI carry ARIA roles, accessible names, and `tablist/tabpanel` wiring.

Requires a running Boba Project backend. BobaLink is a companion to a self-hosted Boba Project install â€” it needs the Boba merge service reachable on `http://localhost:7187`. It is not a standalone downloader.

Status honesty (Â§11.4.6): the end-to-end detect â†’ send â†’ torrent-appears-in-qBittorrent path against a **live** backend is still **in progress** (Phase 4 in the plan). Detection, parsing, dedup, the popup/options UI, and the send-wiring are implemented and tested. Listing copy above describes the intended user-facing capability; do not publish to the public stores before Phase 4 live-backend integration lands (see `Status.md`).

Supported torrent sites (curated selector table)

Detection works on **any page** via the generic `magnet:` and `.torrent` link patterns. In addition, BobaLink ships a curated selector table (`SITE_SELECTORS` in `extension/src/shared/constants.ts`) tuned for these hosts. The content script's matches are derived from this table â€” BobaLink does **not** request `<all_urls>`. The table has **24 entries** (one generic pattern set plus 23 site-specific hosts):

#	Host	Notes
	â€” generic	<code>magnet / .torrent / download.php?id=</code> patterns applied everywhere
1	<code>1337x.to</code>	
2	<code>thepiratebay.org</code>	
3	<code>thepiratebay10.org</code>	
4	<code>rarbg.to</code>	
5	<code>rarbgtorrents.org</code>	
6	<code>yts.mx</code>	
7	<code>yts.lt</code>	
8	<code>eztv.re</code>	
9	<code>limetorrents.lol</code>	
10	<code>torrentgalaxy.to</code>	
11	<code>nyaa.si</code>	anime
12	<code>animetosho.org</code>	
13	<code>torrentz2.eu</code>	
14	<code>fitgirl-repacks.site</code>	
15	<code>rutracker.org</code>	Boba private tracker
16	<code>kinozal.tv</code>	Boba private tracker
17	<code>nnmclub.to</code>	Boba private tracker
18	<code>rutor.info</code>	Boba public tracker
19	<code>katcr.co</code>	Kickass Torrents
20	<code>demonoid.is</code>	
21	<code>iptorrents.com</code>	Boba private tracker
22	<code>torrentleech.org</code>	private
23	<code>beyond-hd.me</code>	private

#	Host	Notes
24	passthepopcorn.me	private

Permission-justification table

Both stores require a per-permission justification. Each row below traces to the literal `permissions / host_permissions` array in `extension/wxt.config.ts` (lines 28-40, `host_permissions` line 43). No permission is requested that is not justified here, and no justification claims a permission BobaLink does not request.

Permission	In manifest?	Justification
storage	Yes (<code>wxt.config.ts:29</code>)	Persist user settings, detected items per tab, the offline send queue, and send history (<code>chrome.storage.local</code>).
alarms	Yes (<code>wxt.config.ts:30</code>)	Wake the MV3 service worker to run periodic backend health checks (no content/host access).
notifications	Yes (<code>wxt.config.ts:31</code>)	Tell the user when a send succeeds or fails.
activeTab	Yes (<code>wxt.config.ts:32</code>)	Act on the page the user explicitly invokes BobaLink on (toolbar click / shortcut / context menu) â€” granted transiently, not a standing all-sites grant.
contextMenus	Yes (<code>wxt.config.ts:33</code>)	Provide the right-click "Send magnet to Boba", "Send all on page", "Send tab group" actions.
tabGroups	Yes (<code>wxt.config.ts:39</code>)	"Send tab group": read which group the clicked tab belongs to and enumerate the group's tabs via <code>chrome.tabs.query({groupId})</code> . Grants no host/content/URL access.
host_permissions: <code>http://localhost:7187/*</code>	Yes (<code>wxt.config.ts:43</code>)	Talk to the user's own local Boba merge service â€” the single network destination. Nothing else.

Permissions deliberately NOT requested (state this in the privacy review)

Not requested Why it's safe to omit

<code>tabs</code>	The tab-group batcher reads only <code>tab.id</code> (never <code>url/title/favIconUrl</code>), which per the Chrome docs needs no <code>tabs</code> permission.
<code>scripting</code>	Not requested â€” <code>wxt.config.ts</code> comment "scripting intentionally NOT requested" (least-privilege, Plan E Â§3.1).
<code>cookies</code>	Not requested â€” BobaLink never touches the user's cookies.
<code><all_urls></code>	Content-script match patterns are derived from the curated <code>SITE_SELECTORS</code> host list, not a blanket all-sites grant.

Privacy-policy summary

Use the following as the public privacy statement (both stores require a privacy policy / data-use disclosure). Every clause is accurate to the real network behavior – the only `host_permissions` entry and the only `connect-src` CSP origin is `http://localhost:7187`.

BobaLink collects no personal data and transmits no data to BobaLink's authors or any third party.

- The only network destination BobaLink contacts is the **Boba merge service on the user's own machine** at `http://localhost:7187` (the sole `host_permissions` entry and the sole non-`'self'` `connect-src` CSP origin).
- BobaLink sends only the magnet links / `.torrent` URLs the user chooses to forward, and an optional Boba API token (only if the user's backend requires one). Nothing is sent to any remote server controlled by BobaLink.
- Settings, detected items, the offline queue, and history are stored **locally** in the browser (`chrome.storage.local`).
- The optional Boba API token is encrypted at rest (AES-GCM-256, PBKDF2) under a **session passphrase** held only in `chrome.storage.session` (never on disk), and is never logged. With no passphrase, no token is stored.
- BobaLink uses no analytics, no telemetry, and no remote code.

CSP (verbatim, `wxt.config.ts:57–58`):

```
default-src 'self'; script-src 'self'; object-src 'self'; style-src 'self'
```

Required store-asset checklist

Asset	Chrome Web Store	Firefox AMO	Status
Icon 16—16	(used in manifest)	(used in manifest)	Done – <code>output/chrome-mv3/icons/16.png</code> (rasterized from <code>src/assets/icon.png</code> by <code>@wxt-dev/auto-icons</code>)
Icon 32—32	optional	used	Done – <code>icons/32.png</code>
Icon 48—48	required	required	Done – <code>icons/48.png</code>
Icon 128—128	required (store icon)	required	Done – <code>icons/128.png</code>
Short description (≈132 chars)	required	required (summary)	Done – see "Short description" above (91 chars)
Detailed description	required	required	Done – see "Detailed description" above
Privacy policy / data-use disclosure	required	required	Done – see "Privacy-policy summary" above
Permission justifications	required (single-purpose + per-permission) required	required (in review notes) required	Done – see "Permission-justification table" above

Asset	Chrome Web Store	Firefox AMO	Status
Screenshots (1280—800 or 640—400; 1, up to 5)			(TODO operator asset) capture popup + options + detection-in-action
Small promo tile 440—280	optional	n/a	(TODO operator asset)
Marquee promo tile 1400—560	optional	n/a	(TODO operator asset)
Promotional / featured images	optional	optional	(TODO operator asset)
Support / homepage URL	required	required	(TODO operator asset) Boba Project repo / docs URL

Icon note: only the four sizes 16 / 32 / 48 / 128 are produced and required; they are generated at build time from the single `src/assets/icon.png`. No other icon size is referenced by the manifest.

Submission checklist (manual NO CI/CD)

Per the Boba constitution Hard Stop (no CI/CD), packaging is performed by the manual `gate extension/ci-ext.sh` only there is no pipeline. Sequence:

- Pre-flight** `cd extension && npm install` (populate `node_modules`); ensure `node`, `npx`, `jq` are on `PATH`.
 - Run the manual gate** `cd extension && bash ci-ext.sh`. It runs, in order: `tsc` type gate `eslint` full vitest suite Chrome MV3 build Firefox build `11.4.38 artifact-asset` verification (opens the produced manifest and confirms every referenced asset + the `default_locale` catalog exist non-zero) `per-store wxt zip`. It prints `CI-EXT: PASS` only if every step passed.
 - Collect the artifacts** on `PASS`, `.output/` contains:
 - `bobalink-1.0.0-chrome.zip` upload to the **Chrome Web Store**.
 - `bobalink-1.0.0-firefox.zip` upload to **Firefox AMO**.
 - `bobalink-1.0.0-sources.zip` Firefox AMO source-code submission (AMO requires sources for built extensions).
 - Chrome Web Store** Developer Dashboard `new item` upload `bobalink-1.0.0-chrome.zip` paste the short description, detailed description, privacy disclosure, and per-permission justifications from this document upload screenshots + (optional) promo tiles (TODO operator asset) set the support/homepage URL (TODO operator asset) submit for review.
 - Firefox AMO** `addons.mozilla.org` submit a new add-on upload `bobalink-1.0.0-firefox.zip` upload `bobalink-1.0.0-sources.zip` when prompted for sources paste the summary, detailed description, and privacy notes add the permission justifications in the reviewer notes upload screenshots (TODO operator asset) submit for review.
 - Pre-submission gate (release-readiness)**: do **not** submit to the public stores until Phase 4 live-backend integration is **GREEN** with captured evidence (`Status.md` the detect `send` torrent-in-qBittorrent round-trip against a live `7187` backend is currently **in progress**). Listing copy is ready; the live-path proof is the remaining gate.
-

Sources verified

- extension/wxt.config.ts (permissions, host_permissions, CSP, commands, version, default_locale, minimum_chrome_version) â€” read 2026-06-10.
- extension/package.json (version: 1.0.0, name, MIT license) â€” read 2026-06-10.
- extension/src/shared/constants.ts (SITE_SELECTORS 24 entries, DEFAULT_URLS : 7187, ENCRYPTION, BOBA_TOKEN_HEADERS, ICON_SIZES) â€” read 2026-06-10.
- extension/src/public/_locales/en/messages.json (extDescription short string; locales en/ru/de/fr present on disk) â€” read 2026-06-10.
- extension/ci-ext.sh + .output/artifacts(bobalink-1.0.0-{chrome,firefox,sources}.zip, icons/{16,32,48,128}.png) â€” read 2026-06-10.
- docs/browser_extension/Status.md (Rev 5), docs/browser_extension/USER_GUIDE.md (Rev 1) â€” read 2026-06-10.