

MULTITRACK

Boba — Multi-Track Development Registration

Revision: 1 **Last modified:** 2026-08-08T17:10:00Z **Status:** active

Decision (operator mandate, 2026-08-08)

Boba permanently adopts the constitution's multi-track development discipline (§11.4.58 parallel work-unit pipeline, §11.4.176 work-division, §11.4.178 track-qualified identity, §11.4.182 work-stream labels, §11.4.187 automatic ruler orchestration, §11.4.192 continuous auto-backfill) as its **standing working mode going forward** — not a one-off exercise.

This checkout (/run/media/milosvasic/DATA4TB/Projects/boba, host ne zha) is permanently registered as the home of Track 11 in the operator's multi-track fleet, chosen to avoid colliding with track numbers already in use by other projects/hosts (/mnt/track1..4 are occupied elsewhere).

Execution scope right now (operator instruction, 2026-08-08): single-track only. No parallel background ruler/subagent streams have been spawned for this project yet. The identity/labeling convention below is adopted immediately and permanently; actual parallel dispatch is deferred until the operator asks for it.

Label convention

Every work-stream label for boba follows §11.4.182's (T<N>/<branch> - <alias> - <model> - <effort>) form, derived via scripts/multitrack/track_branch_label.sh (a thin, boba-owned

wrapper — never a copy — around the canonical, fleet-wide constitution/scripts/multitrack/track_branch_label.sh, per §11.4.28(B)/ §11.4.177 decoupling: shared engines are wrapped, never edited in place).

- **Trunk (main/master) work is ALWAYS T1** — the canonical script’s hard-coded TRUNK RULE (§11.4.182 amendment, 2026-07-28) is intentionally **never overridden**. This is deliberate: the rule exists so trunk work is never mistaken for “an unknown track” across the operator’s whole fleet, and weakening it here would misrepresent trunk work as a numbered track it isn’t.
- **Non-trunk work (feat//product//flavor/ branches per §11.4.195) dispatched from this checkout is T11**. The canonical script has no way to know that a checkout outside /mnt/track<N> should map to track 11 — it honestly emits T? there — so the wrapper’s only job is filling that specific ? in with 11, and only on non-trunk branches.

Verified 2026-08-08 (real invocation, on main):

```
$ bash scripts/multitrack/track_branch_label.sh  
(T1/main - milos85vasic - ? - xhigh)
```

(? for <model> is the labeler’s own honest fallback for this native-alias’s session-transcript lookup shape — not a bug in this wrapper.)

Cross-references

- scripts/multitrack/track_branch_label.sh — the boba-owned wrapper.
- constitution/scripts/multitrack/track_branch_label.sh — the canonical, inherited-by-reference engine this wrapper delegates to.
- docs/CONTINUATION.md — session handoff, references this decision.
- CLAUDE.md — Critical Constraints section carries a one-line pointer here.