

TOKENS_AND_KEYS

Tokens, API Keys & Environment Variables

Revision: 2 **Last modified:** 2026-08-09T00:00:00Z

Single source of truth for every credential, token, and API key the platform consumes. **Mandatory** rows fail the service at boot if unset; **Optional** rows gate specific features and degrade silently.

Every value is read from either:

1. `./.env` (gitignored — project-local)
2. `~/.qbit.env` (user-level fallback)
3. Shell environment (highest priority)
4. `docker-compose.yml` defaults (lowest)

Loading order is defined in `.specify/memory/constitution.md` §III.

1. qBittorrent WebUI (built in)

Variable	Default	Required	Where to get it
WEBUI_USERNAME	admin	No	Hardcoded default per constitution III .
WEBUI_PASSWORD	admin	No	Same. Change in qBittorrent WebUI → Options → Web UI.

Portal: <http://localhost:7186/> **Change password:** qBittorrent WebUI → Options → Web UI → Authentication → Password.

2. Private tracker credentials

Each of these unlocks exactly one tracker in the merge search. None of them are mandatory — the service simply skips the tracker if the variable is unset.

2.1 RuTracker (rutracker)

Variable	Required	Notes
RUTRACKER_USERNAME	Mandatory for RuTracker	Forum username.
RUTRACKER_PASSWORD	Mandatory for RuTracker	Account password.

Register: <https://rutracker.org/forum/register.php> **CAPTCHA refresh:** GET /api/v1/auth/rutracker/captcha (the dashboard surfaces this from the tracker chip — see [SECURITY.md](#)).

2.2 Kinozal (kinozal)

Variable	Required	Fallback
KINOZAL_USERNAME	Mandatory for Kinozal	Falls back to IPTORRENTS_USERNAME if unset (shared-account rigs).
KINOZAL_PASSWORD	Mandatory for Kinozal	Falls back to IPTORRENTS_PASSWORD.

Register: <https://kinozal.tv/signup.php> (may require invite).

2.3 NNM-Club (nnmclub)

Variable	Required	Notes
NNMCLUB_COOKIES	Mandatory for NNM-Club	Full phpbb2mysql_* cookie string; copy

Variable	Required	Notes
		from browser devtools after login.

Register: <https://nnmclub.to/forum/ucp.php?mode=register> **How to extract cookies:** sign in → DevTools → Application → Cookies → copy all phpbb2mysql_* entries into one name=value; name2=value2 string.

2.4 IPTorrents (iptorrents)

Variable	Required	Notes
IPTORRENTS_USERNAME	Mandatory for IPTorrents	Ratio-sensitive — see constitution VIII .
IPTORRENTS_PASSWORD	Mandatory for IPTorrents	

Register: <https://iptorrents.com/> (invite-only; apply via iptorrents.ooooo.io or similar). **Freeleech safety net:** automated downloads are restricted to &free=on results by the platform (constitution VIII).

3. Public tracker API keys (optional)

The 40+ public-tracker engines ship without authentication. A handful can use an API key for rate-limit uplift:

Variable	Used by	Required	Register
JACKETT_API_KEY	plugins/ jackett.py	Auto-discovered — start.sh extracts it from Jackett's config automatically. Manual override optional.	https://github.com/Jackett/Jackett#installation → Admin → Jackett API Key
JACKETT_URL	plugins/ jackett.py	Optional (default http:// localhost:9117)	Your Jackett host

Variable	Used by	Required	Register
TORRENTSCSV_API_KEY	plugins/ torrentscsv.py	Optional	https://torrentscsv.com/ (no auth typically)

4. Metadata enrichment APIs (optional)

The merge service decorates results with poster/year/genre when these keys are present. Unset = no enrichment, service runs normally.

MetadataEnricher.resolve() tries every source in order until one returns a hit (download-proxy/src/merge_service/enricher.py): TMDB → OMDb → TVMaze → AniList → OpenLibrary → MusicBrainz.

Variable	Required	Register	Purpose
TMDB_API_KEY	Optional	https://www.themoviedb.org/signup → Settings → API → Request API Key (v3 auth)	Movie / TV posters + metadata (enricher.py:73,163,172)
OMDB_API_KEY	Optional	http://www.omdbapi.com/apikey.aspx	Movie metadata via OMDb, tried after TMDB (enricher.py:72,102,133-135)
ANILIST_CLIENT_ID	Optional	https://anilist.co/settings/developer	Anime metadata via the AniList GraphQL API (enricher.py:74,225-228)

The **TVMaze** (TV shows), **MusicBrainz** (music), and **OpenLibrary** (books) lookups (enricher.py:_lookup_tvmaze, _lookup_musicbrainz, _lookup_openlibrary) always run automatically as fallback sources — they read **no** environment variable, require **no** API key, and send no configurable User-Agent header. There is no TVDB_API_KEY, MUSICBRAINZ_USER_AGENT, ANIDB_CLIENT, or OPENLIBRARY_USER_AGENT env var anywhere in the codebase; a prior revision of this table documented those four as configuration knobs that do not exist in code (RD2-05 / RD2-37 — see GOVERNANCE_AUDIT_2026-08-08_ROUND2.md). There is no AniDB integration — anime metadata comes from AniList, gated by ANILIST_CLIENT_ID above. There is no TVDB integration — TV-show fallback is TVMaze, which is keyless.

5. Security scanner tokens (opt-in CI / local scans)

`./scripts/scan.sh` skips scanners whose tokens are missing. None of these are mandatory for the platform to function.

Variable	Required	Register
SNYK_TOKEN	Optional	https://app.snyk.io/ → Account Settings → Auth Token
SONAR_TOKEN	Optional	https://sonarcloud.io/account/security/ or your SonarQube instance
SONAR_HOST_URL	Optional	Default <code>http://localhost:9000</code> (the compose profile runs SonarQube there)
GITLEAKS_LICENSE	Optional	https://gitleaks.io/ for commercial use; the OSS scan runs without it

6. Observability endpoints (opt-in compose profile)

Start with `$COMPOSE_CMD -f docker-compose.yml -f docker-compose.quality.yml --profile observability up -d`.

Variable	Default	Required
GRAFANA_USER	admin	Optional
GRAFANA_PASSWORD	admin	Optional (change for anything beyond localhost)
PROMETHEUS_PORT	9090	Optional
GRAFANA_PORT	3000	Optional

Portals (after compose up): - Prometheus: <http://localhost:9090/> -
Grafana: <http://localhost:3000/>

7. Orchestrator tuning (optional — Phase 3)

All have safe defaults; tune for your workload.

Variable	Default	Purpose
ALLOWED_ORIGINS	* (with startup warning)	CORS whitelist. Comma-separated. Set this in production to avoid the wildcard warning.
MAX_CONCURRENT_TRACKERS	5	Semaphore cap on tracker fan-out.
MAX_ACTIVE_SEARCHES	256	TTLCache maxsize for in-flight searches.
ACTIVE_SEARCH_TTL_SECONDS	3600	Per-search metadata retention.
PENDING_CAPTCHAS_MAX	1024	CAPTCHA session TTLCache maxsize.
PENDING_CAPTCHAS_TTL_SECONDS	900	CAPTCHA session lifetime.
HOOK_LOG_MAXLEN	500	Deque cap for hook-execution logs.
MERGE_SERVICE_HOST	0.0.0.0	Bind interface for the merge service.
MERGE_SERVICE_PORT	7187	HTTP port.
MERGE_SERVICE_URL	http://localhost:7187	Base URL of the merge service. (No longer consumed by the download-proxy: the themed-WebUI overlay it fed was removed 2026-09-01.)
PROXY_PORT	7186	Download proxy port.
BRIDGE_PORT	7188	WebUI bridge port.
THEME_STATE_PATH	/config/merge-service/theme.json	JSON file the merge service uses to persist the active palette + mode (see

Variable	Default	Purpose
DISABLE_THEME_INJECTION	(unset)	docs/ CROSS_APP_THEME_PLAN.md). OBSOLETE / NO-OP in the Python stack (2026-09-01). The themed-WebUI overlay it disabled was removed entirely — the download-proxy now always serves qBittorrent's HTML untouched, so there is nothing left to switch off. Still read by the Go backend (qBitTorrent-go/internal/config/config.go).

8. Data directory

Variable	Default	Required	Notes
QBITTORRENT_DATA_DIR	/mnt/DATA	No	Where qBittorrent stores torrents + incomplete + finished subdirs. Must be writable by PUID/PGID.
PUID	1000	No	Container user ID.
PGID	1000	No	Container group ID.

Quick-start matrix

Minimum-viable .env for *public-tracker-only* deployment:

No credentials required – service runs out of the box.

QBITTORRENT_DATA_DIR=/mnt/DATA

Minimum-viable .env for *private-tracker* deployment:

Pick the trackers you have accounts on.

RUTRACKER_USERNAME=your-user

RUTRACKER_PASSWORD=your-password

KINOZAL_USERNAME=your-user

KINOZAL_PASSWORD=your-password

NNMCLUB_COOKIES="phpbb2mysql_data=...; phpbb2mysql_sid=..."

IPTORRENTS_USERNAME=your-user

IPTORRENTS_PASSWORD=your-password

QBITTORRENT_DATA_DIR=/mnt/DATA

Minimum-viable .env for *CI/ scanner uplift*:

SNYK_TOKEN=your-token

SONAR_TOKEN=your-token

SONAR_HOST_URL=https://sonarcloud.io

ALLOWED_ORIGINS=https://qbit.example.com

Verification

After editing .env, restart the stack and probe auth:

```
./stop.sh && ./start.sh  
curl -s http://localhost:7187/api/v1/auth/status | python3 -m  
    json.tool
```

Every tracker with `has_session: true` is live; anything with `has_session: false` either has wrong credentials or the tracker's login flow changed. For rutracker + iptorrents you can then trigger CAPTCHA refresh from the dashboard chip.

Related

- [SECURITY.md](#) — threat model and credential storage.
- [SCANNING.md](#) — scanner config that uses \$5 tokens.
- [OBSERVABILITY.md](#) — \$6 endpoints.
- [USER_MANUAL.md](#) — walk-through per tracker.

- .specify/memory/constitution.md — legal binding of the above.