

STORE_LISTING

BobaLink — Store Listing & Submission Checklist

Revision: 2 **Last modified:** 2026-06-13T00:00:00Z **Scope:** Chrome Web Store + Firefox AMO listing content and a manual submission checklist for BobaLink, the Boba Project browser extension (extension/).
Authority: extension/wxt.config.ts, extension/package.json, docs/browser_extension/Status.md (Rev 5), docs/browser_extension/USER_GUIDE.md.

Accuracy note (§11.4.6): every permission justification, feature claim, and privacy statement below was traced to the real extension source/config — the generated wxt.config.ts manifest (permissions / host_permissions / CSP / commands), package.json (version 1.0.0), the _locales/en/messages.json store-description string, and src/shared/constants.ts (SITE_SELECTORS, DEFAULT_URLS). Nothing reads as shipped that is not. Items not yet produced (screenshots, promo tiles) are marked (**TODO — operator asset**).

Listing identity

Field	Value	Source
Name	BobaLink	_locales/en/messages.json extName; wxt.config.ts name: "__MSG_extName__"
Version	1.0.0	wxt.config.ts version; package.json version —

Field	Value	Source
Category (suggested)	Productivity / Developer Tools	
Default locale	English (en)	wxt.config.ts default_locale: "en"
Minimum Chrome version	109	wxt.config.ts minimum_chrome_version
Manifest version	MV3 (Chrome); MV2 build also produced for Firefox AMO	wxt.config.ts; ci- ext.sh builds chrome- mv3/ + firefox-mv2/
License	MIT	package.json

Short description (≤ 132 characters)

This is the verbatim store-description string the extension already ships (`_locales/en/messages.json` `extDescription`) — 92 characters, within both the Chrome (132) and Firefox (132) short-description limits:

Detects torrent files and magnet links, sending them to Boba Project's qBitTorrent dashboard

(Length: 92 characters.)

Detailed description

BobaLink finds magnet links and .torrent files on the pages you visit and forwards them to your own self-hosted Boba Project merge service, which adds them to qBittorrent for you. It is a privacy-first, least-privilege Manifest V3 extension: it never talks to qBittorrent directly, never collects your data, and only ever contacts the Boba merge service running on your own machine at `http://localhost:7187`.

What it does

- **Detects** magnet links and .torrent file URLs on any page, with an extra-tuned selector table for popular trackers.

- **Parses** each item to its BitTorrent infohash (magnet btih / .torrent → SHA-1) and **deduplicates by infohash**, so the same torrent is never sent twice.
- **Forwards** them to your local Boba merge service on port 7187, which adds them to qBittorrent server-side.
- **Tab-group batch send** (Chrome family): scan every tab in a tab group, deduplicate across the whole group, and send them as one batch.
- **Context-menu actions**: “Send magnet to Boba”, “Send all on page”, “Send tab group”.
- **Keyboard shortcuts**: Send to Boba (Ctrl/Cmd+Shift+B), Scan page (Ctrl/Cmd+Shift+S), Open dashboard (Ctrl/Cmd+Shift+D).
- **A configurable options page** (7 tabs: Server, Download Prefs, Queue, Notifications, Detection, UI, Security) with an optional offline queue for failed sends.

Privacy & security first

- **No data collection.** BobaLink sends nothing to any third party. The only network destination is your own Boba merge service at `http://localhost:7187`.
- **Least privilege.** No tabs, no scripting, no cookies, no `<all_urls>`. The content script only runs on the curated tracker host list, not every site.
- **Delegate-by-default credentials.** In the normal localhost deployment BobaLink stores no decryptable secret — your Boba service already owns the qBittorrent and tracker credentials. The one optional secret (a Boba API token, only needed if your backend sets `BOBA_API_TOKEN`) is encrypted with AES-GCM-256 under a session passphrase you type, held only in `chrome.storage.session` and never written to disk or logged.
- **Tight CSP:** `script-src 'self'` (no `unsafe-inline` / `unsafe-eval`), `connect-src` scoped to `http://localhost:7187`.

Internationalization & accessibility

- UI message catalogs for English, German, Spanish, French, Italian, Japanese, Portuguese, and Russian (8 locales); the browser auto-selects by UI language, falling back to English.
- The popup and options UI carry ARIA roles, accessible names, and `tablist/tabpanel` wiring.

Requires a running Boba Project backend. BobaLink is a companion to a self-hosted Boba Project install — it needs the Boba merge service reachable on `http://localhost:7187`. It is not a standalone downloader.

Status honesty (§11.4.6): the end-to-end detect → send → torrent-appears-in- qBittorrent path against a **live** backend is still **in progress** (Phase 4 in the plan). Detection, parsing, dedup, the popup/options UI, and the send-wiring are implemented and tested. Listing copy above describes the intended user-facing capability; do not publish to the public stores before Phase 4 live-backend integration lands (see `Status.md`).

Supported torrent sites (curated selector table)

Detection works on **any page** via the generic magnet: and .torrent link patterns. In addition, BobaLink ships a curated selector table (`SITE_SELECTORS` in `extension/src/shared/constants.ts`) tuned for these hosts. The content script's matches are derived from this table — BobaLink does **not** request `<all_urls>`. The table has **24 entries** (one generic pattern set plus 23 site-specific hosts):

#	Host	Notes
—	generic	magnet / .torrent / download.php?id= patterns applied everywhere
1	1337x.to	
2	thepiratebay.org	
3	thepiratebay10.org	
4	rarbg.to	
5	rarbgtorrents.org	
6	yts.mx	
7	yts.lt	
8	eztv.re	
9	limetorrents.lol	
10	torrentgalaxy.to	
11	nyaa.si	anime

#	Host	Notes
12	animetosho.org	
13	torrentz2.eu	
14	fitgirl-repacks.site	
15	rutracker.org	Boba private tracker
16	kinozal.tv	Boba private tracker
17	nnmclub.to	Boba private tracker
18	rutor.info	Boba public tracker
19	katcr.co	Kickass Torrents
20	demonoid.is	
21	iptorrents.com	Boba private tracker
22	torrentleech.org	private
23	beyond-hd.me	private
24	passthepopcorn.me	private

Permission-justification table

Both stores require a per-permission justification. Each row below traces to the literal permissions / host_permissions array in extension/wxt.config.ts (lines 28–40, host_permissions line 43). No permission is requested that is not justified here, and no justification claims a permission BobaLink does not request.

Permission	In manifest?	Justification
storage	Yes (wxt.config.ts:29)	Persist user settings, detected items per tab, the offline send queue, and send history (chrome.storage.local).
alarms	Yes (wxt.config.ts:30)	Wake the MV3 service worker to run periodic backend health checks (no content/host access).
notifications	Yes (wxt.config.ts:31)	Tell the user when a send succeeds or fails.
activeTab	Yes (wxt.config.ts:32)	Act on the page the user explicitly invokes BobaLink on (toolbar click / shortcut /

Permission	In manifest?	Justification
contextMenus	Yes (wxt.config.ts:33)	context menu) — granted transiently, not a standing all-sites grant. Provide the right-click “Send magnet to Boba”, “Send all on page”, “Send tab group” actions.
tabGroups	Yes (wxt.config.ts:39)	“Send tab group”: read which group the clicked tab belongs to and enumerate the group’s tabs via <code>chrome.tabs.query({groupId})</code> . Grants no host/content/URL access.
host_permissions: http:// localhost:7187/*	Yes (wxt.config.ts:43)	Talk to the user’s own local Boba merge service — the single network destination. Nothing else.

Permissions deliberately NOT requested (state this in the privacy review)

Not requested	Why it’s safe to omit
tabs	The tab-group batcher reads only <code>tab.id</code> (never <code>url/title/favIconUrl</code>), which per the Chrome docs needs no tabs permission.
scripting	Not requested — <code>wxt.config.ts</code> comment “scripting intentionally NOT requested” (least-privilege, Plan E §3.1).
cookies	Not requested — BobaLink never touches the user’s cookies.
<all_urls>	Content-script match patterns are derived from the curated <code>SITE_SELECTORS</code> host list, not a blanket all-sites grant.

Privacy-policy summary

Use the following as the public privacy statement (both stores require a privacy policy / data-use disclosure). Every clause is accurate to the real network behavior — the only `host_permissions` entry and the only `connect-src` CSP origin is `http://localhost:7187`.

BobaLink collects no personal data and transmits no data to BobaLink's authors or any third party.

- The only network destination BobaLink contacts is the **Boba merge service on the user's own machine at `http://localhost:7187`** (the sole `host_permissions` entry and the sole non-`'self'` `connect-src` CSP origin).
- BobaLink sends only the magnet links / `.torrent` URLs the user chooses to forward, and an optional Boba API token (only if the user's backend requires one). Nothing is sent to any remote server controlled by BobaLink.
- Settings, detected items, the offline queue, and history are stored **locally** in the browser (`chrome.storage.local`).
- The optional Boba API token is encrypted at rest (AES-GCM-256, PBKDF2) under a **session passphrase** held only in `chrome.storage.session` (never on disk), and is never logged. With no passphrase, no token is stored.
- BobaLink uses no analytics, no telemetry, and no remote code.

CSP (verbatim, `wxt.config.ts:57–58`):

```
default-src 'self'; script-src 'self'; object-src 'self'; style-  
src 'self' 'unsafe-inline'; connect-src 'self' http://  
localhost:7187; img-src 'self' data:; base-uri 'none'; frame-  
ancestors 'none'
```

Required store-asset checklist

Asset	Chrome Web Store	Firefox AMO	Status
Icon 16×16	(used in manifest)	(used in manifest)	Done — <code>.output/ chrome-mv3/ icons/ 16.png</code> (rasterized)

Asset	Chrome Web Store	Firefox AMO	Status
			from src/ assets/ icon.png by @wxt-dev/ auto-icons)
Icon 32×32	optional	used	Done — icons/ 32.png
Icon 48×48	required	required	Done — icons/ 48.png
Icon 128×128	required (store icon)	required	Done — icons/ 128.png
Short description (≤132 chars)	required	required (summary)	Done — see “Short description” above (92 chars)
Detailed description	required	required	Done — see “Detailed description” above
Privacy policy / data- use disclosure	required	required	Done — see “Privacy- policy summary” above
Permission justifications	required (single- purpose + per- permission)	required (in review notes)	Done — see “Permission- justification table” above
Screenshots (1280×800 or 640×400; ≥1, up to 5)	required	required	(TODO — operator asset) — capture popup + options + detection-in- action

Asset	Chrome Web Store	Firefox AMO	Status
Small promo tile 440×280	optional	n/a	(TODO — operator asset)
Marquee promo tile 1400×560	optional	n/a	(TODO — operator asset)
Promotional / featured images	optional	optional	(TODO — operator asset)
Support / homepage URL	required	required	(TODO — operator asset) — Boba Project repo / docs URL

Icon note: only the four sizes 16 / 32 / 48 / 128 are produced and required; they are generated at build time from the single `src/assets/icon.png`. No other icon size is referenced by the manifest.

Submission checklist (manual — NO CI/CD)

Per the Boba constitution Hard Stop (no CI/CD), packaging is performed by the manual gate extension/ci-ext.sh only — there is no pipeline. Sequence:

- 1. Pre-flight** — `cd extension && npm install` (populate `node_modules`); ensure `node`, `npm`, `jq` are on `PATH`.
- 2. Run the manual gate** — `cd extension && bash ci-ext.sh`. It runs, in order: `tsc` type gate → `eslint` → full vitest suite → Chrome MV3 build → Firefox build → §11.4.38 artifact-asset verification (opens the produced manifest and confirms every referenced asset + the `default_locale` catalog exist non-zero) → `per-store wxt zip`. It prints `CI-EXT: PASS` only if every step passed.
- 3. Collect the artifacts** — on `PASS`, `.output/` contains:
 - `bobalink-1.0.0-chrome.zip` — upload to the **Chrome Web Store**.
 - `bobalink-1.0.0-firefox.zip` — upload to **Firefox AMO**.
 - `bobalink-1.0.0-sources.zip` — Firefox AMO source-code submission (AMO requires sources for built extensions).

4. **Chrome Web Store** — Developer Dashboard → new item → upload bobalink-1.0.0-chrome.zip → paste the short description, detailed description, privacy disclosure, and per-permission justifications from this document → upload screenshots + (optional) promo tiles (**TODO — operator asset**) → set the support/homepage URL (**TODO — operator asset**) → submit for review.
 5. **Firefox AMO** — addons.mozilla.org → submit a new add-on → upload bobalink-1.0.0-firefox.zip → upload bobalink-1.0.0-sources.zip when prompted for sources → paste the summary, detailed description, and privacy notes → add the permission justifications in the reviewer notes → upload screenshots (**TODO — operator asset**) → submit for review.
 6. **Pre-submission gate (release-readiness):** do **not** submit to the public stores until Phase 4 live-backend integration is GREEN with captured evidence (Status.md — the detect → send → torrent-in-qBittorrent round-trip against a live :7187 backend is currently **in progress**). Listing copy is ready; the live-path proof is the remaining gate.
-

Sources verified

- extension/wxt.config.ts (permissions, host_permissions, CSP, commands, version, default_locale, minimum_chrome_version) — read 2026-06-10.
- extension/package.json (version: 1.0.0, name, MIT license) — read 2026-06-10.
- extension/src/shared/constants.ts (SITE_SELECTORS 24 entries, DEFAULT_URLS :7187, ENCRYPTION, BOBA_TOKEN_HEADERS, ICON_SIZES) — read 2026-06-10.
- extension/src/public/_locales/en/messages.json (extDescription short string; 8 locales de/en/es/fr/it/ja/pt/ru present on disk and in the built .output/*/_locales/) — read 2026-06-10.
- extension/ci-ext.sh + .output/artifacts (bobalink-1.0.0-{chrome,firefox,sources}.zip, icons/{16,32,48,128}.png) — read 2026-06-10.
- docs/browser_extension/Status.md (Rev 5), docs/browser_extension/USER_GUIDE.md (Rev 1) — read 2026-06-10.