

DESELECTED_DESTRUCTIVE

Deselected from the live run: tests/integration/ test_start_sh_reload_paths.py

Excluded via `--ignore=tests/integration/test_start_sh_reload_paths.py` because it DRIVES THE OPERATOR'S RUNNING STACK, which this session is forbidden from disturbing.

Evidence (read from the file, not inferred):

- `test_recreate_stack_destroys_and_recreates_container` (line 239) runs `./start.sh --recreate`, which per `CLAUDE.md` is `<compose> down && <compose> up -d` — a full TEARDOWN of the stack. Its own assertion is that the container **id changes**, i.e. it requires the destroy to happen.
- `test_reload_python_clears_pycache_and_restarts` (line 139) and `test_reload_plugins_restarts_without_copying_files` (line 191) run `./start.sh --reload-python / --reload-plugins`, each of which restarts the qbittorrent-proxy container (their assertions require `StartedAt` to move forward).

All three are legitimate tests of a real contract; they are simply UNSAFE to run while the operator and other work streams are using the live stack. They were NOT run and are therefore NOT counted as passing in the live results.

Everything else in `tests/integration` and `tests/e2e` was run. `tests/conftest.py docker_cleanup()` returns `[]` (verified) and `tests/fixtures/compose.py::compose_up` only issues `compose up -d` when ports are NOT already listening (they were), so no other collected test tears the stack down.