

README

scripts/

Operational and CI scripts. All scripts auto-detect container runtime (podman preferred).

Scripts

Script	Purpose
<code>run-tests.sh</code>	Full test suite with coverage. Args: hermetic (fast, no services), live (needs containers), all
<code>scan.sh</code>	Security scanner orchestrator. Runs pip-audit, bandit, ruff, snyk, semgrep, trivy, gitleaks. Reports to artifacts/scans/ as SARIF
<code>freeze-openapi.sh</code>	Exports FastAPI /openapi.json to docs/api/openapi.json for drift detection
<code>build-releases.sh</code>	Build release artifacts
<code>audit-plugins.sh</code>	Audit plugin matrix (canonical vs community)
<code>add-submodules.sh</code>	Add git submodules
<code>helixqa.sh</code>	Helix QA runner
<code>opencode-helixqa.sh</code>	OpenCode Helix QA runner

Usage

```
# Run full test suite
./scripts/run-tests.sh all
```

```
# Quick hermetic tests only
./scripts/run-tests.sh hermetic

# Run all security scanners
./scripts/scan.sh --all

# Freeze OpenAPI spec
./scripts/freeze-openapi.sh
```

Conventions

- All scripts use `set -euo pipefail`.
- Non-interactive — no `sudo` or human input required.
- Container runtime auto-detected (podman > docker).